

MySQL 9.5 Error Message Reference

Abstract

This is the MySQL 9.5 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 9.5. This document accompanies [Error Messages and Common Problems](#), in [MySQL 9.5 Reference Manual](#).

For help with using MySQL, please visit the [MySQL Forums](#), where you can discuss your issues with other MySQL users.

Document generated on: 2026-01-23 (revision: 84317)

Table of Contents

Preface and Legal Notices	v
1 MySQL Error Reference	1
2 Server Error Message Reference	3
3 Client Error Message Reference	429
4 Global Error Message Reference	435
Index	443

Preface and Legal Notices

This is the MySQL 9.5 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 9.5.

Legal Notices

Copyright © 1997, 2026, Oracle and/or its affiliates.

License Restrictions

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Trademark Notice

Oracle, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC

International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

Third-Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Use of This Documentation

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support for Accessibility

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Chapter 1 MySQL Error Reference

This document provides a reference for the various types of error messages in MySQL:

- Error messages produced only by the server: [Chapter 2, *Server Error Message Reference*](#)

On the server side, error messages may occur during the startup and shutdown processes, as a result of issues that occur during SQL statement execution, and so forth.

- The MySQL server writes some error messages to its error log. These indicate issues of interest to database administrators or that require DBA action.
- The server sends other error messages to client programs. These indicate issues pertaining only to a particular client. The MySQL client library takes errors received from the server and makes them available to the host client program.
- Error messages that originate only from within the MySQL client library: [Chapter 3, *Client Error Message Reference*](#)

Client-side error messages are generated from within the MySQL client library, usually involving problems communicating with the server.

- Error messages that are shared between the server and the client library: [Chapter 4, *Global Error Message Reference*](#)

Some “global” error messages are shared in the sense that they can be produced by the MySQL server or by MySQL client programs.

For a description of the types of error information MySQL provides and how to obtain information about them, see [Error Messages and Common Problems](#), in [MySQL 9.5 Reference Manual](#).

Chapter 2 Server Error Message Reference

The MySQL server writes some error messages to its error log, and sends others to client programs.

Example server-side error messages written to the error log:

```
2018-10-28T13:01:32.735983Z 0 [Note] [MY-010303] [Server] Skipping
generation of SSL certificates as options related to SSL are specified.

2018-10-02T03:20:39.410387Z 768 [ERROR] [MY-010045] [Server] Event Scheduler:
[evtuser@localhost][myschema.e_daily] Unknown database 'mydb'
```

Example server-side error message sent to client programs, as displayed by the `mysql` client:

```
mysql> SELECT * FROM no_such_table;
ERROR 1146 (42S02): Table 'test.no_such_table' doesn't exist
```

Each server error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#).

In addition to the errors in the following list, the server can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: [1002](#); Symbol: [ER_NO](#); SQLSTATE: [HY000](#)

Message: NO

Used in the construction of other messages.

- Error number: [1003](#); Symbol: [ER_YES](#); SQLSTATE: [HY000](#)

Message: YES

Used in the construction of other messages.

Extended [EXPLAIN](#) format generates Note messages. [ER_YES](#) is used in the [Code](#) column for these messages in subsequent [SHOW WARNINGS](#) output.

- Error number: [1004](#); Symbol: [ER_CANT_CREATE_FILE](#); SQLSTATE: [HY000](#)

Message: Can't create file '%s' (errno: %d - %s)

Occurs for failure to create or copy a file needed for some operation.

Possible causes: Permissions problem for source file; destination file already exists but is not writeable.

- Error number: [1005](#); Symbol: [ER_CANT_CREATE_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't create table '%s' (errno: %d - %s)

[InnoDB](#) reports this error when a table cannot be created. If the error message refers to error 150, table creation failed because a [foreign key constraint](#) was not correctly formed. If the error message refers to error -1, table creation probably failed because the table includes a column name that matched the name of an internal [InnoDB](#) table.

- Error number: [1006](#); Symbol: [ER_CANT_CREATE_DB](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s' (errno: %d - %s)

- Error number: [1007](#); Symbol: [ER_DB_CREATE_EXISTS](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s'; database exists

An attempt to create a database failed because the database already exists.

Drop the database first if you really want to replace an existing database, or add an **IF NOT EXISTS** clause to the **CREATE DATABASE** statement if to retain an existing database without having the statement produce an error.

- Error number: **1008**; Symbol: **ER_DB_DROP_EXISTS**; SQLSTATE: **HY000**

Message: Can't drop database '%s'; database doesn't exist

- Error number: **1010**; Symbol: **ER_DB_DROP_RMDIR**; SQLSTATE: **HY000**

Message: Error dropping database (can't rmdir '%s', errno: %d - %s)

- Error number: **1012**; Symbol: **ER_CANT_FIND_SYSTEM_REC**; SQLSTATE: **HY000**

Message: Can't read record in system table

Returned by **InnoDB** for attempts to access **InnoDB INFORMATION_SCHEMA** tables when **InnoDB** is unavailable.

- Error number: **1013**; Symbol: **ER_CANT_GET_STAT**; SQLSTATE: **HY000**

Message: Can't get status of '%s' (errno: %d - %s)

- Error number: **1015**; Symbol: **ER_CANT_LOCK**; SQLSTATE: **HY000**

Message: Can't lock file (errno: %d - %s)

- Error number: **1016**; Symbol: **ER_CANT_OPEN_FILE**; SQLSTATE: **HY000**

Message: Can't open file: '%s' (errno: %d - %s)

InnoDB reports this error when the table from the **InnoDB data files** cannot be found.

- Error number: **1017**; Symbol: **ER_FILE_NOT_FOUND**; SQLSTATE: **HY000**

Message: Can't find file: '%s' (errno: %d - %s)

- Error number: **1018**; Symbol: **ER_CANT_READ_DIR**; SQLSTATE: **HY000**

Message: Can't read dir of '%s' (errno: %d - %s)

- Error number: **1020**; Symbol: **ER_CHECKREAD**; SQLSTATE: **HY000**

Message: Record has changed since last read in table '%s'

- Error number: **1022**; Symbol: **ER_DUP_KEY**; SQLSTATE: **23000**

Message: Can't write; duplicate key in table '%s'

- Error number: **1024**; Symbol: **ER_ERROR_ON_READ**; SQLSTATE: **HY000**

Message: Error reading file '%s' (errno: %d - %s)

- Error number: **1025**; Symbol: **ER_ERROR_ON_RENAME**; SQLSTATE: **HY000**

Message: Error on rename of '%s' to '%s' (errno: %d - %s)

- Error number: **1026**; Symbol: **ER_ERROR_ON_WRITE**; SQLSTATE: **HY000**

Message: Error writing file '%s' (errno: %d - %s)

- Error number: **1027**; Symbol: **ER_FILE_USED**; SQLSTATE: **HY000**

Message: '%s' is locked against change

- Error number: [1030](#); Symbol: [ER_GET_ERRNO](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine

Check the %d value to see what the OS error means. For example, 28 indicates that you have run out of disk space.

- Error number: [1031](#); Symbol: [ER_ILLEGAL_HA](#); SQLSTATE: [HY000](#)

Message: Table storage engine for '%s' doesn't have this option

- Error number: [1032](#); Symbol: [ER_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find record in '%s'

- Error number: [1033](#); Symbol: [ER_NOT_FORM_FILE](#); SQLSTATE: [HY000](#)

Message: Incorrect information in file: '%s'

- Error number: [1034](#); Symbol: [ER_NOT_KEYFILE](#); SQLSTATE: [HY000](#)

Message: Incorrect key file for table '%s'; try to repair it

- Error number: [1035](#); Symbol: [ER_OLD_KEYFILE](#); SQLSTATE: [HY000](#)

Message: Old key file for table '%s'; repair it!

- Error number: [1036](#); Symbol: [ER_OPEN_AS_READONLY](#); SQLSTATE: [HY000](#)

Message: Table '%s' is read only

- Error number: [1037](#); Symbol: [ER_OUTOFMEMORY](#); SQLSTATE: [HY001](#)

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: [1038](#); Symbol: [ER_OUT_OF_SORTMEMORY](#); SQLSTATE: [HY001](#)

Message: Out of sort memory, consider increasing server sort buffer size

- Error number: [1040](#); Symbol: [ER_CON_COUNT_ERROR](#); SQLSTATE: [08004](#)

Message: Too many connections

- Error number: [1041](#); Symbol: [ER_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: [1042](#); Symbol: [ER_BAD_HOST_ERROR](#); SQLSTATE: [08S01](#)

Message: Can't get hostname for your address

- Error number: [1043](#); Symbol: [ER_HANDSHAKE_ERROR](#); SQLSTATE: [08S01](#)

Message: Bad handshake

- Error number: [1044](#); Symbol: [ER_DBACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)

Message: Access denied for user '%s'@'%s' to database '%s'

- Error number: [1045](#); Symbol: [ER_ACCESS_DENIED_ERROR](#); SQLSTATE: [28000](#)

Message: Access denied for user '%s'@'%s' (using password: %s)

- Error number: [1046](#); Symbol: [ER_NO_DB_ERROR](#); SQLSTATE: [3D000](#)

Message: No database selected

- Error number: [1047](#); Symbol: [ER_UNKNOWN_COM_ERROR](#); SQLSTATE: [08S01](#)

Message: Unknown command

- Error number: [1048](#); Symbol: [ER_BAD_NULL_ERROR](#); SQLSTATE: [23000](#)

Message: Column '%s' cannot be null

- Error number: [1049](#); Symbol: [ER_BAD_DB_ERROR](#); SQLSTATE: [42000](#)

Message: Unknown database '%s'

- Error number: [1050](#); Symbol: [ER_TABLE_EXISTS_ERROR](#); SQLSTATE: [42S01](#)

Message: Table '%s' already exists

- Error number: [1051](#); Symbol: [ER_BAD_TABLE_ERROR](#); SQLSTATE: [42S02](#)

Message: Unknown table '%s'

- Error number: [1052](#); Symbol: [ER_NON_UNIQ_ERROR](#); SQLSTATE: [23000](#)

Message: Column '%s' in %s is ambiguous

%s = column name

%s = location of column (for example, "field list")

Likely cause: A column appears in a query without appropriate qualification, such as in a select list or ON clause.

Examples:

```
mysql> SELECT i FROM t INNER JOIN t AS t2;  
ERROR 1052 (23000): Column 'i' in field list is ambiguous
```

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;  
ERROR 1052 (23000): Column 'i' in on clause is ambiguous
```

Resolution:

- Qualify the column with the appropriate table name:

```
mysql> SELECT t2.i FROM t INNER JOIN t AS t2;
```

- Modify the query to avoid the need for qualification:

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 USING (i);
```

- Error number: [1053](#); Symbol: [ER_SERVER_SHUTDOWN](#); SQLSTATE: [08S01](#)

Message: Server shutdown in progress

- Error number: [1054](#); Symbol: [ER_BAD_FIELD_ERROR](#); SQLSTATE: [42S22](#)

Message: Unknown column '%s' in '%s'

- Error number: [1055](#); Symbol: [ER_WRONG_FIELD_WITH_GROUP](#); SQLSTATE: [42000](#)

Message: '%s' isn't in GROUP BY

-
- Error number: [1056](#); Symbol: [ER_WRONG_GROUP_FIELD](#); SQLSTATE: [42000](#)
Message: Can't group on '%s'
 - Error number: [1057](#); Symbol: [ER_WRONG_SUM_SELECT](#); SQLSTATE: [42000](#)
Message: Statement has sum functions and columns in same statement
 - Error number: [1058](#); Symbol: [ER_WRONG_VALUE_COUNT](#); SQLSTATE: [21S01](#)
Message: Column count doesn't match value count
 - Error number: [1059](#); Symbol: [ER_TOO_LONG_IDENT](#); SQLSTATE: [42000](#)
Message: Identifier name '%s' is too long
 - Error number: [1060](#); Symbol: [ER_DUP_FIELDNAME](#); SQLSTATE: [42S21](#)
Message: Duplicate column name '%s'
 - Error number: [1061](#); Symbol: [ER_DUP_KEYNAME](#); SQLSTATE: [42000](#)
Message: Duplicate key name '%s'
 - Error number: [1062](#); Symbol: [ER_DUP_ENTRY](#); SQLSTATE: [23000](#)
Message: Duplicate entry '%s' for key %d
The message returned with this error uses the format string for [ER_DUP_ENTRY_WITH_KEY_NAME](#).
 - Error number: [1063](#); Symbol: [ER_WRONG_FIELD_SPEC](#); SQLSTATE: [42000](#)
Message: Incorrect column specifier for column '%s'
 - Error number: [1064](#); Symbol: [ER_PARSE_ERROR](#); SQLSTATE: [42000](#)
Message: %s near '%s' at line %d
 - Error number: [1065](#); Symbol: [ER_EMPTY_QUERY](#); SQLSTATE: [42000](#)
Message: Query was empty
 - Error number: [1066](#); Symbol: [ER_NONUNIQ_TABLE](#); SQLSTATE: [42000](#)
Message: Not unique table/alias: '%s'
 - Error number: [1067](#); Symbol: [ER_INVALID_DEFAULT](#); SQLSTATE: [42000](#)
Message: Invalid default value for '%s'
 - Error number: [1068](#); Symbol: [ER_MULTIPLE_PRI_KEY](#); SQLSTATE: [42000](#)
Message: Multiple primary key defined
 - Error number: [1069](#); Symbol: [ER_TOO_MANY_KEYS](#); SQLSTATE: [42000](#)
Message: Too many keys specified; max %d keys allowed
 - Error number: [1070](#); Symbol: [ER_TOO_MANY_KEY_PARTS](#); SQLSTATE: [42000](#)
Message: Too many key parts specified; max %d parts allowed
 - Error number: [1071](#); Symbol: [ER_TOO_LONG_KEY](#); SQLSTATE: [42000](#)
Message: Specified key was too long; max key length is %d bytes

-
- Error number: [1072](#); Symbol: [ER_KEY_COLUMN_DOES_NOT_EXISTS](#); SQLSTATE: [42000](#)
Message: Key column '%s' doesn't exist in table
 - Error number: [1073](#); Symbol: [ER_BLOB_USED_AS_KEY](#); SQLSTATE: [42000](#)
Message: BLOB column '%s' can't be used in key specification with the used table type
 - Error number: [1074](#); Symbol: [ER_TOO_BIG_FIELDLENGTH](#); SQLSTATE: [42000](#)
Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead
 - Error number: [1075](#); Symbol: [ER_WRONG_AUTO_KEY](#); SQLSTATE: [42000](#)
Message: Incorrect table definition; there can be only one auto column and it must be defined as a key
 - Error number: [1076](#); Symbol: [ER_READY](#); SQLSTATE: [HY000](#)
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d
 - Error number: [1079](#); Symbol: [ER_SHUTDOWN_COMPLETE](#); SQLSTATE: [HY000](#)
Message: %s: Shutdown complete
 - Error number: [1080](#); Symbol: [ER_FORCING_CLOSE](#); SQLSTATE: [08S01](#)
Message: %s: Forcing close of thread %ld user: '%s'
 - Error number: [1081](#); Symbol: [ER_IPSOCK_ERROR](#); SQLSTATE: [08S01](#)
Message: Can't create IP socket
 - Error number: [1082](#); Symbol: [ER_NO_SUCH_INDEX](#); SQLSTATE: [42S12](#)
Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table
 - Error number: [1083](#); Symbol: [ER_WRONG_FIELD_TERMINATORS](#); SQLSTATE: [42000](#)
Message: Field separator argument is not what is expected; check the manual
 - Error number: [1084](#); Symbol: [ER_BLOBS_AND_NO_TERMINATED](#); SQLSTATE: [42000](#)
Message: You can't use fixed rowlength with BLOBs; please use 'fields terminated by'
 - Error number: [1085](#); Symbol: [ER_TEXTFILE_NOT_READABLE](#); SQLSTATE: [HY000](#)
Message: The file '%s' must be in the database directory or be readable by all
 - Error number: [1086](#); Symbol: [ER_FILE_EXISTS_ERROR](#); SQLSTATE: [HY000](#)
Message: File '%s' already exists
 - Error number: [1087](#); Symbol: [ER_LOAD_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld
 - Error number: [1088](#); Symbol: [ER_ALTER_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Duplicates: %ld
 - Error number: [1089](#); Symbol: [ER_WRONG_SUB_KEY](#); SQLSTATE: [HY000](#)
Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part, or the storage engine doesn't support unique prefix keys

-
- Error number: [1090](#); Symbol: [ER_CANT_REMOVE_ALL_FIELDS](#); SQLSTATE: [42000](#)
Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead
 - Error number: [1091](#); Symbol: [ER_CANT_DROP_FIELD_OR_KEY](#); SQLSTATE: [42000](#)
Message: Can't DROP '%s'; check that column/key exists
 - Error number: [1092](#); Symbol: [ER_INSERT_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Duplicates: %ld Warnings: %ld
 - Error number: [1093](#); Symbol: [ER_UPDATE_TABLE_USED](#); SQLSTATE: [HY000](#)
Message: You can't specify target table '%s' for update in FROM clause

This error occurs for attempts to select from and modify the same table within a single statement. If the select attempt occurs within a derived table, you can avoid this error by setting the [derived_merge](#) flag of the [optimizer_switch](#) system variable to force the subquery to be materialized into a temporary table, which effectively causes it to be a different table from the one modified. See [Optimizing Derived Tables, View References, and Common Table Expressions with Merging or Materialization](#).
 - Error number: [1094](#); Symbol: [ER_NO_SUCH_THREAD](#); SQLSTATE: [HY000](#)
Message: Unknown thread id: %lu
 - Error number: [1095](#); Symbol: [ER_KILL_DENIED_ERROR](#); SQLSTATE: [HY000](#)
Message: You are not owner of thread %lu
 - Error number: [1096](#); Symbol: [ER_NO_TABLES_USED](#); SQLSTATE: [HY000](#)
Message: No tables used
 - Error number: [1097](#); Symbol: [ER_TOO_BIG_SET](#); SQLSTATE: [HY000](#)
Message: Too many strings for column %s and SET
 - Error number: [1098](#); Symbol: [ER_NO_UNIQUE_LOGFILE](#); SQLSTATE: [HY000](#)
Message: Can't generate a unique log-filename %s.(1-999)
 - Error number: [1099](#); Symbol: [ER_TABLE_NOT_LOCKED_FOR_WRITE](#); SQLSTATE: [HY000](#)
Message: Table '%s' was locked with a READ lock and can't be updated
 - Error number: [1100](#); Symbol: [ER_TABLE_NOT_LOCKED](#); SQLSTATE: [HY000](#)
Message: Table '%s' was not locked with LOCK TABLES
 - Error number: [1101](#); Symbol: [ER_BLOB_CANT_HAVE_DEFAULT](#); SQLSTATE: [42000](#)
Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value
 - Error number: [1102](#); Symbol: [ER_WRONG_DB_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect database name '%s'
 - Error number: [1103](#); Symbol: [ER_WRONG_TABLE_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect table name '%s'
 - Error number: [1104](#); Symbol: [ER_TOO_BIG_SELECT](#); SQLSTATE: [42000](#)

Message: The SELECT would examine more than MAX_JOIN_SIZE rows; check your WHERE and use SET SQL_BIG_SELECTS=1 or SET MAX_JOIN_SIZE=# if the SELECT is okay

- Error number: [1105](#); Symbol: [ER_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)

Message: Unknown error

- Error number: [1106](#); Symbol: [ER_UNKNOWN_PROCEDURE](#); SQLSTATE: [42000](#)

Message: Unknown procedure '%s'

- Error number: [1107](#); Symbol: [ER_WRONG_PARAMCOUNT_TO_PROCEDURE](#); SQLSTATE: [42000](#)

Message: Incorrect parameter count to procedure '%s'

- Error number: [1108](#); Symbol: [ER_WRONG_PARAMETERS_TO_PROCEDURE](#); SQLSTATE: [HY000](#)

Message: Incorrect parameters to procedure '%s'

- Error number: [1109](#); Symbol: [ER_UNKNOWN_TABLE](#); SQLSTATE: [42S02](#)

Message: Unknown table '%s' in %s

- Error number: [1110](#); Symbol: [ER_FIELD_SPECIFIED_TWICE](#); SQLSTATE: [42000](#)

Message: Column '%s' specified twice

- Error number: [1111](#); Symbol: [ER_INVALID_GROUP_FUNC_USE](#); SQLSTATE: [HY000](#)

Message: Invalid use of group function

- Error number: [1112](#); Symbol: [ER_UNSUPPORTED_EXTENSION](#); SQLSTATE: [42000](#)

Message: Table '%s' uses an extension that doesn't exist in this MySQL version

- Error number: [1113](#); Symbol: [ER_TABLE_MUST_HAVE_COLUMNS](#); SQLSTATE: [42000](#)

Message: A table must have at least 1 column

- Error number: [1114](#); Symbol: [ER_RECORD_FILE_FULL](#); SQLSTATE: [HY000](#)

Message: The table '%s' is full

[InnoDB](#) reports this error when the system tablespace runs out of free space. Reconfigure the system tablespace to add a new data file.

- Error number: [1115](#); Symbol: [ER_UNKNOWN_CHARACTER_SET](#); SQLSTATE: [42000](#)

Message: Unknown character set: '%s'

- Error number: [1116](#); Symbol: [ER_TOO_MANY_TABLES](#); SQLSTATE: [HY000](#)

Message: Too many tables; MySQL can only use %d tables in a join

- Error number: [1117](#); Symbol: [ER_TOO_MANY_FIELDS](#); SQLSTATE: [HY000](#)

Message: Too many columns

- Error number: [1118](#); Symbol: [ER_TOO_BIG_ROW_SIZE](#); SQLSTATE: [42000](#)

Message: Row size too large. The maximum row size for the used table type, not counting BLOBs, is %ld. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs

-
- Error number: [1119](#); Symbol: [ER_STACK_OVERRUN](#); SQLSTATE: [HY000](#)
Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread_stack=#' to specify a bigger stack if needed
 - Error number: [1120](#); Symbol: [ER_WRONG_OUTER_JOIN_UNUSED](#); SQLSTATE: [42000](#)
Message: Cross dependency found in OUTER JOIN; examine your ON conditions
 - Error number: [1121](#); Symbol: [ER_NULL_COLUMN_IN_INDEX](#); SQLSTATE: [42000](#)
Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler
 - Error number: [1122](#); Symbol: [ER_CANT_FIND_UDF](#); SQLSTATE: [HY000](#)
Message: Can't load function '%s'
 - Error number: [1123](#); Symbol: [ER_CANT_INITIALIZE_UDF](#); SQLSTATE: [HY000](#)
Message: Can't initialize function '%s'; %s
 - Error number: [1124](#); Symbol: [ER_UDF_NO_PATHS](#); SQLSTATE: [HY000](#)
Message: No paths allowed for shared library
 - Error number: [1125](#); Symbol: [ER_UDF_EXISTS](#); SQLSTATE: [HY000](#)
Message: Function '%s' already exists
 - Error number: [1126](#); Symbol: [ER_CANT_OPEN_LIBRARY](#); SQLSTATE: [HY000](#)
Message: Can't open shared library '%s' (errno: %d %s)
 - Error number: [1127](#); Symbol: [ER_CANT_FIND_DL_ENTRY](#); SQLSTATE: [HY000](#)
Message: Can't find symbol '%s' in library
 - Error number: [1128](#); Symbol: [ER_FUNCTION_NOT_DEFINED](#); SQLSTATE: [HY000](#)
Message: Function '%s' is not defined
 - Error number: [1129](#); Symbol: [ER_HOST_IS_BLOCKED](#); SQLSTATE: [HY000](#)
Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'
 - Error number: [1130](#); Symbol: [ER_HOST_NOT_PRIVILEGED](#); SQLSTATE: [HY000](#)
Message: Host '%s' is not allowed to connect to this MySQL server
 - Error number: [1131](#); Symbol: [ER_PASSWORD_ANONYMOUS_USER](#); SQLSTATE: [42000](#)
Message: You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords
 - Error number: [1132](#); Symbol: [ER_PASSWORD_NOT_ALLOWED](#); SQLSTATE: [42000](#)
Message: You must have privileges to update tables in the mysql database to be able to change passwords for others
 - Error number: [1133](#); Symbol: [ER_PASSWORD_NO_MATCH](#); SQLSTATE: [42000](#)
Message: Can't find any matching row in the user table

-
- Error number: [1134](#); Symbol: [ER_UPDATE_INFO](#); SQLSTATE: [HY000](#)
Message: Rows matched: %ld Changed: %ld Warnings: %ld
 - Error number: [1135](#); Symbol: [ER_CANT_CREATE_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create a new thread (errno %d); if you are not out of available memory, you can consult the manual for a possible OS-dependent bug
 - Error number: [1136](#); Symbol: [ER_WRONG_VALUE_COUNT_ON_ROW](#); SQLSTATE: [21S01](#)
Message: Column count doesn't match value count at row %ld
 - Error number: [1137](#); Symbol: [ER_CANT_REOPEN_TABLE](#); SQLSTATE: [HY000](#)
Message: Can't reopen table: '%s'
 - Error number: [1138](#); Symbol: [ER_INVALID_USE_OF_NULL](#); SQLSTATE: [22004](#)
Message: Invalid use of NULL value
 - Error number: [1139](#); Symbol: [ER_REGEXP_ERROR](#); SQLSTATE: [42000](#)
Message: Got error '%s' from regexp
 - Error number: [1140](#); Symbol: [ER_MIX_OF_GROUP_FUNC_AND_FIELDS](#); SQLSTATE: [42000](#)
Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GROUP BY clause
 - Error number: [1141](#); Symbol: [ER_NONEXISTING_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s'
 - Error number: [1142](#); Symbol: [ER_TABLEACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: %s command denied to user '%s'@'%s' for table '%s'
 - Error number: [1143](#); Symbol: [ER_COLUMNACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'
 - Error number: [1144](#); Symbol: [ER_ILLEGAL_GRANT_FOR_TABLE](#); SQLSTATE: [42000](#)
Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used
 - Error number: [1145](#); Symbol: [ER_GRANT_WRONG_HOST_OR_USER](#); SQLSTATE: [42000](#)
Message: The host or user argument to GRANT is too long
 - Error number: [1146](#); Symbol: [ER_NO_SUCH_TABLE](#); SQLSTATE: [42S02](#)
Message: Table '%s.%s' doesn't exist
 - Error number: [1147](#); Symbol: [ER_NONEXISTING_TABLE_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s' on table '%s'
 - Error number: [1148](#); Symbol: [ER_NOT_ALLOWED_COMMAND](#); SQLSTATE: [42000](#)
Message: The used command is not allowed with this MySQL version
 - Error number: [1149](#); Symbol: [ER_SYNTAX_ERROR](#); SQLSTATE: [42000](#)

Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use

- Error number: [1152](#); Symbol: [ER_ABORTING_CONNECTION](#); SQLSTATE: [08S01](#)
Message: Aborted connection %ld to db: '%s' user: '%s' (%s)
- Error number: [1153](#); Symbol: [ER_NET_PACKET_TOO_LARGE](#); SQLSTATE: [08S01](#)
Message: Got a packet bigger than 'max_allowed_packet' bytes
- Error number: [1154](#); Symbol: [ER_NET_READ_ERROR_FROM_PIPE](#); SQLSTATE: [08S01](#)
Message: Got a read error from the connection pipe
- Error number: [1155](#); Symbol: [ER_NET_FCNTL_ERROR](#); SQLSTATE: [08S01](#)
Message: Got an error from fcntl()
- Error number: [1156](#); Symbol: [ER_NET_PACKETS_OUT_OF_ORDER](#); SQLSTATE: [08S01](#)
Message: Got packets out of order
- Error number: [1157](#); Symbol: [ER_NET_UNCOMPRESS_ERROR](#); SQLSTATE: [08S01](#)
Message: Couldn't uncompress communication packet
- Error number: [1158](#); Symbol: [ER_NET_READ_ERROR](#); SQLSTATE: [08S01](#)
Message: Got an error reading communication packets
- Error number: [1159](#); Symbol: [ER_NET_READ_INTERRUPTED](#); SQLSTATE: [08S01](#)
Message: Got timeout reading communication packets
- Error number: [1160](#); Symbol: [ER_NET_ERROR_ON_WRITE](#); SQLSTATE: [08S01](#)
Message: Got an error writing communication packets
- Error number: [1161](#); Symbol: [ER_NET_WRITE_INTERRUPTED](#); SQLSTATE: [08S01](#)
Message: Got timeout writing communication packets
- Error number: [1162](#); Symbol: [ER_TOO_LONG_STRING](#); SQLSTATE: [42000](#)
Message: Result string is longer than 'max_allowed_packet' bytes
- Error number: [1163](#); Symbol: [ER_TABLE_CANT_HANDLE_BLOB](#); SQLSTATE: [42000](#)
Message: The used table type doesn't support BLOB/TEXT columns
- Error number: [1164](#); Symbol: [ER_TABLE_CANT_HANDLE_AUTO_INCREMENT](#); SQLSTATE: [42000](#)
Message: The used table type doesn't support AUTO_INCREMENT columns
- Error number: [1166](#); Symbol: [ER_WRONG_COLUMN_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect column name '%s'
- Error number: [1167](#); Symbol: [ER_WRONG_KEY_COLUMN](#); SQLSTATE: [42000](#)
Message: The used storage engine can't index column '%s'
- Error number: [1168](#); Symbol: [ER_WRONG_MRG_TABLE](#); SQLSTATE: [HY000](#)

Message: Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist

- Error number: [1169](#); Symbol: [ER_DUP_UNIQUE](#); SQLSTATE: [23000](#)

Message: Can't write, because of unique constraint, to table '%s'

- Error number: [1170](#); Symbol: [ER_BLOB_KEY_WITHOUT_LENGTH](#); SQLSTATE: [42000](#)

Message: BLOB/TEXT column '%s' used in key specification without a key length

- Error number: [1171](#); Symbol: [ER_PRIMARY_CANT_HAVE_NULL](#); SQLSTATE: [42000](#)

Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead

- Error number: [1172](#); Symbol: [ER_TOO_MANY_ROWS](#); SQLSTATE: [42000](#)

Message: Result consisted of more than one row

- Error number: [1173](#); Symbol: [ER_REQUIRES_PRIMARY_KEY](#); SQLSTATE: [42000](#)

Message: This table type requires a primary key

- Error number: [1175](#); Symbol: [ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE](#); SQLSTATE: [HY000](#)

Message: You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column. %s

- Error number: [1176](#); Symbol: [ER_KEY_DOES_NOT_EXIST](#); SQLSTATE: [42000](#)

Message: Key '%s' doesn't exist in table '%s'

- Error number: [1177](#); Symbol: [ER_CHECK_NO_SUCH_TABLE](#); SQLSTATE: [42000](#)

Message: Can't open table

- Error number: [1178](#); Symbol: [ER_CHECK_NOT_IMPLEMENTED](#); SQLSTATE: [42000](#)

Message: The storage engine for the table doesn't support %s

- Error number: [1179](#); Symbol: [ER_CANT_DO_THIS_DURING_AN_TRANSACTION](#); SQLSTATE: [25000](#)

Message: You are not allowed to execute this command in a transaction

- Error number: [1180](#); Symbol: [ER_ERROR_DURING_COMMIT](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' during COMMIT

- Error number: [1181](#); Symbol: [ER_ERROR_DURING_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' during ROLLBACK

- Error number: [1182](#); Symbol: [ER_ERROR_DURING_FLUSH_LOGS](#); SQLSTATE: [HY000](#)

Message: Got error %d during FLUSH_LOGS

- Error number: [1184](#); Symbol: [ER_NEW_ABORTING_CONNECTION](#); SQLSTATE: [08S01](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)

- Error number: [1188](#); Symbol: [ER_SOURCE](#); SQLSTATE: [HY000](#)

Message: Error from source: '%s'

- Error number: [1189](#); Symbol: [ER_SOURCE_NET_READ](#); SQLSTATE: [08S01](#)

Message: Net error reading from source

- Error number: [1190](#); Symbol: [ER_SOURCE_NET_WRITE](#); SQLSTATE: [08S01](#)

Message: Net error writing to source

- Error number: [1191](#); Symbol: [ER_FT_MATCHING_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find FULLTEXT index matching the column list

- Error number: [1192](#); Symbol: [ER_LOCK_OR_ACTIVE_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: Can't execute the given command because you have active locked tables or an active transaction

- Error number: [1193](#); Symbol: [ER_UNKNOWN_SYSTEM_VARIABLE](#); SQLSTATE: [HY000](#)

Message: Unknown system variable '%s'

- Error number: [1194](#); Symbol: [ER_CRASHED_ON_USAGE](#); SQLSTATE: [HY000](#)

Message: Table '%s' is marked as crashed and should be repaired

- Error number: [1195](#); Symbol: [ER_CRASHED_ON_REPAIR](#); SQLSTATE: [HY000](#)

Message: Table '%s' is marked as crashed and last (automatic?) repair failed

- Error number: [1196](#); Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: Some non-transactional changed tables couldn't be rolled back

- Error number: [1197](#); Symbol: [ER_TRANS_CACHE_FULL](#); SQLSTATE: [HY000](#)

Message: Multi-statement transaction required more than 'max_binlog_cache_size' bytes of storage; increase this mysqld variable and try again

- Error number: [1199](#); Symbol: [ER_REPLICA_NOT_RUNNING](#); SQLSTATE: [HY000](#)

Message: This operation requires a running replica; configure replica and do START REPLICA

- Error number: [1200](#); Symbol: [ER_BAD_REPLICA](#); SQLSTATE: [HY000](#)

Message: The server is not configured as replica; fix in config file or with CHANGE REPLICATION SOURCE TO

- Error number: [1201](#); Symbol: [ER_CONNECTION_METADATA](#); SQLSTATE: [HY000](#)

Message: Could not initialize connection metadata structure; more error messages can be found in the MySQL error log

- Error number: [1202](#); Symbol: [ER_REPLICA_THREAD](#); SQLSTATE: [HY000](#)

Message: Could not create replica thread; check system resources

- Error number: [1203](#); Symbol: [ER_TOO_MANY_USER_CONNECTIONS](#); SQLSTATE: [42000](#)

Message: User %s already has more than 'max_user_connections' active connections

- Error number: [1204](#); Symbol: [ER_SET_CONSTANTS_ONLY](#); SQLSTATE: [HY000](#)

Message: You may only use constant expressions with SET

- Error number: [1205](#); Symbol: [ER_LOCK_WAIT_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Lock wait timeout exceeded; try restarting transaction

[InnoDB](#) reports this error when lock wait timeout expires. The statement that waited too long was [rolled back](#) (not the entire [transaction](#)). You can increase the value of the [innodb_lock_wait_timeout](#) configuration option if SQL statements should wait longer for other transactions to complete, or decrease it if too many long-running transactions are causing [locking](#) problems and reducing [concurrency](#) on a busy system.

- Error number: [1206](#); Symbol: [ER_LOCK_TABLE_FULL](#); SQLSTATE: [HY000](#)

Message: The total number of locks exceeds the lock table size

[InnoDB](#) reports this error when the total number of locks exceeds the amount of memory devoted to managing locks. To avoid this error, increase the value of [innodb_buffer_pool_size](#). Within an individual application, a workaround may be to break a large operation into smaller pieces. For example, if the error occurs for a large [INSERT](#), perform several smaller [INSERT](#) operations.

- Error number: [1207](#); Symbol: [ER_READ_ONLY_TRANSACTION](#); SQLSTATE: [25000](#)

Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction

- Error number: [1210](#); Symbol: [ER_WRONG_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Incorrect arguments to %s

- Error number: [1211](#); Symbol: [ER_NO_PERMISSION_TO_CREATE_USER](#); SQLSTATE: [42000](#)

Message: '%s'@'%s' is not allowed to create new users

- Error number: [1213](#); Symbol: [ER_LOCK_DEADLOCK](#); SQLSTATE: [40001](#)

Message: Deadlock found when trying to get lock; try restarting transaction

[InnoDB](#) reports this error when a [transaction](#) encounters a [deadlock](#) and is automatically [rolled back](#) so that your application can take corrective action. To recover from this error, run all the operations in this transaction again. A deadlock occurs when requests for locks arrive in inconsistent order between transactions. The transaction that was rolled back released all its locks, and the other transaction can now get all the locks it requested. Thus, when you re-run the transaction that was rolled back, it might have to wait for other transactions to complete, but typically the deadlock does not recur. If you encounter frequent deadlocks, make the sequence of locking operations ([LOCK TABLES](#), [SELECT . . . FOR UPDATE](#), and so on) consistent between the different transactions or applications that experience the issue. See [Deadlocks in InnoDB](#) for details.

- Error number: [1214](#); Symbol: [ER_TABLE_CANT_HANDLE_FT](#); SQLSTATE: [HY000](#)

Message: The used table type doesn't support FULLTEXT indexes

- Error number: [1215](#); Symbol: [ER_CANNOT_ADD_FOREIGN](#); SQLSTATE: [HY000](#)

Message: Cannot add foreign key constraint

- Error number: [1216](#); Symbol: [ER_NO_REFERENCED_ROW](#); SQLSTATE: [23000](#)

Message: Cannot add or update a child row: a foreign key constraint fails

[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.

-
- Error number: [1217](#); Symbol: [ER_ROW_IS_REFERENCED](#); SQLSTATE: [23000](#)
Message: Cannot delete or update a parent row: a foreign key constraint fails
[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
 - Error number: [1218](#); Symbol: [ER_CONNECT_TO_SOURCE](#); SQLSTATE: [08S01](#)
Message: Error connecting to source: %s
 - Error number: [1220](#); Symbol: [ER_ERROR_WHEN_EXECUTING_COMMAND](#); SQLSTATE: [HY000](#)
Message: Error when executing command %s: %s
 - Error number: [1221](#); Symbol: [ER_WRONG_USAGE](#); SQLSTATE: [HY000](#)
Message: Incorrect usage of %s and %s
 - Error number: [1222](#); Symbol: [ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT](#); SQLSTATE: [21000](#)
Message: The used SELECT statements have a different number of columns
 - Error number: [1223](#); Symbol: [ER_CANT_UPDATE_WITH_READLOCK](#); SQLSTATE: [HY000](#)
Message: Can't execute the query because you have a conflicting read lock
 - Error number: [1224](#); Symbol: [ER_MIXING_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: Mixing of transactional and non-transactional tables is disabled
 - Error number: [1225](#); Symbol: [ER_DUP_ARGUMENT](#); SQLSTATE: [HY000](#)
Message: Option '%s' used twice in statement
 - Error number: [1226](#); Symbol: [ER_USER_LIMIT_REACHED](#); SQLSTATE: [42000](#)
Message: User '%s' has exceeded the '%s' resource (current value: %ld)
 - Error number: [1227](#); Symbol: [ER_SPECIFIC_ACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: Access denied; you need (at least one of) the %s privilege(s) for this operation
 - Error number: [1228](#); Symbol: [ER_LOCAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL
 - Error number: [1229](#); Symbol: [ER_GLOBAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL
 - Error number: [1230](#); Symbol: [ER_NO_DEFAULT](#); SQLSTATE: [42000](#)
Message: Variable '%s' doesn't have a default value
 - Error number: [1231](#); Symbol: [ER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Variable '%s' can't be set to the value of '%s'
 - Error number: [1232](#); Symbol: [ER_WRONG_TYPE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Incorrect argument type to variable '%s'
 - Error number: [1233](#); Symbol: [ER_VAR_CANT_BE_READ](#); SQLSTATE: [HY000](#)

Message: Variable '%s' can only be set, not read

- Error number: [1234](#); Symbol: [ER_CANT_USE_OPTION_HERE](#); SQLSTATE: [42000](#)

Message: Incorrect usage/placement of '%s'

- Error number: [1235](#); Symbol: [ER_NOT_SUPPORTED_YET](#); SQLSTATE: [42000](#)

Message: This version of MySQL doesn't yet support '%s'

- Error number: [1236](#); Symbol: [ER_SOURCE_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)

Message: Got fatal error %d from source when reading data from binary log: '%s'

- Error number: [1237](#); Symbol: [ER_REPLICA_IGNORED_TABLE](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread ignored the query because of replicate-*table rules

- Error number: [1238](#); Symbol: [ER_INCORRECT_GLOBAL_LOCAL_VAR](#); SQLSTATE: [HY000](#)

Message: Variable '%s' is a %s variable

- Error number: [1239](#); Symbol: [ER_WRONG_FK_DEF](#); SQLSTATE: [42000](#)

Message: Incorrect foreign key definition for '%s': %s

- Error number: [1240](#); Symbol: [ER_KEY_REF_DO_NOT_MATCH_TABLE_REF](#); SQLSTATE: [HY000](#)

Message: Key reference and table reference don't match

- Error number: [1241](#); Symbol: [ER_OPERAND_COLUMNS](#); SQLSTATE: [21000](#)

Message: Operand should contain %d column(s)

- Error number: [1242](#); Symbol: [ER_SUBQUERY_NO_1_ROW](#); SQLSTATE: [21000](#)

Message: Subquery returns more than 1 row

- Error number: [1243](#); Symbol: [ER_UNKNOWN_STMT_HANDLER](#); SQLSTATE: [HY000](#)

Message: Unknown prepared statement handler (%.*s) given to %s

- Error number: [1244](#); Symbol: [ER_CORRUPT_HELP_DB](#); SQLSTATE: [HY000](#)

Message: Help database is corrupt or does not exist

- Error number: [1246](#); Symbol: [ER_AUTO_CONVERT](#); SQLSTATE: [HY000](#)

Message: Converting column '%s' from %s to %s

- Error number: [1247](#); Symbol: [ER_ILLEGAL_REFERENCE](#); SQLSTATE: [42S22](#)

Message: Reference '%s' not supported (%s)

- Error number: [1248](#); Symbol: [ER_DERIVED_MUST_HAVE_ALIAS](#); SQLSTATE: [42000](#)

Message: Every derived table must have its own alias

- Error number: [1249](#); Symbol: [ER_SELECT_REDUCE](#); SQLSTATE: [01000](#)

Message: Select %u was reduced during optimization

- Error number: [1250](#); Symbol: [ER_TABLENAME_NOT_ALLOWED_HERE](#); SQLSTATE: [42000](#)

Message: Table '%s' from one of the SELECTs cannot be used in %s

-
- Error number: [1251](#); Symbol: [ER_NOT_SUPPORTED_AUTH_MODE](#); SQLSTATE: [08004](#)
Message: Client does not support authentication protocol requested by server; consider upgrading MySQL client
 - Error number: [1252](#); Symbol: [ER_SPATIAL_CANT_HAVE_NULL](#); SQLSTATE: [42000](#)
Message: All parts of a SPATIAL index must be NOT NULL
 - Error number: [1253](#); Symbol: [ER_COLLATION_CHARSET_MISMATCH](#); SQLSTATE: [42000](#)
Message: COLLATION '%s' is not valid for CHARACTER SET '%s'
 - Error number: [1256](#); Symbol: [ER_TOO_BIG_FOR_UNCOMPRESS](#); SQLSTATE: [HY000](#)
Message: Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was corrupted)
 - Error number: [1257](#); Symbol: [ER_ZLIB_Z_MEM_ERROR](#); SQLSTATE: [HY000](#)
Message: ZLIB: Not enough memory
 - Error number: [1258](#); Symbol: [ER_ZLIB_Z_BUF_ERROR](#); SQLSTATE: [HY000](#)
Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted)
 - Error number: [1259](#); Symbol: [ER_ZLIB_Z_DATA_ERROR](#); SQLSTATE: [HY000](#)
Message: ZLIB: Input data corrupted
 - Error number: [1260](#); Symbol: [ER_CUT_VALUE_GROUP_CONCAT](#); SQLSTATE: [HY000](#)
Message: Row %u was cut by GROUP_CONCAT()
 - Error number: [1261](#); Symbol: [ER_WARN_TOO_FEW_RECORDS](#); SQLSTATE: [01000](#)
Message: Row %ld doesn't contain data for all columns
 - Error number: [1262](#); Symbol: [ER_WARN_TOO_MANY_RECORDS](#); SQLSTATE: [01000](#)
Message: Row %ld was truncated; it contained more data than there were input columns
 - Error number: [1263](#); Symbol: [ER_WARN_NULL_TO_NOTNULL](#); SQLSTATE: [22004](#)
Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld
 - Error number: [1264](#); Symbol: [ER_WARN_DATA_OUT_OF_RANGE](#); SQLSTATE: [22003](#)
Message: Out of range value for column '%s' at row %ld
 - Error number: [1265](#); Symbol: [WARN_DATA_TRUNCATED](#); SQLSTATE: [01000](#)
Message: Data truncated for column '%s' at row %ld
 - Error number: [1266](#); Symbol: [ER_WARN_USING_OTHER_HANDLER](#); SQLSTATE: [HY000](#)
Message: Using storage engine %s for table '%s'
 - Error number: [1267](#); Symbol: [ER_CANT_AGGREGATE_2COLLATIONS](#); SQLSTATE: [HY000](#)
Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'
 - Error number: [1269](#); Symbol: [ER_REVOKE_GRANTS](#); SQLSTATE: [HY000](#)

Message: Can't revoke all privileges for one or more of the requested users

- Error number: [1270](#); Symbol: [ER_CANT_AGGREGATE_3COLLATIONS](#); SQLSTATE: [HY000](#)

Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'

- Error number: [1271](#); Symbol: [ER_CANT_AGGREGATE_NCOLLATIONS](#); SQLSTATE: [HY000](#)

Message: Illegal mix of collations for operation '%s'

- Error number: [1272](#); Symbol: [ER_VARIABLE_IS_NOT_STRUCT](#); SQLSTATE: [HY000](#)

Message: Variable '%s' is not a variable component (can't be used as XXXX.variable_name)

- Error number: [1273](#); Symbol: [ER_UNKNOWN_COLLATION](#); SQLSTATE: [HY000](#)

Message: Unknown collation: '%s'

- Error number: [1274](#); Symbol: [ER_REPLICA_IGNORED_SSL_PARAMS](#); SQLSTATE: [HY000](#)

Message: SSL parameters in CHANGE REPLICATION SOURCE are ignored because this MySQL replica was compiled without SSL support; they can be used later if MySQL replica with SSL is started

- Error number: [1276](#); Symbol: [ER_WARN_FIELD_RESOLVED](#); SQLSTATE: [HY000](#)

Message: Field or reference '%s%s%s%s%s' of SELECT #%d was resolved in SELECT #%d

- Error number: [1277](#); Symbol: [ER_BAD_REPLICA_UNTIL_COND](#); SQLSTATE: [HY000](#)

Message: Incorrect parameter or combination of parameters for START REPLICA UNTIL

- Error number: [1278](#); Symbol: [ER_MISSING_SKIP_REPLICA](#); SQLSTATE: [HY000](#)

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START REPLICA UNTIL; otherwise, you will get problems if you get an unexpected replica's mysqld restart

- Error number: [1279](#); Symbol: [ER_UNTIL_COND_IGNORED](#); SQLSTATE: [HY000](#)

Message: SQL thread is not to be started so UNTIL options are ignored

- Error number: [1280](#); Symbol: [ER_WRONG_NAME_FOR_INDEX](#); SQLSTATE: [42000](#)

Message: Incorrect index name '%s'

- Error number: [1281](#); Symbol: [ER_WRONG_NAME_FOR_CATALOG](#); SQLSTATE: [42000](#)

Message: Incorrect catalog name '%s'

- Error number: [1283](#); Symbol: [ER_BAD_FT_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' cannot be part of FULLTEXT index

- Error number: [1284](#); Symbol: [ER_UNKNOWN_KEY_CACHE](#); SQLSTATE: [HY000](#)

Message: Unknown key cache '%s'

- Error number: [1285](#); Symbol: [ER_WARN_HOSTNAME_WONT_WORK](#); SQLSTATE: [HY000](#)

Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work

- Error number: [1286](#); Symbol: [ER_UNKNOWN_STORAGE_ENGINE](#); SQLSTATE: [42000](#)

Message: Unknown storage engine '%s'

- Error number: [1287](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

- Error number: [1288](#); Symbol: [ER_NON_UPDATABLE_TABLE](#); SQLSTATE: [HY000](#)

Message: The target table %s of the %s is not updatable

- Error number: [1289](#); Symbol: [ER_FEATURE_DISABLED](#); SQLSTATE: [HY000](#)

Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working

- Error number: [1290](#); Symbol: [ER_OPTION_PREVENTS_STATEMENT](#); SQLSTATE: [HY000](#)

Message: The MySQL server is running with the %s option so it cannot execute this statement

- Error number: [1291](#); Symbol: [ER_DUPLICATED_VALUE_IN_TYPE](#); SQLSTATE: [HY000](#)

Message: Column '%s' has duplicated value '%s' in %s

- Error number: [1292](#); Symbol: [ER_TRUNCATED_WRONG_VALUE](#); SQLSTATE: [22007](#)

Message: Truncated incorrect %s value: '%s'

- Error number: [1294](#); Symbol: [ER_INVALID_ON_UPDATE](#); SQLSTATE: [HY000](#)

Message: Invalid ON UPDATE clause for '%s' column

- Error number: [1295](#); Symbol: [ER_UNSUPPORTED_PS](#); SQLSTATE: [HY000](#)

Message: This command is not supported in the prepared statement protocol yet

- Error number: [1296](#); Symbol: [ER_GET_ERRMSG](#); SQLSTATE: [HY000](#)

Message: Got error %d '%s' from %s

- Error number: [1297](#); Symbol: [ER_GET_TEMPORARY_ERRMSG](#); SQLSTATE: [HY000](#)

Message: Got temporary error %d '%s' from %s

- Error number: [1298](#); Symbol: [ER_UNKNOWN_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: Unknown or incorrect time zone: '%s'

- Error number: [1299](#); Symbol: [ER_WARN_INVALID_TIMESTAMP](#); SQLSTATE: [HY000](#)

Message: Invalid TIMESTAMP value in column '%s' at row %ld

- Error number: [1300](#); Symbol: [ER_INVALID_CHARACTER_STRING](#); SQLSTATE: [HY000](#)

Message: Invalid %s character string: '%s'

- Error number: [1301](#); Symbol: [ER_WARN_ALLOWED_PACKET_OVERFLOWED](#); SQLSTATE: [HY000](#)

Message: Result of %s() was larger than max_allowed_packet (%ld) - truncated

- Error number: [1302](#); Symbol: [ER_CONFLICTING_DECLARATIONS](#); SQLSTATE: [HY000](#)

Message: Conflicting declarations: '%s%s' and '%s%s'

- Error number: [1303](#); Symbol: [ER_SP_NO_RECURSIVE_CREATE](#); SQLSTATE: [2F003](#)

Message: Can't create a %s from within another stored routine

-
- Error number: [1304](#); Symbol: [ER_SP_ALREADY_EXISTS](#); SQLSTATE: [42000](#)
Message: %s %s already exists
 - Error number: [1305](#); Symbol: [ER_SP_DOES_NOT_EXIST](#); SQLSTATE: [42000](#)
Message: %s %s does not exist
 - Error number: [1306](#); Symbol: [ER_SP_DROP_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to DROP %s %s
 - Error number: [1307](#); Symbol: [ER_SP_STORE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to CREATE %s %s
 - Error number: [1308](#); Symbol: [ER_SP_LILABEL_MISMATCH](#); SQLSTATE: [42000](#)
Message: %s with no matching label: %s
 - Error number: [1309](#); Symbol: [ER_SP_LABEL_REDEFINE](#); SQLSTATE: [42000](#)
Message: Redefining label %s
 - Error number: [1310](#); Symbol: [ER_SP_LABEL_MISMATCH](#); SQLSTATE: [42000](#)
Message: End-label %s without match
 - Error number: [1311](#); Symbol: [ER_SP_UNINIT_VAR](#); SQLSTATE: [01000](#)
Message: Referring to uninitialized variable %s
 - Error number: [1312](#); Symbol: [ER_SP_BADSELECT](#); SQLSTATE: [0A000](#)
Message: PROCEDURE %s can't return a result set in the given context
 - Error number: [1313](#); Symbol: [ER_SP_BADRETURN](#); SQLSTATE: [42000](#)
Message: RETURN is only allowed in a FUNCTION
 - Error number: [1314](#); Symbol: [ER_SP_BADSTATEMENT](#); SQLSTATE: [0A000](#)
Message: %s is not allowed in stored procedures
 - Error number: [1315](#); Symbol: [ER_UPDATE_LOG_DEPRECATED_IGNORED](#); SQLSTATE: [42000](#)
Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been ignored.
 - Error number: [1316](#); Symbol: [ER_UPDATE_LOG_DEPRECATED_TRANSLATED](#); SQLSTATE: [42000](#)
Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been translated to SET SQL_LOG_BIN.
 - Error number: [1317](#); Symbol: [ER_QUERY_INTERRUPTED](#); SQLSTATE: [70100](#)
Message: Query execution was interrupted
 - Error number: [1318](#); Symbol: [ER_SP_WRONG_NO_OF_ARGS](#); SQLSTATE: [42000](#)
Message: Incorrect number of arguments for %s %s; expected %u, got %u
 - Error number: [1319](#); Symbol: [ER_SP_COND_MISMATCH](#); SQLSTATE: [42000](#)
Message: Undefined CONDITION: %s

-
- Error number: [1320](#); Symbol: [ER_SP_NORETURN](#); SQLSTATE: [42000](#)
Message: No RETURN found in FUNCTION %s
 - Error number: [1321](#); Symbol: [ER_SP_NORETURNEND](#); SQLSTATE: [2F005](#)
Message: FUNCTION %s ended without RETURN
 - Error number: [1322](#); Symbol: [ER_SP_BAD_CURSOR_QUERY](#); SQLSTATE: [42000](#)
Message: Cursor statement must be a SELECT
 - Error number: [1323](#); Symbol: [ER_SP_BAD_CURSOR_SELECT](#); SQLSTATE: [42000](#)
Message: Cursor SELECT must not have INTO
 - Error number: [1324](#); Symbol: [ER_SP_CURSOR_MISMATCH](#); SQLSTATE: [42000](#)
Message: Undefined CURSOR: %s
 - Error number: [1325](#); Symbol: [ER_SP_CURSOR_ALREADY_OPEN](#); SQLSTATE: [24000](#)
Message: Cursor is already open
 - Error number: [1326](#); Symbol: [ER_SP_CURSOR_NOT_OPEN](#); SQLSTATE: [24000](#)
Message: Cursor is not open
 - Error number: [1327](#); Symbol: [ER_SP_UNDECLARED_VAR](#); SQLSTATE: [42000](#)
Message: Undeclared variable: %s
 - Error number: [1328](#); Symbol: [ER_SP_WRONG_NO_OF_FETCH_ARGS](#); SQLSTATE: [HY000](#)
Message: Incorrect number of FETCH variables
 - Error number: [1329](#); Symbol: [ER_SP_FETCH_NO_DATA](#); SQLSTATE: [02000](#)
Message: No data - zero rows fetched, selected, or processed
 - Error number: [1330](#); Symbol: [ER_SP_DUP_PARAM](#); SQLSTATE: [42000](#)
Message: Duplicate parameter: %s
 - Error number: [1331](#); Symbol: [ER_SP_DUP_VAR](#); SQLSTATE: [42000](#)
Message: Duplicate variable: %s
 - Error number: [1332](#); Symbol: [ER_SP_DUP_COND](#); SQLSTATE: [42000](#)
Message: Duplicate condition: %s
 - Error number: [1333](#); Symbol: [ER_SP_DUP_CURS](#); SQLSTATE: [42000](#)
Message: Duplicate cursor: %s
 - Error number: [1334](#); Symbol: [ER_SP_CANT_ALTER](#); SQLSTATE: [HY000](#)
Message: Failed to ALTER %s %s
 - Error number: [1335](#); Symbol: [ER_SP_SUBSELECT_NYI](#); SQLSTATE: [0A000](#)
Message: Subquery value not supported
 - Error number: [1336](#); Symbol: [ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG](#); SQLSTATE: [0A000](#)

Message: %s is not allowed in stored function or trigger

- Error number: [1337](#); Symbol: [ER_SP_VARCOND_AFTER_CURSHNDLR](#); SQLSTATE: [42000](#)

Message: Variable or condition declaration after cursor or handler declaration

- Error number: [1338](#); Symbol: [ER_SP_CURSOR_AFTER_HANDLER](#); SQLSTATE: [42000](#)

Message: Cursor declaration after handler declaration

- Error number: [1339](#); Symbol: [ER_SP_CASE_NOT_FOUND](#); SQLSTATE: [20000](#)

Message: Case not found for CASE statement

- Error number: [1340](#); Symbol: [ER_FPARSER_TOO_BIG_FILE](#); SQLSTATE: [HY000](#)

Message: Configuration file '%s' is too big

- Error number: [1341](#); Symbol: [ER_FPARSER_BAD_HEADER](#); SQLSTATE: [HY000](#)

Message: Malformed file type header in file '%s'

- Error number: [1342](#); Symbol: [ER_FPARSER_EOF_IN_COMMENT](#); SQLSTATE: [HY000](#)

Message: Unexpected end of file while parsing comment '%s'

- Error number: [1343](#); Symbol: [ER_FPARSER_ERROR_IN_PARAMETER](#); SQLSTATE: [HY000](#)

Message: Error while parsing parameter '%s' (line: '%s')

- Error number: [1344](#); Symbol: [ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER](#); SQLSTATE: [HY000](#)

Message: Unexpected end of file while skipping unknown parameter '%s'

- Error number: [1345](#); Symbol: [ER_VIEW_NO_EXPLAIN](#); SQLSTATE: [HY000](#)

Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table

- Error number: [1347](#); Symbol: [ER_WRONG_OBJECT](#); SQLSTATE: [HY000](#)

Message: '%s.%s' is not %s

The named object is incorrect for the type of operation attempted on it. It must be an object of the named type. Example: [HANDLER OPEN](#) requires a base table, not a view. It fails if attempted on an [INFORMATION_SCHEMA](#) table that is implemented as a view on data dictionary tables.

- Error number: [1348](#); Symbol: [ER_NONUPDATEABLE_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' is not updatable

- Error number: [1350](#); Symbol: [ER_VIEW_SELECT_CLAUSE](#); SQLSTATE: [HY000](#)

Message: View's SELECT contains a '%s' clause

- Error number: [1351](#); Symbol: [ER_VIEW_SELECT_VARIABLE](#); SQLSTATE: [HY000](#)

Message: View's SELECT contains a variable or parameter

- Error number: [1352](#); Symbol: [ER_VIEW_SELECT_TMPTABLE](#); SQLSTATE: [HY000](#)

Message: View's SELECT refers to a temporary table '%s'

- Error number: [1353](#); Symbol: [ER_VIEW_WRONG_LIST](#); SQLSTATE: [HY000](#)

Message: In definition of view, derived table or common table expression, SELECT list and column names list have different column counts

- Error number: [1354](#); Symbol: [ER_WARN_VIEW_MERGE](#); SQLSTATE: [HY000](#)

Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

- Error number: [1355](#); Symbol: [ER_WARN_VIEW_WITHOUT_KEY](#); SQLSTATE: [HY000](#)

Message: View being updated does not have complete key of underlying table in it

- Error number: [1356](#); Symbol: [ER_VIEW_INVALID](#); SQLSTATE: [HY000](#)

Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer invoker of view lack rights to use them

- Error number: [1357](#); Symbol: [ER_SP_NO_DROP_SP](#); SQLSTATE: [HY000](#)

Message: Can't drop or alter a %s from within another stored routine

- Error number: [1359](#); Symbol: [ER_TRG_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: Trigger already exists

- Error number: [1360](#); Symbol: [ER_TRG_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Trigger does not exist

- Error number: [1361](#); Symbol: [ER_TRG_ON_VIEW_OR_TEMP_TABLE](#); SQLSTATE: [HY000](#)

Message: Trigger's '%s' is view or temporary table

- Error number: [1362](#); Symbol: [ER_TRG_CANT_CHANGE_ROW](#); SQLSTATE: [HY000](#)

Message: Updating of %s row is not allowed in %strigger

- Error number: [1363](#); Symbol: [ER_TRG_NO_SUCH_ROW_IN_TRG](#); SQLSTATE: [HY000](#)

Message: There is no %s row in %s trigger

- Error number: [1364](#); Symbol: [ER_NO_DEFAULT_FOR_FIELD](#); SQLSTATE: [HY000](#)

Message: Field '%s' doesn't have a default value

- Error number: [1365](#); Symbol: [ER_DIVISION_BY_ZERO](#); SQLSTATE: [22012](#)

Message: Division by 0

- Error number: [1366](#); Symbol: [ER_TRUNCATED_WRONG_VALUE_FOR_FIELD](#); SQLSTATE: [HY000](#)

Message: Incorrect %s value: '%s' for column '%s' at row %ld

- Error number: [1367](#); Symbol: [ER_ILLEGAL_VALUE_FOR_TYPE](#); SQLSTATE: [22007](#)

Message: Illegal %s '%s' value found during parsing

- Error number: [1368](#); Symbol: [ER_VIEW_NONUPD_CHECK](#); SQLSTATE: [HY000](#)

Message: CHECK OPTION on non-updatable view '%s.%s'

- Error number: [1369](#); Symbol: [ER_VIEW_CHECK_FAILED](#); SQLSTATE: [HY000](#)

Message: CHECK OPTION failed '%s.%s'

- Error number: [1370](#); Symbol: [ER_PROCACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)

Message: %s command denied to user '%s'@'%s' for routine '%s'

- Error number: [1371](#); Symbol: [ER_RELAY_LOG_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed purging old relay logs: %s

- Error number: [1373](#); Symbol: [ER_UNKNOWN_TARGET_BINLOG](#); SQLSTATE: [HY000](#)

Message: Target log not found in binlog index

- Error number: [1374](#); Symbol: [ER_IO_ERR_LOG_INDEX_READ](#); SQLSTATE: [HY000](#)

Message: I/O error reading log index file

- Error number: [1375](#); Symbol: [ER_BINLOG_PURGE_PROHIBITED](#); SQLSTATE: [HY000](#)

Message: Server configuration does not permit binlog purge

- Error number: [1376](#); Symbol: [ER_FSEEK_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed on fseek()

- Error number: [1377](#); Symbol: [ER_BINLOG_PURGE_FATAL_ERR](#); SQLSTATE: [HY000](#)

Message: Fatal error during log purge

- Error number: [1378](#); Symbol: [ER_LOG_IN_USE](#); SQLSTATE: [HY000](#)

Message: A purgeable log is in use, will not purge

- Error number: [1379](#); Symbol: [ER_LOG_PURGE_UNKNOWN_ERR](#); SQLSTATE: [HY000](#)

Message: Unknown error during log purge

- Error number: [1380](#); Symbol: [ER_RELAY_LOG_INIT](#); SQLSTATE: [HY000](#)

Message: Failed initializing relay log position: %s

- Error number: [1381](#); Symbol: [ER_NO_BINARY_LOGGING](#); SQLSTATE: [HY000](#)

Message: You are not using binary logging

- Error number: [1382](#); Symbol: [ER_RESERVED_SYNTAX](#); SQLSTATE: [HY000](#)

Message: The '%s' syntax is reserved for purposes internal to the MySQL server

- Error number: [1390](#); Symbol: [ER_PS_MANY_PARAM](#); SQLSTATE: [HY000](#)

Message: Prepared statement contains too many placeholders

- Error number: [1391](#); Symbol: [ER_KEY_PART_0](#); SQLSTATE: [HY000](#)

Message: Key part '%s' length cannot be 0

- Error number: [1392](#); Symbol: [ER_VIEW_CHECKSUM](#); SQLSTATE: [HY000](#)

Message: View text checksum failed

- Error number: [1393](#); Symbol: [ER_VIEW_MULTIUPDATE](#); SQLSTATE: [HY000](#)

Message: Can not modify more than one base table through a join view '%s.%s'

- Error number: [1394](#); Symbol: [ER_VIEW_NO_INSERT_FIELD_LIST](#); SQLSTATE: [HY000](#)

Message: Can not insert into join view '%s.%s' without fields list

-
- Error number: [1395](#); Symbol: [ER_VIEW_DELETE_MERGE_VIEW](#); SQLSTATE: [HY000](#)
Message: Can not delete from join view '%s.%s'
 - Error number: [1396](#); Symbol: [ER_CANNOT_USER](#); SQLSTATE: [HY000](#)
Message: Operation %s failed for %s
 - Error number: [1397](#); Symbol: [ER_XAER_NOTA](#); SQLSTATE: [XAE04](#)
Message: XAER_NOTA: Unknown XID
 - Error number: [1398](#); Symbol: [ER_XAER_INVAL](#); SQLSTATE: [XAE05](#)
Message: XAER_INVAL: Invalid arguments (or unsupported command)
 - Error number: [1399](#); Symbol: [ER_XAER_RMFAIL](#); SQLSTATE: [XAE07](#)
Message: XAER_RMFAIL: The command cannot be executed when global transaction is in the %s state
 - Error number: [1400](#); Symbol: [ER_XAER_OUTSIDE](#); SQLSTATE: [XAE09](#)
Message: XAER_OUTSIDE: Some work is done outside global transaction
 - Error number: [1401](#); Symbol: [ER_XAER_RMERR](#); SQLSTATE: [XAE03](#)
Message: XAER_RMERR: Fatal error occurred in the transaction branch - check your data for consistency
 - Error number: [1402](#); Symbol: [ER_XA_RBROLLBACK](#); SQLSTATE: [XA100](#)
Message: XA_RBROLLBACK: Transaction branch was rolled back
 - Error number: [1403](#); Symbol: [ER_NONEXISTING_PROC_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'
 - Error number: [1404](#); Symbol: [ER_PROC_AUTO_GRANT_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to grant EXECUTE and ALTER ROUTINE privileges
 - Error number: [1405](#); Symbol: [ER_PROC_AUTO_REVOKE_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to revoke all privileges to dropped routine
 - Error number: [1406](#); Symbol: [ER_DATA_TOO_LONG](#); SQLSTATE: [22001](#)
Message: Data too long for column '%s' at row %ld
 - Error number: [1407](#); Symbol: [ER_SP_BAD_SQLSTATE](#); SQLSTATE: [42000](#)
Message: Bad SQLSTATE: '%s'
 - Error number: [1408](#); Symbol: [ER_STARTUP](#); SQLSTATE: [HY000](#)
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s
 - Error number: [1409](#); Symbol: [ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR](#); SQLSTATE: [HY000](#)
Message: Can't load value from file with fixed size rows to variable
 - Error number: [1410](#); Symbol: [ER_CANT_CREATE_USER_WITH_GRANT](#); SQLSTATE: [42000](#)
Message: You are not allowed to create a user with GRANT

-
- Error number: [1411](#); Symbol: [ER_WRONG_VALUE_FOR_TYPE](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s' for function %s
 - Error number: [1412](#); Symbol: [ER_TABLE_DEF_CHANGED](#); SQLSTATE: [HY000](#)
Message: Table definition has changed, please retry transaction
 - Error number: [1413](#); Symbol: [ER_SP_DUP_HANDLER](#); SQLSTATE: [42000](#)
Message: Duplicate handler declared in the same block
 - Error number: [1414](#); Symbol: [ER_SP_NOT_VAR_ARG](#); SQLSTATE: [42000](#)
Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger
 - Error number: [1415](#); Symbol: [ER_SP_NO_RETSET](#); SQLSTATE: [0A000](#)
Message: Not allowed to return a result set from a %s
 - Error number: [1416](#); Symbol: [ER_CANT_CREATE_GEOMETRY_OBJECT](#); SQLSTATE: [22003](#)
Message: Cannot get geometry object from data you send to the GEOMETRY field
 - Error number: [1418](#); Symbol: [ER_BINLOG_UNSAFE_ROUTINE](#); SQLSTATE: [HY000](#)
Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
 - Error number: [1419](#); Symbol: [ER_BINLOG_CREATE_ROUTINE_NEED_SUPER](#); SQLSTATE: [HY000](#)
Message: You do not have the SUPER privilege and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
 - Error number: [1421](#); Symbol: [ER_STMT_HAS_NO_OPEN_CURSOR](#); SQLSTATE: [HY000](#)
Message: The statement (%lu) has no open cursor.
 - Error number: [1422](#); Symbol: [ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG](#); SQLSTATE: [HY000](#)
Message: Explicit or implicit commit is not allowed in stored function or trigger.
 - Error number: [1423](#); Symbol: [ER_NO_DEFAULT_FOR_VIEW_FIELD](#); SQLSTATE: [HY000](#)
Message: Field of view '%s.%s' underlying table doesn't have a default value
 - Error number: [1424](#); Symbol: [ER_SP_NO_RECURSION](#); SQLSTATE: [HY000](#)
Message: Recursive stored functions and triggers are not allowed.
 - Error number: [1425](#); Symbol: [ER_TOO_BIG_SCALE](#); SQLSTATE: [42000](#)
Message: Too big scale %d specified for column '%s'. Maximum is %lu.
 - Error number: [1426](#); Symbol: [ER_TOO_BIG_PRECISION](#); SQLSTATE: [42000](#)
Message: Too-big precision %d specified for '%s'. Maximum is %lu.
 - Error number: [1427](#); Symbol: [ER_M_BIGGER_THAN_D](#); SQLSTATE: [42000](#)
Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').
 - Error number: [1428](#); Symbol: [ER_WRONG_LOCK_OF_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: You can't combine write-locking of system tables with other tables or lock types

- Error number: [1429](#); Symbol: [ER_CONNECT_TO_FOREIGN_DATA_SOURCE](#); SQLSTATE: [HY000](#)

Message: Unable to connect to foreign data source: %s

- Error number: [1430](#); Symbol: [ER_QUERY_ON_FOREIGN_DATA_SOURCE](#); SQLSTATE: [HY000](#)

Message: There was a problem processing the query on the foreign data source. Data source error: %s

- Error number: [1431](#); Symbol: [ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST](#); SQLSTATE: [HY000](#)

Message: The foreign data source you are trying to reference does not exist. Data source error: %s

- Error number: [1432](#); Symbol: [ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE](#); SQLSTATE: [HY000](#)

Message: Can't create federated table. The data source connection string '%s' is not in the correct format

- Error number: [1433](#); Symbol: [ER_FOREIGN_DATA_STRING_INVALID](#); SQLSTATE: [HY000](#)

Message: The data source connection string '%s' is not in the correct format

- Error number: [1435](#); Symbol: [ER_TRG_IN_WRONG_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Trigger in wrong schema

- Error number: [1436](#); Symbol: [ER_STACK_OVERRUN_NEED_MORE](#); SQLSTATE: [HY000](#)

Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread_stack=#' to specify a bigger stack.

- Error number: [1437](#); Symbol: [ER_TOO_LONG_BODY](#); SQLSTATE: [42000](#)

Message: Routine body for '%s' is too long

- Error number: [1438](#); Symbol: [ER_WARN_CANT_DROP_DEFAULT_KEYCACHE](#); SQLSTATE: [HY000](#)

Message: Cannot drop default keycache

- Error number: [1439](#); Symbol: [ER_TOO_BIG_DISPLAYWIDTH](#); SQLSTATE: [42000](#)

Message: Display width out of range for column '%s' (max = %lu)

- Error number: [1440](#); Symbol: [ER_XAER_DUPID](#); SQLSTATE: [XAE08](#)

Message: XAER_DUPID: The XID already exists

- Error number: [1441](#); Symbol: [ER_DATETIME_FUNCTION_OVERFLOW](#); SQLSTATE: [22008](#)

Message: Datetime function: %s field overflow

- Error number: [1442](#); Symbol: [ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG](#); SQLSTATE: [HY000](#)

Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.

- Error number: [1443](#); Symbol: [ER_VIEW_PREVENT_UPDATE](#); SQLSTATE: [HY000](#)

Message: The definition of table '%s' prevents operation %s on table '%s'.

-
- Error number: [1444](#); Symbol: [ER_PS_NO_RECURSION](#); SQLSTATE: [HY000](#)
Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner
 - Error number: [1445](#); Symbol: [ER_SP_CANT_SET_AUTOCOMMIT](#); SQLSTATE: [HY000](#)
Message: Not allowed to set autocommit from a stored function or trigger
 - Error number: [1447](#); Symbol: [ER_VIEW_FRM_NO_USER](#); SQLSTATE: [HY000](#)
Message: View '%s'.'%s' has no definer information (old table format). Current user is used as definer. Please recreate the view!
 - Error number: [1448](#); Symbol: [ER_VIEW_OTHER_USER](#); SQLSTATE: [HY000](#)
Message: You need the SUPER privilege for creation view with '%s'@'%s' definer
 - Error number: [1449](#); Symbol: [ER_NO_SUCH_USER](#); SQLSTATE: [HY000](#)
Message: The user specified as a definer ('%s'@'%s') does not exist
 - Error number: [1450](#); Symbol: [ER_FORBID_SCHEMA_CHANGE](#); SQLSTATE: [HY000](#)
Message: Changing schema from '%s' to '%s' is not allowed.
 - Error number: [1451](#); Symbol: [ER_ROW_IS_REFERENCED_2](#); SQLSTATE: [23000](#)
Message: Cannot delete or update a parent row: a foreign key constraint fails%
[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
 - Error number: [1452](#); Symbol: [ER_NO_REFERENCED_ROW_2](#); SQLSTATE: [23000](#)
Message: Cannot add or update a child row: a foreign key constraint fails%
[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.
 - Error number: [1453](#); Symbol: [ER_SP_BAD_VAR_SHADOW](#); SQLSTATE: [42000](#)
Message: Variable '%s' must be quoted with `...`, or renamed
 - Error number: [1454](#); Symbol: [ER_TRG_NO_DEFINER](#); SQLSTATE: [HY000](#)
Message: No definer attribute for trigger '%s'.'%s'. It's disallowed to create trigger without definer.
 - Error number: [1455](#); Symbol: [ER_OLD_FILE_FORMAT](#); SQLSTATE: [HY000](#)
Message: '%s' has an old format, you should re-create the '%s' object(s)
 - Error number: [1456](#); Symbol: [ER_SP_RECURSION_LIMIT](#); SQLSTATE: [HY000](#)
Message: Recursive limit %d (as set by the max_sp_recursion_depth variable) was exceeded for routine %s
 - Error number: [1458](#); Symbol: [ER_SP_WRONG_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect routine name '%s'
 - Error number: [1459](#); Symbol: [ER_TABLE_NEEDS_UPGRADE](#); SQLSTATE: [HY000](#)
Message: Table upgrade required. Please do "REPAIR TABLE `%s`" or dump/reload to fix it!

-
- Error number: [1460](#); Symbol: [ER_SP_NO_AGGREGATE](#); SQLSTATE: [42000](#)
Message: AGGREGATE is not supported for stored functions
 - Error number: [1461](#); Symbol: [ER_MAX_PREPARED_STMT_COUNT_REACHED](#); SQLSTATE: [42000](#)
Message: Can't create more than max_prepared_stmt_count statements (current value: %lu)
 - Error number: [1462](#); Symbol: [ER_VIEW_RECURSIVE](#); SQLSTATE: [HY000](#)
Message: `%s`.`%s` contains view recursion
 - Error number: [1463](#); Symbol: [ER_NON_GROUPING_FIELD_USED](#); SQLSTATE: [42000](#)
Message: Non-grouping field '%s' is used in %s clause
 - Error number: [1464](#); Symbol: [ER_TABLE_CANT_HANDLE_SPKEYS](#); SQLSTATE: [HY000](#)
Message: The used table type doesn't support SPATIAL indexes
 - Error number: [1465](#); Symbol: [ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Triggers can not be created on system tables
 - Error number: [1466](#); Symbol: [ER_REMOVED_SPACES](#); SQLSTATE: [HY000](#)
Message: Leading spaces are removed from name '%s'
 - Error number: [1467](#); Symbol: [ER_AUTOINC_READ_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to read auto-increment value from storage engine
 - Error number: [1468](#); Symbol: [ER_USERNAME](#); SQLSTATE: [HY000](#)
Message: user name
 - Error number: [1469](#); Symbol: [ER_HOSTNAME](#); SQLSTATE: [HY000](#)
Message: host name
 - Error number: [1470](#); Symbol: [ER_WRONG_STRING_LENGTH](#); SQLSTATE: [HY000](#)
Message: String '%s' is too long for %s (should be no longer than %d)
 - Error number: [1471](#); Symbol: [ER_NON_INSERTABLE_TABLE](#); SQLSTATE: [HY000](#)
Message: The target table %s of the %s is not insertable-into
 - Error number: [1472](#); Symbol: [ER_ADMIN_WRONG_MRG_TABLE](#); SQLSTATE: [HY000](#)
Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist
 - Error number: [1473](#); Symbol: [ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT](#); SQLSTATE: [HY000](#)
Message: Too high level of nesting for select
 - Error number: [1474](#); Symbol: [ER_NAME_BECOMES_EMPTY](#); SQLSTATE: [HY000](#)
Message: Name '%s' has become "
 - Error number: [1475](#); Symbol: [ER_AMBIGUOUS_FIELD_TERM](#); SQLSTATE: [HY000](#)
Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-empty FIELDS ENCLOSED BY

-
- Error number: [1476](#); Symbol: [ER_FOREIGN_SERVER_EXISTS](#); SQLSTATE: [HY000](#)
Message: The foreign server, %s, you are trying to create already exists.
 - Error number: [1477](#); Symbol: [ER_FOREIGN_SERVER_DOESNT_EXIST](#); SQLSTATE: [HY000](#)
Message: The foreign server name you are trying to reference does not exist. Data source error: %s
 - Error number: [1478](#); Symbol: [ER_ILLEGAL_HA_CREATE_OPTION](#); SQLSTATE: [HY000](#)
Message: Table storage engine '%s' does not support the create option '%s'
 - Error number: [1479](#); Symbol: [ER_PARTITION_REQUIRES_VALUES_ERROR](#); SQLSTATE: [HY000](#)
Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition
 - Error number: [1480](#); Symbol: [ER_PARTITION_WRONG_VALUES_ERROR](#); SQLSTATE: [HY000](#)
Message: Only %s PARTITIONING can use VALUES %s in partition definition
 - Error number: [1481](#); Symbol: [ER_PARTITION_MAXVALUE_ERROR](#); SQLSTATE: [HY000](#)
Message: MAXVALUE can only be used in last partition definition
 - Error number: [1484](#); Symbol: [ER_PARTITION_WRONG_NO_PART_ERROR](#); SQLSTATE: [HY000](#)
Message: Wrong number of partitions defined, mismatch with previous setting
 - Error number: [1485](#); Symbol: [ER_PARTITION_WRONG_NO_SUBPART_ERROR](#); SQLSTATE: [HY000](#)
Message: Wrong number of subpartitions defined, mismatch with previous setting
 - Error number: [1486](#); Symbol: [ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR](#); SQLSTATE: [HY000](#)
Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not allowed
 - Error number: [1488](#); Symbol: [ER_FIELD_NOT_FOUND_PART_ERROR](#); SQLSTATE: [HY000](#)
Message: Field in list of fields for partition function not found in table
 - Error number: [1490](#); Symbol: [ER_INCONSISTENT_PARTITION_INFO_ERROR](#); SQLSTATE: [HY000](#)
Message: The partition info in the frm file is not consistent with what can be written into the frm file
 - Error number: [1491](#); Symbol: [ER_PARTITION_FUNC_NOT_ALLOWED_ERROR](#); SQLSTATE: [HY000](#)
Message: The %s function returns the wrong type
 - Error number: [1492](#); Symbol: [ER_PARTITIONS_MUST_BE_DEFINED_ERROR](#); SQLSTATE: [HY000](#)
Message: For %s partitions each partition must be defined
 - Error number: [1493](#); Symbol: [ER_RANGE_NOT_INCREASING_ERROR](#); SQLSTATE: [HY000](#)
Message: VALUES LESS THAN value must be strictly increasing for each partition
 - Error number: [1494](#); Symbol: [ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR](#); SQLSTATE: [HY000](#)
Message: VALUES value must be of same type as partition function
 - Error number: [1495](#); Symbol: [ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR](#); SQLSTATE: [HY000](#)

Message: Multiple definition of same constant in list partitioning

- Error number: 1496; Symbol: `ER_PARTITION_ENTRY_ERROR`; SQLSTATE: `HY000`

Message: Partitioning can not be used stand-alone in query

- Error number: 1497; Symbol: `ER_MIX_HANDLER_ERROR`; SQLSTATE: `HY000`

Message: The mix of handlers in the partitions is not allowed in this version of MySQL

- Error number: 1498; Symbol: `ER_PARTITION_NOT_DEFINED_ERROR`; SQLSTATE: `HY000`

Message: For the partitioned engine it is necessary to define all %s

- Error number: 1499; Symbol: `ER_TOO_MANY_PARTITIONS_ERROR`; SQLSTATE: `HY000`

Message: Too many partitions (including subpartitions) were defined

- Error number: 1500; Symbol: `ER_SUBPARTITION_ERROR`; SQLSTATE: `HY000`

Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning

- Error number: 1501; Symbol: `ER_CANT_CREATE_HANDLER_FILE`; SQLSTATE: `HY000`

Message: Failed to create specific handler file

- Error number: 1502; Symbol: `ER_BLOB_FIELD_IN_PART_FUNC_ERROR`; SQLSTATE: `HY000`

Message: A BLOB field is not allowed in partition function

- Error number: 1503; Symbol: `ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF`; SQLSTATE: `HY000`

Message: A %s must include all columns in the table's partitioning function (prefixed columns are not considered).

- Error number: 1504; Symbol: `ER_NO_PARTS_ERROR`; SQLSTATE: `HY000`

Message: Number of %s = 0 is not an allowed value

- Error number: 1505; Symbol: `ER_PARTITION_MGMT_ON_NONPARTITIONED`; SQLSTATE: `HY000`

Message: Partition management on a not partitioned table is not possible

- Error number: 1506; Symbol: `ER_FOREIGN_KEY_ON_PARTITIONED`; SQLSTATE: `HY000`

Message: Foreign keys are not yet supported in conjunction with partitioning

- Error number: 1507; Symbol: `ER_DROP_PARTITION_NON_EXISTENT`; SQLSTATE: `HY000`

Message: Error in list of partitions to %s

- Error number: 1508; Symbol: `ER_DROP_LAST_PARTITION`; SQLSTATE: `HY000`

Message: Cannot remove all partitions, use DROP TABLE instead

- Error number: 1509; Symbol: `ER_COALESCE_ONLY_ON_HASH_PARTITION`; SQLSTATE: `HY000`

Message: COALESCE PARTITION can only be used on HASH/KEY partitions

- Error number: 1510; Symbol: `ER_REORG_HASH_ONLY_ON_SAME_NO`; SQLSTATE: `HY000`

Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers

-
- Error number: [1511](#); Symbol: [ER_REORG_NO_PARAM_ERROR](#); SQLSTATE: [HY000](#)
Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONS
 - Error number: [1512](#); Symbol: [ER_ONLY_ON_RANGE_LIST_PARTITION](#); SQLSTATE: [HY000](#)
Message: %s PARTITION can only be used on RANGE/LIST partitions
 - Error number: [1513](#); Symbol: [ER_ADD_PARTITION_SUBPART_ERROR](#); SQLSTATE: [HY000](#)
Message: Trying to Add partition(s) with wrong number of subpartitions
 - Error number: [1514](#); Symbol: [ER_ADD_PARTITION_NO_NEW_PARTITION](#); SQLSTATE: [HY000](#)
Message: At least one partition must be added
 - Error number: [1515](#); Symbol: [ER_COALESCE_PARTITION_NO_PARTITION](#); SQLSTATE: [HY000](#)
Message: At least one partition must be coalesced
 - Error number: [1516](#); Symbol: [ER_REORG_PARTITION_NOT_EXIST](#); SQLSTATE: [HY000](#)
Message: More partitions to reorganize than there are partitions
 - Error number: [1517](#); Symbol: [ER_SAME_NAME_PARTITION](#); SQLSTATE: [HY000](#)
Message: Duplicate partition name %s
 - Error number: [1518](#); Symbol: [ER_NO_BINLOG_ERROR](#); SQLSTATE: [HY000](#)
Message: It is not allowed to shut off binlog on this command
 - Error number: [1519](#); Symbol: [ER_CONSECUTIVE_REORG_PARTITIONS](#); SQLSTATE: [HY000](#)
Message: When reorganizing a set of partitions they must be in consecutive order
 - Error number: [1520](#); Symbol: [ER_REORG_OUTSIDE_RANGE](#); SQLSTATE: [HY000](#)
Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range
 - Error number: [1521](#); Symbol: [ER_PARTITION_FUNCTION_FAILURE](#); SQLSTATE: [HY000](#)
Message: Partition function not supported in this version for this handler
 - Error number: [1523](#); Symbol: [ER_LIMITED_PART_RANGE](#); SQLSTATE: [HY000](#)
Message: The %s handler only supports 32 bit integers in VALUES
 - Error number: [1524](#); Symbol: [ER_PLUGIN_IS_NOT_LOADED](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is not loaded
 - Error number: [1525](#); Symbol: [ER_WRONG_VALUE](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s'
 - Error number: [1526](#); Symbol: [ER_NO_PARTITION_FOR_GIVEN_VALUE](#); SQLSTATE: [HY000](#)
Message: Table has no partition for value %s
 - Error number: [1527](#); Symbol: [ER_FILEGROUP_OPTION_ONLY_ONCE](#); SQLSTATE: [HY000](#)
Message: It is not allowed to specify %s more than once

-
- Error number: [1528](#); Symbol: [ER_CREATE_FILEGROUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to create %s
 - Error number: [1529](#); Symbol: [ER_DROP_FILEGROUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to drop %s
 - Error number: [1530](#); Symbol: [ER_TABLESPACE_AUTO_EXTEND_ERROR](#); SQLSTATE: [HY000](#)
Message: The handler doesn't support autoextend of tablespaces
 - Error number: [1531](#); Symbol: [ER_WRONG_SIZE_NUMBER](#); SQLSTATE: [HY000](#)
Message: A size parameter was incorrectly specified, either number or on the form 10M
 - Error number: [1532](#); Symbol: [ER_SIZE_OVERFLOW_ERROR](#); SQLSTATE: [HY000](#)
Message: The size number was correct but we don't allow the digit part to be more than 2 billion
 - Error number: [1533](#); Symbol: [ER_ALTER_FILEGROUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to alter: %s
 - Error number: [1534](#); Symbol: [ER_BINLOG_ROW_LOGGING_FAILED](#); SQLSTATE: [HY000](#)
Message: Writing one row to the row-based binary log failed
 - Error number: [1537](#); Symbol: [ER_EVENT_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)
Message: Event '%s' already exists
 - Error number: [1539](#); Symbol: [ER_EVENT_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)
Message: Unknown event '%s'
 - Error number: [1542](#); Symbol: [ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG](#); SQLSTATE: [HY000](#)
Message: INTERVAL is either not positive or too big
 - Error number: [1543](#); Symbol: [ER_EVENT_ENDS_BEFORE_STARTS](#); SQLSTATE: [HY000](#)
Message: ENDS is either invalid or before STARTS
 - Error number: [1544](#); Symbol: [ER_EVENT_EXEC_TIME_IN_THE_PAST](#); SQLSTATE: [HY000](#)
Message: Event execution time is in the past. Event has been disabled
 - Error number: [1551](#); Symbol: [ER_EVENT_SAME_NAME](#); SQLSTATE: [HY000](#)
Message: Same old and new event name
 - Error number: [1553](#); Symbol: [ER_DROP_INDEX_FK](#); SQLSTATE: [HY000](#)
Message: Cannot drop index '%s': needed in a foreign key constraint

[InnoDB](#) reports this error when you attempt to drop the last index that can enforce a particular referential constraint.

For optimal performance with DML statements, [InnoDB](#) requires an index to exist on [foreign key](#) columns, so that [UPDATE](#) and [DELETE](#) operations on a [parent table](#) can easily check whether corresponding rows exist in the [child table](#). MySQL creates or drops such indexes automatically when needed, as a side-effect of [CREATE TABLE](#), [CREATE INDEX](#), and [ALTER TABLE](#) statements.

When you drop an index, **InnoDB** checks if the index is used for checking a foreign key constraint. It is still OK to drop the index if there is another index that can be used to enforce the same constraint. **InnoDB** prevents you from dropping the last index that can enforce a particular referential constraint.

- Error number: [1554](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX_WITH_VER](#); SQLSTATE: [HY000](#)
Message: The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead
- Error number: [1556](#); Symbol: [ER_CANT_LOCK_LOG_TABLE](#); SQLSTATE: [HY000](#)
Message: You can't use locks with log tables.
- Error number: [1557](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED](#); SQLSTATE: [23000](#)
Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry
- Error number: [1558](#); Symbol: [ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE](#); SQLSTATE: [HY000](#)
Message: The column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.
- Error number: [1560](#); Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)
Message: Cannot change the binary logging format inside a stored function or trigger
- Error number: [1562](#); Symbol: [ER_PARTITION_NO_TEMPORARY](#); SQLSTATE: [HY000](#)
Message: Cannot create temporary table with partitions
- Error number: [1563](#); Symbol: [ER_PARTITION_CONST_DOMAIN_ERROR](#); SQLSTATE: [HY000](#)
Message: Partition constant is out of partition function domain
- Error number: [1564](#); Symbol: [ER_PARTITION_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: This partition function is not allowed
- Error number: [1566](#); Symbol: [ER_NULL_IN_VALUES_LESS_THAN](#); SQLSTATE: [HY000](#)
Message: Not allowed to use NULL value in VALUES LESS THAN
- Error number: [1567](#); Symbol: [ER_WRONG_PARTITION_NAME](#); SQLSTATE: [HY000](#)
Message: Incorrect partition name
- Error number: [1568](#); Symbol: [ER_CANT_CHANGE_TX_CHARACTERISTICS](#); SQLSTATE: [25001](#)
Message: Transaction characteristics can't be changed while a transaction is in progress
- Error number: [1569](#); Symbol: [ER_DUP_ENTRY_AUTOINCREMENT_CASE](#); SQLSTATE: [HY000](#)
Message: ALTER TABLE causes auto_increment resequencing, resulting in duplicate entry '%s' for key '%s'
- Error number: [1571](#); Symbol: [ER_EVENT_SET_VAR_ERROR](#); SQLSTATE: [HY000](#)
Message: Error during starting/stopping of the scheduler. Error code %u
- Error number: [1572](#); Symbol: [ER_PARTITION_MERGE_ERROR](#); SQLSTATE: [HY000](#)
Message: Engine cannot be used in partitioned tables

-
- Error number: [1575](#); Symbol: [ER_BASE64_DECODE_ERROR](#); SQLSTATE: [HY000](#)
Message: Decoding of base64 string failed
 - Error number: [1576](#); Symbol: [ER_EVENT_RECURSION_FORBIDDEN](#); SQLSTATE: [HY000](#)
Message: Recursion of EVENT DDL statements is forbidden when body is present
 - Error number: [1578](#); Symbol: [ER_ONLY_INTEGERS_ALLOWED](#); SQLSTATE: [HY000](#)
Message: Only integers allowed as number here
 - Error number: [1579](#); Symbol: [ER_UNSUPPORTED_LOG_ENGINE](#); SQLSTATE: [HY000](#)
Message: This storage engine cannot be used for log tables
 - Error number: [1580](#); Symbol: [ER_BAD_LOG_STATEMENT](#); SQLSTATE: [HY000](#)
Message: You cannot '%s' a log table if logging is enabled
 - Error number: [1581](#); Symbol: [ER_CANT_RENAME_LOG_TABLE](#); SQLSTATE: [HY000](#)
Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log table to an archive table and another table back to '%s'
 - Error number: [1582](#); Symbol: [ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT](#); SQLSTATE: [42000](#)
Message: Incorrect parameter count in the call to native function '%s'
 - Error number: [1583](#); Symbol: [ER_WRONG_PARAMETERS_TO_NATIVE_FCT](#); SQLSTATE: [42000](#)
Message: Incorrect parameters in the call to native function '%s'
 - Error number: [1584](#); Symbol: [ER_WRONG_PARAMETERS_TO_STORED_FCT](#); SQLSTATE: [42000](#)
Message: Incorrect parameters in the call to stored function %s
 - Error number: [1585](#); Symbol: [ER_NATIVE_FCT_NAME_COLLISION](#); SQLSTATE: [HY000](#)
Message: This function '%s' has the same name as a native function
 - Error number: [1586](#); Symbol: [ER_DUP_ENTRY_WITH_KEY_NAME](#); SQLSTATE: [23000](#)
Message: Duplicate entry '%s' for key '%s'

The format string for this error is also used with [ER_DUP_ENTRY](#).
 - Error number: [1587](#); Symbol: [ER_BINLOG_PURGE_EMFILE](#); SQLSTATE: [HY000](#)
Message: Too many files opened, please execute the command again
 - Error number: [1588](#); Symbol: [ER_EVENT_CANNOT_CREATE_IN_THE_PAST](#); SQLSTATE: [HY000](#)
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped immediately after creation.
 - Error number: [1589](#); Symbol: [ER_EVENT_CANNOT_ALTER_IN_THE_PAST](#); SQLSTATE: [HY000](#)
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was not changed. Specify a time in the future.
 - Error number: [1591](#); Symbol: [ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT](#); SQLSTATE: [HY000](#)
Message: Table has no partition for some existing values

-
- Error number: [1592](#); Symbol: [ER_BINLOG_UNSAFE_STATEMENT](#); SQLSTATE: [HY000](#)
Message: Unsafe statement written to the binary log using statement format since BINLOG_FORMAT = STATEMENT. %s
 - Error number: [1593](#); Symbol: [ER_BINLOG_FATAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Fatal error: %s
 - Error number: [1598](#); Symbol: [ER_BINLOG_LOGGING_IMPOSSIBLE](#); SQLSTATE: [HY000](#)
Message: Binary logging not possible. Message: %s
 - Error number: [1599](#); Symbol: [ER_VIEW_NO_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: View `%s`.`%s` has no creation context
 - Error number: [1600](#); Symbol: [ER_VIEW_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: Creation context of view `%s`.`%s` is invalid
 - Error number: [1602](#); Symbol: [ER_TRG_CORRUPTED_FILE](#); SQLSTATE: [HY000](#)
Message: Corrupted TRG file for table `%s`.`%s`
 - Error number: [1603](#); Symbol: [ER_TRG_NO_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: Triggers for table `%s`.`%s` have no creation context
 - Error number: [1604](#); Symbol: [ER_TRG_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: Trigger creation context of table `%s`.`%s` is invalid
 - Error number: [1605](#); Symbol: [ER_EVENT_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: Creation context of event `%s`.`%s` is invalid
 - Error number: [1606](#); Symbol: [ER_TRG_CANT_OPEN_TABLE](#); SQLSTATE: [HY000](#)
Message: Cannot open table for trigger `%s`.`%s`
 - Error number: [1609](#); Symbol: [ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT](#); SQLSTATE: [HY000](#)
Message: The BINLOG statement of type `%s` was not preceded by a format description BINLOG statement.
 - Error number: [1610](#); Symbol: [ER_REPLICA_CORRUPT_EVENT](#); SQLSTATE: [HY000](#)
Message: Corrupted replication event was detected
 - Error number: [1612](#); Symbol: [ER_LOG_PURGE_NO_FILE](#); SQLSTATE: [HY000](#)
Message: Being purged log %s was not found
 - Error number: [1613](#); Symbol: [ER_XA_RBTIMEOUT](#); SQLSTATE: [XA106](#)
Message: XA_RBTIMEOUT: Transaction branch was rolled back: took too long
 - Error number: [1614](#); Symbol: [ER_XA_RBDEADLOCK](#); SQLSTATE: [XA102](#)
Message: XA_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected
 - Error number: [1615](#); Symbol: [ER_NEED_REPREPARE](#); SQLSTATE: [HY000](#)

Message: Prepared statement needs to be re-prepared

- Error number: [1617](#); Symbol: [WARN_NO_CONNECTION_METADATA](#); SQLSTATE: [HY000](#)

Message: The connection metadata structure does not exist

- Error number: [1618](#); Symbol: [WARN_OPTION_IGNORED](#); SQLSTATE: [HY000](#)

Message: <%s> option ignored

- Error number: [1619](#); Symbol: [ER_PLUGIN_DELETE_BUILTIN](#); SQLSTATE: [HY000](#)

Message: Built-in plugins cannot be deleted

- Error number: [1620](#); Symbol: [WARN_PLUGIN_BUSY](#); SQLSTATE: [HY000](#)

Message: Plugin is busy and will be uninstalled on shutdown

- Error number: [1621](#); Symbol: [ER_VARIABLE_IS_READONLY](#); SQLSTATE: [HY000](#)

Message: %s variable '%s' is read-only. Use SET %s to assign the value

- Error number: [1622](#); Symbol: [ER_WARN_ENGINE_TRANSACTION_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: Storage engine %s does not support rollback for this statement. Transaction rolled back and must be restarted

- Error number: [1624](#); Symbol: [ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).

- Error number: [1625](#); Symbol: [ER_NDB_REPLICATION_SCHEMA_ERROR](#); SQLSTATE: [HY000](#)

Message: Bad schema for mysql.ndb_replication table. Message: %s

- Error number: [1626](#); Symbol: [ER_CONFLICT_FN_PARSE_ERROR](#); SQLSTATE: [HY000](#)

Message: Error in parsing conflict function. Message: %s

- Error number: [1627](#); Symbol: [ER_EXCEPTIONS_WRITE_ERROR](#); SQLSTATE: [HY000](#)

Message: Write to exceptions table failed. Message: %s

- Error number: [1628](#); Symbol: [ER_TOO_LONG_TABLE_COMMENT](#); SQLSTATE: [HY000](#)

Message: Comment for table '%s' is too long (max = %lu)

- Error number: [1629](#); Symbol: [ER_TOO_LONG_FIELD_COMMENT](#); SQLSTATE: [HY000](#)

Message: The maximum supported character limit for the field, '%s', has been exceeded (max = %lu)

- Error number: [1630](#); Symbol: [ER_FUNC_INEXISTENT_NAME_COLLISION](#); SQLSTATE: [42000](#)

Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual

- Error number: [1631](#); Symbol: [ER_DATABASE_NAME](#); SQLSTATE: [HY000](#)

Message: Database

- Error number: [1632](#); Symbol: [ER_TABLE_NAME](#); SQLSTATE: [HY000](#)

Message: Table

- Error number: 1633; Symbol: ER_PARTITION_NAME; SQLSTATE: HY000

Message: Partition

- Error number: 1634; Symbol: ER_SUBPARTITION_NAME; SQLSTATE: HY000

Message: Subpartition

- Error number: 1635; Symbol: ER_TEMPORARY_NAME; SQLSTATE: HY000

Message: Temporary

- Error number: 1636; Symbol: ER_RENAMED_NAME; SQLSTATE: HY000

Message: Renamed

- Error number: 1637; Symbol: ER_TOO_MANY_CONCURRENT_TRXS; SQLSTATE: HY000

Message: Too many active concurrent transactions

- Error number: 1638; Symbol: WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED; SQLSTATE: HY000

Message: Non-ASCII separator arguments are not fully supported

- Error number: 1639; Symbol: ER_DEBUG_SYNC_TIMEOUT; SQLSTATE: HY000

Message: debug sync point wait timed out

- Error number: 1640; Symbol: ER_DEBUG_SYNC_HIT_LIMIT; SQLSTATE: HY000

Message: debug sync point hit limit reached

- Error number: 1641; Symbol: ER_DUP_SIGNAL_SET; SQLSTATE: 42000

Message: Duplicate condition information item '%s'

- Error number: 1642; Symbol: ER_SIGNAL_WARN; SQLSTATE: 01000

Message: Unhandled user-defined warning condition

- Error number: 1643; Symbol: ER_SIGNAL_NOT_FOUND; SQLSTATE: 02000

Message: Unhandled user-defined not found condition

- Error number: 1644; Symbol: ER_SIGNAL_EXCEPTION; SQLSTATE: HY000

Message: Unhandled user-defined exception condition

- Error number: 1645; Symbol: ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER; SQLSTATE: 0K000

Message: RESIGNAL when handler not active

- Error number: 1646; Symbol: ER_SIGNAL_BAD_CONDITION_TYPE; SQLSTATE: HY000

Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE

- Error number: 1647; Symbol: WARN_COND_ITEM_TRUNCATED; SQLSTATE: HY000

Message: Data truncated for condition item '%s'

- Error number: 1648; Symbol: ER_COND_ITEM_TOO_LONG; SQLSTATE: HY000

Message: Data too long for condition item '%s'

- Error number: 1649; Symbol: [ER_UNKNOWN_LOCALE](#); SQLSTATE: HY000

Message: Unknown locale: '%s'

- Error number: 1650; Symbol: [ER_REPLICA_IGNORE_SERVER_IDS](#); SQLSTATE: HY000

Message: The requested server id %d clashes with the replica startup option --replicate-same-server-id

- Error number: 1652; Symbol: [ER_SAME_NAME_PARTITION_FIELD](#); SQLSTATE: HY000

Message: Duplicate partition field name '%s'

- Error number: 1653; Symbol: [ER_PARTITION_COLUMN_LIST_ERROR](#); SQLSTATE: HY000

Message: Inconsistency in usage of column lists for partitioning

- Error number: 1654; Symbol: [ER_WRONG_TYPE_COLUMN_VALUE_ERROR](#); SQLSTATE: HY000

Message: Partition column values of incorrect type

- Error number: 1655; Symbol: [ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR](#); SQLSTATE: HY000

Message: Too many fields in '%s'

- Error number: 1656; Symbol: [ER_MAXVALUE_IN_VALUES_IN](#); SQLSTATE: HY000

Message: Cannot use MAXVALUE as value in VALUES IN

- Error number: 1657; Symbol: [ER_TOO_MANY_VALUES_ERROR](#); SQLSTATE: HY000

Message: Cannot have more than one value for this type of %s partitioning

- Error number: 1658; Symbol: [ER_ROW_SINGLE_PARTITION_FIELD_ERROR](#); SQLSTATE: HY000

Message: Row expressions in VALUES IN only allowed for multi-field column partitioning

- Error number: 1659; Symbol: [ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD](#); SQLSTATE: HY000

Message: Field '%s' is of a not allowed type for this type of partitioning

- Error number: 1660; Symbol: [ER_PARTITION_FIELDS_TOO_LONG](#); SQLSTATE: HY000

Message: The total length of the partitioning fields is too large

- Error number: 1661; Symbol: [ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.

- Error number: 1662; Symbol: [ER_BINLOG_ROW_MODE_AND_STMT_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.

- Error number: 1663; Symbol: [ER_BINLOG_UNSAFE_AND_STMT_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG_FORMAT = MIXED. %s

-
- Error number: 1664; Symbol: `ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.
 - Error number: 1665; Symbol: `ER_BINLOG_STMT_MODE_AND_ROW_ENGINE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since `BINLOG_FORMAT = STATEMENT` and at least one table uses a storage engine limited to row-based logging. %s
 - Error number: 1666; Symbol: `ER_BINLOG_ROW_INJECTION_AND_STMT_MODE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and `BINLOG_FORMAT = STATEMENT`.
 - Error number: 1667; Symbol: `ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.
 - Error number: 1668; Symbol: `ER_BINLOG_UNSAFE_LIMIT`; SQLSTATE: `HY000`

Message: The statement is unsafe because it uses a `LIMIT` clause. This is unsafe because the set of rows included cannot be predicted.
 - Error number: 1670; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_TABLE`; SQLSTATE: `HY000`

Message: The statement is unsafe because it uses the general log, slow query log, or `performance_schema` table(s). This is unsafe because system tables may differ on replicas.
 - Error number: 1671; Symbol: `ER_BINLOG_UNSAFE_AUTOINC_COLUMNS`; SQLSTATE: `HY000`

Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an `AUTO_INCREMENT` column. Inserted values cannot be logged correctly.
 - Error number: 1672; Symbol: `ER_BINLOG_UNSAFE_UDF`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a UDF which may not return the same value on the replica.
 - Error number: 1673; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_VARIABLE`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a system variable that may have a different value on the replica.
 - Error number: 1674; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_FUNCTION`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a system function that may return a different value on the replica.
 - Error number: 1675; Symbol: `ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS`; SQLSTATE: `HY000`

Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction.
 - Error number: 1676; Symbol: `ER_MESSAGE_AND_STATEMENT`; SQLSTATE: `HY000`

Message: %s Statement: %s

-
- Error number: [1678](#); Symbol: [ER_REPLICA_CANT_CREATE_CONVERSION](#); SQLSTATE: [HY000](#)
Message: Can't create conversion table for table '%s.%s'
 - Error number: [1679](#); Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)
Message: Cannot modify @@session.binlog_format inside a transaction
 - Error number: [1680](#); Symbol: [ER_PATH_LENGTH](#); SQLSTATE: [HY000](#)
Message: The path specified for %s is too long.
 - Error number: [1681](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release.
 - Error number: [1682](#); Symbol: [ER_WRONG_NATIVE_TABLE_STRUCTURE](#); SQLSTATE: [HY000](#)
Message: Native table '%s'.'%s' has the wrong structure
 - Error number: [1683](#); Symbol: [ER_WRONG_PERFSCHEMA_USAGE](#); SQLSTATE: [HY000](#)
Message: Invalid performance_schema usage.
 - Error number: [1684](#); Symbol: [ER_WARN_I_S_SKIPPED_TABLE](#); SQLSTATE: [HY000](#)
Message: Table '%s'.'%s' was skipped since its definition is being modified by concurrent DDL statement
 - Error number: [1685](#); Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: [HY000](#)
Message: Cannot modify @@session.binlog_direct_non_transactional_updates inside a transaction
 - Error number: [1686](#); Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: [HY000](#)
Message: Cannot change the binlog direct flag inside a stored function or trigger
 - Error number: [1687](#); Symbol: [ER_SPATIAL_MUST_HAVE_GEOM_COL](#); SQLSTATE: [42000](#)
Message: A SPATIAL index may only contain a geometrical type column
 - Error number: [1688](#); Symbol: [ER_TOO_LONG_INDEX_COMMENT](#); SQLSTATE: [HY000](#)
Message: Comment for index '%s' is too long (max = %lu)
 - Error number: [1689](#); Symbol: [ER_LOCK_ABORTED](#); SQLSTATE: [HY000](#)
Message: Wait on a lock was aborted due to a pending exclusive lock
 - Error number: [1690](#); Symbol: [ER_DATA_OUT_OF_RANGE](#); SQLSTATE: [22003](#)
Message: %s value is out of range in '%s'
 - Error number: [1692](#); Symbol: [ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE](#); SQLSTATE: [HY000](#)
Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.
 - Error number: [1693](#); Symbol: [ER_BINLOG_UNSAFE_MIXED_STATEMENT](#); SQLSTATE: [HY000](#)

Message: Statement accesses nontransactional table as well as transactional or temporary table, and writes to any of them.

- Error number: 1694; Symbol: ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN; SQLSTATE: HY000

Message: Cannot modify @@session.sql_log_bin inside a transaction

- Error number: 1695; Symbol: ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN; SQLSTATE: HY000

Message: Cannot change the sql_log_bin inside a stored function or trigger

- Error number: 1696; Symbol: ER_FAILED_READ_FROM_PAR_FILE; SQLSTATE: HY000

Message: Failed to read from the .par file

- Error number: 1697; Symbol: ER_VALUES_IS_NOT_INT_TYPE_ERROR; SQLSTATE: HY000

Message: VALUES value for partition '%s' must have type INT

- Error number: 1698; Symbol: ER_ACCESS_DENIED_NO_PASSWORD_ERROR; SQLSTATE: 28000

Message: Access denied for user '%s'@'%s'

- Error number: 1701; Symbol: ER_TRUNCATE_ILLEGAL_FK; SQLSTATE: 42000

Message: Cannot truncate a table referenced in a foreign key constraint (%s)

- Error number: 1702; Symbol: ER_PLUGIN_IS_PERMANENT; SQLSTATE: HY000

Message: Plugin '%s' is force_plus_permanent and can not be unloaded

- Error number: 1703; Symbol: ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN; SQLSTATE: HY000

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

- Error number: 1704; Symbol: ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX; SQLSTATE: HY000

Message: The requested value for the heartbeat period exceeds the value of `replica\_net\_timeout` seconds. A sensible value for the period should be less than the timeout.

- Error number: 1705; Symbol: ER_STMT_CACHE_FULL; SQLSTATE: HY000

Message: Multi-row statements required more than 'max_binlog_stmt_cache_size' bytes of storage; increase this mysqld variable and try again

- Error number: 1706; Symbol: ER_MULTI_UPDATE_KEY_CONFLICT; SQLSTATE: HY000

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.

- Error number: 1707; Symbol: ER_TABLE_NEEDS_REBUILD; SQLSTATE: HY000

Message: Table rebuild required. Please do "ALTER TABLE `%(table)s` FORCE" or dump/reload to fix it!

- Error number: 1708; Symbol: WARN_OPTION_BELOW_LIMIT; SQLSTATE: HY000

Message: The value of '%s' should be no less than the value of '%s'

- Error number: 1709; Symbol: ER_INDEX_COLUMN_TOO_LONG; SQLSTATE: HY000

Message: Index column size too large. The maximum column size is %lu bytes.

- Error number: [1710](#); Symbol: [ER_ERROR_IN_TRIGGER_BODY](#); SQLSTATE: [HY000](#)

Message: Trigger '%s' has an error in its body: '%s'

- Error number: [1711](#); Symbol: [ER_ERROR_IN_UNKNOWN_TRIGGER_BODY](#); SQLSTATE: [HY000](#)

Message: Unknown trigger has an error in its body: '%s'

- Error number: [1712](#); Symbol: [ER_INDEX_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Index %s is corrupted

- Error number: [1713](#); Symbol: [ER_UNDO_RECORD_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Undo log record is too big.

- Error number: [1714](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT](#); SQLSTATE: [HY000](#)

Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: [1715](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE](#); SQLSTATE: [HY000](#)

Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on source and the replica.

- Error number: [1716](#); Symbol: [ER_BINLOG_UNSAFE_REPLACE_SELECT](#); SQLSTATE: [HY000](#)

Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: [1717](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT](#); SQLSTATE: [HY000](#)

Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: [1718](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT](#); SQLSTATE: [HY000](#)

Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: [1719](#); Symbol: [ER_BINLOG_UNSAFE_UPDATE_IGNORE](#); SQLSTATE: [HY000](#)

Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: [1720](#); Symbol: [ER_PLUGIN_NO_UNINSTALL](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.

-
- Error number: [1721](#); Symbol: [ER_PLUGIN_NO_INSTALL](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.
 - Error number: [1722](#); Symbol: [ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT](#); SQLSTATE: [HY000](#)
Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1723](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC](#); SQLSTATE: [HY000](#)
Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1724](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_TWO_KEYS](#); SQLSTATE: [HY000](#)
Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe
 - Error number: [1725](#); Symbol: [ER_TABLE_IN_FK_CHECK](#); SQLSTATE: [HY000](#)
Message: Table is being used in foreign key check.
 - Error number: [1726](#); Symbol: [ER_UNSUPPORTED_ENGINE](#); SQLSTATE: [HY000](#)
Message: Storage engine '%s' does not support system tables. [%s.%s]
 - Error number: [1727](#); Symbol: [ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST](#); SQLSTATE: [HY000](#)
Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.
 - Error number: [1728](#); Symbol: [ER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: [HY000](#)
Message: Cannot load from %s.%s. The table is probably corrupted
 - Error number: [1729](#); Symbol: [ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)
Message: The requested value %s for the source delay exceeds the maximum %u
 - Error number: [1730](#); Symbol: [ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT](#); SQLSTATE: [HY000](#)
Message: Only Format_description_log_event and row events are allowed in BINLOG statements (but %s was provided)
 - Error number: [1731](#); Symbol: [ER_PARTITION_EXCHANGE_DIFFERENT_OPTION](#); SQLSTATE: [HY000](#)
Message: Non matching attribute '%s' between partition and table
 - Error number: [1732](#); Symbol: [ER_PARTITION_EXCHANGE_PART_TABLE](#); SQLSTATE: [HY000](#)
Message: Table to exchange with partition is partitioned: '%s'
 - Error number: [1733](#); Symbol: [ER_PARTITION_EXCHANGE_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: Table to exchange with partition is temporary: '%s'

-
- Error number: [1734](#); Symbol: [ER_PARTITION_INSTEAD_OF_SUBPARTITION](#); SQLSTATE: [HY000](#)
Message: Subpartitioned table, use subpartition instead of partition
 - Error number: [1735](#); Symbol: [ER_UNKNOWN_PARTITION](#); SQLSTATE: [HY000](#)
Message: Unknown partition '%s' in table '%s'
 - Error number: [1736](#); Symbol: [ER_TABLES_DIFFERENT_METADATA](#); SQLSTATE: [HY000](#)
Message: Tables have different definitions
 - Error number: [1737](#); Symbol: [ER_ROW_DOES_NOT_MATCH_PARTITION](#); SQLSTATE: [HY000](#)
Message: Found a row that does not match the partition
 - Error number: [1738](#); Symbol: [ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX](#); SQLSTATE: [HY000](#)
Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.
 - Error number: [1739](#); Symbol: [ER_WARN_INDEX_NOT_APPLICABLE](#); SQLSTATE: [HY000](#)
Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'
 - Error number: [1740](#); Symbol: [ER_PARTITION_EXCHANGE_FOREIGN_KEY](#); SQLSTATE: [HY000](#)
Message: Table to exchange with partition has foreign key references: '%s'
 - Error number: [1742](#); Symbol: [ER_RPL_INFO_DATA_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Data for column '%s' too long
 - Error number: [1745](#); Symbol: [ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX](#); SQLSTATE: [HY000](#)
Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.
 - Error number: [1746](#); Symbol: [ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT](#); SQLSTATE: [HY000](#)
Message: Can't update table '%s' while '%s' is being created.
 - Error number: [1747](#); Symbol: [ER_PARTITION_CLAUSE_ON_NONPARTITIONED](#); SQLSTATE: [HY000](#)
Message: PARTITION () clause on non partitioned table
 - Error number: [1748](#); Symbol: [ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET](#); SQLSTATE: [HY000](#)
Message: Found a row not matching the given partition set
 - Error number: [1750](#); Symbol: [ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE](#); SQLSTATE: [HY000](#)
Message: Failure while changing the type of replication repository: %s.
 - Error number: [1751](#); Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: The creation of some temporary tables could not be rolled back.
-

-
- Error number: [1752](#); Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: Some temporary tables were dropped, but these operations could not be rolled back.
 - Error number: [1753](#); Symbol: [ER_MTA_FEATURE_IS_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: %s is not supported in multi-threaded replica mode. %s
 - Error number: [1754](#); Symbol: [ER_MTA_UPDATED_DBS_GREATER_MAX](#); SQLSTATE: [HY000](#)
Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.
 - Error number: [1755](#); Symbol: [ER_MTA_CANT_PARALLEL](#); SQLSTATE: [HY000](#)
Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.
 - Error number: [1756](#); Symbol: [ER_MTA_INCONSISTENT_DATA](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [1757](#); Symbol: [ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING](#); SQLSTATE: [HY000](#)
Message: FULLTEXT index is not supported for partitioned tables.
 - Error number: [1758](#); Symbol: [ER_DA_INVALID_CONDITION_NUMBER](#); SQLSTATE: [35000](#)
Message: Invalid condition number
 - Error number: [1759](#); Symbol: [ER_INSECURE_PLAIN_TEXT](#); SQLSTATE: [HY000](#)
Message: Sending passwords in plain text without SSL/TLS is extremely insecure.
 - Error number: [1760](#); Symbol: [ER_INSECURE_CHANGE_SOURCE](#); SQLSTATE: [HY000](#)
Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.
 - Error number: [1761](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO](#); SQLSTATE: [23000](#)
Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table '%s', key '%s'
 - Error number: [1762](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO](#); SQLSTATE: [23000](#)
Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child table
 - Error number: [1763](#); Symbol: [ER_SQLTHREAD_WITH_SECURE_REPLICA](#); SQLSTATE: [HY000](#)
Message: Setting authentication options is not possible when only the Replica SQL Thread is being started.
 - Error number: [1764](#); Symbol: [ER_TABLE_HAS_NO_FT](#); SQLSTATE: [HY000](#)
Message: The table does not have FULLTEXT index to support this query

-
- Error number: [1765](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER](#); SQLSTATE: [HY000](#)
Message: The system variable %s cannot be set in stored functions or triggers.
 - Error number: [1766](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION](#); SQLSTATE: [HY000](#)
Message: The system variable %s cannot be set when there is an ongoing transaction.
 - Error number: [1769](#); Symbol: [ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION](#); SQLSTATE: [HY000](#)
Message: The statement 'SET %s' cannot invoke a stored function.
 - Error number: [1770](#); Symbol: [ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_NON_NULL](#); SQLSTATE: [HY000](#)
Message: The system variable @@SESSION.GTID_NEXT cannot be 'AUTOMATIC' when @@SESSION.GTID_NEXT_LIST is non-NULL.
 - Error number: [1772](#); Symbol: [ER_MALFORMED_GTID_SET_SPECIFICATION](#); SQLSTATE: [HY000](#)
Message: Malformed GTID set specification '%s'.
 - Error number: [1773](#); Symbol: [ER_MALFORMED_GTID_SET_ENCODING](#); SQLSTATE: [HY000](#)
Message: Malformed GTID set encoding.
 - Error number: [1774](#); Symbol: [ER_MALFORMED_GTID_SPECIFICATION](#); SQLSTATE: [HY000](#)
Message: Malformed GTID specification '%s'.
 - Error number: [1775](#); Symbol: [ER_GNO_EXHAUSTED](#); SQLSTATE: [HY000](#)
Message: Impossible to generate GTID: the integer component reached the maximum value. Restart the server with a new server_uuid.
 - Error number: [1776](#); Symbol: [ER_BAD_REPLICA_AUTO_POSITION](#); SQLSTATE: [HY000](#)
Message: Parameters SOURCE_LOG_FILE, SOURCE_LOG_POS, RELAY_LOG_FILE and RELAY_LOG_POS cannot be set when SOURCE_AUTO_POSITION is active.
 - Error number: [1777](#); Symbol: [ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF](#); SQLSTATE: [HY000](#)
Message: CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 1 cannot be executed because @@GLOBAL.GTID_MODE = OFF.
 - Error number: [1778](#); Symbol: [ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET](#); SQLSTATE: [HY000](#)
Message: Cannot execute statements with implicit commit inside a transaction when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.
 - Error number: [1779](#); Symbol: [ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON](#); SQLSTATE: [HY000](#)
Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.
 - Error number: [1781](#); Symbol: [ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF](#); SQLSTATE: [HY000](#)

Message: @@SESSION.GTID_NEXT cannot be set to UUID:NUMBER when @@GLOBAL.GTID_MODE = OFF.

- Error number: 1782; Symbol: ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON; SQLSTATE: HY000

Message: @@SESSION.GTID_NEXT cannot be set to ANONYMOUS when @@GLOBAL.GTID_MODE = ON.

- Error number: 1783; Symbol: ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF; SQLSTATE: HY000

Message: @@SESSION.GTID_NEXT_LIST cannot be set to a non-NULL value when @@GLOBAL.GTID_MODE = OFF.

- Error number: 1785; Symbol: ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE; SQLSTATE: HY000

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

- Error number: 1786; Symbol: ER_GTID_UNSAFE_CREATE_SELECT; SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

- Error number: 1788; Symbol: ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME; SQLSTATE: HY000

Message: The value of @@GLOBAL.GTID_MODE can only be changed one step at a time: OFF <-> OFF_PERMISSIVE <-> ON_PERMISSIVE <-> ON. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.

- Error number: 1789; Symbol: ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS; SQLSTATE: HY000

Message: Cannot replicate because the source purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new replica from backup. Consider increasing the source's binary log expiration period. %s

- Error number: 1790; Symbol: ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID; SQLSTATE: HY000

Message: @@SESSION.GTID_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.

- Error number: 1791; Symbol: ER_UNKNOWN_EXPLAIN_FORMAT; SQLSTATE: HY000

Message: Unknown EXPLAIN format name: '%s'

- Error number: 1792; Symbol: ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION; SQLSTATE: 25006

Message: Cannot execute statement in a READ ONLY transaction.

- Error number: 1793; Symbol: ER_TOO_LONG_TABLE_PARTITION_COMMENT; SQLSTATE: HY000

Message: Comment for table partition '%s' is too long (max = %lu)

-
- Error number: [1794](#); Symbol: [ER_REPLICA_CONFIGURATION](#); SQLSTATE: [HY000](#)
Message: Replica is not configured or failed to initialize properly. You must at least set --server-id to enable either a source or a replica. Additional error messages can be found in the MySQL error log.
 - Error number: [1795](#); Symbol: [ER_INNO_DB_FT_LIMIT](#); SQLSTATE: [HY000](#)
Message: InnoDB presently supports one FULLTEXT index creation at a time
 - Error number: [1796](#); Symbol: [ER_INNO_DB_NO_FT_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: Cannot create FULLTEXT index on temporary InnoDB table
 - Error number: [1797](#); Symbol: [ER_INNO_DB_FT_WRONG_DOCID_COLUMN](#); SQLSTATE: [HY000](#)
Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index
 - Error number: [1798](#); Symbol: [ER_INNO_DB_FT_WRONG_DOCID_INDEX](#); SQLSTATE: [HY000](#)
Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index
 - Error number: [1799](#); Symbol: [ER_INNO_DB_ONLINE_LOG_TOO_BIG](#); SQLSTATE: [HY000](#)
Message: Creating index '%s' required more than 'innodb_online_alter_log_max_size' bytes of modification log. Please try again.
 - Error number: [1800](#); Symbol: [ER_UNKNOWN_ALTER_ALGORITHM](#); SQLSTATE: [HY000](#)
Message: Unknown ALGORITHM '%s'
 - Error number: [1801](#); Symbol: [ER_UNKNOWN_ALTER_LOCK](#); SQLSTATE: [HY000](#)
Message: Unknown LOCK type '%s'
 - Error number: [1802](#); Symbol: [ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS](#); SQLSTATE: [HY000](#)
Message: CHANGE REPLICATION SOURCE cannot be executed when the replica was stopped with an error or killed in MTA mode. Consider using RESET REPLICATION or START REPLICATION UNTIL.
 - Error number: [1803](#); Symbol: [ER_MTA_RECOVERY_FAILURE](#); SQLSTATE: [HY000](#)
Message: Cannot recover after REPLICATION errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.
 - Error number: [1804](#); Symbol: [ER_MTA_RESET_WORKERS](#); SQLSTATE: [HY000](#)
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.
 - Error number: [1805](#); Symbol: [ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#); SQLSTATE: [HY000](#)
Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted
 - Error number: [1806](#); Symbol: [ER_REPLICA_SILENT_RETRY_TRANSACTION](#); SQLSTATE: [HY000](#)
Message: Replica must silently retry current transaction
 - Error number: [1807](#); Symbol: [ER_DISCARD_FK_CHECKS_RUNNING](#); SQLSTATE: [HY000](#)
Message: There is a foreign key check running on table '%s'. Cannot discard the table.
 - Error number: [1808](#); Symbol: [ER_TABLE_SCHEMA_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Schema mismatch (%s)

- Error number: [1809](#); Symbol: [ER_TABLE_IN_SYSTEM_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Table '%s' in system tablespace

- Error number: [1810](#); Symbol: [ER_IO_READ_ERROR](#); SQLSTATE: [HY000](#)

Message: IO Read error: (%lu, %s) %s

- Error number: [1811](#); Symbol: [ER_IO_WRITE_ERROR](#); SQLSTATE: [HY000](#)

Message: IO Write error: (%lu, %s) %s

- Error number: [1812](#); Symbol: [ER_TABLESPACE_MISSING](#); SQLSTATE: [HY000](#)

Message: Tablespace is missing for table %s.

- Error number: [1813](#); Symbol: [ER_TABLESPACE_EXISTS](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' exists.

- Error number: [1814](#); Symbol: [ER_TABLESPACE_DISCARDED](#); SQLSTATE: [HY000](#)

Message: Tablespace is discarded for table, '%s'

- Error number: [1815](#); Symbol: [ER_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Internal error: %s

- Error number: [1816](#); Symbol: [ER_INNODB_IMPORT_ERROR](#); SQLSTATE: [HY000](#)

Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu : '%s'

- Error number: [1817](#); Symbol: [ER_INNODB_INDEX_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Index corrupt: %s

- Error number: [1818](#); Symbol: [ER_INVALID_YEAR_COLUMN_LENGTH](#); SQLSTATE: [HY000](#)

Message: Invalid display width. Use YEAR instead.

- Error number: [1819](#); Symbol: [ER_NOT_VALID_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Your password does not satisfy the current policy requirements

- Error number: [1820](#); Symbol: [ER_MUST_CHANGE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: You must reset your password using ALTER USER statement before executing this statement.

- Error number: [1821](#); Symbol: [ER_FK_NO_INDEX_CHILD](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign table '%s'

- Error number: [1822](#); Symbol: [ER_FK_NO_INDEX_PARENT](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced table '%s'

- Error number: [1823](#); Symbol: [ER_FK_FAIL_ADD_SYSTEM](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint '%s' to system tables

-
- Error number: [1824](#); Symbol: [ER_FK_CANNOT_OPEN_PARENT](#); SQLSTATE: [HY000](#)
Message: Failed to open the referenced table '%s'
 - Error number: [1825](#); Symbol: [ER_FK_INCORRECT_OPTION](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY constraint '%s'
 - Error number: [1826](#); Symbol: [ER_FK_DUP_NAME](#); SQLSTATE: [HY000](#)
Message: Duplicate foreign key constraint name '%s'
 - Error number: [1827](#); Symbol: [ER_PASSWORD_FORMAT](#); SQLSTATE: [HY000](#)
Message: The password hash doesn't have the expected format.
 - Error number: [1828](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP](#); SQLSTATE: [HY000](#)
Message: Cannot drop column '%s': needed in a foreign key constraint '%s'
 - Error number: [1829](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP_CHILD](#); SQLSTATE: [HY000](#)
Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'
 - Error number: [1830](#); Symbol: [ER_FK_COLUMN_NOT_NULL](#); SQLSTATE: [HY000](#)
Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL
 - Error number: [1831](#); Symbol: [ER_DUP_INDEX](#); SQLSTATE: [HY000](#)
Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be disallowed in a future release.
 - Error number: [1832](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE](#); SQLSTATE: [HY000](#)
Message: Cannot change column '%s': used in a foreign key constraint '%s'
 - Error number: [1833](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE_CHILD](#); SQLSTATE: [HY000](#)
Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'
 - Error number: [1835](#); Symbol: [ER_MALFORMED_PACKET](#); SQLSTATE: [HY000](#)
Message: Malformed communication packet.
 - Error number: [1836](#); Symbol: [ER_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Running in read-only mode
 - Error number: [1837](#); Symbol: [ER_GTID_NEXT_TYPE_UNDEFINED_GTID](#); SQLSTATE: [HY000](#)
Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.
 - Error number: [1838](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_SP](#); SQLSTATE: [HY000](#)
Message: The system variable %s cannot be set in stored procedures.
 - Error number: [1840](#); Symbol: [ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NOT_EMPTY](#); SQLSTATE: [HY000](#)
Message: @@GLOBAL.GTID_PURGED can only be set when @@GLOBAL.GTID_EXECUTED is empty.

-
- Error number: [1841](#); Symbol: [ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NOT_EMPTY](#); SQLSTATE: [HY000](#)
Message: @@GLOBAL.GTID_PURGED can only be set when there are no ongoing transactions (not even in other clients).
 - Error number: [1842](#); Symbol: [ER_GTID_PURGED_WAS_CHANGED](#); SQLSTATE: [HY000](#)
Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.
 - Error number: [1843](#); Symbol: [ER_GTID_EXECUTED_WAS_CHANGED](#); SQLSTATE: [HY000](#)
Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.
 - Error number: [1844](#); Symbol: [ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES](#); SQLSTATE: [HY000](#)
Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT, and both replicated and non replicated tables are written to.
 - Error number: [1845](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)
Message: %s is not supported for this operation. Try %s.
 - Error number: [1846](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON](#); SQLSTATE: [0A000](#)
Message: %s is not supported. Reason: %s. Try %s.
 - Error number: [1847](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY](#); SQLSTATE: [HY000](#)
Message: COPY algorithm requires a lock
 - Error number: [1848](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION](#); SQLSTATE: [HY000](#)
Message: Partition specific operations do not yet support LOCK/ALGORITHM
 - Error number: [1849](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_RENAME](#); SQLSTATE: [HY000](#)
Message: Columns participating in a foreign key are renamed
 - Error number: [1850](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE](#); SQLSTATE: [HY000](#)
Message: Cannot change column type INPLACE
 - Error number: [1851](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK](#); SQLSTATE: [HY000](#)
Message: Adding foreign keys needs foreign_key_checks=OFF
 - Error number: [1853](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK](#); SQLSTATE: [HY000](#)
Message: Dropping a primary key is not allowed without also adding a new primary key
 - Error number: [1854](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOINC](#); SQLSTATE: [HY000](#)
Message: Adding an auto-increment column requires a lock

-
- Error number: [1855](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN_FTS](#); SQLSTATE: [HY000](#)

Message: Cannot replace hidden FTS_DOC_ID with a user-visible one

- Error number: [1856](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE_FTS](#); SQLSTATE: [HY000](#)

Message: Cannot drop or rename FTS_DOC_ID

- Error number: [1857](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS](#); SQLSTATE: [HY000](#)

Message: Fulltext index creation requires a lock

- Error number: [1859](#); Symbol: [ER_DUP_UNKNOWN_IN_INDEX](#); SQLSTATE: [23000](#)

Message: Duplicate entry for key '%s'

- Error number: [1860](#); Symbol: [ER_IDENT_CAUSES_TOO_LONG_PATH](#); SQLSTATE: [HY000](#)

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

- Error number: [1861](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_NULL](#); SQLSTATE: [HY000](#)

Message: cannot silently convert NULL values, as required in this SQL_MODE

- Error number: [1862](#); Symbol: [ER_MUST_CHANGE_PASSWORD_LOGIN](#); SQLSTATE: [HY000](#)

Message: Your password has expired. To log in you must change it using a client that supports expired passwords.

- Error number: [1863](#); Symbol: [ER_ROW_IN_WRONG_PARTITION](#); SQLSTATE: [HY000](#)

Message: Found a row in wrong partition %s

- Error number: [1864](#); Symbol: [ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX](#); SQLSTATE: [HY000](#)

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica_pending_jobs_size_max.

- Error number: [1866](#); Symbol: [ER_BINLOG_LOGICAL_CORRUPTION](#); SQLSTATE: [HY000](#)

Message: The binary log file '%s' is logically corrupted: %s

- Error number: [1867](#); Symbol: [ER_WARN_PURGE_LOG_IN_USE](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.

- Error number: [1868](#); Symbol: [ER_WARN_PURGE_LOG_IS_ACTIVE](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it is the active log file.

- Error number: [1869](#); Symbol: [ER_AUTO_INCREMENT_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Auto-increment value in UPDATE conflicts with internally generated values

-
- Error number: [1870](#); Symbol: [WARN_ON_BLOCKHOLE_IN_RBR](#); SQLSTATE: [HY000](#)
Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format. Table(s): '%s'
 - Error number: [1871](#); Symbol: [ER_REPLICA_CM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)
Message: Replica failed to initialize connection metadata structure from the repository
 - Error number: [1872](#); Symbol: [ER_REPLICA_AM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)
Message: Replica failed to initialize applier metadata structure from the repository
 - Error number: [1873](#); Symbol: [ER_ACCESS_DENIED_CHANGE_USER_ERROR](#); SQLSTATE: [28000](#)
Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.
 - Error number: [1874](#); Symbol: [ER_INNODB_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: InnoDB is in read only mode.
 - Error number: [1875](#); Symbol: [ER_STOP_REPLICA_SQL_THREAD_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.
 - Error number: [1876](#); Symbol: [ER_STOP_REPLICA_IO_THREAD_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.
 - Error number: [1877](#); Symbol: [ER_TABLE_CORRUPT](#); SQLSTATE: [HY000](#)
Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.
 - Error number: [1878](#); Symbol: [ER_TEMP_FILE_WRITE_FAILURE](#); SQLSTATE: [HY000](#)
Message: Temporary file write failure.
 - Error number: [1879](#); Symbol: [ER_INNODB_FT_AUX_NOT_HEX_ID](#); SQLSTATE: [HY000](#)
Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.
 - Error number: [1880](#); Symbol: [ER_OLD_TEMPORALS_UPGRADED](#); SQLSTATE: [HY000](#)
Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.
 - Error number: [1881](#); Symbol: [ER_INNODB_FORCED_RECOVERY](#); SQLSTATE: [HY000](#)
Message: Operation not allowed when innodb_force_recovery > 0.
 - Error number: [1882](#); Symbol: [ER_AES_INVALID_IV](#); SQLSTATE: [HY000](#)
Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long
 - Error number: [1883](#); Symbol: [ER_PLUGIN_CANNOT_BE_UNINSTALLED](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' cannot be uninstalled now. %s
 - Error number: [1884](#); Symbol: [ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_GTID](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.

- Error number: 1885; Symbol: ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE; SQLSTATE: HY000

Message: Replica has more GTIDs than the source has, using the source's SERVER_UUID. This may indicate that the the last binary log file was truncated or lost, e.g., after a power failure when sync_binlog != 1. The source may have rolled back transactions that were already replicated to the replica. Replicate any transactions that source has rolled back from replica to source, and/or commit empty transactions on source to account for transactions that have been committed on source but are not included in GTID_EXECUTED.

- Error number: 1886; Symbol: ER_MISSING_KEY; SQLSTATE: HY000

Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.

- Error number: 1887; Symbol: WARN_NAMED_PIPE_ACCESS_EVERYONE; SQLSTATE: HY000

Message: Setting named_pipe_full_access_group='%s' is insecure. Consider using a Windows group with fewer members.

- Error number: 3000; Symbol: ER_FILE_CORRUPT; SQLSTATE: HY000

Message: File %s is corrupted

- Error number: 3001; Symbol: ER_ERROR_ON_SOURCE; SQLSTATE: HY000

Message: Query partially completed on the source (error on source: %d) and was aborted. There is a chance that your source is inconsistent at this point. If you are sure that your source is ok, run this query manually on the replica and then restart the replica with SET GLOBAL SQL_REPLICA_SKIP_COUNTER=1; START REPLICA;. Query: '%s'

- Error number: 3003; Symbol: ER_STORAGE_ENGINE_NOT_LOADED; SQLSTATE: HY000

Message: Storage engine for table '%s'.'%s' is not loaded.

- Error number: 3004; Symbol: ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER; SQLSTATE: 0Z002

Message: GET STACKED DIAGNOSTICS when handler not active

- Error number: 3005; Symbol: ER_WARN_LEGACY_SYNTAX_CONVERTED; SQLSTATE: HY000

Message: %s is no longer supported. The statement was converted to %s.

- Error number: 3006; Symbol: ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN; SQLSTATE: HY000

Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the replica.

- Error number: 3007; Symbol: ER_CANNOT_DISCARD_TEMPORARY_TABLE; SQLSTATE: HY000

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

- Error number: 3008; Symbol: ER_FK_DEPTH_EXCEEDED; SQLSTATE: HY000

Message: Foreign key cascade delete/update exceeds max depth of %d.

- Error number: 3009; Symbol: ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2; SQLSTATE: HY000

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: [3010](#); Symbol: [ER_WARN_TRIGGER_DOESNT_HAVE_CREATED](#); SQLSTATE: [HY000](#)

Message: Trigger %s.%s.%s does not have CREATED attribute.

- Error number: [3011](#); Symbol: [ER_REFERENCED_TRG_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Referenced trigger '%s' for the given action time and event type does not exist.

- Error number: [3012](#); Symbol: [ER_EXPLAIN_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: EXPLAIN FOR CONNECTION command is supported only for SELECT/UPDATE/INSERT/DELETE/REPLACE

- Error number: [3013](#); Symbol: [ER_INVALID_FIELD_SIZE](#); SQLSTATE: [HY000](#)

Message: Invalid size for column '%s'.

- Error number: [3014](#); Symbol: [ER_MISSING_HA_CREATE_OPTION](#); SQLSTATE: [HY000](#)

Message: Table storage engine '%s' found required create option missing

- Error number: [3015](#); Symbol: [ER_ENGINE_OUT_OF_MEMORY](#); SQLSTATE: [HY000](#)

Message: Out of memory in storage engine '%s'.

- Error number: [3016](#); Symbol: [ER_PASSWORD_EXPIRE_ANONYMOUS_USER](#); SQLSTATE: [HY000](#)

Message: The password for anonymous user cannot be expired.

- Error number: [3017](#); Symbol: [ER_REPLICA_SQL_THREAD_MUST_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL_THREAD first

- Error number: [3018](#); Symbol: [ER_NO_FT_MATERIALIZED_SUBQUERY](#); SQLSTATE: [HY000](#)

Message: Cannot create FULLTEXT index on materialized subquery

- Error number: [3019](#); Symbol: [ER_INNODB_UNDO_LOG_FULL](#); SQLSTATE: [HY000](#)

Message: Undo Log error: %s

- Error number: [3020](#); Symbol: [ER_INVALID_ARGUMENT_FOR_LOGARITHM](#); SQLSTATE: [2201E](#)

Message: Invalid argument for logarithm

- Error number: [3021](#); Symbol: [ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed with a running replica io thread; run STOP REPLICA IO_THREAD FOR CHANNEL '%s' first.

- Error number: [3022](#); Symbol: [ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO](#); SQLSTATE: [HY000](#)

Message: This operation may not be safe when the replica has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until replica_open_temp_tables = 0.

- Error number: [3023](#); Symbol: [ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS](#); SQLSTATE: [HY000](#)

Message: CHANGE REPLICATION SOURCE TO with a SOURCE_LOG_FILE clause but no SOURCE_LOG_POS clause may not be safe. The old position value may not be valid for the new binary log file.

- Error number: 3024; Symbol: ER_QUERY_TIMEOUT; SQLSTATE: HY000

Message: Query execution was interrupted, maximum statement execution time exceeded

- Error number: 3025; Symbol: ER_NON_RO_SELECT_DISABLE_TIMER; SQLSTATE: HY000

Message: Select is not a read only statement, disabling timer

- Error number: 3026; Symbol: ER_DUP_LIST_ENTRY; SQLSTATE: HY000

Message: Duplicate entry '%s'.

- Error number: 3028; Symbol: ER_AGGREGATE_ORDER_FOR_UNION; SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION, EXCEPT or INTERSECT

- Error number: 3029; Symbol: ER_AGGREGATE_ORDER_NON_AGG_QUERY; SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query

- Error number: 3030; Symbol: ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR; SQLSTATE: HY000

Message: Replica worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the replica after fixing any failed threads, you should fix this worker as well.

- Error number: 3032; Symbol: ER_SERVER_OFFLINE_MODE; SQLSTATE: HY000

Message: The server is currently in offline mode

- Error number: 3033; Symbol: ER_GIS_DIFFERENT_SRIDS; SQLSTATE: HY000

Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.

Geometry values passed as arguments to spatial functions must have the same SRID value.

- Error number: 3034; Symbol: ER_GIS_UNSUPPORTED_ARGUMENT; SQLSTATE: HY000

Message: Calling geometry function %s with unsupported types of arguments.

A spatial function was called with a combination of argument types that the function does not support.

- Error number: 3035; Symbol: ER_GIS_UNKNOWN_ERROR; SQLSTATE: HY000

Message: Unknown GIS error occurred in function %s.

- Error number: 3036; Symbol: ER_GIS_UNKNOWN_EXCEPTION; SQLSTATE: HY000

Message: Unknown exception caught in GIS function %s.

- Error number: 3037; Symbol: ER_GIS_INVALID_DATA; SQLSTATE: 22023

Message: Invalid GIS data provided to function %s.

A spatial function was called with an argument not recognized as a valid geometry value.

- Error number: 3038; Symbol: `ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION`; SQLSTATE: `HY000`

Message: The geometry has no data in function %s.

- Error number: 3039; Symbol: `ER_BOOST_GEOMETRY_CENTROID_EXCEPTION`; SQLSTATE: `HY000`

Message: Unable to calculate centroid because geometry is empty in function %s.

- Error number: 3040; Symbol: `ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION`; SQLSTATE: `HY000`

Message: Geometry overlay calculation error: geometry data is invalid in function %s.

- Error number: 3041; Symbol: `ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION`; SQLSTATE: `HY000`

Message: Geometry turn info calculation error: geometry data is invalid in function %s.

- Error number: 3042; Symbol: `ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION`; SQLSTATE: `HY000`

Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.

- Error number: 3043; Symbol: `ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`

Message: Unknown exception thrown in function %s.

- Error number: 3044; Symbol: `ER_STD_BAD_ALLOC_ERROR`; SQLSTATE: `HY000`

Message: Memory allocation error: %s in function %s.

- Error number: 3045; Symbol: `ER_STD_DOMAIN_ERROR`; SQLSTATE: `HY000`

Message: Domain error: %s in function %s.

- Error number: 3046; Symbol: `ER_STD_LENGTH_ERROR`; SQLSTATE: `HY000`

Message: Length error: %s in function %s.

- Error number: 3047; Symbol: `ER_STD_INVALID_ARGUMENT`; SQLSTATE: `HY000`

Message: Invalid argument error: %s in function %s.

- Error number: 3048; Symbol: `ER_STD_OUT_OF_RANGE_ERROR`; SQLSTATE: `HY000`

Message: Out of range error: %s in function %s.

- Error number: 3049; Symbol: `ER_STD_OVERFLOW_ERROR`; SQLSTATE: `HY000`

Message: Overflow error: %s in function %s.

- Error number: 3050; Symbol: `ER_STD_RANGE_ERROR`; SQLSTATE: `HY000`

Message: Range error: %s in function %s.

- Error number: 3051; Symbol: `ER_STD_UNDERFLOW_ERROR`; SQLSTATE: `HY000`

Message: Underflow error: %s in function %s.

- Error number: 3052; Symbol: `ER_STD_LOGIC_ERROR`; SQLSTATE: `HY000`

Message: Logic error: %s in function %s.

- Error number: 3053; Symbol: [ER_STD_RUNTIME_ERROR](#); SQLSTATE: HY000

Message: Runtime error: %s in function %s.

- Error number: 3054; Symbol: [ER_STD_UNKNOWN_EXCEPTION](#); SQLSTATE: HY000

Message: Unknown exception: %s in function %s.

- Error number: 3055; Symbol: [ER_GIS_DATA_WRONG_ENDIANESS](#); SQLSTATE: HY000

Message: Geometry byte string must be little endian.

- Error number: 3056; Symbol: [ER_CHANGE_SOURCE_PASSWORD_LENGTH](#); SQLSTATE: HY000

Message: The password provided for the replication user exceeds the maximum length of 32 characters

- Error number: 3057; Symbol: [ER_USER_LOCK_WRONG_NAME](#); SQLSTATE: 42000

Message: Incorrect user-level lock name '%s'. The name is empty, NULL, or can not be expressed in the current character-set.

- Error number: 3058; Symbol: [ER_USER_LOCK_DEADLOCK](#); SQLSTATE: HY000

Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.

This error is returned when the metadata locking subsystem detects a deadlock for an attempt to acquire a named lock with [GET_LOCK](#).

- Error number: 3059; Symbol: [ER_REPLACE_INACCESSIBLE_ROWS](#); SQLSTATE: HY000

Message: REPLACE cannot be executed as it requires deleting rows that are not in the view

- Error number: 3060; Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS](#); SQLSTATE: HY000

Message: Do not support online operation on table with GIS index

- Error number: 3061; Symbol: [ER_ILLEGAL_USER_VAR](#); SQLSTATE: 42000

Message: User variable name '%s' is illegal

- Error number: 3062; Symbol: [ER_GTID_MODE_OFF](#); SQLSTATE: HY000

Message: Cannot %s when GTID_MODE = OFF.

- Error number: 3064; Symbol: [ER_INCORRECT_TYPE](#); SQLSTATE: HY000

Message: Incorrect type for argument %s in function %s.

- Error number: 3065; Symbol: [ER_FIELD_IN_ORDER_NOT_SELECT](#); SQLSTATE: HY000

Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s

- Error number: 3066; Symbol: [ERAggregate_IN_ORDER_NOT_SELECT](#); SQLSTATE: HY000

Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s

-
- Error number: 3067; Symbol: `ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN`; SQLSTATE: `HY000`
Message: Supplied filter list contains a value which is not in the required format 'db_pattern.table_pattern'
 - Error number: 3068; Symbol: `ER_NET_OK_PACKET_TOO_LARGE`; SQLSTATE: `08S01`
Message: OK packet too large
 - Error number: 3069; Symbol: `ER_INVALID_JSON_DATA`; SQLSTATE: `HY000`
Message: Invalid JSON data provided to function %s: %s
 - Error number: 3070; Symbol: `ER_INVALID_GEOJSON_MISSING_MEMBER`; SQLSTATE: `HY000`
Message: Invalid GeoJSON data provided to function %s: Missing required member %s'
 - Error number: 3071; Symbol: `ER_INVALID_GEOJSON_WRONG_TYPE`; SQLSTATE: `HY000`
Message: Invalid GeoJSON data provided to function %s: Member %s' must be of type %s'
 - Error number: 3072; Symbol: `ER_INVALID_GEOJSON_UNSPECIFIED`; SQLSTATE: `HY000`
Message: Invalid GeoJSON data provided to function %s
 - Error number: 3073; Symbol: `ER_DIMENSION_UNSUPPORTED`; SQLSTATE: `HY000`
Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u
 - Error number: 3074; Symbol: `ER_REPLICA_CHANNEL_DOES_NOT_EXIST`; SQLSTATE: `HY000`
Message: Replica channel %s' does not exist.
 - Error number: 3076; Symbol: `ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG`; SQLSTATE: `HY000`
Message: Couldn't create channel: Channel name is either invalid or too long.
 - Error number: 3077; Symbol: `ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY`; SQLSTATE: `HY000`
Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.
 - Error number: 3079; Symbol: `ER_REPLICA_MULTIPLE_CHANNELS_CMD`; SQLSTATE: `HY000`
Message: Multiple channels exist on the replica. Please provide channel name as an argument.
 - Error number: 3080; Symbol: `ER_REPLICA_MAX_CHANNELS_EXCEEDED`; SQLSTATE: `HY000`
Message: Maximum number of replication channels allowed exceeded.
 - Error number: 3081; Symbol: `ER_REPLICA_CHANNEL_MUST_STOP`; SQLSTATE: `HY000`
Message: This operation cannot be performed with running replication threads; run STOP REPLICA FOR CHANNEL %s' first
 - Error number: 3082; Symbol: `ER_REPLICA_CHANNEL_NOT_RUNNING`; SQLSTATE: `HY000`
Message: This operation requires running replication threads; configure replica and run START REPLICA FOR CHANNEL %s'
 - Error number: 3083; Symbol: `ER_REPLICA_CHANNEL_WAS_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already running.

- Error number: 3084; Symbol: `ER_REPLICA_CHANNEL_WAS_NOT_RUNNING`; SQLSTATE: HY000

Message: Replication thread(s) for channel '%s' are already stopped.

- Error number: 3085; Symbol: `ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP`; SQLSTATE: HY000

Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL_THREAD FOR CHANNEL '%s' first.

- Error number: 3086; Symbol: `ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER`; SQLSTATE: HY000

Message: When sql_replica_skip_counter > 0, it is not allowed to start more than one SQL thread by using 'START REPLICA [SQL_THREAD]'. Value of sql_replica_skip_counter can only be used by one SQL thread at a time. Please use 'START REPLICA [SQL_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql_replica_skip_counter.

- Error number: 3087; Symbol: `ER_WRONG_FIELD_WITH_GROUP_V2`; SQLSTATE: HY000

Message: Expression #%u of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with sql_mode=only_full_group_by

- Error number: 3088; Symbol: `ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2`; SQLSTATE: HY000

Message: In aggregated query without GROUP BY, expression #%u of %s contains nonaggregated column '%s'; this is incompatible with sql_mode=only_full_group_by

- Error number: 3089; Symbol: `ER_WARN_DEPRECATED_SYSVAR_UPDATE`; SQLSTATE: HY000

Message: Updating '%s' is deprecated. It will be made read-only in a future release.

- Error number: 3090; Symbol: `ER_WARN_DEPRECATED_SQLMODE`; SQLSTATE: HY000

Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.

- Error number: 3091; Symbol: `ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID`; SQLSTATE: HY000

Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to GTID_EXECUTED and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET GTID_NEXT='%s'; (3) DROP DATABASE '%s'.

- Error number: 3092; Symbol: `ER_GROUP_REPLICATION_CONFIGURATION`; SQLSTATE: HY000

Message: The server is not configured properly to be an active member of the group. Please see more details on error log.

- Error number: 3093; Symbol: `ER_GROUP_REPLICATION_RUNNING`; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the group is already running.

- Error number: 3094; Symbol: `ER_GROUP_REPLICATION_APPLIER_INIT_ERROR`; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed as the applier module failed to start.

- Error number: 3095; Symbol: `ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT`; SQLSTATE: HY000

Message: The STOP GROUP_REPLICATION command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.

- Error number: 3096; Symbol: [ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR](#); SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed as there was an error when initializing the group communication layer.

- Error number: 3097; Symbol: [ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR](#); SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed as there was an error when joining the communication group.

- Error number: 3098; Symbol: [ER_BEFORE_DML_VALIDATION_ERROR](#); SQLSTATE: HY000

Message: The table does not comply with the requirements by an external plugin.

- Error number: 3099; Symbol: [ER_PREVENTS_VARIABLE_WITHOUT_RBR](#); SQLSTATE: HY000

Message: Cannot change the value of variable %s without binary log format as ROW.

- Error number: 3100; Symbol: [ER_RUN_HOOK_ERROR](#); SQLSTATE: HY000

Message: Error on observer while running replication hook '%s'.

- Error number: 3101; Symbol: [ER_TRANSACTION_ROLLBACK_DURING_COMMIT](#); SQLSTATE: 40000

Message: Plugin instructed the server to rollback the current transaction.

When using Group Replication, this means that a transaction failed the group certification process, due to one or more members detecting a potential conflict, and was thus rolled back. See [Group Replication](#).

- Error number: 3102; Symbol: [ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000

Message: Expression of generated column '%s' contains a disallowed function.

- Error number: 3103; Symbol: [ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN](#); SQLSTATE: HY000

Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions

- Error number: 3104; Symbol: [ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN](#); SQLSTATE: HY000

Message: Cannot define foreign key with %s clause on a generated column.

- Error number: 3105; Symbol: [ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN](#); SQLSTATE: HY000

Message: The value specified for generated column '%s' in table '%s' is not allowed.

- Error number: 3106; Symbol: [ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN](#); SQLSTATE: HY000

Message: '%s' is not supported for generated columns.

- Error number: 3107; Symbol: [ER_GENERATED_COLUMN_NON_PRIOR](#); SQLSTATE: HY000

Message: Generated column can refer only to generated columns defined prior to it.

To address this issue, change the table definition to define each generated column later than any generated columns to which it refers.

- Error number: [3108](#); Symbol: [ER_DEPENDENT_BY_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' has a generated column dependency.

You cannot drop or rename a generated column if another column refers to it. You must either drop those columns as well, or redefine them not to refer to the generated column.

- Error number: [3109](#); Symbol: [ER_GENERATED_COLUMN_REF_AUTO_INC](#); SQLSTATE: [HY000](#)

Message: Generated column '%s' cannot refer to auto-increment column.

- Error number: [3110](#); Symbol: [ER_FEATURE_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'

- Error number: [3111](#); Symbol: [ER_CANT_SET_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: SET @@GLOBAL.GTID_MODE = %s is not allowed because %s.

- Error number: [3112](#); Symbol: [ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: The replication receiver thread%s cannot start in AUTO_POSITION mode: this server uses @@GLOBAL.GTID_MODE = OFF.

- Error number: [3116](#); Symbol: [ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX](#); SQLSTATE: [HY000](#)

Message: Cannot set ENFORCE_GTID_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.

[ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS](#) was renamed to [ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX](#).

- Error number: [3117](#); Symbol: [ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX](#); SQLSTATE: [HY000](#)

Message: There are ongoing transactions that violate GTID consistency.

[ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS](#) was renamed to [ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX](#).

- Error number: [3118](#); Symbol: [ER_ACCOUNT_HAS_BEEN_LOCKED](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is locked.

The account was locked with [CREATE USER ... ACCOUNT LOCK](#) or [ALTER USER ... ACCOUNT LOCK](#). An administrator can unlock it with [ALTER USER ... ACCOUNT UNLOCK](#).

- Error number: [3119](#); Symbol: [ER_WRONG_TABLESPACE_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect tablespace name `'%s`

-
- Error number: [3120](#); Symbol: [ER_TABLESPACE_IS_NOT_EMPTY](#); SQLSTATE: [HY000](#)
Message: Tablespace '%s' is not empty.
 - Error number: [3121](#); Symbol: [ER_WRONG_FILE_NAME](#); SQLSTATE: [HY000](#)
Message: Incorrect File Name '%s'.
 - Error number: [3122](#); Symbol: [ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION](#); SQLSTATE: [HY000](#)
Message: Inconsistent intersection points.
 - Error number: [3123](#); Symbol: [ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR](#); SQLSTATE: [HY000](#)
Message: Optimizer hint syntax error
 - Error number: [3124](#); Symbol: [ER_WARN_BAD_MAX_EXECUTION_TIME](#); SQLSTATE: [HY000](#)
Message: Unsupported MAX_EXECUTION_TIME
 - Error number: [3125](#); Symbol: [ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME](#); SQLSTATE: [HY000](#)
Message: MAX_EXECUTION_TIME hint is supported by top-level standalone SELECT statements only
The [MAX_EXECUTION_TIME](#) optimizer hint is supported only for [SELECT](#) statements.
 - Error number: [3126](#); Symbol: [ER_WARN_CONFLICTING_HINT](#); SQLSTATE: [HY000](#)
Message: Hint %s is ignored as conflicting/duplicated
 - Error number: [3127](#); Symbol: [ER_WARN_UNKNOWN_QB_NAME](#); SQLSTATE: [HY000](#)
Message: Query block name %s is not found for %s hint
 - Error number: [3128](#); Symbol: [ER_UNRESOLVED_HINT_NAME](#); SQLSTATE: [HY000](#)
Message: Unresolved name %s for %s hint
 - Error number: [3129](#); Symbol: [ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE](#); SQLSTATE: [HY000](#)
Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for committed transactions. Modifying it can lead to an inconsistent GTID state.
 - Error number: [3130](#); Symbol: [ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Command not supported by pluggable protocols
 - Error number: [3131](#); Symbol: [ER_LOCKING_SERVICE_WRONG_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect locking service lock name '%s'.
A locking service name was specified as [NULL](#), the empty string, or a string longer than 64 characters. Namespace and lock names must be non-[NULL](#), nonempty, and no more than 64 characters long.
 - Error number: [3132](#); Symbol: [ER_LOCKING_SERVICE_DEADLOCK](#); SQLSTATE: [HY000](#)
Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting lock acquisition.

-
- Error number: [3133](#); Symbol: [ER_LOCKING_SERVICE_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: Service lock wait timeout exceeded.
 - Error number: [3134](#); Symbol: [ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED](#); SQLSTATE: [HY000](#)
Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.
 - Error number: [3135](#); Symbol: [ER_SQL_MODE_MERGED](#); SQLSTATE: [HY000](#)
Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.
 - Error number: [3138](#); Symbol: [ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID](#); SQLSTATE: [HY000](#)
Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
 - Error number: [3139](#); Symbol: [ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: %s cannot be performed on channel '%s'.
 - Error number: [3140](#); Symbol: [ER_INVALID_JSON_TEXT](#); SQLSTATE: [22032](#)
Message: Invalid JSON text: "%s" at position %u in value for column '%s'.
 - Error number: [3141](#); Symbol: [ER_INVALID_JSON_TEXT_IN_PARAM](#); SQLSTATE: [22032](#)
Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s
 - Error number: [3142](#); Symbol: [ER_INVALID_JSON_BINARY_DATA](#); SQLSTATE: [HY000](#)
Message: The JSON binary value contains invalid data.
 - Error number: [3143](#); Symbol: [ER_INVALID_JSON_PATH](#); SQLSTATE: [42000](#)
Message: Invalid JSON path expression. The error is around character position %u.%s
 - Error number: [3144](#); Symbol: [ER_INVALID_JSON_CHARSET](#); SQLSTATE: [22032](#)
Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.
 - Error number: [3145](#); Symbol: [ER_INVALID_JSON_CHARSET_IN_FUNCTION](#); SQLSTATE: [22032](#)
Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.
 - Error number: [3146](#); Symbol: [ER_INVALID_TYPE_FOR_JSON](#); SQLSTATE: [22032](#)
Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.
 - Error number: [3147](#); Symbol: [ER_INVALID_CAST_TO_JSON](#); SQLSTATE: [22032](#)
Message: Cannot CAST value to JSON.
 - Error number: [3148](#); Symbol: [ER_INVALID_JSON_PATH_CHARSET](#); SQLSTATE: [42000](#)
Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.
 - Error number: [3149](#); Symbol: [ER_INVALID_JSON_PATH_WILDCARD](#); SQLSTATE: [42000](#)

Message: In this situation, path expressions may not contain the * and ** tokens or an array range.

- Error number: 3150; Symbol: [ER_JSON_VALUE_TOO_BIG](#); SQLSTATE: 22032

Message: The JSON value is too big to be stored in a JSON column.

- Error number: 3151; Symbol: [ER_JSON_KEY_TOO_BIG](#); SQLSTATE: 22032

Message: The JSON object contains a key name that is too long.

- Error number: 3152; Symbol: [ER_JSON_USED_AS_KEY](#); SQLSTATE: 42000

Message: JSON column '%s' supports indexing only via generated columns on a specified JSON path.

- Error number: 3153; Symbol: [ER_JSON_VACUOUS_PATH](#); SQLSTATE: 42000

Message: The path expression '\$' is not allowed in this context.

- Error number: 3154; Symbol: [ER_JSON_BAD_ONE_OR_ALL_ARG](#); SQLSTATE: 42000

Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.

- Error number: 3155; Symbol: [ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE](#); SQLSTATE: 22003

Message: Out of range JSON value for CAST to %s%s from column %s at row %ld

- Error number: 3156; Symbol: [ER_INVALID_JSON_VALUE_FOR_CAST](#); SQLSTATE: 22018

Message: Invalid JSON value for CAST to %s%s from column %s at row %ld

- Error number: 3157; Symbol: [ER_JSON_DOCUMENT_TOO_DEEP](#); SQLSTATE: 22032

Message: The JSON document exceeds the maximum depth.

- Error number: 3158; Symbol: [ER_JSON_DOCUMENT_NULL_KEY](#); SQLSTATE: 22032

Message: JSON documents may not contain NULL member names.

- Error number: 3159; Symbol: [ER_SECURE_TRANSPORT_REQUIRED](#); SQLSTATE: HY000

Message: Connections using insecure transport are prohibited while --require_secure_transport=ON.

With the [require_secure_transport](#) system variable, clients can connect only using secure transports. Qualifying connections are those using SSL, a Unix socket file, or shared memory.

- Error number: 3160; Symbol: [ER_NO_SECURE_TRANSPORTS_CONFIGURED](#); SQLSTATE: HY000

Message: No secure transports (SSL or Shared Memory) are configured, unable to set --require_secure_transport=ON.

The [require_secure_transport](#) system variable cannot be enabled if the server does not support at least one secure transport. Configure the server with the required SSL keys/certificates to enable SSL connections, or enable the [shared_memory](#) system variable to enable shared-memory connections.

- Error number: 3161; Symbol: [ER_DISABLED_STORAGE_ENGINE](#); SQLSTATE: HY000

Message: Storage engine %s is disabled (Table creation is disallowed).

An attempt was made to create a table or tablespace using a storage engine listed in the value of the [disabled_storage_engines](#) system variable, or to change an existing table or tablespace to such an engine. Choose a different storage engine.

-
- Error number: [3162](#); Symbol: [ER_USER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)
Message: Authorization ID %s does not exist.
 - Error number: [3163](#); Symbol: [ER_USER_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)
Message: Authorization ID %s already exists.
 - Error number: [3164](#); Symbol: [ER_AUDIT_API_ABORT](#); SQLSTATE: [HY000](#)
Message: Aborted by Audit API ('%s';%d).

This error indicates that an audit plugin terminated execution of an event. The message typically indicates the event subclass name and a numeric status value.
 - Error number: [3165](#); Symbol: [ER_INVALID_JSON_PATH_ARRAY_CELL](#); SQLSTATE: [42000](#)
Message: A path expression is not a path to a cell in an array.
 - Error number: [3166](#); Symbol: [ER_BUFPOOL_RESIZE_INPROGRESS](#); SQLSTATE: [HY000](#)
Message: Another buffer pool resize is already in progress.
 - Error number: [3167](#); Symbol: [ER_FEATURE_DISABLED_SEE_DOC](#); SQLSTATE: [HY000](#)
Message: The '%s' feature is disabled; see the documentation for '%s'
 - Error number: [3168](#); Symbol: [ER_SERVER_ISNT_AVAILABLE](#); SQLSTATE: [HY000](#)
Message: Server isn't available
 - Error number: [3169](#); Symbol: [ER_SESSION_WAS_KILLED](#); SQLSTATE: [HY000](#)
Message: Session was killed
 - Error number: [3170](#); Symbol: [ER_CAPACITY_EXCEEDED](#); SQLSTATE: [HY000](#)
Message: Memory capacity of %llu bytes for '%s' exceeded. %s
 - Error number: [3171](#); Symbol: [ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER](#); SQLSTATE: [HY000](#)
Message: Range optimization was not done for this query.
 - Error number: [3173](#); Symbol: [ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_A_GTID](#); SQLSTATE: [HY000](#)
Message: The client holds ownership of the GTID %s. Therefore, WAIT_FOR_EXECUTED_GTID_SET cannot wait for this GTID.
 - Error number: [3174](#); Symbol: [ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL](#); SQLSTATE: [HY000](#)
Message: Cannot add foreign key on the base column of indexed virtual column.
 - Error number: [3175](#); Symbol: [ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT](#); SQLSTATE: [HY000](#)
Message: Cannot create index on virtual column whose base column has foreign constraint.

-
- Error number: [3176](#); Symbol: [ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE](#); SQLSTATE: [HY000](#)

Message: Please do not modify the %s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.
 - Error number: [3177](#); Symbol: [ER_LOCK_REFUSED_BY_ENGINE](#); SQLSTATE: [HY000](#)

Message: Lock acquisition refused by storage engine.
 - Error number: [3178](#); Symbol: [ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN](#); SQLSTATE: [HY000](#)

Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)
 - Error number: [3179](#); Symbol: [ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE](#); SQLSTATE: [HY000](#)

Message: Master key rotation is not supported by storage engine.
 - Error number: [3181](#); Symbol: [ER_MASTER_KEY_ROTATION_BINLOG_FAILED](#); SQLSTATE: [HY000](#)

Message: Write to binlog failed. However, master key rotation has been completed successfully.
 - Error number: [3182](#); Symbol: [ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE](#); SQLSTATE: [HY000](#)

Message: Storage engine is not available.
 - Error number: [3183](#); Symbol: [ER_TABLESPACE_CANNOT_ENCRYPT](#); SQLSTATE: [HY000](#)

Message: This tablespace can't be encrypted.
 - Error number: [3184](#); Symbol: [ER_INVALID_ENCRYPTION_OPTION](#); SQLSTATE: [HY000](#)

Message: Invalid encryption option.
 - Error number: [3185](#); Symbol: [ER_CANNOT_FIND_KEY_IN_KEYRING](#); SQLSTATE: [HY000](#)

Message: Can't find master key from keyring, please check in the server log if a keyring is loaded and initialized successfully.
 - Error number: [3186](#); Symbol: [ER_CAPACITY_EXCEEDED_IN_PARSER](#); SQLSTATE: [HY000](#)

Message: Parser bailed out for this query.
 - Error number: [3187](#); Symbol: [ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE](#); SQLSTATE: [HY000](#)

Message: Cannot alter encryption attribute by inplace algorithm.
 - Error number: [3188](#); Symbol: [ER_KEYRING_UDF_KEYRING_SERVICE_ERROR](#); SQLSTATE: [HY000](#)

Message: Function '%s' failed because underlying keyring service returned an error. Please check if a keyring is installed and that provided arguments are valid for the keyring you are using.
 - Error number: [3189](#); Symbol: [ER_USER_COLUMN_OLD_LENGTH](#); SQLSTATE: [HY000](#)

Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93 characters long. Please perform the MySQL upgrade procedure.
 - Error number: [3190](#); Symbol: [ER_CANT_RESET_SOURCE](#); SQLSTATE: [HY000](#)

Message: RESET BINARY LOGS AND GTIDS is not allowed because %s.

- Error number: 3191; Symbol: ER_GROUP_REPLICATION_MAX_GROUP_SIZE; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the group already has 9 members.

- Error number: 3192; Symbol: ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED; SQLSTATE: HY000

Message: Cannot add foreign key on the base column of stored column.

- Error number: 3193; Symbol: ER_TABLE_REFERENCED; SQLSTATE: HY000

Message: Cannot complete the operation because table is referenced by another connection.

- Error number: 3197; Symbol: ER_XA_RETRY; SQLSTATE: HY000

Message: The resource manager is not able to commit the transaction branch at this time. Please retry later.

- Error number: 3198; Symbol: ER_KEYRING_AWS_UDF_AWS_KMS_ERROR; SQLSTATE: HY000

Message: Function %s failed due to: %s.

- Error number: 3199; Symbol: ER_BINLOG_UNSAFE_XA; SQLSTATE: HY000

Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA transactions may deadlock on replicas when replicated using statements.

- Error number: 3200; Symbol: ER_UDF_ERROR; SQLSTATE: HY000

Message: %s UDF failed; %s

- Error number: 3201; Symbol: ER_KEYRING_MIGRATION_FAILURE; SQLSTATE: HY000

Message: Can not perform keyring migration : %s

- Error number: 3202; Symbol: ER_KEYRING_ACCESS_DENIED_ERROR; SQLSTATE: 42000

Message: Access denied; you need %s privileges for this operation

- Error number: 3203; Symbol: ER_KEYRING_MIGRATION_STATUS; SQLSTATE: HY000

Message: Keyring migration %s.

- Error number: 3218; Symbol: ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE; SQLSTATE: HY000

Message: Invalid "max_array_length" argument value.

- Error number: 3231; Symbol: ER_WRITE_SET_EXCEEDS_LIMIT; SQLSTATE: HY000

Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group_replication_transaction_size_limit'.

- Error number: 3235; Symbol: ER_AES_INVALID_KDF_NAME; SQLSTATE: HY000

Message: KDF method name is not valid. Please use hkdf or pbkdf2_hmac method name

- Error number: 3236; Symbol: ER_AES_INVALID_KDF_ITERATIONS; SQLSTATE: HY000

Message: For KDF method pbkdf2_hmac iterations value less than 1000 or more than 65535 is not allowed due to security reasons. Please provide iterations >= 1000 and iterations < 65535

-
- Error number: [3237](#); Symbol: [WARN_AES_KEY_SIZE](#); SQLSTATE: [HY000](#)
Message: AES key size should be %d bytes length or secure KDF methods hkdf or pbkdf2_hmac should be used, please provide exact AES key size or use KDF methods for better security.
 - Error number: [3238](#); Symbol: [ER_AES_INVALID_KDF_OPTION_SIZE](#); SQLSTATE: [HY000](#)
Message: KDF option size is invalid, please provide valid size < %d bytes and not NULL
 - Error number: [3500](#); Symbol: [ER_UNSUPPORT_COMPRESSED_TEMPORARY_TABLE](#); SQLSTATE: [HY000](#)
Message: CREATE TEMPORARY TABLE is not allowed with ROW_FORMAT=COMPRESSED or KEY_BLOCK_SIZE.
 - Error number: [3501](#); Symbol: [ER_ACL_OPERATION_FAILED](#); SQLSTATE: [HY000](#)
Message: The ACL operation failed due to the following error from SE: errcode %d - %s
 - Error number: [3502](#); Symbol: [ER_UNSUPPORTED_INDEX_ALGORITHM](#); SQLSTATE: [HY000](#)
Message: This storage engine does not support the %s index algorithm, storage engine default was used instead.
 - Error number: [3503](#); Symbol: [ER_NO_SUCH_DB](#); SQLSTATE: [42Y07](#)
Message: Database '%s' doesn't exist
 - Error number: [3504](#); Symbol: [ER_TOO_BIG_ENUM](#); SQLSTATE: [HY000](#)
Message: Too many enumeration values for column %s.
 - Error number: [3505](#); Symbol: [ER_TOO_LONG_SET_ENUM_VALUE](#); SQLSTATE: [HY000](#)
Message: Too long enumeration/set value for column %s.
 - Error number: [3506](#); Symbol: [ER_INVALID_DD_OBJECT](#); SQLSTATE: [HY000](#)
Message: %s dictionary object is invalid. (%s)
 - Error number: [3507](#); Symbol: [ER_UPDATING_DD_TABLE](#); SQLSTATE: [HY000](#)
Message: Failed to update %s dictionary object.
 - Error number: [3508](#); Symbol: [ER_INVALID_DD_OBJECT_ID](#); SQLSTATE: [HY000](#)
Message: Dictionary object id (%lu) does not exist.
 - Error number: [3509](#); Symbol: [ER_INVALID_DD_OBJECT_NAME](#); SQLSTATE: [HY000](#)
Message: Dictionary object name '%s' is invalid. (%s)
 - Error number: [3510](#); Symbol: [ER_TABLESPACE_MISSING_WITH_NAME](#); SQLSTATE: [HY000](#)
Message: Tablespace %s doesn't exist.
 - Error number: [3511](#); Symbol: [ER_TOO_LONG_ROUTINE_COMMENT](#); SQLSTATE: [HY000](#)
Message: Comment for routine '%s' is too long (max = %lu)
 - Error number: [3512](#); Symbol: [ER_SP_LOAD_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to load routine '%s'.

-
- Error number: [3513](#); Symbol: [ER_INVALID_BITWISE_OPERANDS_SIZE](#); SQLSTATE: [HY000](#)
Message: Binary operands of bitwise operators must be of equal length
 - Error number: [3514](#); Symbol: [ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE](#); SQLSTATE: [HY000](#)
Message: Aggregate bitwise functions cannot accept arguments longer than 511 bytes; consider using the SUBSTRING() function
 - Error number: [3515](#); Symbol: [ER_WARN_UNSUPPORTED_HINT](#); SQLSTATE: [HY000](#)
Message: Hints aren't supported in %s
 - Error number: [3516](#); Symbol: [ER_UNEXPECTED_GEOMETRY_TYPE](#); SQLSTATE: [22S01](#)
Message: %s value is a geometry of unexpected type %s in %s.
 - Error number: [3517](#); Symbol: [ER_SRS_PARSE_ERROR](#); SQLSTATE: [SR002](#)
Message: Can't parse the spatial reference system definition of SRID %u.
 - Error number: [3518](#); Symbol: [ER_SRS_PROJ_PARAMETER_MISSING](#); SQLSTATE: [SR003](#)
Message: The spatial reference system definition for SRID %u does not specify the mandatory %s (EPSG %u) projection parameter.
 - Error number: [3519](#); Symbol: [ER_WARN_SRS_NOT_FOUND](#); SQLSTATE: [01000](#)
Message: There's no spatial reference system with SRID %u.
 - Error number: [3520](#); Symbol: [ER_SRS_NOT_CARTESIAN](#); SQLSTATE: [22S00](#)
Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which is not Cartesian.
 - Error number: [3521](#); Symbol: [ER_SRS_NOT_CARTESIAN_UNDEFINED](#); SQLSTATE: [SR001](#)
Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which has not been defined.
 - Error number: [3522](#); Symbol: [ER_PK_INDEX_CANT_BE_INVISIBLE](#); SQLSTATE: [HY000](#)
Message: A primary key index cannot be invisible
 - Error number: [3523](#); Symbol: [ER_UNKNOWN_AUTHID](#); SQLSTATE: [HY000](#)
Message: Unknown authorization ID `%s`@`%s`
 - Error number: [3524](#); Symbol: [ER_FAILED_ROLE_GRANT](#); SQLSTATE: [HY000](#)
Message: Failed to grant %s` to %s
 - Error number: [3525](#); Symbol: [ER_OPEN_ROLE_TABLES](#); SQLSTATE: [HY000](#)
Message: Failed to open the security system tables
 - Error number: [3526](#); Symbol: [ER_FAILED_DEFAULT_ROLES](#); SQLSTATE: [HY000](#)
Message: Failed to set default roles
 - Error number: [3527](#); Symbol: [ER_COMPONENTS_NO_SCHEME](#); SQLSTATE: [HY000](#)
Message: Cannot find schema in specified URN: '%s'.

-
- Error number: [3528](#); Symbol: [ER_COMPONENTS_NO_SCHEME_SERVICE](#); SQLSTATE: [HY000](#)
Message: Cannot acquire scheme load service implementation for schema '%s' in specified URN: '%s'.
 - Error number: [3529](#); Symbol: [ER_COMPONENTS_CANT_LOAD](#); SQLSTATE: [HY000](#)
Message: Cannot load component from specified URN: '%s'.
 - Error number: [3530](#); Symbol: [ER_ROLE_NOT_GRANTED](#); SQLSTATE: [HY000](#)
Message: '%s`@`%s`' is not granted to '%s`@`%s`'
 - Error number: [3531](#); Symbol: [ER_FAILED_REVOKE_ROLE](#); SQLSTATE: [HY000](#)
Message: Could not revoke role from '%s`@`%s`'
 - Error number: [3532](#); Symbol: [ER_RENAME_ROLE](#); SQLSTATE: [HY000](#)
Message: Renaming of a role identifier is forbidden
 - Error number: [3533](#); Symbol: [ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION](#); SQLSTATE: [HY000](#)
Message: Cannot acquire specified service implementation: '%s'.
 - Error number: [3534](#); Symbol: [ER_COMPONENTS_CANT_SATISFY_DEPENDENCY](#); SQLSTATE: [HY000](#)
Message: Cannot satisfy dependency for service '%s' required by component '%s'.
 - Error number: [3535](#); Symbol: [ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION](#); SQLSTATE: [HY000](#)
Message: Cannot register service implementation '%s' provided by component '%s'.
 - Error number: [3536](#); Symbol: [ER_COMPONENTS_LOAD_CANT_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: Initialization method provided by component '%s' failed.
 - Error number: [3537](#); Symbol: [ER_COMPONENTS_UNLOAD_NOT_LOADED](#); SQLSTATE: [HY000](#)
Message: Component specified by URN '%s' to unload has not been loaded before.
 - Error number: [3538](#); Symbol: [ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE](#); SQLSTATE: [HY000](#)
Message: De-initialization method provided by component '%s' failed.
 - Error number: [3539](#); Symbol: [ER_COMPONENTS_CANT_RELEASE_SERVICE](#); SQLSTATE: [HY000](#)
Message: Release of previously acquired service implementation failed.
 - Error number: [3540](#); Symbol: [ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE](#); SQLSTATE: [HY000](#)
Message: Unregistration of service implementation '%s' provided by component '%s' failed during unloading of the component.
 - Error number: [3541](#); Symbol: [ER_COMPONENTS_CANT_UNLOAD](#); SQLSTATE: [HY000](#)
Message: Cannot unload component from specified URN: '%s'.
 - Error number: [3542](#); Symbol: [ER_WARN_UNLOAD_THE_NOT_PERSISTED](#); SQLSTATE: [HY000](#)

Message: The Persistent Dynamic Loader was used to unload a component '%s', but it was not used to load that component before.

- Error number: 3543; Symbol: `ER_COMPONENT_TABLE_INCORRECT`; SQLSTATE: `HY000`

Message: The mysql.component table is missing or has an incorrect definition.

- Error number: 3544; Symbol: `ER_COMPONENT_MANIPULATE_ROW_FAILED`; SQLSTATE: `HY000`

Message: Failed to manipulate component '%s' persistence data. Error code %d from storage engine.

- Error number: 3545; Symbol: `ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP`; SQLSTATE: `HY000`

Message: The component with specified URN: '%s' was specified in group more than once.

- Error number: 3546; Symbol: `ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS`; SQLSTATE: `HY000`

Message: @@GLOBAL.GTID_PURGED cannot be changed: %s

- Error number: 3547; Symbol: `ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES`; SQLSTATE: `HY000`

Message: Can not lock user management caches for processing.

- Error number: 3548; Symbol: `ER_SRS_NOT_FOUND`; SQLSTATE: `SR001`

Message: There's no spatial reference system with SRID %u.

- Error number: 3549; Symbol: `ER_VARIABLE_NOT_PERSISTED`; SQLSTATE: `HY000`

Message: Variables cannot be persisted. Please retry.

- Error number: 3550; Symbol: `ER_IS_QUERY_INVALID_CLAUSE`; SQLSTATE: `HY000`

Message: Information schema queries do not support the '%s' clause.

- Error number: 3551; Symbol: `ER_UNABLE_TO_STORE_STATISTICS`; SQLSTATE: `HY000`

Message: Unable to store dynamic %s statistics into data dictionary.

- Error number: 3552; Symbol: `ER_NO_SYSTEM_SCHEMA_ACCESS`; SQLSTATE: `HY000`

Message: Access to system schema '%s' is rejected.

- Error number: 3553; Symbol: `ER_NO_SYSTEM_TABLESPACE_ACCESS`; SQLSTATE: `HY000`

Message: Access to system tablespace '%s' is rejected.

- Error number: 3554; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS`; SQLSTATE: `HY000`

Message: Access to %s '%s.%s' is rejected.

- Error number: 3555; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE`; SQLSTATE: `HY000`

Message: data dictionary table

- Error number: 3556; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE`; SQLSTATE: `HY000`

Message: system table

-
- Error number: [3557](#); Symbol: [ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE](#); SQLSTATE: [HY000](#)
Message: table
 - Error number: [3558](#); Symbol: [ER_INVALID_OPTION_KEY](#); SQLSTATE: [22023](#)
Message: Invalid option key '%s' in function %s.
 - Error number: [3559](#); Symbol: [ER_INVALID_OPTION_VALUE](#); SQLSTATE: [22023](#)
Message: Invalid value '%s' for option '%s' in function '%s'.
 - Error number: [3560](#); Symbol: [ER_INVALID_OPTION_KEY_VALUE_PAIR](#); SQLSTATE: [22023](#)
Message: The string '%s' is not a valid key %c value pair in function %s.
 - Error number: [3561](#); Symbol: [ER_INVALID_OPTION_START_CHARACTER](#); SQLSTATE: [22023](#)
Message: The options argument in function %s starts with the invalid character '%c'.
 - Error number: [3562](#); Symbol: [ER_INVALID_OPTION_END_CHARACTER](#); SQLSTATE: [22023](#)
Message: The options argument in function %s ends with the invalid character '%c'.
 - Error number: [3563](#); Symbol: [ER_INVALID_OPTION_CHARACTERS](#); SQLSTATE: [22023](#)
Message: The options argument in function %s contains the invalid character sequence '%s'.
 - Error number: [3564](#); Symbol: [ER_DUPLICATE_OPTION_KEY](#); SQLSTATE: [22023](#)
Message: Duplicate option key '%s' in funtion '%s'.
 - Error number: [3565](#); Symbol: [ER_WARN_SRS_NOT_FOUND_AXIS_ORDER](#); SQLSTATE: [01000](#)
Message: There's no spatial reference system with SRID %u. The axis order is unknown.
 - Error number: [3566](#); Symbol: [ER_NO_ACCESS_TO_NATIVE_FCT](#); SQLSTATE: [HY000](#)
Message: Access to native function '%s' is rejected.
 - Error number: [3567](#); Symbol: [ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)
Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.
 - Error number: [3568](#); Symbol: [ER_UNRESOLVED_TABLE_LOCK](#); SQLSTATE: [HY000](#)
Message: Unresolved table name %s in locking clause.
 - Error number: [3569](#); Symbol: [ER_DUPLICATE_TABLE_LOCK](#); SQLSTATE: [HY000](#)
Message: Table %s appears in multiple locking clauses.
 - Error number: [3570](#); Symbol: [ER_BINLOG_UNSAFE_SKIP_LOCKED](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it uses SKIP LOCKED. The set of inserted values is non-deterministic.
 - Error number: [3571](#); Symbol: [ER_BINLOG_UNSAFE_NOWAIT](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it uses NOWAIT. Whether the command will succeed or fail is not deterministic.
 - Error number: [3572](#); Symbol: [ER_LOCK_NOWAIT](#); SQLSTATE: [HY000](#)

Message: Statement aborted because lock(s) could not be acquired immediately and NOWAIT is set.

- Error number: 3573; Symbol: [ER_CTE_RECURSIVE_REQUIRES_UNION](#); SQLSTATE: HY000

Message: Recursive Common Table Expression '%s' should contain a UNION

- Error number: 3574; Symbol: [ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST](#); SQLSTATE: HY000

Message: Recursive Common Table Expression '%s' should have one or more non-recursive query blocks followed by one or more recursive ones

- Error number: 3575; Symbol: [ER_CTE_RECURSIVE_FORBIDS_AGGREGATION](#); SQLSTATE: HY000

Message: Recursive Common Table Expression '%s' can contain neither aggregation nor window functions in recursive query block

- Error number: 3576; Symbol: [ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER](#); SQLSTATE: HY000

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must neither be in the right argument of a LEFT JOIN, nor be forced to be non-first with join order hints

- Error number: 3577; Symbol: [ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE](#); SQLSTATE: HY000

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must be referenced only once, and not in any subquery

- Error number: 3578; Symbol: [ER_SWITCH_TMP_ENGINE](#); SQLSTATE: HY000

Message: '%s' requires @@internal_tmp_disk_storage_engine=InnoDB

- Error number: 3579; Symbol: [ER_WINDOW_NO_SUCH_WINDOW](#); SQLSTATE: HY000

Message: Window name '%s' is not defined.

- Error number: 3580; Symbol: [ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH](#); SQLSTATE: HY000

Message: There is a circularity in the window dependency graph.

- Error number: 3581; Symbol: [ER_WINDOW_NO_CHILD_PARTITIONING](#); SQLSTATE: HY000

Message: A window which depends on another cannot define partitioning.

- Error number: 3582; Symbol: [ER_WINDOW_NO_INHERIT_FRAME](#); SQLSTATE: HY000

Message: Window '%s' has a frame definition, so cannot be referenced by another window.

- Error number: 3583; Symbol: [ER_WINDOW_NO_REDEFINE_ORDER_BY](#); SQLSTATE: HY000

Message: Window '%s' cannot inherit '%s' since both contain an ORDER BY clause.

- Error number: 3584; Symbol: [ER_WINDOW_FRAME_START_ILLEGAL](#); SQLSTATE: HY000

Message: Window '%s': frame start cannot be UNBOUNDED FOLLOWING.

- Error number: 3585; Symbol: [ER_WINDOW_FRAME_END_ILLEGAL](#); SQLSTATE: HY000

Message: Window '%s': frame end cannot be UNBOUNDED PRECEDING.

- Error number: 3586; Symbol: [ER_WINDOW_FRAME_ILLEGAL](#); SQLSTATE: HY000

Message: Window '%s': frame start or end is negative, NULL or of non-integral type

- Error number: 3587; Symbol: [ER_WINDOW_RANGE_FRAME_ORDER_TYPE](#); SQLSTATE: HY000

Message: Window '%s' with RANGE N PRECEDING/FOLLOWING frame requires exactly one deterministic ORDER BY expression, of numeric or temporal type

- Error number: 3588; Symbol: [ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE](#); SQLSTATE: HY000

Message: Window '%s' with RANGE frame has ORDER BY expression of datetime type. Only INTERVAL bound value allowed.

- Error number: 3589; Symbol: [ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE](#); SQLSTATE: HY000

Message: Window '%s' with RANGE frame has ORDER BY expression of numeric type, INTERVAL bound value not allowed.

- Error number: 3590; Symbol: [ER_WINDOW_RANGE_BOUND_NOT_CONSTANT](#); SQLSTATE: HY000

Message: Window '%s' has a non-constant frame bound.

- Error number: 3591; Symbol: [ER_WINDOW_DUPLICATE_NAME](#); SQLSTATE: HY000

Message: Window '%s' is defined twice.

- Error number: 3592; Symbol: [ER_WINDOW_ILLEGAL_ORDER_BY](#); SQLSTATE: HY000

Message: Window '%s': ORDER BY or PARTITION BY uses legacy position indication which is not supported, use expression.

- Error number: 3593; Symbol: [ER_WINDOW_INVALID_WINDOW_FUNC_USE](#); SQLSTATE: HY000

Message: You cannot use the window function '%s' in this context.'

- Error number: 3594; Symbol: [ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE](#); SQLSTATE: HY000

Message: You cannot use the alias '%s' of an expression containing a window function in this context.'

- Error number: 3595; Symbol: [ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC](#); SQLSTATE: HY000

Message: You cannot nest a window function in the specification of window '%s'.

- Error number: 3596; Symbol: [ER_WINDOW_ROWS_INTERVAL_USE](#); SQLSTATE: HY000

Message: Window '%s': INTERVAL can only be used with RANGE frames.

- Error number: 3597; Symbol: [ER_WINDOW_NO_GROUP_ORDER_UNUSED](#); SQLSTATE: HY000

Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY

- Error number: 3598; Symbol: [ER_WINDOW_EXPLAIN_JSON](#); SQLSTATE: HY000

Message: To get information about window functions use EXPLAIN FORMAT=JSON

- Error number: 3599; Symbol: [ER_WINDOW_FUNCTION_IGNORES_FRAME](#); SQLSTATE: HY000

Message: Window function '%s' ignores the frame clause of window '%s' and aggregates over the whole partition

- Error number: 3600; Symbol: [ER_WL9236_NOW_UNUSED](#); SQLSTATE: HY000

Message: Windowing requires @@internal_tmp_mem_storage_engine=TempTable.

- Error number: 3601; Symbol: ER_INVALID_NO_OF_ARGS; SQLSTATE: HY000

Message: Too many arguments for function %s: %lu; maximum allowed is %s.

- Error number: 3602; Symbol: ER_FIELD_IN_GROUPING_NOT_GROUP_BY; SQLSTATE: HY000

Message: Argument #%u of GROUPING function is not in GROUP BY

- Error number: 3603; Symbol: ER_TOO_LONG_TABLESPACE_COMMENT; SQLSTATE: HY000

Message: Comment for tablespace '%s' is too long (max = %lu)

- Error number: 3604; Symbol: ER_ENGINE_CANT_DROP_TABLE; SQLSTATE: HY000

Message: Storage engine can't drop table '%s'

- Error number: 3605; Symbol: ER_ENGINE_CANT_DROP_MISSING_TABLE; SQLSTATE: HY000

Message: Storage engine can't drop table '%s' because it is missing. Use DROP TABLE IF EXISTS to remove it from data-dictionary.

- Error number: 3606; Symbol: ER_TABLESPACE_DUP_FILENAME; SQLSTATE: HY000

Message: Duplicate file name for tablespace '%s'

- Error number: 3607; Symbol: ER_DB_DROP_RMDIR2; SQLSTATE: HY000

Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.

- Error number: 3608; Symbol: ER_IMP_NO_FILES_MATCHED; SQLSTATE: HY000

Message: No SDI files matched the pattern '%s'

- Error number: 3609; Symbol: ER_IMP_SCHEMA_DOES_NOT_EXIST; SQLSTATE: HY000

Message: Schema '%s', referenced in SDI, does not exist.

- Error number: 3610; Symbol: ER_IMP_TABLE_ALREADY_EXISTS; SQLSTATE: HY000

Message: Table '%s.%s', referenced in SDI, already exists.

- Error number: 3611; Symbol: ER_IMP_INCOMPATIBLE_MYSQLD_VERSION; SQLSTATE: HY000

Message: Imported mysqld_version (%llu) is not compatible with current (%llu)

- Error number: 3612; Symbol: ER_IMP_INCOMPATIBLE_DD_VERSION; SQLSTATE: HY000

Message: Imported dd version (%u) is not compatible with current (%u)

- Error number: 3613; Symbol: ER_IMP_INCOMPATIBLE_SDI_VERSION; SQLSTATE: HY000

Message: Imported sdi version (%llu) is not compatible with current (%llu)

- Error number: 3614; Symbol: ER_WARN_INVALID_HINT; SQLSTATE: HY000

Message: Invalid number of arguments for hint %s

- Error number: 3615; Symbol: ER_VAR_DOES_NOT_EXIST; SQLSTATE: HY000

Message: Variable %s does not exist in persisted config file

- Error number: 3616; Symbol: ER_LONGITUDE_OUT_OF_RANGE; SQLSTATE: 22S02

Message: Longitude %f is out of range in function %s. It must be within (%f, %f].

- Error number: 3617; Symbol: [ER_LATITUDE_OUT_OF_RANGE](#); SQLSTATE: 22S03

Message: Latitude %f is out of range in function %s. It must be within [%f, %f].

- Error number: 3618; Symbol: [ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS](#); SQLSTATE: 22S00

Message: %s(%s) has not been implemented for geographic spatial reference systems.

- Error number: 3619; Symbol: [ER_ILLEGAL_PRIVILEGE_LEVEL](#); SQLSTATE: HY000

Message: Illegal privilege level specified for %s

- Error number: 3620; Symbol: [ER_NO_SYSTEM_VIEW_ACCESS](#); SQLSTATE: HY000

Message: Access to system view INFORMATION_SCHEMA.'%s' is rejected.

- Error number: 3621; Symbol: [ER_COMPONENT_FILTER_FLABBERGASTED](#); SQLSTATE: HY000

Message: The log-filter component "%s" got confused at "%s" ...

- Error number: 3622; Symbol: [ER_PART_EXPR_TOO_LONG](#); SQLSTATE: HY000

Message: Partitioning expression is too long.

- Error number: 3623; Symbol: [ER_UDF_DROP_DYNAMICALLY_REGISTERED](#); SQLSTATE: HY000

Message: DROP FUNCTION can't drop a dynamically registered user defined function

- Error number: 3624; Symbol: [ER_UNABLE_TO_STORE_COLUMN_STATISTICS](#); SQLSTATE: HY000

Message: Unable to store column statistics for column '%s' in table '%s'. '%s'

- Error number: 3625; Symbol: [ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS](#); SQLSTATE: HY000

Message: Unable to update column statistics for column '%s' in table '%s'. '%s'

- Error number: 3626; Symbol: [ER_UNABLE_TO_DROP_COLUMN_STATISTICS](#); SQLSTATE: HY000

Message: Unable to remove column statistics for column '%s' in table '%s'. '%s'

- Error number: 3627; Symbol: [ER_UNABLE_TO_BUILD_HISTOGRAM](#); SQLSTATE: HY000

Message: Unable to build histogram statistics for column '%s' in table '%s'. '%s'

- Error number: 3628; Symbol: [ER_MANDATORY_ROLE](#); SQLSTATE: HY000

Message: The role %s is a mandatory role and can't be revoked or dropped. The restriction can be lifted by excluding the role identifier from the global variable mandatory_roles.

- Error number: 3629; Symbol: [ER_MISSING_TABLESPACE_FILE](#); SQLSTATE: HY000

Message: Tablespace '%s' does not have a file named '%s'

- Error number: 3630; Symbol: [ER_PERSIST_ONLY_ACCESS_DENIED_ERROR](#); SQLSTATE: 42000

Message: Access denied; you need %s privileges for this operation

- Error number: 3632; Symbol: [ER_PATH_IN_DATADIR](#); SQLSTATE: HY000

Message: Path is within the current data directory '%s'

-
- Error number: [3633](#); Symbol: [ER_CLONE_DDL_IN_PROGRESS](#); SQLSTATE: [HY000](#)
Message: Concurrent DDL is performed during clone operation. Please try again.
 - Error number: [3634](#); Symbol: [ER_CLONE_TOO_MANY_CONCURRENT_CLONES](#); SQLSTATE: [HY000](#)
Message: Too many concurrent clone operations. Maximum allowed - %d.
 - Error number: [3635](#); Symbol: [ER_APPLIER_LOG_EVENT_VALIDATION_ERROR](#); SQLSTATE: [HY000](#)
Message: The table in transaction %s does not comply with the requirements by an external plugin.
 - Error number: [3636](#); Symbol: [ER_CTE_MAX_RECURSION_DEPTH](#); SQLSTATE: [HY000](#)
Message: Recursive query aborted after %u iterations. Try increasing @@cte_max_recursion_depth to a larger value.
 - Error number: [3637](#); Symbol: [ER_NOT_HINT_UPDATABLE_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable %s cannot be set using SET_VAR hint.
 - Error number: [3638](#); Symbol: [ER_CREDENTIALS_CONTRADICT_TO_HISTORY](#); SQLSTATE: [HY000](#)
Message: Cannot use these credentials for '%.*s@%.*s' because they contradict the password history policy
 - Error number: [3639](#); Symbol: [ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID](#); SQLSTATE: [HY000](#)
Message: Non-zero password history clauses ignored for user '%s'@'%s' as its authentication plugin %s does not support password history
 - Error number: [3640](#); Symbol: [ER_CLIENT_DOES_NOT_SUPPORT](#); SQLSTATE: [HY000](#)
Message: The client doesn't support %s
 - Error number: [3641](#); Symbol: [ER_I_S_SKIPPED_TABLESPACE](#); SQLSTATE: [HY000](#)
Message: Tablespace '%s' was skipped since its definition is being modified by concurrent DDL statement
 - Error number: [3642](#); Symbol: [ER_TABLESPACE_ENGINE_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Engine '%s' does not match stored engine '%s' for tablespace '%s'
 - Error number: [3643](#); Symbol: [ER_WRONG_SRID_FOR_COLUMN](#); SQLSTATE: [HY000](#)
Message: The SRID of the geometry does not match the SRID of the column '%s'. The SRID of the geometry is %lu, but the SRID of the column is %lu. Consider changing the SRID of the geometry or the SRID property of the column.
 - Error number: [3644](#); Symbol: [ER_CANNOT_ALTER_SRID_DUE_TO_INDEX](#); SQLSTATE: [HY000](#)
Message: The SRID specification on the column '%s' cannot be changed because there is a spatial index on the column. Please remove the spatial index before altering the SRID specification.
 - Error number: [3645](#); Symbol: [ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED](#); SQLSTATE: [HY000](#)
Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.
-

-
- Error number: [3647](#); Symbol: [ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES](#); SQLSTATE: [HY000](#)
Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog_row_value_options is limited to less than 50%%.
 - Error number: [3648](#); Symbol: [ER_COULD_NOT_APPLY_JSON_DIFF](#); SQLSTATE: [HY000](#)
Message: Could not apply JSON diff in table %.*s, column %s.
 - Error number: [3649](#); Symbol: [ER_CORRUPTED_JSON_DIFF](#); SQLSTATE: [HY000](#)
Message: Corrupted JSON diff for table %.*s, column %s.
 - Error number: [3650](#); Symbol: [ER_RESOURCE_GROUP_EXISTS](#); SQLSTATE: [HY000](#)
Message: Resource Group '%s' exists
 - Error number: [3651](#); Symbol: [ER_RESOURCE_GROUP_NOT_EXISTS](#); SQLSTATE: [HY000](#)
Message: Resource Group '%s' does not exist.
 - Error number: [3652](#); Symbol: [ER_INVALID_VCPU_ID](#); SQLSTATE: [HY000](#)
Message: Invalid cpu id %u
 - Error number: [3653](#); Symbol: [ER_INVALID_VCPU_RANGE](#); SQLSTATE: [HY000](#)
Message: Invalid VCPU range %u-%u
 - Error number: [3654](#); Symbol: [ER_INVALID_THREAD_PRIORITY](#); SQLSTATE: [HY000](#)
Message: Invalid thread priority value %d for %s resource group %s. Allowed range is [%d, %d].
 - Error number: [3655](#); Symbol: [ER_DISALLOWED_OPERATION](#); SQLSTATE: [HY000](#)
Message: %s operation is disallowed on %s
 - Error number: [3656](#); Symbol: [ER_RESOURCE_GROUP_BUSY](#); SQLSTATE: [HY000](#)
Message: Resource group %s is busy.
 - Error number: [3657](#); Symbol: [ER_RESOURCE_GROUP_DISABLED](#); SQLSTATE: [HY000](#)
Message: Resource group %s is disabled.
 - Error number: [3658](#); Symbol: [ER_FEATURE_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: Feature %s is unsupported (%s).
 - Error number: [3659](#); Symbol: [ER_ATTRIBUTE_IGNORED](#); SQLSTATE: [HY000](#)
Message: Attribute %s is ignored (%s).
 - Error number: [3660](#); Symbol: [ER_INVALID_THREAD_ID](#); SQLSTATE: [HY000](#)
Message: Invalid thread id (%llu).
 - Error number: [3661](#); Symbol: [ER_RESOURCE_GROUP_BIND_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to bind resource group %s with thread id (%llu).(s).
 - Error number: [3662](#); Symbol: [ER_INVALID_USE_OF_FORCE_OPTION](#); SQLSTATE: [HY000](#)

Message: Option FORCE invalid as DISABLE option is not specified.

- Error number: 3663; Symbol: `ER_GROUP_REPLICATION_COMMAND_FAILURE`; SQLSTATE: HY000

Message: The %s command encountered a failure. %s

- Error number: 3664; Symbol: `ER_SDI_OPERATION_FAILED`; SQLSTATE: HY000

Message: Failed to %s SDI '%s.%s' in tablespace '%s'.

- Error number: 3665; Symbol: `ER_MISSING_JSON_TABLE_VALUE`; SQLSTATE: 22035

Message: Missing value for JSON_TABLE column '%s'

- Error number: 3666; Symbol: `ER_WRONG_JSON_TABLE_VALUE`; SQLSTATE: 2203F

Message: Can't store an array or an object in the scalar JSON_TABLE column '%s'

- Error number: 3667; Symbol: `ER_TF_MUST_HAVE_ALIAS`; SQLSTATE: 42000

Message: Every table function must have an alias

- Error number: 3668; Symbol: `ER_TF_FORBIDDEN_JOIN_TYPE`; SQLSTATE: HY000

Message: INNER or LEFT JOIN must be used for LATERAL references made by '%s'

- Error number: 3669; Symbol: `ER_JT_VALUE_OUT_OF_RANGE`; SQLSTATE: 22003

Message: Value is out of range for JSON_TABLE's column '%s'

- Error number: 3670; Symbol: `ER_JT_MAX_NESTED_PATH`; SQLSTATE: 42000

Message: More than supported %u NESTED PATHs were found in JSON_TABLE '%s'

- Error number: 3671; Symbol: `ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD`; SQLSTATE: HY000

Message: The selected authentication method %.*s does not support password expiration

- Error number: 3672; Symbol: `ER_INVALID_GEOJSON CRS_NOT_TOP_LEVEL`; SQLSTATE: HY000

Message: Invalid GeoJSON data provided to function %s: Member 'crs' must be specified in the top level object.

- Error number: 3673; Symbol: `ER_BAD_NULL_ERROR_NOT_IGNORED`; SQLSTATE: 23000

Message: Column '%s' cannot be null

- Error number: 3674; Symbol: `WARN_USELESS_SPATIAL_INDEX`; SQLSTATE: HY000

Message: The spatial index on column '%s' will not be used by the query optimizer since the column does not have an SRID attribute. Consider adding an SRID attribute to the column.

- Error number: 3675; Symbol: `ER_DISK_FULL_NOWAIT`; SQLSTATE: HY000

Message: Create table/tablespace '%s' failed, as disk is full

- Error number: 3676; Symbol: `ER_PARSE_ERROR_IN_DIGEST_FN`; SQLSTATE: HY000

Message: Could not parse argument to digest function: "%s".

- Error number: 3677; Symbol: `ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN`; SQLSTATE: HY000

Message: Could not parse argument to digest function.

- Error number: 3678; Symbol: [ER_SCHEMA_DIR_EXISTS](#); SQLSTATE: HY000

Message: Schema directory '%s' already exists. This must be resolved manually (e.g. by moving the schema directory to another location).

- Error number: 3679; Symbol: [ER_SCHEMA_DIR_MISSING](#); SQLSTATE: HY000

Message: Schema directory '%s' does not exist

- Error number: 3680; Symbol: [ER_SCHEMA_DIR_CREATE_FAILED](#); SQLSTATE: HY000

Message: Failed to create schema directory '%s' (errno: %d - %s)

- Error number: 3681; Symbol: [ER_SCHEMA_DIR_UNKNOWN](#); SQLSTATE: HY000

Message: Schema '%s' does not exist, but schema directory '%s' was found. This must be resolved manually (e.g. by moving the schema directory to another location).

- Error number: 3682; Symbol: [ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326](#); SQLSTATE: 22S00

Message: Function %s is only defined for SRID 0 and SRID 4326.

- Error number: 3684; Symbol: [ER_REGEX_BUFFER_OVERFLOW](#); SQLSTATE: HY000

Message: The result string is larger than the result buffer.

- Error number: 3685; Symbol: [ER_REGEX_ILLEGAL_ARGUMENT](#); SQLSTATE: HY000

Message: Illegal argument to a regular expression.

- Error number: 3686; Symbol: [ER_REGEX_INDEX_OUTOFBOUNDS_ERROR](#); SQLSTATE: HY000

Message: Index out of bounds in regular expression search.

- Error number: 3687; Symbol: [ER_REGEX_INTERNAL_ERROR](#); SQLSTATE: HY000

Message: Internal error in the regular expression library.

- Error number: 3688; Symbol: [ER_REGEX_RULE_SYNTAX](#); SQLSTATE: HY000

Message: Syntax error in regular expression on line %u, character %u.

- Error number: 3689; Symbol: [ER_REGEX_BAD_ESCAPE_SEQUENCE](#); SQLSTATE: HY000

Message: Unrecognized escape sequence in regular expression.

- Error number: 3690; Symbol: [ER_REGEX_UNIMPLEMENTED](#); SQLSTATE: HY000

Message: The regular expression contains a feature that is not implemented in this library version.

- Error number: 3691; Symbol: [ER_REGEX_MISMATCHED_PAREN](#); SQLSTATE: HY000

Message: Mismatched parenthesis in regular expression.

- Error number: 3692; Symbol: [ER_REGEX_BAD_INTERVAL](#); SQLSTATE: HY000

Message: Incorrect description of a {min,max} interval.

- Error number: 3693; Symbol: [ER_REGEX_MAX_LT_MIN](#); SQLSTATE: HY000

Message: The maximum is less than the minumum in a {min,max} interval.

-
- Error number: [3694](#); Symbol: [ER_REGEX_INVALID_BACK_REF](#); SQLSTATE: [HY000](#)
Message: Invalid back-reference in regular expression.
 - Error number: [3695](#); Symbol: [ER_REGEX_LOOK_BEHIND_LIMIT](#); SQLSTATE: [HY000](#)
Message: The look-behind assertion exceeds the limit in regular expression.
 - Error number: [3696](#); Symbol: [ER_REGEX_MISSING_CLOSE_BRACKET](#); SQLSTATE: [HY000](#)
Message: The regular expression contains an unclosed bracket expression.
 - Error number: [3697](#); Symbol: [ER_REGEX_INVALID_RANGE](#); SQLSTATE: [HY000](#)
Message: The regular expression contains an [x-y] character range where x comes after y.
 - Error number: [3698](#); Symbol: [ER_REGEX_STACK_OVERFLOW](#); SQLSTATE: [HY000](#)
Message: Overflow in the regular expression backtrack stack.
 - Error number: [3699](#); Symbol: [ER_REGEX_TIME_OUT](#); SQLSTATE: [HY000](#)
Message: Timeout exceeded in regular expression match.
 - Error number: [3700](#); Symbol: [ER_REGEX_PATTERN_TOO_BIG](#); SQLSTATE: [HY000](#)
Message: The regular expression pattern exceeds limits on size or complexity.
 - Error number: [3701](#); Symbol: [ER_CANT_SET_ERROR_LOG_SERVICE](#); SQLSTATE: [HY000](#)
Message: Value for %s got confusing at or around "%s". Syntax may be wrong, component may not be INSTALLED, or a component that does not support instances may be listed more than once.
 - Error number: [3702](#); Symbol: [ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE](#); SQLSTATE: [HY000](#)
Message: Setting an empty %s pipeline disables error logging!
 - Error number: [3703](#); Symbol: [ER_COMPONENT_FILTER_DIAGNOSTICS](#); SQLSTATE: [HY000](#)
Message: filter %s: %s
 - Error number: [3704](#); Symbol: [ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS](#); SQLSTATE: [22S00](#)
Message: %s(%s) has not been implemented for Cartesian spatial reference systems.
 - Error number: [3705](#); Symbol: [ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS](#); SQLSTATE: [22S00](#)
Message: %s(%s) has not been implemented for projected spatial reference systems.
 - Error number: [3706](#); Symbol: [ER_NONPOSITIVE_RADIUS](#); SQLSTATE: [22003](#)
Message: Invalid radius provided to function %s: Radius must be greater than zero.
 - Error number: [3707](#); Symbol: [ER_RESTART_SERVER_FAILED](#); SQLSTATE: [HY000](#)
Message: Restart server failed (%s).
 - Error number: [3708](#); Symbol: [ER_SRS_MISSING_MANDATORY_ATTRIBUTE](#); SQLSTATE: [SR006](#)
Message: Missing mandatory attribute %s.
 - Error number: [3709](#); Symbol: [ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS](#); SQLSTATE: [SR006](#)

Message: Multiple definitions of attribute %s.

- Error number: 3710; Symbol: `ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: `SR006`

Message: The spatial reference system name can't be an empty string or start or end with whitespace.

- Error number: 3711; Symbol: `ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: `SR006`

Message: The organization name can't be an empty string or start or end with whitespace.

- Error number: 3712; Symbol: `ER_SRS_ID_ALREADY_EXISTS`; SQLSTATE: `SR004`

Message: There is already a spatial reference system with SRID %u.

- Error number: 3713; Symbol: `ER_WARN_SRS_ID_ALREADY_EXISTS`; SQLSTATE: `01S00`

Message: There is already a spatial reference system with SRID %u.

- Error number: 3714; Symbol: `ER_CANT_MODIFY_SRID_0`; SQLSTATE: `SR000`

Message: SRID 0 is not modifiable.

- Error number: 3715; Symbol: `ER_WARN_RESERVED_SRID_RANGE`; SQLSTATE: `01S01`

Message: The SRID range [%u, %u] has been reserved for system use. SRSs in this range may be added, modified or removed without warning during upgrade.

- Error number: 3716; Symbol: `ER_CANT_MODIFY_SRS_USED_BY_COLUMN`; SQLSTATE: `SR005`

Message: Can't modify SRID %u. There is at least one column depending on it.

- Error number: 3717; Symbol: `ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE`; SQLSTATE: `SR006`

Message: Invalid character in attribute %s.

- Error number: 3718; Symbol: `ER_SRS_ATTRIBUTE_STRING_TOO_LONG`; SQLSTATE: `SR006`

Message: Attribute %s is too long. The maximum length is %u characters.

- Error number: 3719; Symbol: `ER_DEPRECATED_UTF8_ALIAS`; SQLSTATE: `HY000`

Message: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

- Error number: 3720; Symbol: `ER_DEPRECATED_NATIONAL`; SQLSTATE: `HY000`

Message: NATIONAL/NCHAR/NVARCHAR implies the character set UTF8MB3, which will be replaced by UTF8MB4 in a future release. Please consider using CHAR(x) CHARACTER SET UTF8MB4 in order to be unambiguous.

- Error number: 3721; Symbol: `ER_INVALID_DEFAULT_UTF8MB4_COLLATION`; SQLSTATE: `HY000`

Message: Invalid default collation %s: utf8mb4_0900_ai_ci or utf8mb4_general_ci expected

- Error number: 3722; Symbol: `ER_UNABLE_TO_COLLECT_LOG_STATUS`; SQLSTATE: `HY000`

Message: Unable to collect information for column '%s': %s.

- Error number: 3723; Symbol: `ER_RESERVED_TABLESPACE_NAME`; SQLSTATE: `HY000`

Message: The table '%s' may not be created in the reserved tablespace '%s'.

- Error number: 3724; Symbol: [ER_UNABLE_TO_SET_OPTION](#); SQLSTATE: [HY000](#)

Message: This option cannot be set %s.

- Error number: 3725; Symbol: [ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL](#); SQLSTATE: [HY000](#)

Message: A commit for an atomic DDL statement was unsuccessful on the source and the replica. The replica supports atomic DDL statements but the source does not, so the action taken by the replica and source might differ. Check that their states have not diverged before proceeding.

- Error number: 3726; Symbol: [ER_SRS_NOT_GEOGRAPHIC](#); SQLSTATE: [22S00](#)

Message: Function %s is only defined for geographic spatial reference systems, but one of its arguments is in SRID %u, which is not geographic.

- Error number: 3727; Symbol: [ER_POLYGON_TOO_LARGE](#); SQLSTATE: [22023](#)

Message: Function %s encountered a polygon that was too large. Polygons must cover less than half the planet.

- Error number: 3728; Symbol: [ER_SPATIAL_UNIQUE_INDEX](#); SQLSTATE: [HY000](#)

Message: Spatial indexes can't be primary or unique indexes.

- Error number: 3729; Symbol: [ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX](#); SQLSTATE: [HY000](#)

Message: The index type %s is not supported for spatial indexes.

- Error number: 3730; Symbol: [ER_FK_CANNOT_DROP_PARENT](#); SQLSTATE: [HY000](#)

Message: Cannot drop table '%s' referenced by a foreign key constraint '%s' on table '%s'.

- Error number: 3731; Symbol: [ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE](#); SQLSTATE: [22S02](#)

Message: A parameter of function %s contains a geometry with longitude %f, which is out of range. It must be within (%f, %f].

- Error number: 3732; Symbol: [ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE](#); SQLSTATE: [22S03](#)

Message: A parameter of function %s contains a geometry with latitude %f, which is out of range. It must be within [%f, %f].

- Error number: 3733; Symbol: [ER_FK_CANNOT_USE_VIRTUAL_COLUMN](#); SQLSTATE: [HY000](#)

Message: Foreign key '%s' uses virtual column '%s' which is not supported.

- Error number: 3734; Symbol: [ER_FK_NO_COLUMN_PARENT](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint. Missing column '%s' for constraint '%s' in the referenced table '%s'

- Error number: 3735; Symbol: [ER_CANT_SET_ERROR_SUPPRESSION_LIST](#); SQLSTATE: [HY000](#)

Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.

- Error number: 3736; Symbol: [ER_SRS_GEOGCS_INVALID_AXES](#); SQLSTATE: [SR002](#)

Message: The spatial reference system definition for SRID %u specifies invalid geographic axes '%s' and '%s'. One axis must be NORTH or SOUTH and the other must be EAST or WEST.

- Error number: 3737; Symbol: [ER_SRS_INVALID_SEMI_MAJOR_AXIS](#); SQLSTATE: SR002

Message: The length of the semi-major axis must be a positive number.

- Error number: 3738; Symbol: [ER_SRS_INVALID_INVERSE_FLATTENING](#); SQLSTATE: SR002

Message: The inverse flattening must be larger than 1.0, or 0.0 if the ellipsoid is a sphere.

- Error number: 3739; Symbol: [ER_SRS_INVALID_ANGULAR_UNIT](#); SQLSTATE: SR002

Message: The angular unit conversion factor must be a positive number.

- Error number: 3740; Symbol: [ER_SRS_INVALID_PRIME_MERIDIAN](#); SQLSTATE: SR002

Message: The prime meridian must be within (-180, 180] degrees, specified in the SRS angular unit.

- Error number: 3741; Symbol: [ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED](#); SQLSTATE: 22S00

Message: Transformation from SRID %u is not supported.

- Error number: 3742; Symbol: [ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED](#); SQLSTATE: 22S00

Message: Transformation to SRID %u is not supported.

- Error number: 3743; Symbol: [ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84](#); SQLSTATE: 22S00

Message: Transformation from SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

- Error number: 3744; Symbol: [ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84](#); SQLSTATE: 22S00

Message: Transformation to SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

- Error number: 3745; Symbol: [ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT](#); SQLSTATE: HY000

Message: Changing @@session.binlog_format is disallowed when the session has open temporary table(s). You could wait until these temporary table(s) are dropped and try again.

- Error number: 3746; Symbol: [ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#); SQLSTATE: HY000

Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel has open temporary table(s). You could wait until Replica_open_temp_tables = 0 and try again

- Error number: 3747; Symbol: [ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#); SQLSTATE: HY000

Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel applier thread is running. You could execute STOP REPLICA SQL_THREAD and try again.

- Error number: 3748; Symbol: [ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#); SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog_format=STATEMENT.

- Error number: [3750](#); Symbol: [ER_TABLE_WITHOUT_PK](#); SQLSTATE: [HY000](#)

Message: Unable to create or change a table without a primary key, when the system variable 'sql_require_primary_key' is set. Add a primary key to the table or unset this variable to avoid this message. Note that tables without a primary key can cause performance problems in row-based replication, so please consult your DBA before changing this setting.

- Error number: [3751](#); Symbol: [ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX](#); SQLSTATE: [01000](#)

Message: Data truncated for functional index '%s' at row %ld

- Error number: [3752](#); Symbol: [ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX](#); SQLSTATE: [22003](#)

Message: Value is out of range for functional index '%s' at row %ld

- Error number: [3753](#); Symbol: [ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION](#); SQLSTATE: [42000](#)

Message: Cannot create a functional index on a function that returns a JSON or GEOMETRY value.

- Error number: [3754](#); Symbol: [ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT](#); SQLSTATE: [HY000](#)

Message: Functional index '%s' cannot refer to an auto-increment column.

- Error number: [3755](#); Symbol: [ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX](#); SQLSTATE: [HY000](#)

Message: Cannot drop column '%s' because it is used by a functional index. In order to drop the column, you must remove the functional index.

- Error number: [3756](#); Symbol: [ER_FUNCTIONAL_INDEX_PRIMARY_KEY](#); SQLSTATE: [HY000](#)

Message: The primary key cannot be a functional index

- Error number: [3757](#); Symbol: [ER_FUNCTIONAL_INDEX_ON_LOB](#); SQLSTATE: [HY000](#)

Message: Cannot create a functional index on an expression that returns a BLOB or TEXT. Please consider using CAST.

- Error number: [3758](#); Symbol: [ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Expression of functional index '%s' contains a disallowed function.

- Error number: [3759](#); Symbol: [ER_FULLTEXT_FUNCTIONAL_INDEX](#); SQLSTATE: [HY000](#)

Message: Fulltext functional index is not supported.

- Error number: [3760](#); Symbol: [ER_SPATIAL_FUNCTIONAL_INDEX](#); SQLSTATE: [HY000](#)

Message: Spatial functional index is not supported.

- Error number: [3761](#); Symbol: [ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX](#); SQLSTATE: [HY000](#)

Message: The used storage engine cannot index the expression '%s'.

-
- Error number: 3762; Symbol: [ER_FUNCTIONAL_INDEX_ON_FIELD](#); SQLSTATE: HY000
Message: Functional index on a column is not supported. Consider using a regular index instead.
 - Error number: 3763; Symbol: [ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000
Message: Expression of generated column '%s' contains a disallowed function: %s.
 - Error number: 3764; Symbol: [ER_GENERATED_COLUMN_ROW_VALUE](#); SQLSTATE: HY000
Message: Expression of generated column '%s' cannot refer to a row value.
 - Error number: 3765; Symbol: [ER_GENERATED_COLUMN_VARIABLES](#); SQLSTATE: HY000
Message: Expression of generated column '%s' cannot refer user or system variables.
 - Error number: 3766; Symbol: [ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE](#); SQLSTATE: HY000
Message: Column '%s' of table '%s' has a default value expression dependency and cannot be dropped or renamed.
 - Error number: 3767; Symbol: [ER_DEFAULT_VAL_GENERATED_NON_PRIOR](#); SQLSTATE: HY000
Message: Default value expression of column '%s' cannot refer to a column defined after it if that column is a generated column or has an expression as default value.
 - Error number: 3768; Symbol: [ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC](#); SQLSTATE: HY000
Message: Default value expression of column '%s' cannot refer to an auto-increment column.
 - Error number: 3769; Symbol: [ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000
Message: Default value expression of column '%s' contains a disallowed function.
 - Error number: 3770; Symbol: [ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000
Message: Default value expression of column '%s' contains a disallowed function: %s.
 - Error number: 3771; Symbol: [ER_DEFAULT_VAL_GENERATED_ROW_VALUE](#); SQLSTATE: HY000
Message: Default value expression of column '%s' cannot refer to a row value.
 - Error number: 3772; Symbol: [ER_DEFAULT_VAL_GENERATED_VARIABLES](#); SQLSTATE: HY000
Message: Default value expression of column '%s' cannot refer user or system variables.
 - Error number: 3773; Symbol: [ER_DEFAULT_AS_VAL_GENERATED](#); SQLSTATE: HY000
Message: DEFAULT function cannot be used with default value expressions
 - Error number: 3774; Symbol: [ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED](#); SQLSTATE: HY000
Message: '%s' is not supported for default value expressions.

-
- Error number: [3775](#); Symbol: [ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.
 - Error number: [3776](#); Symbol: [ER_FK_CANNOT_CHANGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot change table's storage engine because the table participates in a foreign key constraint.
 - Error number: [3777](#); Symbol: [ER_WARN_DEPRECATED_USER_SET_EXPR](#); SQLSTATE: [HY000](#)

Message: Setting user variables within expressions is deprecated and will be removed in a future release. Consider alternatives: 'SET variable=expression, ...', or 'SELECT expression(s) INTO variables(s)'.
 - Error number: [3778](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_COLLATION](#); SQLSTATE: [HY000](#)

Message: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.
 - Error number: [3779](#); Symbol: [ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX](#); SQLSTATE: [HY000](#)

Message: Nested comment syntax is deprecated and will be removed in a future release.
 - Error number: [3780](#); Symbol: [ER_FK_INCOMPATIBLE_COLUMNS](#); SQLSTATE: [HY000](#)

Message: Referencing column '%s' and referenced column '%s' in foreign key constraint '%s' are incompatible.
 - Error number: [3781](#); Symbol: [ER_GR_HOLD_WAIT_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Timeout exceeded for held statement while new Group Replication primary member is applying backlog.
 - Error number: [3782](#); Symbol: [ER_GR_HOLD_KILLED](#); SQLSTATE: [HY000](#)

Message: Held statement aborted because Group Replication plugin got shut down or thread was killed while new primary member was applying backlog.
 - Error number: [3783](#); Symbol: [ER_GR_HOLD_MEMBER_STATUS_ERROR](#); SQLSTATE: [HY000](#)

Message: Held statement was aborted due to member being in error state, while backlog is being applied during Group Replication primary election.
 - Error number: [3784](#); Symbol: [ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to fetch key from keyring, please check if keyring is loaded.
 - Error number: [3785](#); Symbol: [ER_RPL_ENCRYPTION_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.
 - Error number: [3786](#); Symbol: [ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY](#); SQLSTATE: [HY000](#)

Message: Fetched an invalid key from keyring.
 - Error number: [3787](#); Symbol: [ER_RPL_ENCRYPTION_HEADER_ERROR](#); SQLSTATE: [HY000](#)

Message: Error reading a replication log encryption header: %s.

- Error number: 3788; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS`; SQLSTATE: `HY000`

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

- Error number: 3789; Symbol: `ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED`; SQLSTATE: `HY000`

Message: Key %s exists unexpected.

- Error number: 3790; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: `HY000`

Message: Failed to generate key, please check if keyring is loaded.

- Error number: 3791; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: `HY000`

Message: Failed to store key, please check if keyring is loaded.

- Error number: 3792; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: `HY000`

Message: Failed to remove key, please check if keyring is loaded.

- Error number: 3793; Symbol: `ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION`; SQLSTATE: `HY000`

Message: Failed to change binlog_encryption value. %s.

- Error number: 3794; Symbol: `ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: `HY000`

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

- Error number: 3795; Symbol: `ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE`; SQLSTATE: `HY000`

Message: slow query log file format changed as requested, but setting will have no effect when not actually logging to a file.

- Error number: 3796; Symbol: `ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: The option group_replication_consistency cannot be used on the current member state.

- Error number: 3797; Symbol: `ER_GRP_TRX_CONSISTENCY_BEFORE`; SQLSTATE: `HY000`

Message: Error while waiting for group transactions commit on group_replication_consistency= 'BEFORE'.

- Error number: 3798; Symbol: `ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN`; SQLSTATE: `HY000`

Message: Error while waiting for transactions with group_replication_consistency= 'AFTER' to commit.

-
- Error number: 3799; Symbol: ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED; SQLSTATE: HY000

Message: The Group Replication plugin is stopping, therefore new transactions are not allowed to start.

- Error number: 3800; Symbol: ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED; SQLSTATE: HY000

Message: Expression of functional index '%s' cannot refer to a row value.

- Error number: 3801; Symbol: ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT; SQLSTATE: HY000

Message: Failed to encrypt content to write into binlog file: %s.

- Error number: 3802; Symbol: ER_PAGE_TRACKING_NOT_STARTED; SQLSTATE: HY000

Message: Page Tracking is not started yet.

- Error number: 3803; Symbol: ER_PAGE_TRACKING_RANGE_NOT_TRACKED; SQLSTATE: HY000

Message: Tracking was not enabled for the LSN range specified

- Error number: 3804; Symbol: ER_PAGE_TRACKING_CANNOT_PURGE; SQLSTATE: HY000

Message: Cannot purge data when concurrent clone is in progress. Try later.

- Error number: 3805; Symbol: ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY; SQLSTATE: HY000

Message: Cannot rotate binary log master key when 'binlog-encryption' is off.

- Error number: 3806; Symbol: ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION; SQLSTATE: HY000

Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u, master_key_seqno=%u and old_master_key_seqno=%u are wrong.

- Error number: 3807; Symbol: ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY; SQLSTATE: HY000

Message: Failed to operate binary log master key on keyring, please check if keyring is loaded. The statement had no effect: the old binary log master key is still in use, the keyring, binary and relay log files are unchanged, and the server could not start using a new binary log master key for encrypting new binary and relay log files.

- Error number: 3808; Symbol: ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS; SQLSTATE: HY000

Message: Failed to rotate one or more binary or relay log files. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

- Error number: 3809; Symbol: ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG; SQLSTATE: HY000

Message: %s. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

- Error number: 3810; Symbol: ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS; SQLSTATE: HY000

Message: Failed to remove unused binary log encryption keys from the keyring, please check if keyring is loaded. The unused binary log encryption keys may still exist in the keyring, and they will be removed upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

- Error number: [3811](#); Symbol: [ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

- Error number: [3812](#); Symbol: [ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT](#); SQLSTATE: [HY000](#)

Message: An expression of non-boolean type specified to a check constraint '%s'.

- Error number: [3813](#); Symbol: [ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column check constraint '%s' references other column.

- Error number: [3814](#); Symbol: [ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: An expression of a check constraint '%s' contains disallowed function: %s.

- Error number: [3815](#); Symbol: [ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: An expression of a check constraint '%s' contains disallowed function.

- Error number: [3816](#); Symbol: [ER_CHECK_CONSTRAINT_VARIABLES](#); SQLSTATE: [HY000](#)

Message: An expression of a check constraint '%s' cannot refer to a user or system variable.

- Error number: [3817](#); Symbol: [ER_CHECK_CONSTRAINT_ROW_VALUE](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' cannot refer to a row value.

- Error number: [3818](#); Symbol: [ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' cannot refer to an auto-increment column.

- Error number: [3819](#); Symbol: [ER_CHECK_CONSTRAINT_VIOLATED](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' is violated.

- Error number: [3820](#); Symbol: [ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' refers to non-existing column '%s'.

- Error number: [3821](#); Symbol: [ER_CHECK_CONSTRAINT_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' is not found in the table.

- Error number: [3822](#); Symbol: [ER_CHECK_CONSTRAINT_DUP_NAME](#); SQLSTATE: [HY000](#)

Message: Duplicate check constraint name '%s'.

-
- Error number: [3823](#); Symbol: [ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' cannot be used in a check constraint '%s': needed in a foreign key constraint '%s' referential action.
 - Error number: [3824](#); Symbol: [WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB](#); SQLSTATE: [HY000](#)

Message: Creating an unencrypted table in a database with default encryption enabled.
 - Error number: [3825](#); Symbol: [ER_INVALID_ENCRYPTION_REQUEST](#); SQLSTATE: [HY000](#)

Message: Request to create %s table while using an %s tablespace.
 - Error number: [3826](#); Symbol: [ER_CANNOT_SET_TABLE_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Table encryption differ from its database default encryption, and user doesn't have enough privilege.
 - Error number: [3827](#); Symbol: [ER_CANNOT_SET_DATABASE_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Database default encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.
 - Error number: [3828](#); Symbol: [ER_CANNOT_SET_TABLESPACE_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Tablespace encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.
 - Error number: [3829](#); Symbol: [ER_TABLESPACE_CANNOT_BE_ENCRYPTED](#); SQLSTATE: [HY000](#)

Message: This tablespace can't be encrypted, because one of table's schema has default encryption OFF and user doesn't have enough privilege.
 - Error number: [3830](#); Symbol: [ER_TABLESPACE_CANNOT_BE_DECRYPTED](#); SQLSTATE: [HY000](#)

Message: This tablespace can't be decrypted, because one of table's schema has default encryption ON and user doesn't have enough privilege.
 - Error number: [3831](#); Symbol: [ER_TABLESPACE_TYPE_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Cannot determine the type of the tablespace named '%s'.
 - Error number: [3832](#); Symbol: [ER_TARGET_TABLESPACE_UNENCRYPTED](#); SQLSTATE: [HY000](#)

Message: Source tablespace is encrypted but target tablespace is not.
 - Error number: [3833](#); Symbol: [ER_CANNOT_USE_ENCRYPTION_CLAUSE](#); SQLSTATE: [HY000](#)

Message: ENCRYPTION clause is not valid for %s tablespace.
 - Error number: [3834](#); Symbol: [ER_INVALID_MULTIPLE_CLAUSES](#); SQLSTATE: [HY000](#)

Message: Multiple %s clauses
 - Error number: [3835](#); Symbol: [ER_UNSUPPORTED_USE_OF_GRANT_AS](#); SQLSTATE: [HY000](#)

Message: GRANT ... AS is currently supported only for global privileges.

-
- Error number: [3836](#); Symbol: [ER_UKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_AS](#); SQLSTATE: [HY000](#)

Message: Either some of the authorization IDs in the AS clause are invalid or the current user lacks privileges to execute the statement.

- Error number: [3837](#); Symbol: [ER_DEPENDENT_BY_FUNCTIONAL_INDEX](#); SQLSTATE: [HY000](#)

Message: Column '%s' has a functional index dependency and cannot be dropped or renamed.

- Error number: [3838](#); Symbol: [ER_PLUGIN_NOT_EARLY](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

- Error number: [3839](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH](#); SQLSTATE: [HY000](#)

Message: Redo log archiving start prohibits path name in 'subdir' argument

- Error number: [3840](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Redo log archiving start timed out

- Error number: [3841](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID](#); SQLSTATE: [HY000](#)

Message: Server variable 'innodb_redo_log_archive_dirs' is NULL or empty

- Error number: [3842](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Label '%s' not found in server variable 'innodb_redo_log_archive_dirs'

- Error number: [3843](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY](#); SQLSTATE: [HY000](#)

Message: Directory is empty after label '%s' in server variable 'innodb_redo_log_archive_dirs'

- Error number: [3844](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR](#); SQLSTATE: [HY000](#)

Message: Redo log archive directory '%s' does not exist or is not a directory

- Error number: [3845](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH](#); SQLSTATE: [HY000](#)

Message: Redo log archive directory '%s' is in, under, or over server directory '%s' - '%s'

- Error number: [3846](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS](#); SQLSTATE: [HY000](#)

Message: Redo log archive directory '%s' is accessible to all OS users

- Error number: [3847](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE](#); SQLSTATE: [HY000](#)

Message: Cannot create redo log archive file '%s' (OS errno: %d - %s)

- Error number: [3848](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE](#); SQLSTATE: [HY000](#)

Message: Redo log archiving has been started on '%s' - Call innodb_redo_log_archive_stop() first

- Error number: [3849](#); Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE](#); SQLSTATE: [HY000](#)

Message: Redo log archiving is not active

- Error number: 3850; Symbol: ER_INNODB_REDO_LOG_ARCHIVE_FAILED; SQLSTATE: HY000

Message: Redo log archiving failed: %s

- Error number: 3851; Symbol: ER_INNODB_REDO_LOG_ARCHIVE_SESSION; SQLSTATE: HY000

Message: Redo log archiving has not been started by this session

- Error number: 3852; Symbol: ER_STD_REGEX_ERROR; SQLSTATE: HY000

Message: Regex error: %s in function %s.

- Error number: 3853; Symbol: ER_INVALID_JSON_TYPE; SQLSTATE: 22032

Message: Invalid JSON type in argument %u to function %s; an %s is required.

- Error number: 3854; Symbol: ER_CANNOT_CONVERT_STRING; SQLSTATE: HY000

Message: Cannot convert string '%s' from %s to %s

- Error number: 3855; Symbol: ER_DEPENDENT_BY_PARTITION_FUNC; SQLSTATE: HY000

Message: Column '%s' has a partitioning function dependency and cannot be dropped or renamed.

- Error number: 3856; Symbol: ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT; SQLSTATE: HY000

Message: AUTO_INCREMENT support for FLOAT/DOUBLE columns is deprecated and will be removed in a future release. Consider removing AUTO_INCREMENT from column '%s'.

- Error number: 3857; Symbol: ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP; SQLSTATE: HY000

Message: Cannot stop the replica SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.

- Error number: 3858; Symbol: ER_WARN_DEPRECATED_FLOAT_DIGITS; SQLSTATE: HY000

Message: Specifying number of digits for floating point data types is deprecated and will be removed in a future release.

- Error number: 3859; Symbol: ER_WARN_DEPRECATED_FLOAT_UNSIGNED; SQLSTATE: HY000

Message: UNSIGNED for decimal and floating point data types is deprecated and support for it will be removed in a future release.

- Error number: 3860; Symbol: ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH; SQLSTATE: HY000

Message: Integer display width is deprecated and will be removed in a future release.

- Error number: 3861; Symbol: ER_WARN_DEPRECATED_ZEROFILL; SQLSTATE: HY000

Message: The ZEROFILL attribute is deprecated and will be removed in a future release. Use the LPAD function to zero-pad numbers, or store the formatted numbers in a CHAR column.

- Error number: 3862; Symbol: ER_CLONE_DONOR; SQLSTATE: HY000

Message: Clone Donor Error: %s.

- Error number: 3863; Symbol: ER_CLONE_PROTOCOL; SQLSTATE: HY000

Message: Clone received unexpected response from Donor : %s.

- Error number: 3864; Symbol: ER_CLONE_DONOR_VERSION; SQLSTATE: HY000

Message: Clone Donor MySQL version: %s is different from Recipient MySQL version %s.

- Error number: 3865; Symbol: ER_CLONE_OS; SQLSTATE: HY000

Message: Clone Donor OS: %s is different from Recipient OS: %s.

- Error number: 3866; Symbol: ER_CLONE_PLATFORM; SQLSTATE: HY000

Message: Clone Donor platform: %s is different from Recipient platform: %s.

- Error number: 3867; Symbol: ER_CLONE_CHARSET; SQLSTATE: HY000

Message: Clone Donor collation: %s is unavailable in Recipient.

- Error number: 3868; Symbol: ER_CLONE_CONFIG; SQLSTATE: HY000

Message: Clone Configuration %s: Donor value: %s is different from Recipient value: %s.

- Error number: 3869; Symbol: ER_CLONE_SYS_CONFIG; SQLSTATE: HY000

Message: Clone system configuration: %s

- Error number: 3870; Symbol: ER_CLONE_PLUGIN_MATCH; SQLSTATE: HY000

Message: Clone Donor plugin %s is not active in Recipient.

- Error number: 3871; Symbol: ER_CLONE_LOOPBACK; SQLSTATE: HY000

Message: Clone cannot use loop back connection while cloning into current data directory.

- Error number: 3872; Symbol: ER_CLONE_ENCRYPTION; SQLSTATE: HY000

Message: Clone needs SSL connection for encrypted table.

- Error number: 3873; Symbol: ER_CLONE_DISK_SPACE; SQLSTATE: HY000

Message: Clone estimated database size is %s. Available space %s is not enough.

- Error number: 3874; Symbol: ER_CLONE_IN_PROGRESS; SQLSTATE: HY000

Message: Concurrent clone in progress. Please try after clone is complete.

- Error number: 3875; Symbol: ER_CLONE_DISALLOWED; SQLSTATE: HY000

Message: The clone operation cannot be executed when %s.

- Error number: 3876; Symbol: ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER; SQLSTATE: HY000

Message: Cannot grant roles to an anonymous user.

- Error number: 3877; Symbol: ER_SECONDARY_ENGINE_PLUGIN; SQLSTATE: HY000

Message: %s

- Error number: 3878; Symbol: ER_SECOND_PASSWORD_CANNOT_BE_EMPTY; SQLSTATE: HY000

Message: Empty password can not be retained as second password for user '%s'@'%s'.

- Error number: 3879; Symbol: ER_DB_ACCESS_DENIED; SQLSTATE: HY000

Message: Access denied for AuthId '%s'@'%s' to database '%s'.

- Error number: 3880; Symbol: [ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#); SQLSTATE: HY000
Message: Cannot set mandatory_roles: AuthId '%s'@'%s' has '%s' privilege.
- Error number: 3881; Symbol: [ER_DA_RPL_GTID_TABLE_CANNOT_OPEN](#); SQLSTATE: HY000
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.
- Error number: 3882; Symbol: [ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT](#); SQLSTATE: SU001
Message: The geometry passed to function %s is in SRID 0, which doesn't specify a length unit. Can't convert to '%s'.
- Error number: 3883; Symbol: [ER_DA_PLUGIN_INSTALL_ERROR](#); SQLSTATE: HY000
Message: Error installing plugin '%s': %s
- Error number: 3884; Symbol: [ER_NO_SESSION_TEMP](#); SQLSTATE: HY000
Message: Storage engine could not allocate temporary tablespace for this session.
- Error number: 3885; Symbol: [ER_DA_UNKNOWN_ERROR_NUMBER](#); SQLSTATE: HY000
Message: Got unknown error: %d
- Error number: 3886; Symbol: [ER_COLUMN_CHANGE_SIZE](#); SQLSTATE: HY000
Message: Could not change column '%s' of table '%s'. The resulting size of index '%s' would exceed the max key length of %d bytes.
- Error number: 3887; Symbol: [ER_REGEXP_INVALID_CAPTURE_GROUP_NAME](#); SQLSTATE: HY000
Message: A capture group has an invalid name.
- Error number: 3888; Symbol: [ER_DA_SSL_LIBRARY_ERROR](#); SQLSTATE: HY000
Message: Failed to set up SSL because of the following SSL library error: %s
- Error number: 3889; Symbol: [ER_SECONDARY_ENGINE](#); SQLSTATE: HY000
Message: Secondary engine operation failed. %s.
- Error number: 3890; Symbol: [ER_SECONDARY_ENGINE_DDL](#); SQLSTATE: HY000
Message: You cannot perform DDLs on a table that has a secondary engine defined.
- Error number: 3891; Symbol: [ER_INCORRECT_CURRENT_PASSWORD](#); SQLSTATE: HY000
Message: Incorrect current password. Specify the correct password which has to be replaced.
- Error number: 3892; Symbol: [ER_MISSING_CURRENT_PASSWORD](#); SQLSTATE: HY000
Message: Current password needs to be specified in the REPLACE clause in order to change it.
- Error number: 3893; Symbol: [ER_CURRENT_PASSWORD_NOT_REQUIRED](#); SQLSTATE: HY000
Message: Do not specify the current password while changing it for other users.
- Error number: 3894; Symbol: [ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE](#); SQLSTATE: HY000

Message: Current password can not be retained for user '%s'@'%s' because authentication plugin is being changed.

- Error number: [3895](#); Symbol: [ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED](#); SQLSTATE: [HY000](#)

Message: Current password can not be retained for user '%s'@'%s' because new password is empty.

- Error number: [3896](#); Symbol: [ER_PARTIAL_REVOKES_EXIST](#); SQLSTATE: [HY000](#)

Message: At least one partial revoke exists on a database. The system variable '@@partial_revokes' must be set to ON.

- Error number: [3897](#); Symbol: [ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE](#); SQLSTATE: [HY000](#)

Message: AuthId '%s'@'%s' is set as mandatory_roles. Cannot grant the '%s' privilege.

- Error number: [3898](#); Symbol: [ER_XA_REPLICATION_FILTERS](#); SQLSTATE: [HY000](#)

Message: The use of replication filters with XA transactions is not supported, and can lead to an undefined state in the replica.

- Error number: [3899](#); Symbol: [ER_UNSUPPORTED_SQL_MODE](#); SQLSTATE: [HY000](#)

Message: sql_mode=0x%08x is not supported.

- Error number: [3900](#); Symbol: [ER_REGEX_INVALID_FLAG](#); SQLSTATE: [HY000](#)

Message: Invalid match mode flag in regular expression.

- Error number: [3901](#); Symbol: [ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS](#); SQLSTATE: [HY000](#)

Message: '%s' privilege for database '%s' exists both as partial revoke and mysql.db simultaneously. It could mean that the 'mysql' schema is corrupted.

- Error number: [3902](#); Symbol: [ER_UNIT_NOT_FOUND](#); SQLSTATE: [SU001](#)

Message: There's no unit of measure named '%s'.

- Error number: [3903](#); Symbol: [ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX](#); SQLSTATE: [22018](#)

Message: Invalid JSON value for CAST for functional index '%s'.

- Error number: [3904](#); Symbol: [ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX](#); SQLSTATE: [22003](#)

Message: Out of range JSON value for CAST for functional index '%s'.

- Error number: [3905](#); Symbol: [ER_EXCEEDED_MV_KEYS_NUM](#); SQLSTATE: [HY000](#)

Message: Exceeded max number of values per record for multi-valued index '%s' by %u value(s).

- Error number: [3906](#); Symbol: [ER_EXCEEDED_MV_KEYS_SPACE](#); SQLSTATE: [HY000](#)

Message: Exceeded max total length of values per record for multi-valued index '%s' by %u bytes.

- Error number: [3907](#); Symbol: [ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG](#); SQLSTATE: [22001](#)

Message: Data too long for functional index '%s'.

-
- Error number: [3908](#); Symbol: [ER_WRONG_MVI_VALUE](#); SQLSTATE: [HY000](#)
Message: Cannot store an array or an object in a scalar key part of the index '%s'.
 - Error number: [3909](#); Symbol: [ER_WARN_FUNC_INDEX_NOT_APPLICABLE](#); SQLSTATE: [HY000](#)
Message: Cannot use functional index '%s' due to type or collation conversion.
 - Error number: [3910](#); Symbol: [ER_GRP_RPL_UDF_ERROR](#); SQLSTATE: [HY000](#)
Message: The function '%s' failed. %s
 - Error number: [3911](#); Symbol: [ER_UPDATE_GTID_PURGED_WITH_GR](#); SQLSTATE: [HY000](#)
Message: Cannot update GTID_PURGED with the Group Replication plugin running
 - Error number: [3912](#); Symbol: [ER_GROUPING_ON_TIMESTAMP_IN_DST](#); SQLSTATE: [HY000](#)
Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.
 - Error number: [3913](#); Symbol: [ER_TABLE_NAME_CAUSES_TOO_LONG_PATH](#); SQLSTATE: [HY000](#)
Message: Long database name and identifier for object resulted in a path length too long for table '%s'. Please check the path limit for your OS.
 - Error number: [3914](#); Symbol: [ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE](#); SQLSTATE: [HY000](#)
Message: Request ignored for '%s'@'%s'. Role needed to perform operation: '%s'
 - Error number: [3916](#); Symbol: [ER_DA_GRP_RPL_STARTED_AUTO_REJOIN](#); SQLSTATE: [HY000](#)
Message: Started auto-rejoin procedure attempt %lu of %lu
 - Error number: [3917](#); Symbol: [ER_SYSVAR_CHANGE_DURING_QUERY](#); SQLSTATE: [HY000](#)
Message: A plugin was loaded or unloaded during a query, a system variable table was changed.
 - Error number: [3918](#); Symbol: [ER_GLOBSTAT_CHANGE_DURING_QUERY](#); SQLSTATE: [HY000](#)
Message: A plugin was loaded or unloaded during a query, a global status variable was changed.
 - Error number: [3919](#); Symbol: [ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE](#); SQLSTATE: [HY000](#)
Message: The START GROUP_REPLICATION command failed to start its message service.
 - Error number: [3920](#); Symbol: [ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT](#); SQLSTATE: [HY000](#)
Message: Invalid SOURCE_COMPRESSION_ALGORITHMS '%s' for channel '%s'.
 - Error number: [3921](#); Symbol: [ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT](#); SQLSTATE: [HY000](#)
Message: Invalid SOURCE_ZSTD_COMPRESSION_LEVEL %u for channel '%s'.
 - Error number: [3922](#); Symbol: [ER_WRONG_COMPRESSION_ALGORITHM_CLIENT](#); SQLSTATE: [HY000](#)
Message: Invalid compression algorithm '%s'.
 - Error number: [3923](#); Symbol: [ER_WRONG_COMPRESSION_LEVEL_CLIENT](#); SQLSTATE: [HY000](#)
Message: Invalid zstd compression level for algorithm '%s'.

-
- Error number: [3924](#); Symbol: [ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT](#); SQLSTATE: [HY000](#)
Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.
 - Error number: [3925](#); Symbol: [ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS](#); SQLSTATE: [HY000](#)
Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to ``@%s`, but anonymous users are disallowed for PRIVILEGE_CHECKS_USER.
 - Error number: [3926](#); Symbol: [ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)
Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this is not an existing user.
 - Error number: [3927](#); Symbol: [ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT](#); SQLSTATE: [HY000](#)
Message: Invalid, corrupted PRIVILEGE_CHECKS_USER was found in the replication configuration repository for channel '%s'. Use CHANGE REPLICATION SOURCE TO PRIVILEGE_CHECKS_USER to correct the configuration.
 - Error number: [3928](#); Symbol: [ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV](#); SQLSTATE: [HY000](#)
Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this user does not have REPLICATION_APPLIER privilege.
 - Error number: [3929](#); Symbol: [ER_WARN_DA_PRIVILEGE_NOT_REGISTERED](#); SQLSTATE: [HY000](#)
Message: Dynamic privilege '%s' is not registered with the server.
 - Error number: [3930](#); Symbol: [ER_CLIENT_KEYRING_UDF_KEY_INVALID](#); SQLSTATE: [HY000](#)
Message: Function '%s' failed because key is invalid.
 - Error number: [3931](#); Symbol: [ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID](#); SQLSTATE: [HY000](#)
Message: Function '%s' failed because key type is invalid.
 - Error number: [3932](#); Symbol: [ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Function '%s' failed because key length is too long.
 - Error number: [3933](#); Symbol: [ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Function '%s' failed because key type is too long.
 - Error number: [3934](#); Symbol: [ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT](#); SQLSTATE: [HY000](#)
Message: %s.
 - Error number: [3935](#); Symbol: [ER_DA_UDF_INVALID_CHARSET_SPECIFIED](#); SQLSTATE: [HY000](#)
Message: Invalid character set '%s' was specified. It must be either character set name or collation name as supported by server.
 - Error number: [3936](#); Symbol: [ER_DA_UDF_INVALID_CHARSET](#); SQLSTATE: [HY000](#)

Message: Invalid character set '%s' was specified. It must be a character set name as supported by server.

- Error number: 3937; Symbol: `ER_DA_UDF_INVALID_COLLATION`; SQLSTATE: `HY000`

Message: Invalid collation '%s' was specified. It must be a collation name as supported by server.

- Error number: 3938; Symbol: `ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE`; SQLSTATE: `HY000`

Message: Invalid extension argument type '%s' was specified. Refer the MySQL manual for the valid UDF extension arguments type.

- Error number: 3939; Symbol: `ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME`; SQLSTATE: `HY000`

Message: Table has multiple constraints with the name '%s'. Please use constraint specific '%s' clause.

- Error number: 3940; Symbol: `ER_CONSTRAINT_NOT_FOUND`; SQLSTATE: `HY000`

Message: Constraint '%s' does not exist.

- Error number: 3941; Symbol: `ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Altering constraint enforcement is not supported for the constraint '%s'. Enforcement state alter is not supported for the PRIMARY, UNIQUE and FOREIGN KEY type constraints.

- Error number: 3942; Symbol: `ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS`; SQLSTATE: `HY000`

Message: Each row of a VALUES clause must have at least one column, unless when used as source in an INSERT statement.

- Error number: 3943; Symbol: `ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT`; SQLSTATE: `HY000`

Message: A VALUES clause cannot use DEFAULT values, unless used as a source in an INSERT statement.

- Error number: 3944; Symbol: `ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT`; SQLSTATE: `HY000`

Message: The query does not comply with variable `require_row_format` restrictions.

- Error number: 3945; Symbol: `ER_REQUIRE_ROW_FORMAT_INVALID_VALUE`; SQLSTATE: `HY000`

Message: The requested value %s is invalid for `REQUIRE_ROW_FORMAT`, must be either 0 or 1.

- Error number: 3946; Symbol: `ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY`; SQLSTATE: `HY000`

Message: Failed to acquire lock on user management service, unable to determine if role '%s'@'%s' is mandatory

- Error number: 3947; Symbol: `ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST`; SQLSTATE: `HY000`

Message: Failed to acquire lock on user management service, unable to fetch mandatory role list

- Error number: 3948; Symbol: `ER_CLIENT_LOCAL_FILES_DISABLED`; SQLSTATE: `42000`

Message: Loading local data is disabled; this must be enabled on both the client and server sides

- Error number: 3949; Symbol: [ER_IMP_INCOMPATIBLE_CFG_VERSION](#); SQLSTATE: [HY000](#)

Message: Failed to import %s because the CFG file version (%u) is not compatible with the current version (%u)

- Error number: 3950; Symbol: [ER_DA_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory

- Error number: 3951; Symbol: [ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET](#); SQLSTATE: [HY000](#)

Message: Character set can be set only for the UDF argument type STRING.

- Error number: 3952; Symbol: [ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET](#); SQLSTATE: [HY000](#)

Message: Character set can be set only for the UDF RETURN type STRING.

- Error number: 3953; Symbol: [ER_MULTIPLE_INT0 CLAUSES](#); SQLSTATE: [HY000](#)

Message: Multiple INTO clauses in one query block.

- Error number: 3954; Symbol: [ER_MISPLACED_INT0](#); SQLSTATE: [HY000](#)

Message: Misplaced INTO clause, INTO is not allowed inside subqueries, and must be placed at end of UNION clauses.

- Error number: 3955; Symbol: [ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins.

- Error number: 3956; Symbol: [ER_WARN_DEPRECATED_YEAR_UNSIGNED](#); SQLSTATE: [HY000](#)

Message: UNSIGNED for the YEAR data type is deprecated and support for it will be removed in a future release.

- Error number: 3957; Symbol: [ER_CLONE_NETWORK_PACKET](#); SQLSTATE: [HY000](#)

Message: Clone needs max_allowed_packet value to be %u or more. Current value is %u

- Error number: 3958; Symbol: [ER_SDI_OPERATION_FAILED_MISSING_RECORD](#); SQLSTATE: [HY000](#)

Message: Failed to %s sdi for %s.%s in %s due to missing record.

- Error number: 3959; Symbol: [ER_DEPENDENT_BY_CHECK_CONSTRAINT](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' uses column '%s', hence column cannot be dropped or renamed.

- Error number: 3960; Symbol: [ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed while Group Replication is running; run STOP GROUP_REPLICATION first

- Error number: 3961; Symbol: [ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY](#); SQLSTATE: [HY000](#)

Message: Specifying an ON EMPTY clause after the ON ERROR clause in a JSON_TABLE column definition is deprecated syntax and will be removed in a future release. Specify ON EMPTY before ON ERROR instead.

- Error number: 3962; Symbol: ER_WARN_DEPRECATED_INNER_INT0; SQLSTATE: HY000

Message: The INTO clause is deprecated inside query blocks of query expressions and will be removed in a future release. Please move the INTO clause to the end of statement instead.

- Error number: 3963; Symbol: ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL; SQLSTATE: HY000

Message: The VALUES function is deprecated and will be removed in a future release. It always returns NULL in this context. If you meant to access a value from the VALUES clause of the INSERT statement, consider using an alias (INSERT INTO ... VALUES (...) AS alias) and reference alias.col instead of VALUES(col) in the ON DUPLICATE KEY UPDATE clause.

- Error number: 3964; Symbol: ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS; SQLSTATE: HY000

Message: SQL_CALC_FOUND_ROWS is deprecated and will be removed in a future release. Consider using two separate queries instead.

- Error number: 3965; Symbol: ER_WARN_DEPRECATED_FOUND_ROWS; SQLSTATE: HY000

Message: FOUND_ROWS() is deprecated and will be removed in a future release. Consider using COUNT(*) instead.

- Error number: 3966; Symbol: ER_MISSING_JSON_VALUE; SQLSTATE: 22035

Message: No value was found by '%s' on the specified path.

- Error number: 3967; Symbol: ER_MULTIPLE_JSON_VALUES; SQLSTATE: 22034

Message: More than one value was found by '%s' on the specified path.

- Error number: 3968; Symbol: ER_HOSTNAME_TOO_LONG; SQLSTATE: HY000

Message: Hostname cannot be longer than %d characters.

- Error number: 3970; Symbol: ER_GROUP_REPLICATION_USER_EMPTY_MSG; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the username provided for recovery channel is empty.

- Error number: 3971; Symbol: ER_GROUP_REPLICATION_USER_MANDATORY_MSG; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the USER option was not provided with PASSWORD for recovery channel.

- Error number: 3972; Symbol: ER_GROUP_REPLICATION_PASSWORD_LENGTH; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the password provided for the recovery channel exceeds the maximum length of 32 characters.

- Error number: 3973; Symbol: ER_SUBQUERY_TRANSFORM_REJECTED; SQLSTATE: HY000

Message: Statement requires a transform of a subquery to a non-SET operation (like IN2EXISTS, or subquery-to-LATERAL-derived-table). This is not allowed with optimizer switch 'subquery_to_derived' on.

-
- Error number: 3974; Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT`; SQLSTATE: `HY000`

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port).

- Error number: 3975; Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID`; SQLSTATE: `HY000`

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

- Error number: 3976; Symbol: `ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART`; SQLSTATE: `HY000`

Message: Variable '%s' cannot be set to the value of '%s'. %s

- Error number: 3977; Symbol: `ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION`; SQLSTATE: `HY000`

Message: Only BINLOG INSERT, COMMIT and ROLLBACK statements are allowed after CREATE TABLE with START TRANSACTION statement.

- Error number: 3978; Symbol: `ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT`; SQLSTATE: `HY000`

Message: Foreign key creation is not allowed with CREATE TABLE as SELECT and CREATE TABLE with START TRANSACTION statement.

- Error number: 3979; Symbol: `ER_NOT_ALLOWED_WITH_START_TRANSACTION`; SQLSTATE: `HY000`

Message: START TRANSACTION clause cannot be used %s

- Error number: 3980; Symbol: `ER_INVALID_JSON_ATTRIBUTE`; SQLSTATE: `HY000`

Message: Invalid json attribute, error: "%s" at pos %u: '%s'

- Error number: 3981; Symbol: `ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Storage engine '%s' does not support ENGINE_ATTRIBUTE.

- Error number: 3982; Symbol: `ER_INVALID_USER_ATTRIBUTE_JSON`; SQLSTATE: `HY000`

Message: The user attribute must be a valid JSON object

- Error number: 3983; Symbol: `ER_INNODB_REDO_DISABLED`; SQLSTATE: `HY000`

Message: Cannot perform operation as InnoDB redo logging is disabled. Please retry after enabling redo log with ALTER INSTANCE

- Error number: 3984; Symbol: `ER_INNODB_REDO_ARCHIVING_ENABLED`; SQLSTATE: `HY000`

Message: Cannot perform operation as InnoDB is archiving redo log. Please retry after stopping redo archive by invoking `innodb_redo_log_archive_stop()`

- Error number: 3985; Symbol: `ER_MDL_OUT_OF_RESOURCES`; SQLSTATE: `HY000`

Message: Not enough resources to complete lock request.

-
- Error number: [3986](#); Symbol: [ER_IMPLICIT_COMPARISON_FOR_JSON](#); SQLSTATE: [HY000](#)
Message: Evaluating a JSON value in SQL boolean context does an implicit comparison against JSON integer 0; if this is not what you want, consider converting JSON to a SQL numeric type with JSON_VALUE RETURNING
 - Error number: [3987](#); Symbol: [ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET](#); SQLSTATE: [HY000](#)
Message: The function %s does not support the character set '%s'.
 - Error number: [3988](#); Symbol: [ER_IMPOSSIBLE_STRING_CONVERSION](#); SQLSTATE: [HY000](#)
Message: Conversion from collation %s into %s impossible for %s
 - Error number: [3989](#); Symbol: [ER_SCHEMA_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: Schema '%s' is in read only mode.
 - Error number: [3990](#); Symbol: [ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)
Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1 can only be set when @@GLOBAL.GTID_MODE = ON.
 - Error number: [3991](#); Symbol: [ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF](#); SQLSTATE: [HY000](#)
Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1 can only be set when SOURCE_AUTO_POSITION option of CHANGE REPLICATION SOURCE TO is enabled.
 - Error number: [3992](#); Symbol: [ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF](#); SQLSTATE: [HY000](#)
Message: The @@GLOBAL.GTID_MODE = %s cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.
 - Error number: [3993](#); Symbol: [ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF](#); SQLSTATE: [HY000](#)
Message: CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 0 cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.
 - Error number: [3994](#); Symbol: [ER_INVALID_PARAMETER_USE](#); SQLSTATE: [HY000](#)
Message: Invalid use of parameters in '%s'
 - Error number: [3995](#); Symbol: [ER_CHARACTER_SET_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Character set '%s' cannot be used in conjunction with '%s' in call to %s.
 - Error number: [3996](#); Symbol: [ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Changing %s not supported on this platform. Falling back to the default.
 - Error number: [3997](#); Symbol: [ER_INVALID_TIME_ZONE_INTERVAL](#); SQLSTATE: [HY000](#)
Message: Invalid time zone interval: '%s'
 - Error number: [3998](#); Symbol: [ER_INVALID_CAST](#); SQLSTATE: [HY000](#)

Message: Cannot cast value to %s.

- Error number: 3999; Symbol: [ER_HYPERGRAPH_NOT_SUPPORTED_YET](#); SQLSTATE: 42000

Message: The hypergraph optimizer does not yet support '%s'

- Error number: 4001; Symbol: [ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED](#); SQLSTATE: HY000

Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance_schema.error_log.

- Error number: 4002; Symbol: [ER_DA_ERROR_LOG_TABLE_DISABLED](#); SQLSTATE: HY000

Message: None of the log-sinks selected in @@global.log_error_services supports writing to the performance schema. The server will not be able to make the current runs' error events available in performance_schema.error_log. To change this, add a log-sink that supports the performance schema to @@global.log_error_services.

- Error number: 4003; Symbol: [ER_DA_ERROR_LOG_MULTIPLE_FILTERS](#); SQLSTATE: HY000

Message: @@global.log_error_services lists more than one log-filter service. This is discouraged as it will make it hard to understand which rule in which filter affected a log-event.

- Error number: 4004; Symbol: [ER_DA_CANT_OPEN_ERROR_LOG](#); SQLSTATE: HY000

Message: Could not open file '%s' for error logging%s%s

- Error number: 4005; Symbol: [ER_USER_REFERENCED_AS_DEFINER](#); SQLSTATE: HY000

Message: User %s is referenced as a definer account in %s.

- Error number: 4006; Symbol: [ER_CANNOT_USER_REFERENCED_AS_DEFINER](#); SQLSTATE: HY000

Message: Operation %s failed for %s as it is referenced as a definer account in %s.

- Error number: 4007; Symbol: [ER_REGEX_NUMBER_TOO_BIG](#); SQLSTATE: HY000

Message: Decimal number in regular expression is too large.

- Error number: 4008; Symbol: [ER_SPVAR_NONINTEGER_TYPE](#); SQLSTATE: HY000

Message: The variable "%s" has a non-integer based type

- Error number: 4009; Symbol: [WARN_UNSUPPORTED_ACL_TABLES_READ](#); SQLSTATE: HY000

Message: Reads with serializable isolation/SELECT FOR SHARE are not supported for ACL tables.

- Error number: 4010; Symbol: [ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL](#); SQLSTATE: HY000

Message: The statement is unsafe because it updates a table depending on ACL table read operation. As storage engine row locks are skipped for ACL table, it may not have same effect on source and replica.

- Error number: 4011; Symbol: [ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT](#); SQLSTATE: HY000

Message: STOP REPLICA command execution is incomplete: Replica Monitor thread got the stop signal, thread is busy, Monitor thread will stop once the current task is complete.

- Error number: 4012; Symbol: [ER_STARTING_REPLICA_MONITOR_IO_THREAD](#); SQLSTATE: HY000

Message: The Replica Monitor thread failed to start.

- Error number: [4013](#); Symbol: [ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NOT_ON](#); SQLSTATE: [HY000](#)

Message: Replication cannot start with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` as this server uses `@@GLOBAL.GTID_MODE <> ON`.

- Error number: [4014](#); Symbol: [ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPOSITION](#); SQLSTATE: [HY000](#)

Message: The options `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` and `SOURCE_AUTO_POSITION = 1` cannot be used together.

- Error number: [4015](#); Symbol: [ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: `CHANGE REPLICATION SOURCE TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` cannot be executed because `@@GLOBAL.GTID_MODE <> ON`.

- Error number: [4016](#); Symbol: [ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: The value of `sql_replica_skip_counter` will only take effect for channels running with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.

- Error number: [4017](#); Symbol: [ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID](#); SQLSTATE: [HY000](#)

Message: Using `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` creates limitations on the replication topology - you cannot fail over between downstream and upstream servers. Only use this option if it is not possible to enable GTIDs on the source, for instance, because of lack of permissions. If possible, use the procedure for enabling GTID transactions online instead, as described in the documentation.

- Error number: [4019](#); Symbol: [ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID](#); SQLSTATE: [HY000](#)

Message: The `SQL_AFTER_GTIDS` or `SQL_BEFORE_GTIDS` clauses for `START REPLICA` cannot be used when the replication channel is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`.

- Error number: [4020](#); Symbol: [ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME](#); SQLSTATE: [HY000](#)

Message: Replication '`%s`' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` where the UUID value is equal to the `group_replication_group_name`

- Error number: [4021](#); Symbol: [ER_CANT_USE_SAME_UUID_AS_GROUP_NAME](#); SQLSTATE: [HY000](#)

Message: `CHANGE REPLICATION SOURCE TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` cannot be executed because the UUID value is equal to the `group_replication_group_name`.

-
- Error number: [4022](#); Symbol: [ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING](#); SQLSTATE: [HY000](#)

Message: The group_replication_recovery channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.
 - Error number: [4023](#); Symbol: [ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE](#); SQLSTATE: [HY000](#)

Message: AUTOEXTEND_SIZE should be a multiple of %uM
 - Error number: [4024](#); Symbol: [ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: InnoDB: "%s" not allowed with general tablespaces
 - Error number: [4025](#); Symbol: [ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: AUTOEXTEND_SIZE value should be between %uM and %uM
 - Error number: [4026](#); Symbol: [ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE](#); SQLSTATE: [HY000](#)

Message: AUTOEXTEND_SIZE clause is not valid for %s tablespace.
 - Error number: [4027](#); Symbol: [ER_ROLE_GRANTED_TO_ITSELF](#); SQLSTATE: [HY000](#)

Message: User account %s is directly or indirectly granted to the role %s. The GRANT would create a loop
 - Error number: [4028](#); Symbol: [ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN](#); SQLSTATE: [HY000](#)

Message: A table must have at least one visible column.
 - Error number: [4029](#); Symbol: [ER_INNODB_COMPRESSION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Compression failed with the following error : %s
 - Error number: [4030](#); Symbol: [ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE](#); SQLSTATE: [HY000](#)

Message: The parameter network_namespace is reserved for future use. Please use the CHANGE REPLICATION SOURCE command to set channel network_namespace parameter.
 - Error number: [4031](#); Symbol: [ER_CLIENT_INTERACTION_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: The client was disconnected by the server because of inactivity. See wait_timeout and interactive_timeout for configuring this behavior.
 - Error number: [4032](#); Symbol: [ER_INVALID_CAST_TO_GEOMETRY](#); SQLSTATE: [22S01](#)

Message: Invalid cast from %s to %s.
 - Error number: [4033](#); Symbol: [ER_INVALID_CAST_POLYGON_RING_DIRECTION](#); SQLSTATE: [22S04](#)

Message: Invalid cast from %s to %s. A polygon ring is in the wrong direction.
 - Error number: [4034](#); Symbol: [ER_GIS_DIFFERENT_SRIDS_AGGREGATION](#); SQLSTATE: [22S05](#)

Message: Arguments to function %s contains geometries with different SRIDs: %u and %u. All geometries must have the same SRID.

-
- Error number: [4035](#); Symbol: [ER_RELOAD_KEYRING_FAILURE](#); SQLSTATE: [HY000](#)
Message: Keyring reload failed. Please check error log for more details.
 - Error number: [4036](#); Symbol: [ER_SDI_GET_KEYS_INVALID_TABLESPACE](#); SQLSTATE: [HY000](#)
Message: Tablespace '%s' is invalid for SDI operations.
 - Error number: [4037](#); Symbol: [ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE](#); SQLSTATE: [HY000](#)
Message: Value too long setting SOURCE_COMPRESSION_ALGORITHMS option to a %d chars long string for channel '%s'.
 - Error number: [4039](#); Symbol: [ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)
Message: CHANGE REPLICATION SOURCE TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group_replication_view_change_uuid.
 - Error number: [4040](#); Symbol: [ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)
Message: Replication '%s' is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> where the UUID value is equal to the group_replication_view_change_uuid
 - Error number: [4041](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Unable to retrieve group_replication_view_change_uuid variable during server checks on replication operations.
 - Error number: [4042](#); Symbol: [ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS](#); SQLSTATE: [HY000](#)
Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero. audit_log_max_size takes precedence and audit_log_prune_seconds is ignored
 - Error number: [4043](#); Symbol: [ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE](#); SQLSTATE: [HY000](#)
Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.
 - Error number: [4044](#); Symbol: [ER_KERBEROS_CREATE_USER](#); SQLSTATE: [HY000](#)
Message: Create/Alter user has failed, Configured user realm as authentication string is empty, Please make sure to configure authentication string as user realm.
 - Error number: [4045](#); Symbol: [ER_INSTALL_PLUGIN_CONFLICT_CLIENT](#); SQLSTATE: [HY000](#)
Message: Cannot install the %s plugin when the %s plugin is installed.
 - Error number: [4046](#); Symbol: [ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED](#); SQLSTATE: [HY000](#)
Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.
 - Error number: [4047](#); Symbol: [ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED](#); SQLSTATE: [HY000](#)

Message: The until clause SQL_AFTER_MTS_GAPS is being used for channel '%s' when GTID_MODE = ON and SOURCE_AUTO_POSITION=1 meaning the server did not compute internally what gaps may exist in the relay log transaction execution. To close any execution gaps use either the SQL_BEFORE_GTIDS or SQL_AFTER_GTIDS until clause.

- Error number: 4048; Symbol: ER_INVALID_ASSIGNMENT_TARGET; SQLSTATE: 42000

Message: Invalid target for assignment in INSERT or UPDATE statement '%s'.

- Error number: 4049; Symbol: ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY; SQLSTATE: HY000

Message: This operation cannot be performed on a Group Replication secondary member, it must be done on the group primary.

- Error number: 4050; Symbol: ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION; SQLSTATE: HY000

Message: Unable to propagate the SOURCE_CONNECTION_AUTO_FAILOVER value for channel '%s' to group replication members. Please retry the operation.

- Error number: 4051; Symbol: ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON; SQLSTATE: HY000

Message: audit_log_format_unix_timestamp is applicable only when audit_log_format = JSON.

- Error number: 4052; Symbol: ER_INVALID_MFA_PLUGIN_SPECIFIED; SQLSTATE: HY000

Message: Invalid plugin "%s" specified as %d factor during "%s".

- Error number: 4053; Symbol: ER_IDENTIFIED_BY_UNSUPPORTED; SQLSTATE: HY000

Message: IDENTIFIED BY clause during "%s" not supported for plugin "%s".

- Error number: 4054; Symbol: ER_INVALID_PLUGIN_FOR_REGISTRATION; SQLSTATE: HY000

Message: This operation is not supported for plugin "%s".

- Error number: 4055; Symbol: ER_PLUGIN_REQUIRES_REGISTRATION; SQLSTATE: HY000

Message: Authentication plugin requires registration. Please refer ALTER USER syntax or set --register-factor command line option to do registration.

- Error number: 4056; Symbol: ER_MFA_METHOD_EXISTS; SQLSTATE: HY000

Message: %d factor authentication method exists. Please do ALTER USER... DROP %d factor before doing this operation OR do ALTER USER... MODIFY %d factor... to modify existing %d factor authentication method.

- Error number: 4057; Symbol: ER_MFA_METHOD_NOT_EXISTS; SQLSTATE: HY000

Message: %d factor authentication method doesn't exist. Please do ALTER USER... ADD %d factor... before doing this operation.

- Error number: 4058; Symbol: ER_AUTHENTICATION_POLICY_MISMATCH; SQLSTATE: HY000

Message: %d factor authentication method does not match against authentication policy. Please refer @@authentication_policy system variable.

- Error number: 4059; Symbol: ER_PLUGIN_REGISTRATION_DONE; SQLSTATE: HY000

Message: The registration for %d factor authentication method is already completed. You cannot perform registration multiple times.

-
- Error number: [4060](#); Symbol: [ER_INVALID_USER_FOR_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: The registration operation is not allowed for user '%s'@'%s'. The operation can only be performed in user's own session.
 - Error number: [4061](#); Symbol: [ER_USER_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Authentication plugin's registration failed.
 - Error number: [4062](#); Symbol: [ER_MFA_METHODS_INVALID_ORDER](#); SQLSTATE: [HY000](#)

Message: %d factor authentication method should be added before %d factor authentication method.
 - Error number: [4063](#); Symbol: [ER_MFA_METHODS_IDENTICAL](#); SQLSTATE: [HY000](#)

Message: Authentication factor should be different.
 - Error number: [4064](#); Symbol: [ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER](#); SQLSTATE: [HY000](#)

Message: The operation "%s" cannot be performed for user '%s'@'%s' configured to connect without a password.
 - Error number: [4065](#); Symbol: [ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY](#); SQLSTATE: [HY000](#)

Message: GTID_ONLY cannot be enabled for replication channel '%s'. You need GTID_MODE = ON, SOURCE_AUTO_POSITION = 1 and REQUIRE_ROW_FORMAT = 1.
 - Error number: [4066](#); Symbol: [ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY](#); SQLSTATE: [HY000](#)

Message: REQUIRE_ROW_FORMAT cannot be disabled for replication channel '%s' when GTID_ONLY=1.
 - Error number: [4067](#); Symbol: [ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY](#); SQLSTATE: [HY000](#)

Message: SOURCE_AUTO_POSITION cannot be disabled for replication channel '%s' when GTID_ONLY=1.
 - Error number: [4068](#); Symbol: [ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS](#); SQLSTATE: [HY000](#)

Message: When disabling GTID_ONLY and SOURCE_AUTO_POSITION FOR CHANNEL '%s' you must provide SOURCE_LOG_FILE and SOURCE_LOG_POS as source positions are invalid.
 - Error number: [4069](#); Symbol: [ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS](#); SQLSTATE: [HY000](#)

Message: When disabling SOURCE_AUTO_POSITION FOR CHANNEL '%s' you must provide SOURCE_LOG_FILE and SOURCE_LOG_POS as source positions are invalid.
 - Error number: [4070](#); Symbol: [ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON](#); SQLSTATE: [HY000](#)

Message: When configuring a group replication channel you must do it when GTID_MODE = ON.
-

-
- Error number: [4071](#); Symbol: [ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON](#); SQLSTATE: [HY000](#)

Message: Replication cannot start%s with GTID_ONLY = 1 as this server uses @@GLOBAL.GTID_MODE <> ON.

- Error number: [4072](#); Symbol: [ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS](#); SQLSTATE: [HY000](#)

Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.

- Error number: [4073](#); Symbol: [ER_DA_SSL_FIPS_MODE_ERROR](#); SQLSTATE: [HY000](#)

Message: SSL fips mode error: %s

- Error number: [4074](#); Symbol: [ER_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: %s=%llu is outside the valid range [%llu,%llu]. %llu will be used.

- Error number: [4075](#); Symbol: [ER_FULLTEXT_WITH_ROLLUP](#); SQLSTATE: [HY000](#)

Message: MATCH does not support ROLLUP columns.

- Error number: [4076](#); Symbol: [ER_REGEXP_MISSING_RESOURCE](#); SQLSTATE: [HY000](#)

Message: Missing locale resource in regular expression library.

- Error number: [4077](#); Symbol: [ER_WARN_REGEXP_USING_DEFAULT](#); SQLSTATE: [HY000](#)

Message: Regular expression library used default (root) locale.

- Error number: [4078](#); Symbol: [ER_REGEXP_MISSING_FILE](#); SQLSTATE: [HY000](#)

Message: Missing data file in regular expression library.

- Error number: [4079](#); Symbol: [ER_WARN_DEPRECATED_COLLATION](#); SQLSTATE: [HY000](#)

Message: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

- Error number: [4080](#); Symbol: [ER_CONCURRENT_PROCEDURE_USAGE](#); SQLSTATE: [HY000](#)

Message: The %s was called when there was already another concurrent call to this procedure. No action was taken. Wait for other calls to %s to finish before retrying.

- Error number: [4081](#); Symbol: [ER_DA_GLOBAL_CONN_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

- Error number: [4082](#); Symbol: [ER_DA_CONN_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

- Error number: [4083](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE_INSTANT](#); SQLSTATE: [HY000](#)

Message: Need to rebuild the table to change column type

-
- Error number: [4084](#); Symbol: [ER_WARN_SF_UDF_NAME_COLLISION](#); SQLSTATE: [HY000](#)
Message: This function '%s' has the same name as a loadable function (UDF). To invoke the stored function, it is necessary to qualify it with the schema name.
 - Error number: [4085](#); Symbol: [ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK](#); SQLSTATE: [HY000](#)
Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.
 - Error number: [4086](#); Symbol: [ER_TOO_MANY_WINDOWS](#); SQLSTATE: [HY000](#)
Message: Too many windows in SELECT: %d. Maximum allowed is %d. Use named windows to share windows between window functions.
 - Error number: [4087](#); Symbol: [ER_MYSQLBACKUP_CLIENT_MSG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [4088](#); Symbol: [ER_COMMENT_CONTAINS_INVALID_STRING](#); SQLSTATE: [HY000](#)
Message: Comment for %s '%s' contains an invalid %s character string: '%s'.
 - Error number: [4089](#); Symbol: [ER_DEFINITION_CONTAINS_INVALID_STRING](#); SQLSTATE: [HY000](#)
Message: Definition of %s '%s.%s' contains an invalid %s character string: '%s'.
 - Error number: [4090](#); Symbol: [ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID_NEXT](#); SQLSTATE: [HY000](#)
Message: Can't execute the given command when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.
 - Error number: [4091](#); Symbol: [ER_XA_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: XA: Temporary tables cannot be accessed inside XA transactions when xa_detach_on_prepare=ON
 - Error number: [4092](#); Symbol: [ER_INNODB_MAX_ROW_VERSION](#); SQLSTATE: [HY000](#)
Message: Maximum row versions reached for table %s. No more columns can be added or dropped instantly. Please use COPY/INPLACE.
 - Error number: [4094](#); Symbol: [ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING](#); SQLSTATE: [HY000](#)
Message: All queries have been blocked while function 'group_replication_set_as_primary()' is executing. Please refer timeout parameter of function 'group_replication_set_as_primary()'.
 - Error number: [4095](#); Symbol: [ER_WARN_DEPRECATED_DATETIME_DELIMITER](#); SQLSTATE: [HY000](#)
Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is deprecated. Prefer the standard '%c'.
 - Error number: [4096](#); Symbol: [ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER](#); SQLSTATE: [HY000](#)
Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is superfluous and is deprecated. Please remove.
 - Error number: [4097](#); Symbol: [ER_CANNOT_PERSIST_SENSITIVE_VARIABLES](#); SQLSTATE: [HY000](#)

Message: Cannot persist SENSITIVE system variable '%s' because keyring component support is unavailable.

- Error number: [4098](#); Symbol: [ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES](#); SQLSTATE: [HY000](#)

Message: SENSITIVE system variable '%s' was persisted without encryption. Consider restarting server with keyring component support to persist SENSITIVE variables securely.

- Error number: [4099](#); Symbol: [ER_WARN_TRG_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: Trigger '%s' already exists on the table '%s'. '%s'.

- Error number: [4100](#); Symbol: [ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE](#); SQLSTATE: [HY000](#)

Message: Trigger '%s'. '%s' already exists on a different table. The 'IF NOT EXISTS' clause is only supported for triggers associated with the same table.

- Error number: [4101](#); Symbol: [ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME_COLLISION](#); SQLSTATE: [HY000](#)

Message: This function '%s' has the same name as a native function. The 'IF NOT EXISTS' clause is not supported while creating a loadable function with the same name as a native function.

- Error number: [4102](#); Symbol: [ER_SET_PASSWORD_AUTH_PLUGIN_ERROR](#); SQLSTATE: [HY000](#)

Message: SET PASSWORD has no significance for user '%s'@'%s' as the authentication method used doesn't store authentication data in the MySQL server. Please consider using ALTER USER instead if you want to change authentication parameters.

- Error number: [4105](#); Symbol: [ER_SRS_INVALID_LATITUDE_OF_ORIGIN](#); SQLSTATE: [SR002](#)

Message: Latitude of origin must be within [-90, 90] degrees, specified in the SRS angular unit.

- Error number: [4106](#); Symbol: [ER_SRS_INVALID_LONGITUDE_OF_ORIGIN](#); SQLSTATE: [SR002](#)

Message: Longitude of origin must be within (-180, 180] degrees, specified in the SRS angular unit.

- Error number: [4107](#); Symbol: [ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT](#); SQLSTATE: [SR002](#)

Message: The spatial reference system definition for SRID %u contains unused projection parameter "%s".

- Error number: [4108](#); Symbol: [ER_GIPK_COLUMN_EXISTS](#); SQLSTATE: [HY000](#)

Message: Failed to generate invisible primary key. Column 'my_row_id' already exists.

- Error number: [4109](#); Symbol: [ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS](#); SQLSTATE: [HY000](#)

Message: Failed to generate invisible primary key. Auto-increment column already exists.

- Error number: [4110](#); Symbol: [ER_GIPK_COLUMN_ALTER_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Altering generated invisible primary key column 'my_row_id' is not allowed.

- Error number: [4111](#); Symbol: [ER_DROP_PK_COLUMN_TO_DROP_GIPK](#); SQLSTATE: [HY000](#)

Message: Please drop primary key column to be able to drop generated invisible primary key.

- Error number: [4112](#); Symbol: [ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR](#); SQLSTATE: [HY000](#)

Message: Generating an invisible primary key for a table created using CREATE TABLE ... SELECT ... is disallowed when binlog_format=STATEMENT. It cannot be guaranteed that the SELECT retrieves rows in the same order on source and replica. Therefore, it cannot be guaranteed that the value generated for the generated implicit primary key column will be the same on source and replica for all rows. Use binlog_format=ROW or MIXED to execute this statement.

- Error number: [4114](#); Symbol: [ER_CTE_RECURSIVE_NOT_UNION](#); SQLSTATE: [HY000](#)

Message: Recursive table reference in EXCEPT or INTERSECT operand is not allowed.

- Error number: [4115](#); Symbol: [ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Error when trying to fetch information from security context object, when trying to connect the server.

- Error number: [4116](#); Symbol: [ER_COMMAND_SERVICE_BACKEND_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in command service backend interface, because of : "%s"

- Error number: [4117](#); Symbol: [ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#); SQLSTATE: [HY000](#)

Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE_CHECKS_USER.

- Error number: [4118](#); Symbol: [ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE](#); SQLSTATE: [HY000](#)

Message: The 'SET GLOBAL group_replication_force_members=%s' command encountered a failure. %s

- Error number: [4119](#); Symbol: [ER_WARN_DEPRECATED_IDENT](#); SQLSTATE: [HY000](#)

Message: Using %s as unquoted identifier is deprecated, please use quotes or rename the identifier.

- Error number: [4120](#); Symbol: [ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: Max number of duplicate rows in INTERSECT ALL exceeded.

- Error number: [4121](#); Symbol: [ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT](#); SQLSTATE: [HY000](#)

Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group

- Error number: [4122](#); Symbol: [ER_BAD_TIMESTAMP_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid timestamp format in %s udf

- Error number: [4123](#); Symbol: [ER_SHAPE_PREDICTION_UDF](#); SQLSTATE: [HY000](#)

Message: SHAPE_PREDICTION UDF %s got error because of %s.

- Error number: [4124](#); Symbol: [ER_SRS_INVALID_HEIGHT](#); SQLSTATE: [SR002](#)

Message: Height parameter must be non negative.

- Error number: [4125](#); Symbol: [ER_SRS_INVALID_SCALING](#); SQLSTATE: [SR002](#)

Message: Scaling parameter must be non negative.

- Error number: [4126](#); Symbol: [ER_SRS_INVALID_ZONE_WIDTH](#); SQLSTATE: [SR002](#)

Message: Zone width parameter must be an integer between 1-60.

- Error number: [4127](#); Symbol: [ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A](#); SQLSTATE: [SR002](#)

Message: Latitude of origin must be +-90 degrees, specified in the SRS angular unit, in Polar Stereographic (variant A) projection method (EPSG:9810).

- Error number: [4128](#); Symbol: [ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION](#); SQLSTATE: [HY000](#)

Message: The client is using a deprecated CLIENT_NO_SCHEMA client option. CLIENT_NO_SCHEMA will be removed in a future release.

- Error number: [4129](#); Symbol: [ER_TABLE_NOT_EMPTY](#); SQLSTATE: [HY000](#)

Message: Table '%s' is not empty.

- Error number: [4130](#); Symbol: [ER_TABLE_NO_PRIMARY_KEY](#); SQLSTATE: [HY000](#)

Message: Table '%s' has no primary key.

- Error number: [4131](#); Symbol: [ER_TABLE_IN_SHARED_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Table '%s' is in a shared tablespace.

- Error number: [4132](#); Symbol: [ER_INDEX_OTHER_THAN_PK](#); SQLSTATE: [HY000](#)

Message: Table '%s' has indexes other than primary key.

- Error number: [4133](#); Symbol: [ER_LOAD_BULK_DATA_UNSORTED](#); SQLSTATE: [HY000](#)

Message: [IN PRIMARY KEY ORDER] specified but data not sorted: '%s'

- Error number: [4134](#); Symbol: [ER_BULK_EXECUTOR_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk executor error: %s

- Error number: [4135](#); Symbol: [ER_BULK_READER_LIBCURL_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Bulk reader failed to initialize libcurl

- Error number: [4136](#); Symbol: [ER_BULK_READER_LIBCURL_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader got libcurl error: %s

- Error number: [4137](#); Symbol: [ER_BULK_READER_SERVER_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error response from server: %ld

- Error number: [4138](#); Symbol: [ER_BULK_READER_COMMUNICATION_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error in communication with source server, check the error log for additional details.

- Error number: [4139](#); Symbol: [ER_BULK_LOAD_DATA_FAILED](#); SQLSTATE: [HY000](#)

Message: Bulk loader failed in Innodb storage engine, check the error log for additional details.

-
- Error number: [4140](#); Symbol: [ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER_BUFFER](#); SQLSTATE: [HY000](#)

Message: CSV column too big for leftover buffer.
 - Error number: [4141](#); Symbol: [ER_BULK_LOADER_COMPONENT_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk loader component error: %s
 - Error number: [4142](#); Symbol: [ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_CLAUSE](#); SQLSTATE: [HY000](#)

Message: The first file being loaded contained less lines than the ignore clause
 - Error number: [4143](#); Symbol: [ER_BULK_PARSER_MISSING_ENCLOSED_BY](#); SQLSTATE: [HY000](#)

Message: Missing ENCLOSED BY character at row %ld in file '%s'.
 - Error number: [4144](#); Symbol: [ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.
 - Error number: [4145](#); Symbol: [ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.
 - Error number: [4146](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT](#); SQLSTATE: [HY000](#)

Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.
 - Error number: [4147](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR](#); SQLSTATE: [HY000](#)

Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.
 - Error number: [4148](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.
 - Error number: [4149](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.
 - Error number: [4150](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after column terminator found at row %ld in file '%s'.
 - Error number: [4151](#); Symbol: [ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.

-
- Error number: [4152](#); Symbol: [ER_LOAD_BULK_DATA_FAILED](#); SQLSTATE: [HY000](#)
Message: LOAD BULK DATA into table '%s' failed: %s
 - Error number: [4153](#); Symbol: [ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'
 - Error number: [4154](#); Symbol: [ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL](#); SQLSTATE: [HY000](#)
Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'
 - Error number: [4155](#); Symbol: [ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR](#); SQLSTATE: [HY000](#)
Message: On a Group Replication channel, setting REQUIRE_TABLE_PRIMARY_KEY_CHECK to 'GENERATE' is not allowed.
 - Error number: [4156](#); Symbol: [ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Cannot change the '%s' system variable in read-only mode.
 - Error number: [4157](#); Symbol: [ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTEDED_MAX_SIZE](#); SQLSTATE: [HY000](#)
Message: Column can't be added or dropped with ALGORITHM=INSTANT as either max possible row size already crosses max permissible row size or may cross it after add. Try ALGORITHM=INPLACE/COPY.
 - Error number: [4158](#); Symbol: [ER_INNODB_INSTANT_ADD_NOT_SUPPORTEDED_MAX_FIELDS](#); SQLSTATE: [HY000](#)
Message: Column can't be added to '%s' with ALGORITHM=INSTANT anymore. Please try ALGORITHM=INPLACE/COPY.
 - Error number: [4159](#); Symbol: [ER_CANT_SET_PERSISTED](#); SQLSTATE: [HY000](#)
Message: Failed to set persisted options.
 - Error number: [4160](#); Symbol: [ER_INSTALL_COMPONENT_SET_NULL_VALUE](#); SQLSTATE: [HY000](#)
Message: The value supplied for %s in the SET list cannot be null
 - Error number: [4161](#); Symbol: [ER_INSTALL_COMPONENT_SET_UNUSED_VALUE](#); SQLSTATE: [HY000](#)
Message: The assignment of %s in SET doesn't match any of the variables registered by the component(s)
 - Error number: [4162](#); Symbol: [ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS](#); SQLSTATE: [HY000](#)
Message: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.
 - Error number: [4163](#); Symbol: [ER_USER_LOCK_OVERLONG_NAME](#); SQLSTATE: [42000](#)
Message: User-level lock name '%s' should not exceed %d characters.
 - Error number: [4164](#); Symbol: [ER_WARN_NO_SPACE_VERSION_COMMENT](#); SQLSTATE: [HY000](#)

Message: Immediately starting the version comment after the version number is deprecated and may change behavior in a future release. Please insert a white-space character after the version number.

- Error number: 4165; Symbol: [ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS](#); SQLSTATE: HY000

Message: The new password must have at least '%u' characters that are different from the old password. It has only '%u' character(s) different. For this comparison, uppercase letters and lowercase letters are considered to be equal.

- Error number: 4166; Symbol: [ER_WARN_DEPRECATED_WITH_NOTE](#); SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release. %s

- Error number: 4167; Symbol: [ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY](#); SQLSTATE: HY000

Message: Running recursive calls to SQL execution service is not supported

- Error number: 4168; Symbol: [ER_WARN_SET_OPERATIONS_BUFFER](#); SQLSTATE: HY000

Message: System variable "set_operations_buffer_size" set too low for hashed set operation. Consult optimizer trace for recommendations.

- Error number: 6000; Symbol: [ER_LANGUAGE_COMPONENT](#); SQLSTATE: HY000

Message: %s

- Error number: 6001; Symbol: [ER_LANGUAGE_COMPONENT_NOT_AVAILABLE](#); SQLSTATE: HY000

Message: Language component: Not available.

- Error number: 6002; Symbol: [ER_LANGUAGE_COMPONENT_UNSUPPORTED_LANGUAGE](#); SQLSTATE: HY000

Message: Language component: Unsupported language '%s'

- Error number: 6003; Symbol: [ER_LANGUAGE_COMPONENT_CANNOT_UNINSTALL](#); SQLSTATE: HY000

Message: Language component: Cannot uninstall due to connected sessions. Please disconnect all sessions and try again.

- Error number: 6004; Symbol: [ER_SP_NO_ALTER_LANGUAGE](#); SQLSTATE: HY000

Message: Altering the language of an existing routine is not possible.

- Error number: 6006; Symbol: [ER_EXPLAIN INTO_IMPLICIT_FORMAT_NOT_SUPPORTED](#); SQLSTATE: 0A000

Message: EXPLAIN INTO does not support implicit FORMAT.

- Error number: 6007; Symbol: [ER_EXPLAIN INTO_FORMAT_NOT_SUPPORTED](#); SQLSTATE: 0A000

Message: EXPLAIN INTO does not support FORMAT=%s.

- Error number: 6008; Symbol: [ER_NULL_CANT_BE_PERSISTED_FOR_READONLY](#); SQLSTATE: HY000

Message: Trying to persist a NULL into a variable '%s' that's settable only on command line is not supported

-
- Error number: [6009](#); Symbol: [ER_EXPLAIN_INT0_FOR_CONNECTION_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)
Message: EXPLAIN FOR CONNECTION does not support the INTO clause.
 - Error number: [6010](#); Symbol: [ER_INNO0B_IMPORT_WRONG_DROPPED_ENUM_LENGTH](#); SQLSTATE: [HY000](#)
Message: Enum element name length %lu, is invalid for column %s
 - Error number: [6011](#); Symbol: [ER_INNO0B_IMPORT_WRONG_NUMBER_OF_INDEXES_ZERO](#); SQLSTATE: [HY000](#)
Message: Number of indexes in meta-data file is 0
 - Error number: [6012](#); Symbol: [ER_INNO0B_IMPORT_WRONG_NUMBER_OF_INDEXES_TOO_HIGH](#); SQLSTATE: [HY000](#)
Message: Number of indexes in meta-data file is too high: %llu
 - Error number: [6013](#); Symbol: [ER_INNO0B_IMPORT_DROP_COL_METADATA_MISMATCH](#); SQLSTATE: [HY000](#)
Message: DD metadata for INSTANT DROP column %s in target table doesn't match with CFG.
 - Error number: [6014](#); Symbol: [ER_INNO0B_IMPORT_ENUM_NULL_TERMINATOR_MISSING](#); SQLSTATE: [HY000](#)
Message: Enum/Set element name missing null terminator for column '%s'
 - Error number: [6015](#); Symbol: [ER_SIMULATED_INJECTION_ERROR](#); SQLSTATE: [HY000](#)
Message: %s %s %zu.
 - Error number: [6016](#); Symbol: [ER_WARN_DEPRECATED_DYNAMIC_PRIV_IN_GRANT](#); SQLSTATE: [HY000](#)
Message: The privilege '%s' is deprecated.
 - Error number: [6017](#); Symbol: [ER_BULK_MULTI_READER_OPEN_FILE_FAILED](#); SQLSTATE: [HY000](#)
Message: Bulk Multi Reader: Failed to open file
 - Error number: [6018](#); Symbol: [ER_BULK_MULTI_READER_READ_FILE_FAILED](#); SQLSTATE: [HY000](#)
Message: Bulk Multi Reader: Failed to read file
 - Error number: [6019](#); Symbol: [ER_BULK_MERGE_INVALID_CHUNK](#); SQLSTATE: [HY000](#)
Message: Bulk Merge Loader: Invalid Chunk
 - Error number: [6020](#); Symbol: [ER_BULK_MERGE_NOT_ALL_CHUNKS_CONSUMED](#); SQLSTATE: [HY000](#)
Message: Bulk Merge Loader: Not all chunks consumed
 - Error number: [6021](#); Symbol: [ER_BULK_WRITER_LIBCURL_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Bulk writer failed to initialize libcurl
 - Error number: [6022](#); Symbol: [ER_BULK_WRITER_LIBCURL_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk writer got libcurl error: %s

- Error number: [6023](#); Symbol: [ER_BULK_SORTING_LOADER_WRITE](#); SQLSTATE: [HY000](#)

Message: Bulk Sorting Loader: Failed to write data to temporary file

- Error number: [6024](#); Symbol: [ER_BULK_SORTING_LOADER_WAIT](#); SQLSTATE: [HY000](#)

Message: Bulk Sorting Loader: Interrupted while waiting

- Error number: [6025](#); Symbol: [ER_BULK_READER_OPEN_FILE_FAILED](#); SQLSTATE: [HY000](#)

Message: Bulk Reader: Failed to access file %s

- Error number: [6026](#); Symbol: [ER_BULK_LOAD_TABLE_HAS_INSTANT_COLS](#); SQLSTATE: [HY000](#)

Message: Bulk Loader: Table '%s' has instantly added/dropped columns. Please TRUNCATE TABLE and retry.

- Error number: [6027](#); Symbol: [ER_BULK_LOAD_RESOURCE](#); SQLSTATE: [HY000](#)

Message: Bulk Loader: Not enough memory available. Memory needed for loading %s data: %s for %u threads, %s with minimal configuration. Total configured memory is %s, Available memory is %s.

- Error number: [6028](#); Symbol: [ER_BULK_LOAD_SECONDARY_ENGINE](#); SQLSTATE: [HY000](#)

Message: LOAD DATA with BULK Algorithm is not supported on a table with secondary engine.

- Error number: [6029](#); Symbol: [ER_BULK_READER_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader error: %s

- Error number: [6030](#); Symbol: [ER_BULK_READER_FILE_DOESNT_EXIST](#); SQLSTATE: [HY000](#)

Message: File not found, check whether it exists: %s

- Error number: [6031](#); Symbol: [ER_BULK_READER_COULDNT_RESOLVE_HOST](#); SQLSTATE: [HY000](#)

Message: Couldn't resolve host: %s

- Error number: [6032](#); Symbol: [ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Cannot start replication channel '%s' because %s.

- Error number: [6033](#); Symbol: [ER_CANNOT_EXECUTE_IN_PRIMARY](#); SQLSTATE: [HY000](#)

Message: '%s' is not supported

- Error number: [6034](#); Symbol: [ER_TOO_MANY_GROUP_BY_MODIFIER_BRANCHES](#); SQLSTATE: [HY000](#)

Message: '%s' is supported with maximum %d elements in the GROUP BY list

- Error number: [6035](#); Symbol: [ER_WARN_DEPRECATED_ENGINE_SYNTAX_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' for '%s' storage engine is deprecated and will be removed in a future release.

- Error number: [6036](#); Symbol: [ER_QUALIFY_WITHOUT_WINDOW_FUNCTION](#); SQLSTATE: [HY000](#)

Message: QUALIFY clause cannot be used without a window function.

-
- Error number: [6037](#); Symbol: [ER_SUPPORTED_ONLY_WITH_HYPERGRAPH](#); SQLSTATE: [HY000](#)
Message: '%s' can be used only if the hypergraph optimizer is enabled.
 - Error number: [6038](#); Symbol: [ER_SPECIFIC_ACCESS_DENIED](#); SQLSTATE: [HY000](#)
Message: Access denied; you need %s privilege(s) for this operation
 - Error number: [6039](#); Symbol: [ER_CANT_SET_GTID_NEXT_TO_AUTOMATIC_TAGGED_WHEN_GTID_MODE_IS_OFF](#); SQLSTATE: [HY000](#)
Message: @@SESSION.GTID_NEXT cannot be set to AUTOMATIC:<TAG> when @@GLOBAL.GTID_MODE = OFF or OFF_PERMISSIVE
 - Error number: [6040](#); Symbol: [ER_GTID_NEXT_TAG_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)
Message: @@SESSION.GTID_NEXT cannot be set to UUID:TAG:NUMBER when @@GLOBAL.GTID_MODE = OFF.
 - Error number: [6041](#); Symbol: [ER_LH_COL_NOT_NULLABLE](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Column contains null but it is not nullable.
 - Error number: [6042](#); Symbol: [ER_LH_WARN_COL_MISSING_NOT_NULLABLE](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Column is missing, but it is not nullable and no explicit default value is provided.
 - Error number: [6043](#); Symbol: [ER_LH_COL_IS_EMPTY](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Column is empty.
 - Error number: [6044](#); Symbol: [ER_LH_COL_IS_EMPTY_WARN](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Column is empty, setting default value.
 - Error number: [6045](#); Symbol: [ER_LH_BAD_VALUE](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Invalid %s value.
 - Error number: [6046](#); Symbol: [ER_LH_DECIMAL_UNKNOWN_ERR](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Unknown error while parsing decimal.
 - Error number: [6047](#); Symbol: [ER_LH_DECIMAL_OOM_ERR](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Out of memory loading decimal.
 - Error number: [6048](#); Symbol: [ER_LH_WARN_DECIMAL_ROUNDING](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Fraction exceeds schema, rounding value.
 - Error number: [6049](#); Symbol: [ER_LH_DECIMAL_PRECISION_EXCEEDS_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : decimal precision exceeds schema.
 - Error number: [6050](#); Symbol: [ER_LH_EXCEEDS_MIN](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : %s exceeds min.
 - Error number: [6051](#); Symbol: [ER_LH_EXCEEDS_MAX](#); SQLSTATE: [HY000](#)

Message: Column %d of %s : %s exceeds max.

- Error number: 6052; Symbol: [ER_LH_WARN_EXCEEDS_MIN_TRUNCATING](#); SQLSTATE: HY000

Message: Column %d of %s : %s exceeds min, setting to min value possible.

- Error number: 6053; Symbol: [ER_LH_WARN_EXCEEDS_MAX_TRUNCATING](#); SQLSTATE: HY000

Message: Column %d of %s : %s exceeds max, setting to max value possible.

- Error number: 6054; Symbol: [ER_LH_REAL_IS_NAN](#); SQLSTATE: HY000

Message: Column %d of %s : Real value is NaN.

- Error number: 6055; Symbol: [ER_LH_OUT_OF_RANGE](#); SQLSTATE: HY000

Message: Column %d of %s : %s value is out of range.

- Error number: 6056; Symbol: [ER_LH_DATETIME_FORMAT](#); SQLSTATE: HY000

Message: Column %d of %s : Error while applying %s.

- Error number: 6057; Symbol: [ER_LH_WARN_TRUNCATED](#); SQLSTATE: HY000

Message: Column %d of %s : %s value was truncated.

- Error number: 6058; Symbol: [ER_LH_CANNOT_CONVERT_STRING](#); SQLSTATE: HY000

Message: Column %d of %s : Cannot convert string %s.

- Error number: 6059; Symbol: [ER_LH_RESOURCE_PRINCIPAL_ERR](#); SQLSTATE: HY000

Message: Resource principal error.

- Error number: 6060; Symbol: [ER_LH_AWS_AUTH_ERR](#); SQLSTATE: HY000

Message: AWS authentication error.

- Error number: 6061; Symbol: [ER_LH_CSV_PARSING_ERR](#); SQLSTATE: HY000

Message: %s at byte offset %lu: Parsing error. %s

- Error number: 6062; Symbol: [ER_LH_COLUMN_MISMATCH_ERR](#); SQLSTATE: HY000

Message: %s: Mismatch in the number of columns. Expected %u, found %u.

- Error number: 6063; Symbol: [ER_LH_COLUMN_MAX_ERR](#); SQLSTATE: HY000

Message: %s: More than %u column(s) found.

- Error number: 6064; Symbol: [ER_LH_CHARSET_UNSUPPORTED](#); SQLSTATE: HY000

Message: Column %d in %s: Charset is not supported.

- Error number: 6065; Symbol: [ER_LH_PARQUET_DECIMAL_CONVERSION_ERR](#); SQLSTATE: HY000

Message: Column %d in %s: Decimal conversion error.

- Error number: 6066; Symbol: [ER_LH_STRING_TOO_LONG](#); SQLSTATE: HY000

Message: Column %d in %s: String is too long.

- Error number: 6067; Symbol: [ER_LH_RESOURCE_PRINCIPAL_BUCKET_ERR](#); SQLSTATE: HY000

Message: Resource Principal endpoint is not configured. Cannot access following buckets: %s.

- Error number: 6068; Symbol: [ER_LH_NO_FILES_FOUND](#); SQLSTATE: HY000

Message: No files found corresponding to the following data locations: %s.

- Error number: 6069; Symbol: [ER_LH_EMPTY_FILE](#); SQLSTATE: HY000

Message: File %s is empty.

- Error number: 6070; Symbol: [ER_LH_DUPLICATE_FILE](#); SQLSTATE: HY000

Message: File %s was not processed (duplicate).

- Error number: 6071; Symbol: [ER_LH_AVRO_SCHEMA_DEPTH_EXCEEDS_MAX](#); SQLSTATE: HY000

Message: File %s: Avro schema depth exceeds max allowed depth.

- Error number: 6072; Symbol: [ER_LH_AVRO_HEADER_MISMATCH](#); SQLSTATE: HY000

Message: File %s: Header does not match other files.

- Error number: 6073; Symbol: [ER_LH_AVRO_ENUM_CANNOT_CONVERT_CHARSET](#); SQLSTATE: HY000

Message: File %s: Enum symbol can't convert to column charset.

- Error number: 6074; Symbol: [ER_LH_AVRO_ENUM_MISMATCH](#); SQLSTATE: HY000

Message: File %s: Enum symbols are not the same, or are not in the same order.

- Error number: 6075; Symbol: [ER_LH_AVRO_TYPE_CANNOT_CONVERT](#); SQLSTATE: HY000

Message: Column %d in %s: Avro value of physical type %s logical type %s cannot be converted to mysql type %s.

- Error number: 6076; Symbol: [ER_LH_AVRO_FILE_ENDS_UNEXPECTEDLY](#); SQLSTATE: HY000

Message: File %s: Ends unexpectedly.

- Error number: 6077; Symbol: [ER_LH_AVRO_FILE_DATA_CORRUPT](#); SQLSTATE: HY000

Message: File %s: File data might be corrupt.

- Error number: 6078; Symbol: [ER_LH_AVRO_INVALID_UNION](#); SQLSTATE: HY000

Message: Column %d in %s: Invalid Avro union encountered. Unions are only supported to represent nullable columns. One of the two types of the union must be null.

- Error number: 6079; Symbol: [ER_LH_AVRO_INVALID_BLOCK_SIZE](#); SQLSTATE: HY000

Message: File %s: Invalid avro block size.

- Error number: 6080; Symbol: [ER_LH_AVRO_INVALID_BLOCK_RECORD_COUNT](#); SQLSTATE: HY000

Message: File %s: Invalid Avro block record count.

- Error number: 6081; Symbol: [ER_LH_FORMAT_HEADER_NO_MAGIC_BYTES](#); SQLSTATE: HY000

Message: File %s: Cannot locate %s specific metadata. Either the file is corrupted or this is not an %s file.

-
- Error number: [6082](#); Symbol: [ER_LH_AVRO_HEADER_METADATA_ERR](#); SQLSTATE: [HY000](#)
Message: File %s: Could not process Avro header metadata. The metadata is corrupted or invalid.
 - Error number: [6083](#); Symbol: [ER_LH_AVRO_HEADER_NO_SCHEMA](#); SQLSTATE: [HY000](#)
Message: File %s: No schema in Avro header metadata.
 - Error number: [6084](#); Symbol: [ER_LH_AVRO_NO_CODEC_IN_HEADER](#); SQLSTATE: [HY000](#)
Message: File %s: No codec in Avro header metadata.
 - Error number: [6085](#); Symbol: [ER_LH_AVRO_INVALID_NAME_IN_SCHEMA](#); SQLSTATE: [HY000](#)
Message: File %s: Invalid name in Avro schema.
 - Error number: [6086](#); Symbol: [ER_LH_AVRO_DECODING_ERR](#); SQLSTATE: [HY000](#)
Message: File %s: Error decoding Avro %s. %s
 - Error number: [6087](#); Symbol: [ER_LH_PARQUET_NON_UTF8_FILE_ENC](#); SQLSTATE: [HY000](#)
Message: Column %d in %s: String with non-utf8 file encoding.
 - Error number: [6088](#); Symbol: [ER_LH_PARQUET_SCHEMA_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Column %d in %s: Difference in column type among Parquet files.
 - Error number: [6089](#); Symbol: [ER_LH_PARQUET_ROW_GROUP_SIZE_EXCEEDS_MAX](#); SQLSTATE: [HY000](#)
Message: File %s: Size of row group %ld is larger than maximum allowed size (%d).
 - Error number: [6090](#); Symbol: [ER_LH_PARQUET_CANNOT_LOCATE_OFFSET](#); SQLSTATE: [HY000](#)
Message: File %s: Cannot locate offset of row group %ld in metadata.
 - Error number: [6091](#); Symbol: [ER_LH_PARQUET_TYPE_CANNOT_CONVERT](#); SQLSTATE: [HY000](#)
Message: Column %d in %s: Parquet type cannot be converted to mysql %s.
 - Error number: [6092](#); Symbol: [ER_LH_PARQUET_CANNOT_LOCATE_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Cannot locate schema in %s.
 - Error number: [6093](#); Symbol: [ER_LH_INFER_NUM_COL_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Column count mismatch between files: '%s' has %d columns, but '%s' has %d columns.
 - Error number: [6094](#); Symbol: [ER_LH_OOM](#); SQLSTATE: [HY000](#)
Message: Insufficient memory.
 - Error number: [6095](#); Symbol: [ER_LH_WARN_INFER_SKIPPED_LINES](#); SQLSTATE: [HY000](#)
Message: Skipped %lu line(s) due to mismatched num of cols.
 - Error number: [6096](#); Symbol: [ER_LH_WARN_INFER_SKIPPED_FILES](#); SQLSTATE: [HY000](#)
Message: Skipped %lu file(s) due to mismatched num of cols.
 - Error number: [6097](#); Symbol: [ER_LH_INFER_FILE_HAS_NO_DATA](#); SQLSTATE: [HY000](#)
Message: File %s is skipped because it has no valid data. File is either empty or all rows are skipped.

-
- Error number: 6098; Symbol: `ER_LH_INFER_NO_DATA`; SQLSTATE: `HY000`
Message: No valid data found for processing.
 - Error number: 6099; Symbol: `ER_LH_INFER_NO_FILES`; SQLSTATE: `HY000`
Message: No valid files found for processing.
 - Error number: 6100; Symbol: `ER_LH_WARN_INFER_USE_DEFAULT_COL_NAMES`; SQLSTATE: `HY000`
Message: Used default column names for column index(es) %s as they are %s.
 - Error number: 6101; Symbol: `ER_LH_PARQUET_CANNOT_READ_HEADER`; SQLSTATE: `HY000`
Message: File %s: Unable to read Parquet header.
 - Error number: 6102; Symbol: `ER_LH_INFER_WARN_GOT_EXCEPTION`; SQLSTATE: `HY000`
Message: Got an exception while trying to process file task.
 - Error number: 6103; Symbol: `ER_LH_AVRO_CANNOT_PARSE_HEADER`; SQLSTATE: `HY000`
Message: File %.*s: Could not parse avro header. Probably corrupted avro file.
 - Error number: 6104; Symbol: `ER_LH_PARQUET_CANT_OPEN_FILE`; SQLSTATE: `HY000`
Message: Parquet reader cannot open %s. %s
 - Error number: 6105; Symbol: `ER_LH_TOO_LARGE_VALUE_ERR`; SQLSTATE: `HY000`
Message: File %.*s: %s
 - Error number: 6106; Symbol: `ER_LH_TOO_LARGE_ROW_ERR`; SQLSTATE: `HY000`
Message: File %.*s: %s
 - Error number: 6107; Symbol: `ER_TABLESAMPLE_PERCENTAGE`; SQLSTATE: `2202H`
Message: Tablesample percentage should range between 0 and 100.
 - Error number: 6108; Symbol: `ER_TABLESAMPLE_ONLY_ON_BASE_TABLES`; SQLSTATE: `HY000`
Message: Tablesample can be applied only on base tables.
 - Error number: 6110; Symbol: `ER_RESULT_SIZE_LIMIT_EXCEEDED`; SQLSTATE: `HY000`
Message: Result size limit exceeded.
 - Error number: 6111; Symbol: `ER_LANGUAGE_COMPONENT_INTERNAL`; SQLSTATE: `HY000`
Message: Language component: Internal error.
 - Error number: 6112; Symbol: `ER_LANGUAGE_COMPONENT_CONCURRENCY_LIMIT`; SQLSTATE: `HY000`
Message: Language component: Concurrency limit (%s) has been reached.
 - Error number: 6113; Symbol: `ER_LANGUAGE_COMPONENT_RUNTIME`; SQLSTATE: `HY000`
Message: %s> %s
 - Error number: 6114; Symbol: `ER_LANGUAGE_COMPONENT_TIMEZONE`; SQLSTATE: `HY000`
Message: %s> Time zone %s is not supported.

-
- Error number: [6115](#); Symbol: [ER_LANGUAGE_COMPONENT_KEYWORD](#); SQLSTATE: [HY000](#)
Message: %s> The identifier '%s' is not valid.
 - Error number: [6116](#); Symbol: [ER_LANGUAGE_COMPONENT_SET_SYSTEM_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Language component: System variable '%s' cannot be configured when component is active.
 - Error number: [6117](#); Symbol: [ER_LANGUAGE_COMPONENT_UNSUPPORTED_TYPE](#); SQLSTATE: [HY000](#)
Message: %s> %s
 - Error number: [6118](#); Symbol: [ER_LANGUAGE_COMPONENT_CONVERSION](#); SQLSTATE: [HY000](#)
Message: %s> %s
 - Error number: [6119](#); Symbol: [ER_WARN_SP_STATEMENT_PARTIALLY_EXECUTED](#); SQLSTATE: [HY000](#)
Message: Stored program statement is partially completed. Result set might not contain all the rows.
 - Error number: [6120](#); Symbol: [ER_STMT_EXECUTION_NOT_ALLOWED_WITHIN_SP_OR_TRG_OR_UDF](#); SQLSTATE: [HY000](#)
Message: Executing SQL statement using %s Statement Handle Interface is not allowed within stored function, trigger or loadable function (UDF).
 - Error number: [6121](#); Symbol: [ER_LH_JSON_PARSING](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : %s
 - Error number: [6122](#); Symbol: [ER_ENGINE_CANNOT_BE_DEFAULT](#); SQLSTATE: [HY000](#)
Message: Engine %s cannot be set as default_storage_engine.
 - Error number: [6123](#); Symbol: [ER_PARTITION_PREFIX_KEY_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Column '%s.%s.%s' having prefix key part '%s(%u)' in the PARTITION BY KEY() clause is not supported.
 - Error number: [6124](#); Symbol: [ER_WARN_DEPRECATED_NON_STANDARD_KEY](#); SQLSTATE: [HY000](#)
Message: Foreign key '%s' refers to non-unique key or partial key. This is deprecated and will be removed in a future release.
 - Error number: [6125](#); Symbol: [ER_FK_NO_UNIQUE_INDEX_PARENT](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint. Missing unique key for constraint '%s' in the referenced table '%s'
 - Error number: [6126](#); Symbol: [ER_ACCESS_DENIED_NO_PROXY_GRANT](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s', missing proxy privilege.
 - Error number: [6127](#); Symbol: [ER_ACCESS_DENIED_NO_PROXY](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s', proxied user doesn't exist.
 - Error number: [6128](#); Symbol: [ER_LH_USER_DATA_ACCESS_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to access the following data locations: %s

- Error number: 6129; Symbol: [ER_BULK_READER_ZSTD_ERROR](#); SQLSTATE: HY000

Message: ZSTD decompression failed: %s

- Error number: 6130; Symbol: [ER_BULK_PARSER_ERROR](#); SQLSTATE: HY000

Message: %s

- Error number: 6131; Symbol: [ER_LH_INVALID_JSON_FILE_FORMAT_SCHEMA](#); SQLSTATE: HY000

Message: Invalid json file format schema: %s

- Error number: 6132; Symbol: [ER_LH_INFER_JSON_INVALID_SCHEMA](#); SQLSTATE: HY000

Message: Inferred invalid schema. A single column with JSON type is the only valid schema for JSON file format.

- Error number: 6133; Symbol: [ER_LH_JSON_FILE_FORMAT_WARN_INFER_SCHEMA](#); SQLSTATE: HY000

Message: Altered the inferred schema to a single JSON column.

- Error number: 6134; Symbol: [ER_NON_SCALAR_USED_AS_KEY](#); SQLSTATE: HY000

Message: Non-scalar (e.g., vector) column '%s' cannot be used as key.

- Error number: 6135; Symbol: [ER_INCOMPATIBLE_TYPE_AGG](#); SQLSTATE: HY000

Message: Columns aggregated with incompatible types: '%s', '%s'.

- Error number: 6136; Symbol: [ER_DATA_INCOMPATIBLE_WITH_VECTOR](#); SQLSTATE: HY000

Message: Value of type '%s', size: %zu' cannot be converted to 'vector' type.

- Error number: 6137; Symbol: [ER_EXCEEDS_VECTOR_MAX_DIMENSIONS](#); SQLSTATE: HY000

Message: Data size (%zu Bytes, %u dimensions) exceeds VECTOR max (%zu Bytes, %u dimensions) for column: '%s'

- Error number: 6138; Symbol: [ER_TO_VECTOR_CONVERSION](#); SQLSTATE: HY000

Message: Data cannot be converted to a valid vector: '%.*s'

- Error number: 6140; Symbol: [ER_TP_CANNOT_DISABLE_MTL_WITH_DL](#); SQLSTATE: HY000

Message: The variable thread_pool_max_transactions_limit cannot be set to 0 when thread_pool_dedicated_listerner is ON.

- Error number: 6400; Symbol: [ER_SERVER_OFFLINE_MODE_REASON](#); SQLSTATE: HY000

Message: The server is currently in offline mode since %s, reason: %s

- Error number: 6402; Symbol: [ER_LH_UNSTRUCTURED_NO_DATA_FOUND](#); SQLSTATE: HY000

Message: No data was extracted from provided files.

- Error number: 6403; Symbol: [ER_LH_UNSTRUCTURED_FILE_PARSE_ERR](#); SQLSTATE: HY000

Message: File: %.*s Could not be parsed. %s

- Error number: 6404; Symbol: [ER_LH_UNSTRUCTURED_ENCODING_ERR](#); SQLSTATE: HY000

Message: Segments %d to %d in file: %.*s Could not be encoded.

- Error number: 6405; Symbol: `ER_LH_UNSTRUCTURED_FILE_TYPE_MISMATCH_ERR`; SQLSTATE: `HY000`

Message: File: %.*s is not a supported file type.

- Error number: 6406; Symbol: `ER_LH_UNSTRUCTURED_SCHEMA_ERR`; SQLSTATE: `HY000`

Message: Defined schema does not match expected for column: %s.

- Error number: 6407; Symbol: `ER_LH_COLUMN_ENGINE_ATTR_ERR`; SQLSTATE: `HY000`

Message: Invalid column engine attribute: %s.

- Error number: 6408; Symbol: `ER_LH_UNSTRUCTURED_OBJ_READ_ERR`; SQLSTATE: `HY000`

Message: File: %.*s Could not be read.

- Error number: 6409; Symbol: `ER_LH_NO_SEGMENTS_GENERATED`; SQLSTATE: `HY000`

Message: File: %.*s did not result in segments.

- Error number: 6410; Symbol: `ER_LH_UNSTRUCTURED_FILE_TOO_LARGE`; SQLSTATE: `HY000`

Message: File: %s is too large.

- Error number: 6411; Symbol: `ER_EXCEEDED_MAX_REGULAR_STATEMENT_HANDLE_LIMIT`; SQLSTATE: `HY000`

Message: Exceeded limit of %u regular SQL statement handles per session.

- Error number: 6412; Symbol: `ER_EXPLAIN_ANALYZE_JSON_FORMAT_VERSION_NOT_SUPPORTED`; SQLSTATE: `0A000`

Message: EXPLAIN ANALYZE does not support FORMAT=JSON with explain_json_format_version=1.

- Error number: 6413; Symbol: `ER_NON_DML_DYNAMIC_PARAMETERS`; SQLSTATE: `HY000`

Message: Dynamic parameters can only be used in DML statements.

- Error number: 6414; Symbol: `ER_DEPRECATED_NON_COMPOSABLE_MULTIPLE_ENGINE`; SQLSTATE: `HY000`

Message: Combining the storage engines %s and %s is deprecated, but the statement or transaction updates both the %s table %s.%s and the %s table %s.%s.

- Error number: 6415; Symbol: `ER_BULK_JSON_INVALID`; SQLSTATE: `HY000`

Message: Bulk load reports invalid JSON: error='%s', table='%s', field='%s'

- Error number: 6416; Symbol: `ER_BULK_BLOB_TOO_BIG`; SQLSTATE: `HY000`

Message: Column data bigger than %zu bytes for column='%s' of table='%s'

- Error number: 6417; Symbol: `ER_NO_QUERY_PLAN_FOUND`; SQLSTATE: `HY000`

Message: No query execution plan was found for the statement.

- Error number: 6418; Symbol: `ER_LH_CP_TOO_MANY_CHANGES`; SQLSTATE: `HY000`

Message: More than %llu changes detected. Certain changes are ignored.

-
- Error number: [6419](#); Symbol: [ER_LH_CP_NOT_ENABLED](#); SQLSTATE: [HY000](#)
Message: Lakehouse Incremental Load is not enabled.
 - Error number: [6420](#); Symbol: [ER_LH_CP_NO_VECTOR_STORE](#); SQLSTATE: [HY000](#)
Message: Lakehouse Incremental Load is not supported for vector store tables.
 - Error number: [6421](#); Symbol: [ER_LH_CP_NO_VALIDATION_MODE](#); SQLSTATE: [HY000](#)
Message: Lakehouse Incremental Load is not supported with validation mode.
 - Error number: [6423](#); Symbol: [ER_LH_CP_COMMIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Lakehouse Incremental Load commit operation failed.
 - Error number: [6424](#); Symbol: [ER_LH_UNSTRUCTURED_INVALID_LANGUAGE](#); SQLSTATE: [HY000](#)
Message: Invalid language code. %s.
 - Error number: [6425](#); Symbol: [ER_LH_VECTOR_TOO_MANY_ENTRIES](#); SQLSTATE: [HY000](#)
Message: Column %d in %s: Vector has more entries than its dimension: %s
 - Error number: [6426](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_ENCLOSED_BY_CHARACTER](#); SQLSTATE: [HY000](#)
Message: Unexpected enclosed by character found inside unenclosed string at row %ld in file '%s' resulting in malformed CSV.
 - Error number: [6427](#); Symbol: [ER_CMD_NEED_SUPER_OR_CREATE_SPATIAL_REFERENCE_SYSTEM](#); SQLSTATE: [HY000](#)
Message: You need the SUPER or CREATE_SPATIAL_REFERENCE_SYSTEM privilege for command '%s'
 - Error number: [6428](#); Symbol: [ER_CLAUSE_IGNORED](#); SQLSTATE: [HY000](#)
Message: %s is ignored in %s.
 - Error number: [6429](#); Symbol: [ER_INVALID_CLAUSE_IN_CONTEXT](#); SQLSTATE: [HY000](#)
Message: Clause %s is not valid with %s.
 - Error number: [6430](#); Symbol: [ER_INVALID_CLAUSE_COMBINATION](#); SQLSTATE: [HY000](#)
Message: Clauses %s and %s cannot be combined.
 - Error number: [6431](#); Symbol: [ER_WARN_REDACTED_PRIVILEGES](#); SQLSTATE: [HY000](#)
Message: Result of SHOW was redacted due to insufficient privileges for table %s.
 - Error number: [6432](#); Symbol: [ER_INVALID_OUTER_REFERENCE](#); SQLSTATE: [HY000](#)
Message: Outer reference %s in window's ORDER BY or PARTITION BY clause not allowed.
 - Error number: [6433](#); Symbol: [ER_LIBRARIES_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Libraries are not supported for %s.
 - Error number: [6434](#); Symbol: [ER_LH_WARN_SUMMARY](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: 6435; Symbol: ER_LH_WARN_INFER_USE_DEFAULT_DELIMITERS; SQLSTATE: HY000
Message: Feature Auto delimiter detection is skipped (%s).
 - Error number: 6436; Symbol: ER_LIBRARY_INVALID; SQLSTATE: HY000
Message: The routine '%s' references a missing library '%s.%s' or definer/invoker of the routine lack rights to use it.
 - Error number: 6437; Symbol: ER_CANNOT_PERSIST_TRANSACTION_ISOLATION; SQLSTATE: HY000
Message: Cannot persist transaction isolation.
 - Error number: 6438; Symbol: ER_LH_AVRO_INVALID_RECORD; SQLSTATE: HY000
Message: Column %d in %s: Invalid Avro record encountered. Nested records are not supported.
 - Error number: 6439; Symbol: ER_LH_INVALID_VALUE_IN_VECTOR; SQLSTATE: HY000
Message: Column %d in %s: Invalid vector: contains a value %s.
 - Error number: 6440; Symbol: ER_LH_WARN_VECTOR_LOSSY_CONVERSION; SQLSTATE: HY000
Message: Column %d in %s: Conversion from type Int to type Float could result in loss of precision.
 - Error number: 6441; Symbol: ER_LH_UNSTRUCTURED_TRUNCATION_ERROR; SQLSTATE: HY000
Message: Vector chunks are truncated for file: %.*s
 - Error number: 6442; Symbol: ER_LH_UNSTRUCTURED_PAGE_CHUNK_WARN; SQLSTATE: HY000
Message: Split by 'page' chunking is changed to 'document' chunking for %.*s because split by 'page' is not possible for docx, doc, html, or txt formats.
 - Error number: 6443; Symbol: ER_LH_UNSTRUCTURED_TOO_MANY_CHUNKS; SQLSTATE: HY000
Message: Too many chunks for file: %.*s
 - Error number: 6444; Symbol: ER_ACCESS_DENIED_FIREWALL; SQLSTATE: 28000
Message: Access denied.
 - Error number: 6445; Symbol: ER_LH_DECOMPRESSION_ERR; SQLSTATE: HY000
Message: Failed to extract from %s: corrupted file, wrong compression format, or multiple files in archive.
 - Error number: 6446; Symbol: ER_JDV_INVALID_DEFINITION_WRONG_ANNOTATIONS; SQLSTATE: HY000
Message: Invalid JSON duality view definition: Invalid, Duplicate or Conflicting annotations for the JSON field.
 - Error number: 6447; Symbol: ER_JDV_ALGO_TEMPTABLE_NOT_SUPPORTED; SQLSTATE: HY000
Message: ALGORITHM = TEMPTABLE is not supported for duality views.
 - Error number: 6448; Symbol: ER_JDV_WITH_CHECK_OPTION_NOT_SUPPORTED; SQLSTATE: HY000
Message: Invalid JSON duality view definition: WITH [LOCAL/CASCADE] CHECK OPTION clause is not supported.

-
- Error number: [6449](#); Symbol: [ER_JDV_INVALID_DEFINITION_NON_SIMPLE_SELECT_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Invalid JSON duality view definition: Set Operations such as UNION, INTERSECT, EXCEPT and multi-level ORDER are not supported. Object "%s" violates this rule.
 - Error number: [6450](#); Symbol: [ER_JDV_INVALID_DEFINITION_CTE_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Common Table Expressions (CTE) are not supported. Object "%s" violates this rule.
 - Error number: [6451](#); Symbol: [ER_JDV_INVALID_DEFINITION_GROUPBY_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Clauses like GROUP BY, HAVING are not supported. Object "%s" violates this rule.
 - Error number: [6452](#); Symbol: [ER_JDV_INVALID_DEFINITION_WINDOW_FUNCTION_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: WINDOW functions are not supported. Object "%s" violates this rule.
 - Error number: [6453](#); Symbol: [ER_JDV_INVALID_DEFINITION_LIMIT_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: LIMIT clause is not supported. Object "%s" violates this rule.
 - Error number: [6454](#); Symbol: [ER_JDV_INVALID_DEFINITION_ORDERBY_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: ORDER BY clause is not supported. Object "%s" violates this rule.
 - Error number: [6455](#); Symbol: [ER_JDV_INVALID_DEFINITION_MULTI_TABLES_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: FROM clause must include exactly one table. Object "%s" violates this rule.
 - Error number: [6456](#); Symbol: [ER_JDV_INVALID_DEFINITION_NO_WHERE_CONDITION_IN_SUBOBJECT](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: WHERE clause is mandatory with sub-objects. Object "%s" is missing this clause.
 - Error number: [6457](#); Symbol: [ER_JDV_INVALID_DEFINITION_WHERE_CONDITION_IN_ROOTOBJECT](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: WHERE clause is not supported with root object.
 - Error number: [6458](#); Symbol: [ER_JDV_INVALID_DEFINITION_WRONG_WHERE_FORMAT_FOR_SUBOBJECT](#); SQLSTATE: [HY000](#)

Message: Invalid JSON Duality View Definition: The WHERE clause in sub-objects must consist of a single condition being an equality comparison between parent object and sub-object's table columns. Object "%s" violates this rule.
 - Error number: [6459](#); Symbol: [ER_JDV_INVALID_DEFINITION_WRONG_FIELD_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: JSON_DUALITY_OBJECT value must be either a table column or a sub-query. Object "%s" contains an invalid value.

- Error number: 6460; Symbol: [ER_JDV_INVALID_DEFINITION_CONTEXT_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: JSON duality view context initialization failed.

- Error number: 6461; Symbol: [ER_JDV_INVALID_DEFINITION_NO_JSON_OBJECT_IN_ROOT](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Only JSON_DUALITY_OBJECT() is allowed in the select list of root object's query.

- Error number: 6462; Symbol: [ER_JDV_INVALID_DEFINITION_MUSTBE_JSON_OBJECT_FOR_SINGLETON](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Only JSON_DUALITY_OBJECT() is allowed in the select list of singleton descendant object's query. Object "%s" violates this rule.

- Error number: 6463; Symbol: [ER_JDV_INVALID_DEFINITION_MUSTBE_JSON_OBJECT_FOR_NESTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Only JSON_ARRAYAGG() is allowed in the select list of nested descendant object's query. Object "%s" violates this rule.

- Error number: 6464; Symbol: [ER_JDV_INVALID_DEFINITION_NO_JSON_OBJ_IN_ARRAYAGG](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Only JSON_DUALITY_OBJECT() is allowed in the argument list of JSON_ARRAYAGG(). Object "%s" violates this rule.

- Error number: 6465; Symbol: [ER_JDV_INVALID_DEFINITION_RELATIONSHIP_RULES_VIOLATED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: For singleton descendant object, the primary key column of a current object's table must be used in the WHERE condition. For a nested descendant object, the primary key column of the parent object's table must be used in where condition. Object "%s" violates the rule.

- Error number: 6466; Symbol: [ER_JDV_INVALID_DEFINITION_COLUMN_TYPE_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Object "%s" projecting "%s.%s" includes column "%s" of type "%s". This type of projection is not supported.

- Error number: 6467; Symbol: [ER_JDV_INVALID_DEFINITION_NON_BASE_TABLE_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Only base tables can be used to create JSON DUALITY VIEW. "%s.%s" is not a base table.

- Error number: 6468; Symbol: [ER_JDV_INVALID_DEFINITION_TABLE_WITHOUT_PK_FOUND](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: All participating tables should have a primary key, "%s.%s" does not have it.

- Error number: 6469; Symbol: [ER_JDV_INVALID_DEFINITION_TABLE_WITHOUT_PK_PROJECTION_FOUND](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Primary key column of every table should be projected, object "%s" that projects table "%s.%s" does not.

- Error number: 6470; Symbol: [ER_JDV_INVALID_DEFINITION_ID_KEY_USED_BY_NOT_ROOT_TABLE](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: The key name "_id" can only be used for primary key column of the root object and cannot be assigned to column "%s" of table "%s.%s".

- Error number: 6471; Symbol: [ER_JDV_INVALID_DEFINITION_ID_KEY_NOT_USED_BY_ROOT_TABLE](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: Primary key column of a root object's table must always be projected as "_id".

- Error number: 6472; Symbol: [ER_JDV_INVALID_TABLE_ANNOTATIONS_FOR_SINGLETON_OBJ](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: Incorrect annotations for "%s". For singleton child object linked using primary key column with parent, table annotations must enforce both read-only or INSERT and UPDATE. DELETE is not allowed.

- Error number: 6473; Symbol: [ER_JDV_INVALID_TABLE_ANNOTATIONS_FOR_NESTED_OBJ](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: Incorrect annotations for "%s". Table annotations for Root, Nested child object and Singleton child linked using non-primary key column should enforce read-only or full writability (i.e. usage of UPDATE, INSERT and DELETE tags).

- Error number: 6474; Symbol: [ER_JDV_INVALID_DEFINITION_DUPLICATE_KEYS_NOT_SUPPORTED](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: Object "%s" projects key "%s" more than once.

- Error number: 6475; Symbol: [ER_JDV_INVALID_DEFINITION_DUPLICATE_COLUMN_NOT_SUPPORTED](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: Object "%s" projecting table "%s", projects column "%s" more than once.

- Error number: 6476; Symbol: [ER_JDV_INVALID_DEFINITION_SAME_TABLE_INCONSISTENT_PROJECTION](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: If a table is projected multiple times, the set of columns projected must be consistent across all instances of the table projection. Table "%s.%s" violates the rule.

- Error number: 6477; Symbol: [ER_JDV_INVALID_DEFINITION_COLUMN_LIST_NOT_SUPPORTED](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: Specifying column list is not supported for duality views.

- Error number: 6478; Symbol: [ER_JDV_INVALID_DEFINITION_INCONSISTENT_TABLE_FIELD_IN_THE_OBJECT](#); SQLSTATE: HY000

Message: Invalid JSON duality view definition: JSON_DUALITY_OBJECT can only contain columns from the projected table. Object "%s" is expected to project columns from "%s.%s" but includes columns from "%s.%s", violating this rule.

-
- Error number: [6479](#); Symbol: [ER_JDV_INVALID_DEFINITION_WHERE_USES_NON_IMMEDIATE_PARENT](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: The WHERE condition in sub-objects can only reference columns from the table being projected in the current object and columns from the table projected in the parent object. The object "%s" violates this rule.
 - Error number: [6480](#); Symbol: [ER_JDV_INVALID_DEFINITION_COMPOSITE_KEY_USED](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Composite primary key is not supported. Object "%s" projecting "%s" table violates the rule.
 - Error number: [6481](#); Symbol: [ER_JDV_INVALID_DEFINITION_ALIAS_NOT_USED_FOR_SAME_TABLES](#); SQLSTATE: [HY000](#)

Message: Invalid JSON duality view definition: Parent and child objects cannot project the same table without aliasing at least one of them. Objects "%s" and "%s" violate this rule.
 - Error number: [6482](#); Symbol: [ER_JDV_OPERATION_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)

Message: %s is not supported for JSON Duality Views.
 - Error number: [6483](#); Symbol: [ER_JDV_ALTER_OR_REPLACE_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: View '%s.%s' of '%s' type already exists. Replacing view with mismatched type is not supported.
 - Error number: [6484](#); Symbol: [ER_JDV_INVALID_JSON_DUALITY_OBJECT_USAGE](#); SQLSTATE: [HY000](#)

Message: JSON_DUALITY_OBJECT() can only be used to define a JSON duality view.
 - Error number: [6485](#); Symbol: [ER_JDV_UNEXPECTED_JSON_TYPE](#); SQLSTATE: [HY000](#)

Message: Path '%s' is not of type '%s'.
 - Error number: [6486](#); Symbol: [ER_JDV_PRIMARY_KEY_MUST_BE_PROVIDED](#); SQLSTATE: [HY000](#)

Message: Primary key column %s.%s must be provided as path '%s.%s' (this also applies to auto-generated columns).
 - Error number: [6487](#); Symbol: [ER_JDV_JOIN_CONDITION_NOT_SATISFIED](#); SQLSTATE: [HY000](#)

Message: Join condition is not satisfied as path '%s' for child column %s.%s is not equal to path '%s' for parent column %s.%s.
 - Error number: [6488](#); Symbol: [ER_JDV_PK_DUPLICATES_NOT_IDENTICAL](#); SQLSTATE: [HY000](#)

Message: Path '%s' is a duplicate for primary key column %s.%s but has conflicting values for column %s: path '%s' vs path '%s'
 - Error number: [6489](#); Symbol: [ER_JDV_UNMAPPED_KEY](#); SQLSTATE: [HY000](#)

Message: Path '%s' is not mapped to any column of %s.
 - Error number: [6490](#); Symbol: [ER_JDV_MISSING_INSERT_TAG](#); SQLSTATE: [HY000](#)

Message: Missing INSERT tag on table %s, path '%s'.

-
- Error number: [6491](#); Symbol: [ER_JDV_MISSING_READONLY_SUBOBJECT](#); SQLSTATE: [HY000](#)
Message: Read-only subobject with path '%s', maps to row where %s.%s = (%s), which does not exist.
 - Error number: [6492](#); Symbol: [ER_JDV_JOIN_CONDITION_VIOLATION](#); SQLSTATE: [HY000](#)
Message: Path '%s' references a READ-ONLY subobject for which column %s.%s violates the join condition of the attempted INSERT.
 - Error number: [6493](#); Symbol: [ER_JDV_MISSING_ETAG](#); SQLSTATE: [HY000](#)
Message: ETAG missing for updated value
 - Error number: [6494](#); Symbol: [ER_JDV_ETAG_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Cannot update JSON duality view. The ETAG of the document in the database did not match the ETAG '%s' passed in.
 - Error number: [6495](#); Symbol: [ER_JDV_MISSING_VALUE](#); SQLSTATE: [HY000](#)
Message: Value was not provided for path '%s' and could not be inferred for column %s.%s.
 - Error number: [6496](#); Symbol: [ER_JDV_PK_UPDATES_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: Cannot update primary key column %s.%s from path '%s'.
 - Error number: [6497](#); Symbol: [ER_JDV_MISSING_UPDATE_TAG](#); SQLSTATE: [HY000](#)
Message: Missing UPDATE tag on %s.%s, path '%s'.
 - Error number: [6498](#); Symbol: [ER_JDV_MISSING_DELETE_TAG](#); SQLSTATE: [HY000](#)
Message: Missing DELETE tag on table %s, path '%s'.
 - Error number: [6499](#); Symbol: [ER_JDV_NULL_INSERT_VALUE](#); SQLSTATE: [HY000](#)
Message: NULL is not allowed when inserting into a JSON DUALITY VIEW.
 - Error number: [6500](#); Symbol: [ER_JDV_INSERT_VALUE_NOT_FIXED](#); SQLSTATE: [HY000](#)
Message: Insert value must be fixed (not require resolving).
 - Error number: [6501](#); Symbol: [ER_JDV_NULL_UPDATE_VALUE](#); SQLSTATE: [HY000](#)
Message: NULL is not allowed when updating a JSON DUALITY VIEW.
 - Error number: [6502](#); Symbol: [ER_JDV_UPDATE_VALUE_NOT_FIXED](#); SQLSTATE: [HY000](#)
Message: Update values must be fixed (not require resolving).
 - Error number: [6503](#); Symbol: [ER_JDV_FEATURE_EDITION_LIMIT](#); SQLSTATE: [HY000](#)
Message: Feature not available in this edition.
 - Error number: [6504](#); Symbol: [ER_JDV_CANNOT_BE_USED_WITH](#); SQLSTATE: [HY000](#)
Message: JSON DUALITY VIEW %s cannot be used with %s.
 - Error number: [6505](#); Symbol: [ER_JDV_DML_INFO](#); SQLSTATE: [HY000](#)
Message: Rows affected: %ld Warnings: %ld.
 - Error number: [6507](#); Symbol: [ER_JDV_INVALID_BINARY_TYPE_HEADER](#); SQLSTATE: [HY000](#)

Message: Path '%s' is mapped to a binary column, but its value does not have a valid base64 type header.

- Error number: [6508](#); Symbol: [ER_ETAG_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: ETAG is not supported with Vector/ Geometry types.

- Error number: [6509](#); Symbol: [ER_ENGINE_ATTRIBUTE_CONFLICT](#); SQLSTATE: [HY000](#)

Message: ENGINE_ATTRIBUTE conflicts with %s %s.

- Error number: [6510](#); Symbol: [ER_EXTERNAL_FORMAT_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Column '%s': EXTERNAL_FORMAT is only supported for temporal data types.

- Error number: [6511](#); Symbol: [ER_EXTERNAL_TABLE_INVALID_OPTION](#); SQLSTATE: [HY000](#)

Message: Invalid option specified for %s of external table: %s

- Error number: [6512](#); Symbol: [ER_EXTERNAL_TABLE_ENGINE_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: The '%s' storage engine does not support external tables

- Error number: [6513](#); Symbol: [ER_EXTERNAL_TABLE_ENGINE_NOT_SPECIFIED](#); SQLSTATE: [HY000](#)

Message: External storage engine is not specified

- Error number: [6514](#); Symbol: [ER_LH_NO_FILES_FOUND_NO_SECURE_FILE_PRIV](#); SQLSTATE: [HY000](#)

Message: No files found or files provided not under secure-file-priv.

- Error number: [6515](#); Symbol: [ER_LH_COL_NAME_MISSING](#); SQLSTATE: [HY000](#)

Message: Column %d of %s: Column name is not present in the file header or metadata.

- Error number: [6516](#); Symbol: [ER_LH_COL_NAME_DUPLICATE](#); SQLSTATE: [HY000](#)

Message: File %s: Duplicate column name in the file header or metadata.

- Error number: [6517](#); Symbol: [ER_LH_UNSTRUCTURED_OCI_GENAI_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error when using OCI GenAI Service: %s

- Error number: [6518](#); Symbol: [ER_LH_UNSTRUCTURED_PARTIAL_FILE_PARSE_ERR](#); SQLSTATE: [HY000](#)

Message: File: %.*s – Part of the document was parsed. %s.

- Error number: [6519](#); Symbol: [ER_JDV_EXPLICIT_AUTO_INCREMENT_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Using 0 to request the next value of an AUTO_INCREMENT column is not allowed in JDVs, column %s.%s, referenced by path '%s', key '%s'.

- Error number: [6520](#); Symbol: [ER_LH_INFER_COL_NAME_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Column '%s' found in file '%s', but not in file '%s' during column name matching.

- Error number: [6521](#); Symbol: [ER_LH_DELTA_SCHEMA_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Detected schema mismatch for delta table: %s

-
- Error number: 6522; Symbol: [ER_LH_DELTA_METADATA_READ_ERROR](#); SQLSTATE: HY000
Message: Error while reading metadata for delta table: %s
 - Error number: 6523; Symbol: [ER_LH_DELTA_UNSUPPORTED_ERROR](#); SQLSTATE: HY000
Message: Feature %s of delta tables is unsupported
 - Error number: 6524; Symbol: [ER_WARN_ACCOUNT_TRIMMED](#); SQLSTATE: HY000
Message: Leading or trailing spaces have been trimmed from user or host, account: %s.
[ER_WARN_ACCOUNT_TRIMMED](#) was added in 9.5.1.
 - Error number: 6525; Symbol: [ER_LH_WARN_DATETIME_MULTIPLE_PARAM_USE](#); SQLSTATE: HY000
Message: Both 'datetime_format' and 'timestamp_format' are specified%s. Only 'datetime_format' will be considered.
[ER_LH_WARN_DATETIME_MULTIPLE_PARAM_USE](#) was added in 9.5.1.
 - Error number: 6526; Symbol: [ER_LH_GENCOL_ERROR](#); SQLSTATE: HY000
Message: File %.*s: Error encountered during generated column evaluation
[ER_LH_GENCOL_ERROR](#) was added in 9.5.1.
 - Error number: MY-010000; Symbol: [ER_PARSER_TRACE](#); SQLSTATE: XX999
Message: Parser saw: %s
 - Error number: MY-010001; Symbol: [ER_BOOTSTRAP_CANT_THREAD](#); SQLSTATE: HY000
Message: Can't create thread to handle bootstrap (errno: %d)
 - Error number: MY-010002; Symbol: [ER_TRIGGER_INVALID_VALUE](#); SQLSTATE: HY000
Message: Trigger for table '%s'. '%s': invalid %s value (%s).
 - Error number: MY-010003; Symbol: [ER_OPT_WRONG_TREE](#); SQLSTATE: HY000
Message: Wrong tree: %s
 - Error number: MY-010004; Symbol: [ER_DD_FAILSAFE](#); SQLSTATE: HY000
Message: Error: Invalid %s
 - Error number: MY-010005; Symbol: [ER_DD_NO_WRITES_NO_REPOPULATION](#); SQLSTATE: HY000
Message: Skip re-populating collations and character sets tables in %s%sread-only mode.
 - Error number: MY-010006; Symbol: [ER_DD_VERSION_FOUND](#); SQLSTATE: HY000
Message: Using data dictionary with version '%d'.
 - Error number: MY-010007; Symbol: [ER_DD_VERSION_INSTALLED](#); SQLSTATE: HY000
Message: Installed data dictionary with version %d
 - Error number: MY-010008; Symbol: [ER_DD_VERSION_UNSUPPORTED](#); SQLSTATE: HY000
Message: Data Dictionary version '%d' not supported.
 - Error number: MY-010010; Symbol: [ER_LOG_SYSLOG_CANNOT_OPEN](#); SQLSTATE: HY000

Message: Cannot open %s; check privileges, or remove syseventlog from --log-error-services!

- Error number: [MY-010011](#); Symbol: [ER_LOG_SLOW_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: either restart the query logging by using "SET GLOBAL SLOW_QUERY_LOG=ON" or

- Error number: [MY-010012](#); Symbol: [ER_LOG_GENERAL_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: either restart the query logging by using "SET GLOBAL GENERAL_LOG=ON" or

- Error number: [MY-010013](#); Symbol: [ER_LOG_CANNOT_WRITE](#); SQLSTATE: [HY000](#)

Message: Failed to write to %s: %s

- Error number: [MY-010015](#); Symbol: [ER_RPL_GTID_TABLE_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.

- Error number: [MY-010016](#); Symbol: [ER_SYSTEM_SCHEMA_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: System schema directory does not exist.

- Error number: [MY-010018](#); Symbol: [ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION](#); SQLSTATE: [HY000](#)

Message: View '%s'. '%s': unknown charset name and/or collation name (client: '%s'; connection: '%s').

- Error number: [MY-010019](#); Symbol: [ER_DD_VIEW_CANT_ALLOC_CHARSET](#); SQLSTATE: [HY000](#)

Message: Error in allocating memory for character set name for view %s.%s.

- Error number: [MY-010020](#); Symbol: [ER_DD_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Data Dictionary initialization failed.

- Error number: [MY-010021](#); Symbol: [ER_DD_UPDATING_PLUGIN_MD_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to update plugin metadata in dictionary tables.

- Error number: [MY-010023](#); Symbol: [ER_DD_VIEW_CANT_CREATE](#); SQLSTATE: [HY000](#)

Message: Error in Creating View %s.%s

- Error number: [MY-010024](#); Symbol: [ER_DD_METADATA_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. Cannot find the meta data for data dictionary table '%s'.

- Error number: [MY-010025](#); Symbol: [ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Dictionary cache not empty at shutdown.

- Error number: [MY-010026](#); Symbol: [ER_DD_OBJECT_REMAINS](#); SQLSTATE: [HY000](#)

Message: Dictionary objects used but not released.

- Error number: [MY-010027](#); Symbol: [ER_DD_OBJECT_REMAINS_IN_RELEASER](#); SQLSTATE: [HY000](#)

Message: Dictionary objects left in default releaser.

- Error number: [MY-010028](#); Symbol: [ER_DD_OBJECT_RELEASER_REMAINS](#); SQLSTATE: [HY000](#)

Message: Dictionary object auto releaser not deleted

- Error number: [MY-010029](#); Symbol: [ER_DD_CANT_GET_OBJECT_KEY](#); SQLSTATE: [HY000](#)

Message: Error: Unable to create primary object key

- Error number: [MY-010030](#); Symbol: [ER_DD_CANT_CREATE_OBJECT_KEY](#); SQLSTATE: [HY000](#)

Message: Error: Unable to create object key

- Error number: [MY-010031](#); Symbol: [ER_CANT_CREATE_HANDLE_MGR_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create handle_manager thread (errno= %d)

- Error number: [MY-010032](#); Symbol: [ER_RPL_REPO_HAS_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log's repository because there are workers' repositories with gaps. Please, fix the gaps first before doing such change.

- Error number: [MY-010033](#); Symbol: [ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: option 'enforce-gtid-consistency': value '%s' was not recognized. Setting enforce-gtid-consistency to OFF.

- Error number: [MY-010034](#); Symbol: [ER_CHANGED_ENFORCE_GTID_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: Changed ENFORCE_GTID_CONSISTENCY from %s to %s.

- Error number: [MY-010035](#); Symbol: [ER_CHANGED_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: Changed GTID_MODE from %s to %s.

- Error number: [MY-010036](#); Symbol: [ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT](#); SQLSTATE: [HY000](#)

Message: %s is set to a disabled storage engine %s.

- Error number: [MY-010037](#); Symbol: [ER_DEBUG_SYNC_HIT](#); SQLSTATE: [HY000](#)

Message: Debug sync points hit: %s

- Error number: [MY-010038](#); Symbol: [ER_DEBUG_SYNC_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Debug sync points executed: %s

- Error number: [MY-010039](#); Symbol: [ER_DEBUG_SYNC_THREAD_MAX](#); SQLSTATE: [HY000](#)

Message: Debug sync points max active per thread: %s

- Error number: [MY-010040](#); Symbol: [ER_DEBUG_SYNC_OOM](#); SQLSTATE: [HY000](#)

Message: Debug Sync Facility disabled due to lack of memory.

- Error number: [MY-010041](#); Symbol: [ER_CANT_INIT_TC_LOG](#); SQLSTATE: [HY000](#)

Message: Can't init tc log

- Error number: [MY-010042](#); Symbol: [ER_EVENT_CANT_INIT_QUEUE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Can't initialize the execution queue

-
- Error number: [MY-010043](#); Symbol: [ER_EVENT_PURGING_QUEUE](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Purging the queue. %u events
 - Error number: [MY-010044](#); Symbol: [ER_EVENT_LAST_EXECUTION](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Last execution of %s.%s. %s
 - Error number: [MY-010045](#); Symbol: [ER_EVENT_MESSAGE_STACK](#); SQLSTATE: [HY000](#)
Message: %*s
 - Error number: [MY-010046](#); Symbol: [ER_EVENT_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: [%s].[%s.%s] event execution failed.
 - Error number: [MY-010047](#); Symbol: [ER_CANT_INIT_SCHEDULER_THREAD](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Cannot initialize the scheduler thread
 - Error number: [MY-010048](#); Symbol: [ER_SCHEDULER_STOPPED](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Stopped
 - Error number: [MY-010049](#); Symbol: [ER_CANT_CREATE_SCHEDULER_THREAD](#); SQLSTATE: [HY000](#)
Message: Event scheduler: Failed to start scheduler, Can not create thread for event scheduler (errno=%d)
 - Error number: [MY-010050](#); Symbol: [ER_SCHEDULER_WAITING](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Waiting for the scheduler thread to reply
 - Error number: [MY-010051](#); Symbol: [ER_SCHEDULER_STARTED](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: scheduler thread started with id %u
 - Error number: [MY-010052](#); Symbol: [ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Serious error during getting next event to execute. Stopping
 - Error number: [MY-010053](#); Symbol: [ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER](#); SQLSTATE: [HY000](#)
Message: Event_scheduler::execute_top: Can not create event worker thread (errno=%d). Stopping event scheduler
 - Error number: [MY-010054](#); Symbol: [ER_SCHEDULER_KILLING](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Killing the scheduler thread, thread id %u
 - Error number: [MY-010055](#); Symbol: [ER_UNABLE_TO_RESOLVE_IP](#); SQLSTATE: [HY000](#)
Message: IP address '%s' could not be resolved: %s
 - Error number: [MY-010056](#); Symbol: [ER_UNABLE_TO_RESOLVE_HOSTNAME](#); SQLSTATE: [HY000](#)
Message: Host name '%s' could not be resolved: %s
 - Error number: [MY-010057](#); Symbol: [ER_HOSTNAME_RESEMBLES_IPV4](#); SQLSTATE: [HY000](#)
Message: IP address '%s' has been resolved to the host name '%s', which resembles IPv4-address itself.

-
- Error number: [MY-010058](#); Symbol: [ER_HOSTNAME_DOESNT_RESOLVE_TO](#); SQLSTATE: [HY000](#)
Message: Hostname '%s' does not resolve to '%s'.
 - Error number: [MY-010059](#); Symbol: [ER_ADDRESSES_FOR_HOSTNAME_HEADER](#); SQLSTATE: [HY000](#)
Message: Hostname '%s' has the following IP addresses:
 - Error number: [MY-010060](#); Symbol: [ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM](#); SQLSTATE: [HY000](#)
Message: - %s
 - Error number: [MY-010061](#); Symbol: [ER_TRG_WITHOUT_DEFINER](#); SQLSTATE: [HY000](#)
Message: Definer clause is missing in Trigger of Table %s. Rebuild Trigger to fix definer.
 - Error number: [MY-010062](#); Symbol: [ER_TRG_NO_CLIENT_CHARSET](#); SQLSTATE: [HY000](#)
Message: Client character set is missing for trigger of table %s. Using default character set.
 - Error number: [MY-010063](#); Symbol: [ER_PARSING_VIEW](#); SQLSTATE: [HY000](#)
Message: Error in parsing view %s.%s
 - Error number: [MY-010064](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP](#); SQLSTATE: [HY000](#)
Message: Failed to bootstrap components infrastructure.
 - Error number: [MY-010065](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Failed to shutdown components infrastructure.
 - Error number: [MY-010066](#); Symbol: [ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP](#); SQLSTATE: [HY000](#)
Message: Failed to bootstrap persistent components loader.
 - Error number: [MY-010067](#); Symbol: [ER_DEPART_WITH_GRACE](#); SQLSTATE: [HY000](#)
Message: Giving %d client threads a chance to die gracefully
 - Error number: [MY-010068](#); Symbol: [ER_CA_SELF_SIGNED](#); SQLSTATE: [HY000](#)
Message: CA certificate %s is self signed.
 - Error number: [MY-010069](#); Symbol: [ER_SSL_LIBRARY_ERROR](#); SQLSTATE: [HY000](#)
Message: Failed to set up SSL because of the following SSL library error: %s
 - Error number: [MY-010070](#); Symbol: [ER_NO_THD_NO_UUID](#); SQLSTATE: [HY000](#)
Message: Failed to generate a server UUID because it is failed to allocate the THD.
 - Error number: [MY-010071](#); Symbol: [ER_UUID_SALT](#); SQLSTATE: [HY000](#)
Message: Salting uuid generator variables, current_pid: %lu, server_start_time: %lu, bytes_sent: %llu,
 - Error number: [MY-010072](#); Symbol: [ER_UUID_IS](#); SQLSTATE: [HY000](#)

Message: Generated uuid: '%s', server_start_time: %lu, bytes_sent: %llu

- Error number: [MY-010073](#); Symbol: [ER_UUID_INVALID](#); SQLSTATE: [HY000](#)

Message: The server_uuid stored in auto.cnf file is not a valid UUID.

- Error number: [MY-010074](#); Symbol: [ER_UUID_SCRUB](#); SQLSTATE: [HY000](#)

Message: Garbage characters found at the end of the server_uuid value in auto.cnf file. It should be of length '%d' (UUID_LENGTH). Clear it and restart the server.

- Error number: [MY-010075](#); Symbol: [ER_CREATING_NEW_UUID](#); SQLSTATE: [HY000](#)

Message: No existing UUID has been found, so we assume that this is the first time that this server has been started. Generating a new UUID: %s.

- Error number: [MY-010076](#); Symbol: [ER_CANT_CREATE_UUID](#); SQLSTATE: [HY000](#)

Message: Initialization of the server's UUID failed because it could not be read from the auto.cnf file. If this is a new server, the initialization failed because it was not possible to generate a new UUID.

- Error number: [MY-010077](#); Symbol: [ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unknown/unsupported storage engine: %s

- Error number: [MY-010078](#); Symbol: [ER_SECURE_AUTH_VALUE_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Unsupported value 0 for secure-auth

- Error number: [MY-010079](#); Symbol: [ER_INVALID_INSTRUMENT](#); SQLSTATE: [HY000](#)

Message: Invalid instrument name or value for performance_schema_instrument '%s'.

- Error number: [MY-010080](#); Symbol: [ER_INNODB_MANDATORY](#); SQLSTATE: [HY000](#)

Message: The use of InnoDB is mandatory since MySQL 5.7. The former options like '--innodb=0/1/OFF/ON' or '--skip-innodb' are ignored.

- Error number: [MY-010083](#); Symbol: [ER_VERBOSE_REQUIRES_HELP](#); SQLSTATE: [HY000](#)

Message: --verbose is for use with --help; did you mean --log-error-verbosity?

- Error number: [MY-010084](#); Symbol: [ER_POINTLESS_WITHOUT_SLOWLOG](#); SQLSTATE: [HY000](#)

Message: options --log-slow-admin-statements, --log-queries-not-using-indexes and --log-slow-replica-statements have no effect if --slow-query-log is not set

- Error number: [MY-010085](#); Symbol: [ER_WASTEFUL_NET_BUFFER_SIZE](#); SQLSTATE: [HY000](#)

Message: net_buffer_length (%lu) is set to be larger than max_allowed_packet (%lu). Please rectify.

- Error number: [MY-010086](#); Symbol: [ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS](#); SQLSTATE: [HY000](#)

Message: TIMESTAMP with implicit DEFAULT value is deprecated. Please use --explicit_defaults_for_timestamp server option (see documentation for more details).

- Error number: [MY-010087](#); Symbol: [ER_FT_BOOL_SYNTAX_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid ft-boolean-syntax string: %s

-
- Error number: [MY-010088](#); Symbol: [ER_CREDENTIALLESS_AUTO_USER_BAD](#); SQLSTATE: [HY000](#)
Message: 'NO_AUTO_CREATE_USER' sql mode was not set.
 - Error number: [MY-010089](#); Symbol: [ER_CONNECTION_HANDLING_OOM](#); SQLSTATE: [HY000](#)
Message: Could not allocate memory for connection handling
 - Error number: [MY-010090](#); Symbol: [ER_THREAD_HANDLING_OOM](#); SQLSTATE: [HY000](#)
Message: Could not allocate memory for thread handling
 - Error number: [MY-010091](#); Symbol: [ER_CANT_CREATE_TEST_FILE](#); SQLSTATE: [HY000](#)
Message: Can't create test file %s
 - Error number: [MY-010092](#); Symbol: [ER_CANT_CREATE_PID_FILE](#); SQLSTATE: [HY000](#)
Message: Can't start server: can't create PID file: %s
 - Error number: [MY-010093](#); Symbol: [ER_CANT_REMOVE_PID_FILE](#); SQLSTATE: [HY000](#)
Message: Unable to delete pid file: %s
 - Error number: [MY-010094](#); Symbol: [ER_CANT_CREATE_SHUTDOWN_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create thread to handle shutdown requests (errno= %d)
 - Error number: [MY-010095](#); Symbol: [ER_SEC_FILE_PRIV_CANT_ACCESS_DIR](#); SQLSTATE: [HY000](#)
Message: Failed to access directory for --secure-file-priv. Please make sure that directory exists and is accessible by MySQL Server. Supplied value : %s
 - Error number: [MY-010096](#); Symbol: [ER_SEC_FILE_PRIV_IGNORED](#); SQLSTATE: [HY000](#)
Message: Ignoring --secure-file-priv value as server is running with --initialize(-insecure).
 - Error number: [MY-010097](#); Symbol: [ER_SEC_FILE_PRIV_EMPTY](#); SQLSTATE: [HY000](#)
Message: Insecure configuration for --secure-file-priv: Current value does not restrict location of generated files. Consider setting it to a valid, non-empty path.
 - Error number: [MY-010098](#); Symbol: [ER_SEC_FILE_PRIV_NULL](#); SQLSTATE: [HY000](#)
Message: --secure-file-priv is set to NULL. Operations related to importing and exporting data are disabled
 - Error number: [MY-010099](#); Symbol: [ER_SEC_FILE_PRIV_DIRECTORY_INSECURE](#); SQLSTATE: [HY000](#)
Message: Insecure configuration for --secure-file-priv: %s is accessible through --secure-file-priv. Consider choosing a different directory.
 - Error number: [MY-010100](#); Symbol: [ER_SEC_FILE_PRIV_CANT_STAT](#); SQLSTATE: [HY000](#)
Message: Failed to get stat for directory pointed out by --secure-file-priv
 - Error number: [MY-010101](#); Symbol: [ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS](#); SQLSTATE: [HY000](#)
Message: Insecure configuration for --secure-file-priv: Location is accessible to all OS users. Consider choosing a different directory.

-
- Error number: [MY-010102](#); Symbol: [ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Value for --secure-file-priv is longer than maximum limit of %d
 - Error number: [MY-010103](#); Symbol: [ER_CANT_CREATE_NAMED_PIPES_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create thread to handle named pipes (errno= %d)
 - Error number: [MY-010104](#); Symbol: [ER_CANT_CREATE_TCPIP_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create thread to handle TCP/IP (errno= %d)
 - Error number: [MY-010105](#); Symbol: [ER_CANT_CREATE_SHM_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create thread to handle shared memory (errno= %d)
 - Error number: [MY-010106](#); Symbol: [ER_CANT_CREATE_INTERRUPT_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create interrupt-thread (error %d, errno: %d)
 - Error number: [MY-010107](#); Symbol: [ER_WRITABLE_CONFIG_REMOVED](#); SQLSTATE: [HY000](#)
Message: World-writable config file '%s' has been removed.
 - Error number: [MY-010108](#); Symbol: [ER_CORE_VALUES](#); SQLSTATE: [HY000](#)
Message: setrlimit could not change the size of core files to 'infinity'; We may not be able to generate a core file on signals
 - Error number: [MY-010109](#); Symbol: [ER_WRONG_DATETIME_SPEC](#); SQLSTATE: [HY000](#)
Message: Wrong date/time format specifier: %s
 - Error number: [MY-010110](#); Symbol: [ER_RPL_BINLOG_FILTERS_OOM](#); SQLSTATE: [HY000](#)
Message: Could not allocate replication and binlog filters: %s
 - Error number: [MY-010111](#); Symbol: [ER_KEYCACHE_OOM](#); SQLSTATE: [HY000](#)
Message: Cannot allocate the keycache
 - Error number: [MY-010112](#); Symbol: [ER_CONFIRMING_THE_FUTURE](#); SQLSTATE: [HY000](#)
Message: Current time has got past year 2038. Validating current time with %d iterations before initiating the normal server shutdown process.
 - Error number: [MY-010113](#); Symbol: [ER_BACK_IN_TIME](#); SQLSTATE: [HY000](#)
Message: Iteration %d: Obtained valid current time from system
 - Error number: [MY-010114](#); Symbol: [ER_FUTURE_DATE](#); SQLSTATE: [HY000](#)
Message: Iteration %d: Current time obtained from system is greater than 2038
 - Error number: [MY-010115](#); Symbol: [ER_UNSUPPORTED_DATE](#); SQLSTATE: [HY000](#)
Message: This MySQL server doesn't support dates later then 2038
 - Error number: [MY-010116](#); Symbol: [ER_STARTING_AS](#); SQLSTATE: [HY000](#)
Message: %s (mysqld %s) starting as process %lu

-
- Error number: [MY-010117](#); Symbol: [ER_SHUTTING_DOWN_REPLICA_THREADS](#); SQLSTATE: [HY000](#)
Message: Shutting down replica threads
 - Error number: [MY-010118](#); Symbol: [ER_DISCONNECTING_REMAINING_CLIENTS](#); SQLSTATE: [HY000](#)
Message: Forcefully disconnecting %d remaining clients
 - Error number: [MY-010119](#); Symbol: [ER_ABORTING](#); SQLSTATE: [HY000](#)
Message: Aborting
 - Error number: [MY-010120](#); Symbol: [ER_BINLOG_END](#); SQLSTATE: [HY000](#)
Message: Binlog end
 - Error number: [MY-010121](#); Symbol: [ER_CALL_ME_LOCALHOST](#); SQLSTATE: [HY000](#)
Message: gethostname failed, using '%s' as hostname
 - Error number: [MY-010122](#); Symbol: [ER_USER_REQUIRES_ROOT](#); SQLSTATE: [HY000](#)
Message: One can only use the --user switch if running as root
 - Error number: [MY-010123](#); Symbol: [ER REALLY RUN AS ROOT](#); SQLSTATE: [HY000](#)
Message: Fatal error: Please read "Security" section of the manual to find out how to run mysqld as root!
 - Error number: [MY-010124](#); Symbol: [ER_USER_WHAT_USER](#); SQLSTATE: [HY000](#)
Message: Fatal error: Can't change to run as user '%s' ; Please check that the user exists!
 - Error number: [MY-010125](#); Symbol: [ER_TRANSPORTS_WHAT_TRANSPORTS](#); SQLSTATE: [HY000](#)
Message: Server is started with --require-secure-transport=ON but no secure transports (SSL or Shared Memory) are configured.
 - Error number: [MY-010126](#); Symbol: [ER_FAIL_SETGID](#); SQLSTATE: [HY000](#)
Message: setgid: %s
 - Error number: [MY-010127](#); Symbol: [ER_FAIL_SETUID](#); SQLSTATE: [HY000](#)
Message: setuid: %s
 - Error number: [MY-010128](#); Symbol: [ER_FAIL_SETREGID](#); SQLSTATE: [HY000](#)
Message: setregid: %s
 - Error number: [MY-010129](#); Symbol: [ER_FAIL_SETREUID](#); SQLSTATE: [HY000](#)
Message: setreuid: %s
 - Error number: [MY-010130](#); Symbol: [ER_FAIL_CHROOT](#); SQLSTATE: [HY000](#)
Message: chroot: %s
 - Error number: [MY-010131](#); Symbol: [ER_WIN_LISTEN_BUT_HOW](#); SQLSTATE: [HY000](#)
Message: TCP/IP, --shared-memory, or --named-pipe should be configured on NT OS

-
- Error number: [MY-010132](#); Symbol: [ER_NOT_RIGHT_NOW](#); SQLSTATE: [HY000](#)
Message: CTRL-C ignored during startup
 - Error number: [MY-010133](#); Symbol: [ER_FIXING_CLIENT_CHARSET](#); SQLSTATE: [HY000](#)
Message: '%s' can not be used as client character set. '%s' will be used as default client character set.
 - Error number: [MY-010134](#); Symbol: [ER_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory
 - Error number: [MY-010135](#); Symbol: [ER_FAILED_TO_LOCK_MEM](#); SQLSTATE: [HY000](#)
Message: Failed to lock memory. Errno: %d
 - Error number: [MY-010136](#); Symbol: [ER_MYINIT_FAILED](#); SQLSTATE: [HY000](#)
Message: my_init() failed.
 - Error number: [MY-010137](#); Symbol: [ER_BEG_INITFILE](#); SQLSTATE: [HY000](#)
Message: Execution of init_file '%s' started.
 - Error number: [MY-010138](#); Symbol: [ER_END_INITFILE](#); SQLSTATE: [HY000](#)
Message: Execution of init_file '%s' ended.
 - Error number: [MY-010139](#); Symbol: [ER_CHANGED_MAX_OPEN_FILES](#); SQLSTATE: [HY000](#)
Message: Changed limits: max_open_files: %lu (requested %lu)
 - Error number: [MY-010140](#); Symbol: [ER_CANT_INCREASE_MAX_OPEN_FILES](#); SQLSTATE: [HY000](#)
Message: Could not increase number of max_open_files to more than %lu (request: %lu)
 - Error number: [MY-010141](#); Symbol: [ER_CHANGED_MAX_CONNECTIONS](#); SQLSTATE: [HY000](#)
Message: Changed limits: max_connections: %lu (requested %lu)
 - Error number: [MY-010142](#); Symbol: [ER_CHANGED_TABLE_OPEN_CACHE](#); SQLSTATE: [HY000](#)
Message: Changed limits: table_open_cache: %lu (requested %lu)
 - Error number: [MY-010143](#); Symbol: [ER_THE_USER_ABIDES](#); SQLSTATE: [HY000](#)
Message: Ignoring user change to '%s' because the user was set to '%s' earlier on the command line
 - Error number: [MY-010144](#); Symbol: [ER_RPL_CANT_ADD_DO_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not add do table rule '%s'!
 - Error number: [MY-010145](#); Symbol: [ER_RPL_CANT_ADD_IGNORE_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not add ignore table rule '%s'!
 - Error number: [MY-010146](#); Symbol: [ER_TRACK_VARIABLES_BOGUS](#); SQLSTATE: [HY000](#)
Message: The variable session_track_system_variables either has duplicate values or invalid values.
 - Error number: [MY-010147](#); Symbol: [ER_EXCESS_ARGUMENTS](#); SQLSTATE: [HY000](#)
Message: Too many arguments (first extra is '%s').

-
- Error number: [MY-010148](#); Symbol: [ER_VERBOSE_HINT](#); SQLSTATE: [HY000](#)
Message: Use --verbose --help to get a list of available options!
 - Error number: [MY-010149](#); Symbol: [ER_CANT_READ_ERRMSG](#); SQLSTATE: [HY000](#)
Message: Unable to read errmsg.sys file
 - Error number: [MY-010150](#); Symbol: [ER_CANT_INIT_DBS](#); SQLSTATE: [HY000](#)
Message: Can't init databases
 - Error number: [MY-010151](#); Symbol: [ER_LOG_OUTPUT_CONTRADICTORY](#); SQLSTATE: [HY000](#)
Message: There were other values specified to log-output besides NONE. Disabling slow and general logs anyway.
 - Error number: [MY-010152](#); Symbol: [ER_NO_CSV_NO_LOG_TABLES](#); SQLSTATE: [HY000](#)
Message: CSV engine is not present, falling back to the log files
 - Error number: [MY-010153](#); Symbol: [ER_RPL_REWRITEDB_MISSING_ARROW](#); SQLSTATE: [HY000](#)
Message: Bad syntax in replicate-rewrite-db - missing '->'
 - Error number: [MY-010154](#); Symbol: [ER_RPL_REWRITEDB_EMPTY_FROM](#); SQLSTATE: [HY000](#)
Message: Bad syntax in replicate-rewrite-db - empty FROM db!
 - Error number: [MY-010155](#); Symbol: [ER_RPL_REWRITEDB_EMPTY_TO](#); SQLSTATE: [HY000](#)
Message: Bad syntax in replicate-rewrite-db - empty TO db!
 - Error number: [MY-010156](#); Symbol: [ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE](#); SQLSTATE: [HY000](#)
Message: Although a path was specified for the %s, log tables are used. To enable logging to files use the --log-output=file option.
 - Error number: [MY-010157](#); Symbol: [ER_LOG_FILE_INVALID](#); SQLSTATE: [HY000](#)
Message: Invalid value for %s: %s
 - Error number: [MY-010158](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: The server option 'lower_case_table_names' is configured to use case sensitive table names but the data directory is on a case-insensitive file system which is an unsupported combination. Please consider either using a case sensitive file system for your data directory or switching to a case-insensitive table name mode.
 - Error number: [MY-010159](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_USING_2](#); SQLSTATE: [HY000](#)
Message: Setting lower_case_table_names=2 because file system for %s is case insensitive
 - Error number: [MY-010160](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_USING_0](#); SQLSTATE: [HY000](#)
Message: lower_case_table_names was set to 2, even though your the file system '%s' is case sensitive. Now setting lower_case_table_names to 0 to avoid future problems.
 - Error number: [MY-010161](#); Symbol: [ER_NEED_LOG_BIN](#); SQLSTATE: [HY000](#)

Message: You need to use --log-bin to make %s work.

- Error number: [MY-010162](#); Symbol: [ER_NEED_FILE_INSTEAD_OF_DIR](#); SQLSTATE: [HY000](#)

Message: Path '%s' is a directory name, please specify a file name for %s option

- Error number: [MY-010163](#); Symbol: [ER_LOG_BIN_BETTER_WITH_NAME](#); SQLSTATE: [HY000](#)

Message: No argument was provided to --log-bin, and --log-bin-index was not used; so replication may break when this MySQL server acts as a source and has his hostname changed!! Please use '--log-bin=%s' to avoid this problem.

- Error number: [MY-010164](#); Symbol: [ER_BINLOG_NEEDS_SERVERID](#); SQLSTATE: [HY000](#)

Message: You have enabled the binary log, but you haven't provided the mandatory server-id. Please refer to the proper server start-up parameters documentation

- Error number: [MY-010165](#); Symbol: [ER_RPL_CANT_MAKE_PATHS](#); SQLSTATE: [HY000](#)

Message: Unable to create replication path names: out of memory or path names too long (path name exceeds %d or file name exceeds %d).

- Error number: [MY-010166](#); Symbol: [ER_CANT_INITIALIZE_GTID](#); SQLSTATE: [HY000](#)

Message: Failed to initialize GTID structures.

- Error number: [MY-010167](#); Symbol: [ER_CANT_INITIALIZE_EARLY_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize early plugins.

- Error number: [MY-010168](#); Symbol: [ER_CANT_INITIALIZE_BUILTIN_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize builtin plugins.

- Error number: [MY-010169](#); Symbol: [ER_CANT_INITIALIZE_DYNAMIC_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize dynamic plugins.

- Error number: [MY-010170](#); Symbol: [ER_PERFSCHEMA_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Performance schema disabled (reason: init failed).

- Error number: [MY-010171](#); Symbol: [ER_STACKSIZE_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Asked for %lu thread stack, but got %ld

- Error number: [MY-010173](#); Symbol: [ER_CANT_STAT_DATADIR](#); SQLSTATE: [HY000](#)

Message: Can't read data directory's stats (%d): %s. Assuming that it's not owned by the same user/group

- Error number: [MY-010174](#); Symbol: [ER_CANT_CHOWN_DATADIR](#); SQLSTATE: [HY000](#)

Message: Can't change data directory owner to %s

- Error number: [MY-010175](#); Symbol: [ER_CANT_SET_UP_PERSISTED_VALUES](#); SQLSTATE: [HY000](#)

Message: Setting persistent options failed.

- Error number: [MY-010176](#); Symbol: [ER_CANT_SAVE_GTIDS](#); SQLSTATE: [HY000](#)

Message: Failed to save the set of Global Transaction Identifiers of the last binary log into the mysql.gtid_executed table while the server was shutting down. The next server restart will make another attempt to save Global Transaction Identifiers into the table.

- Error number: [MY-010178](#); Symbol: [ER_CANT_JOIN_SHUTDOWN_THREAD](#); SQLSTATE: [HY000](#)

Message: Could not join %sthread. error:%d

- Error number: [MY-010179](#); Symbol: [ER_CANT_HASH_DO_AND_IGNORE_RULES](#); SQLSTATE: [HY000](#)

Message: An error occurred while building do_table and ignore_table rules to hashes for global replication filter.

- Error number: [MY-010180](#); Symbol: [ER_CANT_OPEN_CA](#); SQLSTATE: [HY000](#)

Message: Error opening CA certificate file

- Error number: [MY-010181](#); Symbol: [ER_CANT_ACCESS_CAPATH](#); SQLSTATE: [HY000](#)

Message: Error accessing directory pointed by --ssl-capath

- Error number: [MY-010182](#); Symbol: [ER_SSL_TRYING_DATADIR_DEFAULTS](#); SQLSTATE: [HY000](#)

Message: Found %s, %s and %s in data directory. Trying to enable SSL support using them.

- Error number: [MY-010183](#); Symbol: [ER_AUTO_OPTIONS_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create %s(file: '%s', errno %d)

- Error number: [MY-010184](#); Symbol: [ER_CANT_INIT_TIMER](#); SQLSTATE: [HY000](#)

Message: Failed to initialize timer component (errno %d).

- Error number: [MY-010185](#); Symbol: [ER_SERVERID_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: server-id configured is too large to represent with server-id-bits configured.

- Error number: [MY-010186](#); Symbol: [ER_DEFAULT_SE_UNAVAILABLE](#); SQLSTATE: [HY000](#)

Message: Default%s storage engine (%s) is not available

- Error number: [MY-010187](#); Symbol: [ER_CANT_OPEN_ERROR_LOG](#); SQLSTATE: [HY000](#)

Message: Could not open file '%s' for error logging%s%s

- Error number: [MY-010188](#); Symbol: [ER_INVALID_ERROR_LOG_NAME](#); SQLSTATE: [HY000](#)

Message: Invalid log file name after expanding symlinks: '%s'

- Error number: [MY-010189](#); Symbol: [ER_RPL_INFINITY_DENIED](#); SQLSTATE: [HY000](#)

Message: using --replicate-same-server-id in conjunction with --log-replica-updates is impossible, it would lead to infinite loops in this server.

- Error number: [MY-010190](#); Symbol: [ER_RPL_INFINITY_IGNORED](#); SQLSTATE: [HY000](#)

Message: using --replicate-same-server-id in conjunction with --log-replica-updates would lead to infinite loops in this server. However this will be ignored as the --log-bin option is not defined or your server is running with global transaction identifiers enabled.

- Error number: [MY-010192](#); Symbol: [ER_TABLE_CHECK_INTACT](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-010193](#); Symbol: [ER_DD_TABLESPACE_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Unable to start server. The data dictionary tablespace '%s' does not exist.
 - Error number: [MY-010194](#); Symbol: [ER_DD_TRG_CONNECTION_COLLATION_MISSING](#); SQLSTATE: [HY000](#)
Message: Connection collation is missing for trigger of table %s. Using default connection collation.
 - Error number: [MY-010195](#); Symbol: [ER_DD_TRG_DB_COLLATION_MISSING](#); SQLSTATE: [HY000](#)
Message: Database collation is missing for trigger of table %s. Using Default character set.
 - Error number: [MY-010196](#); Symbol: [ER_DD_TRG_DEFINER_OOM](#); SQLSTATE: [HY000](#)
Message: Error in Memory allocation for Definer %s for Trigger.
 - Error number: [MY-010197](#); Symbol: [ER_DD_TRG_FILE_UNREADABLE](#); SQLSTATE: [HY000](#)
Message: Error in reading %s.TRG file.
 - Error number: [MY-010198](#); Symbol: [ER_TRG_CANT_PARSE](#); SQLSTATE: [HY000](#)
Message: Error in parsing Triggers from %s.TRG file.
 - Error number: [MY-010199](#); Symbol: [ER_DD_TRG_CANT_ADD](#); SQLSTATE: [HY000](#)
Message: Error in creating DD entry for Trigger %s.%s
 - Error number: [MY-010200](#); Symbol: [ER_DD_CANT_RESOLVE_VIEW](#); SQLSTATE: [HY000](#)
Message: Resolving dependency for the view '%s.%s' failed. View is no more valid to use
 - Error number: [MY-010201](#); Symbol: [ER_DD_VIEW_WITHOUT_DEFINER](#); SQLSTATE: [HY000](#)
Message: %s.%s has no definer (as per an old view format). Current user is used as definer. Please recreate the view.
 - Error number: [MY-010202](#); Symbol: [ER_PLUGIN_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' init function returned error.
 - Error number: [MY-010203](#); Symbol: [ER_RPL_TRX_DELEGATES_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Initialization of transaction delegates failed. Please report a bug.
 - Error number: [MY-010204](#); Symbol: [ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Initialization binlog storage delegates failed. Please report a bug.
 - Error number: [MY-010205](#); Symbol: [ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Initialization of binlog transmit delegates failed. Please report a bug.
 - Error number: [MY-010206](#); Symbol: [ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Initialization binlog relay IO delegates failed. Please report a bug.
 - Error number: [MY-010207](#); Symbol: [ER_RPL_PLUGIN_FUNCTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Run function '...' in plugin '%s' failed

-
- Error number: [MY-010208](#); Symbol: [ER_SQL_HA_READ_FAILED](#); SQLSTATE: [HY000](#)
Message: mysql_ha_read: Got error %d when reading table '%s'
 - Error number: [MY-010209](#); Symbol: [ER_SR_BOGUS_VALUE](#); SQLSTATE: [HY000](#)
Message: Stored routine '%s'. '%s': invalid value in column %s.
 - Error number: [MY-010210](#); Symbol: [ER_SR_INVALID_CONTEXT](#); SQLSTATE: [HY000](#)
Message: Invalid creation context '%s.%s'.
 - Error number: [MY-010211](#); Symbol: [ER_READING_TABLE_FAILED](#); SQLSTATE: [HY000](#)
Message: Got error %d when reading table '%s'
 - Error number: [MY-010212](#); Symbol: [ER_DES_FILE_WRONG_KEY](#); SQLSTATE: [HY000](#)
Message: load_des_file: Found wrong key_number: %c
 - Error number: [MY-010214](#); Symbol: [ER_JSON_PARSE_ERROR](#); SQLSTATE: [HY000](#)
Message: Persisted config file is corrupt. Please ensure mysqld-auto.cnf file is valid JSON.
 - Error number: [MY-010215](#); Symbol: [ER_CONFIG_OPTION_WITHOUT_GROUP](#); SQLSTATE: [HY000](#)
Message: Found option without preceding group in config file
 - Error number: [MY-010216](#); Symbol: [ER_VALGRIND_DO_QUICK_LEAK_CHECK](#); SQLSTATE: [HY000](#)
Message: VALGRIND_DO_QUICK_LEAK_CHECK
 - Error number: [MY-010217](#); Symbol: [ER_VALGRIND_COUNT_LEAKS](#); SQLSTATE: [HY000](#)
Message: VALGRIND_COUNT_LEAKS reports %lu leaked bytes for query '%.*s'
 - Error number: [MY-010218](#); Symbol: [ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY](#); SQLSTATE: [HY000](#)
Message: LOAD DATA INFILE in the replica SQL Thread can only read from --replica-load-tmpdir. Please, report a bug.
 - Error number: [MY-010219](#); Symbol: [ER_UNKNOWN_ERROR_NUMBER](#); SQLSTATE: [HY000](#)
Message: Got unknown error: %d
 - Error number: [MY-010220](#); Symbol: [ER_UDF_CANT_ALLOC_FOR_STRUCTURES](#); SQLSTATE: [HY000](#)
Message: Can't allocate memory for udf structures
 - Error number: [MY-010221](#); Symbol: [ER_UDF_CANT_ALLOC_FOR_FUNCTION](#); SQLSTATE: [HY000](#)
Message: Can't alloc memory for udf function: '%s'
 - Error number: [MY-010222](#); Symbol: [ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE](#); SQLSTATE: [HY000](#)
Message: Invalid row in mysql.func table for function '%s'
 - Error number: [MY-010223](#); Symbol: [ER_UDF_CANT_OPEN_FUNCTION_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not open the mysql.func table. Please perform the MySQL upgrade procedure.

-
- Error number: [MY-010224](#); Symbol: [ER_XA_RECOVER_FOUND_TRX_IN_SE](#); SQLSTATE: [HY000](#)
Message: Found %d prepared transaction(s) in %s
 - Error number: [MY-010225](#); Symbol: [ER_XA_RECOVER_FOUND_XA_TRX](#); SQLSTATE: [HY000](#)
Message: Found %d prepared XA transactions
 - Error number: [MY-010229](#); Symbol: [ER_XA_STARTING_RECOVERY](#); SQLSTATE: [HY000](#)
Message: Starting XA crash recovery...
 - Error number: [MY-010230](#); Symbol: [ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER](#); SQLSTATE: [HY000](#)
Message: --tc-heuristic-recover rollback strategy is not safe on systems with more than one 2-phase-commit-capable storage engine. Aborting crash recovery.
 - Error number: [MY-010231](#); Symbol: [ER_XA_RECOVER_EXPLANATION](#); SQLSTATE: [HY000](#)
Message: Found %d prepared transactions! It means that mysqld was not shut down properly last time and critical recovery information (last binlog or %s file) was manually deleted after a crash. You have to start mysqld with --tc-heuristic-recover switch to commit or rollback pending transactions.
 - Error number: [MY-010232](#); Symbol: [ER_XA_RECOVERY_DONE](#); SQLSTATE: [HY000](#)
Message: XA crash recovery finished.
 - Error number: [MY-010233](#); Symbol: [ER_TRX_GTID_COLLECT_REJECT](#); SQLSTATE: [HY000](#)
Message: Failed to collect GTID to send in the response packet!
 - Error number: [MY-010234](#); Symbol: [ER_SQL_AUTH0R_DEFAULT_ROLES_FAIL](#); SQLSTATE: [HY000](#)
Message: MYSQL.DEFAULT_ROLES couldn't be updated for authorization identifier %s
 - Error number: [MY-010235](#); Symbol: [ER_SQL_USER_TABLE_CREATE_WARNING](#); SQLSTATE: [HY000](#)
Message: Following users were specified in CREATE USER IF NOT EXISTS but they already exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s
 - Error number: [MY-010236](#); Symbol: [ER_SQL_USER_TABLE_ALTER_WARNING](#); SQLSTATE: [HY000](#)
Message: Following users were specified in ALTER USER IF EXISTS but they do not exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s
 - Error number: [MY-010237](#); Symbol: [ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR](#); SQLSTATE: [HY000](#)
Message: Table '%s' corrupted: row in wrong partition: %s -- Please REPAIR the table!
 - Error number: [MY-010238](#); Symbol: [ER_MYISAM_CRASHED_ERROR_IN_THREAD](#); SQLSTATE: [HY000](#)
Message: Got an error from thread_id=%u, %s:%d
 - Error number: [MY-010239](#); Symbol: [ER_MYISAM_CRASHED_ERROR_IN](#); SQLSTATE: [HY000](#)
Message: Got an error from unknown thread, %s:%d
-

-
- Error number: [MY-010240](#); Symbol: [ER_TOO_MANY_STORAGE_ENGINES](#); SQLSTATE: [HY000](#)
Message: Too many storage engines!
 - Error number: [MY-010241](#); Symbol: [ER_SE_TYPECODE_CONFLICT](#); SQLSTATE: [HY000](#)
Message: Storage engine '%s' has conflicting typecode. Assigning value %d.
 - Error number: [MY-010242](#); Symbol: [ER_TRX_WRITE_SET_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory on transaction write set extraction
 - Error number: [MY-010243](#); Symbol: [ER_HANDLERTON_OOM](#); SQLSTATE: [HY000](#)
Message: Unable to allocate memory for plugin '%s' handlerton.
 - Error number: [MY-010244](#); Symbol: [ER_CONN_SHM_LISTENER](#); SQLSTATE: [HY000](#)
Message: Shared memory setting up listener
 - Error number: [MY-010245](#); Symbol: [ER_CONN_SHM_CANT_CREATE_SERVICE](#); SQLSTATE: [HY000](#)
Message: Can't create shared memory service: %s. : %s
 - Error number: [MY-010246](#); Symbol: [ER_CONN_SHM_CANT_CREATE_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Can't create shared memory connection: %s. : %s
 - Error number: [MY-010247](#); Symbol: [ER_CONN_PIP_CANT_CREATE_EVENT](#); SQLSTATE: [HY000](#)
Message: Can't create event, last error=%u
 - Error number: [MY-010248](#); Symbol: [ER_CONN_PIP_CANT_CREATE_PIPE](#); SQLSTATE: [HY000](#)
Message: Can't create new named pipe!: %s
 - Error number: [MY-010249](#); Symbol: [ER_CONN_PER_THREAD_NO_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create thread to handle new connection(errno= %d)
 - Error number: [MY-010250](#); Symbol: [ER_CONN_TCP_NO_SOCKET](#); SQLSTATE: [HY000](#)
Message: Failed to create a socket for %s '%s': errno: %d.
 - Error number: [MY-010251](#); Symbol: [ER_CONN_TCP_CREATED](#); SQLSTATE: [HY000](#)
Message: Server socket created on IP: '%s'.
 - Error number: [MY-010252](#); Symbol: [ER_CONN_TCP_ADDRESS](#); SQLSTATE: [HY000](#)
Message: Server hostname (bind-address): '%s'; port: %d
 - Error number: [MY-010253](#); Symbol: [ER_CONN_TCP_IPV6_AVAILABLE](#); SQLSTATE: [HY000](#)
Message: IPv6 is available.
 - Error number: [MY-010254](#); Symbol: [ER_CONN_TCP_IPV6_UNAVAILABLE](#); SQLSTATE: [HY000](#)
Message: IPv6 is not available.
 - Error number: [MY-010255](#); Symbol: [ER_CONN_TCP_ERROR_WITH_STRERROR](#); SQLSTATE: [HY000](#)
Message: Can't create IP socket: %s

-
- Error number: [MY-010256](#); Symbol: [ER_CONN_TCP_CANT_RESOLVE_HOSTNAME](#); SQLSTATE: [HY000](#)
Message: Can't start server: cannot resolve hostname!
 - Error number: [MY-010257](#); Symbol: [ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT](#); SQLSTATE: [HY000](#)
Message: Do you already have another mysqld server running on port: %d ?
 - Error number: [MY-010258](#); Symbol: [ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET](#); SQLSTATE: [HY000](#)
Message: Do you already have another mysqld server running on socket: %s ?
 - Error number: [MY-010259](#); Symbol: [ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE](#); SQLSTATE: [HY000](#)
Message: Another process with pid %d is using unix socket file.
 - Error number: [MY-010260](#); Symbol: [ER_CONN_TCP_CANT_RESET_V6ONLY](#); SQLSTATE: [HY000](#)
Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.
 - Error number: [MY-010261](#); Symbol: [ER_CONN_TCP_BIND_RETRY](#); SQLSTATE: [HY000](#)
Message: Retrying bind on TCP/IP port %u
 - Error number: [MY-010262](#); Symbol: [ER_CONN_TCP_BIND_FAIL](#); SQLSTATE: [HY000](#)
Message: Can't start server: Bind on TCP/IP port: %s
 - Error number: [MY-010263](#); Symbol: [ER_CONN_TCP_IP_NOT_LOGGED](#); SQLSTATE: [HY000](#)
Message: Fails to print out IP-address.
 - Error number: [MY-010264](#); Symbol: [ER_CONN_TCP_RESOLVE_INFO](#); SQLSTATE: [HY000](#)
Message: - '%s' resolves to '%s';
 - Error number: [MY-010265](#); Symbol: [ER_CONN_TCP_START_FAIL](#); SQLSTATE: [HY000](#)
Message: Can't start server: listen() on TCP/IP port: %s
 - Error number: [MY-010266](#); Symbol: [ER_CONN_TCP_LISTEN_FAIL](#); SQLSTATE: [HY000](#)
Message: listen() on TCP/IP failed with error %d
 - Error number: [MY-010267](#); Symbol: [ER_CONN_UNIX_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: The socket file path is too long (> %u): %s
 - Error number: [MY-010268](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_FAIL](#); SQLSTATE: [HY000](#)
Message: Unable to setup unix socket lock file.
 - Error number: [MY-010269](#); Symbol: [ER_CONN_UNIX_NO_FD](#); SQLSTATE: [HY000](#)
Message: Can't start server: UNIX Socket : %s
 - Error number: [MY-010270](#); Symbol: [ER_CONN_UNIX_NO_BIND_NO_START](#); SQLSTATE: [HY000](#)
Message: Can't start server : Bind on unix socket: %s

-
- Error number: [MY-010271](#); Symbol: [ER_CONN_UNIX_LISTEN_FAILED](#); SQLSTATE: [HY000](#)
Message: listen() on Unix socket failed with error %d
 - Error number: [MY-010272](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_GIVING_UP](#); SQLSTATE: [HY000](#)
Message: Unable to create unix socket lock file %s after retries.
 - Error number: [MY-010273](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_CREATE](#); SQLSTATE: [HY000](#)
Message: Could not create unix socket lock file %s.
 - Error number: [MY-010274](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_OPEN](#); SQLSTATE: [HY000](#)
Message: Could not open unix socket lock file %s.
 - Error number: [MY-010275](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_READ](#); SQLSTATE: [HY000](#)
Message: Could not read unix socket lock file %s.
 - Error number: [MY-010276](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_EMPTY](#); SQLSTATE: [HY000](#)
Message: Unix socket lock file is empty %s.
 - Error number: [MY-010277](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_PIDLESS](#); SQLSTATE: [HY000](#)
Message: Invalid pid in unix socket lock file %s.
 - Error number: [MY-010278](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_WRITE](#); SQLSTATE: [HY000](#)
Message: Could not write unix socket lock file %s errno %d.
 - Error number: [MY-010279](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_DELETE](#); SQLSTATE: [HY000](#)
Message: Could not remove unix socket lock file %s errno %d.
 - Error number: [MY-010280](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_SYNC](#); SQLSTATE: [HY000](#)
Message: Could not sync unix socket lock file %s errno %d.
 - Error number: [MY-010281](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE](#); SQLSTATE: [HY000](#)
Message: Could not close unix socket lock file %s errno %d.
 - Error number: [MY-010282](#); Symbol: [ER_CONN_SOCKET_SELECT_FAILED](#); SQLSTATE: [HY000](#)
Message: mysqld: Got error %d from select
 - Error number: [MY-010283](#); Symbol: [ER_CONN_SOCKET_ACCEPT_FAILED](#); SQLSTATE: [HY000](#)
Message: Error in accept: %s
 - Error number: [MY-010284](#); Symbol: [ER_AUTH_RSA_CANT_FIND](#); SQLSTATE: [HY000](#)
Message: RSA %s key file not found: %s. Some authentication plugins will not work.

-
- Error number: [MY-010285](#); Symbol: [ER_AUTH_RSA_CANT_PARSE](#); SQLSTATE: [HY000](#)
Message: Failure to parse RSA %s key (file exists): %s: %s
 - Error number: [MY-010286](#); Symbol: [ER_AUTH_RSA_CANT_READ](#); SQLSTATE: [HY000](#)
Message: Failure to read key file: %s
 - Error number: [MY-010287](#); Symbol: [ER_AUTH_RSA_FILES_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: RSA key files not found. Some authentication plugins will not work.
 - Error number: [MY-010288](#); Symbol: [ER_CONN_ATTR_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: Connection attributes of length %lu were truncated (%d bytes lost) for connection %llu, user %s@%s (as %s), auth: %s
 - Error number: [MY-010289](#); Symbol: [ER_X509_CIPHERS_MISMATCH](#); SQLSTATE: [HY000](#)
Message: X.509 ciphers mismatch: should be '%s' but is '%s'
 - Error number: [MY-010290](#); Symbol: [ER_X509_ISSUER_MISMATCH](#); SQLSTATE: [HY000](#)
Message: X.509 issuer mismatch: should be '%s' but is '%s'
 - Error number: [MY-010291](#); Symbol: [ER_X509_SUBJECT_MISMATCH](#); SQLSTATE: [HY000](#)
Message: X.509 subject mismatch: should be '%s' but is '%s'
 - Error number: [MY-010292](#); Symbol: [ER_AUTH_CANT_ACTIVATE_ROLE](#); SQLSTATE: [HY000](#)
Message: Failed to activate default role %s for %s
 - Error number: [MY-010293](#); Symbol: [ER_X509_NEEDS_RSA_PRIVKEY](#); SQLSTATE: [HY000](#)
Message: Could not generate RSA private key required for X.509 certificate.
 - Error number: [MY-010294](#); Symbol: [ER_X509_CANT_WRITE_KEY](#); SQLSTATE: [HY000](#)
Message: Could not write key file: %s
 - Error number: [MY-010295](#); Symbol: [ER_X509_CANT_CHMOD_KEY](#); SQLSTATE: [HY000](#)
Message: Could not set file permission for %s
 - Error number: [MY-010296](#); Symbol: [ER_X509_CANT_READ_CA_KEY](#); SQLSTATE: [HY000](#)
Message: Could not read CA key file: %s
 - Error number: [MY-010297](#); Symbol: [ER_X509_CANT_READ_CA_CERT](#); SQLSTATE: [HY000](#)
Message: Could not read CA certificate file: %s
 - Error number: [MY-010298](#); Symbol: [ER_X509_CANT_CREATE_CERT](#); SQLSTATE: [HY000](#)
Message: Could not generate X.509 certificate.
 - Error number: [MY-010299](#); Symbol: [ER_X509_CANT_WRITE_CERT](#); SQLSTATE: [HY000](#)
Message: Could not write certificate file: %s
 - Error number: [MY-010300](#); Symbol: [ER_AUTH_CANT_CREATE_RSA_PAIR](#); SQLSTATE: [HY000](#)
Message: Could not generate RSA Private/Public key pair

-
- Error number: [MY-010301](#); Symbol: [ER_AUTH_CANT_WRITE_PRIVKEY](#); SQLSTATE: [HY000](#)
Message: Could not write private key file: %s
 - Error number: [MY-010302](#); Symbol: [ER_AUTH_CANT_WRITE_PUBKEY](#); SQLSTATE: [HY000](#)
Message: Could not write public key file: %s
 - Error number: [MY-010303](#); Symbol: [ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION](#); SQLSTATE: [HY000](#)
Message: Skipping generation of SSL certificates as options related to SSL are specified.
 - Error number: [MY-010304](#); Symbol: [ER_AUTH_USING_EXISTING_CERTS](#); SQLSTATE: [HY000](#)
Message: Skipping generation of SSL certificates as certificate files are present in data directory.
 - Error number: [MY-010305](#); Symbol: [ER_AUTH_CERTS_SAVED_TO_DATADIR](#); SQLSTATE: [HY000](#)
Message: Auto generated SSL certificates are placed in data directory.
 - Error number: [MY-010306](#); Symbol: [ER_AUTH_CERT_GENERATION_DISABLED](#); SQLSTATE: [HY000](#)
Message: Skipping generation of SSL certificates as --auto_generate_certs is set to OFF.
 - Error number: [MY-010307](#); Symbol: [ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION](#); SQLSTATE: [HY000](#)
Message: Skipping generation of RSA key pair through %s as options related to RSA keys are specified.
 - Error number: [MY-010308](#); Symbol: [ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT](#); SQLSTATE: [HY000](#)
Message: Skipping generation of RSA key pair through %s as key files are present in data directory.
 - Error number: [MY-010309](#); Symbol: [ER_AUTH_KEYS_SAVED_TO_DATADIR](#); SQLSTATE: [HY000](#)
Message: Auto generated RSA key files through %s are placed in data directory.
 - Error number: [MY-010310](#); Symbol: [ER_AUTH_KEY_GENERATION_DISABLED](#); SQLSTATE: [HY000](#)
Message: Skipping generation of RSA key pair as %s is set to OFF.
 - Error number: [MY-010311](#); Symbol: [ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)
Message: 'proxies_priv' entry '%s@%s %s@%s' ignored in --skip-name-resolve mode.
 - Error number: [MY-010312](#); Symbol: [ER_AUTHCACHE_PLUGIN_MISSING](#); SQLSTATE: [HY000](#)
Message: The plugin '%.*s' used to authenticate user '%s'@'%.*s' is not loaded. Nobody can currently login using this account.
 - Error number: [MY-010313](#); Symbol: [ER_AUTHCACHE_PLUGIN_CONFIG](#); SQLSTATE: [HY000](#)
Message: The plugin '%s' is used to authenticate user '%s'@'%.*s', %s configured. Nobody can currently login using this account.
 - Error number: [MY-010315](#); Symbol: [ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)
Message: 'user' entry '%s@%s' ignored in --skip-name-resolve mode.

-
- Error number: [MY-010316](#); Symbol: [ER_AUTHCACHE_USER_TABLE_DODGY](#); SQLSTATE: [HY000](#)
Message: Fatal error: Could not read the column 'authentication_string' from table 'mysql.user'. Please perform the MySQL upgrade procedure.
 - Error number: [MY-010317](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD](#); SQLSTATE: [HY000](#)
Message: User entry '%s'@'%s' has a deprecated pre-4.1 password. The user will be ignored and no one can login with this user anymore.
 - Error number: [MY-010318](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN](#); SQLSTATE: [HY000](#)
Message: User entry '%s'@'%s' has an empty plugin value. The user will be ignored and no one can login with this user anymore.
 - Error number: [MY-010319](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Found invalid password for user: '%s@%s'; Ignoring user
 - Error number: [MY-010320](#); Symbol: [ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: 'user' entry '%s@%s' has the password ignore flag raised, but its authentication plugin doesn't support password expiration. The user id will be ignored.
 - Error number: [MY-010321](#); Symbol: [ER_NO_SUPER_WITHOUT_USER_PLUGIN](#); SQLSTATE: [HY000](#)
Message: Some of the user accounts with SUPER privileges were disabled because of empty mysql.user.plugin value. If you are upgrading from MySQL 5.6 to MySQL 5.7 it means that substitution for the empty plugin column was not possible. Probably because of pre 4.1 password hash. If your account is disabled you will need to perform the MySQL upgrade procedure. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.
 - Error number: [MY-010322](#); Symbol: [ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME](#); SQLSTATE: [HY000](#)
Message: Found an entry in the 'db' table with empty database name; Skipped
 - Error number: [MY-010323](#); Symbol: [ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)
Message: 'db' entry '%s %s@%s' ignored in --skip-name-resolve mode.
 - Error number: [MY-010324](#); Symbol: [ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL](#); SQLSTATE: [HY000](#)
Message: 'db' entry '%s %s@%s' had database in mixed case that has been forced to lowercase because lower_case_table_names is set. It will not be possible to remove this privilege using REVOKE.
 - Error number: [MY-010325](#); Symbol: [ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING](#); SQLSTATE: [HY000](#)
Message: The system table mysql.proxies_priv is missing. Please perform the MySQL upgrade procedure.
 - Error number: [MY-010326](#); Symbol: [ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES](#); SQLSTATE: [HY000](#)
-

Message: Fatal error: Can't open and lock privilege tables: %s

- Error number: [MY-010327](#); Symbol: [ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM](#); SQLSTATE: [HY000](#)

Message: Fatal: can't initialize grant subsystem - '%s'

- Error number: [MY-010328](#); Symbol: [ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'procs_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.

- Error number: [MY-010329](#); Symbol: [ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE](#); SQLSTATE: [HY000](#)

Message: 'procs_priv' entry '%s' ignored, bad routine type

- Error number: [MY-010330](#); Symbol: [ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'tables_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.

- Error number: [MY-010331](#); Symbol: [ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE](#); SQLSTATE: [HY000](#)

Message: Failed to add %s in extra_users. Binary log entry may miss some of the users.

- Error number: [MY-010332](#); Symbol: [ER_DD_SCHEMA_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary schema '%s' does not exist.

- Error number: [MY-010333](#); Symbol: [ER_DD_TABLE_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary table '%s' does not exist.

- Error number: [MY-010334](#); Symbol: [ER_DD_SE_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize DD Storage Engine

- Error number: [MY-010335](#); Symbol: [ER_DD_ABORTING_PARTIAL_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

- Error number: [MY-010336](#); Symbol: [ER_DD_FRM_EXISTS_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: Found .frm file with same name as one of the Dictionary Tables.

- Error number: [MY-010337](#); Symbol: [ER_DD_CREATED_FOR_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Created Data Dictionary for upgrade

- Error number: [MY-010338](#); Symbol: [ER_ERRMSG_CANT_FIND_FILE](#); SQLSTATE: [HY000](#)

Message: Can't find error-message file '%s'. Check error-message file location and 'lc-messages-dir' configuration directive.

- Error number: [MY-010340](#); Symbol: [ER_ERRMSG_MISSING_IN_FILE](#); SQLSTATE: [HY000](#)

Message: Error message file '%s' had only %d error messages, but it should contain at least %d error messages. Check that the above file is the right version for this program!

- Error number: [MY-010341](#); Symbol: [ER_ERRMSG_OOM](#); SQLSTATE: [HY000](#)

Message: Not enough memory for messagefile '%s'

- Error number: [MY-010342](#); Symbol: [ER_ERRMSG_CANT_READ](#); SQLSTATE: [HY000](#)

Message: Can't read from messagefile '%s'

- Error number: [MY-010343](#); Symbol: [ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD](#); SQLSTATE: [HY000](#)

Message: Found incompatible DECIMAL field '%s' in %s; Please do "ALTER TABLE `%s` FORCE" to fix it!

- Error number: [MY-010344](#); Symbol: [ER_TABLE_INCOMPATIBLE_YEAR_FIELD](#); SQLSTATE: [HY000](#)

Message: Found incompatible YEAR(x) field '%s' in %s; Please do "ALTER TABLE `%s` FORCE" to fix it!

- Error number: [MY-010345](#); Symbol: [ER_INVALID_CHARSET_AND_DEFAULT_IS_MB](#); SQLSTATE: [HY000](#)

Message: '%s' had no or invalid character set, and default character set is multi-byte, so character column sizes may have changed

- Error number: [MY-010346](#); Symbol: [ER_TABLE_WRONG_KEY_DEFINITION](#); SQLSTATE: [HY000](#)

Message: Found wrong key definition in %s; Please do "ALTER TABLE `%s` FORCE " to fix it!

- Error number: [MY-010347](#); Symbol: [ER_CANT_OPEN_FRM_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to open file %s

- Error number: [MY-010348](#); Symbol: [ER_CANT_READ_FRM_FILE](#); SQLSTATE: [HY000](#)

Message: Error in reading file %s

- Error number: [MY-010349](#); Symbol: [ER_TABLE_CREATED_WITH_DIFFERENT_VERSION](#); SQLSTATE: [HY000](#)

Message: Table '%s' was created with a different version of MySQL and cannot be read

- Error number: [MY-010350](#); Symbol: [ER_VIEW_UNPARSABLE](#); SQLSTATE: [HY000](#)

Message: Unable to read view %s

- Error number: [MY-010351](#); Symbol: [ER_FILE_TYPE_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: File %s has unknown type in its header.

- Error number: [MY-010352](#); Symbol: [ER_INVALID_INFO_IN_FRM](#); SQLSTATE: [HY000](#)

Message: Incorrect information in file %s

- Error number: [MY-010353](#); Symbol: [ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES](#); SQLSTATE: [HY000](#)

Message: Can't open and lock privilege tables: %s

- Error number: [MY-010354](#); Symbol: [ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' cannot subscribe to MYSQL_AUDIT_AUTHORIZATION events. Currently not supported.

-
- Error number: [MY-010355](#); Symbol: [ER_AUDIT_PLUGIN_HAS_INVALID_DATA](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' has invalid data.
 - Error number: [MY-010356](#); Symbol: [ER_TZ_OOM_INITIALIZING_TIME_ZONES](#); SQLSTATE: [HY000](#)
Message: Fatal error: OOM while initializing time zones
 - Error number: [MY-010357](#); Symbol: [ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE](#); SQLSTATE: [HY000](#)
Message: Can't open and lock time zone table: %s trying to live without them
 - Error number: [MY-010358](#); Symbol: [ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE](#); SQLSTATE: [HY000](#)
Message: Fatal error: Out of memory while loading mysql.time_zone_leap_second table
 - Error number: [MY-010359](#); Symbol: [ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE](#); SQLSTATE: [HY000](#)
Message: Fatal error: While loading mysql.time_zone_leap_second table: too much leaps
 - Error number: [MY-010360](#); Symbol: [ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE](#); SQLSTATE: [HY000](#)
Message: Fatal error: Error while loading mysql.time_zone_leap_second table
 - Error number: [MY-010361](#); Symbol: [ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE](#); SQLSTATE: [HY000](#)
Message: Fatal error: Illegal or unknown default time zone '%s'
 - Error number: [MY-010362](#); Symbol: [ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE](#); SQLSTATE: [HY000](#)
Message: Can't find description of time zone '%.*s'
 - Error number: [MY-010363](#); Symbol: [ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID](#); SQLSTATE: [HY000](#)
Message: Can't find description of time zone '%u'
 - Error number: [MY-010364](#); Symbol: [ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE](#); SQLSTATE: [HY000](#)
Message: Error while loading time zone description from mysql.time_zone_transition_type table: too big transition type id
 - Error number: [MY-010365](#); Symbol: [ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE](#); SQLSTATE: [HY000](#)
Message: Error while loading time zone description from mysql.time_zone_transition_type table: not enough room for abbreviations
 - Error number: [MY-010366](#); Symbol: [ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR](#); SQLSTATE: [HY000](#)
Message: Error while loading time zone description from mysql.time_zone_transition_type table
 - Error number: [MY-010367](#); Symbol: [ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS](#); SQLSTATE: [HY000](#)

Message: Error while loading time zone description from mysql.time_zone_transition table: too much transitions

- Error number: [MY-010368](#); Symbol: [ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE](#); SQLSTATE: [HY000](#)

Message: Error while loading time zone description from mysql.time_zone_transition table: bad transition type id

- Error number: [MY-010369](#); Symbol: [ER_TZ_TRANSITION_TABLE_LOAD_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while loading time zone description from mysql.time_zone_transition table

- Error number: [MY-010370](#); Symbol: [ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: loading time zone without transition types

- Error number: [MY-010371](#); Symbol: [ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION](#); SQLSTATE: [HY000](#)

Message: Out of memory while loading time zone description

- Error number: [MY-010372](#); Symbol: [ER_TZ_CANT_BUILD_MKTIME_MAP](#); SQLSTATE: [HY000](#)

Message: Unable to build mktime map for time zone

- Error number: [MY-010373](#); Symbol: [ER_TZ_OOM_WHILE_LOADING_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: Out of memory while loading time zone

- Error number: [MY-010374](#); Symbol: [ER_TZ_OOM_WHILE_SETTING_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: Fatal error: Out of memory while setting new time zone

- Error number: [MY-010375](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread is stopped because UNTIL condition is bad(%s:%llu).

- Error number: [MY-010376](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached its UNTIL position %llu

- Error number: [MY-010377](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because UNTIL SQL_BEFORE_GTIDS %s is already applied

- Error number: [MY-010378](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached UNTIL SQL_BEFORE_GTIDS %s

- Error number: [MY-010379](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached UNTIL SQL_AFTER_GTIDS %s

-
- Error number: [MY-010380](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped according to UNTIL SQL_AFTER_MTS_GAPS as it has processed all gap transactions left from the previous replica session.
 - Error number: [MY-010381](#); Symbol: [ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED](#); SQLSTATE: [HY000](#)

Message: Group Replication plugin is not installed.
 - Error number: [MY-010382](#); Symbol: [ER_GTID_ALREADY_ADDED_BY_USER](#); SQLSTATE: [HY000](#)

Message: The transaction owned GTID is already in the %s table, which is caused by an explicit modifying from user client.
 - Error number: [MY-010383](#); Symbol: [ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to delete the row: '%s' from the gtid_executed table.
 - Error number: [MY-010384](#); Symbol: [ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to compress the gtid_executed table.
 - Error number: [MY-010385](#); Symbol: [ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM](#); SQLSTATE: [HY000](#)

Message: Failed to compress the gtid_executed table, because it is failed to allocate the THD.
 - Error number: [MY-010386](#); Symbol: [ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION](#); SQLSTATE: [HY000](#)

Message: Failed to initialize thread attribute when creating compression thread.
 - Error number: [MY-010387](#); Symbol: [ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD](#); SQLSTATE: [HY000](#)

Message: Can not create thread to compress gtid_executed table (errno= %d)
 - Error number: [MY-010388](#); Symbol: [ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD](#); SQLSTATE: [HY000](#)

Message: Could not join gtid_executed table compression thread. error:%d
 - Error number: [MY-010389](#); Symbol: [ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR](#); SQLSTATE: [HY000](#)

Message: Can't start server : Initialize security descriptor: %s
 - Error number: [MY-010390](#); Symbol: [ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR](#); SQLSTATE: [HY000](#)

Message: Can't start server : Set security descriptor: %s
 - Error number: [MY-010391](#); Symbol: [ER_NPIPE_PIPE_ALREADY_IN_USE](#); SQLSTATE: [HY000](#)

Message: Can't start server : Named Pipe "%s" already in use.
 - Error number: [MY-010405](#); Symbol: [ER_RPL_CANT_OPEN_INFO_TABLE](#); SQLSTATE: [HY000](#)

Message: Info table is not ready to be used. Table '%s.%s' cannot be opened.

-
- Error number: [MY-010406](#); Symbol: [ER_RPL_CANT_SCAN_INFO_TABLE](#); SQLSTATE: [HY000](#)
Message: Info table is not ready to be used. Table '%s.%s' cannot be scanned.
 - Error number: [MY-010407](#); Symbol: [ER_RPL_CORRUPTED_INFO_TABLE](#); SQLSTATE: [HY000](#)
Message: Corrupted table %s.%s. Check out table definition.
 - Error number: [MY-010408](#); Symbol: [ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE](#); SQLSTATE: [HY000](#)
Message: Info table has a problem with its key field(s). Table '%s.%s' expected field #%u to be '%s' but found '%s' instead.
 - Error number: [MY-010409](#); Symbol: [ER_RPL_WORKER_ID_IS](#); SQLSTATE: [HY000](#)
Message: Choosing worker id %lu, the following is going to be %lu
 - Error number: [MY-010410](#); Symbol: [ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX](#); SQLSTATE: [HY000](#)
Message: Transaction %s in file %s is tagged with inconsistent logical timestamps: sequence_number (%lld) <= last_committed (%lld). There may be a bug in how these timestamps were generated. Transaction will be applied in isolation
 - Error number: [MY-010411](#); Symbol: [ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX](#); SQLSTATE: [HY000](#)
Message: Transaction %s sequence number in file %s is inconsistent with that of a preceding one: sequence_number (%lld) <= previous sequence_number (%lld). There may be a bug in how these timestamps were generated. Transaction will be applied in isolation
 - Error number: [MY-010413](#); Symbol: [ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID](#); SQLSTATE: [HY000](#)
Message: For the creation of replication channels the server id must be different from 0
 - Error number: [MY-010415](#); Symbol: [ER_RPL_ERROR_CREATING_CONNECTION_METADATA](#); SQLSTATE: [HY000](#)
Message: Error creating connection metadata: %s.
 - Error number: [MY-010418](#); Symbol: [ER_RPL_ERROR_CREATING_APPLIER_METADATA](#); SQLSTATE: [HY000](#)
Message: Error creating applier metadata: %s.
 - Error number: [MY-010420](#); Symbol: [ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKERS_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)
Message: Could not delete from Replica Workers info repository.
 - Error number: [MY-010421](#); Symbol: [ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)
Message: Could not store the reset Replica Worker state into the replica info repository.
 - Error number: [MY-010423](#); Symbol: [ER_RPL_REPLICA_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)
Message: Replica: %s
 - Error number: [MY-010424](#); Symbol: [ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST](#); SQLSTATE: [HY000](#)

Message: Replica: Could not create channel list

- Error number: [MY-010425](#); Symbol: [ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES](#); SQLSTATE: [HY000](#)

Message: Replica: This replica was a multisourced replica previously which is supported only by both TABLE based connection metadata and applier metadata repositories. Found one or both of the info repos to be type FILE. Set both repos to type TABLE.

- Error number: [MY-010426](#); Symbol: [ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE](#); SQLSTATE: [HY000](#)

Message: Replica: Failed to initialize the connection metadata structure for channel '%s'; its record may still be present in the applier metadata repository, consider deleting it.

- Error number: [MY-010427](#); Symbol: [ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE](#); SQLSTATE: [HY000](#)

Message: Failed to initialize the connection metadata structure%s

- Error number: [MY-010428](#); Symbol: [ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION_METADATA](#); SQLSTATE: [HY000](#)

Message: Replica: Failed to create a channel from connection metadata repository.

- Error number: [MY-010429](#); Symbol: [ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to create a new info file (file '%s', errno %d)

- Error number: [MY-010430](#); Symbol: [ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to create a cache on info file (file '%s')

- Error number: [MY-010431](#); Symbol: [ER_RPL_FAILED_TO_OPEN_INFO_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to open the existing info file (file '%s', errno %d)

- Error number: [MY-010432](#); Symbol: [ER_RPL_GTID_MEMORY_FINALY_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Server overcomes the temporary 'out of memory' in '%d' tries while allocating a new chunk of intervals for storing GTIDs.

- Error number: [MY-010433](#); Symbol: [ER_SERVER_COST_UNKNOWN_COST_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Unknown cost constant "%s" in mysql.server_cost table

- Error number: [MY-010434](#); Symbol: [ER_SERVER_COST_INVALID_COST_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" in mysql.server_cost table: %.1f

- Error number: [MY-010435](#); Symbol: [ER_ENGINE_COST_UNKNOWN_COST_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Unknown cost constant "%s" in mysql.engine_cost table

-
- Error number: [MY-010436](#); Symbol: [ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)
Message: Unknown storage engine "%s" in mysql.engine_cost table
 - Error number: [MY-010437](#); Symbol: [ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE](#); SQLSTATE: [HY000](#)
Message: Invalid device type %d for "%s" storage engine for cost constant "%s" in mysql.engine_cost table
 - Error number: [MY-010438](#); Symbol: [ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND_DEVICE](#); SQLSTATE: [HY000](#)
Message: Invalid value for cost constant "%s" for "%s" storage engine and device type %d in mysql.engine_cost table: %.1f
 - Error number: [MY-010439](#); Symbol: [ER_SERVER_COST_FAILED_TO_READ](#); SQLSTATE: [HY000](#)
Message: Error while reading from mysql.server_cost table.
 - Error number: [MY-010440](#); Symbol: [ER_ENGINE_COST_FAILED_TO_READ](#); SQLSTATE: [HY000](#)
Message: Error while reading from mysql.engine_cost table.
 - Error number: [MY-010441](#); Symbol: [ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES](#); SQLSTATE: [HY000](#)
Message: Failed to open optimizer cost constant tables
 - Error number: [MY-010442](#); Symbol: [ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)
Message: Unsupported non-ignorable event fed into the event stream.
 - Error number: [MY-010443](#); Symbol: [ER_RPL_GTID_LOG_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)
Message: GTID_LOG_EVENT, GTID_TAGGED_LOG_EVENT or ANONYMOUS_GTID_LOG_EVENT is not expected in an event stream %s.
 - Error number: [MY-010444](#); Symbol: [ER_RPL_UNEXPECTED_BEGIN_IN_STREAM](#); SQLSTATE: [HY000](#)
Message: QUERY(BEGIN) is not expected in an event stream in the middle of a %s.
 - Error number: [MY-010445](#); Symbol: [ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)
Message: QUERY(COMMIT or ROLLBACK) or XID_LOG_EVENT is not expected in an event stream %s.
 - Error number: [MY-010446](#); Symbol: [ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM](#); SQLSTATE: [HY000](#)
Message: QUERY(XA ROLLBACK) is not expected in an event stream %s.
 - Error number: [MY-010447](#); Symbol: [ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: [%s].[%s.%s] execution failed, failed to authenticate the user.
 - Error number: [MY-010448](#); Symbol: [ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PRIVILEGE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: [%s].[%s.%s] execution failed, user no longer has EVENT privilege.

- Error number: MY-010449; Symbol: ER_EVENT_ERROR_DURING_COMPILATION; SQLSTATE: HY000

Message: Event Scheduler: %serror during compilation of %s.%s

- Error number: MY-010450; Symbol: ER_EVENT_DROPPING; SQLSTATE: HY000

Message: Event Scheduler: Dropping %s.%s

- Error number: MY-010452; Symbol: ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR; SQLSTATE: HY000

Message: In RBR mode, Replica received incompatible DECIMAL field (old-style decimal field) from Source while creating conversion table. Please consider changing datatype on Source to new style decimal by executing ALTER command for column Name: %s.%s.%s.

- Error number: MY-010453; Symbol: ER_INIT_ROOT_WITHOUT_PASSWORD; SQLSTATE: HY000

Message: root@localhost is created with an empty password ! Please consider switching off the --initialize-insecure option.

- Error number: MY-010454; Symbol: ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT; SQLSTATE: HY000

Message: A temporary password is generated for root@localhost: %s

- Error number: MY-010455; Symbol: ER_INIT_CANT_OPEN_BOOTSTRAP_FILE; SQLSTATE: HY000

Message: Failed to open the bootstrap file %s

- Error number: MY-010456; Symbol: ER_INIT_BOOTSTRAP_COMPLETE; SQLSTATE: HY000

Message: Bootstrapping complete

- Error number: MY-010457; Symbol: ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE; SQLSTATE: HY000

Message: --initialize specified but the data directory has files in it. Aborting.

- Error number: MY-010458; Symbol: ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE; SQLSTATE: HY000

Message: --initialize specified on an existing data directory.

- Error number: MY-010459; Symbol: ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE; SQLSTATE: HY000

Message: --initialize specified but the data directory exists and the path is too long. Aborting.

- Error number: MY-010460; Symbol: ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE; SQLSTATE: HY000

Message: --initialize specified but the data directory exists and is not writable. Aborting.

- Error number: MY-010461; Symbol: ER_INIT_CREATING_DD; SQLSTATE: HY000

Message: Creating the data directory %s

- Error number: MY-010462; Symbol: ER_RPL_BINLOG_STARTING_DUMP; SQLSTATE: HY000

Message: Start binlog_dump to source_thread_id(%u) replica_server(%u), pos(%s, %llu)

- Error number: [MY-010463](#); Symbol: [ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT](#); SQLSTATE: [HY000](#)

Message: source sends heartbeat message

- Error number: [MY-010464](#); Symbol: [ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO](#); SQLSTATE: [HY000](#)

Message: the rest of heartbeat info skipped ...

- Error number: [MY-010465](#); Symbol: [ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT](#); SQLSTATE: [HY000](#)

Message: Source is configured to log replication events with checksum, but will not send such events to replicas that cannot process them

- Error number: [MY-010467](#); Symbol: [ER_KILLING_THREAD](#); SQLSTATE: [HY000](#)

Message: Killing thread %lu

- Error number: [MY-010468](#); Symbol: [ER_DETACHING_SESSION_LEFT_BY_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Plugin %s is deinitializing a thread but left a session attached. Detaching it forcefully.

- Error number: [MY-010469](#); Symbol: [ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Failed to detach the session.

- Error number: [MY-010470](#); Symbol: [ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Closed forcefully %u session%s left opened by plugin %s

- Error number: [MY-010471](#); Symbol: [ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS](#); SQLSTATE: [HY000](#)

Message: Failed to decrement the number of threads

- Error number: [MY-010472](#); Symbol: [ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS](#); SQLSTATE: [HY000](#)

Message: Plugin %s did not deinitialize %u threads

- Error number: [MY-010473](#); Symbol: [ER_KILLED_THREADS_OF_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Killed %u threads of plugin %s

- Error number: [MY-010517](#); Symbol: [ER_DEBUG_CHECK_SHARES_OPEN](#); SQLSTATE: [HY000](#)

Message: debug_check_shares open:

- Error number: [MY-010518](#); Symbol: [ER_DEBUG_CHECK_SHARES_INFO](#); SQLSTATE: [HY000](#)

Message: %s.%s: state: %s(%u) use_count: %u

- Error number: [MY-010519](#); Symbol: [ER_DEBUG_CHECK_SHARES_DROPPED](#); SQLSTATE: [HY000](#)

Message: debug_check_shares dropped:

-
- Error number: [MY-010520](#); Symbol: [ER_INVALID_OR_OLD_TABLE_OR_DB_NAME](#); SQLSTATE: [HY000](#)

Message: Invalid (old?) table or database name '%s'
 - Error number: [MY-010521](#); Symbol: [ER_TC_RECOVERING_AFTER_CRASH_USING](#); SQLSTATE: [HY000](#)

Message: Recovering after a crash using %s
 - Error number: [MY-010522](#); Symbol: [ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER](#); SQLSTATE: [HY000](#)

Message: Cannot perform automatic crash recovery when --tc-heuristic-recover is used
 - Error number: [MY-010523](#); Symbol: [ER_TC_BAD_MAGIC_IN_TC_LOG](#); SQLSTATE: [HY000](#)

Message: Bad magic header in tc log
 - Error number: [MY-010524](#); Symbol: [ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Recovery failed! You must enable exactly %d storage engines that support two-phase commit protocol
 - Error number: [MY-010525](#); Symbol: [ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete tc log and start mysqld with --tc-heuristic-recover={commit|rollback}
 - Error number: [MY-010526](#); Symbol: [ER_TC_HEURISTIC_RECOVERY_MODE](#); SQLSTATE: [HY000](#)

Message: Heuristic crash recovery mode
 - Error number: [MY-010527](#); Symbol: [ER_TC_HEURISTIC_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Heuristic crash recovery failed
 - Error number: [MY-010528](#); Symbol: [ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER](#); SQLSTATE: [HY000](#)

Message: Please restart mysqld without --tc-heuristic-recover
 - Error number: [MY-010529](#); Symbol: [ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES](#); SQLSTATE: [HY000](#)

Message: Failed to create or recover replication info repositories.
 - Error number: [MY-010530](#); Symbol: [ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '%s' was configured with AUTO_POSITION = 1, but the server was started with --gtid-mode=off. Either reconfigure replication using CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 0 FOR CHANNEL '%s', or change GTID_MODE to some value other than OFF, before starting the replica receiver thread.
 - Error number: [MY-010531](#); Symbol: [ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica: Could not start replica for channel '%s'. operation discontinued

-
- Error number: [MY-010532](#); Symbol: [ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL](#); SQLSTATE: [HY000](#)
Message: Replica: Could not stop replica for channel '%s' operation discontinued
 - Error number: [MY-010533](#); Symbol: [ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE](#); SQLSTATE: [HY000](#)
Message: Error during --relay-log-recovery: Could not locate rotate event from the source.
 - Error number: [MY-010534](#); Symbol: [ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Error during --relay-log-recovery: Error reading events from relay log: %d
 - Error number: [MY-010536](#); Symbol: [ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL](#); SQLSTATE: [HY000](#)
Message: Relay log recovery skipped for group replication channel.
 - Error number: [MY-010537](#); Symbol: [ER_RPL_RECOVERY_ERROR](#); SQLSTATE: [HY000](#)
Message: Error during --relay-log-recovery: %s
 - Error number: [MY-010538](#); Symbol: [ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX](#); SQLSTATE: [HY000](#)
Message: Error during --relay-log-recovery: Could not read relay log index file due to an IO error.
 - Error number: [MY-010539](#); Symbol: [ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO](#); SQLSTATE: [HY000](#)
Message: Recovery from source pos %ld and file %s%s. Previous relay log pos and relay log file had been set to %lld, %s respectively.
 - Error number: [MY-010540](#); Symbol: [ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRES_POSITION](#); SQLSTATE: [HY000](#)
Message: Error during --relay-log-recovery: replicate_same_server_id is in use and sql thread's positions are not initialized, hence relay log recovery cannot happen.
 - Error number: [MY-010541](#); Symbol: [ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR](#); SQLSTATE: [HY000](#)
Message: MTA recovery: starting coordinator thread to fill MTA gaps.
 - Error number: [MY-010542](#); Symbol: [ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR](#); SQLSTATE: [HY000](#)
Message: MTA recovery: failed to start the coordinator thread. Check the error log for additional details.
 - Error number: [MY-010543](#); Symbol: [ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)
Message: MTA recovery: automatic recovery failed. Either the replica server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the replica side error and restart the replica server or consider using RESET REPLICA.
 - Error number: [MY-010544](#); Symbol: [ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Failed to open the relay log '%s' (relay_log_pos %s).
-

-
- Error number: [MY-010545](#); Symbol: [ER_RPL_MTA_RECOVERY_SUCCESSFUL](#); SQLSTATE: [HY000](#)
Message: MTA recovery: completed successfully.
 - Error number: [MY-010546](#); Symbol: [ER_RPL_SERVER_ID_MISSING](#); SQLSTATE: [HY000](#)
Message: Server id not set, will not start replica%s
 - Error number: [MY-010547](#); Symbol: [ER_RPL_CANT_CREATE_REPLICA_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create replica thread%s.
 - Error number: [MY-010548](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_WAS_KILLED](#); SQLSTATE: [HY000](#)
Message: The replica IO thread%s was killed while executing initialization query '%s'
 - Error number: [MY-010550](#); Symbol: [ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_PRE_50](#); SQLSTATE: [HY000](#)
Message: Found a source with MySQL server version older than 5.0. With checksums enabled on the replica, replication might not work correctly. To ensure correct replication, restart the replica server with --replica_sql_verify_checksum=0.
 - Error number: [MY-010551](#); Symbol: [ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS](#); SQLSTATE: [HY000](#)
Message: "SELECT UNIX_TIMESTAMP()" failed on source, do not trust column Seconds_Behind_Source of SHOW REPLICA STATUS. Error: %s (%d)
 - Error number: [MY-010552](#); Symbol: [ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA_REPOS](#); SQLSTATE: [HY000](#)
Message: Failed to flush connection metadata repository.
 - Error number: [MY-010553](#); Symbol: [ER_RPL_REPLICA_REPORT_HOST_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: The length of report_host is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.
 - Error number: [MY-010554](#); Symbol: [ER_RPL_REPLICA_REPORT_USER_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: The length of report_user is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.
 - Error number: [MY-010555](#); Symbol: [ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: The length of report_password is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.
 - Error number: [MY-010556](#); Symbol: [ER_RPL_REPLICA_ERROR_RETRYING](#); SQLSTATE: [HY000](#)
Message: Error on %s: %d %s, will retry in %d secs
 - Error number: [MY-010557](#); Symbol: [ER_RPL_REPLICA_ERROR_READING_FROM_SERVER](#); SQLSTATE: [HY000](#)
Message: Error reading packet from server%s: %s (server_errno=%d)

-
- Error number: [MY-010558](#); Symbol: [ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE](#); SQLSTATE: [HY000](#)

Message: Replica%s: received end packet from server due to dump thread being killed on source. Dump threads are killed for example during source shutdown, explicitly by a user, or when the source receives a binlog send request from a duplicate server UUID <%s> : Error %s
 - Error number: [MY-010559](#); Symbol: [ER_RPL_MTA_STATISTICS](#); SQLSTATE: [HY000](#)

Message: Multi-threaded replica statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu
 - Error number: [MY-010560](#); Symbol: [ER_RPL_MTA_RECOVERY_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Replica%s: MTA Recovery has completed at relay log %s, position %llu source log %s, position %llu.
 - Error number: [MY-010561](#); Symbol: [ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION](#); SQLSTATE: [HY000](#)

Message: Error initializing relay log position%s: %s
 - Error number: [MY-010563](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_KILLED](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread%s killed while connecting to source
 - Error number: [MY-010564](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread couldn't register on source
 - Error number: [MY-010565](#); Symbol: [ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD](#); SQLSTATE: [HY000](#)

Message: Forcing to reconnect replica I/O thread%s
 - Error number: [MY-010566](#); Symbol: [ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP](#); SQLSTATE: [HY000](#)

Message: Failed on request_dump() %s
 - Error number: [MY-010567](#); Symbol: [ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET](#); SQLSTATE: [HY000](#)

Message: Log entry on source is longer than replica_max_allowed_packet (%lu) on replica. If the entry is correct, restart the server with a higher value of replica_max_allowed_packet
 - Error number: [MY-010568](#); Symbol: [ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM](#); SQLSTATE: [HY000](#)

Message: Stopping replica I/O thread due to out-of-memory error from source
 - Error number: [MY-010569](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread aborted while waiting for relay log space
 - Error number: [MY-010570](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread exiting%s, read up to log '%s', position %s

- Error number: [MY-010571](#); Symbol: [ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER](#); SQLSTATE: [HY000](#)

Message: Failed during replica worker initialization%s

- Error number: [MY-010572](#); Symbol: [ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_FOR_WORKER](#); SQLSTATE: [HY000](#)

Message: Replica: MTA group recovery applier metadata based on Worker-Id %lu, group_relay_log_name %s, group_relay_log_pos %llu group_source_log_name %s, group_source_log_pos %llu

- Error number: [MY-010573](#); Symbol: [ER_RPL_ERROR_LOOKING_FOR_LOG](#); SQLSTATE: [HY000](#)

Message: Error looking for %s.

- Error number: [MY-010574](#); Symbol: [ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA](#); SQLSTATE: [HY000](#)

Message: Replica: MTA group recovery applier metadata group_source_log_name %s, event_source_log_pos %llu.

- Error number: [MY-010575](#); Symbol: [ER_RPL_CANT_FIND_FOLLOWUP_FILE](#); SQLSTATE: [HY000](#)

Message: Error looking for file after %s.

- Error number: [MY-010576](#); Symbol: [ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT](#); SQLSTATE: [HY000](#)

Message: This an error cnt != mta_checkpoint_period

- Error number: [MY-010577](#); Symbol: [ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed during replica worker thread creation%s

- Error number: [MY-010578](#); Symbol: [ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO](#); SQLSTATE: [HY000](#)

Message: Failed during replica worker thread creation%s (errno= %d)

- Error number: [MY-010579](#); Symbol: [ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH](#); SQLSTATE: [HY000](#)

Message: Failed to init partitions hash

- Error number: [MY-010581](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_STARTING](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s

- Error number: [MY-010582](#); Symbol: [ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED](#); SQLSTATE: [HY000](#)

Message: 'SQL_REPLICA_SKIP_COUNTER=%ld' executed at relay_log_file='%s', relay_log_pos='%ld', source_log_name='%s', source_log_pos='%ld' and new position at relay_log_file='%s', relay_log_pos='%ld', source_log_name='%s', source_log_pos='%ld'

- Error number: [MY-010583](#); Symbol: [ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)

Message: Replica (additional info): %s Error_code: MY-%06d

- Error number: [MY-010584](#); Symbol: [ER_RPL_REPLICA_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)

Message: Replica: %s Error_code: MY-%06d

- Error number: [MY-010585](#); Symbol: [ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Error loading user-defined library, replica SQL thread aborted. Install the missing library, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

- Error number: [MY-010586](#); Symbol: [ER_RPL_REPLICA_ERROR_RUNNING_QUERY](#); SQLSTATE: [HY000](#)

Message: Error running query, replica SQL thread aborted. Fix the problem, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

- Error number: [MY-010587](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s exiting, replication stopped in log '%s' at position %s

- Error number: [MY-010588](#); Symbol: [ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE](#); SQLSTATE: [HY000](#)

Message: Read invalid event from source: '%s', source could be corrupt but a more likely cause of this is a bug

- Error number: [MY-010589](#); Symbol: [ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: The queue event failed for channel '%s' as its configuration is invalid.

- Error number: [MY-010590](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from source '%s' binary log file, at position %llu.

- Error number: [MY-010591](#); Symbol: [ER_RPL_REPLICA_CANT_USE_CHARSET](#); SQLSTATE: [HY000](#)

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to source.

- Error number: [MY-010592](#); Symbol: [ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION_RESUMED](#); SQLSTATE: [HY000](#)

Message: Replica%s: connected to source '%s@%s:%d', replication resumed in log '%s' at position %s

- Error number: [MY-010593](#); Symbol: [ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is active

- Error number: [MY-010594](#); Symbol: [ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is not active

-
- Error number: [MY-010595](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT](#); SQLSTATE: [HY000](#)
 Message: Replica SQL thread%s: I/O error reading event (errno: %d cur_log->error: %d)
 - Error number: [MY-010596](#); Symbol: [ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS](#); SQLSTATE: [HY000](#)
 Message: Error reading relay log event%s: %s
 - Error number: [MY-010597](#); Symbol: [ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED](#); SQLSTATE: [HY000](#)
 Message: 'CHANGE REPLICATION SOURCE TO%s executed'. Previous state source_host='%s', source_port= %u, source_log_file='%s', source_log_pos= %ld, source_bind='%s'. New state source_host='%s', source_port= %u, source_log_file='%s', source_log_pos= %ld, source_bind='%s'.
 - Error number: [MY-010598](#); Symbol: [ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_THAN_FILE](#); SQLSTATE: [HY000](#)
 Message: Replica: Cannot create new connection metadata structure when repositories are of type FILE. Convert replica repositories to TABLE to replicate from multiple sources.
 - Error number: [MY-010599](#); Symbol: [ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX](#); SQLSTATE: [HY000](#)
 Message: log %s listed in the index, but failed to stat.
 - Error number: [MY-010600](#); Symbol: [ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_SPACE](#); SQLSTATE: [HY000](#)
 Message: Could not find first log while counting relay log space.
 - Error number: [MY-010601](#); Symbol: [ER_REPLICA_CANT_USE_TMPDIR](#); SQLSTATE: [HY000](#)
 Message: Unable to use replica's temporary directory '%s'.
 - Error number: [MY-010602](#); Symbol: [ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY](#); SQLSTATE: [HY000](#)
 Message: Path '%s' is a directory name, please specify a file name for --relay-log option.
 - Error number: [MY-010603](#); Symbol: [ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY](#); SQLSTATE: [HY000](#)
 Message: Path '%s' is a directory name, please specify a file name for --relay-log-index option.
 - Error number: [MY-010604](#); Symbol: [ER_RPL_PLEASE_USE_OPTION_RELAY_LOG](#); SQLSTATE: [HY000](#)
 Message: Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a replica and has his hostname changed!! Please use '--relay-log=%s' to avoid this problem.
 - Error number: [MY-010605](#); Symbol: [ER_RPL_OPEN_INDEX_FILE_FAILED](#); SQLSTATE: [HY000](#)
 Message: Failed in open_index_file() called from Relay_log_info::rli_init_info().
 - Error number: [MY-010606](#); Symbol: [ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO](#); SQLSTATE: [HY000](#)
 Message: Failed in init_gtid_sets() called from Relay_log_info::rli_init_info().

-
- Error number: [MY-010607](#); Symbol: [ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO](#); SQLSTATE: [HY000](#)
Message: Failed in open_log() called from Relay_log_info::rli_init_info().
 - Error number: [MY-010608](#); Symbol: [ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION](#); SQLSTATE: [HY000](#)
Message: Error writing relay log configuration.
 - Error number: [MY-010709](#); Symbol: [ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT](#); SQLSTATE: [HY000](#)
Message: Wrong tree: Parent doesn't point at parent
 - Error number: [MY-010710](#); Symbol: [ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK](#); SQLSTATE: [HY000](#)
Message: Wrong tree: Root should be black
 - Error number: [MY-010711](#); Symbol: [ER_TREE_CORRUPT_2_CONSECUTIVE_REDS](#); SQLSTATE: [HY000](#)
Message: Wrong tree: Found two red in a row
 - Error number: [MY-010712](#); Symbol: [ER_TREE_CORRUPT_RIGHT_IS_LEFT](#); SQLSTATE: [HY000](#)
Message: Wrong tree: Found right == left
 - Error number: [MY-010713](#); Symbol: [ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT](#); SQLSTATE: [HY000](#)
Message: Wrong tree: Incorrect black-count: %d - %d
 - Error number: [MY-010714](#); Symbol: [ER_WRONG_COUNT_FOR_ORIGIN](#); SQLSTATE: [HY000](#)
Message: Use_count: Wrong count %lu for origin %p
 - Error number: [MY-010715](#); Symbol: [ER_WRONG_COUNT_FOR_KEY](#); SQLSTATE: [HY000](#)
Message: Use_count: Wrong count for key at %p, %lu should be %lu
 - Error number: [MY-010716](#); Symbol: [ER_WRONG_COUNT_OF_ELEMENTS](#); SQLSTATE: [HY000](#)
Message: Wrong number of elements: %u (should be %u) for tree at %p
 - Error number: [MY-010717](#); Symbol: [ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION](#); SQLSTATE: [HY000](#)
Message: Error reading replica worker configuration
 - Error number: [MY-010719](#); Symbol: [ER_RPL_FAILED_TO_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Failed to open relay log %s, error: %s
 - Error number: [MY-010720](#); Symbol: [ER_RPL_WORKER_CANT_READ_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Error when worker read relay log events, relay log name %s, position %llu
 - Error number: [MY-010721](#); Symbol: [ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Failed to find next relay log when retrying the transaction, current relay log is %s

-
- Error number: [MY-010722](#); Symbol: [ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED](#); SQLSTATE: [HY000](#)

Message: Multi-threaded replica: Coordinator has waited %lu times hitting replica_pending_jobs_size_max; current event size = %zu.
 - Error number: [MY-010723](#); Symbol: [ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to write the DROP statement for temporary tables to binary log
 - Error number: [MY-010724](#); Symbol: [ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP_TABLE](#); SQLSTATE: [HY000](#)

Message: When opening HEAP table, could not allocate memory to write 'DELETE FROM `%%s`. `%%s`' to the binary log
 - Error number: [MY-010725](#); Symbol: [ER_FAILED_TO_REPAIR_TABLE](#); SQLSTATE: [HY000](#)

Message: Couldn't repair table: %%s.%%s
 - Error number: [MY-010726](#); Symbol: [ER_FAILED_TO_REMOVE_TEMP_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not remove temporary table: '%%s', error: %d
 - Error number: [MY-010727](#); Symbol: [ER_SYSTEM_TABLE_NOT_TRANSACTIONAL](#); SQLSTATE: [HY000](#)

Message: System table '%%.*s' is expected to be transactional.
 - Error number: [MY-010728](#); Symbol: [ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error writing source configuration.
 - Error number: [MY-010729](#); Symbol: [ER_RPL_ERROR_READING_SOURCE_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error reading source configuration.
 - Error number: [MY-010730](#); Symbol: [ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED](#); SQLSTATE: [HY000](#)

Message: SSL information in the connection metadata repository are ignored because this MySQL replica was compiled without SSL support.
 - Error number: [MY-010731](#); Symbol: [ER_PLUGIN_FAILED_DEINITIALIZATION](#); SQLSTATE: [HY000](#)

Message: Plugin '%%s' of type %%s failed deinitialization
 - Error number: [MY-010732](#); Symbol: [ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION](#); SQLSTATE: [HY000](#)

Message: Plugin '%%s' has ref_count=%%d after deinitialization.
 - Error number: [MY-010733](#); Symbol: [ER_PLUGIN_SHUTTING_DOWN_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Shutting down plugin '%%s'
 - Error number: [MY-010734](#); Symbol: [ER_PLUGIN_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Plugin '%%s' registration as a %%s failed.

-
- Error number: [MY-010735](#); Symbol: [ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not open the mysql.plugin table. Please perform the MySQL upgrade procedure.
 - Error number: [MY-010736](#); Symbol: [ER_PLUGIN_CANT_LOAD](#); SQLSTATE: [HY000](#)
Message: Couldn't load plugin named '%s' with soname '%s'.
 - Error number: [MY-010737](#); Symbol: [ER_PLUGIN_LOAD_PARAMETER_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: plugin-load parameter too long
 - Error number: [MY-010738](#); Symbol: [ER_PLUGIN_FORCING_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' will be forced to shutdown
 - Error number: [MY-010739](#); Symbol: [ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' has ref_count=%d after shutdown.
 - Error number: [MY-010740](#); Symbol: [ER_PLUGIN_UNKNOWN_VARIABLE_TYPE](#); SQLSTATE: [HY000](#)
Message: Unknown variable type code 0x%x in plugin '%s'.
 - Error number: [MY-010741](#); Symbol: [ER_PLUGIN_VARIABLE_SET_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: Server variable %s of plugin %s was forced to be read-only: string variable without update_func and PLUGIN_VAR_MEMALLOC flag
 - Error number: [MY-010742](#); Symbol: [ER_PLUGIN_VARIABLE_MISSING_NAME](#); SQLSTATE: [HY000](#)
Message: Missing variable name in plugin '%s'.
 - Error number: [MY-010743](#); Symbol: [ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL](#); SQLSTATE: [HY000](#)
Message: Thread local variable '%s' not allocated in plugin '%s'.
 - Error number: [MY-010744](#); Symbol: [ER_PLUGIN_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory for plugin '%s'.
 - Error number: [MY-010745](#); Symbol: [ER_PLUGIN_BAD_OPTIONS](#); SQLSTATE: [HY000](#)
Message: Bad options for plugin '%s'.
 - Error number: [MY-010746](#); Symbol: [ER_PLUGIN_PARSING_OPTIONS_FAILED](#); SQLSTATE: [HY000](#)
Message: Parsing options for plugin '%s' failed.
 - Error number: [MY-010747](#); Symbol: [ER_PLUGIN_DISABLED](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is disabled.
 - Error number: [MY-010748](#); Symbol: [ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' has conflicting system variables

-
- Error number: [MY-010749](#); Symbol: [ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS](#); SQLSTATE: [HY000](#)
Message: Setting persistent options for plugin '%s' failed.
 - Error number: [MY-010750](#); Symbol: [ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR](#); SQLSTATE: [HY000](#)
Message: Failed on my_net_write, writing to stderr instead: %s
 - Error number: [MY-010751](#); Symbol: [ER_RETRYING_REPAIR_WITHOUT_QUICK](#); SQLSTATE: [HY000](#)
Message: Retrying repair of: '%s' without quick
 - Error number: [MY-010752](#); Symbol: [ER_RETRYING_REPAIR_WITH_KEYCACHE](#); SQLSTATE: [HY000](#)
Message: Retrying repair of: '%s' with keycache
 - Error number: [MY-010753](#); Symbol: [ER_FOUND_ROWS_WHILE_REPAIRING](#); SQLSTATE: [HY000](#)
Message: Found %s of %s rows when repairing '%s'
 - Error number: [MY-010754](#); Symbol: [ER_ERROR_DURING_OPTIMIZE_TABLE](#); SQLSTATE: [HY000](#)
Message: Warning: Optimize table got errno %d on %s.%s, retrying
 - Error number: [MY-010755](#); Symbol: [ER_ERROR_ENABLING_KEYS](#); SQLSTATE: [HY000](#)
Message: Warning: Enabling keys got errno %d on %s.%s, retrying
 - Error number: [MY-010756](#); Symbol: [ER_CHECKING_TABLE](#); SQLSTATE: [HY000](#)
Message: Checking table: '%s'
 - Error number: [MY-010757](#); Symbol: [ER_RECOVERING_TABLE](#); SQLSTATE: [HY000](#)
Message: Recovering table: '%s'
 - Error number: [MY-010758](#); Symbol: [ER_CANT_CREATE_TABLE_SHARE_FROM_FRM](#); SQLSTATE: [HY000](#)
Message: Error in creating TABLE_SHARE from %s.frm file.
 - Error number: [MY-010759](#); Symbol: [ER_CANT_LOCK_TABLE](#); SQLSTATE: [HY000](#)
Message: Unable to acquire lock on %s.%s
 - Error number: [MY-010760](#); Symbol: [ER_CANT_ALLOC_TABLE_OBJECT](#); SQLSTATE: [HY000](#)
Message: Error in allocation memory for TABLE object.
 - Error number: [MY-010761](#); Symbol: [ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE](#); SQLSTATE: [HY000](#)
Message: Error in creating handler object for table %s.%s
 - Error number: [MY-010762](#); Symbol: [ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE](#); SQLSTATE: [HY000](#)
Message: Error in setting handler reference for table %s.%s
 - Error number: [MY-010763](#); Symbol: [ER_CANT_LOCK_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Unable to acquire lock on tablespace name %s

- Error number: [MY-010764](#); Symbol: [ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD](#); SQLSTATE: [HY000](#)

Message: Error in processing generated columns for table %s.%s

- Error number: [MY-010765](#); Symbol: [ER_DD_ERROR_CREATING_ENTRY](#); SQLSTATE: [HY000](#)

Message: Error in Creating DD entry for %s.%s

- Error number: [MY-010766](#); Symbol: [ER_DD_CANT_FETCH_TABLE_DATA](#); SQLSTATE: [HY000](#)

Message: Error in fetching %s.%s table data from dictionary

- Error number: [MY-010767](#); Symbol: [ER_DD_CANT_FIX_SE_DATA](#); SQLSTATE: [HY000](#)

Message: Error in fixing SE data for %s.%s

- Error number: [MY-010768](#); Symbol: [ER_DD_CANT_CREATE_SP](#); SQLSTATE: [HY000](#)

Message: Error in creating stored program '%s.%s'

- Error number: [MY-010769](#); Symbol: [ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET](#); SQLSTATE: [HY000](#)

Message: Unable to open db.opt file %s. Using default Character set.

- Error number: [MY-010770](#); Symbol: [ER_CANT_CREATE_CACHE_FOR_DB_OPT](#); SQLSTATE: [HY000](#)

Message: Unable to initialize IO cache to open db.opt file %s.

- Error number: [MY-010771](#); Symbol: [ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT](#); SQLSTATE: [HY000](#)

Message: Unable to identify the charset in %s. Using default character set.

- Error number: [MY-010772](#); Symbol: [ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET](#); SQLSTATE: [HY000](#)

Message: db.opt file not found for %s database. Using default Character set.

- Error number: [MY-010773](#); Symbol: [ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD](#); SQLSTATE: [HY000](#)

Message: Event '%s'. '%s': invalid value in column mysql.event.time_zone.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.event](#) system table and migrates its contents to the internal data dictionary.

- Error number: [MY-010774](#); Symbol: [ER_EVENT_CANT_FIND_TIMEZONE](#); SQLSTATE: [HY000](#)

Message: Event '%s'. '%s': has invalid time zone value

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.event](#) system table and migrates its contents to the internal data dictionary.

- Error number: [MY-010775](#); Symbol: [ER_EVENT_CANT_GET_CHARSET](#); SQLSTATE: [HY000](#)

Message: Event '%s'. '%s': invalid value in column mysql.event.character_set_client.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

- Error number: `MY-010776`; Symbol: `ER_EVENT_CANT_GET_COLLATION`; SQLSTATE: `HY000`

Message: Event '%s'. '%s': invalid value in column mysql.event.collation_connection.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

- Error number: `MY-010777`; Symbol: `ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT`; SQLSTATE: `HY000`

Message: Failed to open mysql.event Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

- Error number: `MY-010778`; Symbol: `ER_CANT_PARSE_STORED_ROUTINE_BODY`; SQLSTATE: `HY000`

Message: Parsing '%s.%s' routine body failed.%s

- Error number: `MY-010779`; Symbol: `ER_CANT_OPEN_TABLE_MYSQL_PROC`; SQLSTATE: `HY000`

Message: Failed to open mysql.proc Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

- Error number: `MY-010780`; Symbol: `ER_CANT_READ_TABLE_MYSQL_PROC`; SQLSTATE: `HY000`

Message: Failed to read mysql.proc table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

- Error number: `MY-010781`; Symbol: `ER_FILE_EXISTS_DURING_UPGRADE`; SQLSTATE: `HY000`

Message: Found %s file in mysql schema. DD will create .ibd file with same name. Please rename table and start upgrade process again.

- Error number: `MY-010782`; Symbol: `ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE`; SQLSTATE: `HY000`

Message: Unable to open the data directory %s during clean up after upgrade failed

- Error number: `MY-010783`; Symbol: `ER_CANT_SET_PATH_FOR`; SQLSTATE: `HY000`

Message: Failed to set path %s

- Error number: `MY-010784`; Symbol: `ER_CANT_OPEN_DIR`; SQLSTATE: `HY000`

Message: Failed to open dir %s

- Error number: `MY-010801`; Symbol: `ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG`; SQLSTATE: `HY000`

Message: Event Error: An error occurred while creating query string, before writing it into binary log.

- Error number: [MY-010802](#); Symbol: [ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading from disk.

- Error number: [MY-010803](#); Symbol: [ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error getting event object.

- Error number: [MY-010804](#); Symbol: [ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading events from mysql.events. The table probably contains bad data or is corrupted

- Error number: [MY-010805](#); Symbol: [ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to obtain lock for dropping event %s from schema %s

- Error number: [MY-010806](#); Symbol: [ER_EVENT_UNABLE_TO_DROP_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to drop event %s from schema %s

- Error number: [MY-010808](#); Symbol: [ER_BINLOG_CANT_RESIZE_CACHE](#); SQLSTATE: [HY000](#)

Message: Unable to resize binlog IOCACHE auxiliary file

- Error number: [MY-010809](#); Symbol: [ER_BINLOG_FILE_BEING_READ_NOT_PURGED](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by thread number %u

- Error number: [MY-010810](#); Symbol: [ER_BINLOG_IO_ERROR_READING_HEADER](#); SQLSTATE: [HY000](#)

Message: I/O error reading the header from the binary log, errno=%d, io cache code=%d

- Error number: [MY-010813](#); Symbol: [ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED](#); SQLSTATE: [HY000](#)

Message: Log filename extension number exhausted: %06lu. Please fix this by archiving old logs and updating the index files.

- Error number: [MY-010814](#); Symbol: [ER_BINLOG_FILE_NAME_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Log filename too large: %s%s (%zu). Please fix this by archiving old logs and updating the index files.

- Error number: [MY-010815](#); Symbol: [ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW](#); SQLSTATE: [HY000](#)

Message: Next log extension: %lu. Remaining log filename extensions: %lu. Please consider archiving some logs.

- Error number: [MY-010816](#); Symbol: [ER_BINLOG_CANT_OPEN_FOR_LOGGING](#); SQLSTATE: [HY000](#)

Message: Could not open %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

-
- Error number: [MY-010817](#); Symbol: [ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE](#); SQLSTATE: [HY000](#)
Message: MYSQL_BIN_LOG::open_index_file failed to sync the index file.
 - Error number: [MY-010818](#); Symbol: [ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Error reading GTIDs from relaylog: %d
 - Error number: [MY-010819](#); Symbol: [ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA](#); SQLSTATE: [HY000](#)
Message: %lu events read in relaylog file '%s' for updating Retrieved_Gtid_Set and/or IO thread transaction parser state.
 - Error number: [MY-010820](#); Symbol: [ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG](#); SQLSTATE: [HY000](#)
Message: Error reading GTIDs from binary log: %d
 - Error number: [MY-010821](#); Symbol: [ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO](#); SQLSTATE: [HY000](#)
Message: Read %lu events from binary log file '%s' to determine the GTIDs purged from binary logs.
 - Error number: [MY-010822](#); Symbol: [ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME](#); SQLSTATE: [HY000](#)
Message: MYSQL_BIN_LOG::open failed to generate new file name.
 - Error number: [MY-010823](#); Symbol: [ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN](#); SQLSTATE: [HY000](#)
Message: MYSQL_BIN_LOG::open failed to sync the index file.
 - Error number: [MY-010824](#); Symbol: [ER_BINLOG_CANT_USE_FOR_LOGGING](#); SQLSTATE: [HY000](#)
Message: Could not use %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.
 - Error number: [MY-010825](#); Symbol: [ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)
Message: While rebuilding index file %s: Failed to close the index file.
 - Error number: [MY-010826](#); Symbol: [ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)
Message: While rebuilding index file %s: Failed to delete the existing index file. It could be that file is being used by some other process.
 - Error number: [MY-010827](#); Symbol: [ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)
Message: While rebuilding index file %s: Failed to rename the new index file to the existing index file.
 - Error number: [MY-010828](#); Symbol: [ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING](#); SQLSTATE: [HY000](#)
Message: After rebuilding the index file %s: Failed to open the index file.
 - Error number: [MY-010829](#); Symbol: [ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::add_log_to_index failed to append log file name: %s, to crash safe index file.

- Error number: [MY-010830](#); Symbol: [ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES](#); SQLSTATE: [HY000](#)

Message: Failed to locate old binlog or relay log files

- Error number: [MY-010831](#); Symbol: [ER_BINLOG_CANT_DELETE_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to delete file '%s'

- Error number: [MY-010832](#); Symbol: [ER_BINLOG_CANT_SET_TMP_INDEX_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::set_crash_safe_index_file_name failed to set file name.

- Error number: [MY-010833](#); Symbol: [ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open_crash_safe_index_file failed to open temporary index file.

- Error number: [MY-010835](#); Symbol: [ER_BINLOG_CANT_OPEN_TMP_INDEX](#); SQLSTATE: [HY000](#)

Message: %s failed to open the crash safe index file.

- Error number: [MY-010836](#); Symbol: [ER_BINLOG_CANT_COPY_INDEX_TO_TMP](#); SQLSTATE: [HY000](#)

Message: %s failed to copy index file to crash safe index file.

- Error number: [MY-010837](#); Symbol: [ER_BINLOG_CANT_CLOSE_TMP_INDEX](#); SQLSTATE: [HY000](#)

Message: %s failed to close the crash safe index file.

- Error number: [MY-010838](#); Symbol: [ER_BINLOG_CANT_MOVE_TMP_TO_INDEX](#); SQLSTATE: [HY000](#)

Message: %s failed to move crash safe index file to index file.

- Error number: [MY-010839](#); Symbol: [ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs was called with file %s not listed in the index.

- Error number: [MY-010840](#); Symbol: [ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to sync the index file.

- Error number: [MY-010841](#); Symbol: [ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to copy %s to register file.

- Error number: [MY-010842](#); Symbol: [ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to flush register file.

- Error number: [MY-010843](#); Symbol: [ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to update the index file

- Error number: [MY-010844](#); Symbol: [ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to process registered files that would be purged.

- Error number: [MY-010845](#); Symbol: [ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::set_purge_index_file_name failed to set file name.

- Error number: [MY-010846](#); Symbol: [ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open_purge_index_file failed to open register file.

- Error number: [MY-010847](#); Symbol: [ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_index_entry failed to reinit register file for read

- Error number: [MY-010848](#); Symbol: [ER_BINLOG_FAILED_TO_READ_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_index_entry error %d reading from register file.

- Error number: [MY-010849](#); Symbol: [ER_CANT_STAT_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to execute mysql_file_stat on file '%s'

- Error number: [MY-010850](#); Symbol: [ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES](#); SQLSTATE: [HY000](#)

Message: Failed to delete log file '%s'; consider examining correspondence of your binlog index file to the actual binlog files

- Error number: [MY-010851](#); Symbol: [ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: Failed to delete file '%s' and read the binlog index file

- Error number: [MY-010852](#); Symbol: [ER_BINLOG_FAILED_TO_DELETE_LOG_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to delete log file '%s'

- Error number: [MY-010853](#); Symbol: [ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS](#); SQLSTATE: [HY000](#)

Message: %s An incident event has been written to the binary log which will stop the replicas.

- Error number: [MY-010854](#); Symbol: [ER_BINLOG_CANT_FIND_LOG_IN_INDEX](#); SQLSTATE: [HY000](#)

Message: find_log_pos() failed (error: %d)

- Error number: [MY-010855](#); Symbol: [ER_BINLOG_RECOVERING_AFTER_CRASH_USING](#); SQLSTATE: [HY000](#)

Message: Recovering after a crash using %s

-
- Error number: [MY-010856](#); Symbol: [ER_BINLOG_CANT_OPEN_CRASHED_BINLOG](#); SQLSTATE: [HY000](#)
Message: Failed to open the crashed binlog file when source server is recovering it.
 - Error number: [MY-010857](#); Symbol: [ER_BINLOG_CANT_TRIM_CRASHED_BINLOG](#); SQLSTATE: [HY000](#)
Message: Failed to trim the crashed binlog file when source server is recovering it.
 - Error number: [MY-010858](#); Symbol: [ER_BINLOG_CRASHED_BINLOG_TRIMMED](#); SQLSTATE: [HY000](#)
Message: Crashed binlog file %s size is %llu, but recovered up to %llu. Binlog trimmed to %llu bytes.
 - Error number: [MY-010859](#); Symbol: [ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG](#); SQLSTATE: [HY000](#)
Message: Failed to clear LOG_EVENT_BINLOG_IN_USE_F for the crashed binlog file when source server is recovering it.
 - Error number: [MY-010860](#); Symbol: [ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK](#); SQLSTATE: [HY000](#)
Message: Failed to run 'after_sync' hooks
 - Error number: [MY-010861](#); Symbol: [ER_TURNING_LOGGING_OFF_FOR_THE_DURATION](#); SQLSTATE: [HY000](#)
Message: %s Hence turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.
 - Error number: [MY-010862](#); Symbol: [ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK](#); SQLSTATE: [HY000](#)
Message: Failed to run 'after_flush' hooks
 - Error number: [MY-010864](#); Symbol: [ER_BINLOG_WARNING_SUPPRESSED](#); SQLSTATE: [HY000](#)
Message: The following warning was suppressed %d times during the last %d seconds in the error log
 - Error number: [MY-010865](#); Symbol: [ER_NDB_LOG_ENTRY](#); SQLSTATE: [HY000](#)
Message: NDB: %s
 - Error number: [MY-010866](#); Symbol: [ER_NDB_LOG_ENTRY_WITH_PREFIX](#); SQLSTATE: [HY000](#)
Message: NDB %s: %s
 - Error number: [MY-010868](#); Symbol: [ER_INNODB_UNKNOWN_COLLATION](#); SQLSTATE: [HY000](#)
Message: Unknown collation #%lu.
 - Error number: [MY-010869](#); Symbol: [ER_INNODB_INVALID_LOG_GROUP_HOME_DIR](#); SQLSTATE: [HY000](#)
Message: syntax error in innodb_log_group_home_dir
 - Error number: [MY-010870](#); Symbol: [ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY](#); SQLSTATE: [HY000](#)
Message: syntax error in innodb_undo_directory

- Error number: [MY-010871](#); Symbol: [ER_INNODB_ILLEGAL_COLON_IN_POOL](#); SQLSTATE: [HY000](#)
Message: InnoDB: innodb_buffer_pool_filename cannot have colon (:) in the file name.
- Error number: [MY-010872](#); Symbol: [ER_INNODB_INVALID_PAGE_SIZE](#); SQLSTATE: [HY000](#)
Message: InnoDB: Invalid page size=%lu.
- Error number: [MY-010873](#); Symbol: [ER_INNODB_DIRTY_WATER_MARK_NOT_LOW](#); SQLSTATE: [HY000](#)
Message: InnoDB: innodb_max_dirty_pages_pct_lwm cannot be set higher than innodb_max_dirty_pages_pct. Setting innodb_max_dirty_pages_pct_lwm to %lf
- Error number: [MY-010874](#); Symbol: [ER_INNODB_IO_CAPACITY_EXCEEDS_MAX](#); SQLSTATE: [HY000](#)
Message: InnoDB: innodb_io_capacity cannot be set higher than innodb_io_capacity_max. Setting innodb_io_capacity to %lu
- Error number: [MY-010875](#); Symbol: [ER_INNODB_FILES_SAME](#); SQLSTATE: [HY000](#)
Message: %s and %s file names seem to be the same.
- Error number: [MY-010876](#); Symbol: [ER_INNODB_UNREGISTERED_TRX_ACTIVE](#); SQLSTATE: [HY000](#)
Message: Transaction not registered for MySQL 2PC, but transaction is active
- Error number: [MY-010877](#); Symbol: [ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK](#); SQLSTATE: [HY000](#)
Message: MySQL is closing a connection that has an active InnoDB transaction. %llu row modifications will roll back.
- Error number: [MY-010878](#); Symbol: [ER_INNODB_TRX_XLATION_TABLE_OOM](#); SQLSTATE: [HY000](#)
Message: InnoDB: fail to allocate memory for index translation table. Number of Index:%lu, array size:%lu
- Error number: [MY-010879](#); Symbol: [ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD](#); SQLSTATE: [HY000](#)
Message: Cannot find index %s in InnoDB index dictionary.
- Error number: [MY-010880](#); Symbol: [ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS](#); SQLSTATE: [HY000](#)
Message: Found index %s whose column info does not match that of MySQL.
- Error number: [MY-010882](#); Symbol: [ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR](#); SQLSTATE: [HY000](#)
Message: Build InnoDB index translation table for Table %s failed
- Error number: [MY-010883](#); Symbol: [ER_INNODB_PK_NOT_IN_MYSQL](#); SQLSTATE: [HY000](#)
Message: Table %s has a primary key in InnoDB data dictionary, but not in MySQL!
- Error number: [MY-010884](#); Symbol: [ER_INNODB_PK_ONLY_IN_MYSQL](#); SQLSTATE: [HY000](#)
Message: Table %s has no primary key in InnoDB data dictionary, but has one in MySQL! If you created the table with a MySQL version < 3.23.54 and did not define a primary key, but defined a

unique key with all non-NULL columns, then MySQL internally treats that key as the primary key. You can fix this error by dump + DROP + CREATE + reimport of the table.

- Error number: [MY-010885](#); Symbol: [ER_INNODB_CLUSTERED_INDEX_PRIVATE](#); SQLSTATE: [HY000](#)

Message: Table %s key_used_on_scan is %lu even though there is no primary key inside InnoDB.
- Error number: [MY-010887](#); Symbol: [ER_ERRMSG_REPLACEMENT_DODGY](#); SQLSTATE: [HY000](#)

Message: Cannot replace error message (%s,%s,%s) "%s" with "%s"; wrong number or type of %% substitutions.
- Error number: [MY-010888](#); Symbol: [ER_ERRMSG_REPLACEMENTS_FAILED](#); SQLSTATE: [HY000](#)

Message: Table for error message replacements could not be found or read, or one or more replacements could not be applied.
- Error number: [MY-010889](#); Symbol: [ER_NPIPE_CANT_CREATE](#); SQLSTATE: [HY000](#)

Message: %s: %s
- Error number: [MY-010890](#); Symbol: [ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_FIX](#); SQLSTATE: [HY000](#)

Message: Table '%s': Delete from part %d failed with error %d. But it was already inserted into part %d, when moving the misplaced row! Please manually fix the duplicate row: %s
- Error number: [MY-010891](#); Symbol: [ER_AUDIT_CANT_ABORT_COMMAND](#); SQLSTATE: [HY000](#)

Message: Command '%s' cannot be aborted. The trigger error was (%d) [%s]: %s
- Error number: [MY-010892](#); Symbol: [ER_AUDIT_CANT_ABORT_EVENT](#); SQLSTATE: [HY000](#)

Message: Event '%s' cannot be aborted. The trigger error was (%d) [%s]: %s
- Error number: [MY-010893](#); Symbol: [ER_AUDIT_WARNING](#); SQLSTATE: [HY000](#)

Message: %s. The trigger error was (%d) [%s]: %s
- Error number: [MY-010897](#); Symbol: [ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.
- Error number: [MY-010899](#); Symbol: [ER_RPL_REPLICA_INCORRECT_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica channel '%s' does not exist.
- Error number: [MY-010900](#); Symbol: [ER_FAILED_TO_FIND_DL_ENTRY](#); SQLSTATE: [HY000](#)

Message: Can't find symbol '%s' in library.
- Error number: [MY-010901](#); Symbol: [ER_FAILED_TO_OPEN_SHARED_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Can't open shared library '%s' (errno: %d %s).
- Error number: [MY-010902](#); Symbol: [ER_THREAD_PRIORITY_IGNORED](#); SQLSTATE: [HY000](#)

Message: Thread priority attribute setting in Resource Group SQL shall be ignored due to unsupported platform or insufficient privilege.

- Error number: [MY-010903](#); Symbol: [ER_BINLOG_CACHE_SIZE_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.

- Error number: [MY-010904](#); Symbol: [ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.

- Error number: [MY-010905](#); Symbol: [ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE](#); SQLSTATE: [HY000](#)

Message: Can't generate a unique log-filename %s.(1-999).

- Error number: [MY-010906](#); Symbol: [ER_FAILED_TO_READ_FILE](#); SQLSTATE: [HY000](#)

Message: Error reading file '%s' (errno: %d - %s)

- Error number: [MY-010907](#); Symbol: [ER_FAILED_TO_WRITE_TO_FILE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s)

- Error number: [MY-010908](#); Symbol: [ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT](#); SQLSTATE: [HY000](#)

Message: %s Statement: %s

- Error number: [MY-010909](#); Symbol: [ER_FORCE_CLOSE_THREAD](#); SQLSTATE: [HY000](#)

Message: %s: Forcing close of thread %ld user: '%s'.

- Error number: [MY-010910](#); Symbol: [ER_SERVER_SHUTDOWN_COMPLETE](#); SQLSTATE: [HY000](#)

Message: %s: Shutdown complete (mysqld %s) %s.

- Error number: [MY-010911](#); Symbol: [ER_RPL_CANT_HAVE_SAME_BASENAME](#); SQLSTATE: [HY000](#)

Message: Cannot have same base name '%s' for both binary and relay logs. Please check %s (default '%s' if --log-bin option is not used, default '%s' if --log-bin option is used without argument) and %s (default '%s') options to ensure they do not conflict.

- Error number: [MY-010912](#); Symbol: [ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON](#); SQLSTATE: [HY000](#)

Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.

- Error number: [MY-010913](#); Symbol: [ER_WARN_NO_SERVERID_SPECIFIED](#); SQLSTATE: [HY000](#)

Message: You have not provided a mandatory server-id. Servers in a replication topology must have unique server-ids. Please refer to the proper server start-up parameters documentation.

- Error number: [MY-010914](#); Symbol: [ER_ABORTING_USER_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

- Error number: [MY-010915](#); Symbol: [ER_SQL_MODE_MERGED_WITH_STRICT_MODE](#); SQLSTATE: [HY000](#)

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

- Error number: [MY-010916](#); Symbol: [ER_GTID_PURGED_WAS_UPDATED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.

- Error number: [MY-010917](#); Symbol: [ER_GTID_EXECUTED_WAS_UPDATED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.

- Error number: [MY-010918](#); Symbol: [ER_DEPRECATED_MSG_WITH_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead.

- Error number: [MY-010919](#); Symbol: [ER_TRG_CREATION_CTX_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Triggers for table `%s`.`%s` have no creation context

- Error number: [MY-010920](#); Symbol: [ER_FILE_HAS_OLD_FORMAT](#); SQLSTATE: [HY000](#)

Message: '%s' has an old format, you should re-create the '%s' object(s)

- Error number: [MY-010921](#); Symbol: [ER_VIEW_CREATION_CTX_NOT_SET](#); SQLSTATE: [HY000](#)

Message: View `%s`.`%s` has no creation context

- Error number: [MY-010923](#); Symbol: [ER_TABLE_UPGRADE_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Table upgrade required. Please do "REPAIR TABLE `%s`" or dump/reload to fix it!

- Error number: [MY-010924](#); Symbol: [ER_GET_ERRNO_FROM_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine.

- Error number: [MY-010925](#); Symbol: [ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'

- Error number: [MY-010926](#); Symbol: [ER_ACCESS_DENIED_ERROR_WITH_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s' (using password: %s)

- Error number: [MY-010927](#); Symbol: [ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is locked.

- Error number: [MY-010929](#); Symbol: [ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Storage engine '%s' does not support system tables. [%s.%s].

- Error number: [MY-010931](#); Symbol: [ER_SERVER_STARTUP_MSG](#); SQLSTATE: [HY000](#)

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s.

- Error number: [MY-010932](#); Symbol: [ER_FAILED_TO_FIND_LOCALE_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown locale: '%s'.

- Error number: [MY-010933](#); Symbol: [ER_FAILED_TO_FIND_COLLATION_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown collation: '%s'.

- Error number: [MY-010934](#); Symbol: [ER_SERVER_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: [MY-010935](#); Symbol: [ER_SERVER_OUTOFMEMORY](#); SQLSTATE: [HY000](#)

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: [MY-010936](#); Symbol: [ER_INVALID_COLLATION_FOR_CHARSET](#); SQLSTATE: [HY000](#)

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

- Error number: [MY-010937](#); Symbol: [ER_CANT_START_ERROR_LOG_SERVICE](#); SQLSTATE: [HY000](#)

Message: Failed to set %s at or around "%s" -- service is valid, but can not be initialized; please check its configuration and make sure it can read its input(s) and write to its output(s).

- Error number: [MY-010938](#); Symbol: [ER_CREATING_NEW_UUID_FIRST_START](#); SQLSTATE: [HY000](#)

Message: Generating a new UUID: %s.

- Error number: [MY-010939](#); Symbol: [ER_FAILED_TO_GET_ABSOLUTE_PATH](#); SQLSTATE: [HY000](#)

Message: Failed to get absolute path of program executable %s

- Error number: [MY-010940](#); Symbol: [ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap performance schema components infrastructure.

- Error number: [MY-010941](#); Symbol: [ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Failed to deinit performance schema components infrastructure.

- Error number: [MY-010942](#); Symbol: [ER_DUP_FD_OPEN_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not open duplicate fd for %s: %s.

- Error number: [MY-010943](#); Symbol: [ER_SYSTEM_VIEW_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: System views initialization failed.

- Error number: [MY-010944](#); Symbol: [ER_RESOURCE_GROUP_POST_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Resource group post initialization failed.

- Error number: [MY-010945](#); Symbol: [ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Resource Group subsystem initialization failed.

-
- Error number: [MY-010946](#); Symbol: [ER_FAILED_START_MYSQLD_DAEMON](#); SQLSTATE: [HY000](#)
Message: Failed to start mysqld daemon. Check mysqld error log.
 - Error number: [MY-010947](#); Symbol: [ER_CANNOT_CHANGE_TO_ROOT_DIR](#); SQLSTATE: [HY000](#)
Message: Cannot change to root directory: %s.
 - Error number: [MY-010948](#); Symbol: [ER_PERSISTENT_PRIVILEGES_BOOTSTRAP](#); SQLSTATE: [HY000](#)
Message: Failed to bootstrap persistent privileges.
 - Error number: [MY-010949](#); Symbol: [ER_BASEDIR_SET_TO](#); SQLSTATE: [HY000](#)
Message: Basedir set to %s.
 - Error number: [MY-010950](#); Symbol: [ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED](#); SQLSTATE: [HY000](#)
Message: Could not add wild do table rule '%s'!
 - Error number: [MY-010951](#); Symbol: [ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED](#); SQLSTATE: [HY000](#)
Message: Could not add wild ignore table rule '%s'!
 - Error number: [MY-010952](#); Symbol: [ER_PRIVILEGE_SYSTEM_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: The privilege system failed to initialize correctly. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.
 - Error number: [MY-010953](#); Symbol: [ER_CANNOT_SET_LOG_ERROR_SERVICES](#); SQLSTATE: [HY000](#)
Message: Cannot set services "%s" requested in --log-error-services, using defaults.
 - Error number: [MY-010954](#); Symbol: [ER_PERFSCHEMA_TABLES_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Performance schema tables initialization failed.
 - Error number: [MY-010958](#); Symbol: [ER_BINLOG_FILE_OPEN_FAILED](#); SQLSTATE: [HY000](#)
Message: %s.
 - Error number: [MY-010959](#); Symbol: [ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to write an incident event into stmt_cache.
 - Error number: [MY-010960](#); Symbol: [ER_REPLICA_RELAY_LOG_TRUNCATE_INFO](#); SQLSTATE: [HY000](#)
Message: Relaylog file %s size was %llu, but was truncated at %llu.
 - Error number: [MY-010961](#); Symbol: [ER_REPLICA_RELAY_LOG_PURGE_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to purge relay log files. %s:%s.
 - Error number: [MY-010962](#); Symbol: [ER_RPL_REPLICA_FILTER_CREATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Replica: failed in creating filter for channel '%s'.

- Error number: [MY-010963](#); Symbol: [ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED](#); SQLSTATE: [HY000](#)

Message: Replica: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.

- Error number: [MY-010964](#); Symbol: [ER_RPL_REPLICA_RESET_FILTER_OPTIONS](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

- Error number: [MY-010965](#); Symbol: [ER_MISSING_GRANT_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: The system table mysql.global_grants is missing. Please perform the MySQL upgrade procedure.

- Error number: [MY-010966](#); Symbol: [ER_MISSING_ACL_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: ACL table mysql.%.*s missing. Some operations may fail.

- Error number: [MY-010967](#); Symbol: [ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)

Message: Can't set mandatory_role %s@%s: Anonymous authorization IDs are not allowed as roles.

- Error number: [MY-010968](#); Symbol: [ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE](#); SQLSTATE: [HY000](#)

Message: Can't set mandatory_role: There's no such authorization ID %s@%s.

- Error number: [MY-010969](#); Symbol: [ER_WRITE_ROW_TO_PARTITION_FAILED](#); SQLSTATE: [HY000](#)

Message: Table '%s' failed to move/insert a row from part %d into part %d: %s.

- Error number: [MY-010970](#); Symbol: [ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED](#); SQLSTATE: [HY000](#)

Message: Skipped updating resource group metadata in InnoDB read only mode.

- Error number: [MY-010971](#); Symbol: [ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA](#); SQLSTATE: [HY000](#)

Message: Failed to persist resource group %s to Data Dictionary.

- Error number: [MY-010972](#); Symbol: [ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)

Message: Failed to deserialize resource group %s.

- Error number: [MY-010973](#); Symbol: [ER_FAILED_TO_UPDATE_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)

Message: Update of resource group %s failed.

- Error number: [MY-010974](#); Symbol: [ER_RESOURCE_GROUP_VALIDATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Validation of resource group %s failed. Resource group is disabled.

-
- Error number: [MY-010975](#); Symbol: [ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)
Message: Unable to allocate memory for Resource Group %s.
 - Error number: [MY-010976](#); Symbol: [ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH](#); SQLSTATE: [HY000](#)
Message: Failed to allocate memory for resource group hash.
 - Error number: [MY-010977](#); Symbol: [ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP](#); SQLSTATE: [HY000](#)
Message: Failed to add resource group %s to resource group map.
 - Error number: [MY-010978](#); Symbol: [ER_RESOURCE_GROUP_IS_DISABLED](#); SQLSTATE: [HY000](#)
Message: Resource group feature is disabled. (Server is compiled with `DISABLE_PSI_THREAD`).
 - Error number: [MY-010979](#); Symbol: [ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER](#); SQLSTATE: [HY000](#)
Message: Unable to apply resource group controller %s.
 - Error number: [MY-010980](#); Symbol: [ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)
Message: Unable to acquire lock on the resource group %s. Hint to switch resource group shall be ignored.
 - Error number: [MY-010981](#); Symbol: [ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED](#); SQLSTATE: [HY000](#)
Message: PFS %s notification function registration failed.
 - Error number: [MY-010982](#); Symbol: [ER_RES_GRP_SET_THR_AFFINITY_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to bind thread id %llu to cpu id %u (error code %d - %s).
 - Error number: [MY-010983](#); Symbol: [ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to bind thread id %llu to cpu ids (error code %d - %s).
 - Error number: [MY-010984](#); Symbol: [ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED](#); SQLSTATE: [HY000](#)
Message: Unbind thread id %llu failed. (error code %d - %s).
 - Error number: [MY-010985](#); Symbol: [ER_RES_GRP_SET_THREAD_PRIORITY_FAILED](#); SQLSTATE: [HY000](#)
Message: Setting thread priority %d to thread id %llu failed. (error code %d - %s).
 - Error number: [MY-010986](#); Symbol: [ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY](#); SQLSTATE: [HY000](#)
Message: Unable to determine `CAP_SYS_NICE` capability.
 - Error number: [MY-010987](#); Symbol: [ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE](#); SQLSTATE: [HY000](#)
Message: %s failed: Failed to get handle for thread %llu.

-
- Error number: [MY-010988](#); Symbol: [ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Retrieval of thread priority unsupported on %s.
 - Error number: [MY-010989](#); Symbol: [ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT](#); SQLSTATE: [HY000](#)

Message: Unable to determine the number of CPUs.
 - Error number: [MY-010990](#); Symbol: [ER_RES_GRP_FEATURE_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Resource group feature shall not be available. Incompatible thread handling option.
 - Error number: [MY-010991](#); Symbol: [ER_RES_GRP_INVALID_THREAD_PRIORITY](#); SQLSTATE: [HY000](#)

Message: Invalid thread priority %d for a %s resource group. Allowed range is [%d, %d].
 - Error number: [MY-010992](#); Symbol: [ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED](#); SQLSTATE: [HY000](#)

Message: bind_to_cpu failed: processor_bind for cpuid %u failed (error code %d - %s).
 - Error number: [MY-010993](#); Symbol: [ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED](#); SQLSTATE: [HY000](#)

Message: bind_to_cpu failed: processor_bind for thread %llx with cpu id %u (error code %d - %s).
 - Error number: [MY-010994](#); Symbol: [ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED](#); SQLSTATE: [HY000](#)

Message: %s failed: processor_affinity failed (error code %d - %s).
 - Error number: [MY-010995](#); Symbol: [ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in renaming mysql_index_stats.ibd.
 - Error number: [MY-010996](#); Symbol: [ER_DD_UPGRADE_DD_OPEN_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in opening data directory %s.
 - Error number: [MY-010997](#); Symbol: [ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES](#); SQLSTATE: [HY000](#)

Message: Error in fetching list of tablespaces.
 - Error number: [MY-010998](#); Symbol: [ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in acquiring Tablespace for SDI insertion %s.
 - Error number: [MY-010999](#); Symbol: [ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Error in resolving Engine name for tablespace %s with engine %s.
 - Error number: [MY-011000](#); Symbol: [ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in creating SDI for %s tablespace.

-
- Error number: `MY-011001`; Symbol: `ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`
Message: Error in storing SDI for %s tablespace.
 - Error number: `MY-011002`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES`; SQLSTATE: `HY000`
Message: Error in fetching list of tables.
 - Error number: `MY-011003`; Symbol: `ER_DD_UPGRADE_DD_POPULATED`; SQLSTATE: `HY000`
Message: Finished populating Data Dictionary tables with data.
 - Error number: `MY-011004`; Symbol: `ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED`; SQLSTATE: `HY000`
Message: Could not open the upgrade info file '%s' in the MySQL servers datadir, errno: %d.
 - Error number: `MY-011005`; Symbol: `ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED`; SQLSTATE: `HY000`
Message: Could not close the upgrade info file '%s' in the MySQL servers datadir, errno: %d.
 - Error number: `MY-011006`; Symbol: `ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED`; SQLSTATE: `HY000`
Message: Got error %d from SE while migrating tablespaces.
 - Error number: `MY-011007`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS`; SQLSTATE: `HY000`
Message: Error in creating TABLE statistics entry. Fix statistics data by using ANALYZE command.
 - Error number: `MY-011008`; Symbol: `ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`
Message: Finished migrating TABLE statistics data.
 - Error number: `MY-011009`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS`; SQLSTATE: `HY000`
Message: Error in creating Index statistics entry. Fix statistics data by using ANALYZE command.
 - Error number: `MY-011010`; Symbol: `ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`
Message: Finished migrating INDEX statistics data.
 - Error number: `MY-011011`; Symbol: `ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR`; SQLSTATE: `HY000`
Message: Failed to find valid data directory.
 - Error number: `MY-011012`; Symbol: `ER_DD_UPGRADE_START`; SQLSTATE: `HY000`
Message: Starting upgrade of data directory.
 - Error number: `MY-011013`; Symbol: `ER_DD_UPGRADE_FAILED_INIT_DD_SE`; SQLSTATE: `HY000`
Message: Failed to initialize DD Storage Engine.
 - Error number: `MY-011014`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

- Error number: [MY-011015](#); Symbol: [ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE](#); SQLSTATE: [HY000](#)

Message: Found partially upgraded DD. Upgrade will continue and start the server.

- Error number: [MY-011016](#); Symbol: [ER_DD_UPGRADE_SE_LOGS_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in upgrading engine logs.

- Error number: [MY-011017](#); Symbol: [ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in updating SDI information.

- Error number: [MY-011018](#); Symbol: [ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE](#); SQLSTATE: [HY000](#)

Message: Skip updating %s metadata in InnoDB read-only mode.

- Error number: [MY-011019](#); Symbol: [ER_CREATED_SYSTEM_WITH_VERSION](#); SQLSTATE: [HY000](#)

Message: Created system views with I_S version %d.

- Error number: [MY-011020](#); Symbol: [ER_UNKNOWN_ERROR_DETECTED_IN_SE](#); SQLSTATE: [HY000](#)

Message: Unknown error detected %d in handler.

- Error number: [MY-011021](#); Symbol: [ER_READ_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in Log_event::read_log_event(): '%s', data_len: %lu, event_type: %d.

- Error number: [MY-011022](#); Symbol: [ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG](#); SQLSTATE: [HY000](#)

Message: The row data is greater than 4GB, which is too big to write to the binary log.

- Error number: [MY-011023](#); Symbol: [ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY](#); SQLSTATE: [HY000](#)

Message: Unable to construct DROP EVENT SQL query string.

- Error number: [MY-011024](#); Symbol: [ER_FAILED_TO_BINLOG_DROP_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to binlog drop event %s.%s.

- Error number: [MY-011025](#); Symbol: [ER_FAILED_TO_START_REPLICA_THREAD](#); SQLSTATE: [HY000](#)

Message: Failed to start replica threads for channel '%s'.

- Error number: [MY-011026](#); Symbol: [ER_RPL_IO_THREAD_KILLED](#); SQLSTATE: [HY000](#)

Message: %s%s.

- Error number: [MY-011027](#); Symbol: [ER_REPLICA_RECONNECT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed registering on source, reconnecting to try again, log '%s' at position %s. %s.

- Error number: [MY-011028](#); Symbol: [ER_REPLICA_KILLED_AFTER_RECONNECT](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread killed during or after reconnect.

- Error number: [MY-011029](#); Symbol: [ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.

- Error number: [MY-011030](#); Symbol: [ER_FAILED_TO_ADD_RPL_FILTER](#); SQLSTATE: [HY000](#)

Message: Failed to add a replication filter into filter map for channel '%s'.

- Error number: [MY-011031](#); Symbol: [ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for group replication channel '%s' which is disallowed. The filter(s) have been discarded.

- Error number: [MY-011032](#); Symbol: [ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

- Error number: [MY-011033](#); Symbol: [ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES](#); SQLSTATE: [HY000](#)

Message: An error occurred while building do_table and ignore_table rules to hashes for per-channel filter.

- Error number: [MY-011034](#); Symbol: [ER_CLONE_PLUGIN_NOT_LOADED_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone plugin cannot be loaded.

- Error number: [MY-011035](#); Symbol: [ER_CLONE_HANDLER_EXIST_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone Handler exists.

- Error number: [MY-011036](#); Symbol: [ER_CLONE_CREATE_HANDLER_FAIL_TRACE](#); SQLSTATE: [HY000](#)

Message: Could not create Clone Handler.

- Error number: [MY-011037](#); Symbol: [ER_CYCLE_TIMER_IS_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The CYCLE timer is not available. WAIT events in the performance_schema will not be timed.

- Error number: [MY-011038](#); Symbol: [ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The NANOSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance_schema will not be timed.

- Error number: [MY-011039](#); Symbol: [ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The MICROSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance_schema will not be timed.

- Error number: [MY-011040](#); Symbol: [ER_PFS_MALLOC_ARRAY_OVERFLOW](#); SQLSTATE: [HY000](#)

Message: Failed to allocate memory for %zu chunks each of size %zu for buffer '%s' due to overflow.

- Error number: [MY-011041](#); Symbol: [ER_PFS_MALLOC_ARRAY_OOM](#); SQLSTATE: [HY000](#)

Message: Failed to allocate %zu bytes for buffer '%s' due to out-of-memory.

- Error number: [MY-011042](#); Symbol: [ER_INNO_DB_FAILED_TO_FIND_IDX_WITH_KEY_NO](#); SQLSTATE: [HY000](#)

Message: InnoDB could not find index %s key no %u for table %s through its index translation table.

- Error number: [MY-011043](#); Symbol: [ER_INNO_DB_FAILED_TO_FIND_IDX](#); SQLSTATE: [HY000](#)

Message: Cannot find index %s in InnoDB index translation table.

- Error number: [MY-011044](#); Symbol: [ER_INNO_DB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE](#); SQLSTATE: [HY000](#)

Message: InnoDB could not find key no %u with name %s from dict cache for table %s.

- Error number: [MY-011045](#); Symbol: [ER_INNO_DB_ACTIVE_INDEX_CHANGE_FAILED](#); SQLSTATE: [HY000](#)

Message: InnoDB: change_active_index(%u) failed.

- Error number: [MY-011046](#); Symbol: [ER_INNO_DB_DIFF_IN_REF_LEN](#); SQLSTATE: [HY000](#)

Message: Stored ref len is %lu, but table ref len is %lu.

- Error number: [MY-011047](#); Symbol: [ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD](#); SQLSTATE: [HY000](#)

Message: MySQL is trying to create a column prefix index field, on an inappropriate data type. Table name %s, column name %s.

- Error number: [MY-011048](#); Symbol: [ER_INNO_DB_CANNOT_CREATE_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot create table %s.

- Error number: [MY-011049](#); Symbol: [ER_INNO_DB_INTERNAL_INDEX](#); SQLSTATE: [HY000](#)

Message: Found index %s in InnoDB index list but not its MySQL index number. It could be an InnoDB internal index.

- Error number: [MY-011050](#); Symbol: [ER_INNO_DB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL](#); SQLSTATE: [HY000](#)

Message: InnoDB: Table %s contains %lu indexes inside InnoDB, which is different from the number of indexes %u defined in MySQL.

- Error number: [MY-011051](#); Symbol: [ER_INNO_DB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL](#); SQLSTATE: [HY000](#)

Message: Table %s contains fewer indexes inside InnoDB than are defined in the MySQL. Have you mixed up with data dictionary from different installation?

- Error number: [MY-011052](#); Symbol: [ER_INNO_DB_IDX_COLUMN_CNT_DIFF](#); SQLSTATE: [HY000](#)

Message: Index %s of %s has %lu columns unique inside InnoDB, but MySQL is asking statistics for %lu columns. Have you mixed data dictionary from different installation?

- Error number: [MY-011053](#); Symbol: [ER_INNO_DB_USE_MONITOR_GROUP_NAME](#); SQLSTATE: [HY000](#)

Message: Monitor counter '%s' cannot be turned on/off individually. Please use its module name to turn on/off the counters in the module as a group.

- Error number: [MY-011054](#); Symbol: [ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED](#); SQLSTATE: [HY000](#)

Message: Default value is not defined for this set option. Please specify correct counter or module name.

- Error number: [MY-011055](#); Symbol: [ER_INNODB_MONITOR_IS_ENABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB: Monitor %s is already enabled.

- Error number: [MY-011056](#); Symbol: [ER_INNODB_INVALID_MONITOR_COUNTER_NAME](#); SQLSTATE: [HY000](#)

Message: Invalid monitor counter : %s.

- Error number: [MY-011057](#); Symbol: [ER_WIN_LOAD_LIBRARY_FAILED](#); SQLSTATE: [HY000](#)

Message: LoadLibrary("%s") failed: GetLastError returns %lu.

- Error number: [MY-011058](#); Symbol: [ER_PARTITION_HANDLER_ADMIN_MSG](#); SQLSTATE: [HY000](#)

Message: %s.

- Error number: [MY-011059](#); Symbol: [ER_RPL_AM_INIT_INFO_MSG](#); SQLSTATE: [HY000](#)

Message: %s.

- Error number: [MY-011060](#); Symbol: [ER_DD_UPGRADE_TABLE_INTACT_ERROR](#); SQLSTATE: [HY000](#)

Message: %s.

- Error number: [MY-011061](#); Symbol: [ER_SERVER_INIT_COMPILED_IN_COMMANDS](#); SQLSTATE: [HY000](#)

Message: %s.

- Error number: [MY-011062](#); Symbol: [ER_MYISAM_CHECK_METHOD_ERROR](#); SQLSTATE: [HY000](#)

Message: %s.

- Error number: [MY-011063](#); Symbol: [ER_MYISAM_CRASHED_ERROR](#); SQLSTATE: [HY000](#)

Message: %s.

- Error number: [MY-011064](#); Symbol: [ER_WAITPID_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to wait for process %lld.

- Error number: [MY-011065](#); Symbol: [ER_FAILED_TO_FIND_MYSQLD_STATUS](#); SQLSTATE: [HY000](#)

Message: Unable to determine if daemon is running: %s (rc=%d).

- Error number: [MY-011066](#); Symbol: [ER_INNODB_ERROR_LOGGER_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011067](#); Symbol: [ER_INNODB_ERROR_LOGGER_FATAL_MSG](#); SQLSTATE: [HY000](#)

Message: [FATAL] InnoDB: %s

-
- Error number: [MY-011068](#); Symbol: [ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: The syntax '%s' is deprecated and will be removed in a future release. Please use %s instead.
 - Error number: [MY-011069](#); Symbol: [ER_DEPRECATED_SYNTAX_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: The syntax '%s' is deprecated and will be removed in a future release.
 - Error number: [MY-011070](#); Symbol: [ER_DEPRECATED_MSG_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release.
 - Error number: [MY-011071](#); Symbol: [ER_LOG_PRINTF_MSG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011072](#); Symbol: [ER_BINLOG_LOGGING_NOT_POSSIBLE](#); SQLSTATE: [HY000](#)
Message: Binary logging not possible. Message: %s.
 - Error number: [MY-011073](#); Symbol: [ER_FAILED_TO_SET_PERSISTED_OPTIONS](#); SQLSTATE: [HY000](#)
Message: Failed to set persisted options.
 - Error number: [MY-011074](#); Symbol: [ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION](#); SQLSTATE: [HY000](#)
Message: Cannot acquire specified service implementation: '%s'.
 - Error number: [MY-011075](#); Symbol: [ER_RES_GRP_INVALID_VCPU_RANGE](#); SQLSTATE: [HY000](#)
Message: Invalid VCPU range %u-%u.
 - Error number: [MY-011076](#); Symbol: [ER_RES_GRP_INVALID_VCPU_ID](#); SQLSTATE: [HY000](#)
Message: Invalid cpu id %u.
 - Error number: [MY-011077](#); Symbol: [ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE](#); SQLSTATE: [HY000](#)
Message: Got error %d during FLUSH_LOGS.
 - Error number: [MY-011078](#); Symbol: [ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY](#); SQLSTATE: [HY000](#)
Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.
 - Error number: [MY-011080](#); Symbol: [ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: malformed or very old relay log which does not have FormatDescriptor.
 - Error number: [MY-011081](#); Symbol: [ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Upgrade of view '%s.%s' failed. Re-create the view with the explicit column name lesser than 64 characters.
 - Error number: [MY-011082](#); Symbol: [ER_TABLE_NEEDS_DUMP_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Table upgrade required for '%s'. '%s'. Please dump/reload table to fix it!

- Error number: [MY-011083](#); Symbol: [ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in updating version number in %s tablespace.

- Error number: [MY-011084](#); Symbol: [ER_KEYRING_MIGRATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Keyring migration failed.

- Error number: [MY-011085](#); Symbol: [ER_KEYRING_MIGRATION_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: Keyring migration successful.

- Error number: [MY-011086](#); Symbol: [ER_RESTART_RECEIVED_INFO](#); SQLSTATE: [HY000](#)

Message: Received RESTART from user %s. Restarting mysqld (Version: %s).

- Error number: [MY-011087](#); Symbol: [ER_LCTN_CHANGED](#); SQLSTATE: [HY000](#)

Message: Different lower_case_table_names settings for server ('%u') and data dictionary ('%u').

- Error number: [MY-011088](#); Symbol: [ER_DD_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Data dictionary initializing version '%u'.

- Error number: [MY-011089](#); Symbol: [ER_DD_RESTART](#); SQLSTATE: [HY000](#)

Message: Data dictionary restarting version '%u'.

- Error number: [MY-011090](#); Symbol: [ER_DD_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Data dictionary upgrading from version '%u' to '%u'.

- Error number: [MY-011091](#); Symbol: [ER_DD_UPGRADE_OFF](#); SQLSTATE: [HY000](#)

Message: Data dictionary upgrade prohibited by the command line option '--no_dd_upgrade'.

- Error number: [MY-011092](#); Symbol: [ER_DD_UPGRADE_VERSION_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Upgrading the data dictionary from dictionary version '%u' is not supported.

- Error number: [MY-011093](#); Symbol: [ER_DD_UPGRADE_SCHEMA_UNAVAILABLE](#); SQLSTATE: [HY000](#)

Message: Upgrading the data dictionary failed, temporary schema name '%s' not available.

- Error number: [MY-011094](#); Symbol: [ER_DD_MINOR_DOWNGRADE](#); SQLSTATE: [HY000](#)

Message: Data dictionary minor downgrade from version '%u' to '%u'.

- Error number: [MY-011095](#); Symbol: [ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Minor downgrade of the Data dictionary from dictionary version '%u' is not supported.

- Error number: [MY-011096](#); Symbol: [ER_DD_NO_VERSION_FOUND](#); SQLSTATE: [HY000](#)

Message: No data dictionary version number found.

- Error number: [MY-011104](#); Symbol: [ER_THREAD_POOL_CON_HANDLER_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to instantiate the connection handler object.

- Error number: [MY-011105](#); Symbol: [ER_THREAD_POOL_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize thread pool plugin.

- Error number: [MY-011107](#); Symbol: [ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA](#); SQLSTATE: [HY000](#)

Message: Can't setup connection teardown thread-specific data.

- Error number: [MY-011108](#); Symbol: [ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD](#); SQLSTATE: [HY000](#)

Message: Creation of connect handler thread failed.

- Error number: [MY-011109](#); Symbol: [ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN](#); SQLSTATE: [HY000](#)

Message: Failed to create thd and authenticate connection.

- Error number: [MY-011110](#); Symbol: [ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT](#); SQLSTATE: [HY000](#)

Message: Failed to process connection event.

- Error number: [MY-011111](#); Symbol: [ER_THREAD_POOL_FAILED_TO_CREATE_POOL](#); SQLSTATE: [HY000](#)

Message: Can't create pool thread (error %d, errno: %d).

- Error number: [MY-011113](#); Symbol: [ER_THREAD_POOL_LOW_LEVEL_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: tp_group_low_level_init() failed.

- Error number: [MY-011114](#); Symbol: [ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED](#); SQLSTATE: [HY000](#)

Message: Rearm failed even after 30 seconds, can't continue without notify socket.

- Error number: [MY-011115](#); Symbol: [ER_THREAD_POOL_BUFFER_TOO_SMALL](#); SQLSTATE: [HY000](#)

Message: %s: %s buffer is too small

- Error number: [MY-011116](#); Symbol: [ER_MECAB_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Mecab v%s is not supported, the lowest version supported is v%s.

- Error number: [MY-011117](#); Symbol: [ER_MECAB_NOT_VERIFIED](#); SQLSTATE: [HY000](#)

Message: Mecab v%s is not verified, the highest version supported is v%s.

- Error number: [MY-011118](#); Symbol: [ER_MECAB_CREATING_MODEL](#); SQLSTATE: [HY000](#)

Message: Mecab: Trying createModel(%s).

- Error number: [MY-011119](#); Symbol: [ER_MECAB_FAILED_TO_CREATE_MODEL](#); SQLSTATE: [HY000](#)

Message: Mecab: createModel() failed: %s.

- Error number: [MY-011120](#); Symbol: [ER_MECAB_FAILED_TO_CREATE_TRIGGER](#); SQLSTATE: [HY000](#)

Message: Mecab: createTagger() failed: %s.

- Error number: [MY-011121](#); Symbol: [ER_MECAB_UNSUPPORTED_CHARSET](#); SQLSTATE: [HY000](#)

Message: Mecab: Unsupported dictionary charset %s.

- Error number: [MY-011122](#); Symbol: [ER_MECAB_CHARSET_LOADED](#); SQLSTATE: [HY000](#)

Message: Mecab: Loaded dictionary charset is %s.

- Error number: [MY-011123](#); Symbol: [ER_MECAB_PARSE_FAILED](#); SQLSTATE: [HY000](#)

Message: Mecab: parse() failed: %s.

- Error number: [MY-011124](#); Symbol: [ER_MECAB_OOM_WHILE_PARSING_TEXT](#); SQLSTATE: [HY000](#)

Message: Mecab: parse() failed: out of memory.

- Error number: [MY-011125](#); Symbol: [ER_MECAB_CREATE_LATTICE_FAILED](#); SQLSTATE: [HY000](#)

Message: Mecab: createLattice() failed: %s.

- Error number: [MY-011126](#); Symbol: [ER_SEMISYNC_TRACE_ENTER_FUNC](#); SQLSTATE: [HY000](#)

Message: ---> %s enter.

- Error number: [MY-011127](#); Symbol: [ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE](#); SQLSTATE: [HY000](#)

Message: <--- %s exit (%d).

- Error number: [MY-011128](#); Symbol: [ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE](#); SQLSTATE: [HY000](#)

Message: <--- %s exit (%s).

- Error number: [MY-011129](#); Symbol: [ER_SEMISYNC_TRACE_EXIT](#); SQLSTATE: [HY000](#)

Message: <--- %s exit.

- Error number: [MY-011130](#); Symbol: [ER_SEMISYNC_RPL_INIT_FOR_TRX](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication initialized for transactions.

- Error number: [MY-011131](#); Symbol: [ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE](#); SQLSTATE: [HY000](#)

Message: %s: transaction node allocation failed for: (%s, %lu).

- Error number: [MY-011132](#); Symbol: [ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER](#); SQLSTATE: [HY000](#)

Message: %s: binlog write out-of-order, tail (%s, %lu), new node (%s, %lu).

- Error number: [MY-011133](#); Symbol: [ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY](#); SQLSTATE: [HY000](#)

Message: %s: insert (%s, %lu) in entry(%u).

- Error number: [MY-011134](#); Symbol: [ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY](#); SQLSTATE: [HY000](#)

Message: %s: probe (%s, %lu) in entry(%u).

-
- Error number: [MY-011135](#); Symbol: [ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES](#); SQLSTATE: [HY000](#)
Message: %s: cleared all nodes.
 - Error number: [MY-011136](#); Symbol: [ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS](#); SQLSTATE: [HY000](#)
Message: %s: cleared %d nodes back until pos (%s, %lu).
 - Error number: [MY-011137](#); Symbol: [ER_SEMISYNC_REPLY_MAGIC_NO_ERROR](#); SQLSTATE: [HY000](#)
Message: Read semi-sync reply magic number error.
 - Error number: [MY-011138](#); Symbol: [ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL](#); SQLSTATE: [HY000](#)
Message: Read semi-sync reply length error: packet is too small.
 - Error number: [MY-011139](#); Symbol: [ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE](#); SQLSTATE: [HY000](#)
Message: Read semi-sync reply binlog file length too large.
 - Error number: [MY-011140](#); Symbol: [ER_SEMISYNC_SERVER_REPLY](#); SQLSTATE: [HY000](#)
Message: %s: Got reply(%s, %lu) from server %u.
 - Error number: [MY-011141](#); Symbol: [ER_SEMISYNC_FUNCTION_CALLED_TWICE](#); SQLSTATE: [HY000](#)
Message: %s called twice.
 - Error number: [MY-011142](#); Symbol: [ER_SEMISYNC_RPL_ENABLED_ON_SOURCE](#); SQLSTATE: [HY000](#)
Message: Semi-sync replication enabled on the source.
 - Error number: [MY-011143](#); Symbol: [ER_SEMISYNC_SOURCE_OOM](#); SQLSTATE: [HY000](#)
Message: Cannot allocate memory to enable semi-sync on the source.
 - Error number: [MY-011144](#); Symbol: [ER_SEMISYNC_DISABLED_ON_SOURCE](#); SQLSTATE: [HY000](#)
Message: Semi-sync replication disabled on the source.
 - Error number: [MY-011145](#); Symbol: [ER_SEMISYNC_FORCED_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: SEMISYNC: Forced shutdown. Some updates might not be replicated.
 - Error number: [MY-011146](#); Symbol: [ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS](#); SQLSTATE: [HY000](#)
Message: %s: Got reply at (%s, %lu).
 - Error number: [MY-011147](#); Symbol: [ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS](#); SQLSTATE: [HY000](#)
Message: %s: signal all waiting threads.
 - Error number: [MY-011148](#); Symbol: [ER_SEMISYNC_SOURCE_TRX_WAIT_POS](#); SQLSTATE: [HY000](#)
Message: %s: wait pos (%s, %lu), repl(%d).

-
- Error number: [MY-011149](#); Symbol: [ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD](#); SQLSTATE: [HY000](#)
Message: %s: Binlog reply is ahead (%s, %lu).
 - Error number: [MY-011150](#); Symbol: [ER_SEMISYNC_MOVE_BACK_WAIT_POS](#); SQLSTATE: [HY000](#)
Message: %s: move back wait position (%s, %lu).
 - Error number: [MY-011151](#); Symbol: [ER_SEMISYNC_INIT_WAIT_POS](#); SQLSTATE: [HY000](#)
Message: %s: init wait position (%s, %lu).
 - Error number: [MY-011152](#); Symbol: [ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT](#); SQLSTATE: [HY000](#)
Message: %s: wait %lu ms for binlog sent (%s, %lu).
 - Error number: [MY-011153](#); Symbol: [ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT](#); SQLSTATE: [HY000](#)
Message: Timeout waiting for reply of binlog (file: %s, pos: %lu), semi-sync up to file %s, position %lu.
 - Error number: [MY-011154](#); Symbol: [ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED](#); SQLSTATE: [HY000](#)
Message: Assessment of waiting time for commitTrx failed at wait position (%s, %lu).
 - Error number: [MY-011155](#); Symbol: [ER_SEMISYNC_RPL_SWITCHED_OFF](#); SQLSTATE: [HY000](#)
Message: Semi-sync replication switched OFF.
 - Error number: [MY-011156](#); Symbol: [ER_SEMISYNC_RPL_SWITCHED_ON](#); SQLSTATE: [HY000](#)
Message: Semi-sync replication switched ON at (%s, %lu).
 - Error number: [MY-011157](#); Symbol: [ER_SEMISYNC_NO_SPACE_IN_THE_PKT](#); SQLSTATE: [HY000](#)
Message: No enough space in the packet for semi-sync extra header, semi-sync replication disabled.
 - Error number: [MY-011158](#); Symbol: [ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO](#); SQLSTATE: [HY000](#)
Message: %s: server(%d), (%s, %lu) sync(%d), repl(%d).
 - Error number: [MY-011159](#); Symbol: [ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE](#); SQLSTATE: [HY000](#)
Message: Semi-sync failed to insert tranx_node for binlog file: %s, position: %lu.
 - Error number: [MY-011160](#); Symbol: [ER_SEMISYNC_TRX_SKIPPED_AT_POS](#); SQLSTATE: [HY000](#)
Message: %s: Transaction skipped at (%s, %lu).
 - Error number: [MY-011161](#); Symbol: [ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH](#); SQLSTATE: [HY000](#)
Message: Semi-sync source failed on net_flush() before waiting for replica reply.
 - Error number: [MY-011162](#); Symbol: [ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER](#); SQLSTATE: [HY000](#)
Message: The received ack is smaller than m_greatest_ack.

-
- Error number: [MY-011163](#); Symbol: [ER_SEMISYNC_ADD_ACK_TO_SLOT](#); SQLSTATE: [HY000](#)
Message: Add the ack into slot %u.
 - Error number: [MY-011164](#); Symbol: [ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK](#); SQLSTATE: [HY000](#)
Message: Update an existing ack in slot %u.
 - Error number: [MY-011165](#); Symbol: [ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD](#); SQLSTATE: [HY000](#)
Message: Failed to start semi-sync ACK receiver thread, could not create thread(errno:%d).
 - Error number: [MY-011166](#); Symbol: [ER_SEMISYNC_STARTING_ACK_RECEIVER_THD](#); SQLSTATE: [HY000](#)
Message: Starting ack receiver thread.
 - Error number: [MY-011167](#); Symbol: [ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET](#); SQLSTATE: [HY000](#)
Message: Failed to wait on semi-sync dump sockets, error: errno=%d.
 - Error number: [MY-011168](#); Symbol: [ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD](#); SQLSTATE: [HY000](#)
Message: Stopping ack receiver thread.
 - Error number: [MY-011169](#); Symbol: [ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER](#); SQLSTATE: [HY000](#)
Message: Failed to register replica to semi-sync ACK receiver thread.
 - Error number: [MY-011170](#); Symbol: [ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA](#); SQLSTATE: [HY000](#)
Message: Start %s binlog_dump to replica (server_id: %d), pos(%s, %lu).
 - Error number: [MY-011171](#); Symbol: [ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA](#); SQLSTATE: [HY000](#)
Message: Stop %s binlog_dump to replica (server_id: %d).
 - Error number: [MY-011172](#); Symbol: [ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)
Message: unregister_trans_observer failed.
 - Error number: [MY-011173](#); Symbol: [ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)
Message: unregister_binlog_storage_observer failed.
 - Error number: [MY-011174](#); Symbol: [ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)
Message: unregister_binlog_transmit_observer failed.
 - Error number: [MY-011175](#); Symbol: [ER_SEMISYNC_UNREGISTERED_REPLICATOR](#); SQLSTATE: [HY000](#)
Message: unregister_replicator OK.

-
- Error number: [MY-011176](#); Symbol: [ER_SEMISYNC_SOCKET_FD_TOO_LARGE](#); SQLSTATE: [HY000](#)
Message: Semisync replica socket fd is %u. select() cannot handle if the socket fd is bigger than %u (FD_SETSIZE).
 - Error number: [MY-011177](#); Symbol: [ER_SEMISYNC_REPLICA_REPLY](#); SQLSTATE: [HY000](#)
Message: %s: reply - %d.
 - Error number: [MY-011178](#); Symbol: [ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT](#); SQLSTATE: [HY000](#)
Message: Missing magic number for semi-sync packet, packet len: %lu.
 - Error number: [MY-011179](#); Symbol: [ER_SEMISYNC_REPLICA_START](#); SQLSTATE: [HY000](#)
Message: Replica I/O thread: Start %s replication to source '%s@%s:%d' in log '%s' at position %lu.
 - Error number: [MY-011180](#); Symbol: [ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO](#); SQLSTATE: [HY000](#)
Message: %s: reply (%s, %lu).
 - Error number: [MY-011181](#); Symbol: [ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED](#); SQLSTATE: [HY000](#)
Message: Semi-sync replica net_flush() reply failed.
 - Error number: [MY-011182](#); Symbol: [ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED](#); SQLSTATE: [HY000](#)
Message: Semi-sync replica send reply failed: %s (%d).
 - Error number: [MY-011183](#); Symbol: [ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE](#); SQLSTATE: [HY000](#)
Message: Execution failed on source: %s; error %d
 - Error number: [MY-011184](#); Symbol: [ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE](#); SQLSTATE: [HY000](#)
Message: Source server does not support semi-sync, fallback to asynchronous replication
 - Error number: [MY-011185](#); Symbol: [ER_SEMISYNC_REPLICA_SET_FAILED](#); SQLSTATE: [HY000](#)
Message: Set 'rpl_semi_sync_replica=1' on source failed
 - Error number: [MY-011186](#); Symbol: [ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD](#); SQLSTATE: [HY000](#)
Message: Failed to stop ack receiver thread on my_thread_join, errno(%d).
 - Error number: [MY-011187](#); Symbol: [ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES](#); SQLSTATE: [HY000](#)
Message: Failed to read the firewall tables
 - Error number: [MY-011188](#); Symbol: [ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES](#); SQLSTATE: [HY000](#)
Message: Failed to register dynamic privileges
 - Error number: [MY-011189](#); Symbol: [ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Statement was truncated and not recorded: %s

- Error number: [MY-011190](#); Symbol: [ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT](#); SQLSTATE: [HY000](#)

Message: Statement with no text was not recorded

- Error number: [MY-011191](#); Symbol: [ER_FIREWALL_SUSPICIOUS_STMT](#); SQLSTATE: [HY000](#)

Message: SUSPICIOUS STATEMENT from '%s'. Reason: %s Statement: %s

- Error number: [MY-011192](#); Symbol: [ER_FIREWALL_ACCESS_DENIED](#); SQLSTATE: [HY000](#)

Message: ACCESS DENIED for '%s'. Reason: %s Statement: %s

- Error number: [MY-011193](#); Symbol: [ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE](#); SQLSTATE: [HY000](#)

Message: Skipped unknown user mode '%s'

- Error number: [MY-011194](#); Symbol: [ER_FIREWALL_RELOADING_CACHE](#); SQLSTATE: [HY000](#)

Message: Reloading cache from disk

- Error number: [MY-011195](#); Symbol: [ER_FIREWALL_RESET_FOR_USER](#); SQLSTATE: [HY000](#)

Message: FIREWALL RESET for '%s'

- Error number: [MY-011196](#); Symbol: [ER_FIREWALL_STATUS_FLUSHED](#); SQLSTATE: [HY000](#)

Message: Counters are reset to zero

- Error number: [MY-011197](#); Symbol: [ER_KEYRING_LOGGER_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011198](#); Symbol: [ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED](#); SQLSTATE: [HY000](#)

Message: Audit Log plugin supports filtering mode, which has not been installed yet. Audit Log plugin will run in the legacy mode, which will be removed in the next release.

- Error number: [MY-011199](#); Symbol: [ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST](#); SQLSTATE: [HY000](#)

Message: Previously exclude list is used, now we start using include list, exclude list is set to NULL.

- Error number: [MY-011200](#); Symbol: [ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES](#); SQLSTATE: [HY000](#)

Message: Cannot set audit_log_policy simultaneously with either audit_log_connection_policy or audit_log_statement_policy, setting audit_log_connection_policy and audit_log_statement_policy based on audit_log_policy.

- Error number: [MY-011201](#); Symbol: [ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED](#); SQLSTATE: [HY000](#)

Message: Both include and exclude lists provided, include list is preferred, exclude list is set to NULL.

- Error number: [MY-011202](#); Symbol: [ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR](#); SQLSTATE: [HY000](#)

Message: Could not access '%s' directory.

- Error number: [MY-011203](#); Symbol: [ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not rename file from '%s' to '%s'.

- Error number: [MY-011204](#); Symbol: [ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: File '%s' should not exist. It may be incomplete. The server crashed.

- Error number: [MY-011205](#); Symbol: [ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY](#); SQLSTATE: [HY000](#)

Message: Could not rename file from '%s' to '%s'. Remove the file manually.

- Error number: [MY-011206](#); Symbol: [ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED](#); SQLSTATE: [HY000](#)

Message: Incomplete file renamed from '%s' to '%s'.

- Error number: [MY-011207](#); Symbol: [ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s).

- Error number: [MY-011208](#); Symbol: [ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Could not initialize audit log file encryption.

- Error number: [MY-011209](#); Symbol: [ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION](#); SQLSTATE: [HY000](#)

Message: Could not initialize audit log file compression.

- Error number: [MY-011210](#); Symbol: [ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE](#); SQLSTATE: [HY000](#)

Message: Could not create '%s' file for audit logging.

- Error number: [MY-011211](#); Symbol: [ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH](#); SQLSTATE: [HY000](#)

Message: Audit log file (%s) must be manually renamed before audit_log_flush is set to true.

- Error number: [MY-011212](#); Symbol: [ER_AUDIT_LOG_FILTER_RESULT_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011213](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE](#); SQLSTATE: [HY000](#)

Message: Error parsing JSON event. Event not accessible.

- Error number: [MY-011214](#); Symbol: [ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL](#); SQLSTATE: [HY000](#)

Message: Buffer is too small to hold JSON event. Number of events skipped: %zu.

-
- Error number: [MY-011215](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE](#); SQLSTATE: [HY000](#)
Message: Could not open JSON file for reading. Reading next file if exists.
 - Error number: [MY-011216](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR](#); SQLSTATE: [HY000](#)
Message: JSON file parsing error. Reading next file if exists
 - Error number: [MY-011219](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS](#); SQLSTATE: [HY000](#)
Message: Could not store field of the %s table.
 - Error number: [MY-011220](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not update %s table.
 - Error number: [MY-011221](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not insert into %s table.
 - Error number: [MY-011222](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not delete from %s table.
 - Error number: [MY-011223](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ](#); SQLSTATE: [HY000](#)
Message: Could not initialize %s table for reading.
 - Error number: [MY-011224](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not read %s table.
 - Error number: [MY-011225](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING](#); SQLSTATE: [HY000](#)
Message: Could not close %s table reading.
 - Error number: [MY-011226](#); Symbol: [ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY](#); SQLSTATE: [HY000](#)
Message: Both user and host columns of %s table cannot be empty.
 - Error number: [MY-011227](#); Symbol: [ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY](#); SQLSTATE: [HY000](#)
Message: Filtername column of %s table cannot be empty.
 - Error number: [MY-011228](#); Symbol: [ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED](#); SQLSTATE: [HY000](#)
Message: Dictionary file not specified
 - Error number: [MY-011229](#); Symbol: [ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED](#); SQLSTATE: [HY000](#)
Message: Dictionary file not loaded

-
- Error number: [MY-011230](#); Symbol: [ER_VALIDATE_PWD_DICT_FILE_TOO_BIG](#); SQLSTATE: [HY000](#)
Message: Dictionary file size exceeded MAX_DICTIONARY_FILE_LENGTH, not loaded
 - Error number: [MY-011231](#); Symbol: [ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE](#); SQLSTATE: [HY000](#)
Message: Exception while reading the dictionary file
 - Error number: [MY-011232](#); Symbol: [ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX](#); SQLSTATE: [HY000](#)
Message: Can't retrieve the %s from the security context
 - Error number: [MY-011233](#); Symbol: [ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX](#); SQLSTATE: [HY000](#)
Message: Can't retrieve the security context
 - Error number: [MY-011234](#); Symbol: [ER_VALIDATE_PWD_LENGTH_CHANGED](#); SQLSTATE: [HY000](#)
Message: Effective value of validate_password_length is changed. New value is %d
 - Error number: [MY-011235](#); Symbol: [ER_REWRITER_QUERY_ERROR_MSG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011236](#); Symbol: [ER_REWRITER_QUERY_FAILED](#); SQLSTATE: [HY000](#)
Message: Rewritten query failed to parse:%s
 - Error number: [MY-011237](#); Symbol: [ER_XPLUGIN_STARTUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Startup failed with error "%s"
 - Error number: [MY-011240](#); Symbol: [ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER](#); SQLSTATE: [HY000](#)
Message: Using SSL configuration from MySQL Server
 - Error number: [MY-011241](#); Symbol: [ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX](#); SQLSTATE: [HY000](#)
Message: Using SSL configuration from Mysqlx Plugin
 - Error number: [MY-011242](#); Symbol: [ER_XPLUGIN_FAILED_TO_USE_SSL_CONF](#); SQLSTATE: [HY000](#)
Message: Neither MySQL Server nor Mysqlx Plugin has valid SSL configuration
 - Error number: [MY-011243](#); Symbol: [ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Using %s for TLS connections
 - Error number: [MY-011244](#); Symbol: [ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN](#); SQLSTATE: [HY000](#)
Message: For more information, please see the Using Secure Connections with X Plugin section in the MySQL documentation
 - Error number: [MY-011245](#); Symbol: [ER_XPLUGIN_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011246](#); Symbol: [ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING](#); SQLSTATE: [HY000](#)

Message: Failed to parse stored authentication string for %s. Please check if mysql.user table not corrupted

- Error number: [MY-011247](#); Symbol: [ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH](#); SQLSTATE: [HY000](#)

Message: Error in generating multi-round hash for %s. Plugin can not perform authentication without it. This may be a transient problem

- Error number: [MY-011248](#); Symbol: [ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL](#); SQLSTATE: [HY000](#)

Message: Authentication requires either RSA keys or SSL encryption

- Error number: [MY-011249](#); Symbol: [ER_SHA_PWD_RSA_KEY_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: RSA key cipher length of %u is too long. Max value is %u

- Error number: [MY-011250](#); Symbol: [ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables

- Error number: [MY-011251](#); Symbol: [ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table

- Error number: [MY-011252](#); Symbol: [ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011253](#); Symbol: [ER_CONN_CONTROL_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011254](#); Symbol: [ER_GRP_RPL_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011255](#); Symbol: [ER_SHA_PWD_SALT_FOR_USER_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Password salt for user '%s' is corrupt

- Error number: [MY-011256](#); Symbol: [ER_SYS_VAR_COMPONENT_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory for component system variable '%s'.

- Error number: [MY-011257](#); Symbol: [ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: variable %s of component %s was forced to be read-only: string variable without update_func and PLUGIN_VAR_MEMALLOC flag.

- Error number: [MY-011258](#); Symbol: [ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE](#); SQLSTATE: [HY000](#)

Message: Unknown variable type code 0x%x in component '%s'.

- Error number: [MY-011259](#); Symbol: [ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Parsing options for variable '%s' failed.

- Error number: [MY-011260](#); Symbol: [ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT](#); SQLSTATE: [HY000](#)

Message: Setting persistent options for component variable '%s' failed.

- Error number: [MY-011261](#); Symbol: [ER_COMPONENT_FILTER_CONFUSED](#); SQLSTATE: [HY000](#)

Message: The log-filter component "%s" got confused at "%s" (state: %s) ...

- Error number: [MY-011262](#); Symbol: [ER_STOP_REPLICA_IO_THREAD_DISK_SPACE](#); SQLSTATE: [HY000](#)

Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.

- Error number: [MY-011263](#); Symbol: [ER_LOG_FILE_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: Could not use %s for logging (error %d - %s). Turning logging off for the server process. To turn it on again: fix the cause, then %s restart the MySQL server.

- Error number: [MY-011268](#); Symbol: [ER_PERSIST_OPTION_STATUS](#); SQLSTATE: [HY000](#)

Message: Configuring persisted options failed: "%s".

- Error number: [MY-011269](#); Symbol: [ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS](#); SQLSTATE: [HY000](#)

Message: The storage engine '%s' does not provide dynamic table statistics

- Error number: [MY-011272](#); Symbol: [ER_SSL_FIPS_MODE_ERROR](#); SQLSTATE: [HY000](#)

Message: SSL fips mode error: %s

- Error number: [MY-011273](#); Symbol: [ER_CONN_INIT_CONNECT_IGNORED](#); SQLSTATE: [HY000](#)

Message: init_connect variable is ignored for user: %s host: %s due to expired password.

- Error number: [MY-011275](#); Symbol: [ER_REWRITER_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory.

- Error number: [MY-011276](#); Symbol: [ER_REWRITER_TABLE_MALFORMED_ERROR](#); SQLSTATE: [HY000](#)

Message: Wrong column count or names when loading rules.

- Error number: [MY-011277](#); Symbol: [ER_REWRITER_LOAD_FAILED](#); SQLSTATE: [HY000](#)

Message: Some rules failed to load.

- Error number: [MY-011278](#); Symbol: [ER_REWRITER_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Got error from storage engine while refreshing rewrite rules.

- Error number: [MY-011279](#); Symbol: [ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize Connection_event_coordinator

- Error number: MY-011280; Symbol: ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED; SQLSTATE: HY000

Message: Failed to update connection delay triggered stats

- Error number: MY-011281; Symbol: ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED; SQLSTATE: HY000

Message: Failed to reset connection delay triggered stats

- Error number: MY-011282; Symbol: ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE; SQLSTATE: HY000

Message: Unexpected option type for connection delay.

- Error number: MY-011283; Symbol: ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED; SQLSTATE: HY000

Message: Failed to initialize Connection_delay_action

- Error number: MY-011284; Symbol: ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY; SQLSTATE: HY000

Message: Could not set %s delay for connection delay.

- Error number: MY-011285; Symbol: ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH; SQLSTATE: HY000

Message: Failed to update connection delay hash for account : %s

- Error number: MY-011286; Symbol: ER_XPLUGIN_FORCE_STOP_CLIENT; SQLSTATE: HY000

Message: %s: Force stopping client because exception occurred: %s

- Error number: MY-011287; Symbol: ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED; SQLSTATE: HY000

Message: %s.%u: Maximum number of authentication attempts reached, login failed.

- Error number: MY-011288; Symbol: ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED; SQLSTATE: HY000

Message: Error allocating Buffer_page: %s

- Error number: MY-011289; Symbol: ER_XPLUGIN_DETECTED_HANGING_CLIENTS; SQLSTATE: HY000

Message: Detected %u hanging client(s)

- Error number: MY-011290; Symbol: ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT; SQLSTATE: HY000

Message: Error accepting client

- Error number: MY-011291; Symbol: ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT; SQLSTATE: HY000

Message: Internal error scheduling client for execution

- Error number: MY-011292; Symbol: ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES; SQLSTATE: HY000

Message: Preparation of I/O interfaces failed, X Protocol won't be accessible

- Error number: [MY-011293](#); Symbol: [ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED](#); SQLSTATE: [HY000](#)

Message: `srv_session_init_thread` returned error

- Error number: [MY-011294](#); Symbol: [ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT](#); SQLSTATE: [HY000](#)

Message: Unable to use user `mysql.session` account when connecting the server for internal plugin requests.

- Error number: [MY-011295](#); Symbol: [ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTION](#); SQLSTATE: [HY000](#)

Message: For more information, please see the X Plugin User Account section in the MySQL documentation

- Error number: [MY-011296](#); Symbol: [ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD](#); SQLSTATE: [HY000](#)

Message: `%s`: Unexpected exception dispatching command: `%s`

- Error number: [MY-011297](#); Symbol: [ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER](#); SQLSTATE: [HY000](#)

Message: Exception in post: `%s`

- Error number: [MY-011298](#); Symbol: [ER_XPLUGIN_TASK_SCHEDULING_FAILED](#); SQLSTATE: [HY000](#)

Message: Internal error scheduling task

- Error number: [MY-011299](#); Symbol: [ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP](#); SQLSTATE: [HY000](#)

Message: Exception in event loop: "`%s`": `%s`

- Error number: [MY-011300](#); Symbol: [ER_XPLUGIN_LISTENER_SETUP_FAILED](#); SQLSTATE: [HY000](#)

Message: Setup of `%s` failed, `%s`

- Error number: [MY-011301](#); Symbol: [ER_XPLUING_NET_STARTUP_FAILED](#); SQLSTATE: [HY000](#)

Message: `%s`

- Error number: [MY-011302](#); Symbol: [ER_XPLUGIN_FAILED_AT_SSL_CONF](#); SQLSTATE: [HY000](#)

Message: Failed at SSL configuration: "`%s`"

- Error number: [MY-011305](#); Symbol: [ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN](#); SQLSTATE: [HY000](#)

Message: `%s`: Error creating session for connection from `%s`

- Error number: [MY-011306](#); Symbol: [ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION](#); SQLSTATE: [HY000](#)

Message: `%s`: Error initializing session for connection: `%s`

- Error number: [MY-011307](#); Symbol: [ER_XPLUGIN_MESSAGE_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: %s: Message of size %u received, exceeding the limit of %i

- Error number: [MY-011308](#); Symbol: [ER_XPLUGIN_UNINITIALIZED_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Message is not properly initialized: %s

- Error number: [MY-011309](#); Symbol: [ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS](#); SQLSTATE: [HY000](#)

Message: Unable to set minimal number of workers to %u; actual value is %i

- Error number: [MY-011310](#); Symbol: [ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Unable to accept connection, disconnecting client

- Error number: [MY-011311](#); Symbol: [ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED](#); SQLSTATE: [HY000](#)

Message: All I/O interfaces are disabled, X Protocol won't be accessible

- Error number: [MY-011314](#); Symbol: [ER_XPLUGIN_ERROR_READING_SOCKET](#); SQLSTATE: [HY000](#)

Message: %s: Error reading from socket %s (%i)

- Error number: [MY-011315](#); Symbol: [ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY](#); SQLSTATE: [HY000](#)

Message: %s: peer disconnected while reading message body

- Error number: [MY-011316](#); Symbol: [ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION](#); SQLSTATE: [HY000](#)

Message: client_id:%s - %s while reading from socket, closing connection

- Error number: [MY-011322](#); Symbol: [ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR](#); SQLSTATE: [HY000](#)

Message: Please see the MySQL documentation for '%s' system variables to fix the error

- Error number: [MY-011323](#); Symbol: [ER_XPLUGIN_LISTENER_STATUS_MSG](#); SQLSTATE: [HY000](#)

Message: X Plugin ready for connections. %s

- Error number: [MY-011324](#); Symbol: [ER_XPLUGIN_RETRYING_BIND_ON_PORT](#); SQLSTATE: [HY000](#)

Message: Retrying `bind()` on TCP/IP port %i

- Error number: [MY-011327](#); Symbol: [ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS](#); SQLSTATE: [HY000](#)

Message: Using existing %s account for authentication. Incomplete grants will be fixed

- Error number: [MY-011332](#); Symbol: [ER_XPLUGIN_IPv6_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: IPv6 is available

- Error number: [MY-011334](#); Symbol: [ER_XPLUGIN_CLIENT_KILL_MSG](#); SQLSTATE: [HY000](#)

Message: Kill client: %i %s

-
- Error number: [MY-011335](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX](#); SQLSTATE: [HY000](#)
Message: Could not get security context for session
 - Error number: [MY-011337](#); Symbol: [ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION](#); SQLSTATE: [HY000](#)
Message: Error closing SQL session
 - Error number: [MY-011338](#); Symbol: [ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD](#); SQLSTATE: [HY000](#)
Message: Error executing admin command %s: %s
 - Error number: [MY-011339](#); Symbol: [ER_XPLUGIN_EMPTY_ADMIN_CMD](#); SQLSTATE: [HY000](#)
Message: Error executing empty admin command
 - Error number: [MY-011340](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_SYS_VAR](#); SQLSTATE: [HY000](#)
Message: Unable to retrieve system variable '%s'
 - Error number: [MY-011341](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT](#); SQLSTATE: [HY000](#)
Message: Unable to get creation stmt for collection '%s'; query result size: %lu
 - Error number: [MY-011342](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO](#); SQLSTATE: [HY000](#)
Message: Unable to get engine info for collection '%s'; creation stmt: %s
 - Error number: [MY-011345](#); Symbol: [ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG](#); SQLSTATE: [HY000](#)
Message: Failed to set SO_REUSEADDR flag (error: %d).
 - Error number: [MY-011346](#); Symbol: [ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION](#); SQLSTATE: [HY000](#)
Message: Could not open internal MySQL session
 - Error number: [MY-011347](#); Symbol: [ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT](#); SQLSTATE: [HY000](#)
Message: Unable to switch context to user %s
 - Error number: [MY-011348](#); Symbol: [ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF](#); SQLSTATE: [HY000](#)
Message: Can't unregister '%s' user defined function
 - Error number: [MY-011351](#); Symbol: [ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG](#); SQLSTATE: [HY000](#)
Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.
 - Error number: [MY-011352](#); Symbol: [ER_KEYRING_INVALID_KEY_TYPE](#); SQLSTATE: [HY000](#)
Message: Invalid key type

-
- Error number: [MY-011353](#); Symbol: [ER_KEYRING_INVALID_KEY_LENGTH](#); SQLSTATE: [HY000](#)
Message: Invalid key length for given block cipher
 - Error number: [MY-011358](#); Symbol: [ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY](#); SQLSTATE: [HY000](#)
Message: Error while %s key: invalid key_type
 - Error number: [MY-011359](#); Symbol: [ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID](#); SQLSTATE: [HY000](#)
Message: Error while %s key: key_id cannot be empty
 - Error number: [MY-011360](#); Symbol: [ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Failed to %s due to internal exception inside %s plugin
 - Error number: [MY-011361](#); Symbol: [ER_KEYRING_INCORRECT_FILE](#); SQLSTATE: [HY000](#)
Message: Incorrect Keyring file
 - Error number: [MY-011362](#); Symbol: [ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE](#); SQLSTATE: [HY000](#)
Message: Found malformed keyring backup file - removing it
 - Error number: [MY-011363](#); Symbol: [ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE](#); SQLSTATE: [HY000](#)
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup
 - Error number: [MY-011364](#); Symbol: [ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE](#); SQLSTATE: [HY000](#)
Message: Error while flushing in-memory keyring into keyring file
 - Error number: [MY-011365](#); Symbol: [ER_KEYRING_FAILED_TO_GET_FILE_STAT](#); SQLSTATE: [HY000](#)
Message: Error while reading stat for %s. Please check if file %s was not removed. OS returned this error: %s
 - Error number: [MY-011366](#); Symbol: [ER_KEYRING_FAILED_TO_REMOVE_FILE](#); SQLSTATE: [HY000](#)
Message: Could not remove file %s OS returned this error: %s
 - Error number: [MY-011367](#); Symbol: [ER_KEYRING_FAILED_TO_TRUNCATE_FILE](#); SQLSTATE: [HY000](#)
Message: Could not truncate file %s. OS returned this error: %s
 - Error number: [MY-011368](#); Symbol: [ER_KEYRING_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)
Message: Unknown error %d
 - Error number: [MY-011370](#); Symbol: [ER_KEYRING_FILE_IO_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011371](#); Symbol: [ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT](#); SQLSTATE: [HY000](#)

Message: Error while loading keyring content. The keyring might be malformed

- Error number: `MY-011372`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING`; SQLSTATE: `HY000`

Message: Could not flush keys to keyring

- Error number: `MY-011373`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP`; SQLSTATE: `HY000`

Message: Could not flush keys to keyring's backup

- Error number: `MY-011374`; Symbol: `ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID`; SQLSTATE: `HY000`

Message: Error while fetching key: key_id cannot be empty

- Error number: `MY-011375`; Symbol: `ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID`; SQLSTATE: `HY000`

Message: Error while removing key: key_id cannot be empty

- Error number: `MY-011376`; Symbol: `ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED`; SQLSTATE: `HY000`

Message: For keyring_okv to be initialized, please point keyring_okv_conf_dir variable to a directory with Oracle Key Vault configuration file and ssl materials

- Error number: `MY-011377`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF`; SQLSTATE: `HY000`

Message: keyring_okv initialization failure. Please check that the keyring_okv_conf_dir points to a readable directory and that the directory contains Oracle Key Vault configuration file and ssl materials. Please also check that Oracle Key Vault is up and running.

- Error number: `MY-011378`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: keyring_okv initialization failure due to internal exception inside the plugin

- Error number: `MY-011379`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_TYPE`; SQLSTATE: `HY000`

Message: Invalid key type

- Error number: `MY-011380`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`

Message: Invalid key length for given block cipher

- Error number: `MY-011381`; Symbol: `ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Failed to generate a key due to internal exception inside keyring_okv plugin

- Error number: `MY-011382`; Symbol: `ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY`; SQLSTATE: `HY000`

Message: Could not find entry for server in configuration file %s

- Error number: `MY-011383`; Symbol: `ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY`; SQLSTATE: `HY000`

Message: Could not find entry for standby server in configuration file %s

- Error number: [MY-011384](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE](#); SQLSTATE: [HY000](#)

Message: Could not parse the %s file provided

- Error number: [MY-011385](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID](#); SQLSTATE: [HY000](#)

Message: Could not load keys' uids from the OKV server

- Error number: [MY-011386](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER](#); SQLSTATE: [HY000](#)

Message: Could not initialize ssl layer

- Error number: [MY-011387](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT](#); SQLSTATE: [HY000](#)

Message: Could not initialize OKV client

- Error number: [MY-011388](#); Symbol: [ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not connect to the OKV server

- Error number: [MY-011389](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not remove the key

- Error number: [MY-011390](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE](#); SQLSTATE: [HY000](#)

Message: Could not add attribute, attribute_name=%s attribute value=%s

- Error number: [MY-011391](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not generate the key.

- Error number: [MY-011392](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_STORE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not store the key.

- Error number: [MY-011393](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS](#); SQLSTATE: [HY000](#)

Message: Could not activate the key.

- Error number: [MY-011394](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_FETCH_KEY](#); SQLSTATE: [HY000](#)

Message: Could not fetch generated key

- Error number: [MY-011395](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not store/generate the key - failed to set key attribute x-key-ready

-
- Error number: [MY-011396](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE](#); SQLSTATE: [HY000](#)
Message: Could not retrieve key signature from custom attributes
 - Error number: [MY-011397](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY](#); SQLSTATE: [HY000](#)
Message: Could not retrieve key from OKV
 - Error number: [MY-011398](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE](#); SQLSTATE: [HY000](#)
Message: Error loading trust store
 - Error number: [MY-011399](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE](#); SQLSTATE: [HY000](#)
Message: Error setting the certificate file.
 - Error number: [MY-011400](#); Symbol: [ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE](#); SQLSTATE: [HY000](#)
Message: Error setting the key file.
 - Error number: [MY-011401](#); Symbol: [ER_KEYRING_OKV_KEY_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Private key does not match the certificate public key
 - Error number: [MY-011415](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID](#); SQLSTATE: [HY000](#)
Message: keyring_aws_cmk_id cannot be set to the new value as AWS KMS seems to not understand the id provided. Please check that CMK id provided is correct.
 - Error number: [MY-011416](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_SET_REGION](#); SQLSTATE: [HY000](#)
Message: keyring_aws_region cannot be set to the new value as AWS KMS seems to not understand the region provided. Please check that region provided is correct.
 - Error number: [MY-011417](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE](#); SQLSTATE: [HY000](#)
Message: Could not open keyring_aws configuration file: %s. OS returned this error: %s
 - Error number: [MY-011418](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE](#); SQLSTATE: [HY000](#)
Message: Could not read AWS access key id from keyring_aws configuration file: %s. OS returned this error: %s
 - Error number: [MY-011419](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE](#); SQLSTATE: [HY000](#)
Message: Could not read AWS access key from keyring_aws configuration file: %s. OS returned this error: %s
 - Error number: [MY-011420](#); Symbol: [ER_KEYRING_AWS_INVALID_CONF_FILE_PATH](#); SQLSTATE: [HY000](#)
Message: Path to keyring aws configuration file cannot be empty
-

-
- Error number: [MY-011421](#); Symbol: [ER_KEYRING_AWS_INVALID_DATA_FILE_PATH](#); SQLSTATE: [HY000](#)

Message: Path to keyring_aws storage file cannot be empty.
 - Error number: [MY-011422](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR](#); SQLSTATE: [HY000](#)

Message: Unable to create/access keyring directory.
 - Error number: [MY-011423](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to create/access keyring_aws storage file. Please check if keyring_aws_data_file points to location where keyring file can be created/accessed. Please also make sure that MySQL server's user has high enough privileges to access this location.
 - Error number: [MY-011424](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failed due to internal error when initializing synchronization primitive - %s. OS returned this error: %s:
 - Error number: [MY-011425](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE](#); SQLSTATE: [HY000](#)

Message: Could not access keyring_aws storage file in the path provided. Please check if the keyring_aws directory can be accessed by MySQL Server
 - Error number: [MY-011426](#); Symbol: [ER_KEYRING_AWS_CMK_ID_NOT_SET](#); SQLSTATE: [HY000](#)

Message: keyring_aws_cmk_id has to be set
 - Error number: [MY-011427](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE](#); SQLSTATE: [HY000](#)

Message: Could not get AWS KMS credentials from the configuration file
 - Error number: [MY-011428](#); Symbol: [ER_KEYRING_AWS_INIT_FAILURE](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failure.
 - Error number: [MY-011429](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failure due to internal exception inside the plugin
 - Error number: [MY-011430](#); Symbol: [ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER](#); SQLSTATE: [HY000](#)

Message: Invalid key length for given block cipher
 - Error number: [MY-011431](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to generate a key due to internal exception inside keyring_file plugin
 - Error number: [MY-011432](#); Symbol: [ER_KEYRING_AWS_INCORRECT_FILE](#); SQLSTATE: [HY000](#)

Message: Incorrect Keyring file

-
- Error number: [MY-011433](#); Symbol: [ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE](#); SQLSTATE: [HY000](#)
Message: Found malformed keyring backup file - removing it
 - Error number: [MY-011434](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE](#); SQLSTATE: [HY000](#)
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup
 - Error number: [MY-011435](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE](#); SQLSTATE: [HY000](#)
Message: Error while flushing in-memory keyring into keyring file
 - Error number: [MY-011436](#); Symbol: [ER_KEYRING_AWS_INCORRECT_REGION](#); SQLSTATE: [HY000](#)
Message: Wrong region
 - Error number: [MY-011437](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS](#); SQLSTATE: [HY000](#)
Message: Could not connect to AWS KMS with the credentials provided. Please make sure they are correct. AWS KMS returned this error: %s
 - Error number: [MY-011438](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY](#); SQLSTATE: [HY000](#)
Message: Could not generate a new key. AWS KMS returned this error: %s
 - Error number: [MY-011439](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY](#); SQLSTATE: [HY000](#)
Message: Could not encrypt key. AWS KMS returned this error: %s
 - Error number: [MY-011440](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY](#); SQLSTATE: [HY000](#)
Message: Could not re-encrypt key. AWS KMS returned this error: %s
 - Error number: [MY-011441](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY](#); SQLSTATE: [HY000](#)
Message: Could not decrypt key. AWS KMS returned this error: %s
 - Error number: [MY-011442](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK](#); SQLSTATE: [HY000](#)
Message: Could not rotate the CMK. AWS KMS returned this error: %s
 - Error number: [MY-011443](#); Symbol: [ER_GRP_RPL_GTID_ALREADY_USED](#); SQLSTATE: [HY000](#)
Message: The requested GTID '%s:%lld' was already used, the transaction will rollback.
 - Error number: [MY-011444](#); Symbol: [ER_GRP_RPL_APPLIER_THD_KILLED](#); SQLSTATE: [HY000](#)
Message: The group replication applier thread was killed.
 - Error number: [MY-011445](#); Symbol: [ER_GRP_RPL_EVENT_HANDLING_ERROR](#); SQLSTATE: [HY000](#)
Message: Error at event handling! Got error: %d.
 - Error number: [MY-011446](#); Symbol: [ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO](#); SQLSTATE: [HY000](#)

Message: Error when extracting group GTID execution information, some recovery operations may face future issues.

- Error number: [MY-011448](#); Symbol: [ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to create group replication pipeline applier cache!

- Error number: [MY-011449](#); Symbol: [ER_GRP_RPL_UNBLOCK_WAITING_THD](#); SQLSTATE: [HY000](#)

Message: Unblocking the group replication thread waiting for applier to start, as the start group replication was killed.

- Error number: [MY-011450](#); Symbol: [ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED](#); SQLSTATE: [HY000](#)

Message: The group replication applier pipeline was not properly disposed. Check the error log for further info.

- Error number: [MY-011451](#); Symbol: [ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED](#); SQLSTATE: [HY000](#)

Message: The applier thread execution was aborted. Unable to process more transactions, this member will now leave the group.

- Error number: [MY-011452](#); Symbol: [ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error during execution on the Applier process of Group Replication. The server will now leave the group.

- Error number: [MY-011453](#); Symbol: [ER_GRP_RPL_ERROR_STOPPING_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Error stopping all replication channels while server was leaving the group. %s

- Error number: [MY-011454](#); Symbol: [ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG](#); SQLSTATE: [HY000](#)

Message: Error sending single primary message informing that primary did apply relay logs.

- Error number: [MY-011457](#); Symbol: [ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED](#); SQLSTATE: [HY000](#)

Message: Broadcast of committed transactions message failed.

- Error number: [MY-011458](#); Symbol: [ER_GRP_RPL_GROUP_NAME_PARSE_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to parse the group_replication_group_name during the Certification module initialization.

- Error number: [MY-011459](#); Symbol: [ER_GRP_RPL_ADD_GRP_SID_TO_GRP_GTID_SID_MAP_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to add the group_sid in the group_gtid_sid_map during the Certification module initialization.

- Error number: [MY-011460](#); Symbol: [ER_GRP_RPL_UPDATE_GRP_GTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating group_gtid_executed GTID set during the Certification module initialization.

-
- Error number: [MY-011461](#); Symbol: [ER_GRP_RPL_DONOR_TRANS_INFO_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to handle the donor's transaction information when initializing the conflict detection component. Possible out of memory error.
 - Error number: [MY-011462](#); Symbol: [ER_GRP_RPL_SERVER_CONN_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when establishing a server connection during the Certification module initialization.
 - Error number: [MY-011463](#); Symbol: [ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID executed set. Certification module can't be properly initialized.
 - Error number: [MY-011464](#); Symbol: [ER_GRP_RPL_ADD_GTID_TO_GRP_GTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while adding the server GTID EXECUTED set to the group_gtid_execute during the Certification module initialization.
 - Error number: [MY-011465](#); Symbol: [ER_GRP_RPL_ERROR_FETCHING_GTID_SET](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member retrieved set for its applier. Certification module can't be properly initialized.
 - Error number: [MY-011466](#); Symbol: [ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while adding the member retrieved set to the group_gtid_executed during the Certification module initialization.
 - Error number: [MY-011467](#); Symbol: [ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error during Certification module initialization.
 - Error number: [MY-011468](#); Symbol: [ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to update last conflict free transaction, this transaction will not be tracked on performance_schema.replication_group_member_stats.last_conflict_free_transaction.
 - Error number: [MY-011469](#); Symbol: [ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating transaction snapshot version reference for internal storage.
 - Error number: [MY-011472](#); Symbol: [ER_GRP_RPL_CANT_GENERATE_GTID](#); SQLSTATE: [HY000](#)

Message: Impossible to generate Global Transaction Identifier: the integer component reached the maximal value. Restart the group with a new group_replication_group_name.
 - Error number: [MY-011473](#); Symbol: [ER_GRP_RPL_INVALID_GTID_SET](#); SQLSTATE: [HY000](#)

Message: Invalid stable transactions set.
 - Error number: [MY-011474](#); Symbol: [ER_GRP_RPL_UPDATE_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating stable transactions set.

-
- Error number: [MY-011475](#); Symbol: [ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS](#); SQLSTATE: [HY000](#)
Message: There was an error when filling the missing GTIDs on the applier channel received set. Despite not critical, on the long run this may cause performance issues.
 - Error number: [MY-011477](#); Symbol: [ER_GRP_RPL_NULL_PACKET](#); SQLSTATE: [HY000](#)
Message: Null packet on certifier's queue.
 - Error number: [MY-011478](#); Symbol: [ER_GRP_RPL_CANT_READ_GTID](#); SQLSTATE: [HY000](#)
Message: Error reading GTIDs from the message.
 - Error number: [MY-011479](#); Symbol: [ER_GRP_RPL_PROCESS_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)
Message: Error processing stable transactions set.
 - Error number: [MY-011480](#); Symbol: [ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)
Message: Error processing intersection of stable transactions set.
 - Error number: [MY-011481](#); Symbol: [ER_GRP_RPL_SET_STABLE_TRANS_ERROR](#); SQLSTATE: [HY000](#)
Message: Error setting stable transactions set.
 - Error number: [MY-011482](#); Symbol: [ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED](#); SQLSTATE: [HY000](#)
Message: Error reading group_gtid_extracted from the View_change_log_event.
 - Error number: [MY-011483](#); Symbol: [ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM](#); SQLSTATE: [HY000](#)
Message: Error reading the write set item '%s' from the View_change_log_event.
 - Error number: [MY-011484](#); Symbol: [ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE](#); SQLSTATE: [HY000](#)
Message: Error during certification_info initialization.
 - Error number: [MY-011485](#); Symbol: [ER_GRP_RPL_CONFLICT_DETECTION_DISABLED](#); SQLSTATE: [HY000](#)
Message: Primary had applied all relay logs, disabled conflict detection.
 - Error number: [MY-011486](#); Symbol: [ER_GRP_RPL_MSG_DISCARDED](#); SQLSTATE: [HY000](#)
Message: Message received while the plugin is not ready, message discarded.
 - Error number: [MY-011487](#); Symbol: [ER_GRP_RPL_MISSING_GRP_RPL_APPLIER](#); SQLSTATE: [HY000](#)
Message: Message received without a proper group replication applier.
 - Error number: [MY-011488](#); Symbol: [ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR](#); SQLSTATE: [HY000](#)
Message: Error processing message in Certifier.
 - Error number: [MY-011489](#); Symbol: [ER_GRP_RPL_SRV_NOT_ONLINE](#); SQLSTATE: [HY000](#)

Message: This server was not declared online since it is on status %s.

- Error number: [MY-011490](#); Symbol: [ER_GRP_RPL_SRV_ONLINE](#); SQLSTATE: [HY000](#)

Message: This server was declared online within the replication group.

- Error number: [MY-011491](#); Symbol: [ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED](#); SQLSTATE: [HY000](#)

Message: When declaring the plugin online it was not possible to disable the server read mode settings. Try to disable it manually.

- Error number: [MY-011492](#); Symbol: [ER_GRP_RPL_MEM_ONLINE](#); SQLSTATE: [HY000](#)

Message: The member with address %s:%u was declared online within the replication group.

- Error number: [MY-011493](#); Symbol: [ER_GRP_RPL_MEM_UNREACHABLE](#); SQLSTATE: [HY000](#)

Message: Member with address %s:%u has become unreachable.

- Error number: [MY-011494](#); Symbol: [ER_GRP_RPL_MEM_REACHABLE](#); SQLSTATE: [HY000](#)

Message: Member with address %s:%u is reachable again.

- Error number: [MY-011495](#); Symbol: [ER_GRP_RPL_SRV_BLOCKED](#); SQLSTATE: [HY000](#)

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked until contact with the majority is restored. It is possible to use `group_replication_force_members` to force a new group membership.

- Error number: [MY-011496](#); Symbol: [ER_GRP_RPL_SRV_BLOCKED_FOR_SECS](#); SQLSTATE: [HY000](#)

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked for the next %lu seconds. Unless contact with the majority is restored, after this time the member will error out and leave the group. It is possible to use `group_replication_force_members` to force a new group membership.

- Error number: [MY-011497](#); Symbol: [ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED](#); SQLSTATE: [HY000](#)

Message: A group membership change was received but the plugin is already leaving due to the configured timeout on `group_replication_unreachable_majority_timeout` option.

- Error number: [MY-011498](#); Symbol: [ER_GRP_RPL_MEMBER_CONTACT_RESTORED](#); SQLSTATE: [HY000](#)

Message: The member has resumed contact with a majority of the members in the group. Regular operation is restored and transactions are unblocked.

- Error number: [MY-011499](#); Symbol: [ER_GRP_RPL_MEMBER_REMOVED](#); SQLSTATE: [HY000](#)

Message: Members removed from the group: %s

- Error number: [MY-011500](#); Symbol: [ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP](#); SQLSTATE: [HY000](#)

Message: Primary server with address %s left the group. Electing new Primary.

- Error number: [MY-011501](#); Symbol: [ER_GRP_RPL_MEMBER_ADDED](#); SQLSTATE: [HY000](#)

Message: Members joined the group: %s

-
- Error number: [MY-011502](#); Symbol: [ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR](#); SQLSTATE: [HY000](#)

Message: There was a previous plugin error while the member joined the group. The member will now exit the group.

- Error number: [MY-011503](#); Symbol: [ER_GRP_RPL_MEMBER_CHANGE](#); SQLSTATE: [HY000](#)

Message: Group membership changed to %s on view %s.

- Error number: [MY-011504](#); Symbol: [ER_GRP_RPL_MEMBER_LEFT_GRP](#); SQLSTATE: [HY000](#)

Message: Group membership changed: This member has left the group.

- Error number: [MY-011505](#); Symbol: [ER_GRP_RPL_MEMBER_EXPELLED](#); SQLSTATE: [HY000](#)

Message: Member was expelled from the group due to network failures, changing member status to ERROR.

- Error number: [MY-011506](#); Symbol: [ER_GRP_RPL_SESSION_OPEN_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to open session to (re)set read only mode. Skipping.

- Error number: [MY-011507](#); Symbol: [ER_GRP_RPL_NEW_PRIMARY_ELECTED](#); SQLSTATE: [HY000](#)

Message: A new primary with address %s:%u was elected. %s

- Error number: [MY-011508](#); Symbol: [ER_GRP_RPL_DISABLE_READ_ONLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to disable super read only flag. Try to disable it manually

- Error number: [MY-011509](#); Symbol: [ER_GRP_RPL_ENABLE_READ_ONLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to set super read only flag. Try to set it manually.

- Error number: [MY-011510](#); Symbol: [ER_GRP_RPL_SRV_PRIMARY_MEM](#); SQLSTATE: [HY000](#)

Message: This server is working as primary member.

- Error number: [MY-011511](#); Symbol: [ER_GRP_RPL_SRV_SECONDARY_MEM](#); SQLSTATE: [HY000](#)

Message: This server is working as secondary member with primary member address %s:%u.

- Error number: [MY-011512](#); Symbol: [ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM](#); SQLSTATE: [HY000](#)

Message: Unable to set any member as primary. No suitable candidate.

- Error number: [MY-011513](#); Symbol: [ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when activating super_read_only mode on start. The member will now exit the group.

- Error number: [MY-011514](#); Symbol: [ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE](#); SQLSTATE: [HY000](#)

Message: Group contains %lu members which is greater than group_replication_auto_increment_increment value of %lu. This can lead to a higher transactional abort rate.

-
- Error number: [MY-011515](#); Symbol: [ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM](#); SQLSTATE: [HY000](#)

Message: Member with address '%s:%u' didn't provide any data during the last group change. Group information can be outdated and lead to errors on recovery.

- Error number: [MY-011516](#); Symbol: [ER_GRP_RPL_MEMBER_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: There is already a member with server_uuid %s. The member will now exit the group.

- Error number: [MY-011518](#); Symbol: [ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID executed set. Operations and checks made to group joiners may be incomplete.

- Error number: [MY-011519](#); Symbol: [ER_GRP_RPL_GTID_SET_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member retrieved set for its applier. Operations and checks made to group joiners may be incomplete.

- Error number: [MY-011520](#); Symbol: [ER_GRP_RPL_START_FAILED](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the group already has 9 members.

- Error number: [MY-011521](#); Symbol: [ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE](#); SQLSTATE: [HY000](#)

Message: Member version is incompatible with the group.

- Error number: [MY-011522](#); Symbol: [ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP](#); SQLSTATE: [HY000](#)

Message: The member contains transactions not present in the group. The member will now exit the group.

- Error number: [MY-011523](#); Symbol: [ER_GRP_RPL_TRANS_GREATER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: It was not possible to assess if the member has more transactions than the group. The member will now exit the group.

- Error number: [MY-011525](#); Symbol: [ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing local GTID sets when comparing this member transactions against the group.

- Error number: [MY-011526](#); Symbol: [ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: This member has more executed transactions than those present in the group. Local transactions: %s > Group transactions: %s

- Error number: [MY-011527](#); Symbol: [ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a group_replication_gtid_assignment_block_size option value '%llu' different from the group '%llu'. The member will now exit the group.

-
- Error number: [MY-011528](#); Symbol: [ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

 Message: The member is configured with a transaction-write-set-extraction option value '%s' different from the group '%s'. The member will now exit the group.
 - Error number: [MY-011529](#); Symbol: [ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG](#); SQLSTATE: [HY000](#)

 Message: The member configuration is not compatible with the group configuration. Variables such as `group_replication_single_primary_mode` or `group_replication_enforce_update_everywhere_checks` must have the same value on every server in the group. (member configuration option: [%s], group configuration option: [%s]).
 - Error number: [MY-011530](#); Symbol: [ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR](#); SQLSTATE: [HY000](#)

 Message: Error stopping all replication channels while server was leaving the group. %s
 - Error number: [MY-011531](#); Symbol: [ER_GRP_RPL_PURGE_APPLIER_LOGS](#); SQLSTATE: [HY000](#)

 Message: Detected previous RESET BINARY LOGS AND GTIDS invocation or an issue exists in the group replication applier relay log. Purging existing applier logs.
 - Error number: [MY-011532](#); Symbol: [ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR](#); SQLSTATE: [HY000](#)

 Message: Unknown error occurred while resetting applier's module logs.
 - Error number: [MY-011533](#); Symbol: [ER_GRP_RPL_APPLIER_THD_SETUP_ERROR](#); SQLSTATE: [HY000](#)

 Message: Failed to setup the group replication applier thread.
 - Error number: [MY-011534](#); Symbol: [ER_GRP_RPL_APPLIER_THD_START_ERROR](#); SQLSTATE: [HY000](#)

 Message: Error while starting the group replication applier thread
 - Error number: [MY-011535](#); Symbol: [ER_GRP_RPL_APPLIER_THD_STOP_ERROR](#); SQLSTATE: [HY000](#)

 Message: Failed to stop the group replication applier thread.
 - Error number: [MY-011536](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_DATA_FAILED](#); SQLSTATE: [HY000](#)

 Message: Failed to fetch transaction data containing required transaction info for applier
 - Error number: [MY-011537](#); Symbol: [ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

 Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.
 - Error number: [MY-011538](#); Symbol: [ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

 Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.
 - Error number: [MY-011539](#); Symbol: [ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

- Error number: [MY-011540](#); Symbol: [ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

- Error number: [MY-011541](#); Symbol: [ER_GRP_RPL_NEEDS_INNODB_TABLE](#); SQLSTATE: [HY000](#)

Message: Table %s does not use the InnoDB storage engine. This is not compatible with Group Replication.

- Error number: [MY-011542](#); Symbol: [ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED](#); SQLSTATE: [HY000](#)

Message: Table %s does not have any PRIMARY KEY. This is not compatible with Group Replication.

- Error number: [MY-011543](#); Symbol: [ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Table %s has a foreign key with 'CASCADE', 'SET NULL' or 'SET DEFAULT' clause. This is not compatible with Group Replication.

- Error number: [MY-011544](#); Symbol: [ER_GRP_RPL_AUTO_INC_RESET](#); SQLSTATE: [HY000](#)

Message: group_replication_auto_increment_increment is reset to %lu

- Error number: [MY-011545](#); Symbol: [ER_GRP_RPL_AUTO_INC_OFFSET_RESET](#); SQLSTATE: [HY000](#)

Message: auto_increment_offset is reset to %lu

- Error number: [MY-011546](#); Symbol: [ER_GRP_RPL_AUTO_INC_SET](#); SQLSTATE: [HY000](#)

Message: group_replication_auto_increment_increment is set to %lu

- Error number: [MY-011547](#); Symbol: [ER_GRP_RPL_AUTO_INC_OFFSET_SET](#); SQLSTATE: [HY000](#)

Message: auto_increment_offset is set to %lu

- Error number: [MY-011548](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch transaction context containing required transaction info for certification

- Error number: [MY-011549](#); Symbol: [ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch Format_description_log_event containing required server info for applier

- Error number: [MY-011550](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch Transaction_context_log_event containing required transaction info for certification

- Error number: [MY-011551](#); Symbol: [ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read snapshot version from transaction context event required for certification

-
- Error number: [MY-011552](#); Symbol: [ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to fetch Gtid_log_event containing required transaction info for certification
 - Error number: [MY-011553](#); Symbol: [ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to update certification result on server side, thread_id: %lu
 - Error number: [MY-011554](#); Symbol: [ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for local transactions
 - Error number: [MY-011555](#); Symbol: [ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to add gtid information to the group_gtid_executed set when no gtid was provided for local transactions
 - Error number: [MY-011556](#); Symbol: [ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to notify certification outcome
 - Error number: [MY-011557](#); Symbol: [ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for remote transactions
 - Error number: [MY-011558](#); Symbol: [ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to add gtid information to the group_gtid_executed set when gtid was not provided for remote transactions
 - Error number: [MY-011559](#); Symbol: [ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to fetch View_change_log_event containing required info for certification
 - Error number: [MY-011562](#); Symbol: [ER_GRP_RPL_FETCH_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to fetch Log_event containing required server info for applier
 - Error number: [MY-011563](#); Symbol: [ER_GRP_RPL_START_GRP_RPL_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with --initialize, --initialize-insecure or --upgrade=MINIMAL on a server upgrade.
 - Error number: [MY-011564](#); Symbol: [ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to establish an internal server connection to execute plugin operations
 - Error number: [MY-011565](#); Symbol: [ER_GRP_RPL_SUPER_READ_ON](#); SQLSTATE: [HY000](#)
Message: Setting super_read_only=ON.

-
- Error number: [MY-011566](#); Symbol: [ER_GRP_RPL_SUPER_READ_OFF](#); SQLSTATE: [HY000](#)
Message: Setting super_read_only=OFF.
 - Error number: [MY-011567](#); Symbol: [ER_GRP_RPL_KILLED_SESSION_ID](#); SQLSTATE: [HY000](#)
Message: killed session id: %d status: %d
 - Error number: [MY-011568](#); Symbol: [ER_GRP_RPL_KILLED_FAILED_ID](#); SQLSTATE: [HY000](#)
Message: killed failed id: %d failed: %d
 - Error number: [MY-011569](#); Symbol: [ER_GRP_RPL_INTERNAL_QUERY](#); SQLSTATE: [HY000](#)
Message: Internal query: %s result in error. Error number: %ld
 - Error number: [MY-011570](#); Symbol: [ER_GRP_RPL_COPY_FROM_EMPTY_STRING](#); SQLSTATE: [HY000](#)
Message: Error copying from empty string
 - Error number: [MY-011571](#); Symbol: [ER_GRP_RPL_QUERY_FAIL](#); SQLSTATE: [HY000](#)
Message: Query execution resulted in failure. errno: %d
 - Error number: [MY-011572](#); Symbol: [ER_GRP_RPL_CREATE_SESSION_UNABLE](#); SQLSTATE: [HY000](#)
Message: Unable to create a session for executing the queries on the server
 - Error number: [MY-011573](#); Symbol: [ER_GRP_RPL_MEMBER_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: The member with address %s:%u has unexpectedly disappeared, killing the current group replication recovery connection
 - Error number: [MY-011574](#); Symbol: [ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED](#); SQLSTATE: [HY000](#)
Message: Maximum number of retries when trying to connect to a donor reached. Aborting group replication incremental recovery.
 - Error number: [MY-011575](#); Symbol: [ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY](#); SQLSTATE: [HY000](#)
Message: All donors left. Aborting group replication incremental recovery.
 - Error number: [MY-011576](#); Symbol: [ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR](#); SQLSTATE: [HY000](#)
Message: Establishing group recovery connection with a possible donor. Attempt %d/%d
 - Error number: [MY-011577](#); Symbol: [ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR](#); SQLSTATE: [HY000](#)
Message: Retrying group recovery connection with another donor. Attempt %d/%d
 - Error number: [MY-011578](#); Symbol: [ER_GRP_RPL_NO_VALID_DONOR](#); SQLSTATE: [HY000](#)
Message: No valid donors exist in the group, retrying
 - Error number: [MY-011579](#); Symbol: [ER_GRP_RPL_CONFIG_RECOVERY](#); SQLSTATE: [HY000](#)
Message: Error when configuring the asynchronous recovery channel connection to the donor.

-
- Error number: [MY-011580](#); Symbol: [ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR](#); SQLSTATE: [HY000](#)
 Message: Establishing connection to a group replication recovery donor %s at %s port: %d.
 - Error number: [MY-011581](#); Symbol: [ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL](#); SQLSTATE: [HY000](#)
 Message: Error while creating the group replication recovery channel with donor %s at %s port: %d.
 - Error number: [MY-011582](#); Symbol: [ER_GRP_RPL_DONOR_SERVER_CONN](#); SQLSTATE: [HY000](#)
 Message: There was an error when connecting to the donor server. Please check that group_replication_recovery channel credentials and all MEMBER_HOST column values of performance_schema.replication_group_members table are correct and DNS resolvable.
 - Error number: [MY-011583](#); Symbol: [ER_GRP_RPL_CHECK_STATUS_TABLE](#); SQLSTATE: [HY000](#)
 Message: For details please check performance_schema.replication_connection_status table and error log messages of Replica I/O for channel group_replication_recovery.
 - Error number: [MY-011584](#); Symbol: [ER_GRP_RPL_STARTING_GRP_REC](#); SQLSTATE: [HY000](#)
 Message: Error while starting the group replication incremental recovery receiver/applier threads
 - Error number: [MY-011585](#); Symbol: [ER_GRP_RPL_DONOR_CONN_TERMINATION](#); SQLSTATE: [HY000](#)
 Message: Terminating existing group replication donor connection and purging the corresponding logs.
 - Error number: [MY-011586](#); Symbol: [ER_GRP_RPL_STOPPING_GRP_REC](#); SQLSTATE: [HY000](#)
 Message: Error when stopping the group replication incremental recovery's donor connection
 - Error number: [MY-011587](#); Symbol: [ER_GRP_RPL_PURGE_REC](#); SQLSTATE: [HY000](#)
 Message: Error when purging the group replication recovery's relay logs
 - Error number: [MY-011588](#); Symbol: [ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER](#); SQLSTATE: [HY000](#)
 Message: Unable to kill the current group replication recovery donor connection after an applier error. Incremental recovery will shutdown.
 - Error number: [MY-011589](#); Symbol: [ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOVER](#); SQLSTATE: [HY000](#)
 Message: Unable to kill the current group replication recovery donor connection during failover. Incremental recovery will shutdown.
 - Error number: [MY-011590](#); Symbol: [ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT](#); SQLSTATE: [HY000](#)
 Message: Unexpected error when notifying an internal component named %s regarding a group membership event.
 - Error number: [MY-011591](#); Symbol: [ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION](#); SQLSTATE: [HY000](#)
 Message: An undefined error was found while broadcasting an internal group membership notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

-
- Error number: [MY-011592](#); Symbol: [ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION](#); SQLSTATE: [HY000](#)

Message: An undefined error was found while broadcasting an internal group member status notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!
 - Error number: [MY-011593](#); Symbol: [ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH](#); SQLSTATE: [HY000](#)

Message: No memory to generate write identification hash
 - Error number: [MY-011594](#); Symbol: [ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED](#); SQLSTATE: [HY000](#)

Message: Base 64 encoding of the write identification hash failed
 - Error number: [MY-011595](#); Symbol: [ER_GRP_RPL_INVALID_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)

Message: Binlog format should be ROW for Group Replication
 - Error number: [MY-011598](#); Symbol: [ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION](#); SQLSTATE: [HY000](#)

Message: Transaction isolation level (tx_isolation) is set to SERIALIZABLE, which is not compatible with Group Replication
 - Error number: [MY-011599](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is stopping.
 - Error number: [MY-011600](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is recovering. Try again when the server is ONLINE.
 - Error number: [MY-011601](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is on ERROR state. Check for errors and restart the plugin
 - Error number: [MY-011602](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is OFFLINE. Check for errors and restart the plugin
 - Error number: [MY-011603](#); Symbol: [ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION](#); SQLSTATE: [HY000](#)

Message: We can only use one cache type at a time on session %u
 - Error number: [MY-011604](#); Symbol: [ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ](#); SQLSTATE: [HY000](#)

Message: Failed to reinit binlog cache log for read on session %u
 - Error number: [MY-011605](#); Symbol: [ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT](#); SQLSTATE: [HY000](#)

Message: Failed to create the context of the current transaction on session %u

- Error number: [MY-011606](#); Symbol: [ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET](#); SQLSTATE: [HY000](#)

Message: Failed to extract the set of items written during the execution of the current transaction on session %u

- Error number: [MY-011607](#); Symbol: [ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET](#); SQLSTATE: [HY000](#)

Message: Failed to gather the set of items written during the execution of the current transaction on session %u

- Error number: [MY-011608](#); Symbol: [ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT](#); SQLSTATE: [HY000](#)

Message: Error on session %u. Transaction of size %llu exceeds specified limit %lu. To increase the limit please adjust group_replication_transaction_size_limit option.

- Error number: [MY-011611](#); Symbol: [ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while writing to transaction message on session %u

- Error number: [MY-011612](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION](#); SQLSTATE: [HY000](#)

Message: Unable to register for getting notifications regarding the outcome of the transaction on session %u

- Error number: [MY-011613](#); Symbol: [ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED](#); SQLSTATE: [HY000](#)

Message: Error broadcasting transaction to the group on session %u. Message is too big.

- Error number: [MY-011614](#); Symbol: [ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while broadcasting the transaction to the group on session %u

- Error number: [MY-011615](#); Symbol: [ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION](#); SQLSTATE: [HY000](#)

Message: Error while waiting for conflict detection procedure to finish on session %u

- Error number: [MY-011620](#); Symbol: [ER_GRP_RPL_FATAL_REC_PROCESS](#); SQLSTATE: [HY000](#)

Message: Fatal error during the incremental recovery process of Group Replication. The server will leave the group.

- Error number: [MY-011622](#); Symbol: [ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS](#); SQLSTATE: [HY000](#)

Message: Unable to evaluate the group replication applier execution status. Group replication recovery will shutdown to avoid data corruption.

- Error number: [MY-011623](#); Symbol: [ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE](#); SQLSTATE: [HY000](#)

Message: Only one server alive. Declaring this server as online within the replication group

-
- Error number: [MY-011624](#); Symbol: [ER_GRP_RPL_CERTIFICATION_REC_PROCESS](#); SQLSTATE: [HY000](#)

Message: Error when processing certification information in the incremental recovery process
 - Error number: [MY-011625](#); Symbol: [ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC](#); SQLSTATE: [HY000](#)

Message: Unable to ensure the execution of group transactions received during recovery.
 - Error number: [MY-011626](#); Symbol: [ER_GRP_RPL_WHILE_SENDING_MSG_REC](#); SQLSTATE: [HY000](#)

Message: Error while sending message in the group replication incremental recovery process.
 - Error number: [MY-011628](#); Symbol: [ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: Unable to read the server values for the read_only and super_read_only variables.
 - Error number: [MY-011629](#); Symbol: [ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE](#); SQLSTATE: [HY000](#)

Message: Unable to reset the server read mode settings. Try to reset them manually.
 - Error number: [MY-011630](#); Symbol: [ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS](#); SQLSTATE: [HY000](#)

Message: Due to a plugin error, some transactions were unable to be certified and will now rollback.
 - Error number: [MY-011631](#); Symbol: [ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS](#); SQLSTATE: [HY000](#)

Message: Error when trying to unblock non certified or consistent transactions. Check for consistency errors when restarting the service
 - Error number: [MY-011633](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID](#); SQLSTATE: [HY000](#)

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with server_id=0. Please, restart the server with server_id larger than 0.
 - Error number: [MY-011634](#); Symbol: [ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY](#); SQLSTATE: [HY000](#)

Message: group_replication_force_members must be empty on group start. Current value: '%s'
 - Error number: [MY-011635](#); Symbol: [ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START](#); SQLSTATE: [HY000](#)

Message: It was not possible to guarantee the initialization of plugin structures on server start
 - Error number: [MY-011636](#); Symbol: [ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)

Message: Could not enable the server read only mode and guarantee a safe recovery execution
 - Error number: [MY-011637](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE](#); SQLSTATE: [HY000](#)

Message: Error on group communication engine initialization
-

-
- Error number: [MY-011638](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Can't start group replication on secondary member with single-primary mode while asynchronous replication channels are running.
 - Error number: [MY-011639](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE](#); SQLSTATE: [HY000](#)

Message: Error on group communication engine start
 - Error number: [MY-011640](#); Symbol: [ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP](#); SQLSTATE: [HY000](#)

Message: Timeout on wait for view after joining group
 - Error number: [MY-011641](#); Symbol: [ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE](#); SQLSTATE: [HY000](#)

Message: Error calling group communication interfaces
 - Error number: [MY-011642](#); Symbol: [ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP](#); SQLSTATE: [HY000](#)

Message: Member server_uuid is incompatible with the group. Server_uuid %s matches group_replication_group_name %s.
 - Error number: [MY-011643](#); Symbol: [ER_GRP_RPL_MEMBER_CONF_INFO](#); SQLSTATE: [HY000](#)

Message: Member configuration: member_id: %lu; member_uuid: "%s"; single-primary mode: "%s"; group_replication_auto_increment_increment: %lu; group_replication_view_change_uuid: "%s";
 - Error number: [MY-011644](#); Symbol: [ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP](#); SQLSTATE: [HY000](#)

Message: Unable to confirm whether the server has left the group or not. Check performance_schema.replication_group_members to check group membership information.
 - Error number: [MY-011645](#); Symbol: [ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING](#); SQLSTATE: [HY000](#)

Message: Skipping leave operation: concurrent attempt to leave the group is on-going.
 - Error number: [MY-011646](#); Symbol: [ER_GRP_RPL_SERVER_ALREADY_LEFT](#); SQLSTATE: [HY000](#)

Message: Skipping leave operation: member already left the group.
 - Error number: [MY-011647](#); Symbol: [ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE](#); SQLSTATE: [HY000](#)

Message: Going to wait for view modification
 - Error number: [MY-011648](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: While leaving the group due to a stop, shutdown or failure there was a timeout receiving a view change. This can lead to a possible inconsistent state. Check the log for more details
 - Error number: [MY-011649](#); Symbol: [ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE](#); SQLSTATE: [HY000](#)

Message: Requesting to leave the group despite of not being a member

-
- Error number: [MY-011650](#); Symbol: [ER_GRP_RPL_IS_STOPPING](#); SQLSTATE: [HY000](#)
Message: Plugin 'group_replication' is stopping.
 - Error number: [MY-011651](#); Symbol: [ER_GRP_RPL_IS_STOPPED](#); SQLSTATE: [HY000](#)
Message: Plugin 'group_replication' has been stopped.
 - Error number: [MY-011652](#); Symbol: [ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: On plugin shutdown it was not possible to enable the server read only mode. Local transactions will be accepted and committed.
 - Error number: [MY-011653](#); Symbol: [ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: On shutdown there was a timeout on the Group Replication recovery module termination. Check the log for more details
 - Error number: [MY-011654](#); Symbol: [ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: On shutdown there was a timeout on the Group Replication applier termination.
 - Error number: [MY-011655](#); Symbol: [ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE](#); SQLSTATE: [HY000](#)
Message: Unexpected failure while shutting down registry module!
 - Error number: [MY-011656](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_HANDLER](#); SQLSTATE: [HY000](#)
Message: Failure during Group Replication handler initialization
 - Error number: [MY-011657](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER](#); SQLSTATE: [HY000](#)
Message: Failure when registering the server state observers
 - Error number: [MY-011658](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER](#); SQLSTATE: [HY000](#)
Message: Failure when registering the transactions state observers
 - Error number: [MY-011659](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER](#); SQLSTATE: [HY000](#)
Message: Failure when registering the binlog state observers
 - Error number: [MY-011660](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_ON_BOOT](#); SQLSTATE: [HY000](#)
Message: Unable to start Group Replication on boot
 - Error number: [MY-011661](#); Symbol: [ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL](#); SQLSTATE: [HY000](#)
Message: Failure when stopping Group Replication on plugin uninstall
 - Error number: [MY-011662](#); Symbol: [ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER](#); SQLSTATE: [HY000](#)
-

Message: Failure when unregistering the server state observers

- Error number: [MY-011663](#); Symbol: [ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when unregistering the transactions state observers

- Error number: [MY-011664](#); Symbol: [ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when unregistering the binlog state observers

- Error number: [MY-011665](#); Symbol: [ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED](#); SQLSTATE: [HY000](#)

Message: All Group Replication server observers have been successfully unregistered

- Error number: [MY-011666](#); Symbol: [ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME](#); SQLSTATE: [HY000](#)

Message: Unable to parse the group_replication_group_name.

- Error number: [MY-011667](#); Symbol: [ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP](#); SQLSTATE: [HY000](#)

Message: Unable to parse the group_replication_group_name.

- Error number: [MY-011668](#); Symbol: [ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_PREV_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Cannot start the Group Replication applier as a previous shutdown is still running: The thread will stop once its task is complete.

- Error number: [MY-011669](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the Group Replication applier module.

- Error number: [MY-011670](#); Symbol: [ER_GRP_RPL_APPLIER_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: Group Replication applier module successfully initialized!

- Error number: [MY-011671](#); Symbol: [ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO](#); SQLSTATE: [HY000](#)

Message: Group communication SSL configuration: group_replication_ssl_mode: "%s"; server_key_file: "%s"; server_cert_file: "%s"; client_key_file: "%s"; client_cert_file: "%s"; ca_file: "%s"; ca_path: "%s"; cipher: "%s"; tls_version: "%s"; tls_ciphersuites: "%s"; crl_file: "%s"; crl_path: "%s"; ssl_fips_mode: "%s"

- Error number: [MY-011672](#); Symbol: [ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQLD](#); SQLSTATE: [HY000](#)

Message: MySQL server does not have SSL support and group_replication_ssl_mode is "%s", START GROUP_REPLICATION will abort

- Error number: [MY-011673](#); Symbol: [ER_GRP_RPL_SSL_DISABLED](#); SQLSTATE: [HY000](#)

Message: Group communication SSL configuration: group_replication_ssl_mode: "%s"

- Error number: [MY-011674](#); Symbol: [ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the group communication engine

- Error number: [MY-011675](#); Symbol: [ER_GRP_RPL_BINLOG_DISABLED](#); SQLSTATE: [HY000](#)

Message: Binlog must be enabled for Group Replication

- Error number: [MY-011676](#); Symbol: [ER_GRP_RPL_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: Gtid mode should be ON for Group Replication

- Error number: [MY-011677](#); Symbol: [ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET](#); SQLSTATE: [HY000](#)

Message: LOG_REPLICA_UPDATES should be ON for Group Replication

- Error number: [MY-011679](#); Symbol: [ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE](#); SQLSTATE: [HY000](#)

Message: Applier metadata repository must be set to TABLE

- Error number: [MY-011680](#); Symbol: [ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE](#); SQLSTATE: [HY000](#)

Message: Connection metadata repository must be set to TABLE.

- Error number: [MY-011682](#); Symbol: [ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Group Replication requires replica-preserve-commit-order to be set to ON when using more than 1 applier threads.

- Error number: [MY-011683](#); Symbol: [ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_UPDATE_EVERYWHERE](#); SQLSTATE: [HY000](#)

Message: It is not allowed to run single primary mode with 'group_replication_enforce_update_everywhere_checks' enabled.

- Error number: [MY-011684](#); Symbol: [ER_GRP_RPL_MODULE_TERMINATE_ERROR](#); SQLSTATE: [HY000](#)

Message: error_message: %s

- Error number: [MY-011685](#); Symbol: [ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name option is mandatory

- Error number: [MY-011686](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name '%s' is not a valid UUID, its length is too big

- Error number: [MY-011687](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name '%s' is not a valid UUID

- Error number: [MY-011688](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_min_quota cannot be larger than group_replication_flow_control_max_quota

-
- Error number: [MY-011689](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_min_recovery_quota cannot be larger than group_replication_flow_control_max_quota
 - Error number: [MY-011690](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_max_quota cannot be smaller than group_replication_flow_control_min_quota or group_replication_flow_control_min_recovery_quota
 - Error number: [MY-011691](#); Symbol: [ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING](#); SQLSTATE: [HY000](#)

Message: The given value for recovery ssl option 'group_replication_%s' is invalid as its length is beyond the limit
 - Error number: [MY-011694](#); Symbol: [ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF](#); SQLSTATE: [HY000](#)

Message: Initialized group communication with configuration: group_replication_group_name: '%s'; group_replication_local_address: '%s'; group_replication_group_seeds: '%s'; group_replication_bootstrap_group: '%s'; group_replication_poll_spin_loops: %lu; group_replication_compression_threshold: %lu; group_replication_ip_allowlist: '%s'; group_replication_communication_debug_options: '%s'; group_replication_member_expel_timeout: '%lu'; group_replication_communication_max_message_size: %lu; group_replication_message_cache_size: %lu; group_replication_communication_stack: '%lu'
 - Error number: [MY-011695](#); Symbol: [ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED](#); SQLSTATE: [HY000](#)

Message: Unknown group replication applier pipeline requested
 - Error number: [MY-011696](#); Symbol: [ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE](#); SQLSTATE: [HY000](#)

Message: Unable to bootstrap group replication event handling infrastructure. Unknown handler type: %d
 - Error number: [MY-011697](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: One of the group replication applier handlers is null due to an initialization error
 - Error number: [MY-011698](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE](#); SQLSTATE: [HY000](#)

Message: A group replication applier handler, marked as unique, is already in use.
 - Error number: [MY-011699](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE](#); SQLSTATE: [HY000](#)

Message: A group replication applier handler role, that was marked as unique, is already in use.
 - Error number: [MY-011700](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER](#); SQLSTATE: [HY000](#)

Message: Error on group replication applier handler initialization
-

-
- Error number: [MY-011701](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD](#); SQLSTATE: [HY000](#)

Message: Error when initializing a session thread for internal server connection.
 - Error number: [MY-011702](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. The internal server communication session is not initialized
 - Error number: [MY-011703](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. The internal server session was killed or server is shutting down.
 - Error number: [MY-011704](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. Got internal SQL error: %s(%d)
 - Error number: [MY-011705](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. Internal failure.
 - Error number: [MY-011706](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE](#); SQLSTATE: [HY000](#)

Message: Error, maximum number of retries exceeded when waiting for the internal server session state to be operating
 - Error number: [MY-011707](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Error when trying to fetch security context when contacting the server for internal plugin requests.
 - Error number: [MY-011708](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER](#); SQLSTATE: [HY000](#)

Message: There was an error when trying to access the server with user: %s. Make sure the user is present in the server and that the MySQL upgrade procedure was run correctly.
 - Error number: [MY-011709](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER](#); SQLSTATE: [HY000](#)

Message: Failed to establish an internal server connection to execute plugin operations since the server does not have available connections, please increase @@GLOBAL.MAX_CONNECTIONS. Server error: %i.
 - Error number: [MY-011710](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN](#); SQLSTATE: [HY000](#)

Message: Failed to establish an internal server connection to execute plugin operations. Server error: %i. Server error message: %s
-

-
- Error number: [MY-011711](#); Symbol: [ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER](#); SQLSTATE: [HY000](#)

Message: This member could not reach a majority of the members for more than %ld seconds. The member will now leave the group as instructed by the group_replication_unreachable_majority_timeout option.
 - Error number: [MY-011712](#); Symbol: [ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS](#); SQLSTATE: [HY000](#)

Message: The server was automatically set into read only mode after an error was detected.
 - Error number: [MY-011713](#); Symbol: [ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION](#); SQLSTATE: [HY000](#)

Message: Unable to log notification to table (errno: %lu) (res: %d)! Message: %s
 - Error number: [MY-011714](#); Symbol: [ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failure in group communication engine '%s' initialization
 - Error number: [MY-011715](#); Symbol: [ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to set the group communication engine logger
 - Error number: [MY-011716](#); Symbol: [ER_GRP_RPL_DEBUG_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Current debug options are: '%s'.
 - Error number: [MY-011717](#); Symbol: [ER_GRP_RPL_INVALID_DEBUG_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Some debug options in '%s' are not valid.
 - Error number: [MY-011718](#); Symbol: [ER_GRP_RPL_EXIT_GRP_GCS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error calling group communication interfaces while trying to leave the group
 - Error number: [MY-011719](#); Symbol: [ER_GRP_RPL_GRP_MEMBER_OFFLINE](#); SQLSTATE: [HY000](#)

Message: Member is not ONLINE, it is not possible to force a new group membership
 - Error number: [MY-011720](#); Symbol: [ER_GRP_RPL_GCS_INTERFACE_ERROR](#); SQLSTATE: [HY000](#)

Message: Error calling group communication interfaces
 - Error number: [MY-011721](#); Symbol: [ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR](#); SQLSTATE: [HY000](#)

Message: Error setting group_replication_force_members value '%s' on group communication interfaces
 - Error number: [MY-011722](#); Symbol: [ER_GRP_RPL_FORCE_MEMBER_VALUE_SET](#); SQLSTATE: [HY000](#)

Message: The group_replication_force_members value '%s' was set in the group communication interfaces

-
- Error number: [MY-011723](#); Symbol: [ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT](#); SQLSTATE: [HY000](#)

Message: Timeout on wait for view after setting group_replication_force_members value '%s' into group communication interfaces
 - Error number: [MY-011724](#); Symbol: [ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Broadcast of committed transactions message failed. Message is too big.
 - Error number: [MY-011725](#); Symbol: [ER_GRP_RPL_SEND_STATS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while sending stats message
 - Error number: [MY-011726](#); Symbol: [ER_GRP_RPL_MEMBER_STATS_INFO](#); SQLSTATE: [HY000](#)

Message: Flow control - update member stats: %s stats certifier_queue %d, applier_queue %d certified %ld (%ld), applied %ld (%ld), local %ld (%ld), quota %ld (%ld) mode=%d
 - Error number: [MY-011727](#); Symbol: [ER_GRP_RPL_FLOW_CONTROL_STATS](#); SQLSTATE: [HY000](#)

Message: Flow control: throttling to %ld commits per %ld sec, with %d writing and %d non-recovering members, min capacity %ld, lim throttle %ld
 - Error number: [MY-011728](#); Symbol: [ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to convert a packet into an event on the applier. Error: %s
 - Error number: [MY-011729](#); Symbol: [ER_GRP_RPL_PIPELINE_CREATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create group replication pipeline cache.
 - Error number: [MY-011730](#); Symbol: [ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE](#); SQLSTATE: [HY000](#)

Message: Failed to reinit group replication pipeline cache for write.
 - Error number: [MY-011731](#); Symbol: [ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET](#); SQLSTATE: [HY000](#)

Message: Unable to convert the event into a packet on the applier. Error: %s
 - Error number: [MY-011732](#); Symbol: [ER_GRP_RPL_PIPELINE_FLUSH_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to flush group replication pipeline cache.
 - Error number: [MY-011733](#); Symbol: [ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ](#); SQLSTATE: [HY000](#)

Message: Failed to reinit group replication pipeline cache for read.
 - Error number: [MY-011735](#); Symbol: [ER_GRP_RPL_GCS_GR_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-011736](#); Symbol: [ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED](#); SQLSTATE: [HY000](#)

Message: The replica IO thread of channel '%s' is unblocked as the member is declared ONLINE now.

-
- Error number: [MY-011737](#); Symbol: [ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT](#); SQLSTATE: [HY000](#)

Message: The replica IO thread of channel '%s' will error out as the member failed to come ONLINE.

- Error number: [MY-011738](#); Symbol: [ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED](#); SQLSTATE: [HY000](#)

Message: The replica applier thread of channel '%s' is unblocked as the member is declared ONLINE now.

- Error number: [MY-011739](#); Symbol: [ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT](#); SQLSTATE: [HY000](#)

Message: The replica applier thread of channel '%s' will error out as the member failed to come ONLINE.

- Error number: [MY-011740](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION](#); SQLSTATE: [HY000](#)

Message: LDAP authentication initialize: failed to create/ get connection from the pool.

- Error number: [MY-011741](#); Symbol: [ER_LDAP_AUTH_DEINIT_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP authentication de_initialize Failed

- Error number: [MY-011742](#); Symbol: [ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH](#); SQLSTATE: [HY000](#)

Message: Skipping group search, No group attribute mentioned

- Error number: [MY-011743](#); Symbol: [ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO](#); SQLSTATE: [HY000](#)

Message: Pool max size is 0, connection pool is disabled

- Error number: [MY-011744](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR](#); SQLSTATE: [HY000](#)

Message: Connection pool initialization, failed to create LDAP object creator

- Error number: [MY-011745](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT](#); SQLSTATE: [HY000](#)

Message: Connection pool initialization, failed to create LDAP object

- Error number: [MY-011746](#); Symbol: [ER_LDAP_AUTH_TLS_CONF](#); SQLSTATE: [HY000](#)

Message: LDAP TLS configuration

- Error number: [MY-011747](#); Symbol: [ER_LDAP_AUTH_TLS_CONNECTION](#); SQLSTATE: [HY000](#)

Message: LDAP TLS connection

- Error number: [MY-011748](#); Symbol: [ER_LDAP_AUTH_CONN_POOL_NOT_CREATED](#); SQLSTATE: [HY000](#)

Message: LDAP pool is not created.

- Error number: [MY-011749](#); Symbol: [ER_LDAP_AUTH_CONN_POOL_INITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is initializing

-
- Error number: [MY-011750](#); Symbol: [ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is de-initializing
 - Error number: [MY-011751](#); Symbol: [ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED](#); SQLSTATE: [HY000](#)

Message: Pool max size old and new values are 0
 - Error number: [MY-011752](#); Symbol: [ER_LDAP_AUTH_POOL_REINITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is re-initializing
 - Error number: [MY-011753](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET](#); SQLSTATE: [HY000](#)

Message: Plug-in has failed to write the packet.
 - Error number: [MY-011754](#); Symbol: [ER_LDAP_AUTH_SETTING_USERNAME](#); SQLSTATE: [HY000](#)

Message: Setting LDAP user name as : %s
 - Error number: [MY-011755](#); Symbol: [ER_LDAP_AUTH_USER_AUTH_DATA](#); SQLSTATE: [HY000](#)

Message: User authentication data: %s size: %lu
 - Error number: [MY-011757](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO](#); SQLSTATE: [HY000](#)

Message: Group search information base DN: %s scope: %d filter: %s attribute: %s
 - Error number: [MY-011758](#); Symbol: [ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL](#); SQLSTATE: [HY000](#)

Message: Special handling for group search, {GA} found
 - Error number: [MY-011759](#); Symbol: [ER_LDAP_AUTH_GRP_IS_FULL_DN](#); SQLSTATE: [HY000](#)

Message: Group search special handling, group full DN found.
 - Error number: [MY-011760](#); Symbol: [ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP](#); SQLSTATE: [HY000](#)

Message: User %s is not member of any group.
 - Error number: [MY-011761](#); Symbol: [ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS](#); SQLSTATE: [HY000](#)

Message: User %s is member of more than one group
 - Error number: [MY-011762](#); Symbol: [ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES](#); SQLSTATE: [HY000](#)

Message: For user %s has multiple user group names. Please check if group attribute name is correct
 - Error number: [MY-011763](#); Symbol: [ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME](#); SQLSTATE: [HY000](#)

Message: Searched group name: %s
-

-
- Error number: [MY-011764](#); Symbol: [ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP](#); SQLSTATE: [HY000](#)
 Message: LDAP authentication object creation time_stamp: %s dn: %s
 - Error number: [MY-011765](#); Symbol: [ER_LDAP_AUTH_CERTIFICATE_NAME](#); SQLSTATE: [HY000](#)
 Message: Certificate name: %s
 - Error number: [MY-011766](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT](#); SQLSTATE: [HY000](#)
 Message: Failed to pool de-initialized: pool is already reconstructing
 - Error number: [MY-011767](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING](#); SQLSTATE: [HY000](#)
 Message: Pool initialization failed: pool is already initialized
 - Error number: [MY-011768](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE](#); SQLSTATE: [HY000](#)
 Message: Pool initialization failed: pool is initializing
 - Error number: [MY-011769](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE](#); SQLSTATE: [HY000](#)
 Message: Pool initialization failed: pool is de-initializing
 - Error number: [MY-011770](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE](#); SQLSTATE: [HY000](#)
 Message: Failed to pool deinitialized: pool is already reconstructing
 - Error number: [MY-011771](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL](#); SQLSTATE: [HY000](#)
 Message: Failed to pool deinitialized : pool is not ready
 - Error number: [MY-011772](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY](#); SQLSTATE: [HY000](#)
 Message: Ldap_connection_pool::get: Failed to return connection as plug-in is not ready/initializing/de-initializing
 - Error number: [MY-011773](#); Symbol: [ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED](#); SQLSTATE: [HY000](#)
 Message: Connection pool has failed to initialized
 - Error number: [MY-011774](#); Symbol: [ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT](#); SQLSTATE: [HY000](#)
 Message: Ldap_connexion_pool::get LDAP maximum connection allowed size is reached. Increase the maximum limit.
 - Error number: [MY-011775](#); Symbol: [ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED](#); SQLSTATE: [HY000](#)
 Message: Set max pool size failed.
 - Error number: [MY-011776](#); Symbol: [ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET](#); SQLSTATE: [HY000](#)

Message: Plug-in has failed to read the packet from client

- Error number: MY-011777; Symbol: ER_LDAP_AUTH_CREATING_LDAP_CONNECTION; SQLSTATE: HY000

Message: Ldap_authentication::initialize: creating new LDAP connection.

- Error number: MY-011778; Symbol: ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL; SQLSTATE: HY000

Message: Ldap_authentication::initialize: getting connection from pool.

- Error number: MY-011779; Symbol: ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL; SQLSTATE: HY000

Message: Ldap_authentication::de_initialize putting back connection in the pool

- Error number: MY-011780; Symbol: ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND; SQLSTATE: HY000

Message: Ldap_authentication::search_user_group no group attribute found

- Error number: MY-011781; Symbol: ER_LDAP_AUTH_LDAP_INFO_NULL; SQLSTATE: HY000

Message: Ldap_connection_pool::put ldap info null

- Error number: MY-011782; Symbol: ER_LDAP_AUTH_FREEING_CONNECTION; SQLSTATE: HY000

Message: Ldap_connection_pool::put connection is freeing.

- Error number: MY-011783; Symbol: ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL; SQLSTATE: HY000

Message: Ldap_connection_pool::put connection in pushed in the pool

- Error number: MY-011784; Symbol: ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER; SQLSTATE: HY000

Message: Ldap_connection_creator::Ldap_connection_creator

- Error number: MY-011785; Symbol: ER_LDAP_AUTH_STARTING_TLS; SQLSTATE: HY000

Message: starting TLS

- Error number: MY-011786; Symbol: ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL; SQLSTATE: HY000

Message: Ldap_connection_pool::get: (ldap_info == NULL)|| (*ldap_info)

- Error number: MY-011787; Symbol: ER_LDAP_AUTH_DELETING_CONNECTION_KEY; SQLSTATE: HY000

Message: Ldap_connection_pool::deinit: deleting connection key %s

- Error number: MY-011788; Symbol: ER_LDAP_AUTH_POOLED_CONNECTION_KEY; SQLSTATE: HY000

Message: Ldap_connection_pool::get pooled connection key: %s

- Error number: MY-011789; Symbol: ER_LDAP_AUTH_CREATE_CONNECTION_KEY; SQLSTATE: HY000

Message: Ldap_connection_pool::get create connection key: %s

-
- Error number: [MY-011790](#); Symbol: [ER_LDAP_AUTH_COMMUNICATION_HOST_INFO](#); SQLSTATE: [HY000](#)
Message: LDAP communication host %s port %u
 - Error number: [MY-011791](#); Symbol: [ER_LDAP_AUTH_METHOD_TO_CLIENT](#); SQLSTATE: [HY000](#)
Message: Sending authentication method to client : %s
 - Error number: [MY-011792](#); Symbol: [ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT](#); SQLSTATE: [HY000](#)
Message: SASL request received from mysql client: %s
 - Error number: [MY-011793](#); Symbol: [ER_LDAP_AUTH_SASL_PROCESS_SASL](#); SQLSTATE: [HY000](#)
Message: Ldap_sasl_authentication::process_sasl rc: %s
 - Error number: [MY-011794](#); Symbol: [ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO](#); SQLSTATE: [HY000](#)
Message: Ldap_sasl_authentication::process_sasl sasl bind succeed. dn: %s method: %s server credential: %s
 - Error number: [MY-011795](#); Symbol: [ER_LDAP_AUTH_STARTED_FOR_USER](#); SQLSTATE: [HY000](#)
Message: LDAP authentication started for user name: %s
 - Error number: [MY-011796](#); Symbol: [ER_LDAP_AUTH_DISTINGUISHED_NAME](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011797](#); Symbol: [ER_LDAP_AUTH_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: LDAP authentication initialize is failed with: %s
 - Error number: [MY-011798](#); Symbol: [ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED](#); SQLSTATE: [HY000](#)
Message: LDAP authentication failed or group retrieval failed: %s
 - Error number: [MY-011799](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED](#); SQLSTATE: [HY000](#)
Message: Search user group has failed: %s
 - Error number: [MY-011800](#); Symbol: [ER_LDAP_AUTH_USER_BIND_FAILED](#); SQLSTATE: [HY000](#)
Message: LDAP user bind has failed: %s
 - Error number: [MY-011801](#); Symbol: [ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Connection pool get: Failed to create LDAP connection. %s
 - Error number: [MY-011802](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Failed to create new LDAP connection: %s
 - Error number: [MY-011803](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Failed to establish TLS connection: %s

-
- Error number: [MY-011804](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_SEARCH_DN](#); SQLSTATE: [HY000](#)
Message: Failed to search user full dn: %s
 - Error number: [MY-011805](#); Symbol: [ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::reinit
 - Error number: [MY-011806](#); Symbol: [ER_SYSTEMD_NOTIFY_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: The path '%s', from the NOTIFY_SOCKET environment variable, is too long. At %u bytes it exceeds the limit of %u bytes for an AF_UNIX socket.
 - Error number: [MY-011807](#); Symbol: [ER_SYSTEMD_NOTIFY_CONNECT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to connect to systemd notification socket named %s. Error: '%s'
 - Error number: [MY-011808](#); Symbol: [ER_SYSTEMD_NOTIFY_WRITE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to write '%s' to systemd notification. Error: '%s'
 - Error number: [MY-011809](#); Symbol: [ER_FOUND_MISSING_GTIDS](#); SQLSTATE: [HY000](#)
Message: Cannot replicate to server with server_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere, or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.
 - Error number: [MY-011810](#); Symbol: [ER_PID_FILE_PRIV_DIRECTORY_INSECURE](#); SQLSTATE: [HY000](#)
Message: Insecure configuration for --pid-file: Location '%s' in the path is accessible to all OS users. Consider choosing a different directory.
 - Error number: [MY-011811](#); Symbol: [ER_CANT_CHECK_PID_PATH](#); SQLSTATE: [HY000](#)
Message: Can't start server: can't check PID filepath: %s
 - Error number: [MY-011812](#); Symbol: [ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)
Message: validate_password status variables registration failed.
 - Error number: [MY-011813](#); Symbol: [ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED](#); SQLSTATE: [HY000](#)
Message: validate_password status variables unregistration failed.
 - Error number: [MY-011814](#); Symbol: [ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED](#); SQLSTATE: [HY000](#)
Message: Dictionary file open failed
 - Error number: [MY-011815](#); Symbol: [ER_VALIDATE_PWD_COULD_BE_NULL](#); SQLSTATE: [HY000](#)
Message: given password string could be null
 - Error number: [MY-011816](#); Symbol: [ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED](#); SQLSTATE: [HY000](#)
Message: failed to convert the password string to lower case

-
- Error number: [MY-011817](#); Symbol: [ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED](#); SQLSTATE: [HY000](#)
Message: failed to convert the password string into a buffer
 - Error number: [MY-011818](#); Symbol: [ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED](#); SQLSTATE: [HY000](#)
Message: memory allocation failed for string handler
 - Error number: [MY-011819](#); Symbol: [ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED](#); SQLSTATE: [HY000](#)
Message: Since the validate_password_policy is mentioned as Strong, dictionary file must be specified
 - Error number: [MY-011820](#); Symbol: [ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED](#); SQLSTATE: [HY000](#)
Message: convert_to_buffer service failed
 - Error number: [MY-011821](#); Symbol: [ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)
Message: %s variable registration failed.
 - Error number: [MY-011822](#); Symbol: [ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED](#); SQLSTATE: [HY000](#)
Message: %s variable unregistration failed.
 - Error number: [MY-011823](#); Symbol: [ER_KEYRING_MIGRATION_EXTRA_OPTIONS](#); SQLSTATE: [HY000](#)
Message: Please specify options specific to keyring migration. Any additional options can be ignored.
NOTE: Although some options are valid, migration tool can still report error example: plugin variables for which plugin is not loaded yet.
 - Error number: [MY-011825](#); Symbol: [ER_IB_MSG_0](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011826](#); Symbol: [ER_IB_MSG_1](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011827](#); Symbol: [ER_IB_MSG_2](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011828](#); Symbol: [ER_IB_MSG_3](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011829](#); Symbol: [ER_IB_MSG_4](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011830](#); Symbol: [ER_IB_MSG_5](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011831](#); Symbol: [ER_IB_MSG_6](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011832](#); Symbol: [ER_IB_MSG_7](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011833](#); Symbol: [ER_IB_MSG_8](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011834](#); Symbol: [ER_IB_MSG_9](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011835](#); Symbol: [ER_IB_MSG_10](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011836](#); Symbol: [ER_IB_MSG_11](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011837](#); Symbol: [ER_IB_MSG_12](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011838](#); Symbol: [ER_IB_MSG_13](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011839](#); Symbol: [ER_IB_MSG_14](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011840](#); Symbol: [ER_IB_MSG_15](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011841](#); Symbol: [ER_IB_MSG_16](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011842](#); Symbol: [ER_IB_MSG_17](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011843](#); Symbol: [ER_IB_MSG_18](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011844](#); Symbol: [ER_IB_MSG_19](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011845](#); Symbol: [ER_IB_MSG_20](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011846](#); Symbol: [ER_IB_MSG_21](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011847](#); Symbol: [ER_IB_MSG_22](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011848](#); Symbol: [ER_IB_MSG_23](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011849](#); Symbol: [ER_IB_MSG_24](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011850](#); Symbol: [ER_IB_MSG_25](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011851](#); Symbol: [ER_IB_MSG_26](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011852](#); Symbol: [ER_IB_MSG_27](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011853](#); Symbol: [ER_IB_MSG_28](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011854](#); Symbol: [ER_IB_MSG_29](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011855](#); Symbol: [ER_IB_MSG_30](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011857](#); Symbol: [ER_IB_MSG_32](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011858](#); Symbol: [ER_IB_MSG_33](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011859](#); Symbol: [ER_IB_MSG_34](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011860](#); Symbol: [ER_IB_MSG_35](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011861](#); Symbol: [ER_IB_MSG_36](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011862](#); Symbol: [ER_IB_MSG_37](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011863](#); Symbol: [ER_IB_MSG_38](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011864](#); Symbol: [ER_IB_MSG_39](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011865](#); Symbol: [ER_IB_MSG_40](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011866](#); Symbol: [ER_IB_MSG_41](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011867](#); Symbol: [ER_IB_MSG_42](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011868](#); Symbol: [ER_IB_MSG_43](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011869](#); Symbol: [ER_IB_MSG_44](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011870](#); Symbol: [ER_IB_MSG_45](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011871](#); Symbol: [ER_IB_MSG_46](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011872](#); Symbol: [ER_IB_MSG_47](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011873](#); Symbol: [ER_IB_MSG_48](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011874](#); Symbol: [ER_IB_MSG_49](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011875](#); Symbol: [ER_IB_MSG_50](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011876](#); Symbol: [ER_IB_MSG_51](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011877](#); Symbol: [ER_IB_MSG_52](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011878](#); Symbol: [ER_IB_MSG_53](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011879](#); Symbol: [ER_IB_MSG_54](#); SQLSTATE: [HY000](#)

Message: Failed to set NUMA memory policy of buffer pool page frames with mbind(%p,%zu,
%s,...,%s) failed with %s

- Error number: [MY-011880](#); Symbol: [ER_IB_MSG_55](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011881](#); Symbol: [ER_IB_MSG_56](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011882](#); Symbol: [ER_IB_MSG_57](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011883](#); Symbol: [ER_IB_MSG_58](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011884](#); Symbol: [ER_IB_MSG_59](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011885](#); Symbol: [ER_IB_MSG_60](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011886](#); Symbol: [ER_IB_MSG_61](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011887](#); Symbol: [ER_IB_MSG_62](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011888](#); Symbol: [ER_IB_MSG_63](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011889](#); Symbol: [ER_IB_MSG_64](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011890](#); Symbol: [ER_IB_MSG_65](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011891](#); Symbol: [ER_IB_MSG_66](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011892](#); Symbol: [ER_IB_MSG_67](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011893](#); Symbol: [ER_IB_MSG_68](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011894](#); Symbol: [ER_IB_MSG_69](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011895](#); Symbol: [ER_IB_MSG_70](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011896](#); Symbol: [ER_IB_MSG_71](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-011897](#); Symbol: [ER_IB_MSG_72](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011898](#); Symbol: [ER_IB_MSG_73](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011899](#); Symbol: [ER_IB_MSG_74](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011900](#); Symbol: [ER_IB_MSG_75](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011901](#); Symbol: [ER_IB_MSG_76](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011902](#); Symbol: [ER_IB_MSG_77](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011903](#); Symbol: [ER_IB_MSG_78](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011904](#); Symbol: [ER_IB_MSG_79](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011905](#); Symbol: [ER_IB_MSG_80](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011906](#); Symbol: [ER_IB_MSG_81](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011907](#); Symbol: [ER_IB_MSG_82](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011908](#); Symbol: [ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Page still fixed or dirty at shutdown. %s
 - Error number: [MY-011909](#); Symbol: [ER_IB_MSG_84](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011910](#); Symbol: [ER_IB_MSG_85](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011911](#); Symbol: [ER_IB_MSG_86](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011920](#); Symbol: [ER_IB_MSG_95](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011921](#); Symbol: [ER_IB_MSG_96](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011922](#); Symbol: [ER_IB_MSG_97](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011923](#); Symbol: [ER_IB_MSG_98](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011924](#); Symbol: [ER_IB_MSG_99](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011925](#); Symbol: [ER_IB_MSG_100](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011926](#); Symbol: [ER_IB_MSG_101](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011927](#); Symbol: [ER_IB_MSG_102](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011928](#); Symbol: [ER_IB_MSG_103](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011929](#); Symbol: [ER_IB_MSG_104](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011930](#); Symbol: [ER_IB_MSG_105](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011931](#); Symbol: [ER_IB_MSG_106](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011932](#); Symbol: [ER_IB_MSG_107](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011933](#); Symbol: [ER_IB_MSG_108](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011934](#); Symbol: [ER_IB_MSG_109](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011935](#); Symbol: [ER_IB_MSG_110](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011936](#); Symbol: [ER_IB_MSG_111](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011937](#); Symbol: [ER_IB_MSG_112](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011944](#); Symbol: [ER_IB_MSG_119](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011945](#); Symbol: [ER_IB_MSG_120](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011946](#); Symbol: [ER_IB_MSG_121](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011947](#); Symbol: [ER_IB_MSG_122](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011948](#); Symbol: [ER_IB_MSG_123](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011949](#); Symbol: [ER_IB_MSG_124](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011950](#); Symbol: [ER_IB_MSG_125](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011951](#); Symbol: [ER_IB_MSG_126](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011952](#); Symbol: [ER_IB_MSG_127](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011953](#); Symbol: [ER_IB_MSG_128](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011954](#); Symbol: [ER_IB_MSG_129](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011955](#); Symbol: [ER_IB_MSG_130](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011956](#); Symbol: [ER_IB_MSG_131](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011957](#); Symbol: [ER_IB_MSG_132](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011958](#); Symbol: [ER_IB_MSG_133](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011959](#); Symbol: [ER_IB_MSG_134](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011960](#); Symbol: [ER_IB_MSG_135](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011961](#); Symbol: [ER_IB_MSG_136](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011962](#); Symbol: [ER_IB_MSG_137](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011963](#); Symbol: [ER_IB_MSG_138](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011964](#); Symbol: [ER_IB_MSG_139](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011965](#); Symbol: [ER_IB_MSG_140](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011966](#); Symbol: [ER_IB_MSG_141](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011967](#); Symbol: [ER_IB_MSG_142](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011968](#); Symbol: [ER_IB_MSG_143](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011969](#); Symbol: [ER_IB_MSG_144](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011970](#); Symbol: [ER_IB_MSG_145](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011971](#); Symbol: [ER_IB_MSG_146](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011972](#); Symbol: [ER_IB_MSG_147](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011973](#); Symbol: [ER_IB_MSG_148](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011974](#); Symbol: [ER_IB_CLONE_INTERNAL](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011975](#); Symbol: [ER_IB_CLONE_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011976](#); Symbol: [ER_IB_CLONE_STATUS_FILE](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011977](#); Symbol: [ER_IB_CLONE_SQL](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011978](#); Symbol: [ER_IB_CLONE_VALIDATE](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011979](#); Symbol: [ER_IB_CLONE_PUNCH_HOLE](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011980](#); Symbol: [ER_IB_CLONE_GTID_PERSIST](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011981](#); Symbol: [ER_IB_MSG_156](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011982](#); Symbol: [ER_IB_MSG_157](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011983](#); Symbol: [ER_IB_MSG_158](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011984](#); Symbol: [ER_IB_MSG_159](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011985](#); Symbol: [ER_IB_MSG_160](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011986](#); Symbol: [ER_IB_MSG_161](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011987](#); Symbol: [ER_IB_MSG_162](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011988](#); Symbol: [ER_IB_MSG_163](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011989](#); Symbol: [ER_IB_MSG_164](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011990](#); Symbol: [ER_IB_MSG_165](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011991](#); Symbol: [ER_IB_MSG_166](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011992](#); Symbol: [ER_IB_MSG_167](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011993](#); Symbol: [ER_IB_MSG_168](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011994](#); Symbol: [ER_IB_MSG_169](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011995](#); Symbol: [ER_IB_MSG_170](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011996](#); Symbol: [ER_IB_MSG_171](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011997](#); Symbol: [ER_IB_MSG_172](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011998](#); Symbol: [ER_IB_MSG_173](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011999](#); Symbol: [ER_IB_MSG_174](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012000](#); Symbol: [ER_IB_MSG_175](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012002](#); Symbol: [ER_IB_MSG_177](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012003](#); Symbol: [ER_IB_MSG_178](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012004](#); Symbol: [ER_IB_MSG_179](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012005](#); Symbol: [ER_IB_MSG_180](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012006](#); Symbol: [ER_IB_LONG_AHI_DISABLE_WAIT](#); SQLSTATE: [HY000](#)

Message: Waited for %u secs for hash index ref_count (%zu) to drop to 0. index: "%s" table: "%s"

- Error number: [MY-012007](#); Symbol: [ER_IB_MSG_182](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012008](#); Symbol: [ER_IB_MSG_183](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012009](#); Symbol: [ER_IB_MSG_184](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012012](#); Symbol: [ER_IB_MSG_187](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012013](#); Symbol: [ER_IB_MSG_188](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012014](#); Symbol: [ER_IB_MSG_189](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012015](#); Symbol: [ER_IB_MSG_190](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012016](#); Symbol: [ER_IB_MSG_191](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012017](#); Symbol: [ER_IB_MSG_192](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012018](#); Symbol: [ER_IB_MSG_193](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012019](#); Symbol: [ER_IB_MSG_194](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012020](#); Symbol: [ER_IB_MSG_195](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012021](#); Symbol: [ER_IB_MSG_196](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012022](#); Symbol: [ER_IB_MSG_197](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012023](#); Symbol: [ER_IB_MSG_198](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012024](#); Symbol: [ER_IB_MSG_199](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012025](#); Symbol: [ER_IB_MSG_200](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012026](#); Symbol: [ER_IB_MSG_201](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012027](#); Symbol: [ER_IB_MSG_202](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012028](#); Symbol: [ER_IB_MSG_203](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012029](#); Symbol: [ER_IB_MSG_204](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012030](#); Symbol: [ER_IB_MSG_205](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012031](#); Symbol: [ER_IB_MSG_206](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012032](#); Symbol: [ER_IB_MSG_207](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012033](#); Symbol: [ER_IB_MSG_208](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012034](#); Symbol: [ER_IB_MSG_209](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012035](#); Symbol: [ER_IB_MSG_210](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012036](#); Symbol: [ER_IB_MSG_211](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012037](#); Symbol: [ER_IB_MSG_212](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012038](#); Symbol: [ER_IB_MSG_213](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012039](#); Symbol: [ER_IB_MSG_214](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012040](#); Symbol: [ER_IB_MSG_215](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012041](#); Symbol: [ER_IB_MSG_216](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012042](#); Symbol: [ER_IB_MSG_217](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012043](#); Symbol: [ER_IB_MSG_218](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012044](#); Symbol: [ER_IB_MSG_219](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012045](#); Symbol: [ER_IB_MSG_220](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012046](#); Symbol: [ER_IB_MSG_221](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012047](#); Symbol: [ER_IB_MSG_222](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012048](#); Symbol: [ER_IB_MSG_223](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012049](#); Symbol: [ER_IB_MSG_224](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012050](#); Symbol: [ER_IB_MSG_225](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012051](#); Symbol: [ER_IB_MSG_226](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012054](#); Symbol: [ER_IB_MSG_229](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012055](#); Symbol: [ER_IB_MSG_230](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012056](#); Symbol: [ER_IB_MSG_231](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012057](#); Symbol: [ER_IB_MSG_232](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012058](#); Symbol: [ER_IB_MSG_233](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012059](#); Symbol: [ER_IB_MSG_234](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012060](#); Symbol: [ER_IB_MSG_235](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012061](#); Symbol: [ER_IB_MSG_236](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012062](#); Symbol: [ER_IB_MSG_237](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012063](#); Symbol: [ER_IB_MSG_238](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012064](#); Symbol: [ER_IB_MSG_239](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012065](#); Symbol: [ER_IB_MSG_240](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012066](#); Symbol: [ER_IB_MSG_241](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012067](#); Symbol: [ER_IB_MSG_242](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012068](#); Symbol: [ER_IB_MSG_243](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012069](#); Symbol: [ER_IB_MSG_244](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012070](#); Symbol: [ER_IB_MSG_245](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012071](#); Symbol: [ER_IB_MSG_246](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012072](#); Symbol: [ER_IB_MSG_247](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012073](#); Symbol: [ER_IB_MSG_248](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012074](#); Symbol: [ER_IB_MSG_249](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012075](#); Symbol: [ER_IB_MSG_250](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012076](#); Symbol: [ER_IB_MSG_251](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012077](#); Symbol: [ER_IB_MSG_252](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012078](#); Symbol: [ER_IB_MSG_253](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012079](#); Symbol: [ER_IB_MSG_254](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012080](#); Symbol: [ER_IB_MSG_255](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012081](#); Symbol: [ER_IB_MSG_256](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012082](#); Symbol: [ER_IB_MSG_257](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012083](#); Symbol: [ER_IB_MSG_258](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012084](#); Symbol: [ER_IB_MSG_259](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012085](#); Symbol: [ER_IB_MSG_260](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012086](#); Symbol: [ER_IB_MSG_261](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012087](#); Symbol: [ER_IB_MSG_262](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012088](#); Symbol: [ER_IB_MSG_263](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012089](#); Symbol: [ER_IB_MSG_264](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012090](#); Symbol: [ER_IB_MSG_265](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012091](#); Symbol: [ER_IB_MSG_266](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012092](#); Symbol: [ER_IB_MSG_267](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012093](#); Symbol: [ER_IB_MSG_268](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012094](#); Symbol: [ER_IB_MSG_269](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012095](#); Symbol: [ER_IB_MSG_270](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012096](#); Symbol: [ER_IB_MSG_271](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012097](#); Symbol: [ER_IB_MSG_272](#); SQLSTATE: [HY000](#)

Message: Table flags are 0x%lx in the data dictionary but the flags in file %s are 0x%llx!

- Error number: [MY-012098](#); Symbol: [ER_IB_MSG_273](#); SQLSTATE: [HY000](#)

Message: Can't read encryption key from file %s!

- Error number: [MY-012103](#); Symbol: [ER_IB_MSG_278](#); SQLSTATE: [HY000](#)

Message: Tablespace %s, waiting for IO to stop for %lld seconds

- Error number: [MY-012105](#); Symbol: [ER_IB_MSG_280](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012106](#); Symbol: [ER_IB_MSG_281](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012107](#); Symbol: [ER_IB_MSG_282](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012108](#); Symbol: [ER_IB_MSG_283](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012109](#); Symbol: [ER_IB_MSG_284](#); SQLSTATE: [HY000](#)

Message: You must raise the value of innodb_open_files in my.cnf! Remember that InnoDB keeps all redo log files and all system tablespace files open for the whole time mysqld is running, and needs to open also some .ibd files if the file-per-table storage model is used. Current open files %zu, max allowed open files %zu.

- Error number: [MY-012110](#); Symbol: [ER_IB_MSG_285](#); SQLSTATE: [HY000](#)

Message: Max tablespace id is too high, %lu

- Error number: [MY-012111](#); Symbol: [ER_IB_WARN_ACCESSING_NONEXISTINC_SPACE](#); SQLSTATE: [HY000](#)

Message: Trying to access missing tablespace %lu

- Error number: [MY-012112](#); Symbol: [ER_IB_MSG_287](#); SQLSTATE: [HY000](#)

Message: Trying to close/delete tablespace '%s' but there are %lu pending operations on it.

- Error number: [MY-012113](#); Symbol: [ER_IB_MSG_288](#); SQLSTATE: [HY000](#)

Message: Trying to delete/close tablespace '%s' but there are %lu flushes and %zu pending I/O's on it.

- Error number: [MY-012114](#); Symbol: [ER_IB_MSG_289](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012116](#); Symbol: [ER_IB_MSG_291](#); SQLSTATE: [HY000](#)

Message: While deleting tablespace %lu in DISCARD TABLESPACE. File rename/delete failed: %s

- Error number: [MY-012117](#); Symbol: [ER_IB_MSG_292](#); SQLSTATE: [HY000](#)

Message: Cannot delete tablespace %lu in DISCARD TABLESPACE: %s

- Error number: [MY-012118](#); Symbol: [ER_IB_MSG_293](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the source file does not exist.

- Error number: [MY-012119](#); Symbol: [ER_IB_MSG_294](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the target file exists. Remove the target file and try again.

- Error number: [MY-012120](#); Symbol: [ER_IB_MSG_295](#); SQLSTATE: [HY000](#)

Message: Cannot rename file '%s' (space id %lu) retried %llu times. There are either pending IOs or flushes or the file is being extended.

- Error number: [MY-012121](#); Symbol: [ER_IB_MSG_296](#); SQLSTATE: [HY000](#)

Message: Cannot find space id %lu in the tablespace memory cache, though the file '%s' in a rename operation should have that ID.

- Error number: [MY-012122](#); Symbol: [ER_IB_MSG_297](#); SQLSTATE: [HY000](#)

Message: Rename waiting for IO to resume

- Error number: [MY-012123](#); Symbol: [ER_IB_MSG_298](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

- Error number: [MY-012124](#); Symbol: [ER_IB_MSG_299](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

- Error number: [MY-012125](#); Symbol: [ER_IB_MSG_300](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' is already in the tablespace memory cache

- Error number: [MY-012126](#); Symbol: [ER_IB_MSG_301](#); SQLSTATE: [HY000](#)

Message: Cannot create file '%s'

- Error number: [MY-012127](#); Symbol: [ER_IB_MSG_UNEXPECTED_FILE_EXISTS](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT

TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

- Error number: [MY-012128](#); Symbol: [ER_IB_MSG_303](#); SQLSTATE: [HY000](#)

Message: posix_fallocate(): Failed to preallocate data for file %s, desired size %llu Operating system error number %d - %s. Check that the disk is not full or a disk quota exceeded. Make sure the file system supports this function. Refer to your operating system documentation for operating system error code information.

- Error number: [MY-012129](#); Symbol: [ER_IB_MSG_304](#); SQLSTATE: [HY000](#)

Message: Could not write the first page to tablespace '%s'

- Error number: [MY-012130](#); Symbol: [ER_IB_MSG_305](#); SQLSTATE: [HY000](#)

Message: File flush of tablespace '%s' failed

- Error number: [MY-012131](#); Symbol: [ER_IB_MSG_306](#); SQLSTATE: [HY000](#)

Message: Could not find a valid tablespace file for '%s'. %s

- Error number: [MY-012132](#); Symbol: [ER_IB_MSG_307](#); SQLSTATE: [HY000](#)

Message: Ignoring data file '%s' with space ID %lu. Another data file called '%s' exists with the same space ID

- Error number: [MY-012133](#); Symbol: [ER_IB_MSG_308](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012134](#); Symbol: [ER_IB_MSG_309](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012135](#); Symbol: [ER_IB_MSG_310](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012136](#); Symbol: [ER_IB_MSG_311](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012137](#); Symbol: [ER_IB_MSG_312](#); SQLSTATE: [HY000](#)

Message: Can't set encryption information for tablespace %s!

- Error number: [MY-012138](#); Symbol: [ER_IB_MSG_313](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012139](#); Symbol: [ER_IB_MSG_314](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012140](#); Symbol: [ER_IB_MSG_315](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012141](#); Symbol: [ER_IB_MSG_316](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012142](#); Symbol: [ER_IB_MSG_317](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012143](#); Symbol: [ER_IB_MSG_318](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012144](#); Symbol: [ER_IB_MSG_319](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012145](#); Symbol: [ER_IB_MSG_320](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012146](#); Symbol: [ER_IB_MSG_321](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012147](#); Symbol: [ER_IB_MSG_322](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012148](#); Symbol: [ER_IB_MSG_323](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012149](#); Symbol: [ER_IB_MSG_324](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012150](#); Symbol: [ER_IB_MSG_325](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012151](#); Symbol: [ER_IB_MSG_326](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012153](#); Symbol: [ER_IB_MSG_328](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012154](#); Symbol: [ER_IB_MSG_329](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012155](#); Symbol: [ER_IB_MSG_330](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012156](#); Symbol: [ER_IB_MSG_331](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012157](#); Symbol: [ER_IB_MSG_332](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012158](#); Symbol: [ER_IB_MSG_333](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012159](#); Symbol: [ER_IB_MSG_334](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012160](#); Symbol: [ER_IB_MSG_335](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012161](#); Symbol: [ER_IB_MSG_336](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012162](#); Symbol: [ER_IB_MSG_337](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012163](#); Symbol: [ER_IB_MSG_338](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012164](#); Symbol: [ER_IB_MSG_339](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012165](#); Symbol: [ER_IB_MSG_340](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012166](#); Symbol: [ER_IB_MSG_341](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012167](#); Symbol: [ER_IB_MSG_342](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012168](#); Symbol: [ER_IB_MSG_343](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012169](#); Symbol: [ER_IB_MSG_344](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012170](#); Symbol: [ER_IB_MSG_345](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012171](#); Symbol: [ER_IB_MSG_346](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012172](#); Symbol: [ER_IB_MSG_347](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012173](#); Symbol: [ER_IB_MSG_348](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012174](#); Symbol: [ER_IB_MSG_349](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012175](#); Symbol: [ER_IB_MSG_350](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012177](#); Symbol: [ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED](#); SQLSTATE: [HY000](#)

Message: The datafile '%s' for tablespace %s is in an unprotected location. This file cannot be recovered after a crash until this location is added to innodb_directories.

- Error number: [MY-012179](#); Symbol: [ER_IB_MSG_354](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012180](#); Symbol: [ER_IB_MSG_355](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012182](#); Symbol: [ER_IB_MSG_357](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012183](#); Symbol: [ER_IB_MSG_358](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012184](#); Symbol: [ER_IB_MSG_359](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012185](#); Symbol: [ER_IB_MSG_360](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012186](#); Symbol: [ER_IB_MSG_361](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012187](#); Symbol: [ER_IB_MSG_362](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012189](#); Symbol: [ER_IB_MSG_364](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012190](#); Symbol: [ER_IB_MSG_365](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012191](#); Symbol: [ER_IB_MSG_IGNORE_SCAN_PATH](#); SQLSTATE: [HY000](#)

Message: Scan path '%s' is ignored because %s

- Error number: [MY-012192](#); Symbol: [ER_IB_MSG_367](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012193](#); Symbol: [ER_IB_MSG_368](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012194](#); Symbol: [ER_IB_MSG_369](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-012195](#); Symbol: [ER_IB_MSG_370](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012196](#); Symbol: [ER_IB_MSG_371](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012197](#); Symbol: [ER_IB_MSG_372](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012198](#); Symbol: [ER_IB_MSG_373](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012199](#); Symbol: [ER_IB_MSG_374](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012200](#); Symbol: [ER_IB_MSG_375](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012201](#); Symbol: [ER_IB_MSG_376](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012202](#); Symbol: [ER_IB_MSG_377](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012203](#); Symbol: [ER_IB_MSG_378](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012204](#); Symbol: [ER_IB_MSG_379](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012205](#); Symbol: [ER_IB_MSG_380](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012206](#); Symbol: [ER_IB_MSG_381](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012207](#); Symbol: [ER_IB_MSG_382](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012208](#); Symbol: [ER_IB_MSG_383](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012209](#); Symbol: [ER_IB_MSG_384](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012210](#); Symbol: [ER_IB_MSG_385](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012211](#); Symbol: [ER_IB_MSG_386](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012212](#); Symbol: [ER_IB_MSG_387](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012213](#); Symbol: [ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR](#); SQLSTATE: [HY000](#)

Message: A general tablespace cannot be located under the datadir. Cannot open file '%s'.

- Error number: [MY-012214](#); Symbol: [ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR](#); SQLSTATE: [HY000](#)

Message: A file-per-table tablespace cannot be located in the datadir. Cannot open file '%s'.

- Error number: [MY-012215](#); Symbol: [ER_IB_MSG_390](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012216](#); Symbol: [ER_IB_MSG_391](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012217](#); Symbol: [ER_IB_MSG_392](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012218](#); Symbol: [ER_IB_MSG_393](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012219](#); Symbol: [ER_IB_MSG_394](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012220](#); Symbol: [ER_IB_MSG_395](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012221](#); Symbol: [ER_IB_MSG_396](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012222](#); Symbol: [ER_IB_MSG_397](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012223](#); Symbol: [ER_IB_MSG_398](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012224](#); Symbol: [ER_IB_MSG_399](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012226](#); Symbol: [ER_IB_MSG_401](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012227](#); Symbol: [ER_IB_MSG_402](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-012228](#); Symbol: [ER_IB_MSG_403](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012229](#); Symbol: [ER_IB_MSG_404](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012230](#); Symbol: [ER_IB_MSG_405](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012231](#); Symbol: [ER_IB_MSG_406](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012232](#); Symbol: [ER_IB_MSG_407](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012233](#); Symbol: [ER_IB_MSG_408](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012234](#); Symbol: [ER_IB_MSG_409](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012235](#); Symbol: [ER_IB_MSG_410](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012236](#); Symbol: [ER_IB_MSG_411](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012237](#); Symbol: [ER_IB_MSG_412](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012238](#); Symbol: [ER_IB_MSG_413](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012239](#); Symbol: [ER_IB_MSG_414](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012240](#); Symbol: [ER_IB_MSG_415](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012241](#); Symbol: [ER_IB_MSG_416](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012242](#); Symbol: [ER_IB_MSG_417](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012243](#); Symbol: [ER_IB_MSG_418](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012244](#); Symbol: [ER_IB_MSG_419](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012245](#); Symbol: [ER_IB_MSG_420](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012246](#); Symbol: [ER_IB_MSG_421](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012247](#); Symbol: [ER_IB_MSG_422](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012248](#); Symbol: [ER_IB_MSG_423](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012249](#); Symbol: [ER_IB_MSG_424](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012250](#); Symbol: [ER_IB_MSG_425](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012251](#); Symbol: [ER_IB_MSG_426](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012252](#); Symbol: [ER_IB_MSG_427](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012253](#); Symbol: [ER_IB_MSG_428](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012254](#); Symbol: [ER_IB_MSG_429](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012255](#); Symbol: [ER_IB_MSG_430](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012256](#); Symbol: [ER_IB_MSG_431](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012257](#); Symbol: [ER_IB_MSG_432](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012258](#); Symbol: [ER_IB_MSG_433](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012259](#); Symbol: [ER_IB_MSG_434](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012260](#); Symbol: [ER_IB_MSG_435](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012261](#); Symbol: [ER_IB_MSG_436](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012262](#); Symbol: [ER_IB_MSG_437](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012263](#); Symbol: [ER_IB_MSG_438](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012264](#); Symbol: [ER_IB_MSG_439](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012265](#); Symbol: [ER_IB_MSG_440](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012266](#); Symbol: [ER_IB_MSG_441](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012267](#); Symbol: [ER_IB_MSG_442](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012268](#); Symbol: [ER_IB_MSG_443](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012270](#); Symbol: [ER_IB_MSG_445](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012271](#); Symbol: [ER_IB_MSG_446](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012272](#); Symbol: [ER_IB_MSG_447](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012273](#); Symbol: [ER_IB_MSG_448](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012274](#); Symbol: [ER_IB_MSG_449](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012275](#); Symbol: [ER_IB_MSG_450](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012276](#); Symbol: [ER_IB_MSG_451](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012277](#); Symbol: [ER_IB_MSG_452](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012278](#); Symbol: [ER_IB_MSG_453](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012279](#); Symbol: [ER_IB_MSG_454](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012280](#); Symbol: [ER_IB_MSG_455](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012281](#); Symbol: [ER_IB_MSG_456](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012282](#); Symbol: [ER_IB_MSG_457](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012283](#); Symbol: [ER_IB_MSG_458](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012284](#); Symbol: [ER_IB_MSG_459](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012285](#); Symbol: [ER_IB_MSG_460](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012286](#); Symbol: [ER_IB_MSG_461](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012287](#); Symbol: [ER_IB_MSG_462](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012288](#); Symbol: [ER_IB_MSG_463](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012289](#); Symbol: [ER_IB_MSG_464](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012290](#); Symbol: [ER_IB_MSG_465](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012291](#); Symbol: [ER_IB_MSG_466](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012292](#); Symbol: [ER_IB_MSG_467](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012293](#); Symbol: [ER_IB_MSG_468](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012294](#); Symbol: [ER_IB_MSG_469](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012295](#); Symbol: [ER_IB_MSG_470](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012296](#); Symbol: [ER_IB_MSG_471](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012297](#); Symbol: [ER_IB_MSG_472](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012298](#); Symbol: [ER_IB_MSG_473](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012299](#); Symbol: [ER_IB_MSG_474](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012300](#); Symbol: [ER_IB_MSG_475](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012301](#); Symbol: [ER_IB_MSG_476](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012302](#); Symbol: [ER_IB_MSG_477](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012303](#); Symbol: [ER_IB_MSG_478](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012304](#); Symbol: [ER_IB_MSG_479](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012305](#); Symbol: [ER_IB_MSG_480](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012306](#); Symbol: [ER_IB_MSG_481](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012307](#); Symbol: [ER_IB_MSG_482](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012308](#); Symbol: [ER_IB_MSG_483](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012309](#); Symbol: [ER_IB_MSG_484](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012310](#); Symbol: [ER_IB_MSG_485](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012311](#); Symbol: [ER_IB_MSG_486](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012312](#); Symbol: [ER_IB_MSG_487](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012313](#); Symbol: [ER_IB_MSG_488](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012314](#); Symbol: [ER_IB_MSG_489](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012315](#); Symbol: [ER_IB_MSG_490](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012316](#); Symbol: [ER_IB_MSG_491](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012317](#); Symbol: [ER_IB_MSG_492](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012318](#); Symbol: [ER_IB_MSG_493](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012319](#); Symbol: [ER_IB_MSG_494](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012320](#); Symbol: [ER_IB_MSG_495](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012321](#); Symbol: [ER_IB_MSG_496](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012322](#); Symbol: [ER_IB_MSG_497](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012323](#); Symbol: [ER_IB_MSG_498](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012324](#); Symbol: [ER_IB_MSG_499](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012325](#); Symbol: [ER_IB_MSG_500](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012326](#); Symbol: [ER_IB_MSG_501](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012327](#); Symbol: [ER_IB_MSG_502](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012328](#); Symbol: [ER_IB_MSG_503](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012329](#); Symbol: [ER_IB_MSG_504](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012330](#); Symbol: [ER_IB_MSG_505](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012331](#); Symbol: [ER_IB_MSG_506](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012332](#); Symbol: [ER_IB_MSG_507](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012333](#); Symbol: [ER_IB_MSG_508](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012334](#); Symbol: [ER_IB_MSG_509](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012335](#); Symbol: [ER_IB_MSG_510](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012336](#); Symbol: [ER_IB_MSG_511](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012337](#); Symbol: [ER_IB_MSG_512](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012338](#); Symbol: [ER_IB_MSG_513](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012339](#); Symbol: [ER_IB_MSG_514](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012340](#); Symbol: [ER_IB_MSG_515](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012341](#); Symbol: [ER_IB_MSG_516](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012342](#); Symbol: [ER_IB_MSG_517](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012343](#); Symbol: [ER_IB_MSG_518](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012344](#); Symbol: [ER_IB_MSG_519](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012345](#); Symbol: [ER_IB_MSG_520](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012346](#); Symbol: [ER_IB_MSG_521](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012347](#); Symbol: [ER_IB_MSG_522](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012348](#); Symbol: [ER_IB_MSG_523](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012349](#); Symbol: [ER_IB_MSG_524](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012350](#); Symbol: [ER_IB_MSG_525](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012351](#); Symbol: [ER_IB_MSG_526](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012352](#); Symbol: [ER_IB_MSG_527](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012355](#); Symbol: [ER_IB_MSG_530](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012356](#); Symbol: [ER_IB_MSG_531](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012357](#); Symbol: [ER_IB_MSG_532](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012358](#); Symbol: [ER_IB_MSG_533](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012359](#); Symbol: [ER_IB_MSG_534](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012362](#); Symbol: [ER_IB_MSG_537](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012363](#); Symbol: [ER_IB_MSG_538](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012364](#); Symbol: [ER_IB_MSG_539](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012365](#); Symbol: [ER_IB_MSG_540](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012366](#); Symbol: [ER_IB_MSG_541](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012368](#); Symbol: [ER_IB_MSG_543](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012369](#); Symbol: [ER_IB_MSG_544](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012370](#); Symbol: [ER_IB_MSG_545](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012371](#); Symbol: [ER_IB_MSG_546](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012372](#); Symbol: [ER_IB_MSG_547](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012373](#); Symbol: [ER_IB_MSG_548](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012374](#); Symbol: [ER_IB_MSG_549](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012375](#); Symbol: [ER_IB_MSG_550](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012376](#); Symbol: [ER_IB_MSG_551](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012377](#); Symbol: [ER_IB_MSG_552](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012378](#); Symbol: [ER_IB_MSG_553](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012379](#); Symbol: [ER_IB_MSG_554](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012380](#); Symbol: [ER_IB_MSG_555](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012381](#); Symbol: [ER_IB_MSG_556](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012382](#); Symbol: [ER_IB_MSG_557](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012383](#); Symbol: [ER_IB_MSG_558](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012384](#); Symbol: [ER_IB_MSG_559](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012385](#); Symbol: [ER_IB_MSG_560](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012386](#); Symbol: [ER_IB_MSG_561](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012387](#); Symbol: [ER_IB_MSG_562](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012388](#); Symbol: [ER_IB_MSG_563](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012389](#); Symbol: [ER_IB_MSG_564](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012390](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot create a tablespace for table %s because the directory is not a valid location. %s

- Error number: [MY-012391](#); Symbol: [ER_IB_MSG_566](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012392](#); Symbol: [ER_IB_MSG_567](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012393](#); Symbol: [ER_IB_MSG_568](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012394](#); Symbol: [ER_IB_MSG_569](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012395](#); Symbol: [ER_IB_MSG_570](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012396](#); Symbol: [ER_IB_MSG_571](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012398](#); Symbol: [ER_IB_MSG_573](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012399](#); Symbol: [ER_IB_MSG_574](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012403](#); Symbol: [ER_IB_MSG_578](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012404](#); Symbol: [ER_IB_MSG_579](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012405](#); Symbol: [ER_IB_MSG_580](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012406](#); Symbol: [ER_IB_MSG_581](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012407](#); Symbol: [ER_IB_MSG_582](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012408](#); Symbol: [ER_IB_MSG_583](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012409](#); Symbol: [ER_IB_MSG_584](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012410](#); Symbol: [ER_IB_MSG_585](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012411](#); Symbol: [ER_IB_MSG_586](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012412](#); Symbol: [ER_IB_MSG_587](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012413](#); Symbol: [ER_IB_MSG_588](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012414](#); Symbol: [ER_IB_MSG_589](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012415](#); Symbol: [ER_IB_MSG_590](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012416](#); Symbol: [ER_IB_MSG_591](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012417](#); Symbol: [ER_IB_MSG_592](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012418](#); Symbol: [ER_IB_MSG_593](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012419](#); Symbol: [ER_IB_MSG_594](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012420](#); Symbol: [ER_IB_MSG_595](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012421](#); Symbol: [ER_IB_MSG_596](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012422](#); Symbol: [ER_IB_MSG_597](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012423](#); Symbol: [ER_IB_MSG_598](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012424](#); Symbol: [ER_IB_MSG_599](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012425](#); Symbol: [ER_IB_MSG_600](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012426](#); Symbol: [ER_IB_MSG_601](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012427](#); Symbol: [ER_IB_MSG_602](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012428](#); Symbol: [ER_IB_MSG_603](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012429](#); Symbol: [ER_IB_MSG_604](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012430](#); Symbol: [ER_IB_MSG_605](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: MY-012431; Symbol: ER_IB_MSG_606; SQLSTATE: HY000

Message: %s

- Error number: MY-012432; Symbol: ER_IB_MSG_607; SQLSTATE: HY000

Message: %s

- Error number: MY-012433; Symbol: ER_IB_MSG_608; SQLSTATE: HY000

Message: %s

- Error number: MY-012434; Symbol: ER_IB_MSG_609; SQLSTATE: HY000

Message: %s

- Error number: MY-012436; Symbol: ER_IB_MSG_611; SQLSTATE: HY000

Message: %s

- Error number: MY-012437; Symbol: ER_IB_MSG_612; SQLSTATE: HY000

Message: %s

- Error number: MY-012438; Symbol: ER_IB_MSG_613; SQLSTATE: HY000

Message: %s

- Error number: MY-012439; Symbol: ER_IB_MSG_614; SQLSTATE: HY000

Message: %s

- Error number: MY-012440; Symbol: ER_IB_MSG_615; SQLSTATE: HY000

Message: %s

- Error number: MY-012441; Symbol: ER_IB_MSG_616; SQLSTATE: HY000

Message: %s

- Error number: MY-012442; Symbol: ER_IB_MSG_617; SQLSTATE: HY000

Message: %s

- Error number: MY-012444; Symbol: ER_IB_MSG_619; SQLSTATE: HY000

Message: %s

- Error number: MY-012445; Symbol: ER_IB_MSG_IBUF_CURSOR_RESTORATION_FAILED; SQLSTATE: HY000

Message: ibuf cursor restoration fails!. ibuf record inserted to page %s:%s

- Error number: MY-012447; Symbol: ER_IB_MSG_IBUF_FAILED_TO_RESTORE_POSITION; SQLSTATE: HY000

Message: Failed to restore ibuf position.

- Error number: MY-012448; Symbol: ER_IB_MSG_623; SQLSTATE: HY000

Message: %s

-
- Error number: [MY-012449](#); Symbol: [ER_IB_MSG_624](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012451](#); Symbol: [ER_IB_MSG_626](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012452](#); Symbol: [ER_IB_MSG_627](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012453](#); Symbol: [ER_IB_MSG_628](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012454](#); Symbol: [ER_IB_MSG_629](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012455](#); Symbol: [ER_IB_MSG_630](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012456](#); Symbol: [ER_IB_MSG_631](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012457](#); Symbol: [ER_IB_MSG_632](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012458](#); Symbol: [ER_IB_MSG_633](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012459](#); Symbol: [ER_IB_MSG_634](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012460](#); Symbol: [ER_IB_MSG_635](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012461](#); Symbol: [ER_IB_MSG_636](#); SQLSTATE: [HY000](#)
Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) forces rollback of the blocking transaction (ID %llu - %s).
 - Error number: [MY-012462](#); Symbol: [ER_IB_MSG_637](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012463](#); Symbol: [ER_IB_MSG_638](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012464](#); Symbol: [ER_IB_MSG_639](#); SQLSTATE: [HY000](#)
Message: Blocked High Priority Transaction (Thread ID %s) waking up the blocking transaction (ID %llu) by pretending it's a deadlock victim.
 - Error number: [MY-012467](#); Symbol: [ER_IB_MSG_642](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012468](#); Symbol: [ER_IB_MSG_643](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012469](#); Symbol: [ER_IB_MSG_644](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012470](#); Symbol: [ER_IB_MSG_645](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012471](#); Symbol: [ER_IB_MSG_646](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012472](#); Symbol: [ER_IB_MSG_647](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012473](#); Symbol: [ER_IB_MSG_648](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012474](#); Symbol: [ER_IB_MSG_649](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012475](#); Symbol: [ER_IB_MSG_650](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012476](#); Symbol: [ER_IB_MSG_651](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012477](#); Symbol: [ER_IB_MSG_652](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012478](#); Symbol: [ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012479](#); Symbol: [ER_IB_MSG_654](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012480](#); Symbol: [ER_IB_MSG_655](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012481](#); Symbol: [ER_IB_MSG_656](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012482](#); Symbol: [ER_IB_MSG_657](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012483](#); Symbol: [ER_IB_MSG_658](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012484](#); Symbol: [ER_IB_MSG_659](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012485](#); Symbol: [ER_IB_MSG_660](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012486](#); Symbol: [ER_IB_MSG_661](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012487](#); Symbol: [ER_IB_MSG_662](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012488](#); Symbol: [ER_IB_MSG_663](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012519](#); Symbol: [ER_IB_MSG_694](#); SQLSTATE: [HY000](#)
Message: ##### CORRUPT LOG RECORD FOUND #####
 - Error number: [MY-012520](#); Symbol: [ER_IB_MSG_695](#); SQLSTATE: [HY000](#)
Message: Log record type %d, page %lu:%lu. Log parsing proceeded successfully up to %llu.
Previous log record type %d, is multi %llu Recv offset %zd, prev %llu
 - Error number: [MY-012521](#); Symbol: [ER_IB_MSG_696](#); SQLSTATE: [HY000](#)
Message: Hex dump starting %llu bytes before and ending %llu bytes after the corrupted record:
 - Error number: [MY-012522](#); Symbol: [ER_IB_MSG_697](#); SQLSTATE: [HY000](#)
Message: Set innodb_force_recovery to ignore this error.
 - Error number: [MY-012523](#); Symbol: [ER_IB_MSG_LOG_CORRUPT](#); SQLSTATE: [HY000](#)
Message: The redo log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s
 - Error number: [MY-012524](#); Symbol: [ER_IB_MSG_UNPROCESSED_REDO_LOG_RECORDS](#); SQLSTATE: [HY000](#)
Message: %zu pages with log records were left unprocessed!
 - Error number: [MY-012525](#); Symbol: [ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED](#); SQLSTATE: [HY000](#)
Message: Upgrade after a crash is not supported. This redo log was created with %s, and it appears corrupted. Please follow the instructions at %s
 - Error number: [MY-012526](#); Symbol: [ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Upgrade is not supported after a crash or shutdown with innodb_fast_shutdown = 2. This redo log was created with %s, and it appears logically non empty. Please follow the instructions at %s
 - Error number: [MY-012529](#); Symbol: [ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30](#); SQLSTATE: [HY000](#)
-

Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.30.

- Error number: [MY-012530](#); Symbol: [ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Unknown redo log format (v%lu) in file %s. Please follow the instructions at %s

- Error number: [MY-012531](#); Symbol: [ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.

- Error number: [MY-012532](#); Symbol: [ER_IB_MSG_707](#); SQLSTATE: [HY000](#)

Message: Applying a batch of %llu redo log records ...

- Error number: [MY-012533](#); Symbol: [ER_IB_MSG_708](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012534](#); Symbol: [ER_IB_MSG_709](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012535](#); Symbol: [ER_IB_MSG_710](#); SQLSTATE: [HY000](#)

Message: Apply batch completed!

- Error number: [MY-012536](#); Symbol: [ER_IB_MSG_711](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012537](#); Symbol: [ER_IB_MSG_712](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012538](#); Symbol: [ER_IB_MSG_713](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012539](#); Symbol: [ER_IB_MSG_714](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012540](#); Symbol: [ER_IB_MSG_715](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012541](#); Symbol: [ER_IB_MSG_716](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012543](#); Symbol: [ER_IB_MSG_718](#); SQLSTATE: [HY000](#)

Message: Extending tablespace : %lu space name: %s to new size: %lu pages during recovery.

- Error number: [MY-012544](#); Symbol: [ER_IB_MSG_719](#); SQLSTATE: [HY000](#)

Message: Could not extend tablespace: %lu space name: %s to new size: %lu pages during recovery.

- Error number: [MY-012545](#); Symbol: [ER_IB_MSG_720](#); SQLSTATE: [HY000](#)

Message: Log block %lu at lsn %llu has valid header, but checksum field contains %lu, should be %lu.

- Error number: [MY-012546](#); Symbol: [ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)

Message: Skipped necessary redo log applying, --innodb-read-only set!

- Error number: [MY-012547](#); Symbol: [ER_IB_MSG_722](#); SQLSTATE: [HY000](#)

Message: Log scan progressed past the checkpoint LSN %llu.

- Error number: [MY-012548](#); Symbol: [ER_IB_MSG_723](#); SQLSTATE: [HY000](#)

Message: Log parsing buffer overflow. Recovery may have failed! Please set log_buffer_size to a value higher than %lu.

- Error number: [MY-012549](#); Symbol: [ER_IB_MSG_724](#); SQLSTATE: [HY000](#)

Message: Set innodb_force_recovery to ignore this error.

- Error number: [MY-012550](#); Symbol: [ER_IB_MSG_725](#); SQLSTATE: [HY000](#)

Message: Doing recovery: scanned up to log sequence number %llu

- Error number: [MY-012551](#); Symbol: [ER_IB_MSG_726](#); SQLSTATE: [HY000](#)

Message: Database was not shutdown normally!

- Error number: [MY-012552](#); Symbol: [ER_IB_MSG_727](#); SQLSTATE: [HY000](#)

Message: Starting crash recovery.

- Error number: [MY-012553](#); Symbol: [ER_IB_MSG_728](#); SQLSTATE: [HY000](#)

Message: The user has set SRV_FORCE_NO_LOG_REDO on, skipping log redo

- Error number: [MY-012554](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!

- Error number: [MY-012555](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATED_BY_MEB](#); SQLSTATE: [HY000](#)

Message: The redo log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.

- Error number: [MY-012556](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE](#); SQLSTATE: [HY000](#)

Message: Opening cloned database

- Error number: [MY-012557](#); Symbol: [ER_IB_MSG_LOG_FORMAT_OLD](#); SQLSTATE: [HY000](#)

Message: Redo log is from an earlier version, v%lu.

- Error number: [MY-012559](#); Symbol: [ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEAN_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Are you sure you are using the right redo log files to start up the database? Log sequence number in the redo log files is %llu, less than the log sequence number in the first system tablespace file header, %llu.

-
- Error number: [MY-012560](#); Symbol: [ER_IB_MSG_RECOVERY_IS_NEEDED](#); SQLSTATE: [HY000](#)
Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the redo log files!
 - Error number: [MY-012561](#); Symbol: [ER_IB_MSG_RECOVERY_IN_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: Can't initiate database recovery, running in read-only-mode.
 - Error number: [MY-012562](#); Symbol: [ER_IB_MSG_737](#); SQLSTATE: [HY000](#)
Message: We scanned the log up to %llu. A checkpoint was at %llu and the maximum LSN on a database page was %llu. It is possible that the database is now corrupt!
 - Error number: [MY-012563](#); Symbol: [ER_IB_MSG_738](#); SQLSTATE: [HY000](#)
Message: Waiting for recv_writer to finish flushing of buffer pool
 - Error number: [MY-012564](#); Symbol: [ER_IB_MSG_739](#); SQLSTATE: [HY000](#)
Message: Recovery parsing buffer extended to %zu.
 - Error number: [MY-012565](#); Symbol: [ER_IB_MSG_740](#); SQLSTATE: [HY000](#)
Message: Out of memory while resizing recovery parsing buffer.
 - Error number: [MY-012566](#); Symbol: [ER_IB_MSG_741](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012567](#); Symbol: [ER_IB_MSG_742](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012568](#); Symbol: [ER_IB_MSG_743](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012569](#); Symbol: [ER_IB_MSG_744](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012570](#); Symbol: [ER_IB_MSG_745](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012571](#); Symbol: [ER_IB_MSG_746](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012572](#); Symbol: [ER_IB_MSG_747](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012573](#); Symbol: [ER_IB_MSG_748](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012574](#); Symbol: [ER_IB_MSG_749](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012575](#); Symbol: [ER_IB_MSG_750](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012576](#); Symbol: [ER_IB_MSG_751](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012577](#); Symbol: [ER_IB_MSG_752](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012578](#); Symbol: [ER_IB_MSG_753](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012579](#); Symbol: [ER_IB_MSG_754](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012580](#); Symbol: [ER_IB_MSG_755](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012581](#); Symbol: [ER_IB_MSG_756](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012582](#); Symbol: [ER_IB_MSG_757](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012583](#); Symbol: [ER_IB_MSG_758](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012584](#); Symbol: [ER_IB_MSG_759](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012585](#); Symbol: [ER_IB_MSG_760](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012586](#); Symbol: [ER_IB_MSG_761](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012587](#); Symbol: [ER_IB_MSG_762](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012588](#); Symbol: [ER_IB_MSG_763](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012589](#); Symbol: [ER_IB_MSG_764](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012590](#); Symbol: [ER_IB_MSG_765](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012591](#); Symbol: [ER_IB_MSG_766](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012592](#); Symbol: [ER_IB_MSG_767](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012593](#); Symbol: [ER_IB_MSG_768](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012594](#); Symbol: [ER_IB_MSG_769](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012595](#); Symbol: [ER_IB_MSG_770](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012596](#); Symbol: [ER_IB_MSG_771](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012597](#); Symbol: [ER_IB_MSG_772](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012598](#); Symbol: [ER_IB_MSG_773](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012599](#); Symbol: [ER_IB_MSG_774](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012600](#); Symbol: [ER_IB_MSG_775](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012601](#); Symbol: [ER_IB_MSG_776](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012602](#); Symbol: [ER_IB_MSG_777](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012603](#); Symbol: [ER_IB_MSG_778](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012604](#); Symbol: [ER_IB_MSG_779](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012605](#); Symbol: [ER_IB_MSG_780](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012606](#); Symbol: [ER_IB_MSG_781](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012607](#); Symbol: [ER_IB_MSG_782](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012608](#); Symbol: [ER_IB_MSG_783](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012609](#); Symbol: [ER_IB_MSG_784](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012610](#); Symbol: [ER_IB_MSG_785](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012611](#); Symbol: [ER_IB_MSG_786](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012612](#); Symbol: [ER_IB_MSG_787](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012613](#); Symbol: [ER_IB_MSG_788](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012614](#); Symbol: [ER_IB_MSG_789](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012615](#); Symbol: [ER_IB_MSG_790](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012616](#); Symbol: [ER_IB_MSG_791](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012617](#); Symbol: [ER_IB_MSG_792](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012618](#); Symbol: [ER_IB_MSG_793](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012619](#); Symbol: [ER_IB_MSG_794](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012620](#); Symbol: [ER_IB_MSG_795](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012621](#); Symbol: [ER_IB_MSG_796](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012622](#); Symbol: [ER_IB_MSG_797](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012623](#); Symbol: [ER_IB_MSG_798](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012624](#); Symbol: [ER_IB_MSG_799](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012626](#); Symbol: [ER_IB_MSG_801](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012627](#); Symbol: [ER_IB_MSG_802](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012628](#); Symbol: [ER_IB_MSG_803](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012629](#); Symbol: [ER_IB_MSG_804](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012630](#); Symbol: [ER_IB_MSG_805](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012631](#); Symbol: [ER_IB_MSG_806](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012632](#); Symbol: [ER_IB_MSG_807](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012633](#); Symbol: [ER_IB_MSG_808](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012634](#); Symbol: [ER_IB_MSG_809](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012635](#); Symbol: [ER_IB_MSG_810](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012636](#); Symbol: [ER_IB_MSG_811](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012637](#); Symbol: [ER_IB_MSG_812](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012638](#); Symbol: [ER_IB_MSG_813](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012639](#); Symbol: [ER_IB_MSG_814](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012640](#); Symbol: [ER_IB_MSG_815](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012641](#); Symbol: [ER_IB_MSG_816](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012642](#); Symbol: [ER_IB_MSG_817](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012643](#); Symbol: [ER_IB_MSG_818](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012644](#); Symbol: [ER_IB_MSG_819](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012645](#); Symbol: [ER_IB_MSG_820](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012646](#); Symbol: [ER_IB_MSG_821](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012647](#); Symbol: [ER_IB_MSG_822](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012648](#); Symbol: [ER_IB_MSG_823](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012649](#); Symbol: [ER_IB_MSG_824](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012650](#); Symbol: [ER_IB_MSG_825](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012651](#); Symbol: [ER_IB_MSG_826](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012652](#); Symbol: [ER_IB_MSG_827](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012653](#); Symbol: [ER_IB_MSG_828](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012654](#); Symbol: [ER_IB_MSG_829](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012656](#); Symbol: [ER_IB_MSG_831](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012657](#); Symbol: [ER_IB_MSG_832](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012658](#); Symbol: [ER_IB_MSG_833](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012659](#); Symbol: [ER_IB_MSG_834](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012660](#); Symbol: [ER_IB_MSG_835](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012661](#); Symbol: [ER_IB_MSG_836](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012662](#); Symbol: [ER_IB_MSG_837](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012663](#); Symbol: [ER_IB_MSG_838](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012664](#); Symbol: [ER_IB_MSG_839](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012665](#); Symbol: [ER_IB_MSG_840](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012666](#); Symbol: [ER_IB_MSG_841](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012667](#); Symbol: [ER_IB_MSG_842](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012668](#); Symbol: [ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA](#); SQLSTATE: [HY000](#)

Message: Can't encrypt data of redo log

- Error number: [MY-012669](#); Symbol: [ER_IB_MSG_844](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012670](#); Symbol: [ER_IB_MSG_845](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012671](#); Symbol: [ER_IB_MSG_CANT_DECRYPT_REDO_LOG](#); SQLSTATE: [HY000](#)

Message: Decryption of redo log block at offset %llu in file %s failed because there's no keyring configured

- Error number: [MY-012672](#); Symbol: [ER_IB_MSG_847](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012673](#); Symbol: [ER_IB_MSG_848](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-012674](#); Symbol: [ER_IB_MSG_849](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012675](#); Symbol: [ER_IB_MSG_850](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012676](#); Symbol: [ER_IB_MSG_851](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012677](#); Symbol: [ER_IB_MSG_852](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012678](#); Symbol: [ER_IB_MSG_853](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012679](#); Symbol: [ER_IB_MSG_854](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012680](#); Symbol: [ER_IB_MSG_855](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012681](#); Symbol: [ER_IB_MSG_856](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012682](#); Symbol: [ER_IB_MSG_857](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012683](#); Symbol: [ER_IB_MSG_858](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012684](#); Symbol: [ER_IB_MSG_859](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012685](#); Symbol: [ER_IB_MSG_860](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012686](#); Symbol: [ER_IB_MSG_861](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012687](#); Symbol: [ER_IB_MSG_862](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012688](#); Symbol: [ER_IB_MSG_863](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012689](#); Symbol: [ER_IB_MSG_864](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012690](#); Symbol: [ER_IB_MSG_865](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012691](#); Symbol: [ER_IB_MSG_866](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012692](#); Symbol: [ER_IB_MSG_867](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012693](#); Symbol: [ER_IB_MSG_868](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012694](#); Symbol: [ER_IB_MSG_869](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012695](#); Symbol: [ER_IB_MSG_870](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012696](#); Symbol: [ER_IB_MSG_871](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012697](#); Symbol: [ER_IB_MSG_872](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012698](#); Symbol: [ER_IB_MSG_873](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012699](#); Symbol: [ER_IB_MSG_874](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012700](#); Symbol: [ER_IB_MSG_875](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012701](#); Symbol: [ER_IB_MSG_876](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012702](#); Symbol: [ER_IB_MSG_877](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012703](#); Symbol: [ER_IB_MSG_878](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012704](#); Symbol: [ER_IB_MSG_879](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012705](#); Symbol: [ER_IB_MSG_880](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012706](#); Symbol: [ER_IB_MSG_881](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012707](#); Symbol: [ER_IB_MSG_882](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012708](#); Symbol: [ER_IB_MSG_883](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012709](#); Symbol: [ER_IB_MSG_884](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012710](#); Symbol: [ER_IB_MSG_885](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012711](#); Symbol: [ER_IB_MSG_886](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012712](#); Symbol: [ER_IB_MSG_887](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012713](#); Symbol: [ER_IB_MSG_888](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012714](#); Symbol: [ER_IB_MSG_889](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012715](#); Symbol: [ER_IB_MSG_890](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012716](#); Symbol: [ER_IB_MSG_891](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012717](#); Symbol: [ER_IB_MSG_892](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012718](#); Symbol: [ER_IB_MSG_893](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012719](#); Symbol: [ER_IB_MSG_894](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012720](#); Symbol: [ER_IB_MSG_895](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012721](#); Symbol: [ER_IB_MSG_896](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012722](#); Symbol: [ER_IB_MSG_897](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012723](#); Symbol: [ER_IB_MSG_898](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012724](#); Symbol: [ER_IB_MSG_899](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012725](#); Symbol: [ER_IB_MSG_900](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012726](#); Symbol: [ER_IB_MSG_901](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012727](#); Symbol: [ER_IB_MSG_902](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012728](#); Symbol: [ER_IB_MSG_903](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012729](#); Symbol: [ER_IB_MSG_904](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012730](#); Symbol: [ER_IB_MSG_905](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012731](#); Symbol: [ER_IB_MSG_906](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012732](#); Symbol: [ER_IB_MSG_907](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012733](#); Symbol: [ER_IB_MSG_908](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012734](#); Symbol: [ER_IB_MSG_909](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012735](#); Symbol: [ER_IB_MSG_910](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012736](#); Symbol: [ER_IB_MSG_911](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012737](#); Symbol: [ER_IB_MSG_912](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012738](#); Symbol: [ER_IB_MSG_913](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012739](#); Symbol: [ER_IB_MSG_914](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012740](#); Symbol: [ER_IB_MSG_915](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012741](#); Symbol: [ER_IB_MSG_916](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012742](#); Symbol: [ER_IB_MSG_917](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012743](#); Symbol: [ER_IB_MSG_918](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012744](#); Symbol: [ER_IB_MSG_919](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012745](#); Symbol: [ER_IB_MSG_920](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012746](#); Symbol: [ER_IB_MSG_921](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012747](#); Symbol: [ER_IB_MSG_922](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012748](#); Symbol: [ER_IB_MSG_923](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012749](#); Symbol: [ER_IB_MSG_924](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012750](#); Symbol: [ER_IB_MSG_925](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012751](#); Symbol: [ER_IB_MSG_926](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012752](#); Symbol: [ER_IB_MSG_927](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012753](#); Symbol: [ER_IB_MSG_928](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012754](#); Symbol: [ER_IB_MSG_929](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012755](#); Symbol: [ER_IB_MSG_930](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012756](#); Symbol: [ER_IB_MSG_931](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012757](#); Symbol: [ER_IB_MSG_932](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012758](#); Symbol: [ER_IB_MSG_933](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012759](#); Symbol: [ER_IB_MSG_934](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012760](#); Symbol: [ER_IB_MSG_935](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012761](#); Symbol: [ER_IB_MSG_936](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012762](#); Symbol: [ER_IB_MSG_937](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012763](#); Symbol: [ER_IB_MSG_938](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012764](#); Symbol: [ER_IB_MSG_939](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012765](#); Symbol: [ER_IB_MSG_940](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012766](#); Symbol: [ER_IB_MSG_941](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012767](#); Symbol: [ER_IB_MSG_942](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012768](#); Symbol: [ER_IB_MSG_943](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012769](#); Symbol: [ER_IB_MSG_944](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012770](#); Symbol: [ER_IB_MSG_945](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012771](#); Symbol: [ER_IB_MSG_946](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012772](#); Symbol: [ER_IB_IMPORT_INDEX_METADATA_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: IO Error: %s

- Error number: [MY-012773](#); Symbol: [ER_IB_MSG_948](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012774](#); Symbol: [ER_IB_MSG_949](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012775](#); Symbol: [ER_IB_MSG_950](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012776](#); Symbol: [ER_IB_MSG_951](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012777](#); Symbol: [ER_IB_MSG_952](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012778](#); Symbol: [ER_IB_MSG_953](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012779](#); Symbol: [ER_IB_MSG_954](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012780](#); Symbol: [ER_IB_MSG_955](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012781](#); Symbol: [ER_IB_MSG_956](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012782](#); Symbol: [ER_IB_MSG_957](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012783](#); Symbol: [ER_IB_MSG_958](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012784](#); Symbol: [ER_IB_MSG_959](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012785](#); Symbol: [ER_IB_MSG_960](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012786](#); Symbol: [ER_IB_MSG_961](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012787](#); Symbol: [ER_IB_MSG_962](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012788](#); Symbol: [ER_IB_MSG_963](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012789](#); Symbol: [ER_IB_MSG_964](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012790](#); Symbol: [ER_IB_MSG_965](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012791](#); Symbol: [ER_IB_MSG_966](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012792](#); Symbol: [ER_IB_MSG_967](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012793](#); Symbol: [ER_IB_MSG_968](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012794](#); Symbol: [ER_IB_MSG_969](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012795](#); Symbol: [ER_IB_MSG_970](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012796](#); Symbol: [ER_IB_MSG_971](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012797](#); Symbol: [ER_IB_MSG_972](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012798](#); Symbol: [ER_IB_MSG_973](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012799](#); Symbol: [ER_IB_MSG_974](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012800](#); Symbol: [ER_IB_MSG_975](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012801](#); Symbol: [ER_IB_MSG_976](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012802](#); Symbol: [ER_IB_MSG_977](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012803](#); Symbol: [ER_IB_MSG_978](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012804](#); Symbol: [ER_IB_MSG_979](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012805](#); Symbol: [ER_IB_MSG_980](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012806](#); Symbol: [ER_IB_MSG_981](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012807](#); Symbol: [ER_IB_MSG_982](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012808](#); Symbol: [ER_IB_MSG_983](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012809](#); Symbol: [ER_IB_MSG_984](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012810](#); Symbol: [ER_IB_MSG_985](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012811](#); Symbol: [ER_IB_MSG_986](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012812](#); Symbol: [ER_IB_MSG_987](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012813](#); Symbol: [ER_IB_MSG_988](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012814](#); Symbol: [ER_IB_MSG_989](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012815](#); Symbol: [ER_IB_MSG_990](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012816](#); Symbol: [ER_IB_MSG_991](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012817](#); Symbol: [ER_IB_MSG_992](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012818](#); Symbol: [ER_IB_MSG_993](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012819](#); Symbol: [ER_IB_MSG_994](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012820](#); Symbol: [ER_IB_MSG_995](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012821](#); Symbol: [ER_IB_MSG_996](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012822](#); Symbol: [ER_IB_MSG_997](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012823](#); Symbol: [ER_IB_MSG_998](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012824](#); Symbol: [ER_IB_MSG_999](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012825](#); Symbol: [ER_IB_MSG_1000](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012826](#); Symbol: [ER_IB_MSG_1001](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012827](#); Symbol: [ER_IB_MSG_1002](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012828](#); Symbol: [ER_IB_MSG_1003](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012829](#); Symbol: [ER_IB_MSG_1004](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012830](#); Symbol: [ER_IB_MSG_1005](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012831](#); Symbol: [ER_IB_MSG_1006](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012832](#); Symbol: [ER_IB_MSG_1007](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012833](#); Symbol: [ER_IB_MSG_1008](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012834](#); Symbol: [ER_IB_MSG_1009](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012835](#); Symbol: [ER_IB_MSG_1010](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012836](#); Symbol: [ER_IB_MSG_1011](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012837](#); Symbol: [ER_IB_MSG_1012](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012838](#); Symbol: [ER_IB_MSG_1013](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012839](#); Symbol: [ER_IB_IMPORT_START_CFG_NAME](#); SQLSTATE: [HY000](#)

Message: Writing table metadata to '%s'

- Error number: [MY-012840](#); Symbol: [ER_IB_MSG_1015](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012841](#); Symbol: [ER_IB_MSG_1016](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012842](#); Symbol: [ER_IB_MSG_1017](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012843](#); Symbol: [ER_IB_MSG_1018](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012844](#); Symbol: [ER_IB_MSG_1019](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012845](#); Symbol: [ER_IB_MSG_1020](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012846](#); Symbol: [ER_IB_MSG_1021](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012847](#); Symbol: [ER_IB_MSG_1022](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012848](#); Symbol: [ER_IB_MSG_1023](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012849](#); Symbol: [ER_IB_MSG_1024](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012850](#); Symbol: [ER_IB_MSG_1025](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012851](#); Symbol: [ER_IB_MSG_1026](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012852](#); Symbol: [ER_IB_MSG_1027](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012853](#); Symbol: [ER_IB_MSG_1028](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012854](#); Symbol: [ER_IB_MSG_1029](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012855](#); Symbol: [ER_IB_MSG_1030](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012856](#); Symbol: [ER_IB_MSG_1031](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012857](#); Symbol: [ER_IB_MSG_1032](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012858](#); Symbol: [ER_IB_MSG_1033](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012859](#); Symbol: [ER_IB_MSG_1034](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012860](#); Symbol: [ER_IB_MSG_1035](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012861](#); Symbol: [ER_IB_MSG_1036](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012862](#); Symbol: [ER_IB_MSG_1037](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012863](#); Symbol: [ER_IB_MSG_1038](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012864](#); Symbol: [ER_IB_MSG_1039](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012865](#); Symbol: [ER_IB_MSG_1040](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012866](#); Symbol: [ER_IB_MSG_1041](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012867](#); Symbol: [ER_IB_MSG_1042](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012868](#); Symbol: [ER_IB_MSG_1043](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012869](#); Symbol: [ER_IB_MSG_1044](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012870](#); Symbol: [ER_IB_MSG_1045](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012871](#); Symbol: [ER_IB_MSG_1046](#); SQLSTATE: [HY000](#)

Message: Old log sequence number %llu was greater than the new log sequence number %llu.
Please submit a bug report to <http://bugs.mysql.com>

- Error number: [MY-012872](#); Symbol: [ER_IB_MSG_1047](#); SQLSTATE: [HY000](#)

Message: Semaphore wait has lasted > %llu seconds. We intentionally crash the server because it appears to be hung.

- Error number: [MY-012873](#); Symbol: [ER_IB_MSG_1048](#); SQLSTATE: [HY000](#)

Message: Waiting for %llu table(s) to be dropped

- Error number: [MY-012874](#); Symbol: [ER_IB_MSG_1049](#); SQLSTATE: [HY000](#)

Message: Waiting for change buffer merge to complete number of bytes of change buffer just merged: %llu

- Error number: [MY-012876](#); Symbol: [ER_IB_MSG_1051](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace(s) to be encrypted in read-only-mode.

- Error number: [MY-012877](#); Symbol: [ER_IB_MSG_1052](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace '%s' to be encrypted.

- Error number: [MY-012878](#); Symbol: [ER_IB_MSG_1053](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace '%s' to be encrypted. Failed to write header page.

- Error number: [MY-012879](#); Symbol: [ER_IB_MSG_1054](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace '%s' to be encrypted. Error %d - %s

- Error number: [MY-012880](#); Symbol: [ER_IB_MSG_1055](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

- Error number: [MY-012881](#); Symbol: [ER_IB_MSG_1056](#); SQLSTATE: [HY000](#)

Message: Can't rotate encryption on undo tablespace '%s'.

- Error number: [MY-012882](#); Symbol: [ER_IB_MSG_1057](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

-
- Error number: [MY-012883](#); Symbol: [ER_IB_MSG_1058](#); SQLSTATE: [HY000](#)
Message: `os_file_get_status()` failed on '%s'. Can't determine file permissions.
 - Error number: [MY-012884](#); Symbol: [ER_IB_MSG_1059](#); SQLSTATE: [HY000](#)
Message: %s can't be opened in %s mode.
 - Error number: [MY-012885](#); Symbol: [ER_IB_MSG_1060](#); SQLSTATE: [HY000](#)
Message: '%s' not a regular file.
 - Error number: [MY-012886](#); Symbol: [ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Cannot create %s
 - Error number: [MY-012887](#); Symbol: [ER_IB_MSG_FILE_RESIZE](#); SQLSTATE: [HY000](#)
Message: Setting file %s size to %llu MB. Progress : %u%%
 - Error number: [MY-012888](#); Symbol: [ER_IB_MSG_LOG_FILE_RESIZE_FAILED](#); SQLSTATE: [HY000](#)
Message: Cannot resize redo log file %s to %llu MB (%s)
 - Error number: [MY-012889](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Cannot create redo log files in read-only mode (--innodb-read-only).
 - Error number: [MY-012890](#); Symbol: [ER_IB_MSG_1065](#); SQLSTATE: [HY000](#)
Message: Redo log encryption is enabled, but the keyring is not loaded.
 - Error number: [MY-012891](#); Symbol: [ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to create redo log file %s (error: %d) for start LSN %llu
 - Error number: [MY-012893](#); Symbol: [ER_IB_MSG_LOG_FILES_INITIALIZED](#); SQLSTATE: [HY000](#)
Message: New redo log files created, LSN=%llu
 - Error number: [MY-012894](#); Symbol: [ER_IB_MSG_LOG_FILE_OPEN_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to open '%s' (error: %d).
 - Error number: [MY-012895](#); Symbol: [ER_IB_MSG_1070](#); SQLSTATE: [HY000](#)
Message: Cannot create construction log file '%s' for undo tablespace '%s'.
 - Error number: [MY-012896](#); Symbol: [ER_IB_MSG_1071](#); SQLSTATE: [HY000](#)
Message: Creating UNDO Tablespace %s
 - Error number: [MY-012897](#); Symbol: [ER_IB_MSG_1072](#); SQLSTATE: [HY000](#)
Message: Setting file %s size to %llu MB
 - Error number: [MY-012898](#); Symbol: [ER_IB_MSG_1073](#); SQLSTATE: [HY000](#)
Message: Physically writing the file full

-
- Error number: [MY-012899](#); Symbol: [ER_IB_MSG_1074](#); SQLSTATE: [HY000](#)
Message: Error in creating %s: probably out of disk space
 - Error number: [MY-012900](#); Symbol: [ER_IB_MSG_1075](#); SQLSTATE: [HY000](#)
Message: Can't set encryption metadata for space %s
 - Error number: [MY-012901](#); Symbol: [ER_IB_MSG_1076](#); SQLSTATE: [HY000](#)
Message: Cannot read first page of '%s' - %s
 - Error number: [MY-012902](#); Symbol: [ER_IB_MSG_1077](#); SQLSTATE: [HY000](#)
Message: Undo tablespace number %lu was being truncated when mysqld quit.
 - Error number: [MY-012903](#); Symbol: [ER_IB_MSG_1078](#); SQLSTATE: [HY000](#)
Message: Cannot recover a truncated undo tablespace in read-only mode
 - Error number: [MY-012904](#); Symbol: [ER_IB_MSG_1079](#); SQLSTATE: [HY000](#)
Message: Reconstructing undo tablespace number %lu.
 - Error number: [MY-012905](#); Symbol: [ER_IB_MSG_1080](#); SQLSTATE: [HY000](#)
Message: Cannot create %s because %s already uses Space ID=%lu! Did you change innodb_undo_directory?
 - Error number: [MY-012906](#); Symbol: [ER_IB_MSG_1081](#); SQLSTATE: [HY000](#)
Message: UNDO tablespace %s must be %s
 - Error number: [MY-012907](#); Symbol: [ER_IB_MSG_1082](#); SQLSTATE: [HY000](#)
Message: Error creating file for %s
 - Error number: [MY-012908](#); Symbol: [ER_IB_MSG_1083](#); SQLSTATE: [HY000](#)
Message: Error reading encryption for %s
 - Error number: [MY-012910](#); Symbol: [ER_IB_MSG_OPENED_N_UNDO_TS](#); SQLSTATE: [HY000](#)
Message: Opened %zu existing undo tablespaces.
 - Error number: [MY-012911](#); Symbol: [ER_IB_MSG_1086](#); SQLSTATE: [HY000](#)
Message: Cannot create undo tablespaces since innodb_%s has been set. Using %llu existing undo tablespaces.
 - Error number: [MY-012912](#); Symbol: [ER_IB_MSG_1087](#); SQLSTATE: [HY000](#)
Message: Cannot continue InnoDB startup in %s mode because there are no existing undo tablespaces found.
 - Error number: [MY-012913](#); Symbol: [ER_IB_MSG_1088](#); SQLSTATE: [HY000](#)
Message: Could not create undo tablespace '%s'.
 - Error number: [MY-012914](#); Symbol: [ER_IB_MSG_1089](#); SQLSTATE: [HY000](#)
Message: Error %d - %s - opening newly created undo tablespace '%s'.
 - Error number: [MY-012915](#); Symbol: [ER_IB_MSG_1090](#); SQLSTATE: [HY000](#)

Message: Created %llu undo tablespaces.

- Error number: [MY-012916](#); Symbol: [ER_IB_MSG_1091](#); SQLSTATE: [HY000](#)

Message: Unable to create encrypted undo tablespace number %lu. please check if the keyring is initialized correctly

- Error number: [MY-012917](#); Symbol: [ER_IB_MSG_1092](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace number %lu.

- Error number: [MY-012918](#); Symbol: [ER_IB_MSG_1093](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the header page in undo tablespace number %lu.

- Error number: [MY-012922](#); Symbol: [ER_IB_MSG_1097](#); SQLSTATE: [HY000](#)

Message: Waiting for purge to start

- Error number: [MY-012923](#); Symbol: [ER_IB_MSG_1098](#); SQLSTATE: [HY000](#)

Message: Creating shared tablespace for temporary tables

- Error number: [MY-012924](#); Symbol: [ER_IB_MSG_1099](#); SQLSTATE: [HY000](#)

Message: The %s data file must be writable!

- Error number: [MY-012925](#); Symbol: [ER_IB_MSG_1100](#); SQLSTATE: [HY000](#)

Message: Could not create the shared %s.

- Error number: [MY-012926](#); Symbol: [ER_IB_MSG_1101](#); SQLSTATE: [HY000](#)

Message: Unable to create the shared %s.

- Error number: [MY-012927](#); Symbol: [ER_IB_MSG_1102](#); SQLSTATE: [HY000](#)

Message: The %s data file cannot be re-opened after check_file_spec() succeeded!

- Error number: [MY-012928](#); Symbol: [ER_IB_MSG_1103](#); SQLSTATE: [HY000](#)

Message: %d threads created by InnoDB had not exited at shutdown!

- Error number: [MY-012929](#); Symbol: [ER_IB_MSG_1104](#); SQLSTATE: [HY000](#)

Message: InnoDB Database creation was aborted %swith error %s. You may need to delete the ibdata1 file before trying to start up again.

- Error number: [MY-012930](#); Symbol: [ER_IB_MSG_1105](#); SQLSTATE: [HY000](#)

Message: Plugin initialization aborted %swith error %s.

- Error number: [MY-012931](#); Symbol: [ER_IB_MSG_BUF_PENDING_IO](#); SQLSTATE: [HY000](#)

Message: Waiting for %zu buffer page I/Os to complete.

- Error number: [MY-012932](#); Symbol: [ER_IB_MSG_1107](#); SQLSTATE: [HY000](#)

Message: PUNCH HOLE support available

- Error number: [MY-012933](#); Symbol: [ER_IB_MSG_1108](#); SQLSTATE: [HY000](#)

Message: PUNCH HOLE support not available

- Error number: [MY-012934](#); Symbol: [ER_IB_MSG_1109](#); SQLSTATE: [HY000](#)

Message: Size of InnoDB's ulint is %zu but size of void* is %zu. The sizes should be the same so that on a 64-bit platforms you can allocate more than 4 GB of memory.

- Error number: [MY-012935](#); Symbol: [ER_IB_MSG_1110](#); SQLSTATE: [HY000](#)

Message: Database upgrade cannot be accomplished in read-only mode.

- Error number: [MY-012936](#); Symbol: [ER_IB_MSG_1111](#); SQLSTATE: [HY000](#)

Message: Database upgrade cannot be accomplished with innodb_force_recovery > 0

- Error number: [MY-012937](#); Symbol: [ER_IB_MSG_1112](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012938](#); Symbol: [ER_IB_MSG_1113](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012939](#); Symbol: [ER_IB_MSG_1114](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012940](#); Symbol: [ER_IB_MSG_1115](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012941](#); Symbol: [ER_IB_MSG_1116](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012942](#); Symbol: [ER_IB_MSG_1117](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012944](#); Symbol: [ER_IB_MSG_1119](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012945](#); Symbol: [ER_IB_MSG_1120](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012946](#); Symbol: [ER_IB_MSG_1121](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012947](#); Symbol: [ER_IB_MSG_1122](#); SQLSTATE: [HY000](#)

Message: MySQL was built without a memory barrier capability on this architecture, which might allow a mutex/rw_lock violation under high thread concurrency. This may cause a hang.

- Error number: [MY-012948](#); Symbol: [ER_IB_MSG_1123](#); SQLSTATE: [HY000](#)

Message: Compressed tables use zlib %s

- Error number: [MY-012949](#); Symbol: [ER_IB_MSG_1124](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012950](#); Symbol: [ER_IB_MSG_1125](#); SQLSTATE: [HY000](#)

Message: Startup called second time during the process lifetime. In the MySQL Embedded Server Library you cannot call server_init() more than once during the process lifetime.

- Error number: [MY-012951](#); Symbol: [ER_IB_MSG_1126](#); SQLSTATE: [HY000](#)
Message: %s
- Error number: [MY-012952](#); Symbol: [ER_IB_MSG_1127](#); SQLSTATE: [HY000](#)
Message: Unable to create monitor file %s: %s
- Error number: [MY-012953](#); Symbol: [ER_IB_MSG_1128](#); SQLSTATE: [HY000](#)
Message: Disabling background ibuf IO read threads.
- Error number: [MY-012954](#); Symbol: [ER_IB_MSG_1129](#); SQLSTATE: [HY000](#)
Message: Cannot initialize AIO sub-system
- Error number: [MY-012955](#); Symbol: [ER_IB_MSG_1130](#); SQLSTATE: [HY000](#)
Message: Initializing buffer pool, total size = %lf%c, instances = %lu, chunk size =%lf%c
- Error number: [MY-012956](#); Symbol: [ER_IB_MSG_1131](#); SQLSTATE: [HY000](#)
Message: Cannot allocate memory for the buffer pool
- Error number: [MY-012957](#); Symbol: [ER_IB_MSG_1132](#); SQLSTATE: [HY000](#)
Message: Completed initialization of buffer pool
- Error number: [MY-012958](#); Symbol: [ER_IB_MSG_1133](#); SQLSTATE: [HY000](#)
Message: Small buffer pool size (%lluM), the flst_validate() debug function can cause a deadlock if the buffer pool fills up.
- Error number: [MY-012959](#); Symbol: [ER_IB_MSG_1134](#); SQLSTATE: [HY000](#)
Message: Could not open or create the system tablespace. If you tried to add new data files to the system tablespace, and it failed here, you should now edit innodb_data_file_path in my.cnf back to what it was, and remove the new ibdata files InnoDB created in this failed attempt. InnoDB only wrote those files full of zeros, but did not yet use them in any way. But be careful: do not remove old data files which contain your precious data!
- Error number: [MY-012960](#); Symbol: [ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED](#); SQLSTATE: [HY000](#)
Message: Cannot create redo log files because data files are corrupt or the database was not shut down cleanly after creating the data files.
- Error number: [MY-012961](#); Symbol: [ER_IB_MSG_LOG_FILES_INVALID_SET](#); SQLSTATE: [HY000](#)
Message: Only one redo log file found
- Error number: [MY-012962](#); Symbol: [ER_IB_MSG_LOG_FILE_SIZE_INVALID](#); SQLSTATE: [HY000](#)
Message: The redo log file %s size %llu is not a multiple of innodb_page_size
- Error number: [MY-012963](#); Symbol: [ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES](#); SQLSTATE: [HY000](#)
Message: The redo log file %s is of different size %llu bytes than other log files %llu bytes!
- Error number: [MY-012964](#); Symbol: [ER_IB_MSG_1139](#); SQLSTATE: [HY000](#)
Message: Use --innodb-directories to find the tablespace files. If that fails then use --innodb-force-recovery=1 to ignore this and to permanently lose all changes to the missing tablespace(s)

-
- Error number: [MY-012965](#); Symbol: [ER_IB_MSG_RECOVERY_CORRUPT](#); SQLSTATE: [HY000](#)
Message: The redo log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!
 - Error number: [MY-012967](#); Symbol: [ER_IB_MSG_1142](#); SQLSTATE: [HY000](#)
Message: Cannot open DD tablespace.
 - Error number: [MY-012968](#); Symbol: [ER_IB_MSG_LOG_FILES_REWRITING](#); SQLSTATE: [HY000](#)
Message: Starting to delete and rewrite redo log files.
 - Error number: [MY-012970](#); Symbol: [ER_IB_MSG_1145](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012971](#); Symbol: [ER_IB_MSG_1146](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012972](#); Symbol: [ER_IB_MSG_1147](#); SQLSTATE: [HY000](#)
Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is %lu pages
 - Error number: [MY-012973](#); Symbol: [ER_IB_MSG_1148](#); SQLSTATE: [HY000](#)
Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb_data_file_path in my.cnf in an inappropriate way, removing ibdata files from there? You can set innodb_force_recovery=1 in my.cnf to force a startup if you are trying to recover a badly corrupt database.
 - Error number: [MY-012974](#); Symbol: [ER_IB_MSG_1149](#); SQLSTATE: [HY000](#)
Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is only %lu pages
 - Error number: [MY-012975](#); Symbol: [ER_IB_MSG_1150](#); SQLSTATE: [HY000](#)
Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb_data_file_path in my.cnf in an InnoDB: inappropriate way, removing ibdata files from there? You can set innodb_force_recovery=1 in my.cnf to force InnoDB: a startup if you are trying to recover a badly corrupt database.
 - Error number: [MY-012976](#); Symbol: [ER_IB_MSG_1151](#); SQLSTATE: [HY000](#)
Message: %s started; log sequence number %llu
 - Error number: [MY-012977](#); Symbol: [ER_IB_MSG_1152](#); SQLSTATE: [HY000](#)
Message: Waiting for purge to complete
 - Error number: [MY-012979](#); Symbol: [ER_IB_MSG_1154](#); SQLSTATE: [HY000](#)
Message: Query counter shows %lld queries still inside InnoDB at shutdown
 - Error number: [MY-012980](#); Symbol: [ER_IB_MSG_1155](#); SQLSTATE: [HY000](#)
Message: Shutdown completed; log sequence number %llu
 - Error number: [MY-012981](#); Symbol: [ER_IB_MSG_1156](#); SQLSTATE: [HY000](#)
Message: Cannot continue operation.

-
- Error number: [MY-012982](#); Symbol: [ER_IB_MSG_1157](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012983](#); Symbol: [ER_IB_MSG_1158](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012984](#); Symbol: [ER_IB_MSG_1159](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012985](#); Symbol: [ER_IB_MSG_1160](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012986](#); Symbol: [ER_IB_MSG_1161](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012987](#); Symbol: [ER_IB_MSG_1162](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012988](#); Symbol: [ER_IB_MSG_1163](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012989](#); Symbol: [ER_IB_MSG_1164](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012990](#); Symbol: [ER_IB_MSG_1165](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012991](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE](#); SQLSTATE: [HY000](#)
Message: Unable to read the existing undo truncate log file '%s'. The error is %s
 - Error number: [MY-012992](#); Symbol: [ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE](#); SQLSTATE: [HY000](#)
Message: Undo tablespace %s is marked for truncate
 - Error number: [MY-012994](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_START](#); SQLSTATE: [HY000](#)
Message: Truncating UNDO tablespace %s
 - Error number: [MY-012996](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE](#); SQLSTATE: [HY000](#)
Message: Cannot create truncate log for undo tablespace '%s'.
 - Error number: [MY-012998](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE](#); SQLSTATE: [HY000](#)
Message: Failed to truncate undo tablespace '%s'.
 - Error number: [MY-013000](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_COMPLETE](#); SQLSTATE: [HY000](#)
Message: Completed truncate of undo tablespace %s.

-
- Error number: [MY-013002](#); Symbol: [ER_IB_MSG_1177](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013003](#); Symbol: [ER_IB_MSG_1178](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013004](#); Symbol: [ER_IB_MSG_1179](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013005](#); Symbol: [ER_IB_MSG_1180](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013006](#); Symbol: [ER_IB_MSG_1181](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013007](#); Symbol: [ER_IB_MSG_1182](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013008](#); Symbol: [ER_IB_MSG_1183](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013009](#); Symbol: [ER_IB_ERR_ACCESSING_OUT_OF_BOUND_FIELD_IN_INDEX](#); SQLSTATE: [HY000](#)
Message: Trying to access update undo rec field %llu in index %s of table %s but index has only %llu fields. %s. Run also CHECK TABLE %s. n_fields = %llu, i = %llu, ptr = %p.
 - Error number: [MY-013010](#); Symbol: [ER_IB_MSG_1185](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013011](#); Symbol: [ER_IB_MSG_1186](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013012](#); Symbol: [ER_IB_MSG_1187](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013013](#); Symbol: [ER_IB_MSG_1188](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013014](#); Symbol: [ER_IB_MSG_1189](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013015](#); Symbol: [ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED](#); SQLSTATE: [HY000](#)
Message: Rollback of non-prepared transactions completed
 - Error number: [MY-013016](#); Symbol: [ER_IB_MSG_1191](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013017](#); Symbol: [ER_IB_MSG_1192](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013018](#); Symbol: [ER_IB_MSG_1193](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013019](#); Symbol: [ER_IB_MSG_1194](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013020](#); Symbol: [ER_IB_MSG_1195](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013021](#); Symbol: [ER_IB_MSG_1196](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013022](#); Symbol: [ER_IB_MSG_1197](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013023](#); Symbol: [ER_IB_MSG_1198](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013024](#); Symbol: [ER_IB_MSG_1199](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013025](#); Symbol: [ER_IB_MSG_1200](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013026](#); Symbol: [ER_IB_MSG_1201](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013027](#); Symbol: [ER_IB_MSG_1202](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013028](#); Symbol: [ER_IB_MSG_1203](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013029](#); Symbol: [ER_IB_MSG_1204](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013030](#); Symbol: [ER_IB_MSG_1205](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013031](#); Symbol: [ER_IB_MSG_1206](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013032](#); Symbol: [ER_IB_MSG_1207](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013033](#); Symbol: [ER_IB_MSG_1208](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013034](#); Symbol: [ER_IB_MSG_1209](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013035](#); Symbol: [ER_IB_MSG_1210](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013036](#); Symbol: [ER_IB_MSG_1211](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) killed the blocking transaction (ID %llu - %s) by rolling it back.

- Error number: [MY-013037](#); Symbol: [ER_IB_MSG_1212](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013038](#); Symbol: [ER_IB_MSG_1213](#); SQLSTATE: [HY000](#)

Message: gettimeofday() failed: %s

- Error number: [MY-013039](#); Symbol: [ER_IB_MSG_1214](#); SQLSTATE: [HY000](#)

Message: Can't create UNDO tablespace %s %s

- Error number: [MY-013040](#); Symbol: [ER_IB_MSG_WILL_CREATE_N_UNDO_TS](#); SQLSTATE: [HY000](#)

Message: Will create %zu new undo tablespaces.

- Error number: [MY-013041](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_ON_START](#); SQLSTATE: [HY000](#)

Message: Resizing redo log from %lluM to %lluM (LSN=%llu) synchronously. If this takes too long, consider starting the server with large --innodb_redo_log_capacity, and resizing the redo log online using SET.

- Error number: [MY-013042](#); Symbol: [ER_IB_MSG_1217](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013043](#); Symbol: [ER_IB_MSG_1218](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013044](#); Symbol: [ER_IB_MSG_1219](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013045](#); Symbol: [ER_IB_MSG_1220](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013046](#); Symbol: [ER_IB_MSG_1221](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013047](#); Symbol: [ER_IB_MSG_1222](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013048](#); Symbol: [ER_IB_MSG_1223](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013049](#); Symbol: [ER_IB_MSG_1224](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013050](#); Symbol: [ER_IB_MSG_1225](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013051](#); Symbol: [ER_IB_MSG_1226](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013052](#); Symbol: [ER_IB_MSG_1227](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013053](#); Symbol: [ER_IB_MSG_1228](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013054](#); Symbol: [ER_IB_MSG_1229](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013056](#); Symbol: [ER_IB_MSG_1231](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013058](#); Symbol: [ER_IB_MSG_1233](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013059](#); Symbol: [ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE](#); SQLSTATE: [HY000](#)

Message: Out of space in the redo log. Checkpoint LSN: %llu. Consider increasing innodb_redo_log_capacity.

- Error number: [MY-013060](#); Symbol: [ER_IB_MSG_1235](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013061](#); Symbol: [ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer waited too long for redo-archiver to advance (1 second). There are unarchived: %llu bytes. Archiver LSN: %llu. Aborted the redo-archiver. Consider increasing innodb_redo_log_capacity.

- Error number: [MY-013062](#); Symbol: [ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer is waiting for redo-archiver to catch up unarchived: %llu bytes. Archiver LSN: %llu. Consider increasing innodb_redo_log_capacity.

- Error number: [MY-013063](#); Symbol: [ER_IB_MSG_1238](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013064](#); Symbol: [ER_IB_MSG_1239](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-013066](#); Symbol: [ER_IB_MSG_1241](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013067](#); Symbol: [ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: Can't set redo log files to be encrypted in read-only mode.
 - Error number: [MY-013068](#); Symbol: [ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Can't set redo log files to be encrypted.
 - Error number: [MY-013070](#); Symbol: [ER_IB_MSG_1245](#); SQLSTATE: [HY000](#)
Message: Redo log encryption is enabled.
 - Error number: [MY-013071](#); Symbol: [ER_IB_MSG_1246](#); SQLSTATE: [HY000](#)
Message: Waiting for archiver to finish archiving page and log
 - Error number: [MY-013072](#); Symbol: [ER_IB_MSG_1247](#); SQLSTATE: [HY000](#)
Message: Starting shutdown...
 - Error number: [MY-013073](#); Symbol: [ER_IB_MSG_1248](#); SQLSTATE: [HY000](#)
Message: Waiting for %s to exit.
 - Error number: [MY-013074](#); Symbol: [ER_IB_MSG_1249](#); SQLSTATE: [HY000](#)
Message: Waiting for rollback of %zu recovered transactions, before shutdown.
 - Error number: [MY-013075](#); Symbol: [ER_IB_MSG_1250](#); SQLSTATE: [HY000](#)
Message: Waiting for master thread to be suspended.
 - Error number: [MY-013076](#); Symbol: [ER_IB_MSG_1251](#); SQLSTATE: [HY000](#)
Message: Waiting for page_cleaner to finish flushing of buffer pool.
 - Error number: [MY-013077](#); Symbol: [ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Shutdown is waiting for %zu buffer page I/Os to complete.
 - Error number: [MY-013078](#); Symbol: [ER_IB_MSG_1253](#); SQLSTATE: [HY000](#)
Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!
 - Error number: [MY-013080](#); Symbol: [ER_IB_MSG_1255](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013081](#); Symbol: [ER_IB_MSG_1256](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013082](#); Symbol: [ER_IB_MSG_1257](#); SQLSTATE: [HY000](#)
Message: %s
-

-
- Error number: [MY-013083](#); Symbol: [ER_IB_MSG_1258](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013084](#); Symbol: [ER_IB_MSG_1259](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013085](#); Symbol: [ER_IB_MSG_1260](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013086](#); Symbol: [ER_IB_MSG_1261](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013087](#); Symbol: [ER_IB_MSG_1262](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013088](#); Symbol: [ER_IB_MSG_1263](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013089](#); Symbol: [ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM](#); SQLSTATE: [HY000](#)
Message: Invalid redo log header checksum.
 - Error number: [MY-013090](#); Symbol: [ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9](#); SQLSTATE: [HY000](#)
Message: Unsupported redo log format (v%lu). The redo log was created before MySQL 5.7.9
 - Error number: [MY-013091](#); Symbol: [ER_IB_MSG_1266](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013092](#); Symbol: [ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNSAFE](#); SQLSTATE: [HY000](#)
Message: Cannot continue operation. The innodb_redo_log_capacity=%lluM is too small for the innodb_thread_concurrency=%lu. The capacity of redo should be >= %lluM. To get mysqld running, set innodb_thread_concurrency to a smaller value or increase innodb_redo_log_capacity. %s
 - Error number: [MY-013093](#); Symbol: [ER_IB_MSG_1268](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013094](#); Symbol: [ER_IB_MSG_1269](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013095](#); Symbol: [ER_IB_MSG_THREAD_CONCURRENCY_CHANGED](#); SQLSTATE: [HY000](#)
Message: User has set innodb_thread_concurrency to %lu.
 - Error number: [MY-013096](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

-
- Error number: [MY-013097](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.
 - Error number: [MY-013098](#); Symbol: [ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.
 - Error number: [MY-013099](#); Symbol: [ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.
 - Error number: [MY-013101](#); Symbol: [ER_BINLOG_ROW_VALUE_OPTION_IGNORED](#); SQLSTATE: [HY000](#)

Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.
 - Error number: [MY-013103](#); Symbol: [ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES](#); SQLSTATE: [HY000](#)

Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog_row_value_options is limited to less than 50%%.
 - Error number: [MY-013104](#); Symbol: [ER_CONNECTION_ABORTED](#); SQLSTATE: [HY000](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).
 - Error number: [MY-013105](#); Symbol: [ER_NORMAL_SERVER_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: %s: Normal shutdown.
 - Error number: [MY-013106](#); Symbol: [ER_KEYRING_MIGRATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Can not perform keyring migration : %s.
 - Error number: [MY-013107](#); Symbol: [ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a lower_case_table_names option value '%u' different from the group '%u'. The member will now exit the group. If there is existing data on member, it may be incompatible with group if it was created with a lower_case_table_names value different from the group.
 - Error number: [MY-013108](#); Symbol: [ER_OOM_SAVE_GTIDS](#); SQLSTATE: [HY000](#)

Message: An out-of-memory error occurred while saving the set of GTIDs from the last binary log into the mysql.gtid_executed table
 - Error number: [MY-013109](#); Symbol: [ER_LCTN_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: The lower_case_table_names setting for the data dictionary was not found. Starting the server using lower_case_table_names = '%u'.
 - Error number: [MY-013111](#); Symbol: [ER_COMPONENT_FILTER_WRONG_VALUE](#); SQLSTATE: [HY000](#)

Message: Variable '%s' can't be set to the value of '%s'

- Error number: [MY-013112](#); Symbol: [ER_XPLUGIN_FAILED_TO_STOP_SERVICES](#); SQLSTATE: [HY000](#)

Message: Stopping services failed with error "%s"

- Error number: [MY-013113](#); Symbol: [ER_INCONSISTENT_ERROR](#); SQLSTATE: [HY000](#)

Message: Query caused different errors on source and replica. Error on source: message (format)='%s' error code=%d; Error on replica:actual message='%s', error code=%d. Default database:'%s'. Query:'%s'

- Error number: [MY-013114](#); Symbol: [ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)

Message: Got fatal error %d from source when reading data from binary log: '%s'

- Error number: [MY-013115](#); Symbol: [ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE](#); SQLSTATE: [HY000](#)

Message: Replication event checksum verification failed while reading from network.

- Error number: [MY-013116](#); Symbol: [ER_REPLICA_CREATE_EVENT_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to create %s

- Error number: [MY-013117](#); Symbol: [ER_REPLICA_FATAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s

- Error number: [MY-013118](#); Symbol: [ER_REPLICA_HEARTBEAT_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unexpected source's heartbeat data: %s

- Error number: [MY-013119](#); Symbol: [ER_REPLICA_INCIDENT](#); SQLSTATE: [HY000](#)

Message: The incident %s occurred on the source. Message: %s

- Error number: [MY-013120](#); Symbol: [ER_REPLICA_SOURCE_COM_FAILURE](#); SQLSTATE: [HY000](#)

Message: Source command %s failed: %s

- Error number: [MY-013121](#); Symbol: [ER_REPLICA_RELAY_LOG_READ_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s

- Error number: [MY-013122](#); Symbol: [ER_REPLICA_RELAY_LOG_WRITE_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s

- Error number: [MY-013123](#); Symbol: [ER_SERVER_REPLICA_CM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Replica failed to initialize connection metadata structure from the repository

- Error number: [MY-013124](#); Symbol: [ER_SERVER_REPLICA_AM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Replica failed to initialize applier metadata structure from the repository

-
- Error number: [MY-013125](#); Symbol: [ER_SERVER_NET_PACKET_TOO_LARGE](#); SQLSTATE: [HY000](#)
Message: Got a packet bigger than 'max_allowed_packet' bytes
 - Error number: [MY-013126](#); Symbol: [ER_SERVER_NO_SYSTEM_TABLE_ACCESS](#); SQLSTATE: [HY000](#)
Message: Access to %s '%s.%s' is rejected.
 - Error number: [MY-013128](#); Symbol: [ER_SERVER_UNKNOWN_SYSTEM_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Unknown system variable '%s'
 - Error number: [MY-013129](#); Symbol: [ER_SERVER_NO_SESSION_TO_SEND_TO](#); SQLSTATE: [HY000](#)
Message: A message intended for a client cannot be sent there as no client-session is attached. Therefore, we're sending the information to the error-log instead: MY-%06d - %s
 - Error number: [MY-013130](#); Symbol: [ER_SERVER_NEW_ABORTING_CONNECTION](#); SQLSTATE: [08S01](#)
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s; diagnostics area: MY-%06d - %s)
 - Error number: [MY-013131](#); Symbol: [ER_SERVER_OUT_OF_SORTMEMORY](#); SQLSTATE: [HY000](#)
Message: Out of sort memory, consider increasing server sort buffer size!
 - Error number: [MY-013132](#); Symbol: [ER_SERVER_RECORD_FILE_FULL](#); SQLSTATE: [HY000](#)
Message: The table '%s' is full!
 - Error number: [MY-013133](#); Symbol: [ER_SERVER_DISK_FULL_NOWAIT](#); SQLSTATE: [HY000](#)
Message: Create table/tablespace '%s' failed, as disk is full.
 - Error number: [MY-013134](#); Symbol: [ER_SERVER_HANDLER_ERROR](#); SQLSTATE: [HY000](#)
Message: Handler reported error %d - %s
 - Error number: [MY-013135](#); Symbol: [ER_SERVER_NOT_FORM_FILE](#); SQLSTATE: [HY000](#)
Message: Incorrect information in file: '%s'
 - Error number: [MY-013136](#); Symbol: [ER_SERVER_CANT_OPEN_FILE](#); SQLSTATE: [HY000](#)
Message: Can't open file: '%s' (OS errno: %d - %s)
 - Error number: [MY-013137](#); Symbol: [ER_SERVER_FILE_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Can't find file: '%s' (OS errno: %d - %s)
 - Error number: [MY-013138](#); Symbol: [ER_SERVER_FILE_USED](#); SQLSTATE: [HY000](#)
Message: '%s' is locked against change (OS errno: %d - %s)
 - Error number: [MY-013139](#); Symbol: [ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: [HY000](#)
Message: Cannot load from %s.%s. The table is probably corrupted!
 - Error number: [MY-013140](#); Symbol: [ER_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)

Message: Error in diagnostics area: MY-%06d - %s

- Error number: MY-013141; Symbol: ER_SERVER_TABLE_CHECK_FAILED; SQLSTATE: HY000

Message: Incorrect definition of table %s.%s: expected column '%s' at position %d, found '%s'.

- Error number: MY-013142; Symbol: ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2; SQLSTATE: HY000

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: MY-013143; Symbol: ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2; SQLSTATE: HY000

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted.

- Error number: MY-013144; Symbol: ER_SERVER_ACL_TABLE_ERROR; SQLSTATE: HY000

Message:

- Error number: MY-013145; Symbol: ER_SERVER_REPLICA_INIT_QUERY_FAILED; SQLSTATE: HY000

Message: Replica SQL thread aborted. Can't execute init_replica query, MY-%06d - '%s'

- Error number: MY-013146; Symbol: ER_SERVER_REPLICA_CONVERSION_FAILED; SQLSTATE: HY000

Message: Column %d (counting the first column as number 1) of table '%s.%s' cannot be converted from type '%s' to type '%s'

- Error number: MY-013147; Symbol: ER_SERVER_REPLICA_IGNORED_TABLE; SQLSTATE: HY000

Message: Replica SQL thread ignored the query because of replicate-*-table rules

- Error number: MY-013148; Symbol: ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION; SQLSTATE: HY000

Message: Cannot replicate anonymous transaction when AUTO_POSITION = 1, at file %s, position %lld.

- Error number: MY-013149; Symbol: ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON; SQLSTATE: HY000

Message: Cannot replicate anonymous transaction when @@GLOBAL.GTID_MODE = ON, at file %s, position %lld.

- Error number: MY-013150; Symbol: ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF; SQLSTATE: HY000

Message: Cannot replicate GTID-transaction when @@GLOBAL.GTID_MODE = OFF, at file %s, position %lld.

- Error number: MY-013151; Symbol: ER_SERVER_TEST_MESSAGE; SQLSTATE: HY000

Message: Simulated error

- Error number: MY-013152; Symbol: ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR; SQLSTATE: HY000

Message: %s

-
- Error number: [MY-013153](#); Symbol: [ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED](#); SQLSTATE: [HY000](#)
Message: Audit Log filtering has not been installed.
 - Error number: [MY-013154](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLES](#); SQLSTATE: [HY000](#)
Message: Failed to open the %s filter tables.
 - Error number: [MY-013155](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLE](#); SQLSTATE: [HY000](#)
Message: Failed to open '%s.%s' %s table.
 - Error number: [MY-013156](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY](#); SQLSTATE: [HY000](#)
Message: Filter name cannot be empty.
 - Error number: [MY-013157](#); Symbol: [ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER](#); SQLSTATE: [HY000](#)
Message: Invalid character in the user name.
 - Error number: [MY-013158](#); Symbol: [ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE](#); SQLSTATE: [HY000](#)
Message: Request ignored for '%s'@'%s'. SUPER or AUDIT_ADMIN needed to perform operation
 - Error number: [MY-013159](#); Symbol: [ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED](#); SQLSTATE: [HY000](#)
Message: No keyring installed.
 - Error number: [MY-013160](#); Symbol: [ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER](#); SQLSTATE: [HY000](#)
Message: Invalid character in the host name.
 - Error number: [MY-013161](#); Symbol: [ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET](#); SQLSTATE: [HY000](#)
Message: Audit log encryption password has not been set; it will be generated automatically. Use `audit_log_encryption_password_get` to obtain the password or `audit_log_encryption_password_set` to set a new one.
 - Error number: [MY-013162](#); Symbol: [ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY](#); SQLSTATE: [HY000](#)
Message: Could not create AES key. OpenSSL's `EVP_BytesToKey` function failed.
 - Error number: [MY-013163](#); Symbol: [ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED](#); SQLSTATE: [HY000](#)
Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.
 - Error number: [MY-013164](#); Symbol: [ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS](#); SQLSTATE: [HY000](#)
Message: Could not reinitialize audit log filters.
 - Error number: [MY-013165](#); Symbol: [ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY](#); SQLSTATE: [HY000](#)

Message: User cannot be empty.

- Error number: [MY-013166](#); Symbol: [ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC](#); SQLSTATE: [HY000](#)

Message: First character of the user name must be alphanumeric.

- Error number: [MY-013167](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Specified filter has not been found.

- Error number: [MY-013169](#); Symbol: [ER_STARTING_INIT](#); SQLSTATE: [HY000](#)

Message: %s (mysqld %s) initializing of server in progress as process %lu

- Error number: [MY-013170](#); Symbol: [ER_ENDING_INIT](#); SQLSTATE: [HY000](#)

Message: %s (mysqld %s) initializing of server has completed

- Error number: [MY-013171](#); Symbol: [ER_IB_MSG_1272](#); SQLSTATE: [HY000](#)

Message: Cannot boot server version %lu on data directory built by version %llu. Downgrade is not supported

- Error number: [MY-013172](#); Symbol: [ER_SERVER_SHUTDOWN_INFO](#); SQLSTATE: [HY000](#)

Message: Received SHUTDOWN from user %s. Shutting down mysqld (Version: %s).

- Error number: [MY-013173](#); Symbol: [ER_GRP_RPL_PLUGIN_ABORT](#); SQLSTATE: [HY000](#)

Message: The plugin encountered a critical error and will abort: %s

- Error number: [MY-013177](#); Symbol: [ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED](#); SQLSTATE: [HY000](#)

Message: '%s.%s' table definition has not been upgraded; Please perform the MySQL upgrade procedure.

- Error number: [MY-013178](#); Symbol: [ER_DD_INITIALIZE_SQL_ERROR](#); SQLSTATE: [HY000](#)

Message: Execution of server-side SQL statement '%s' failed with error code = %d, error message = '%s'.

- Error number: [MY-013179](#); Symbol: [ER_NO_PATH_FOR_SHARED_LIBRARY](#); SQLSTATE: [HY000](#)

Message: No paths allowed for shared library.

- Error number: [MY-013180](#); Symbol: [ER_UDF_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: Function '%s' already exists.

- Error number: [MY-013181](#); Symbol: [ER_SET_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: Got Error: %ld from SetEvent.

- Error number: [MY-013182](#); Symbol: [ER_FAILED_TO_ALLOCATE_SSL_BIO](#); SQLSTATE: [HY000](#)

Message: Error allocating SSL BIO.

- Error number: [MY-013183](#); Symbol: [ER_IB_MSG_1273](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-013184](#); Symbol: [ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE](#); SQLSTATE: [HY000](#)
Message: One or several locations were inaccessible while checking PID filepath.
 - Error number: [MY-013185](#); Symbol: [ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE](#); SQLSTATE: [HY000](#)
Message: Currently unknown variable '%s' was read from the persisted config file.
 - Error number: [MY-013186](#); Symbol: [ER_FAILED_TO_HANDLE_DEFAULTS_FILE](#); SQLSTATE: [HY000](#)
Message: Fatal error in defaults handling. Program aborted!
 - Error number: [MY-013187](#); Symbol: [ER_DUPLICATE_SYS_VAR](#); SQLSTATE: [HY000](#)
Message: Duplicate variable name '%s'.
 - Error number: [MY-013188](#); Symbol: [ER_FAILED_TO_INIT_SYS_VAR](#); SQLSTATE: [HY000](#)
Message: Failed to initialize system variables.
 - Error number: [MY-013189](#); Symbol: [ER_SYS_VAR_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Variable name '%s' not found.
 - Error number: [MY-013190](#); Symbol: [ER_IB_MSG_1274](#); SQLSTATE: [HY000](#)
Message: Some (%d) threads are still active
 - Error number: [MY-013191](#); Symbol: [ER_IB_MSG_1275](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013193](#); Symbol: [ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD](#); SQLSTATE: [HY000](#)
Message: Waiting for tablespace_alter_encrypt_thread to exit
 - Error number: [MY-013194](#); Symbol: [ER_IB_MSG_1277](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013195](#); Symbol: [ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013196](#); Symbol: [ER_IB_MSG_RESUME_OP_FOR_SPACE](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013197](#); Symbol: [ER_IB_MSG_1280](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013198](#); Symbol: [ER_IB_MSG_1281](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013199](#); Symbol: [ER_IB_MSG_1282](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-013200](#); Symbol: [ER_IB_MSG_1283](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013201](#); Symbol: [ER_IB_MSG_1284](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013202](#); Symbol: [ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE](#); SQLSTATE: [HY000](#)
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.
 - Error number: [MY-013203](#); Symbol: [ER_INVALID_VALUE_OF_BIND_ADDRESSES](#); SQLSTATE: [HY000](#)
Message: Invalid value for command line option bind-addresses: '%s'
 - Error number: [MY-013204](#); Symbol: [ER_RELAY_LOG_SPACE_LIMIT_DISABLED](#); SQLSTATE: [HY000](#)
Message: Ignoring the @@global.relay_log_space_limit option because @@global.relay_log_purge is disabled.
 - Error number: [MY-013205](#); Symbol: [ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION](#); SQLSTATE: [HY000](#)
Message: Error when extracting GTID execution information: %s
 - Error number: [MY-013206](#); Symbol: [ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR](#); SQLSTATE: [HY000](#)
Message: Message received without a proper group coordinator module.
 - Error number: [MY-013207](#); Symbol: [ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING](#); SQLSTATE: [HY000](#)
Message: A member cannot join the group while a group configuration operation '%s' is running initiated by '%s'.
 - Error number: [MY-013208](#); Symbol: [ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING](#); SQLSTATE: [HY000](#)
Message: A member is joining the group while a group configuration operation '%s' is running initiated by '%s'. The member will now leave the group.
 - Error number: [MY-013209](#); Symbol: [ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING](#); SQLSTATE: [HY000](#)
Message: Can't start %s for channel '%s' when group replication is running a group configuration operation '%s' initiated by '%s'.
 - Error number: [MY-013210](#); Symbol: [ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT](#); SQLSTATE: [HY000](#)
Message: A primary election was invoked but the requested primary member is not in the group. Request ignored.
 - Error number: [MY-013211](#); Symbol: [ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING](#); SQLSTATE: [HY000](#)
Message: Error while sending message. Context: %s

-
- Error number: [MY-013212](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_ERROR](#); SQLSTATE: [HY000](#)
Message: Error while executing a group configuration operation: %s
 - Error number: [MY-013213](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION](#); SQLSTATE: [HY000](#)
Message: Configuration operation '%s' terminated. %s
 - Error number: [MY-013214](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_START](#); SQLSTATE: [HY000](#)
Message: Starting group operation local execution: %s
 - Error number: [MY-013215](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_END](#); SQLSTATE: [HY000](#)
Message: Termination of group operation local execution: %s
 - Error number: [MY-013216](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR](#); SQLSTATE: [HY000](#)
Message: A configuration change was killed in this member. The member will now leave the group as its configuration may have diverged.
 - Error number: [MY-013217](#); Symbol: [ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue on the primary election process: %s The member will now leave the group.
 - Error number: [MY-013218](#); Symbol: [ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue when stopping a previous election process: %s
 - Error number: [MY-013219](#); Symbol: [ER_GRP_RPL_NO_STAGE_SERVICE](#); SQLSTATE: [HY000](#)
Message: It was not possible to initialize stage logging for this task. The operation will still run without stage tracking.
 - Error number: [MY-013220](#); Symbol: [ER_GRP_RPL_UDF_REGISTER_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not execute the installation of Group Replication UDF function: %s. Check if the function is already present, if so, try to remove it
 - Error number: [MY-013221](#); Symbol: [ER_GRP_RPL_UDF_UNREGISTER_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not uninstall Group Replication UDF functions. Try to remove them manually if present.
 - Error number: [MY-013222](#); Symbol: [ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not execute the installation of Group Replication UDF functions. Check for other errors in the log and try to reinstall the plugin
 - Error number: [MY-013223](#); Symbol: [ER_GRP_RPL_SERVER_UDF_ERROR](#); SQLSTATE: [HY000](#)
Message: The function '%s' failed. %s
 - Error number: [MY-013227](#); Symbol: [ER_SERVER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [HY000](#)

Message: Variable '%s' can't be set to the value of '%s'

- Error number: [MY-013228](#); Symbol: [ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY](#); SQLSTATE: [HY000](#)

Message: %s was unable to create a new Windows registry key %s for %s; continuing to use the previous ident.

- Error number: [MY-013229](#); Symbol: [ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog_format=STATEMENT.

- Error number: [MY-013233](#); Symbol: [ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Unable to switch security context to user: %s

- Error number: [MY-013234](#); Symbol: [ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.

- Error number: [MY-013235](#); Symbol: [ER_UPGRADE_PARSE_ERROR](#); SQLSTATE: [HY000](#)

Message: Error in parsing %s '%s'. '%s' during upgrade. %s

- Error number: [MY-013236](#); Symbol: [ER_DATA_DIRECTORY_UNUSABLE](#); SQLSTATE: [HY000](#)

Message: The designated data directory %s is unusable. You can remove all files that the server added to it.

- Error number: [MY-013237](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND](#); SQLSTATE: [HY000](#)

Message: Group search rebinding via root DN: %s

- Error number: [MY-013238](#); Symbol: [ER_PLUGIN_INSTALL_ERROR](#); SQLSTATE: [HY000](#)

Message: Error installing plugin '%s': %s

- Error number: [MY-013239](#); Symbol: [ER_PLUGIN_UNINSTALL_ERROR](#); SQLSTATE: [HY000](#)

Message: Error uninstalling plugin '%s': %s

- Error number: [MY-013240](#); Symbol: [ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE](#); SQLSTATE: [HY000](#)

Message: Partitioned table '%s' is not allowed to use shared tablespace '%s'. Please move all partitions to file-per-table tablespaces before upgrade.

- Error number: [MY-013241](#); Symbol: [ER_UNKNOWN_TABLESPACE_TYPE](#); SQLSTATE: [HY000](#)

Message: Cannot determine the type of the tablespace named '%s'.

- Error number: [MY-013242](#); Symbol: [ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

-
- Error number: [MY-013243](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: The character set UTF8MB3 is deprecated and will be removed in a future release. Please consider using UTF8MB4 instead.
 - Error number: [MY-013244](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.
 - Error number: [MY-013245](#); Symbol: [ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: The SSL library function %s failed. This is typically caused by the SSL library already being used. As a result the SSL memory allocation will not be instrumented.
 - Error number: [MY-013246](#); Symbol: [ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet MADV_DONTDUMP is not supported on this platform
 - Error number: [MY-013247](#); Symbol: [ER_IB_MSG_MADVISE_FAILED](#); SQLSTATE: [HY000](#)

Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet madvise(%p,%zu,%s) failed with %s
 - Error number: [MY-013249](#); Symbol: [ER_WARN_REMOVED_SQL_MODE](#); SQLSTATE: [HY000](#)

Message: sql_mode=0x%08x has been removed and will be ignored
 - Error number: [MY-013250](#); Symbol: [ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT](#); SQLSTATE: [HY000](#)

Message: Failed to allocate memory for a pool of size %zu bytes. Will wait for %zu seconds for a thread to free a resource.
 - Error number: [MY-013252](#); Symbol: [ER_IB_MSG_USING_UNDO_SPACE](#); SQLSTATE: [HY000](#)

Message: Using undo tablespace '%s'.
 - Error number: [MY-013253](#); Symbol: [ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE](#); SQLSTATE: [HY000](#)

Message: %s Unable to save the current state of tablespace '%s' to the data dictionary
 - Error number: [MY-013254](#); Symbol: [ER_IB_MSG_MAX_UNDO_SPACES_REACHED](#); SQLSTATE: [HY000](#)

Message: Cannot create undo tablespace %s at %s because %d undo tablespaces already exist.
 - Error number: [MY-013255](#); Symbol: [ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE](#); SQLSTATE: [HY000](#)

Message: Error %d opening newly created undo tablespace %s.
 - Error number: [MY-013256](#); Symbol: [ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR](#); SQLSTATE: [HY000](#)

Message: SDI Compression failed, Z_BUF_ERROR

-
- Error number: [MY-013257](#); Symbol: [ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR](#); SQLSTATE: [HY000](#)
Message: SDI Compression failed, Z_MEM_ERROR
 - Error number: [MY-013258](#); Symbol: [ER_IB_MSG_SDI_Z_STREAM_ERROR](#); SQLSTATE: [HY000](#)
Message: SDI Compression failed, Z_STREAM_ERROR
 - Error number: [MY-013259](#); Symbol: [ER_IB_MSG_SDI_Z_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013261](#); Symbol: [ER_IB_MSG_NOT_END_WITH_IBU](#); SQLSTATE: [HY000](#)
Message: Cannot use %s as an undo tablespace because it does not end with '.ibu'.
 - Error number: [MY-013266](#); Symbol: [ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE](#); SQLSTATE: [HY000](#)
Message: %s Failed to finish truncating Undo Tablespace '%s'
 - Error number: [MY-013268](#); Symbol: [ER_IB_MSG_WRONG_TABLESPACE_DIR](#); SQLSTATE: [HY000](#)
Message: The directory for tablespace %s does not exist or is incorrect.
 - Error number: [MY-013269](#); Symbol: [ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013270](#); Symbol: [ER_CLONE_DONOR_TRACE](#); SQLSTATE: [HY000](#)
Message: Clone donor reported : %s.
 - Error number: [MY-013271](#); Symbol: [ER_CLONE_PROTOCOL_TRACE](#); SQLSTATE: [HY000](#)
Message: Clone received unexpected response from donor : %s.
 - Error number: [MY-013272](#); Symbol: [ER_CLONE_CLIENT_TRACE](#); SQLSTATE: [HY000](#)
Message: Client: %s.
 - Error number: [MY-013273](#); Symbol: [ER_CLONE_SERVER_TRACE](#); SQLSTATE: [HY000](#)
Message: Server: %s.
 - Error number: [MY-013274](#); Symbol: [ER_THREAD_POOL_PFS_TABLES_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to initialize the performance schema tables service.
 - Error number: [MY-013275](#); Symbol: [ER_THREAD_POOL_PFS_TABLES_ADD_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to add thread pool performance schema tables.
 - Error number: [MY-013276](#); Symbol: [ER_CANT_SET_DATA_DIR](#); SQLSTATE: [HY000](#)
Message: Failed to set datadir to '%s\'' (OS errno: %d - %s)
 - Error number: [MY-013277](#); Symbol: [ER_INNOVB_INVALID_INNOVB_UNDO_DIRECTORY_LOCATION](#); SQLSTATE: [HY000](#)

Message: The innodb_undo_directory is not allowed to be an ancestor of the datadir.

- Error number: MY-013278; Symbol: ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY; SQLSTATE: HY000

Message: Failed to fetch key from keyring, please check if keyring is loaded.

- Error number: MY-013279; Symbol: ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND; SQLSTATE: HY000

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

- Error number: MY-013280; Symbol: ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY; SQLSTATE: HY000

Message: Fetched an invalid key from keyring.

- Error number: MY-013281; Symbol: ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR; SQLSTATE: HY000

Message: Error reading a replication log encryption header: %s.

- Error number: MY-013282; Symbol: ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS; SQLSTATE: HY000

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

- Error number: MY-013283; Symbol: ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED; SQLSTATE: HY000

Message: Key %s exists unexpected.

- Error number: MY-013284; Symbol: ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY; SQLSTATE: HY000

Message: Failed to generate key, please check if keyring is loaded.

- Error number: MY-013285; Symbol: ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY; SQLSTATE: HY000

Message: Failed to store key, please check if keyring is loaded.

- Error number: MY-013286; Symbol: ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY; SQLSTATE: HY000

Message: Failed to remove key, please check if keyring is loaded.

- Error number: MY-013287; Symbol: ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED; SQLSTATE: HY000

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

- Error number: MY-013288; Symbol: ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE; SQLSTATE: HY000

Message: Failed to initialize binlog encryption, please check if keyring is loaded.

- Error number: MY-013289; Symbol: ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY_AT_STARTUP; SQLSTATE: HY000

Message: Failed to rotate binlog encryption master key at startup, please check if keyring is loaded.

- Error number: [MY-013290](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY_AT_STARTUP](#); SQLSTATE: [HY000](#)

Message: Ignoring binlog_rotate_encryption_master_key_at_startup because binlog_encryption option is disabled.

- Error number: [MY-013291](#); Symbol: [ER_INVALID_ADMIN_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Invalid value for command line option admin-address: '%s'

- Error number: [MY-013292](#); Symbol: [ER_SERVER_STARTUP_ADMIN_INTERFACE](#); SQLSTATE: [HY000](#)

Message: Admin interface ready for connections, address: '%s' port: %d

- Error number: [MY-013293](#); Symbol: [ER_CANT_CREATE_ADMIN_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle admin connections (errno= %d)

- Error number: [MY-013294](#); Symbol: [ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID](#); SQLSTATE: [HY000](#)

Message: RETAIN CURRENT PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

- Error number: [MY-013295](#); Symbol: [ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID](#); SQLSTATE: [HY000](#)

Message: DISCARD OLD PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

- Error number: [MY-013299](#); Symbol: [ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES](#); SQLSTATE: [HY000](#)

Message: Can not read and process value of User_attributes column from mysql.user table for user: '%s'@'%s'; Ignoring user.

- Error number: [MY-013300](#); Symbol: [ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.

- Error number: [MY-013301](#); Symbol: [ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.

- Error number: [MY-013302](#); Symbol: [ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Second password was used for login by user: '%s'@'%s'.

- Error number: [MY-013303](#); Symbol: [ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error sending transaction '%s:%lld' prepared message from session '%u'.

- Error number: [MY-013304](#); Symbol: [ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction '%s:%lld' for commit on session '%u' after being prepared on all group members.

- Error number: [MY-013305](#); Symbol: [ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER_CERTIFICATION](#); SQLSTATE: [HY000](#)

Message: Transaction '%s:%lld' already exists on Group Replication consistency manager while being registered after conflict detection.

- Error number: [MY-013306](#); Symbol: [ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION](#); SQLSTATE: [HY000](#)

Message: Error registering transaction '%s:%lld' on Group Replication consistency manager after conflict detection.

- Error number: [MY-013307](#); Symbol: [ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error registering transaction '%s:%lld' from session '%u' to wait for being prepared on all group members.

- Error number: [MY-013308](#); Symbol: [ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error on transaction '%s:%lld' from session '%u' while waiting for being prepared on all group members.

- Error number: [MY-013309](#); Symbol: [ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE](#); SQLSTATE: [HY000](#)

Message: Transaction '%s:%lld' does not exist on Group Replication consistency manager while receiving remote transaction prepare.

- Error number: [MY-013310](#); Symbol: [ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction '%s:%lld' for execution on session '%u' after its dependencies did complete commit.

- Error number: [MY-013311](#); Symbol: [ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED](#); SQLSTATE: [HY000](#)

Message: Error registering transaction from session '%u' to wait for its dependencies to complete commit.

- Error number: [MY-013312](#); Symbol: [ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED](#); SQLSTATE: [HY000](#)

Message: Error on session '%u' while waiting for its dependencies to complete commit.

- Error number: [MY-013313](#); Symbol: [ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Error registering transaction from session '%u' to wait for sync before execution.

- Error number: [MY-013314](#); Symbol: [ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Error sending sync before execution message from session '%u'.

- Error number: [MY-013315](#); Symbol: [ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Error on transaction from session '%u' while waiting for sync before execution.

- Error number: [MY-013316](#); Symbol: [ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_EXEC](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction for execution on session '%u' after wait for sync before execution.

- Error number: [MY-013317](#); Symbol: [ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Error waiting for group executed transactions commit on session '%u'.

- Error number: [MY-013320](#); Symbol: [ER_WARN_PROPERTY_STRING_PARSE_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not parse key-value pairs in property string '%s'

- Error number: [MY-013321](#); Symbol: [ER_INVALID_PROPERTY_KEY](#); SQLSTATE: [HY000](#)

Message: Property key '%s' is invalid.

- Error number: [MY-013322](#); Symbol: [ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Error when extracting the group_replication_applier channel received transactions set. Unable to ensure the execution of group transactions received during recovery.

- Error number: [MY-013323](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT](#); SQLSTATE: [HY000](#)

Message: Failed to encrypt content to write into binlog file: %s.

- Error number: [MY-013324](#); Symbol: [ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER](#); SQLSTATE: [HY000](#)

Message: Cannot get the server version number from the dictionary tablespace header.

- Error number: [MY-013325](#); Symbol: [ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER](#); SQLSTATE: [HY000](#)

Message: Cannot set the server version number in the dictionary tablespace header.

- Error number: [MY-013326](#); Symbol: [ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Upgrading the server from server version '%u' is not supported.

- Error number: [MY-013327](#); Symbol: [ER_SERVER_UPGRADE_FROM_VERSION](#); SQLSTATE: [HY000](#)

Message: MySQL server upgrading from version '%u' to '%u'.

- Error number: [MY-013328](#); Symbol: [ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL](#); SQLSTATE: [HY000](#)

Message: The certification information could not be set in this server: '%s'

-
- Error number: [MY-013329](#); Symbol: [ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING](#); SQLSTATE: [HY000](#)

Message: A request to force a new group membership was issued when the member is leaving the group.
 - Error number: [MY-013330](#); Symbol: [ER_TRG_WRONG_ORDER](#); SQLSTATE: [HY000](#)

Message: Trigger %s.%s for table %s.%s is listed in wrong order. Please drop and recreate all triggers for the table.
 - Error number: [MY-013332](#); Symbol: [ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL](#); SQLSTATE: [HY000](#)

Message: Special handling for group search, {GA} not found
 - Error number: [MY-013333](#); Symbol: [ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO](#); SQLSTATE: [HY000](#)

Message: User group retrieval: User object has group information
 - Error number: [MY-013334](#); Symbol: [ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS](#); SQLSTATE: [HY000](#)

Message: Group information found in multiple user objects. Search filter configuration is incorrect.
 - Error number: [MY-013335](#); Symbol: [ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE](#); SQLSTATE: [HY000](#)

Message: User group retrieval: no group attribute found. Incorrect group search attribute.
 - Error number: [MY-013336](#); Symbol: [ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE](#); SQLSTATE: [HY000](#)

Message: User group retrieval: Group attribute values is NULL.
 - Error number: [MY-013337](#); Symbol: [ER_LDAP_AUTH_GRP_DN_PARSING_FAILED](#); SQLSTATE: [HY000](#)

Message: User group retrieval: parsing DN failed.
 - Error number: [MY-013338](#); Symbol: [ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO](#); SQLSTATE: [HY000](#)

Message: User group retrieval: Group object has user information
 - Error number: [MY-013339](#); Symbol: [ER_LDAP_AUTH_LDAPS](#); SQLSTATE: [HY000](#)

Message: Reserved port for ldaps using ldaps
 - Error number: [MY-013340](#); Symbol: [ER_LDAP_MAPPING_GET_USER_PROXY](#); SQLSTATE: [HY000](#)

Message: Get user proxy
 - Error number: [MY-013341](#); Symbol: [ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP](#); SQLSTATE: [HY000](#)

Message: Get user proxy: User doesn't belongs to any group, user name will be treated as authenticated user.
 - Error number: [MY-013342](#); Symbol: [ER_LDAP_MAPPING_INFO](#); SQLSTATE: [HY000](#)

Message: Get user proxy: configured mapping info: %s
-

-
- Error number: [MY-013343](#); Symbol: [ER_LDAP_MAPPING_EMPTY_MAPPING](#); SQLSTATE: [HY000](#)
Message: Get user proxy: User doesn't have group mapping information, First LDAP group will be treated as authenticated user.
 - Error number: [MY-013344](#); Symbol: [ER_LDAP_MAPPING_PROCESS_MAPPING](#); SQLSTATE: [HY000](#)
Message: Process group proxy mapping
 - Error number: [MY-013345](#); Symbol: [ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE](#); SQLSTATE: [HY000](#)
Message: Check delimiter after quote
 - Error number: [MY-013346](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER](#); SQLSTATE: [HY000](#)
Message: Processing delimiter
 - Error number: [MY-013347](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Processing delimiter, separator = not found, resetting position
 - Error number: [MY-013348](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA](#); SQLSTATE: [HY000](#)
Message: Processing delimiter, failed to get data for = separator try for separator ,.
 - Error number: [MY-013349](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Processing delimiter, separator , not found, resetting position
 - Error number: [MY-013350](#); Symbol: [ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP](#); SQLSTATE: [HY000](#)
Message: Processing delimiter: No mapping separator is found, end of group information
 - Error number: [MY-013351](#); Symbol: [ER_LDAP_MAPPING_GETTING_NEXT_MAPPING](#); SQLSTATE: [HY000](#)
Message: Getting next mapping information
 - Error number: [MY-013352](#); Symbol: [ER_LDAP_MAPPING_PARSING_CURRENT_STATE](#); SQLSTATE: [HY000](#)
Message: Parsing mapping, current state: %d delimiter char: %c
 - Error number: [MY-013353](#); Symbol: [ER_LDAP_MAPPING_PARSING_MAPPING_INFO](#); SQLSTATE: [HY000](#)
Message: Parsing mapping info, LDAP group: %s MySQL proxy: %s
 - Error number: [MY-013354](#); Symbol: [ER_LDAP_MAPPING_PARSING_ERROR](#); SQLSTATE: [HY000](#)
Message: Mapping parsing error
 - Error number: [MY-013355](#); Symbol: [ER_LDAP_MAPPING_TRIMMING_SPACES](#); SQLSTATE: [HY000](#)
Message: Trimming left spaces
 - Error number: [MY-013356](#); Symbol: [ER_LDAP_MAPPING_IS_QUOTE](#); SQLSTATE: [HY000](#)

Message: Checking if current characters is quote

- Error number: [MY-013357](#); Symbol: [ER_LDAP_MAPPING_NON_DESIRED_STATE](#); SQLSTATE: [HY000](#)

Message: Not desired state or un-defined states.

- Error number: [MY-013358](#); Symbol: [ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP](#); SQLSTATE: [HY000](#)

Message: Invalid value for named_pipe_full_access_group.

- Error number: [MY-013359](#); Symbol: [ER_PREPARE_FOR_SECONDARY_ENGINE](#); SQLSTATE: [HY000](#)

Message: Retry the statement using a secondary storage engine.

- Error number: [MY-013360](#); Symbol: [ER_SERVER_WARN_DEPRECATED](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

- Error number: [MY-013361](#); Symbol: [ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)

Message: Cannot set mandatory_roles: AuthId '%s'@'%s' has '%s' privilege.

- Error number: [MY-013362](#); Symbol: [ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION](#); SQLSTATE: [HY000](#)

Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u, master_key_seqno=%u and old_master_key_seqno=%u are wrong.

- Error number: [MY-013363](#); Symbol: [ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

- Error number: [MY-013368](#); Symbol: [ER_TURNING_ON_PARTIAL_REVOKES](#); SQLSTATE: [HY000](#)

Message: At least one partial revoke exists on a database. Turning ON the system variable '@@partial_revokes'.

- Error number: [MY-013369](#); Symbol: [ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT](#); SQLSTATE: [HY000](#)

Message: For user '%s'@'%s', one or more privileges granted through mysql.db for database '%s', conflict with partial revoke. It could mean 'mysql' schema is corrupted.

- Error number: [MY-013370](#); Symbol: [ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS](#); SQLSTATE: [HY000](#)

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as these are not valid database privileges.

- Error number: [MY-013371](#); Symbol: [ER_WARN_INVALID_DB_RESTRICTIONS](#); SQLSTATE: [HY000](#)

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as corresponding global privilege(s) are not granted.

-
- Error number: [MY-013372](#); Symbol: [ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL](#); SQLSTATE: [HY000](#)

Message: '%s' is an invalid value for group_replication_communication_protocol_join, please use a MySQL version between 5.7.14 and this server's version
 - Error number: [MY-013373](#); Symbol: [ER_GRP_RPL_STARTED_AUTO_REJOIN](#); SQLSTATE: [HY000](#)

Message: Started auto-rejoin procedure attempt %lu of %lu
 - Error number: [MY-013374](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN](#); SQLSTATE: [HY000](#)

Message: Timeout while waiting for a view change event during the auto-rejoin procedure
 - Error number: [MY-013375](#); Symbol: [ER_GRP_RPL_FINISHED_AUTO_REJOIN](#); SQLSTATE: [HY000](#)

Message: Auto-rejoin procedure attempt %lu of %lu finished. Member was%s able to join the group.
 - Error number: [MY-013376](#); Symbol: [ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a default_table_encryption option value '%d' different from the group '%d'. The member will now exit the group.
 - Error number: [MY-013377](#); Symbol: [ER_SERVER_UPGRADE_OFF](#); SQLSTATE: [HY000](#)

Message: Server shutting down because upgrade is required, yet prohibited by the command line option '--upgrade=NONE'.
 - Error number: [MY-013378](#); Symbol: [ER_SERVER_UPGRADE_SKIP](#); SQLSTATE: [HY000](#)

Message: Server upgrade is required, but skipped by command line option '--upgrade=MINIMAL'.
 - Error number: [MY-013379](#); Symbol: [ER_SERVER_UPGRADE_PENDING](#); SQLSTATE: [HY000](#)

Message: Server upgrade started with version %d, but server upgrade of version %d is still pending.
 - Error number: [MY-013380](#); Symbol: [ER_SERVER_UPGRADE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to upgrade server.
 - Error number: [MY-013381](#); Symbol: [ER_SERVER_UPGRADE_STATUS](#); SQLSTATE: [HY000](#)

Message: Server upgrade from '%d' to '%d' %s.
 - Error number: [MY-013382](#); Symbol: [ER_SERVER_UPGRADE_REPAIR_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Table '%s' requires repair.
 - Error number: [MY-013383](#); Symbol: [ER_SERVER_UPGRADE_REPAIR_STATUS](#); SQLSTATE: [HY000](#)

Message: Table '%s' repair %s.
 - Error number: [MY-013384](#); Symbol: [ER_SERVER_UPGRADE_INFO_FILE](#); SQLSTATE: [HY000](#)

Message: Could not open server upgrade info file '%s' for writing. Please make sure the file is writable.
 - Error number: [MY-013385](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Upgrading the sys schema.

-
- Error number: [MY-013386](#); Symbol: [ER_SERVER_UPGRADE_MYSQL_TABLES](#); SQLSTATE: [HY000](#)
Message: Running queries to upgrade MySQL server.
 - Error number: [MY-013387](#); Symbol: [ER_SERVER_UPGRADE_SYSTEM_TABLES](#); SQLSTATE: [HY000](#)
Message: Upgrading system table data.
 - Error number: [MY-013388](#); Symbol: [ER_SERVER_UPGRADE_EMPTY_SYS](#); SQLSTATE: [HY000](#)
Message: Found empty sys database. Installing the sys schema.
 - Error number: [MY-013389](#); Symbol: [ER_SERVER_UPGRADE_NO_SYS_VERSION](#); SQLSTATE: [HY000](#)
Message: A sys schema exists with no sys.version view. If you have a user created sys schema, this must be renamed for the upgrade to succeed.
 - Error number: [MY-013390](#); Symbol: [ER_SERVER_UPGRADE_SYS_VERSION_EMPTY](#); SQLSTATE: [HY000](#)
Message: A sys schema exists with a sys.version view, but it returns no results.
 - Error number: [MY-013391](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED](#); SQLSTATE: [HY000](#)
Message: Found outdated sys schema version %s.
 - Error number: [MY-013392](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE](#); SQLSTATE: [HY000](#)
Message: The sys schema is already up to date (version %s).
 - Error number: [MY-013393](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT](#); SQLSTATE: [HY000](#)
Message: Found %d sys %s, but expected %d. Re-installing the sys schema.
 - Error number: [MY-013394](#); Symbol: [ER_SERVER_UPGRADE_CHECKING_DB](#); SQLSTATE: [HY000](#)
Message: Checking '%s' schema.
 - Error number: [MY-013395](#); Symbol: [ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT](#); SQLSTATE: [HY000](#)
Message: Too many concurrent transactions while clearing the DDL Log. Please increase the number of Rollback Segments.
 - Error number: [MY-013396](#); Symbol: [ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER](#); SQLSTATE: [HY000](#)
Message: Error in DDL Log recovery during Post-Recovery processing.
 - Error number: [MY-013397](#); Symbol: [ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT](#); SQLSTATE: [HY000](#)
Message: Error in Post-Tablespace-Encryption during Post-Recovery processing.
 - Error number: [MY-013398](#); Symbol: [ER_IB_MSG_DDL_LOG_FAIL_POST_DDL](#); SQLSTATE: [HY000](#)
Message: Error in DLL Log cleanup during Post-DDL processing.
 - Error number: [MY-013399](#); Symbol: [ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#); SQLSTATE: [HY000](#)

Message: '%s' statement is unsafe because it uses a system function that may return a different value on the replica.

- Error number: [MY-013400](#); Symbol: [ER_SERVER_UPGRADE_HELP_TABLE_STATUS](#); SQLSTATE: [HY000](#)

Message: Upgrade of help tables %s.

- Error number: [MY-013404](#); Symbol: [ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY](#); SQLSTATE: [HY000](#)

Message: Unable to create a new binlog file: Table `mysql.gtid\_executed` couldn't be opened. %s

- Error number: [MY-013405](#); Symbol: [ER_NETWORK_NAMESPACES_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Network Namespaces is not supported on this platform

- Error number: [MY-013406](#); Symbol: [ER_UNKNOWN_NETWORK_NAMESPACE](#); SQLSTATE: [HY000](#)

Message: Unknown network namespace '%s'

- Error number: [MY-013407](#); Symbol: [ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Network namespace not allowed for wildcard interface address

- Error number: [MY-013408](#); Symbol: [ER_SETNS_FAILED](#); SQLSTATE: [HY000](#)

Message: setns() failed with error '%s'

- Error number: [MY-013409](#); Symbol: [ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND](#); SQLSTATE: [HY000](#)

Message: Wildcard address value not allowed for multivalued bind address

- Error number: [MY-013410](#); Symbol: [ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The path to a special network namespace file is too long. (got %u > max %u)

- Error number: [MY-013411](#); Symbol: [ER_IB_MSG_TOO_LONG_PATH](#); SQLSTATE: [HY000](#)

Message: Cannot create tablespace '%s'. The filepath is too long for this OS.

- Error number: [MY-013412](#); Symbol: [ER_IB_RECV_FIRST_REC_GROUP_INVALID](#); SQLSTATE: [HY000](#)

Message: The last block of redo had corrupted first_rec_group and became fixed (%u -> %u).

- Error number: [MY-013413](#); Symbol: [ER_DD_UPGRADE_COMPLETED](#); SQLSTATE: [HY000](#)

Message: Data dictionary upgrade from version '%u' to '%u' completed.

- Error number: [MY-013415](#); Symbol: [ER_PERSIST_OPTION_USER_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Truncated a user name for %s that was too long while reading the persisted variables file

- Error number: [MY-013416](#); Symbol: [ER_PERSIST_OPTION_HOST_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Truncated a host name for %s that was too long while reading the persisted variables file

-
- Error number: [MY-013417](#); Symbol: [ER_NET_WAIT_ERROR](#); SQLSTATE: [HY000](#)
Message: The wait_timeout period was exceeded, the idle time since last command was too long.
 - Error number: [MY-013418](#); Symbol: [ER_IB_MSG_1285](#); SQLSTATE: [HY000](#)
Message: '%s' found not encrypted while '%s' is ON. Trying to encrypt it now.
 - Error number: [MY-013419](#); Symbol: [ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: CLOCK_MONOTONIC is unsupported, so do not change the system time when MySQL is running !
 - Error number: [MY-013420](#); Symbol: [ER_IB_MSG_CLOCK_GETTIME_FAILED](#); SQLSTATE: [HY000](#)
Message: clock_gettime() failed: %s
 - Error number: [MY-013421](#); Symbol: [ER_PLUGIN_NOT_EARLY_DUP](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.
 - Error number: [MY-013422](#); Symbol: [ER_PLUGIN_NO_INSTALL_DUP](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.
 - Error number: [MY-013425](#); Symbol: [ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT](#); SQLSTATE: [HY000](#)
Message: The statement is unsafe because it invokes a trigger or a stored function that modifies a table that has a column with a DEFAULT expression that may return a different value on the replica.
 - Error number: [MY-013426](#); Symbol: [ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE](#); SQLSTATE: [HY000](#)
Message: Member version is read compatible with the group.
 - Error number: [MY-013427](#); Symbol: [ER_LOCK_ORDER_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Lock order disabled (reason: init failed).
 - Error number: [MY-013428](#); Symbol: [ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID](#); SQLSTATE: [HY000](#)
Message: Keyring ID timestamp value is invalid: '%s'
 - Error number: [MY-013429](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID](#); SQLSTATE: [HY000](#)
Message: File name timestamp value is missing or invalid: '%s'
 - Error number: [MY-013430](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT](#); SQLSTATE: [HY000](#)
Message: Cannot process audit log file. File name does not have required format: '%s'
 - Error number: [MY-013431](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING](#); SQLSTATE: [HY000](#)
Message: Cannot process audit log file. File name keyring ID value is missing: '%s'

-
- Error number: [MY-013432](#); Symbol: [ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED](#); SQLSTATE: [HY000](#)
Message: Audit log file has been successfully processed: '%s'
 - Error number: [MY-013433](#); Symbol: [ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING](#); SQLSTATE: [HY000](#)
Message: Could not open audit log file for reading: '%s'
 - Error number: [MY-013434](#); Symbol: [ER_AUDIT_LOG_INVALID_FILE_CONTENT](#); SQLSTATE: [HY000](#)
Message: Invalid audit log file content: '%s'
 - Error number: [MY-013435](#); Symbol: [ER_AUDIT_LOG_CANNOT_READ_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Cannot read password: '%s'.
 - Error number: [MY-013436](#); Symbol: [ER_AUDIT_LOG_CANNOT_STORE_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Cannot store password: '%s'.
 - Error number: [MY-013437](#); Symbol: [ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Cannot remove password: '%s'.
 - Error number: [MY-013438](#); Symbol: [ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED](#); SQLSTATE: [HY000](#)
Message: 'audit_log' password has been copied into '%s' and will be removed with first purged password.
 - Error number: [MY-013447](#); Symbol: [ER_LDAP_EMPTY_USERDN_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Empty user dn or password is not allowed, not attempting LDAP bind.
 - Error number: [MY-013449](#); Symbol: [ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG](#); SQLSTATE: [HY000](#)
Message: The current layout of the ACL tables does not conform to the server's expected layout. They're either altered, missing or not upgraded from a previous version. However a best effort attempt to read data from these tables will still be made.
 - Error number: [MY-013450](#); Symbol: [ER_LOCK_ORDER_FAILED_WRITE_FILE](#); SQLSTATE: [HY000](#)
Message: LOCK_ORDER: Failed to write to file <%s>.
 - Error number: [MY-013451](#); Symbol: [ER_LOCK_ORDER_FAILED_READ_FILE](#); SQLSTATE: [HY000](#)
Message: LOCK_ORDER: Failed to read from file <%s>.
 - Error number: [MY-013452](#); Symbol: [ER_LOCK_ORDER_MESSAGE](#); SQLSTATE: [HY000](#)
Message: LOCK_ORDER message: %s
 - Error number: [MY-013453](#); Symbol: [ER_LOCK_ORDER_DEPENDENCIES_SYNTAX](#); SQLSTATE: [HY000](#)
Message: Lock order dependencies file <%s> (%d:%d) - (%d:%d) : %s

-
- Error number: [MY-013454](#); Symbol: [ER_LOCK_ORDER_SCANNER_SYNTAX](#); SQLSTATE: [HY000](#)
Message: Lock order scanner: (%d:%d) - (%d:%d) : %s
 - Error number: [MY-013455](#); Symbol: [ER_DATA_DIRECTORY_UNUSABLE_DELETABLE](#); SQLSTATE: [HY000](#)
Message: The newly created data directory %s by --initialize is unusable. You can remove it.
 - Error number: [MY-013456](#); Symbol: [ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED](#); SQLSTATE: [HY000](#)
Message: No. of B-tree level created for index %s has crossed the permissible limit. If debug option innodb_limit_optimistic_insert_debug is being used try tweaking it to include more records in a page.
 - Error number: [MY-013457](#); Symbol: [ER_IB_CLONE_START_STOP](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013458](#); Symbol: [ER_IB_CLONE_OPERATION](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013459](#); Symbol: [ER_IB_CLONE_RESTART](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013460](#); Symbol: [ER_IB_CLONE_USER_DATA](#); SQLSTATE: [HY000](#)
Message: Clone removing all user data for provisioning: %s
 - Error number: [MY-013461](#); Symbol: [ER_IB_CLONE_NON_INNODB_TABLE](#); SQLSTATE: [HY000](#)
Message: Non innodb table: %s.%s is not cloned and is empty.
 - Error number: [MY-013462](#); Symbol: [ER_CLONE_SHUTDOWN_TRACE](#); SQLSTATE: [HY000](#)
Message: Clone shutting down server as RESTART failed. Please start server to complete clone operation.
 - Error number: [MY-013463](#); Symbol: [ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)
Message: Error when extracting this member GTID purged set. Operations and checks made to group joiners may be incomplete.
 - Error number: [MY-013464](#); Symbol: [ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue when configuring the remote cloning process: %s
 - Error number: [MY-013465](#); Symbol: [ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue when cloning from another server: %s
 - Error number: [MY-013466](#); Symbol: [ER_GRP_RPL_RECOVERY_EVAL_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue when trying to evaluate the best distributed recovery strategy while joining.%s

-
- Error number: [MY-013467](#); Symbol: [ER_GRP_RPL_NO_POSSIBLE_RECOVERY](#); SQLSTATE: [HY000](#)
Message: No valid or ONLINE members exist to get the missing data from the group. For cloning check if donors of the same version and with clone plugin installed exist. For incremental recovery check if you have donors where the required data was not purged from the binary logs.
 - Error number: [MY-013468](#); Symbol: [ER_GRP_RPL_CANT_KILL_THREAD](#); SQLSTATE: [HY000](#)
Message: The group replication plugin could not kill the plugin routine for %s. %s
 - Error number: [MY-013469](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD](#); SQLSTATE: [HY000](#)
Message: This member will start distributed recovery using clone. It is due to the number of missing transactions being higher than the configured threshold of %llu.
 - Error number: [MY-013470](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED](#); SQLSTATE: [HY000](#)
Message: This member will start distributed recovery using clone. It is due to no ONLINE member has the missing data for recovering in its binary logs.
 - Error number: [MY-013471](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CHOICE](#); SQLSTATE: [HY000](#)
Message: Distributed recovery will transfer data using: %s
 - Error number: [MY-013472](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_FALLBACK](#); SQLSTATE: [HY000](#)
Message: Due to some issue on the previous step distributed recovery is now executing: %s
 - Error number: [MY-013473](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK](#); SQLSTATE: [HY000](#)
Message: Due to a critical cloning error or lack of donors, distributed recovery cannot be executed. The member will now leave the group.
 - Error number: [MY-013474](#); Symbol: [ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE](#); SQLSTATE: [HY000](#)
Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server
 - Error number: [MY-013475](#); Symbol: [ER_UNKNOWN_TABLE_IN_UPGRADE](#); SQLSTATE: [HY000](#)
Message: Unknown table '%s'
 - Error number: [MY-013476](#); Symbol: [ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE](#); SQLSTATE: [HY000](#)
Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.
 - Error number: [MY-013477](#); Symbol: [ER_XA_CANT_CREATE_MDL_BACKUP](#); SQLSTATE: [HY000](#)
Message: XA: Failed to take MDL Lock backup of PREPARED XA transaction during client disconnect.
 - Error number: [MY-013478](#); Symbol: [ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED](#); SQLSTATE: [HY000](#)
Message: SUPER privilege or AUDIT_ADMIN role required for '%s'@'%s' user.

-
- Error number: [MY-013479](#); Symbol: [ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE](#); SQLSTATE: [HY000](#)
Message: Invalid argument type
 - Error number: [MY-013480](#); Symbol: [ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT](#); SQLSTATE: [HY000](#)
Message: Invalid argument count
 - Error number: [MY-013481](#); Symbol: [ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED](#); SQLSTATE: [HY000](#)
Message: audit_log plugin has not been installed using INSTALL PLUGIN syntax.
 - Error number: [MY-013482](#); Symbol: [ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE](#); SQLSTATE: [HY000](#)
Message: Invalid "max_array_length" argument type.
 - Error number: [MY-013483](#); Symbol: [ER_LOG_CANNOT_WRITE_EXTENDED](#); SQLSTATE: [HY000](#)
Message: Failed to write to %s: %s (%s)
 - Error number: [MY-013485](#); Symbol: [ER_KEYRING_AWS_INCORRECT_PROXY](#); SQLSTATE: [HY000](#)
Message: Incorrect environment variable %s, invalid port: %s
 - Error number: [MY-013486](#); Symbol: [ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS](#); SQLSTATE: [HY000](#)
Message: The server was automatically set into offline mode after an error was detected.
 - Error number: [MY-013487](#); Symbol: [ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR](#); SQLSTATE: [HY000](#)
Message: A message sent through the Group Replication message deliver service was not delivered successfully. The server will now leave the group. Try to add the server back to the group and check if the problem persists, or check previous messages in the log for hints of what could be the problem.
 - Error number: [MY-013488](#); Symbol: [ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG](#); SQLSTATE: [HY000](#)
Message: Invalid SOURCE_COMPRESSION_ALGORITHMS '%s' found in repository for channel '%s'. Resetting to 'uncompressed' (no compression).
 - Error number: [MY-013489](#); Symbol: [ER_WARN_WRONG_COMPRESSION_LEVEL_LOG](#); SQLSTATE: [HY000](#)
Message: Invalid SOURCE_ZSTD_COMPRESSION_LEVEL found in repository for channel '%s'. Resetting to %u.
 - Error number: [MY-013490](#); Symbol: [ER_PROTOCOL_COMPRESSION_RESET_LOG](#); SQLSTATE: [HY000](#)
Message: Option --protocol-compression-algorithms is reset to default value.
 - Error number: [MY-013491](#); Symbol: [ER_XPLUGIN_COMPRESSION_ERROR](#); SQLSTATE: [HY000](#)
Message: Fatal error while compressing outgoing data - %s
 - Error number: [MY-013492](#); Symbol: [ER_MYSQLBACKUP_MSG](#); SQLSTATE: [HY000](#)
Message: %s
-

-
- Error number: [MY-013493](#); Symbol: [ER_WARN_UNKNOWN_KEYRING_AWS_REGION](#); SQLSTATE: [HY000](#)

Message: Unknown keyring_aws_region '%s'. Connection to AWS KMS may fail.
 - Error number: [MY-013494](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to '%s'@'%s', but this is not an existing user. Correct this before starting replication threads.
 - Error number: [MY-013495](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Invalid, corrupted PRIVILEGE_CHECKS_USER was found in the replication configuration repository for channel '%s'. Use CHANGE REPLICATION SOURCE TO PRIVILEGE_CHECKS_USER to correct the configuration.
 - Error number: [MY-013496](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to '%s'@'%s', but this user does not have REPLICATION_APPLIER privilege. Correct this before starting the replication threads.
 - Error number: [MY-013497](#); Symbol: [ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#); SQLSTATE: [HY000](#)

Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE_CHECKS_USER.
 - Error number: [MY-013498](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s
 - Error number: [MY-013499](#); Symbol: [ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot generate password: '%s'
 - Error number: [MY-013500](#); Symbol: [ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Failed to generate a random password for root. Probably not enough entropy.
 - Error number: [MY-013501](#); Symbol: [ER_PLUGIN_LOAD_OPTIONS_IGNORED](#); SQLSTATE: [HY000](#)

Message: Ignoring --plugin-load[_add] list as the server is running with --initialize(-insecure).
 - Error number: [MY-013502](#); Symbol: [ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)

Message: Cannot set mandatory_roles: AuthId '%s'@'%s' has '%s' privilege. AuthId(s) set in the mandatory_roles are ignored.
 - Error number: [MY-013503](#); Symbol: [ER_IB_MSG_SKIP_HIDDEN_DIR](#); SQLSTATE: [HY000](#)

Message: Directory '%s' will not be scanned because it is a hidden directory.

-
- Error number: [MY-013504](#); Symbol: [ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE_EOF](#); SQLSTATE: [HY000](#)
Message: Server was not able to find a rotate event from source server to initialize relay log recovery for channel '%s'. Skipping relay log recovery for the channel.
 - Error number: [MY-013505](#); Symbol: [ER_IB_LOB_ROLLBACK_INDEX_LEN](#); SQLSTATE: [HY000](#)
Message: Rolling back LOB for transaction %llu undo number %llu : current index length %llu. (iteration %llu)
 - Error number: [MY-013506](#); Symbol: [ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN_TO_DD](#); SQLSTATE: [HY000](#)
Message: Error in processing (possibly deprecated) expression or function '%s' for generated column %s.%s.%s
 - Error number: [MY-013507](#); Symbol: [ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT](#); SQLSTATE: [HY000](#)
Message: The queue event failed for channel '%s' as an invalid event according to REQUIRE_ROW_FORMAT was found.
 - Error number: [MY-013508](#); Symbol: [ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION](#); SQLSTATE: [HY000](#)
Message: The application of relay events failed for channel '%s' as an invalid event according to REQUIRE_ROW_FORMAT was found.
 - Error number: [MY-013509](#); Symbol: [ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SET](#); SQLSTATE: [HY000](#)
Message: PRIVILEGE_CHECKS_USER for replication channel '%s' can't be set to '%s'@'%s' unless REQUIRE_ROW_FORMAT is also set to %d.
 - Error number: [MY-013510](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)
Message: An unexpected event sequence was detected by the SQL thread while applying an event.
 - Error number: [MY-013511](#); Symbol: [ER_IB_MSG_UPGRADE_PARTITION_FILE](#); SQLSTATE: [HY000](#)
Message: Updating partition file name '%s' to '%s' and all other partition files during upgrade
 - Error number: [MY-013512](#); Symbol: [ER_IB_MSG_DOWNGRADE_PARTITION_FILE](#); SQLSTATE: [HY000](#)
Message: Updating partition file name '%s' to '%s' and all other partition files during downgrade
 - Error number: [MY-013513](#); Symbol: [ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT](#); SQLSTATE: [HY000](#)
Message: Updating partition file name '%s' to '%s' for import
 - Error number: [MY-013514](#); Symbol: [ER_IB_WARN_OPEN_PARTITION_FILE](#); SQLSTATE: [HY000](#)
Message: Unable to open partition file with new name '%s'. Please check if innodb_directories is set to include all external file paths
 - Error number: [MY-013515](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_CORRECTED](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Partition tablespace %u, name '%s' is corrected to '%s'

- Error number: [MY-013516](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Tablespace %u, name '%s', '%s' is moved to '%s'

- Error number: [MY-013517](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Partition tablespace %u, name '%s', '%s' is updated to '%s'

- Error number: [MY-013518](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY](#); SQLSTATE: [HY000](#)

Message: %s Too many files have been moved, disabling logging of detailed messages

- Error number: [MY-013519](#); Symbol: [ER_GR_ELECTED_PRIMARY_GTID_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Elected primary member %s: %s

- Error number: [MY-013520](#); Symbol: [ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters is not allowed with lower_case_table_names = 1.

- Error number: [MY-013521](#); Symbol: [ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters is not allowed with lower_case_table_names = 1.

- Error number: [MY-013522](#); Symbol: [ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower_case_table_names = 1.

- Error number: [MY-013523](#); Symbol: [ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower_case_table_names = 1.

- Error number: [MY-013524](#); Symbol: [ER_IB_MSG_DICT_PARTITION_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Table Partition: %s is not found in InnoDB dictionary

- Error number: [MY-013525](#); Symbol: [ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins. Use FLUSH PRIVILEGES or ALTER USER to reset.

- Error number: [MY-013526](#); Symbol: [ER_INNO_DB_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013528](#); Symbol: [ER_MIGRATE_TABLE_TO_DD_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate memory for key_info when migrating table %s.%s

- Error number: [MY-013529](#); Symbol: [ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE](#); SQLSTATE: [HY000](#)

Message: Applier metadata information for channel '%s' was found after a clone operation. Relay log recovery will be executed to adjust positions and file information for this new server. Should that automatic procedure fail please adjust the positions through 'CHANGE REPLICATION SOURCE TO'

- Error number: [MY-013531](#); Symbol: [ER_IB_MSG_DBLWR_1285](#); SQLSTATE: [HY000](#)

Message: Empty doublewrite file: %s

- Error number: [MY-013532](#); Symbol: [ER_IB_MSG_DBLWR_1286](#); SQLSTATE: [HY000](#)

Message: Using '%s' for doublewrite

- Error number: [MY-013533](#); Symbol: [ER_IB_MSG_DBLWR_1287](#); SQLSTATE: [HY000](#)

Message: Error reading doublewrite buffer from the system tablespace

- Error number: [MY-013534](#); Symbol: [ER_IB_MSG_DBLWR_1288](#); SQLSTATE: [HY000](#)

Message: Cannot create doublewrite buffer: you must increase your buffer pool size. Cannot continue operation.

- Error number: [MY-013535](#); Symbol: [ER_IB_MSG_DBLWR_1290](#); SQLSTATE: [HY000](#)

Message: The page in the doublewrite file is corrupt. Cannot continue operation. You can try to recover the database with innodb_force_recovery=6

- Error number: [MY-013536](#); Symbol: [ER_IB_MSG_BAD_DBLWR_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: The doublewrite filename '%s' is incorrect.

- Error number: [MY-013538](#); Symbol: [ER_IB_MSG_DBLWR_1293](#); SQLSTATE: [HY000](#)

Message: Doublewrite file create failed: %s

- Error number: [MY-013539](#); Symbol: [ER_IB_MSG_DBLWR_1294](#); SQLSTATE: [HY000](#)

Message: DBLWRThread: pthread_setaffinity() failed!

- Error number: [MY-013540](#); Symbol: [ER_IB_MSG_DBLWR_1295](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013541](#); Symbol: [ER_IB_MSG_DBLWR_1296](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013542](#); Symbol: [ER_IB_MSG_DBLWR_1297](#); SQLSTATE: [HY000](#)

Message: Doublewrite file read failed: %s

- Error number: [MY-013543](#); Symbol: [ER_IB_MSG_DBLWR_1298](#); SQLSTATE: [HY000](#)

Message: Dump of the data file page:

- Error number: [MY-013544](#); Symbol: [ER_IB_MSG_DBLWR_1300](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013545](#); Symbol: [ER_IB_MSG_DBLWR_1301](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: MY-013546; Symbol: ER_IB_MSG_DBLWR_1304; SQLSTATE: HY000

Message: %s

- Error number: MY-013547; Symbol: ER_IB_MSG_DBLWR_1305; SQLSTATE: HY000

Message: %s

- Error number: MY-013548; Symbol: ER_IB_MSG_DBLWR_1306; SQLSTATE: HY000

Message: %s

- Error number: MY-013549; Symbol: ER_IB_MSG_DBLWR_1307; SQLSTATE: HY000

Message: %s

- Error number: MY-013550; Symbol: ER_IB_MSG_DBLWR_1308; SQLSTATE: HY000

Message: %s

- Error number: MY-013551; Symbol: ER_IB_MSG_DBLWR_1309; SQLSTATE: HY000

Message: %s

- Error number: MY-013552; Symbol: ER_IB_MSG_DBLWR_1310; SQLSTATE: HY000

Message: %s

- Error number: MY-013553; Symbol: ER_IB_MSG_DBLWR_1311; SQLSTATE: HY000

Message: %s

- Error number: MY-013554; Symbol: ER_IB_MSG_DBLWR_1312; SQLSTATE: HY000

Message: %s

- Error number: MY-013555; Symbol: ER_IB_MSG_DBLWR_1313; SQLSTATE: HY000

Message: %s

- Error number: MY-013556; Symbol: ER_IB_MSG_DBLWR_1314; SQLSTATE: HY000

Message: %s

- Error number: MY-013557; Symbol: ER_IB_MSG_DBLWR_1315; SQLSTATE: HY000

Message: %s

- Error number: MY-013558; Symbol: ER_IB_MSG_DBLWR_1316; SQLSTATE: HY000

Message: %s

- Error number: MY-013559; Symbol: ER_IB_MSG_DBLWR_1317; SQLSTATE: HY000

Message: %s

- Error number: MY-013560; Symbol: ER_IB_MSG_DBLWR_1318; SQLSTATE: HY000

Message: %s

- Error number: MY-013561; Symbol: ER_IB_MSG_DBLWR_LOAD_WRONG_SIZE; SQLSTATE: HY000

Message: Doublewrite load file %s size %llu is not a multiple of the configured page size %zu

-
- Error number: [MY-013562](#); Symbol: [ER_IB_MSG_DBLWR_1320](#); SQLSTATE: [HY000](#)
Message: Doublewrite file %s truncate failed
 - Error number: [MY-013563](#); Symbol: [ER_IB_MSG_DBLWR_1321](#); SQLSTATE: [HY000](#)
Message: Doublewrite file %s failed to writ zeros
 - Error number: [MY-013564](#); Symbol: [ER_IB_MSG_DBLWR_OPEN_OR_CREATE_WRONG_SIZE](#); SQLSTATE: [HY000](#)
Message: Doublewrite open or create file %s size %llu is not a multiple of the configured page size %zu
 - Error number: [MY-013565](#); Symbol: [ER_IB_MSG_DBLWR_1323](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013566](#); Symbol: [ER_IB_MSG_DBLWR_1324](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013567](#); Symbol: [ER_IB_MSG_DBLWR_1325](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013568](#); Symbol: [ER_IB_MSG_DBLWR_1326](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013569](#); Symbol: [ER_IB_MSG_DBLWR_1327](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013570](#); Symbol: [ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Could not flush all GTIDs during slow shutdown. Will recover GTIDs when server restarts.
 - Error number: [MY-013571](#); Symbol: [ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to delete 5.7 stat tablespace: %s during upgrade
 - Error number: [MY-013572](#); Symbol: [ER_NDBINFO_UPGRADING_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Installing ndbinfo schema version %s
 - Error number: [MY-013573](#); Symbol: [ER_NDBINFO_NOT_UPGRADING_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Installed ndbinfo schema is current. Not upgrading.
 - Error number: [MY-013574](#); Symbol: [ER_NDBINFO_UPGRADING_SCHEMA_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to upgrade ndbinfo schema.
 - Error number: [MY-013576](#); Symbol: [ER_IB_MSG_INNODB_START_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: InnoDB initialization has started.
 - Error number: [MY-013577](#); Symbol: [ER_IB_MSG_INNODB_END_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: InnoDB initialization has ended.

-
- Error number: [MY-013578](#); Symbol: [ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS](#); SQLSTATE: [HY000](#)
Message: Could not find appropriate reset points.
 - Error number: [MY-013579](#); Symbol: [ER_IB_WRN_PAGE_ARCH_FLUSH_DATA](#); SQLSTATE: [HY000](#)
Message: Unable to flush. Page archiving data may be corrupt in case of a crash.
 - Error number: [MY-013580](#); Symbol: [ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUF](#); SQLSTATE: [HY000](#)
Message: Page archiver's doublewrite buffer for %ld is not valid.
 - Error number: [MY-013581](#); Symbol: [ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)
Message: Page archiver system's recovery failed.
 - Error number: [MY-013582](#); Symbol: [ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT](#); SQLSTATE: [HY000](#)
Message: Invalid archived file name format. The archived file is supposed to have the format %s + [0-9]*.
 - Error number: [MY-013583](#); Symbol: [ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER](#); SQLSTATE: [HY000](#)
Message: X Plugins UNIX socket must use different file than MySQL server. X Plugin won't be accessible through UNIX socket
 - Error number: [MY-013584](#); Symbol: [ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013586](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN](#); SQLSTATE: [HY000](#)
Message: Undo Truncation is occurring too often. Consider increasing --innodb-max-undo-log-size.
 - Error number: [MY-013587](#); Symbol: [ER_GRP_RPL_IS_STARTING](#); SQLSTATE: [HY000](#)
Message: Plugin 'group_replication' is starting.
 - Error number: [MY-013588](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE](#); SQLSTATE: [HY000](#)
Message: Cannot create tablespace %s because the directory is not a valid location. %s
 - Error number: [MY-013589](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_WRONG_DB](#); SQLSTATE: [HY000](#)
Message: Scanned file '%s' for tablespace %s cannot be opened because it is not in a sub-directory named for the schema.
 - Error number: [MY-013590](#); Symbol: [ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE](#); SQLSTATE: [HY000](#)
Message: Cannot find undo tablespace %s with filename '%s' as indicated by the Data Dictionary. Did you move or delete this tablespace? Any undo logs in it cannot be used.
 - Error number: [MY-013591](#); Symbol: [ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port).

- Error number: [MY-013592](#); Symbol: [ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID](#); SQLSTATE: [HY000](#)

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

- Error number: [MY-013593](#); Symbol: [ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT](#); SQLSTATE: [HY000](#)

Message: Received invalid recovery endpoints configuration from donor. This member is not a valid donor for recovery, so it will be skipped.

- Error number: [MY-013594](#); Symbol: [ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS](#); SQLSTATE: [HY000](#)

Message: Failed to retrieve IP addresses from enabled host network interfaces.

- Error number: [MY-013595](#); Symbol: [ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to initialize TLS for channel: %s. See below for the description of exact issue.

- Error number: [MY-013596](#); Symbol: [ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Validation of value '%s' set to `Mysqlx\_bind\_address` failed: %s. Skipping this value.

- Error number: [MY-013597](#); Symbol: [ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Value '%s' set to `Mysqlx\_bind\_address`, X Plugin can't bind to it. Skipping this value.

- Error number: [MY-013598](#); Symbol: [ER_IB_ERR_RECOVERY_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: Server was killed when InnoDB redo logging was disabled. Data files could be corrupt. You can try to restart the database with `innodb_force_recovery=6`

- Error number: [MY-013599](#); Symbol: [ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB cannot do cold shutdown 'innodb_fast_shutdown = 2' and is forcing 'innodb_fast_shutdown = 1' as redo logging is disabled. InnoDB would flush all dirty pages to ensure physical data consistency.

- Error number: [MY-013600](#); Symbol: [ER_IB_WRN_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB redo logging is disabled. All data could be lost in case of a server crash.

- Error number: [MY-013601](#); Symbol: [ER_IB_WRN_REDO_ENABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB redo logging is enabled. Data is now safe and can be recovered in case of a server crash.

- Error number: [MY-013602](#); Symbol: [ER_TLS_CONFIGURED_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Channel %s configured to support TLS. Encrypted connections are now supported for this channel.

-
- Error number: [MY-013603](#); Symbol: [ER_TLS_CONFIGURATION_REUSED](#); SQLSTATE: [HY000](#)
Message: No TLS configuration was given for channel %s; re-using TLS configuration of channel %s.
 - Error number: [MY-013604](#); Symbol: [ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED](#); SQLSTATE: [HY000](#)
Message: Skipping InnoDB tablespace path validation. Manually moved tablespace files will not be detected!
 - Error number: [MY-013605](#); Symbol: [ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES](#); SQLSTATE: [HY000](#)
Message: Upgrade failed because database contains discarded tablespaces.
 - Error number: [MY-013606](#); Symbol: [ER_USERNAME_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: The user name '%s' exceeds the maximum number of allowed characters %d and is truncated.
 - Error number: [MY-013607](#); Symbol: [ER_HOSTNAME_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: The host name '%s' exceeds the maximum number of allowed characters %d and is truncated.
 - Error number: [MY-013608](#); Symbol: [ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED](#); SQLSTATE: [HY000](#)
Message: Rollback of non-prepared transactions not completed, due to fast shutdown
 - Error number: [MY-013609](#); Symbol: [ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME](#); SQLSTATE: [HY000](#)
Message: Found an entry in the 'role_edges' table with empty authorization ID; Skipped
 - Error number: [MY-013610](#); Symbol: [ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID](#); SQLSTATE: [HY000](#)
Message: Found an entry in the 'role_edges' table with unknown authorization ID '%s'; Skipped
 - Error number: [MY-013611](#); Symbol: [ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME](#); SQLSTATE: [HY000](#)
Message: Found an entry in the 'default_roles' table with empty authorization ID; Skipped
 - Error number: [MY-013612](#); Symbol: [ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID](#); SQLSTATE: [HY000](#)
Message: Found an entry in the 'default_roles' table with unknown authorization ID '%s'; Skipped
 - Error number: [MY-013613](#); Symbol: [ER_IB_ERR_DDL_LOG_INSERT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Couldn't insert entry in ddl log for ddl.
 - Error number: [MY-013614](#); Symbol: [ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013615](#); Symbol: [ER_IB_RELOCK_LATCH_ORDER_VIOLATION](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: MY-013621; Symbol: ER_IB_MSG_1357; SQLSTATE: HY000

Message: %s

- Error number: MY-013622; Symbol: ER_IB_MSG_1358; SQLSTATE: HY000

Message: %s

- Error number: MY-013623; Symbol: ER_IB_MSG_1359; SQLSTATE: HY000

Message: %s

- Error number: MY-013624; Symbol: ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE; SQLSTATE: HY000

Message: %s

- Error number: MY-013625; Symbol: ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE_POOL; SQLSTATE: HY000

Message: %s

- Error number: MY-013626; Symbol: ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY; SQLSTATE: HY000

Message: %s

- Error number: MY-013627; Symbol: ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR; SQLSTATE: HY000

Message: %s

- Error number: MY-013628; Symbol: ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST; SQLSTATE: HY000

Message: %s

- Error number: MY-013629; Symbol: ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY; SQLSTATE: HY000

Message: %s

- Error number: MY-013630; Symbol: ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON; SQLSTATE: HY000

Message: %s

- Error number: MY-013631; Symbol: ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR; SQLSTATE: HY000

Message: %s

- Error number: MY-013632; Symbol: ER_IB_ERR_SCHED_SETAFFINITY_FAILED; SQLSTATE: HY000

Message: %s

- Error number: MY-013633; Symbol: ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE; SQLSTATE: HY000

Message: %s

-
- Error number: [MY-013634](#); Symbol: [ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013635](#); Symbol: [ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013636](#); Symbol: [ER_IB_MSG_1372](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013637](#); Symbol: [ER_IB_MSG_1373](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013638](#); Symbol: [ER_IB_MSG_1374](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013639](#); Symbol: [ER_IB_MSG_1375](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013640](#); Symbol: [ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013641](#); Symbol: [ER_IB_ERR_ZLIB_BUF_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013642](#); Symbol: [ER_IB_ERR_ZLIB_MEM_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013643](#); Symbol: [ER_IB_ERR_ZLIB_DATA_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013644](#); Symbol: [ER_IB_ERR_ZLIB_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013645](#); Symbol: [ER_IB_MSG_1381](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013646](#); Symbol: [ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013647](#); Symbol: [ER_IB_ERR_INDEX_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013648](#); Symbol: [ER_IB_ERR_FOUND_N_DUPLICATE_KEYS](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-013649](#); Symbol: [ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013650](#); Symbol: [ER_IB_ERR_PARALLEL_READ_OOM](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013651](#); Symbol: [ER_IB_MSG_UNDO_MARKED_ACTIVE](#); SQLSTATE: [HY000](#)
Message: The state of undo tablespace %s is set to active implicitly.
 - Error number: [MY-013652](#); Symbol: [ER_IB_MSG_UNDO_ALTERED_ACTIVE](#); SQLSTATE: [HY000](#)
Message: The state of undo tablespace %s is set to 'active' by ALTER TABLESPACE.
 - Error number: [MY-013653](#); Symbol: [ER_IB_MSG_UNDO_ALTERED_INACTIVE](#); SQLSTATE: [HY000](#)
Message: The state of undo tablespace %s is set to 'inactive' by ALTER TABLESPACE.
 - Error number: [MY-013654](#); Symbol: [ER_IB_MSG_UNDO_MARKED_EMPTY](#); SQLSTATE: [HY000](#)
Message: The state of undo tablespace %s is set to 'empty'.
 - Error number: [MY-013655](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE](#); SQLSTATE: [HY000](#)
Message: Delaying truncate of undo tablespace %s due to clone activity.
 - Error number: [MY-013656](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL](#); SQLSTATE: [HY000](#)
Message: Delaying truncate of undo tablespace %s due to a metadata lock.
 - Error number: [MY-013657](#); Symbol: [ER_IB_MSG_INJECT_CRASH](#); SQLSTATE: [HY000](#)
Message: Injected debug crash point: %s
 - Error number: [MY-013658](#); Symbol: [ER_IB_MSG_INJECT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Injected debug failure point: %s
 - Error number: [MY-013659](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN](#); SQLSTATE: [HY000](#)
Message: Timeout while waiting for a view change event during the leave step before a auto-rejoin attempt.
 - Error number: [MY-013660](#); Symbol: [ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE](#); SQLSTATE: [HY000](#)
Message: Failed to automatically re-connect to a different source, for channel '%s', because %s. To fix this %s.
 - Error number: [MY-013661](#); Symbol: [ER_UDF_REGISTER_SERVICE_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not execute the installation of UDF functions. Check for other errors in the log
 - Error number: [MY-013662](#); Symbol: [ER_UDF_REGISTER_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not execute the installation of UDF function: %s. Check if the function is already present, if so, try to remove it.

-
- Error number: [MY-013663](#); Symbol: [ER_UDF_UNREGISTER_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not uninstall UDF functions. Try to remove them manually if present.
 - Error number: [MY-013664](#); Symbol: [ER_EMPTY_PRIVILEGE_NAME_IGNORED](#); SQLSTATE: [HY000](#)
Message: An empty or illegal privilege identifier was ignored when global privileges were read from disk.
 - Error number: [MY-013665](#); Symbol: [ER_IB_MSG_INCORRECT_SIZE](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013666](#); Symbol: [ER_TMPDIR_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: A tmpdir temporary path "%s" is too long (> %zu) for this OS. This would not leave enough space for a temporary filename of length %zu within it.
 - Error number: [MY-013667](#); Symbol: [ER_ERROR_LOG_DESTINATION_NOT_A_FILE](#); SQLSTATE: [HY000](#)
Message: Error-log destination "%s" is not a file. Can not restore error log messages from previous run.
 - Error number: [MY-013668](#); Symbol: [ER_NO_ERROR_LOG_PARSER_CONFIGURED](#); SQLSTATE: [HY000](#)
Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance_schema.error_log.
 - Error number: [MY-013669](#); Symbol: [ER_UPGRADE_NONEXISTENT_SCHEMA](#); SQLSTATE: [HY000](#)
Message: The schema "%s" referenced by %s "%s" does not exist. Please clean up any orphan %s before upgrading.
 - Error number: [MY-013670](#); Symbol: [ER_IB_MSG_CREATED_UNDO_SPACE](#); SQLSTATE: [HY000](#)
Message: Created undo tablespace '%s'.
 - Error number: [MY-013671](#); Symbol: [ER_IB_MSG_DROPPED_UNDO_SPACE](#); SQLSTATE: [HY000](#)
Message: Dropped undo tablespace '%s'.
 - Error number: [MY-013672](#); Symbol: [ER_IB_MSG_MASTER_KEY_ROTATED](#); SQLSTATE: [HY000](#)
Message: The InnoDB Encryption Master Key has been rotated in %d tablespaces.
 - Error number: [MY-013673](#); Symbol: [ER_IB_DBLWR_DECOMPRESS_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to decompress a DBLWR page (err=%d). The original size is %d. Reporting the dblwr page as corrupted.
 - Error number: [MY-013674](#); Symbol: [ER_IB_DBLWR_DECRYPT_FAILED](#); SQLSTATE: [HY000](#)
Message: Decrypting a page in doublewrite file failed: %s.
 - Error number: [MY-013675](#); Symbol: [ER_IB_DBLWR_KEY_MISSING](#); SQLSTATE: [HY000](#)
Message: Encryption key missing: %s.
 - Error number: [MY-013676](#); Symbol: [ER_INNODB_IO_WRITE_ERROR_RETRYING](#); SQLSTATE: [HY000](#)

Message: I/O error while writing to file: %s. Retrying ...

- Error number: [MY-013677](#); Symbol: [ER_INNODB_IO_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write data to file: %s

- Error number: [MY-013678](#); Symbol: [ER_LOG_COMPONENT_CANNOT_INIT](#); SQLSTATE: [HY000](#)

Message: Log component %s failed to initialize.

- Error number: [MY-013679](#); Symbol: [ER_RPL_ASYNC_CHANNEL_CANT_CONNECT](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread failed to connect to the source (host:%s port:%u network_namespace:%s) for channel '%s', thence it will try to connect to another source.

- Error number: [MY-013680](#); Symbol: [ER_RPL_ASYNC_SENDER_ADDED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has joined the group (group_name: %s), and so added its entry into replication_asynchronous_connection_failover table.

- Error number: [MY-013681](#); Symbol: [ER_RPL_ASYNC_SENDER_REMOVED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has left the group (group_name: %s), and so removed its entry from replication_asynchronous_connection_failover table.

- Error number: [MY-013682](#); Symbol: [ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

- Error number: [MY-013683](#); Symbol: [ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM](#); SQLSTATE: [HY000](#)

Message: The IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

- Error number: [MY-013685](#); Symbol: [ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica Monitor IO thread exiting.

- Error number: [MY-013686](#); Symbol: [ER_RPL_ASYNC_MANAGED_NAME_REMOVED](#); SQLSTATE: [HY000](#)

Message: The group (group_name: %s) for the channel '%s' has been removed, and so removed its entry from replication_asynchronous_connection_failover_managed and all the group members from replication_asynchronous_connection_failover table.

- Error number: [MY-013687](#); Symbol: [ER_RPL_ASYNC_MANAGED_NAME_ADDED](#); SQLSTATE: [HY000](#)

Message: The group (group_name: %s) for the channel '%s' has been added, and so added its entry in replication_asynchronous_connection_failover_managed and source to replication_asynchronous_connection_failover table.

- Error number: [MY-013688](#); Symbol: [ER_RPL_ASYNC_READ_FAILOVER_TABLE](#); SQLSTATE: [HY000](#)

Message: Error reading failover sources for channel '%s' from replication_asynchronous_connection_failover table.

- Error number: [MY-013689](#); Symbol: [ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error %s the channel '%s', the operation will be automatically retried.

- Error number: [MY-013690](#); Symbol: [ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`. If you intend to not use GTIDs at all in the replication topology, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF` and leave `GTID_MODE = '%s'`.

- Error number: [MY-013691](#); Symbol: [ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to `group_replication_group_name`. To fix this issue, either change the `group_replication_group_name` or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.

- Error number: [MY-013692](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID](#); SQLSTATE: [HY000](#)

Message: The `group_replication_group_name '%s'` is the same as the UUID value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` in a server channel

- Error number: [MY-013693](#); Symbol: [ER_WARN_GTID_THRESHOLD_BREACH](#); SQLSTATE: [HY000](#)

Message: The integer component of the GTID number is high. Suggest restarting the server with a new `server_uuid` to prevent it from reaching the maximum number $2^{63}-1$, which will make it impossible to write the binary log and invoke the behavior specified by `binlog_error_action`.

- Error number: [MY-013694](#); Symbol: [ER_HEALTH_INFO](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013695](#); Symbol: [ER_HEALTH_WARNING](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013696](#); Symbol: [ER_HEALTH_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013697](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 1 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

- Error number: [MY-013698](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 2 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

- Error number: [MY-013699](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 3 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

- Error number: [MY-013700](#); Symbol: [ER_IB_INNO_DB_TBSP_OUT_OF_SPACE](#); SQLSTATE: [HY000](#)

Message: InnoDB: Size of tablespace %s is more than the maximum size allowed.

- Error number: [MY-013701](#); Symbol: [ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING](#); SQLSTATE: [HY000](#)

Message: The group_replication_applier channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

- Error number: [MY-013702](#); Symbol: [ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '%s' was configured with SOURCE_CONNECTION_AUTO_FAILOVER = 1, but the server was started with a value other than --gtid-mode = ON. Either reconfigure replication using CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 0 FOR CHANNEL '%s', or change GTID_MODE to value ON, before starting the replica receiver thread.

- Error number: [MY-013703](#); Symbol: [ER_FIREWALL_SERVICES_NOT_ACQUIRED](#); SQLSTATE: [HY000](#)

Message: Could not acquire required component services.

- Error number: [MY-013704](#); Symbol: [ER_FIREWALL_UDF_REGISTER_FAILED](#); SQLSTATE: [HY000](#)

Message: Automatic registration of function(s) failed.

- Error number: [MY-013705](#); Symbol: [ER_FIREWALL_PFS_TABLE_REGISTER_FAILED](#); SQLSTATE: [HY000](#)

Message: Automatic registration of Performance schema table(s) failed.

- Error number: [MY-013706](#); Symbol: [ER_IB_MSG_STATS_SAMPLING_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013707](#); Symbol: [ER_AUDIT_LOG_FILE_PRUNE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to auto-prune file '%s', Error (%d): %s

- Error number: [MY-013708](#); Symbol: [ER_AUDIT_LOG_FILE_AUTO_PRUNED](#); SQLSTATE: [HY000](#)

Message: File '%s' auto-pruned

- Error number: [MY-013709](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT](#); SQLSTATE: [HY000](#)

Message: Received an error while processing components from manifest file: %s

- Error number: [MY-013710](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT](#); SQLSTATE: [HY000](#)

Message: Received an error while unloading components read from manifest file: %s

- Error number: [MY-013711](#); Symbol: [ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_R0](#); SQLSTATE: [HY000](#)

Message: Manifest file '%s' is not read-only. For better security, please make sure that the file is read-only.

- Error number: [MY-013712](#); Symbol: [ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND](#); SQLSTATE: [HY000](#)

Message: No suitable '%s' service implementation found to fulfill the request.

- Error number: [MY-013713](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: Keyring component initialized successfully.

- Error number: [MY-013714](#); Symbol: [ER_KEYRING_COMPONENT_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: The component is not initialized properly. Error: %s. Make sure that configuration is proper and use ALTER INSTANCE RELOAD KEYRING to reinitialize the component.

- Error number: [MY-013715](#); Symbol: [ER_KEYRING_COMPONENT_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Keyring component encountered an exception while executing : '%s' API of service: '%s'

- Error number: [MY-013716](#); Symbol: [ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to allocated memory for '%s' while executing: '%s' API of service: '%s'

- Error number: [MY-013717](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE](#); SQLSTATE: [HY000](#)

Message: Empty or 0 values for AES encryption mode and/or block size are not permitted.

- Error number: [MY-013718](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY](#); SQLSTATE: [HY000](#)

Message: A valid data identifier is required in order to fetch the key required for the AES operation.

- Error number: [MY-013719](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY](#); SQLSTATE: [HY000](#)

Message: Key identified by Data ID: '%s' and Auth ID: '%s' is not of type AES.

- Error number: [MY-013720](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR](#); SQLSTATE: [HY000](#)

Message: Encountered error: '%s' while executing '%s' API of keyring_aes service. Key details are Data ID: '%s' and Auth ID: '%s'.

- Error number: [MY-013721](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Could not find the data corresponding to Data ID: '%s', Auth ID: '%s'.

- Error number: [MY-013722](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH](#); SQLSTATE: [HY000](#)

Message: Maximum permissible size of data is '%zu' bits

-
- Error number: [MY-013723](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_STORE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error writing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.
 - Error number: [MY-013724](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error removing data for Data ID: '%s', Auth ID: '%s'. Either data does not exists with same identifier or keyring backend encountered an error.
 - Error number: [MY-013725](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error generating data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.
 - Error number: [MY-013726](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FETCH_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to get metadata from current keys metadata iterator position.
 - Error number: [MY-013727](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_INVALID_OUT_PARAM](#); SQLSTATE: [HY000](#)

Message: Key and value length parameters must not be null.
 - Error number: [MY-013728](#); Symbol: [ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE](#); SQLSTATE: [HY000](#)

Message: Innodb could not acquire service : %s
 - Error number: [MY-013729](#); Symbol: [ER_IB_WRN_OLD_GEOMETRY_TYPE](#); SQLSTATE: [HY000](#)

Message: Column %s of type GEOMETRY is in old (5.6) format which could be deprecated in the future. To change the format to latest, please consider rebuilding the table after the upgrade.
 - Error number: [MY-013730](#); Symbol: [ER_NET_WAIT_ERROR2](#); SQLSTATE: [HY000](#)

Message: 'wait_timeout' period of %s seconds was exceeded for %s. The idle time since last command was too long.
 - Error number: [MY-013731](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_TRIGGERED](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" will be run.
 - Error number: [MY-013732](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed, this error is ignored as instructed. Please check previous messages in the error log for hints about what could have caused this failure.
 - Error number: [MY-013733](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_FAILURE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed. Please check previous messages in the error log for hints about what could have caused this failure.

-
- Error number: [MY-013734](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the primary.
 - Error number: [MY-013735](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration with the one sent by the primary. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.
 - Error number: [MY-013736](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to read the member actions configuration during group membership change. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.
 - Error number: [MY-013737](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support member actions, as such it did reset its member configuration to the default one.
 - Error number: [MY-013738](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Unable to reset to member actions default configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.
 - Error number: [MY-013739](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the group on member join.
 - Error number: [MY-013740](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.
 - Error number: [MY-013741](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: The group members were unable to send their member actions configuration. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version' on all members.
 - Error number: [MY-013742](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_ENABLED](#); SQLSTATE: [HY000](#)

Message: Member action enabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".
 - Error number: [MY-013743](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_DISABLED](#); SQLSTATE: [HY000](#)

Message: Member action disabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

-
- Error number: [MY-013744](#); Symbol: [ER_GRP_RPL_MEMBER_ACTIONS_RESET](#); SQLSTATE: [HY000](#)
Message: Member actions configuration was reset.
 - Error number: [MY-013747](#); Symbol: [ER_FIREWALL_DEPRECATED_USER_PROFILE](#); SQLSTATE: [HY000](#)
Message: User profile '%s' loaded. Firewall user profiles are deprecated, consider migrating to group profiles.
 - Error number: [MY-013748](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID](#); SQLSTATE: [HY000](#)
Message: Invalid input value for group_replication_view_change_uuid '%s'. Please, provide a valid UUID.
 - Error number: [MY-013749](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME](#); SQLSTATE: [HY000](#)
Message: Variable 'group_replication_view_change_uuid' cannot be set to the value of '%s'. If you want to use the UUID of 'group_replication_group_name' for the UUID of View_change_log_events, please set 'group_replication_view_change_uuid' to AUTOMATIC.
 - Error number: [MY-013750](#); Symbol: [ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)
Message: group_replication_group_name '%s', which is the same as group_replication_view_change_uuid. Please change group_replication_view_change_uuid to AUTOMATIC
 - Error number: [MY-013751](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID](#); SQLSTATE: [HY000](#)
Message: The group_replication_view_change_uuid '%s' is the same as the UUID value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS in a server channel
 - Error number: [MY-013752](#); Symbol: [ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE_WITH_SERVER_UUID](#); SQLSTATE: [HY000](#)
Message: group_replication_view_change_uuid is incompatible with group.
group_replication_view_change_uuid %s matches server_uuid %s.
 - Error number: [MY-013753](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)
Message: The member is configured with a group_replication_view_change_uuid option value '%s' different from the group '%s'. The member will now exit the group.
 - Error number: [MY-013754](#); Symbol: [ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)
Message: Replication channel '%s' is configured with
ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s' which is
equal to group_replication_view_change_uuid. To fix this issue, either
change the group_replication_view_change_uuid or use a different value for
ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS.
 - Error number: [MY-013755](#); Symbol: [ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)
-

Message: Unable to parse the group_replication_view_change_uuid.

- Error number: MY-013756; Symbol: ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID; SQLSTATE: HY000

Message: Unable to generate sidno for group_replication_view_change_uuid.

- Error number: MY-013757; Symbol: ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR; SQLSTATE: HY000

Message: Unable to parse the group_replication_view_change_uuid during the Certification module initialization.

- Error number: MY-013758; Symbol: ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EXECUTED_ERROR; SQLSTATE: HY000

Message: Error updating group_gtid_executed GTID set with view change uuid during the Certification module initialization.

- Error number: MY-013759; Symbol: ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR; SQLSTATE: HY000

Message: Unable to add the group_replication_view_change_uuid sidno in the group_gtid_sid_map during the Certification module initialization.

- Error number: MY-013760; Symbol: ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR; SQLSTATE: HY000

Message: Unable to handle the donor's view change uuid transaction information when initializing the conflict detection component. Possible out of memory error.

- Error number: MY-013761; Symbol: ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE; SQLSTATE: HY000

Message: Unable to retrieve group_replication_view_change_uuid during server checks on replication operations.

- Error number: MY-013762; Symbol: ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG; SQLSTATE: HY000

Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero. audit_log_max_size takes precedence and audit_log_prune_seconds is ignored

- Error number: MY-013763; Symbol: ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG; SQLSTATE: HY000

Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.

- Error number: MY-013764; Symbol: ER_PLUGIN_INVALID_TABLE_DEFINITION; SQLSTATE: HY000

Message: Invalid table definition for '%s.%s'.

- Error number: MY-013765; Symbol: ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG; SQLSTATE: HY000

Message: %s

- Error number: MY-013766; Symbol: ER_INSTALL_PLUGIN_CONFLICT_LOG; SQLSTATE: HY000

Message: Cannot install the %s plugin when the %s plugin is installed.

-
- Error number: [MY-013767](#); Symbol: [ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS](#); SQLSTATE: [HY000](#)

Message: The variable %s has been renamed to %s, and the old name deprecated. Only the old name was found in the persisted variable file. Next time the file is saved, both names will be stored. Issue any SET PERSIST command to save the file, get rid of this warning, and prepare the persisted configuration for when the variable is removed in a future version.
 - Error number: [MY-013768](#); Symbol: [ER_LOG_COMPONENT_FLUSH_FAILED](#); SQLSTATE: [HY000](#)

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.
 - Error number: [MY-013769](#); Symbol: [ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY](#); SQLSTATE: [HY000](#)

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you rebuild the table for better security.
 - Error number: [MY-013770](#); Symbol: [ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY](#); SQLSTATE: [HY000](#)

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you reencrypt the tablespace for better security.
 - Error number: [MY-013771](#); Symbol: [ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Page Archiver's doublewrite buffer initialisation failed. Page tracking is at risk of losing tracked information.
 - Error number: [MY-013772](#); Symbol: [ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IBUF_MERGES](#); SQLSTATE: [HY000](#)

Message: There is not enough free space in the redo log during recovery to perform pending ibuf merges. Please retry starting MySQL with --innodb-force-recovery=4.
 - Error number: [MY-013773](#); Symbol: [ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: There is not enough free space in the redo log during recovery, restore from backup (or retry with --innodb-force-recovery=6).
 - Error number: [MY-013774](#); Symbol: [ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON_LOG](#); SQLSTATE: [HY000](#)

Message: audit_log_format_unix_timestamp is applicable only when audit_log_format = JSON.
 - Error number: [MY-013775](#); Symbol: [ER_PREPARE_FOR_PRIMARY_ENGINE](#); SQLSTATE: [HY000](#)

Message: Retry the statement using the primary storage engine.
 - Error number: [MY-013776](#); Symbol: [ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG](#); SQLSTATE: [HY000](#)

Message: Parallel initialization of rseg complete
 - Error number: [MY-013777](#); Symbol: [ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG](#); SQLSTATE: [HY000](#)

Message: Time taken to initialize rseg using %u thread: %u ms.
-

-
- Error number: [MY-013778](#); Symbol: [ER_DDL_MSG_1](#); SQLSTATE: [HY000](#)
Message: DDL failed to create a thread to load an index, fall back to single thread
 - Error number: [MY-013779](#); Symbol: [ER_MTR_MSG_1](#); SQLSTATE: [HY000](#)
Message: Debug_check_no_latching failed, slot->type=%d
 - Error number: [MY-013780](#); Symbol: [ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_CONN_ERR](#); SQLSTATE: [HY000](#)
Message: Failed to establish MySQL client connection in Group Replication. Error establishing connection. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.
 - Error number: [MY-013781](#); Symbol: [ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_COMMAND_ERR](#); SQLSTATE: [HY000](#)
Message: Failed to establish MySQL client connection in Group Replication. Error sending connection delegation command. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.
 - Error number: [MY-013782](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA](#); SQLSTATE: [HY000](#)
Message: Unable to read the replication failover channels configuration during group membership change. Please check the tables 'mysql.replication_asynchronous_connection_failover', 'mysql.replication_asynchronous_connection_failover_managed' and 'mysql.replication_group_configuration_version'.
 - Error number: [MY-013783](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION](#); SQLSTATE: [HY000](#)
Message: This member joined a group on which all members do not support replication failover channels integration on Group Replication, as such it did reset its replication failover channels configuration to the default one.
 - Error number: [MY-013784](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT_CONFIGURATION](#); SQLSTATE: [HY000](#)
Message: Unable to reset to replication failover channels default configuration on member join. Please check the tables 'mysql.replication_asynchronous_connection_failover', 'mysql.replication_asynchronous_connection_failover_managed' and 'mysql.replication_group_configuration_version'.
 - Error number: [MY-013785](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)
Message: Unable to parse the replication failover channels configuration sent by the group on member join.
 - Error number: [MY-013786](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)
Message: Unable to set SOURCE_CONNECTION_AUTO_FAILOVER on a non-existent or misconfigured replication channel '%s', please create the channel and rejoin the server to the group.

-
- Error number: [MY-013787](#); Symbol: [ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_SERVICE](#); SQLSTATE: [HY000](#)
Message: Unable to register the listener 'replication_asynchronous_connection_failover_configuration' to the service 'group_replication_message_service_rcv'.
 - Error number: [MY-013788](#); Symbol: [ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY](#); SQLSTATE: [HY000](#)
Message: This server is not able to reach a majority of members in the group. This server will skip the replication failover channels handling until this server is back to the group majority.
 - Error number: [MY-013789](#); Symbol: [ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY](#); SQLSTATE: [HY000](#)
Message: This server is back to the group majority. Replication failover channels handling is resumed.
 - Error number: [MY-013790](#); Symbol: [ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION](#); SQLSTATE: [HY000](#)
Message: Error incrementing member action configuration version for %s.%s table.
 - Error number: [MY-013791](#); Symbol: [ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)
Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.
 - Error number: [MY-013792](#); Symbol: [ER_IB_MSG_CLONE_DDL_NTFN](#); SQLSTATE: [HY000](#)
Message: Clone DDL Notification: %s
 - Error number: [MY-013793](#); Symbol: [ER_IB_MSG_CLONE_DDL_APPLY](#); SQLSTATE: [HY000](#)
Message: Clone DDL APPLY: %s
 - Error number: [MY-013794](#); Symbol: [ER_IB_MSG_CLONE_DDL_INVALIDATE](#); SQLSTATE: [HY000](#)
Message: Clone DDL Invalidate : %s
 - Error number: [MY-013795](#); Symbol: [ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED](#); SQLSTATE: [HY000](#)
Message: Encryption key is loaded for undo tablespace '%s'.
 - Error number: [MY-013796](#); Symbol: [ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Ignoring encryption INFO size in redo log: %zu, expected: %zu
 - Error number: [MY-013797](#); Symbol: [ER_INVALID_AUTHENTICATION_POLICY](#); SQLSTATE: [HY000](#)
Message: Option --authentication-policy is set to an invalid value. Please check if the specified authentication plugins are valid.
 - Error number: [MY-013798](#); Symbol: [ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Signature verification failed during registration.
 - Error number: [MY-013799](#); Symbol: [ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER](#); SQLSTATE: [HY000](#)

Message: Buffer too small to hold registration challenge response.

- Error number: [MY-013800](#); Symbol: [ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT](#); SQLSTATE: [HY000](#)

Message: FIDO device authenticator data corrupt.

- Error number: [MY-013801](#); Symbol: [ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT](#); SQLSTATE: [HY000](#)

Message: FIDO device signature corrupt.

- Error number: [MY-013802](#); Symbol: [ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED](#); SQLSTATE: [HY000](#)

Message: Signature verification failed during authentication.

- Error number: [MY-013803](#); Symbol: [ER_AUTHENTICATION_PLUGIN_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory.

- Error number: [MY-013804](#); Symbol: [ER_AUTHENTICATION_PLUGIN_LOG](#); SQLSTATE: [HY000](#)

Message: Can't initialize logging service.

- Error number: [MY-013805](#); Symbol: [ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with GTID_ONLY=1, which is invalid when GTID_MODE <> ON. If you intend to disable GTIDs in the replication topology, change GTID_ONLY to 0.

- Error number: [MY-013806](#); Symbol: [ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS](#); SQLSTATE: [HY000](#)

Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.

- Error number: [MY-013807](#); Symbol: [ER_RPL_CANNOT_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Could not open relay log: %s

- Error number: [MY-013808](#); Symbol: [ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: Authentication plugin not initialized.

- Error number: [MY-013809](#); Symbol: [ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR](#); SQLSTATE: [HY000](#)

Message: Cannot use the generated private key file.

- Error number: [MY-013810](#); Symbol: [ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY](#); SQLSTATE: [HY000](#)

Message: Unavailable public key with fingerprint %s for user %s in tenancy %s .

- Error number: [MY-013811](#); Symbol: [ER_AUTHENTICATION_OCI_IMDS](#); SQLSTATE: [HY000](#)

Message: Cannot obtain the OCI configuration from the IMDS service.

-
- Error number: [MY-013812](#); Symbol: [ER_AUTHENTICATION_OCI_IAM](#); SQLSTATE: [HY000](#)
Message: Cannot initialize the IAM service.
 - Error number: [MY-013813](#); Symbol: [ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRING](#); SQLSTATE: [HY000](#)
Message: Invalid authentication string details for user: `%s`@`%s`.
 - Error number: [MY-013814](#); Symbol: [ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS](#); SQLSTATE: [HY000](#)
Message: None of the groups returned by IAM matches any of the entries from authentication string.
 - Error number: [MY-013815](#); Symbol: [ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND](#); SQLSTATE: [HY000](#)
Message: User is not part of any groups. However, account is configured to use group mapping.
 - Error number: [MY-013816](#); Symbol: [ER_AUTHENTICATION_OCI_NONCE](#); SQLSTATE: [HY000](#)
Message: Received OpenSSL error: %s while authenticating user %s with fingerprint %s in tenancy %s .
 - Error number: [MY-013817](#); Symbol: [ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 1 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB
 - Error number: [MY-013818](#); Symbol: [ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 2 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB
 - Error number: [MY-013819](#); Symbol: [ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 3 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB
 - Error number: [MY-013820](#); Symbol: [ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)
Message: The member %s:%u, with UUID: %s, was set as the single preferred consensus leader.
 - Error number: [MY-013821](#); Symbol: [ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)
Message: Something went wrong trying to set the member %s:%u, with UUID: %s, as the single preferred consensus leader. Please query the performance_schema.replication_group_communication_information table to see whether the operation took effect, i.e. whether the preferred consensus leader matches the current primary. If not, consider electing a different primary to try again. Please check the error log and GCS_DEBUG_TRACE for more information that may help understanding what went wrong.
 - Error number: [MY-013822](#); Symbol: [ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)
Message: All members were set as consensus leaders.
-

-
- Error number: [MY-013823](#); Symbol: [ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)

Message: Something went wrong trying to set all members as consensus leaders. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the consensus leaders match all members. If not, consider resetting the group communication protocol to a version < 8.0.22, or switch to single-primary mode and back again to multi-primary mode, to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.

- Error number: [MY-013824](#); Symbol: [ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: This member is configured with a `group_replication_paxos_single_leader` option value of '%d' that is different from the group's value ('%d'). This member will now exit the group.

- Error number: [MY-013825](#); Symbol: [ER_MFA_USER_ATTRIBUTES_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Invalid and/or corrupted multi factor authentication methods in `User_attributes` column in `mysql.user` table. "%s".

- Error number: [MY-013826](#); Symbol: [ER_MFA_PLUGIN_NOT_LOADED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not loaded; Ignoring user

- Error number: [MY-013827](#); Symbol: [ER_WARN_DEPRECATED_CHARSET_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: The character set %s is deprecated and will be removed in a future release. Please consider using %s instead.

- Error number: [MY-013828](#); Symbol: [ER_WARN_DEPRECATED_COLLATION_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

- Error number: [MY-013829](#); Symbol: [ER_REGEXP_MISSING_ICU_DATADIR](#); SQLSTATE: [HY000](#)

Message: Missing data directory for ICU regular expressions: %s.

- Error number: [MY-013830](#); Symbol: [ER_IB_WARN_MANY_NON_LRU_FILES_OPENED](#); SQLSTATE: [HY000](#)

Message: More than 90%% of files opened out of the `innodb_open_files` limit are files that are not easy to close. The performance of system may degrade. Consider increasing value of the `innodb_open_files` system variable. There are %zu such files opened out of the total limit for all files opened of %zu.

- Error number: [MY-013831](#); Symbol: [ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME](#); SQLSTATE: [HY000](#)

Message: Trying to open a file for %lld seconds. Configuration only allows for %zu open files. Consider setting `innobase_open_files` higher.

- Error number: [MY-013832](#); Symbol: [ER_GLOBAL_CONN_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

- Error number: [MY-013833](#); Symbol: [ER_CONN_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

-
- Error number: [MY-013834](#); Symbol: [ER_WARN_AUDIT_LOG_DISABLED](#); SQLSTATE: [HY000](#)
Message: Audit Log is disabled. Enable it with audit_log_disable = false.
 - Error number: [MY-013835](#); Symbol: [ER_INVALID_TLS_VERSION](#); SQLSTATE: [HY000](#)
Message: Option --tls-version or --admin-tls-version is set to an invalid value %s.
 - Error number: [MY-013836](#); Symbol: [ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY](#); SQLSTATE: [HY000](#)
Message: Relay log recovery on channel with GTID_ONLY=1. The channel will switch to a new relay log and the GTID protocol will be used to replicate unapplied transactions.
 - Error number: [MY-013837](#); Symbol: [ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED](#); SQLSTATE: [HY000](#)
Message: Number of STANDBY_SERVER values exceeded maximum limit of 64.
 - Error number: [MY-013838](#); Symbol: [ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING](#); SQLSTATE: [HY000](#)
Message: Source keyring does not have any keys to migrate.
 - Error number: [MY-013839](#); Symbol: [ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES](#); SQLSTATE: [HY000](#)
Message: Cannot persist SENSITIVE system variables because keyring component support is unavailable and persist_sensitive_variables_in_plaintext is set to OFF. Please make sure that keyring services are active and required keys are available.
 - Error number: [MY-013840](#); Symbol: [ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES](#); SQLSTATE: [HY000](#)
Message: Cannot interpret persisted SENSITIVE system variables. Please make sure that keyring services are active and required keys are available.
 - Error number: [MY-013841](#); Symbol: [ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED](#); SQLSTATE: [HY000](#)
Message: Keyring has to be loaded through manifest file in order to support secure storage for persisted variables
 - Error number: [MY-013842](#); Symbol: [ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Could not find master key %s in keyring
 - Error number: [MY-013843](#); Symbol: [ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED](#); SQLSTATE: [HY000](#)
Message: A new master key %s could not be generated
 - Error number: [MY-013844](#); Symbol: [ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to encrypt %s using %s
 - Error number: [MY-013845](#); Symbol: [ER_PERSISTED_VARIABLES_DECRYPTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to decrypt %s using %s

-
- Error number: [MY-013846](#); Symbol: [ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT](#); SQLSTATE: [HY000](#)

Message: Persisting SENSITIVE variables in encrypted form requires keyring component loaded through manifest file.
 - Error number: [MY-013847](#); Symbol: [ER_MY_MALLOC_USING_JEMALLOC](#); SQLSTATE: [HY000](#)

Message: Using jemalloc.dll for my_malloc and ut::malloc etc.
 - Error number: [MY-013848](#); Symbol: [ER_MY_MALLOC_USING_STD_MALLOC](#); SQLSTATE: [HY000](#)

Message: %s.
 - Error number: [MY-013849](#); Symbol: [ER_MY_MALLOC_LOADLIBRARY_FAILED](#); SQLSTATE: [HY000](#)

Message: %s.
 - Error number: [MY-013850](#); Symbol: [ER_MY_MALLOC_GETPROCADDRESS_FAILED](#); SQLSTATE: [HY000](#)

Message: %s.
 - Error number: [MY-013851](#); Symbol: [ER_ACCOUNT_WITH_EXPIRED_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Password for the account '%s'@'%s' has expired. To log in, either change it using a client that supports expired passwords or send the change request to an administrator.
 - Error number: [MY-013852](#); Symbol: [ER_THREAD_POOL_PLUGIN_STARTED](#); SQLSTATE: [HY000](#)

Message: Thread pool plugin started successfully with parameters: %s
 - Error number: [MY-013853](#); Symbol: [ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID](#); SQLSTATE: [HY000](#)

Message: thread_pool_dedicated_listeners cannot be set unless thread_pool_max_transactions_limit > 0
 - Error number: [MY-013854](#); Symbol: [ER_IB_DBLWR_BYTES_INFO](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-013855](#); Symbol: [ER_IB_RDBLWR_BYTES_INFO](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-013856](#); Symbol: [ER_IB_MSG_LOG_FILE_IS_EMPTY](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is empty, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file or try recovering without the redo files, in read-only mode, by providing --innodb-force-recovery=6.
 - Error number: [MY-013857](#); Symbol: [ER_IB_MSG_LOG_FILE_TOO_SMALL](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is smaller than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.
 - Error number: [MY-013858](#); Symbol: [ER_IB_MSG_LOG_FILE_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is larger than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.
-

-
- Error number: [MY-013859](#); Symbol: [ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read header of the redo log file %s
 - Error number: [MY-013860](#); Symbol: [ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: --initialize specified but the redo log directory %s has redo log files inside. Aborting.
 - Error number: [MY-013861](#); Symbol: [ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to list redo log files in the redo log directory %s
 - Error number: [MY-013862](#); Symbol: [ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR](#); SQLSTATE: [HY000](#)

Message: Neither found %s subdirectory, nor %s* files in %s
 - Error number: [MY-013863](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot restore cloned data directory, InnoDB running in read-only mode!
 - Error number: [MY-013864](#); Symbol: [ER_IB_MSG_LOG_WRITER_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error %d encountered when writing to the redo log file: %s.
 - Error number: [MY-013865](#); Symbol: [ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE](#); SQLSTATE: [HY000](#)

Message: Redo log writer is waiting for a new redo log file. Consider increasing innodb_redo_log_capacity.
 - Error number: [MY-013866](#); Symbol: [ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE](#); SQLSTATE: [HY000](#)

Message: Found checkpoint LSN %llu in a redo log file %s, but the file represents range of LSN values [%llu, %llu), so the file is corrupted.
 - Error number: [MY-013867](#); Symbol: [ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN](#); SQLSTATE: [HY000](#)

Message: Redo log is running out of free space, pausing user threads... Consider increasing innodb_redo_log_capacity.
 - Error number: [MY-013868](#); Symbol: [ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN](#); SQLSTATE: [HY000](#)

Message: Redo log reclaimed some free space, resuming user threads.
 - Error number: [MY-013871](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_FORCED_RECV](#); SQLSTATE: [HY000](#)

Message: Cannot upgrade format (v%lu) of redo log files when innodb-force-recovery > 0.
 - Error number: [MY-013872](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot upgrade format (v%lu) of redo log files in read-only mode (--innodb-read-only).
-

-
- Error number: [MY-013873](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_CLONED_DB](#); SQLSTATE: [HY000](#)
Message: Cannot upgrade format (v%lu) of redo log files on cloned data directory. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).
 - Error number: [MY-013874](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES](#); SQLSTATE: [HY000](#)
Message: Cannot upgrade format (v%lu) of redo log files because they are marked as uninitialized. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).
 - Error number: [MY-013875](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED](#); SQLSTATE: [HY000](#)
Message: Cannot upgrade format (v%lu) of redo log files when the redo log is corrupted. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).
 - Error number: [MY-013879](#); Symbol: [ER_IB_MSG_LOG_FILE_FOREIGN_UUID](#); SQLSTATE: [HY000](#)
Message: The redo log file %s comes from other data directory than redo log file %s.
 - Error number: [MY-013880](#); Symbol: [ER_IB_MSG_LOG_FILE_INVALID_START_LSN](#); SQLSTATE: [HY000](#)
Message: The redo log file %s has invalid start_lsn %llu.
 - Error number: [MY-013881](#); Symbol: [ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES](#); SQLSTATE: [HY000](#)
Message: The redo log file %s has start_lsn %llu but expected %llu (end_lsn of the previous redo log file).
 - Error number: [MY-013882](#); Symbol: [ER_IB_MSG_LOG_FILE_MISSING_FOR_ID](#); SQLSTATE: [HY000](#)
Message: Missing redo log file %s (with start_lsn = %llu).
 - Error number: [MY-013883](#); Symbol: [ER_IB_MSG_LOG_CHECKPOINT_FOUND](#); SQLSTATE: [HY000](#)
Message: The latest found checkpoint is at lsn = %llu in redo log file %s.
 - Error number: [MY-013884](#); Symbol: [ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED](#); SQLSTATE: [HY000](#)
Message: User has set innodb_redo_log_capacity to %lluM.
 - Error number: [MY-013885](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED](#); SQLSTATE: [HY000](#)
Message: Redo log has been requested to resize from %lluM to %lluM.
 - Error number: [MY-013886](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED](#); SQLSTATE: [HY000](#)
Message: Redo log resize has been cancelled.
 - Error number: [MY-013887](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_FINISHED](#); SQLSTATE: [HY000](#)
Message: Redo log has been resized to %lluM.
 - Error number: [MY-013888](#); Symbol: [ER_IB_MSG_LOG_FILES_UPGRADE](#); SQLSTATE: [HY000](#)
Message: Upgrading redo log: %lluM, LSN=%llu.

-
- Error number: [MY-013889](#); Symbol: [ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE](#); SQLSTATE: [HY000](#)
Message: Marked the current redo log file %s as incomplete.
 - Error number: [MY-013890](#); Symbol: [ER_IB_MSG_LOG_FILE_REMOVE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to remove redo log file %s.
 - Error number: [MY-013891](#); Symbol: [ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to rename %s when creating redo log file %s (error: %d)
 - Error number: [MY-013892](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR](#); SQLSTATE: [HY000](#)
Message: Redo log files created by unknown creator %s.
 - Error number: [MY-013893](#); Symbol: [ER_IB_MSG_LOG_FILES_FOUND_MISSING](#); SQLSTATE: [HY000](#)
Message: Found existing redo log files, but at least one is missing. It is unknown if recovery could reach physically consistent state. Please consider restoring from backup or providing --innodb-force-recovery > 0.
 - Error number: [MY-013894](#); Symbol: [ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW](#); SQLSTATE: [HY000](#)
Message: Found redo log file %s which has format (v%lu) and is stored outside #innodb_redo.
 - Error number: [MY-013895](#); Symbol: [ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD](#); SQLSTATE: [HY000](#)
Message: Found redo log file %s which has format (v%lu) and is stored inside #innodb_redo.
 - Error number: [MY-013896](#); Symbol: [ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS](#); SQLSTATE: [HY000](#)
Message: Found redo log files with different formats: %s has format v%lu, %s has format v%lu.
 - Error number: [MY-013897](#); Symbol: [ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0](#); SQLSTATE: [HY000](#)
Message: Missing ib_logfile0 in the directory %s.
 - Error number: [MY-013898](#); Symbol: [ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to initialize services required to handle redo log PFS tables.
 - Error number: [MY-013899](#); Symbol: [ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to create redo log PFS tables.
 - Error number: [MY-013900](#); Symbol: [ER_IB_MSG_LOG_FILE_TRUNCATE](#); SQLSTATE: [HY000](#)
Message: Truncating redo log file %s...
 - Error number: [MY-013901](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to resize unused redo log file %s to %llu MB (%s).

- Error number: [MY-013902](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to remove unused redo log file %s.

- Error number: [MY-013903](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rename unused redo log file %s to %s.

- Error number: [MY-013904](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to mark unused redo log file %s as in use (by renaming to %s).

- Error number: [MY-013905](#); Symbol: [ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to mark redo log file %s as unused (by renaming to %s).

- Error number: [MY-013906](#); Symbol: [ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED](#); SQLSTATE: [HY000](#)

Message: Option `innodb_dedicated_server` is ignored for `innodb_redo_log_capacity`, because `innodb_redo_log_capacity`, `innodb_log_file_size` or `innodb_log_files_in_group` is specified explicitly. Redo log capacity: %lluM.

- Error number: [MY-013907](#); Symbol: [ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE](#); SQLSTATE: [HY000](#)

Message: Deprecated configuration parameters `innodb_log_file_size` and/or `innodb_log_files_in_group` have been used to compute `innodb_redo_log_capacity=%llu`. Please use `innodb_redo_log_capacity` instead.

- Error number: [MY-013908](#); Symbol: [ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE](#); SQLSTATE: [HY000](#)

Message: This member was unable to log the `View_change_log_event` into the binary log, hence it will leave the group. Please check that there is available disk space and add the member back to the group.

- Error number: [MY-013909](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG](#); SQLSTATE: [HY000](#)

Message: Found invalid event sequence while recovering from binary log file '%s', between positions %llu and %llu: %s. The recovery process was stopped early and no transaction was recovered. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the binary log or, to release possibly acquired locks, disable the binary log during server recovery. Note that disabling the binary log may lead to loss of transactions that were already acknowledged as successful to client connections and may have been replicated to other servers in the topology.

- Error number: [MY-013910](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE](#); SQLSTATE: [HY000](#)

Message: Storage engines failed to recover one or more transactions. The recovery process was stopped early, check previous messages for the details on failed transactions. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions

kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the storage engine (out-of-memory, no disk space, etc) or, to release possibly acquired locks held by XA transactions, disable the binary log during server recovery and check consistency between storage engines and binary log files.

- Error number: [MY-013911](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS](#); SQLSTATE: [HY000](#)

Message: Crash recovery finished in %s engine. %s

- Error number: [MY-013912](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to commit %s in %s, with failure code %s.

- Error number: [MY-013913](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rollback %s in %s, with failure code %s.

- Error number: [MY-013914](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to prepare %s in %s, with failure code %s.

- Error number: [MY-013915](#); Symbol: [ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

- Error number: [MY-013916](#); Symbol: [ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-013917](#); Symbol: [ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered.

- Error number: [MY-013918](#); Symbol: [ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-013919](#); Symbol: [ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Invalid arguments to function '%s'. Expected values: %s.

- Error number: [MY-013920](#); Symbol: [ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: Invalid algorithm value '%s' in function %s.

- Error number: [MY-013921](#); Symbol: [ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid key length '%d' for function '%s' with algorithm '%s'. Please provide a value between [%d, %d].

-
- Error number: [MY-013922](#); Symbol: [ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE](#); SQLSTATE: [HY000](#)

 Message: Failed to generate private key of length '%d' with algorithm '%s' in function '%s'. More details about the error would have been logged before this message.
 - Error number: [MY-013923](#); Symbol: [ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE](#); SQLSTATE: [HY000](#)

 Message: Failed to generate public key with algorithm '%s' for given private key in function '%s'. More details about the error would have been logged before this message.
 - Error number: [MY-013924](#); Symbol: [ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

 Message: Invalid data length '%d' (in bytes) for function '%s' with algorithm '%s'. The maximum support data length for given private key is %d (in bytes).
 - Error number: [MY-013925](#); Symbol: [ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR](#); SQLSTATE: [HY000](#)

 Message: Could not encrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.
 - Error number: [MY-013926](#); Symbol: [ER_COMPONENT_EE_DATA_DECRYPTION_ERROR](#); SQLSTATE: [HY000](#)

 Message: Could not decrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.
 - Error number: [MY-013927](#); Symbol: [ER_COMPONENT_EE_DATA_SIGN_ERROR](#); SQLSTATE: [HY000](#)

 Message: Could not sign data in function '%s' using algorithm '%s' and digest type '%s'. More details about the error would have logged before this message.
 - Error number: [MY-013928](#); Symbol: [ER_COMPONENT_EE_OPENSSL_ERROR](#); SQLSTATE: [HY000](#)

 Message: Received OpenSSL error in function '%s' for algorithm '%s': '%s'
 - Error number: [MY-013929](#); Symbol: [ER_COMPONENT_EE_INSUFFICIENT_LENGTH](#); SQLSTATE: [HY000](#)

 Message: In function '%s' with algorithm '%s': insufficient output buffer length '%zu'. Required length '%zu'.
 - Error number: [MY-013930](#); Symbol: [ER_SYSTEMD_NOTIFY_DEBUG](#); SQLSTATE: [HY000](#)

 Message: %s%s
 - Error number: [MY-013931](#); Symbol: [ER_TMP_SESSION_FOR_VAR](#); SQLSTATE: [HY000](#)

 Message: Setting session values for system variables only makes sense in a user session (failed to set '%s').
 - Error number: [MY-013932](#); Symbol: [ER_BUILD_ID](#); SQLSTATE: [HY000](#)

 Message: BuildID[sha1]=%s
 - Error number: [MY-013933](#); Symbol: [ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGE](#); SQLSTATE: [HY000](#)

 Message: Failed to register dynamic privilege %s.

-
- Error number: [MY-013934](#); Symbol: [ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER](#); SQLSTATE: [HY000](#)

Message: Redo log writer is waiting for %s redo log consumer which is currently reading LSN=%llu preventing reclamation of subsequent portion of the redo log. Consider increasing innodb_redo_log_capacity.
 - Error number: [MY-013935](#); Symbol: [ER_CONDITIONAL_DEBUG](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-013936](#); Symbol: [ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION](#); SQLSTATE: [HY000](#)

Message: Recovery: Generating index information for INSTANT DDL Table in 8.0.29 format
 - Error number: [MY-013941](#); Symbol: [ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA](#); SQLSTATE: [HY000](#)

Message: Failed to clear instant drop column metadata for table %s
 - Error number: [MY-013942](#); Symbol: [ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE](#); SQLSTATE: [HY000](#)

Message: Cannot open signing key file %s.
 - Error number: [MY-013943](#); Symbol: [ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY](#); SQLSTATE: [HY000](#)

Message: Out of memory! Cannot create private key.
 - Error number: [MY-013944](#); Symbol: [ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE](#); SQLSTATE: [HY000](#)

Message: Cannot read signing key file %s.
 - Error number: [MY-013945](#); Symbol: [ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_TYPE](#); SQLSTATE: [HY000](#)

Message: Incomplete key: missing Name/Type for the Key: %s.
 - Error number: [MY-013946](#); Symbol: [ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)

Message: Duplicate key found in keyring with Name: %s and Owner: %s.
 - Error number: [MY-013947](#); Symbol: [ER_KEYRING_OCI_PARSE_JSON](#); SQLSTATE: [HY000](#)

Message: Error parsing JSON response %s.
 - Error number: [MY-013948](#); Symbol: [ER_KEYRING_OCI_INVALID_JSON](#); SQLSTATE: [HY000](#)

Message: Invalid JSON response!
 - Error number: [MY-013949](#); Symbol: [ER_KEYRING_OCI_HTTP_REQUEST](#); SQLSTATE: [HY000](#)

Message: HTTP request failed with error: '%s'
 - Error number: [MY-013950](#); Symbol: [ER_THREAD_POOL_SYSVAR_CHANGE](#); SQLSTATE: [HY000](#)

Message: Variable thread_pool.%s was updated: %s
 - Error number: [MY-013951](#); Symbol: [ER_STACK_BACKTRACE](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013952](#); Symbol: [ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE](#); SQLSTATE: [HY000](#)

Message: Status code %u: Completed

- Error number: [MY-013953](#); Symbol: [ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE](#); SQLSTATE: [HY000](#)

Message: Status code %u: %u%% complete

- Error number: [MY-013954](#); Symbol: [ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS](#); SQLSTATE: [HY000](#)

Message: Status code %u: %s

- Error number: [MY-013957](#); Symbol: [ER_IB_MSG_INVALID_PAGE_TYPE](#); SQLSTATE: [HY000](#)

Message: Found page type mismatch. Expected %u, found %u, in page: space_id=%lu page_no=%lu

- Error number: [MY-013958](#); Symbol: [ER_IB_PARALLEL_READER_WORKER_INFO](#); SQLSTATE: [HY000](#)

Message: preader: thread_id=%zu, n_threads=%zu, n_ctx=%zu, one_range_per_thread=%s, n_index=%zu, index_list=%s, err=%zu

- Error number: [MY-013959](#); Symbol: [ER_IB_BULK_LOAD_SUBTREE_INFO](#); SQLSTATE: [HY000](#)

Message: bulkload: space_id=%zu, table=%s, index=%s, height=%zu, n_extents=%zu, n_pages=%zu

- Error number: [MY-013960](#); Symbol: [ER_IB_BULK_FLUSHER_INFO](#); SQLSTATE: [HY000](#)

Message: bulkflusher: sleep_count=%zu, sleep_duration=%zu milliseconds, total_sleep=%zu milliseconds, pages_flushed=%zu

- Error number: [MY-013961](#); Symbol: [ER_IB_BUFFER_POOL_OVERUSE](#); SQLSTATE: [HY000](#)

Message: %s: Over 67 percent of the buffer pool (curr_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF_BLOCK_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. Starting the InnoDB Monitor to print diagnostics.

- Error number: [MY-013962](#); Symbol: [ER_IB_BUFFER_POOL_FULL](#); SQLSTATE: [HY000](#)

Message: %s: Over 95 percent of the buffer pool (curr_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF_BLOCK_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. We intentionally generate a seg fault to print a stack trace on Linux!

- Error number: [MY-013963](#); Symbol: [ER_IB_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)

Message: %s: table=%s, index=%s, n_uniq=%zu, n_fields=%zu, lhs=(%s), rhs=(%s)

- Error number: [MY-013964](#); Symbol: [ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK](#); SQLSTATE: [HY000](#)

Message: Failed to apply row event with %d columns, originating from a server of version %s on table '%s.%s', which has %d columns, one of which is a generated implicit primary key. Replication

is unsupported when the source server is older than 8.0.30, the replica table has a generated implicit primary key, and there is a difference in column count, not counting the replica's generated implicit primary key. Align the table schemas on source and replica, and restart replication.

- Error number: [MY-013965](#); Symbol: [ER_BULK_EXECUTOR_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk executor: %s
- Error number: [MY-013966](#); Symbol: [ER_BULK_LOADER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk loader: %s
- Error number: [MY-013967](#); Symbol: [ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_CLAUSE_LOG](#); SQLSTATE: [HY000](#)
Message: The first file being loaded contained less lines than the ignore clause
- Error number: [MY-013968](#); Symbol: [ER_BULK_READER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk reader: %s
- Error number: [MY-013969](#); Symbol: [ER_BULK_READER_LIBCURL_INIT_FAILED_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk reader failed to initialize libcurl
- Error number: [MY-013970](#); Symbol: [ER_BULK_READER_LIBCURL_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk reader got libcurl error: %s
- Error number: [MY-013971](#); Symbol: [ER_BULK_READER_SERVER_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk reader got error response from server: %ld
- Error number: [MY-013972](#); Symbol: [ER_BULK_READER_COMMUNICATION_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk reader got error in communication with source server, check the error log for additional details
- Error number: [MY-013973](#); Symbol: [ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG](#); SQLSTATE: [HY000](#)
Message: Missing ENCLOSED BY character at row %ld in file %s.
- Error number: [MY-013974](#); Symbol: [ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED_LOG](#); SQLSTATE: [HY000](#)
Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.
- Error number: [MY-013975](#); Symbol: [ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOG](#); SQLSTATE: [HY000](#)
Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.
- Error number: [MY-013976](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG](#); SQLSTATE: [HY000](#)
Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.

-
- Error number: [MY-013977](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.

- Error number: [MY-013978](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.

- Error number: [MY-013979](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.

- Error number: [MY-013980](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after column terminator found at row %ld in file '%s'.

- Error number: [MY-013981](#); Symbol: [ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.

- Error number: [MY-013982](#); Symbol: [ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG](#); SQLSTATE: [HY000](#)

Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'

- Error number: [MY-013983](#); Symbol: [ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG](#); SQLSTATE: [HY000](#)

Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'

- Error number: [MY-013984](#); Symbol: [ER_IB_BULK_LOAD_THREAD_FAIL](#); SQLSTATE: [HY000](#)

Message: %s: LOAD BULK DATA thread failure (err=%lu), table=%s, index=%s

- Error number: [MY-013985](#); Symbol: [ER_IB_BULK_LOAD_MERGE_FAIL](#); SQLSTATE: [HY000](#)

Message: %s: Failed to merge sub-trees in LOAD BULK DATA, table=%s, index=%s, details=%s

- Error number: [MY-013986](#); Symbol: [ER_IB_LOAD_BULK_CONCURRENCY_REDUCED](#); SQLSTATE: [HY000](#)

Message: LOAD BULK DATA: Buffer pool size is %zu. Reducing concurrency from %zu to %zu. table=%s.

- Error number: [MY-013987](#); Symbol: [ER_PLUGIN_EXCEPTION_OPERATION_FAILED](#); SQLSTATE: [HY000](#)

Message: C++ Exception caught while %s the %s plugin: [%s]

-
- Error number: [MY-013988](#); Symbol: [ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR_IN_REPO](#); SQLSTATE: [HY000](#)

 Message: Replication configuration appears to be corrupted. On Group Replication channel '%s', setting REQUIRE_TABLE_PRIMARY_KEY_CHECK to 'GENERATE' is not allowed. Run RESET REPLICA ALL to reset it.
 - Error number: [MY-013989](#); Symbol: [ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET](#); SQLSTATE: [HY000](#)

 Message: Record has both instant and version bit set.
 - Error number: [MY-013990](#); Symbol: [ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP](#); SQLSTATE: [HY000](#)

 Message: This member is configured with a group_replication_paxos_single_leader option value of 1 and it is trying to join a group with Communication Protocol Version below 8.0.27. In order to join this group, group_replication_paxos_single_leader value must be configured to the value 0. This member will now exit the group.
 - Error number: [MY-013991](#); Symbol: [ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY](#); SQLSTATE: [HY000](#)

 Message: Ignored the innodb-redo-log-capacity option in the Innodb read-only mode. Server is using active redo log files.
 - Error number: [MY-013992](#); Symbol: [ER_IB_PRIMARY_KEY_IS_INSTANT](#); SQLSTATE: [HY000](#)

 Message: Unexpected INSTANTLY Added / Dropped column: '%s' at position %lu for Table '%s', Index '%s' while getting Primary Key for row logging
 - Error number: [MY-013993](#); Symbol: [ER_THREAD_POOL_IDLE_CONNECTION_CLOSED](#); SQLSTATE: [HY000](#)

 Message: %s
 - Error number: [MY-013994](#); Symbol: [ER_IB_HIDDEN_NAME_CONFLICT](#); SQLSTATE: [HY000](#)

 Message: Column name %s and internally generated INSTANT DROP column name %s is causing a conflict.
 - Error number: [MY-013995](#); Symbol: [ER_IB_DICT_INVALID_COLUMN_POSITION](#); SQLSTATE: [HY000](#)

 Message: Field number: %llu too large, Total fields in Record: %zu.
 - Error number: [MY-013996](#); Symbol: [ER_IB_DICT_LOG_TABLE_INFO](#); SQLSTATE: [HY000](#)

 Message: %s
 - Error number: [MY-013997](#); Symbol: [ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED](#); SQLSTATE: [HY000](#)

 Message: The connection has timed out after %lu retries connecting to '%s@%s:%d'%s, and therefore the MySQL server is going to attempt an asynchronous replication connection failover, to '%s@%s:%d'
 - Error number: [MY-013998](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED](#); SQLSTATE: [HY000](#)

 Message: The Replica which was connected to source '%s:%d', is now connected to new source '%s:%d', but still has the same server_uuid %s.
-

- Error number: [MY-013999](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST_PORT_UNCHANGED](#); SQLSTATE: [HY000](#)

 Message: The server_uuid for source server '\%s:%d\' has changed from %s to %s. This should not happen unless you have changed it manually.
- Error number: [MY-014000](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED](#); SQLSTATE: [HY000](#)

 Message: The source server has changed from '\%s:%d\' with server_uuid %s, to '\%s:%d\' with server_uuid %s.
- Error number: [MY-014001](#); Symbol: [ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FILE_BASED](#); SQLSTATE: [HY000](#)

 Message: Replica receiver thread%s: connected to source '\%s@%s:%d\' with server_uuid=%s, server_id=%d. Starting replication from file '%s', position '%s'.
- Error number: [MY-014002](#); Symbol: [ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_GTID_BASED](#); SQLSTATE: [HY000](#)

 Message: Replica receiver thread%s: connected to source '\%s@%s:%d\' with server_uuid=%s, server_id=%d. Starting GTID-based replication.
- Error number: [MY-014003](#); Symbol: [ER_IB_INDEX_LOADER_DONE](#); SQLSTATE: [HY000](#)

 Message: Loader::build_all(): Completed building %zu indexes for old_table=%s, new_table=%s, err=%zu.
- Error number: [MY-014004](#); Symbol: [ER_IB_INDEX_BUILDER_DONE](#); SQLSTATE: [HY000](#)

 Message: Builder::finish(): Completed building index=%s of table=%s, err=%zu.
- Error number: [MY-014005](#); Symbol: [ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_OPTION](#); SQLSTATE: [HY000](#)

 Message: %s: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.
- Error number: [MY-014006](#); Symbol: [ER_IB_INDEX_BUILDER_INIT](#); SQLSTATE: [HY000](#)

 Message: Builder::init(): Initialize for building index=%s of table=%s, n_threads=%zu, sort buffer size=%zu bytes, i/o buffer size=%zu bytes.
- Error number: [MY-014007](#); Symbol: [ER_IB_SELECT_COUNT_STAR](#); SQLSTATE: [HY000](#)

 Message: SELECT COUNT(*) FROM table=%s, n_threads=%zu, n_partitions=%zu.
- Error number: [MY-014008](#); Symbol: [ER_IB_INDEX_LOG_VERSION_MISMATCH](#); SQLSTATE: [HY000](#)

 Message: Index log version %u did not match. Max index version is %u. Recovery can't continue. Please make sure server is not starting up with the datadir generated in future version.
- Error number: [MY-014009](#); Symbol: [ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MULTIPLE_KEYRING](#); SQLSTATE: [HY000](#)

 Message: Multiple keyring component URNs '%s' found in manifest file '%s'. Only one keyring component can be loaded at a time.
- Error number: [MY-014010](#); Symbol: [ER_GRP_RPL_HAS_STARTED](#); SQLSTATE: [HY000](#)

Message: Plugin 'group_replication' has been started.

- Error number: [MY-014011](#); Symbol: [ER_CHECK_TABLE_MIN_REC_FLAG_SET](#); SQLSTATE: [HY000](#)

Message: Minimum record flag is wrongly set to rec on page '%lu' at level '%lu' for index '%s' of table '%s'.

- Error number: [MY-014012](#); Symbol: [ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Minimum record flag is not set to first rec on page '%lu' at level '%lu' for index '%s' of table '%s'.

- Error number: [MY-014013](#); Symbol: [ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS](#); SQLSTATE: [HY000](#)

Message: Successfully registered slot '%d' for component '%s'.

- Error number: [MY-014014](#); Symbol: [ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS](#); SQLSTATE: [HY000](#)

Message: Successfully de-registered slot '%d' from component '%s'.

- Error number: [MY-014015](#); Symbol: [ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Cannot free resources stored by component '%s' in thread with ID: '%d'. Component failed to free required resources.

- Error number: [MY-014016](#); Symbol: [ER_IB_RESURRECT_TRX_INSERT](#); SQLSTATE: [HY000](#)

Message: Transaction ID: %lu found for resurrecting inserts

- Error number: [MY-014017](#); Symbol: [ER_IB_RESURRECT_TRX_UPDATE](#); SQLSTATE: [HY000](#)

Message: Transaction ID: %lu found for resurrecting updates

- Error number: [MY-014018](#); Symbol: [ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK](#); SQLSTATE: [HY000](#)

Message: Identified table ID: %lu to acquire lock

- Error number: [MY-014019](#); Symbol: [ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK](#); SQLSTATE: [HY000](#)

Message: Acquired lock on table ID: %lu, name: %s

- Error number: [MY-014020](#); Symbol: [ER_IB_RESURRECT_RECORD_PROGRESS](#); SQLSTATE: [HY000](#)

Message: Records read: %lu - Pages read: %lu

- Error number: [MY-014021](#); Symbol: [ER_IB_RESURRECT_RECORD_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Total records resurrected: %lu - Total pages read: %lu - Total tables acquired: %lu

- Error number: [MY-014022](#); Symbol: [ER_IB_RESURRECT_TRX_INSERT_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Resurrected %lu transactions doing inserts.

- Error number: [MY-014023](#); Symbol: [ER_IB_RESURRECT_TRX_UPDATE_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Resurrected %lu transactions doing updates.

- Error number: [MY-014024](#); Symbol: [ER_AUTHENTICATION_OCI_INVALID_TOKEN](#); SQLSTATE: [HY000](#)

Message: Invalid security token provided by '%s' for '%s'@'%s': %s.

- Error number: [MY-014025](#); Symbol: [ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Unknown user/tenancy (user: %s tenancy: %s) found in security token provided by '%s' for '%s'@'%s'.

- Error number: [MY-014026](#); Symbol: [ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED](#); SQLSTATE: [HY000](#)

Message: Verification failed for security token provided by '%s' for '%s'@'%s' : %s.

- Error number: [MY-014027](#); Symbol: [ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY](#); SQLSTATE: [HY000](#)

Message: Could not download IDDP Public key. Please check if security token provided by '%s' for '%s'@'%s' is valid.

- Error number: [MY-014031](#); Symbol: [ER_UDF_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered by another component.

- Error number: [MY-014032](#); Symbol: [ER_UDF_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-014033](#); Symbol: [ER_PRIVILEGE_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register privilege '%s'. Please check if it is not already registered.

- Error number: [MY-014034](#); Symbol: [ER_PRIVILEGE_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister privilege '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-014035](#); Symbol: [ER_UDF_EXEC_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s.

- Error number: [MY-014036](#); Symbol: [ER_UDF_EXEC_FAILURE_REASON](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s: %s.

- Error number: [MY-014037](#); Symbol: [ER_COMPONENT_SERVICE_CALL](#); SQLSTATE: [HY000](#)

Message: %s failed.

- Error number: [MY-014038](#); Symbol: [ER_COMPONENT_SERVICE_CALL_RESULT](#); SQLSTATE: [HY000](#)

Message: %s failed with %u.

- Error number: [MY-014039](#); Symbol: [ER_COMPONENT_LOCK](#); SQLSTATE: [HY000](#)

Message: Lock failed at %s : %u.

- Error number: [MY-014040](#); Symbol: [ER_COMPONENT_UNLOCK](#); SQLSTATE: [HY000](#)

Message: Lock from %s : %u failed to unlock.

- Error number: [MY-014041](#); Symbol: [ER_COMPONENT_MASKING_OTHER_ERROR](#); SQLSTATE: [HY000](#)

Message: Masking component error: '%s'.

- Error number: [MY-014042](#); Symbol: [ER_COMPONENT_MASKING_ABI](#); SQLSTATE: [HY000](#)

Message: %s failed.

- Error number: [MY-014043](#); Symbol: [ER_COMPONENT_MASKING_ABI_REASON](#); SQLSTATE: [HY000](#)

Message: %s failed because %s.

- Error number: [MY-014044](#); Symbol: [ER_COMPONENT_MASKING_RANDOM_CREATE](#); SQLSTATE: [HY000](#)

Message: Creation of random context failed.

- Error number: [MY-014045](#); Symbol: [ER_COMPONENT_MASKING_RANDOM_CREATE_REASON](#); SQLSTATE: [HY000](#)

Message: Creation of random context failed because %s.

- Error number: [MY-014046](#); Symbol: [ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot access %s.%s table.

- Error number: [MY-014047](#); Symbol: [ER_REDUCED_DBLWR_FILE_CORRUPTED](#); SQLSTATE: [HY000](#)

Message: Cannot recover from detect_only doublewrite buffer as page %u from batch doublewrite file is corrupted.

- Error number: [MY-014048](#); Symbol: [ER_REDUCED_DBLWR_PAGE_FOUND](#); SQLSTATE: [HY000](#)

Message: Database page corruption of tablespace %s space_id: %u page_num: %u. Cannot recover it from the doublewrite buffer because it was written in detect_only-doublewrite mode.

- Error number: [MY-014049](#); Symbol: [ER_CONN_INIT_CONNECT_IGNORED_MFA](#); SQLSTATE: [HY000](#)

Message: init_connect variable is ignored for user: %s host: %s due to multi-factor registration required sandboxing

- Error number: [MY-014050](#); Symbol: [ER_SECONDARY_ENGINE_DDL_FAILED](#); SQLSTATE: [HY000](#)

Message: Execution of alter table %s %s failed because %s.

- Error number: [MY-014052](#); Symbol: [ER_WARN_SCHEDULED_TASK_RUN_FAILED](#); SQLSTATE: [HY000](#)

Message: Scheduled run of task %s failed

- Error number: [MY-014053](#); Symbol: [ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE](#); SQLSTATE: [HY000](#)

Message: Invalid flush interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d

- Error number: [MY-014054](#); Symbol: [ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK](#); SQLSTATE: [HY000](#)

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

- Error number: [MY-014055](#); Symbol: [ER_CONVERT_MULTI_VALUE](#); SQLSTATE: [HY000](#)

Message: Multi-values cannot be converted to MySQL format: %s

- Error number: [MY-014056](#); Symbol: [ER_IB_DDL_CONVERT_HEAP_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Heap required to convert columns is not present.

- Error number: [MY-014057](#); Symbol: [ER_SERVER_DOWNGRADE_FROM_VERSION](#); SQLSTATE: [HY000](#)

Message: MySQL server downgrading from version '%u' to '%u'.

- Error number: [MY-014058](#); Symbol: [ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD](#); SQLSTATE: [HY000](#)

Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Target MySQL server version is lower than the server downgrade threshold %u.

- Error number: [MY-014059](#); Symbol: [ER_BEYOND_SERVER_UPGRADE_THRESHOLD](#); SQLSTATE: [HY000](#)

Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Target MySQL server version is lower than the server upgrade threshold %u.

- Error number: [MY-014060](#); Symbol: [ER_INVALID_SERVER_UPGRADE_NOT_LTS](#); SQLSTATE: [HY000](#)

Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Upgrade to next major version is only allowed from the last LTS release, which version %u is not.

- Error number: [MY-014061](#); Symbol: [ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH](#); SQLSTATE: [HY000](#)

Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Downgrade is only permitted between patch releases.

- Error number: [MY-014062](#); Symbol: [ER_FAILED_GET_DD_PROPERTY](#); SQLSTATE: [HY000](#)

Message: Failed to get the data dictionary property %s.

- Error number: [MY-014063](#); Symbol: [ER_FAILED_SET_DD_PROPERTY](#); SQLSTATE: [HY000](#)

Message: Failed to set the data dictionary property %s.

- Error number: [MY-014064](#); Symbol: [ER_SERVER_DOWNGRADE_STATUS](#); SQLSTATE: [HY000](#)

Message: Server downgrade from '%d' to '%d' %s.

- Error number: [MY-014065](#); Symbol: [ER_INFORMATION_SCHEMA_VERSION_CHANGE](#); SQLSTATE: [HY000](#)

Message: %s information schema from version %u to %u.

- Error number: [MY-014066](#); Symbol: [ER_PERFORMANCE_SCHEMA_VERSION_CHANGE](#); SQLSTATE: [HY000](#)

Message: %s performance schema from version %u to %u.

-
- Error number: [MY-014067](#); Symbol: [ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER](#); SQLSTATE: [HY000](#)

Message: Value for option '%s' contains cipher '%s' that is either blocked or deprecated (and will be removed in a future release). Please refer to the documentation for more details.
 - Error number: [MY-014068](#); Symbol: [ER_IB_MSG_DDL_FAIL_NO_BUILDER](#); SQLSTATE: [HY000](#)

Message: DDL failed as Builder is already freed. Builder: state=%u, error_state=%u. Index: id=%zu, name='%s', space_id=%u, page=%u. Table: old_name='%s', new_name='%s'.
 - Error number: [MY-014069](#); Symbol: [ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Member identified %s: '%s' does not exist on Group Replication membership during %s.
 - Error number: [MY-014070](#); Symbol: [ER_USAGE_DEPRECATED_COUNTER](#); SQLSTATE: [HY000](#)

Message: Deprecated '%s' used %s times, last time used '%s'.
 - Error number: [MY-014071](#); Symbol: [ER_WAITING_FOR_NO_CONNECTIONS](#); SQLSTATE: [HY000](#)

Message: Waiting for %u connections to be closed.
 - Error number: [MY-014072](#); Symbol: [ER_WAITING_FOR_NO_THDS](#); SQLSTATE: [HY000](#)

Message: Waiting for THDs in partition %u to be closed, %u still left. %u THDs left in total for all partitions.
 - Error number: [MY-014073](#); Symbol: [ER_IB_INDEX_PART_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Index %s of %s.%s exceeds limit of %lu bytes per column.
 - Error number: [MY-014078](#); Symbol: [ER_CHECK_TABLE_FUNCTIONS](#); SQLSTATE: [HY000](#)

Message: Can not open table '%s'. '%s'; functions in constraints, partitions, or virtual columns may have failed.
 - Error number: [MY-014079](#); Symbol: [ER_CHECK_TABLE_FUNCTIONS_DETAIL](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-014080](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create the Group Replication certifier broadcast thread (THD_certifier_broadcast).
 - Error number: [MY-014081](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED](#); SQLSTATE: [HY000](#)

Message: The Group Replication certifier broadcast thread (THD_certifier_broadcast) started.
 - Error number: [MY-014082](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED](#); SQLSTATE: [HY000](#)

Message: The Group Replication certifier broadcast thread (THD_certifier_broadcast) stopped.
 - Error number: [MY-014083](#); Symbol: [ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL](#); SQLSTATE: [HY000](#)

Message: The group replication applier thread has received KILL request.
-

-
- Error number: [MY-014084](#); Symbol: [ER_IB_MSG_WAITING_ON_LAGGING_REDO_LOG_CONSUMER](#); SQLSTATE: [HY000](#)

Message: Threads are unable to reserve space in redo log which can't be reclaimed due to the '%s' consumer still lagging behind at LSN = %llu. Consider increasing innodb_redo_log_capacity.
 - Error number: [MY-014085](#); Symbol: [ER_IB_MSG_ABORTING_LOG_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: The redo log archiver is aborted as it was lagging behind at LSN = %llu and unable to advance for more than 2 seconds. Consider increasing the innodb_redo_log_capacity.
 - Error number: [MY-014086](#); Symbol: [ER_IB_INSTANT_ADD_DROP_COLUMN_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Trying to add or drop column(s) in table '%s' for which the current record size is %zu which is more than the maximum allowed size (%zu) for a record. Therefore ADD or DROP column with ALGORITHM = INSTANT is not allowed.
 - Error number: [MY-014087](#); Symbol: [ER_IB_INSTANT_ADD_NOT_POSSIBLE](#); SQLSTATE: [HY000](#)

Message: Cannot add %zu field(s) in table '%s' because after adding it, the record size would be %zu which is more than the maximum allowed size (%zu) for a record.
 - Error number: [MY-015000](#); Symbol: [ER_LANGUAGE_COMPONENT_INFO](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-015001](#); Symbol: [ER_LANGUAGE_COMPONENT_WARNING](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-015002](#); Symbol: [ER_LANGUAGE_COMPONENT_ERROR](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-015003](#); Symbol: [ER_IB_BULK_FLUSHER_PUNCH_HOLE](#); SQLSTATE: [HY000](#)

Message: bulkflusher: Failed to punch hole: table=%s, index=%s, space_id=%zu, page_no=%zu, disk_page_size=%zu, hole_size=%zu, file=%s, err=%zu
 - Error number: [MY-015004](#); Symbol: [ER_GRP_RPL_CONN_KILLED](#); SQLSTATE: [HY000](#)

Message: %s as the client session was killed.
 - Error number: [MY-015005](#); Symbol: [ER_WARN_CANT_OPEN_CERTIFICATE](#); SQLSTATE: [HY000](#)

Message: Cannot open certificate %s. Please check the certificate
 - Error number: [MY-015006](#); Symbol: [ER_FAILED_TO_VALIDATE_CERTIFICATES_SERVER_EXIT](#); SQLSTATE: [HY000](#)

Message: Certificate validation has failed. Stopping the server as tls-certificates-enforced-validation is enabled
 - Error number: [MY-015007](#); Symbol: [ER_WARN_CA_CERT_VERIFY_FAILED](#); SQLSTATE: [HY000](#)

Message: CA certificate/certificates is invalid. Please check logs for more details.
 - Error number: [MY-015008](#); Symbol: [ER_WARN_FAILED_TO_SETUP_TLS](#); SQLSTATE: [HY000](#)

Message: Internal TLS error %s:%s:%d:%s
 - Error number: [MY-015009](#); Symbol: [ER_TLS_LIBRARY_ERROR_INTERNAL](#); SQLSTATE: [HY000](#)

Message: Failed to set up TLS. Check logs for details

- Error number: [MY-015010](#); Symbol: [ER_SERVER_CERT_VERIFY_FAILED](#); SQLSTATE: [HY000](#)

Message: Server certificate %s verification has failed. Check logs for more details

- Error number: [MY-015011](#); Symbol: [ER_WARN_CERTIFICATE_ERROR_STRING](#); SQLSTATE: [HY000](#)

Message: Failed to validate certificate %s because %s

- Error number: [MY-015012](#); Symbol: [ER_TELEMETRY_INFO](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015013](#); Symbol: [ER_TELEMETRY_WARNING](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015014](#); Symbol: [ER_TELEMETRY_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015015](#); Symbol: [ER_SRV_START](#); SQLSTATE: [HY000](#)

Message: MySQL Server - start.

- Error number: [MY-015016](#); Symbol: [ER_SRV_END](#); SQLSTATE: [HY000](#)

Message: MySQL Server - end.

- Error number: [MY-015017](#); Symbol: [ER_SRV_INIT_START](#); SQLSTATE: [HY000](#)

Message: MySQL Server Initialization - start.

- Error number: [MY-015018](#); Symbol: [ER_SRV_INIT_END](#); SQLSTATE: [HY000](#)

Message: MySQL Server Initialization - end.

- Error number: [MY-015019](#); Symbol: [ER_PLUGINS_SHUTDOWN_START](#); SQLSTATE: [HY000](#)

Message: MySQL Server: Plugins Shutdown - start.

- Error number: [MY-015020](#); Symbol: [ER_PLUGINS_SHUTDOWN_END](#); SQLSTATE: [HY000](#)

Message: MySQL Server: Plugins Shutdown - end.

- Error number: [MY-015021](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_START](#); SQLSTATE: [HY000](#)

Message: MySQL Server: Components Shutdown - start.

- Error number: [MY-015022](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_END](#); SQLSTATE: [HY000](#)

Message: MySQL Server: Components Shutdown - end (with return value = %d).

- Error number: [MY-015023](#); Symbol: [ER_CONNECTIONS_SHUTDOWN_START](#); SQLSTATE: [HY000](#)

Message: MySQL Server: Closing Connections - start.

- Error number: [MY-015024](#); Symbol: [ER_CONNECTIONS_SHUTDOWN_END](#); SQLSTATE: [HY000](#)

Message: MySQL Server: Closing Connections - end.

-
- Error number: [MY-015025](#); Symbol: [ER_THREAD_STILL_ALIVE](#); SQLSTATE: [HY000](#)
Message: Waiting for forceful disconnection of Thread (ID %ld) to end.
 - Error number: [MY-015026](#); Symbol: [ER_NUM_THREADS_STILL_ALIVE](#); SQLSTATE: [HY000](#)
Message: Waiting for forceful disconnection of %ld thread(s) to end.
 - Error number: [MY-015027](#); Symbol: [ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_SERVER_ERROR_COMMAND_ERR](#); SQLSTATE: [HY000](#)
Message: Failed to accept a MySQL connection for Group Replication. %s. Please retry.
 - Error number: [MY-015028](#); Symbol: [ER_COMPONENT_KEYRING_OCI_INVALID_CONFIG_VAR](#); SQLSTATE: [HY000](#)
Message: Invalid value of argument %s (%s).
 - Error number: [MY-015029](#); Symbol: [ER_WARN_OPTION_RESET_AND_IGNORED_DURING_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: Ignoring a non-default value for %s during --initialize.
 - Error number: [MY-015030](#); Symbol: [ER_FIREWALL_SCHEDULER_REGISTER_FAILED](#); SQLSTATE: [HY000](#)
Message: Automatic registration of the scheduler failed.
 - Error number: [MY-015031](#); Symbol: [ER_FIREWALL_INVALID_RELOAD_INTERVAL_VALUE](#); SQLSTATE: [HY000](#)
Message: Invalid reload interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d.
 - Error number: [MY-015033](#); Symbol: [ER_BULK_MULTI_READER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk Multi Reader: %s
 - Error number: [MY-015034](#); Symbol: [ER_BULK_MERGE_LOADER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk Merge Loader: %s
 - Error number: [MY-015035](#); Symbol: [ER_BULK_SORTING_LOADER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk Sorting Loader: %s
 - Error number: [MY-015036](#); Symbol: [ER_BULK_WRITER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk Writer: %s
 - Error number: [MY-015037](#); Symbol: [ER_BULK_WRITER_LIBCURL_INIT_FAILED_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk writer failed to initialize libcurl
 - Error number: [MY-015038](#); Symbol: [ER_BULK_WRITER_LIBCURL_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk writer got libcurl error: %s
 - Error number: [MY-015039](#); Symbol: [ER_IB_WRONG_PAGE_ID](#); SQLSTATE: [HY000](#)
Message: Detected wrong page_id: buf_block_t[space_id=%zu, page_no=%zu], buf_frame_t[space_id=%zu, page_no=%zu], file=%s

-
- Error number: [MY-015040](#); Symbol: [ER_IB_FIXED_PAGE_ID](#); SQLSTATE: [HY000](#)
Message: Fixed wrong page_id with sync read: buf_block_t[space_id=%zu, page_no=%zu], buf_frame_t[space_id=%zu, page_no=%zu], file=%s, retry=%zu
 - Error number: [MY-015041](#); Symbol: [ER_IB_WRONG_PAGEID_AFTER_SYNC_READ](#); SQLSTATE: [HY000](#)
Message: Wrong page_id after sync read: buf_block_t[space_id=%zu, page_no=%zu], buf_frame_t[space_id=%zu, page_no=%zu], file=%s, retry=%zu
 - Error number: [MY-015042](#); Symbol: [ER_IB_SYNC_READ_FAILED](#); SQLSTATE: [HY000](#)
Message: Sync read to fix wrong page_id failed: buf_block_t[space_id=%zu, page_no=%zu], file=%s, err=%zu, retry=%zu
 - Error number: [MY-015043](#); Symbol: [ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION_LOG](#); SQLSTATE: [HY000](#)
Message: Cannot start replication channel '%s' because %s.
 - Error number: [MY-015044](#); Symbol: [ER_GROUP_REPLICATION_CERTIFIER_MESSAGE_LARGE](#); SQLSTATE: [HY000](#)
Message: The certification information, part of the required information to the new member join the group, is too big and cannot be send. Please wait until the value of the column COUNT_TRANSACTIONS_ROWS_VALIDATING of the table performance_schema.replication_group_member_stats decreases and try to join the new member again.
 - Error number: [MY-015045](#); Symbol: [ER_GROUP_REPLICATION_METADATA_SENDER_IS_REMOTE](#); SQLSTATE: [HY000](#)
Message: The member %s:%u will be the one sending the recovery metadata message.
 - Error number: [MY-015046](#); Symbol: [ER_GROUP_REPLICATION_METADATA_SENDER](#); SQLSTATE: [HY000](#)
Message: This member %s:%u will be the one sending the recovery metadata message.
 - Error number: [MY-015047](#); Symbol: [ER_GROUP_REPLICATION_ERROR_COMPRESS_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: Error initializing the %s compression context. Data cannot be compressed.
 - Error number: [MY-015048](#); Symbol: [ER_GROUP_REPLICATION_COMPRESS_PROCESS](#); SQLSTATE: [HY000](#)
Message: Error while compressing data using %s compression. Data cannot be decompressed.
 - Error number: [MY-015049](#); Symbol: [ER_GROUP_REPLICATION_UNKOWN_COMPRESSION_TYPE](#); SQLSTATE: [HY000](#)
Message: Error unknown Compression Library requested.
 - Error number: [MY-015050](#); Symbol: [ER_GROUP_REPLICATION_COMPRESS_EXCEEDS_MAX_SIZE](#); SQLSTATE: [HY000](#)
Message: Error while compressing data using %s compression. The operation could not be performed as buffer size exceeded configured maximum size. Please wait until the value of the column COUNT_TRANSACTIONS_ROWS_VALIDATING of the table performance_schema.replication_group_member_stats decreases and try to join the new member again.

-
- Error number: [MY-015051](#); Symbol: [ER_GROUP_REPLICATION_COMPRESS_OUT_OF_MEMORY](#); SQLSTATE: [HY000](#)

Message: Error while compressing data using %s compression. The operation could not be performed as memory allocation failed.

- Error number: [MY-015052](#); Symbol: [ER_GROUP_REPLICATION_ERROR_DECOMPRESS_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Error initializing the %s decompression context. Data cannot be decompressed.

- Error number: [MY-015053](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_EXCEEDS_MAX_SIZE](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as buffer size exceeded configured maximum size. Please wait until the value of the column `COUNT_TRANSACTIONS_ROWS_VALIDATING` of the table `performance_schema.replication_group_member_stats` decreases and try to join the new member again.

- Error number: [MY-015054](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_OUT_OF_MEMORY](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as memory allocation failed.

- Error number: [MY-015055](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as all the input provided to decompress is consumed, but the decompressed output produced is less than required.

- Error number: [MY-015056](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_CORRUPTED](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as the compression library reported an error.

- Error number: [MY-015057](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_END](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as no more input bytes remaining to decompress. The decompressed output has not been changed.

- Error number: [MY-015058](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_PROCESS](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. Data cannot be decompressed.

- Error number: [MY-015059](#); Symbol: [ER_GRP_RPL_VCLE_NOT_BEING_LOGGED](#); SQLSTATE: [HY000](#)

Message: View_change_log_event will not be logged further on the binary log, as all members of the group are 8.3.0 or greater.

- Error number: [MY-015060](#); Symbol: [ER_GROUP_REPLICATION_METADATA_PROTOBUF_PARSING](#); SQLSTATE: [HY000](#)

Message: Error while parsing serialized Certification_info from received Recovery Metadata to Protobuf format using Protobuf library.

-
- Error number: [MY-015061](#); Symbol: [ER_GROUP_REPLICATION_PROTOBUF_SERIALIZING_ERROR](#); SQLSTATE: [HY000](#)
Message: Error while serializing % data using Protobuf library.
 - Error number: [MY-015062](#); Symbol: [ER_GROUP_REPLICATION_ERROR_RECEIVED_WAITING_METADATA](#); SQLSTATE: [HY000](#)
Message: Error received while the Recovery thread was waiting for the Recovery Metadata. The Recovery will be terminated.
 - Error number: [MY-015063](#); Symbol: [ER_GROUP_REPLICATION_TIMEOUT_ERROR_FETCHING_METADATA](#); SQLSTATE: [HY000](#)
Message: Error fetching AFTER_GTIDS from Recovery Metadata by Recovery thread. The Recovery thread timeout after waiting for %d seconds. The Recovery will be terminated.
 - Error number: [MY-015064](#); Symbol: [ER_GROUP_REPLICATION_METADATA_PAYLOAD_EMPTY](#); SQLSTATE: [HY000](#)
Message: Error while decoding the received Recovery Metadata Message. The received payload is empty which could be due to error in decoding of received Recovery Metadata Message. The joining member will leave the group.
 - Error number: [MY-015065](#); Symbol: [ER_GROUP_REPLICATION_METADATA_MESSAGE_PAYLOAD_EMPTY](#); SQLSTATE: [HY000](#)
Message: The %s payload type of the received Recovery Metadata Message is empty.
 - Error number: [MY-015066](#); Symbol: [ER_GROUP_REPLICATION_METADATA_READ_GTID_EXECUTED](#); SQLSTATE: [HY000](#)
Message: Error reading gtid_executed from the received Recovery Metadata Message.
 - Error number: [MY-015067](#); Symbol: [ER_GROUP_REPLICATION_METADATA_PAYLOAD_DECODING](#); SQLSTATE: [HY000](#)
Message: Error while decoding the received Recovery Metadata Message.
 - Error number: [MY-015068](#); Symbol: [ER_GROUP_REPLICATION_METADATA_SEND_ERROR](#); SQLSTATE: [HY000](#)
Message: The group was unable to send the Recovery Metadata to a joining member.
 - Error number: [MY-015069](#); Symbol: [ER_GROUP_REPLICATION_METADATA_SAVE_RECOVERY_COPY](#); SQLSTATE: [HY000](#)
Message: Error while saving copy of Recovery Metadata Message.
 - Error number: [MY-015070](#); Symbol: [ER_GROUP_REPLICATION_METADATA_CERT_INFO_ERROR_PROCESSING](#); SQLSTATE: [HY000](#)
Message: Error while processing received Certification Information from the Recovery Metadata Message.
 - Error number: [MY-015071](#); Symbol: [ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_EMPTY](#); SQLSTATE: [HY000](#)
Message: Error Certification Information packet from the received Recovery Metadata Message is empty.
 - Error number: [MY-015072](#); Symbol: [ER_GROUP_REPLICATION_METADATA_ERROR_ON_SEND_ERROR_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Error while sending Recovery metadata error message. If this is a temporary failure of send message and member itself hasn't left the group, then joiner will timeout waiting for Recovery metadata message. If this is a permanent failure, the member will leave the group and another member will send the Recovery metadata message.

- Error number: [MY-015073](#); Symbol: [ER_GROUP_REPLICATION_METADATA_SET_IN_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Error when transferring Recovery Metadata Message to Recovery. The joining member will leave the group.

- Error number: [MY-015074](#); Symbol: [ER_GROUP_REPLICATION_CERTIFICATION_MODULE_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error Certification module wasn't properly initialized.

- Error number: [MY-015075](#); Symbol: [ER_GROUP_REPLICATION_METADATA_INITIALIZATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error Recovery Metadata Message module wasn't properly initialized.

- Error number: [MY-015076](#); Symbol: [ER_GROUP_REPLICATION_METADATA_MEMORY_ALLOC](#); SQLSTATE: [HY000](#)

Message: Error while %s. The operation could not be performed as memory allocation failed.

- Error number: [MY-015077](#); Symbol: [ER_GROUP_REPLICATION_RECOVERY_SKIPPED_GTID_PRESENT](#); SQLSTATE: [HY000](#)

Message: The group replication recovery is skipped as the joiner's gtid executed set %s already has all the transactions of the donor's gtid set %s.

- Error number: [MY-015078](#); Symbol: [ER_GROUP_REPLICATION_RECOVERY_FETCHING_GTID_EXECUTED_SET](#); SQLSTATE: [HY000](#)

Message: Error in Group Replication Recovery while getting member's global GTID executed set.

- Error number: [MY-015079](#); Symbol: [ER_GROUP_REPLICATION_RECOVERY_ERROR_ADD_GTID_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Error in Group Replication Recovery while adding GTIDs in string format to Gtid_set.

- Error number: [MY-015080](#); Symbol: [ER_GROUP_REPLICATION_RECOVERY_METADATA_SENDER_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Error computing the current Recovery metadata sender. Check if this MEMBER is not leaving the group and the joiner is able to successfully fetch the recovery metadata or not.

- Error number: [MY-015081](#); Symbol: [ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_COUNT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error in the received Recovery Metadata Message the number of compressed Certification Information packet count mismatch with the number of sent compressed Certification Information packets.

- Error number: [MY-015082](#); Symbol: [ER_GROUP_REPLICATION_METADATA_CERT_INFO_ENCODING_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while encoding Certification Information for the Recovery Metadata Message.

- Error number: [MY-015083](#); Symbol: [ER_GROUP_REPLICATION_METADATA_NO_VALID_DONOR](#); SQLSTATE: [HY000](#)

Message: There are no valid recovery metadata donors. The joining member will leave the group.

- Error number: [MY-015084](#); Symbol: [ER_GROUP_REPLICATION_NO_CERTIFICATION_DONOR_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: No donor available to provide the certification information, part of the required information to the new member join the group. Please wait until there are ONLINE members on the group and try to join the new member again.

- Error number: [MY-015085](#); Symbol: [ER_GROUP_REPLICATION_RECOVERY_STOPPED_GTID_PRESENT](#); SQLSTATE: [HY000](#)

Message: The group replication recovery is complete, joiner gtid executed set has all the transactions of the donor's gtid set %s.

- Error number: [MY-015086](#); Symbol: [ER_RPL_ASYNC_CHECK_CONNECTION_ERROR](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread encountered an error while executing the query to check connection to the source server. Error: %s. The query failed to execute on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

- Error number: [MY-015087](#); Symbol: [ER_RPL_ASYNC_MONITOR_IO_THD_FETCH_GROUP_MAJORITY_ERROR](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread failed to detect if the source belongs to the group majority. Error: %s. The query failed to execute on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

- Error number: [MY-015088](#); Symbol: [ER_RPL_ASYNC_REPLICA_IO_THD_FETCH_GROUP_MAJORITY_ERROR](#); SQLSTATE: [HY000](#)

Message: The replica IO thread failed to detect if the source belongs to the group majority. Error: %s. The query failed to execute on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

- Error number: [MY-015089](#); Symbol: [ER_RPL_ASYNC_GET_GROUP_MEMBERSHIP_DETAILS_ERROR](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread failed to get group membership details. Error: %s. The query failed to execute on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

- Error number: [MY-015090](#); Symbol: [ER_IB_ERR_CORRUPT_TABLESPACE_UNRECOVERABLE](#); SQLSTATE: [HY000](#)

Message: Tablespace '%u' mentioned in the redo log is corrupted in a way it is unrecoverable by double-write buffer, so further redo log recovery is not possible!

- Error number: [MY-015091](#); Symbol: [ER_IB_BULK_LOAD_STATS_WARN](#); SQLSTATE: [HY000](#)

Message: %s: Failed to save statistics for table=%s err=%zu trx_err=%zu

- Error number: [MY-015092](#); Symbol: [ER_COMPONENT_MASKING_INVALID_FLUSH_INTERVAL_VALUE](#); SQLSTATE: [HY000](#)

Message: Invalid flush interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d.

- Error number: [MY-015093](#); Symbol: [ER_COMPONENT_MASKING_VAR_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'.'%s'.

-
- Error number: [MY-015094](#); Symbol: [ER_COMPONENT_MASKING_NOTIFICATION_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)
Message: Masking component failed to register notification service. Periodical masking dictionaries flush will not work.
 - Error number: [MY-015095](#); Symbol: [ER_GRP_RPL_MSG_DECODING_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to decode Group Replication message: %s. Reason : %s
 - Error number: [MY-015096](#); Symbol: [ER_GRP_RPL_APPLIER_ERROR_PACKET_RECEIVED](#); SQLSTATE: [HY000](#)
Message: The Applier process of Group Replication found an error and was requested to stop: %s
 - Error number: [MY-015097](#); Symbol: [ER_LANGUAGE_COMPONENT_INSTALL_ERROR](#); SQLSTATE: [HY000](#)
Message: Cannot install the component.
 - Error number: [MY-015098](#); Symbol: [ER_WARN_LANGUAGE_COMPONENT_CANNOT_UNINSTALL](#); SQLSTATE: [HY000](#)
Message: Cannot uninstall the language component: %s.
 - Error number: [MY-015099](#); Symbol: [ER_LANGUAGE_COMPONENT_SERVER_ERROR](#); SQLSTATE: [HY000](#)
Message: Calling component service: %s.
 - Error number: [MY-015100](#); Symbol: [ER_LANGUAGE_COMPONENT_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Internal error while %s.
 - Error number: [MY-015101](#); Symbol: [ER_LANGUAGE_COMPONENT_VM_API_FUNCTION_ERROR](#); SQLSTATE: [HY000](#)
Message: Internal VM API function failed: %s.
 - Error number: [MY-015102](#); Symbol: [ER_LANGUAGE_COMPONENT_VM_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Internal VM error while %s.
 - Error number: [MY-015103](#); Symbol: [ER_WARN_LANGUAGE_COMPONENT_RESOURCE_LIMIT](#); SQLSTATE: [HY000](#)
Message: The resource limit has been exceeded. Details: %s.
 - Error number: [MY-015104](#); Symbol: [ER_BLOCKED_CIPHER](#); SQLSTATE: [HY000](#)
Message: Value for option '%s' contains cipher '%s' that is blocked. Please refer to the documentation for allowed ciphers.
 - Error number: [MY-015105](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_FILE_NAME_EMPTY](#); SQLSTATE: [HY000](#)
Message: Keyring file path is empty in configuration file.
 - Error number: [MY-015106](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_FILE_READ_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to read keyring file: %s.

-
- Error number: `MY-015107`; Symbol: `ER_KEYRING_COMPONENT_KEYRING_FILE_DECRYPT_FAILED`; SQLSTATE: `HY000`
Message: Failed to decrypt keyring file: %s.
 - Error number: `MY-015108`; Symbol: `ER_KEYRING_COMPONENT_KEYRING_FILE_INVALID_FORMAT`; SQLSTATE: `HY000`
Message: The keyring file content is not in a valid JSON format.
 - Error number: `MY-015109`; Symbol: `ER_KEYRING_COMPONENT_KEYRING_FILE_JSON_EXTRACT_FAILED`; SQLSTATE: `HY000`
Message: Failed to extract a valid JSON data from keyring file.
 - Error number: `MY-015110`; Symbol: `ER_KEYRING_COMPONENT_KEYRING_FILE_KEY_EXTRACT_FAILED`; SQLSTATE: `HY000`
Message: Failed to extract key from keyring file JSON data.
 - Error number: `MY-015111`; Symbol: `ER_NOTE_KEYRING_COMPONENT_NOT_INITIALIZED`; SQLSTATE: `HY000`
Message: Keyring component is not initialized.
 - Error number: `MY-015112`; Symbol: `ER_NOTE_KEYRING_COMPONENT_EMPTY_DATA_ID`; SQLSTATE: `HY000`
Message: Provided Data ID is empty.
 - Error number: `MY-015113`; Symbol: `ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_INIT_FAILED`; SQLSTATE: `HY000`
Message: Failed to initialize metadata iterator.
 - Error number: `MY-015114`; Symbol: `ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR_INIT_FAILED`; SQLSTATE: `HY000`
Message: Failed to initialize key reader iterator.
 - Error number: `MY-015115`; Symbol: `ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR_FETCH_FAILED`; SQLSTATE: `HY000`
Message: Failed to read key from key reader iterator.
 - Error number: `MY-015116`; Symbol: `ER_BACKGROUND_HISTOGRAM_UPDATE`; SQLSTATE: `HY000`
Message: %*s
 - Error number: `MY-015117`; Symbol: `ER_IB_MSG_SUBMIT_DETAILED_BUG_REPORT`; SQLSTATE: `HY000`
Message: Submit a detailed bug report to <http://bugs.mysql.com>
 - Error number: `MY-015118`; Symbol: `ER_AUTO_INCREMENT_NOT_SUPPORTED_FOR_FLOAT_DOUBLE`; SQLSTATE: `HY000`
Message: AUTO_INCREMENT is not supported with DOUBLE/FLOAT field. Please consider fixing (Schema:%s, Table:%s, Column:%s).
 - Error number: `MY-015119`; Symbol: `ER_SERVER_DOWNGRADE_SYS_SCHEMA`; SQLSTATE: `HY000`
Message: Downgrading the sys schema.

-
- Error number: [MY-015120](#); Symbol: [ER_SERVER_DOWNGRADE_HELP_TABLE_STATUS](#); SQLSTATE: [HY000](#)

Message: Downgrade of help tables %s.
 - Error number: [MY-015121](#); Symbol: [ER_KEYRING_MIGRATE_SKIPPED_KEY](#); SQLSTATE: [HY000](#)

Message: Could not find data pointed by data_id: %s, auth_id: %s. Skipping.
 - Error number: [MY-015122](#); Symbol: [ER_KEYRING_MIGRATE_MEMORY_DEALLOCATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to deallocate reader_object.
 - Error number: [MY-015123](#); Symbol: [ER_LOG_CLIENT_INTERACTION_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: A connection from %s was closed by the server due to a timeout in the communication layer (vio:%d, packet:%d) %ld seconds after the last command started. Currently configured wait_timeout is %ld seconds.
 - Error number: [MY-015124](#); Symbol: [ER_GRP_RPL_PREEMPTIVE_GARBAGE_COLLECTION_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a group_replication_preemptive_garbage_collection option value '%d' different from the group '%d'. The member will now exit the group.
 - Error number: [MY-015125](#); Symbol: [ER_IB_LONG_ROLLBACK_FULL](#); SQLSTATE: [HY000](#)

Message: Still rolling back transaction %llu; %llu undo records rolled back out of %llu total (%lu%% complete). Transaction info: last state: %s
 - Error number: [MY-015126](#); Symbol: [ER_IB_LONG_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: Still rolling back transaction %llu; %llu undo records rolled back out of %llu total (%lu%% complete).
 - Error number: [MY-015127](#); Symbol: [ER_INVALID_FILE_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid format of file '%s'.
 - Error number: [MY-015128](#); Symbol: [ER_LOG_SANITIZATION](#); SQLSTATE: [HY000](#)

Message: Relay log sanitization: %s
 - Error number: [MY-015129](#); Symbol: [ER_WARN_LOG_DEPRECATED_NON_STANDARD_KEY](#); SQLSTATE: [HY000](#)

Message: Foreign key '%s' on table '%s'.'%s' refers to non-unique key or partial key. This is deprecated and will be removed in a future release.
 - Error number: [MY-015130](#); Symbol: [ER_THREAD_POOL_MTL_DISABLE](#); SQLSTATE: [HY000](#)

Message: Disabling MTL in thread group %u since it has %u (=MTL per group) long running transactions.
 - Error number: [MY-015131](#); Symbol: [ER_THREAD_POOL_MTL_REENABLE](#); SQLSTATE: [HY000](#)

Message: Re-enabling MTL in thread group %u since it is down to %u long running transactions.

-
- Error number: [MY-015132](#); Symbol: [ER_LOG_PARTITION_PREFIX_KEY_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Column '%s.%s.%s' having prefix key part '%s(%u)' in the PARTITION BY KEY() clause is not supported.
 - Error number: [MY-015133](#); Symbol: [ER_LDAP_AUTH_INFO_USER_MAP](#); SQLSTATE: [HY000](#)
Message: Login user: %s@%s (external: %s) authenticated as: %s
 - Error number: [MY-015134](#); Symbol: [ER_ACCESS_DENIED_NO_PROXY_GRANT_WITH_NAME](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s', missing proxy privilege to '%s'.
 - Error number: [MY-015135](#); Symbol: [ER_ACCESS_DENIED_NO_PROXY_WITH_NAME](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s', proxied user '%s' doesn't exist.
 - Error number: [MY-015136](#); Symbol: [ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_START](#); SQLSTATE: [HY000](#)
Message: Distributed recovery will wait until the transactions '%s' contained on the 'group_replication_applier' channel are applied.
 - Error number: [MY-015137](#); Symbol: [ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_FINISH](#); SQLSTATE: [HY000](#)
Message: Distributed recovery finished applying the transactions '%s' contained on the 'group_replication_applier' channel.
 - Error number: [MY-015138](#); Symbol: [ER_BULK_READER_ZSTD_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: ZSTD decompression failed: %s
 - Error number: [MY-015139](#); Symbol: [ER_SECONDARY_ENGINE_DDL_TRACK_PROGRESS](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-015140](#); Symbol: [ER_IB_MSG_INNODB_FLUSH_METHOD](#); SQLSTATE: [HY000](#)
Message: Using innodb_flush_method=%s
 - Error number: [MY-015141](#); Symbol: [ER_BULK_SCANNER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk Scanner: %s
 - Error number: [MY-015142](#); Symbol: [ER_LOG_DEPRECATED_NON_COMPOSABLE_MULTIPLE_ENGINE](#); SQLSTATE: [HY000](#)
Message: Combining the storage engines %s and %s is deprecated, but the statement or transaction updates both the %s table %s.%s and the %s table %s.%s.
 - Error number: [MY-015143](#); Symbol: [ER_DD_UPDATE_DATADIR_FLAG_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to update data directory flag for dd table with tablespace id '%llu' when ibd file for '%s' is moved to new location '%s' during server shutdown
 - Error number: [MY-015144](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_PREV](#); SQLSTATE: [HY000](#)
Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory, but DD misses info about DATA DIRECTORY

-
- Error number: [MY-015145](#); Symbol: [ER_LOAD_BULK_JSON_ERROR](#); SQLSTATE: [HY000](#)
Message: Bulk CSV parser reports JSON error: %s at %zu
 - Error number: [MY-015146](#); Symbol: [ER_IB_BULK_LOAD_STATS_INFO](#); SQLSTATE: [HY000](#)
Message: %s: %s: Saving statistics for table=%s err=%zu trx_err=%zu
 - Error number: [MY-015147](#); Symbol: [ER_AUTHENTICATION_OPENID_INVALID_TOKEN](#); SQLSTATE: [HY000](#)
Message: Invalid identity token provided by '%s' for '%s'@'%s': %s.
 - Error number: [MY-015148](#); Symbol: [ER_AUTHENTICATION_OPENID_ISSUER_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Issuer (%s) found in identity token provided by '%s' for '%s'@'%s' does not match the issuer in the configuration.
 - Error number: [MY-015149](#); Symbol: [ER_AUTHENTICATION_OPENID_USER_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Unknown subject (%s) found in identity token provided by '%s' for '%s'@'%s'.
 - Error number: [MY-015150](#); Symbol: [ER_AUTHENTICATION_OPENID_INVALID_CONFIGURATION](#); SQLSTATE: [HY000](#)
Message: The configuration for authentication_openid_connect is invalid. %s.
 - Error number: [MY-015151](#); Symbol: [ER_AUTHENTICATION_OPENID_TOKEN_NOT_VERIFIED](#); SQLSTATE: [HY000](#)
Message: Verification failed for identity token provided by '%s' for '%s'@'%s' : %s.
 - Error number: [MY-015152](#); Symbol: [ER_AUTHENTICATION_OPENID_INSECURE_CONNECTION](#); SQLSTATE: [HY000](#)
Message: The Client-Server connection is not secure. Please make sure either a TLS, socket or shared memory connection is established between the client and the server.
 - Error number: [MY-015153](#); Symbol: [ER_AUTHENTICATION_OPENID_READ_PACKET](#); SQLSTATE: [HY000](#)
Message: An error occurred during the client server handshake.
 - Error number: [MY-015154](#); Symbol: [ER_AUTHENTICATION_OPENID_INVALID_TOKEN_SIZE](#); SQLSTATE: [HY000](#)
Message: The ID token is not acceptable. Token size should be less than 10k.
 - Error number: [MY-015155](#); Symbol: [ER_AUTHENTICATION_OPENID_INVALID_IDENTITY_PROVIDER](#); SQLSTATE: [HY000](#)
Message: The provided identity provider in the auth string is not supported.
 - Error number: [MY-015156](#); Symbol: [ER_AUTHENTICATION_OPENID_CONFIGURATION_NOT_SET](#); SQLSTATE: [HY000](#)
Message: The configuration for the plugin is not set. Please set authentication_openid_connect_configuration before a login attempt or user creation.
 - Error number: [MY-015157](#); Symbol: [ER_AUTHENTICATION_OPENID_FAILED_TO_UPDATE_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Failed to update authentication_openid_connect_configuration to a new value and the old value is lost too. Please set it to avoid unexpected results.

- Error number: [MY-015158](#); Symbol: [ER_SIMPLE_ERROR_LOG_COMPONENT_STATUS](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015159](#); Symbol: [ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED](#); SQLSTATE: [HY000](#)

Message: Upon reconnection with the replica, while initializing the dump thread for %s <%s>, an existing dump thread with the same %s was detected. The source is terminating the previous dump thread (%u), which is normal and expected.

- Error number: [MY-015160](#); Symbol: [ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER](#); SQLSTATE: [HY000](#)

Message: The transaction '%s' will commit out of order with respect to its source to follow the group global order.

- Error number: [MY-015161](#); Symbol: [ER_TEMPTABLE_ENGINE_ERROR](#); SQLSTATE: [HY000](#)

Message:temptable: %s

- Error number: [MY-015500](#); Symbol: [ER_INVALID_METER](#); SQLSTATE: [HY000](#)

Message: Invalid meter name or value for performance_schema_meter '%s'.

- Error number: [MY-015501](#); Symbol: [ER_INVALID_LOGGER](#); SQLSTATE: [HY000](#)

Message: Invalid logger name or value for performance_schema_logger '%s'.

- Error number: [MY-015502](#); Symbol: [ER_IB_DELETE_SCHEMA_DIR](#); SQLSTATE: [HY000](#)

Message: deleted the schema directory: %s

- Error number: [MY-015503](#); Symbol: [ER_IB_INSERT_DELETE_SCHEMA_DIRECTORY_DDL_LOG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015504](#); Symbol: [ER_IMDS_OCI_INFO](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015505](#); Symbol: [ER_IMDS_OCI_WARNING](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015506](#); Symbol: [ER_IMDS_OCI_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015507](#); Symbol: [ER_THREAD_POOL_CONNECTION_INIT_REPORT](#); SQLSTATE: [HY000](#)

Message: TP conn (init: in, queue, auth, err, ok. port: managed(delta), active, opened, closed, added, dropped): %s

- Error number: [MY-015508](#); Symbol: [ER_THREAD_POOL_ALLOC_FAILED](#); SQLSTATE: [HY000](#)

Message: Thread pool failed to allocate %s.

-
- Error number: [MY-015509](#); Symbol: [ER_THREAD_POOL_SOCKETPAIR_FAILED](#); SQLSTATE: [HY000](#)

Message: socketpair() failed with errno: %d
 - Error number: [MY-015510](#); Symbol: [ER_THREAD_POOL_LOW_LEVEL_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: tp_client_low_level_init() failed
 - Error number: [MY-015511](#); Symbol: [ER_THREAD_POOL_LOW_LEVEL_ARM_FAILED](#); SQLSTATE: [HY000](#)

Message: tp_client_low_level_arm() failed
 - Error number: [MY-015512](#); Symbol: [ER_THREAD_POOL_LOW_LEVEL_ARM_FAILED_WITH_ERRNO](#); SQLSTATE: [HY000](#)

Message: tp_client_low_level_arm() failed with %d
 - Error number: [MY-015513](#); Symbol: [ER_THREAD_POOL_CREATE_THREAD_FAILED](#); SQLSTATE: [HY000](#)

Message: Can't create pool thread (error %d, errno: %d)
 - Error number: [MY-015514](#); Symbol: [ER_THREAD_POOL_LOW_LEVEL_INIT_ALLOC_FAILED](#); SQLSTATE: [HY000](#)

Message: tp_client_low_level_init() for wait context failed to allocate memory
 - Error number: [MY-015515](#); Symbol: [ER_THREAD_POOL_CREATE_EPOLL_FAILED](#); SQLSTATE: [HY000](#)

Message: epoll_create() failed with %d
 - Error number: [MY-015516](#); Symbol: [ER_THREAD_POOL_EPOLL_WAIT_ERROR](#); SQLSTATE: [HY000](#)

Message: Thread pool epoll_wait() error: errno=%d.
 - Error number: [MY-015517](#); Symbol: [ER_THREAD_POOL_POLL_WAIT_ERROR](#); SQLSTATE: [HY000](#)

Message: Thread pool poll_wait() error: errno=%d.
 - Error number: [MY-015518](#); Symbol: [ER_KEYRING_COMPONENT_AWS_FILE_PATH_EMPTY](#); SQLSTATE: [HY000](#)

Message: Keyring data file path is empty in configuration file.
 - Error number: [MY-015519](#); Symbol: [ER_KEYRING_COMPONENT_AWS_FILE_OPEN_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to open keyring data file: %s.
 - Error number: [MY-015520](#); Symbol: [ER_KEYRING_COMPONENT_AWS_FILE_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read data from keyring data file: %s.
 - Error number: [MY-015521](#); Symbol: [ER_KEYRING_COMPONENT_AWS_FILE_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write data to keyring data file: %s.
-

-
- Error number: [MY-015522](#); Symbol: [ER_KEYRING_COMPONENT_AWS_FILE_PARSE_FAILED](#); SQLSTATE: [HY000](#)
Message: The keyring file content is not in a valid JSON format.
 - Error number: [MY-015523](#); Symbol: [ER_KEYRING_COMPONENT_AWS_KEY_EXTRACT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to extract %d. element from keyring file content.
 - Error number: [MY-015524](#); Symbol: [ER_KEYRING_COMPONENT_AWS_CLIENT_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to create AWS KMS client.
 - Error number: [MY-015525](#); Symbol: [ER_KEYRING_COMPONENT_AWS_CLIENT_OPERATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed AWS KMS operation %s: %s.
 - Error number: [MY-015526](#); Symbol: [ER_KEYRING_COMPONENT_AWS_GENERATE_KEY_INVALID_PARAMETER](#); SQLSTATE: [HY000](#)
Message: Invalid key generate parameter: %s = %s, must be %s.
 - Error number: [MY-015527](#); Symbol: [ER_KEYRING_COMPONENT_AWS_BACKEND_OPERATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed operation %s on key %s owned by %s.
 - Error number: [MY-015528](#); Symbol: [ER_KEYRING_COMPONENT_AWS_CACHE_OPERATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed keyring cache operation %s.
 - Error number: [MY-015529](#); Symbol: [ER_KEYRING_COMPONENT_AWS_ADD_TO_DOC_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to add key %s for %s to JSON document.
 - Error number: [MY-015530](#); Symbol: [ER_KEYRING_COMPONENT_AWS_WRITE_AFTER_REENCRYPTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to write the data after reencryption.
 - Error number: [MY-015531](#); Symbol: [ER_KEYRING_COMPONENT_AWS_READ_ONLY_LIMIT](#); SQLSTATE: [HY000](#)
Message: Cannot %s, the keyring is read only.
 - Error number: [MY-015532](#); Symbol: [ER_KEYRING_COMPONENT_AWS_CANNOT_ENCRYPT_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: CMK was changed and the keyring must be re-encrypted, but the keyring is read only. Set the read_only config parameter to false for re-encryption and reload the component.
 - Error number: [MY-015533](#); Symbol: [ER_AUTHENTICATION_OPENID_OPTION_REGISTER](#); SQLSTATE: [HY000](#)
Message: Option registration failed.
 - Error number: [MY-015534](#); Symbol: [ER_AUTHENTICATION_OPENID_OPTION_DEREGISTER](#); SQLSTATE: [HY000](#)

Message: Option deregistration failed.

- Error number: [MY-015535](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_ENCLOSED_BY_CHARACTER_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected enclosed by character found inside unenclosed string at row %ld in file '%s' resulting in malformed CSV.

- Error number: [MY-015536](#); Symbol: [ER_DIAG_LOG_STRING](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-015537](#); Symbol: [ER_FAILED_TO_CREATE_RPL_OPT_TRACKER_THREAD](#); SQLSTATE: [HY000](#)

Message: Unable to create the thread that periodically tracks the replication features. The server will continue its bootstrap.

- Error number: [MY-015538](#); Symbol: [ER_CONNECTION_CONTROL_STATUS_VAR_REG_FAILED](#); SQLSTATE: [HY000](#)

Message: component_connection_control status variables registration failed.

- Error number: [MY-015539](#); Symbol: [ER_CONNECTION_CONTROL_STATUS_VAR_UNREG_FAILED](#); SQLSTATE: [HY000](#)

Message: component_connection_control status variables unregistration failed.

- Error number: [MY-015540](#); Symbol: [ER_CONNECTION_CONTROL_VARIABLE_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)

Message: %s variable registration failed.

- Error number: [MY-015541](#); Symbol: [ER_CONNECTION_CONTROL_VARIABLE_UNREGISTRATION_FAILED](#); SQLSTATE: [HY000](#)

Message: %s variable unregistration failed.

- Error number: [MY-015542](#); Symbol: [ER_CONNECTION_CONTROL_FAILED_TO_GET_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Can't retrieve the security context from thread.

- Error number: [MY-015543](#); Symbol: [ER_CONNECTION_CONTROL_FAILED_TO_GET_ATTRIBUTE_FROM_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Can't retrieve the %s from the security context.

- Error number: [MY-015544](#); Symbol: [ER_CONNECTION_CONTROL_FAILED_DEINIT](#); SQLSTATE: [HY000](#)

Message: Failed to deinit %s.

- Error number: [MY-015545](#); Symbol: [ER_GR_RM_MEMORY_STATS_FETCH_FAILED](#); SQLSTATE: [HY000](#)

Message: Error fetching system memory stats. Retrying in 5 seconds.

- Error number: [MY-015546](#); Symbol: [ER_GR_RM_MEMORY_STATS_FETCH_SUCCESS](#); SQLSTATE: [HY000](#)

Message: Fetching system memory stats successfully resumed.

-
- Error number: [MY-015547](#); Symbol: [ER_GR_RM_CHANNEL_LAG_QUERY_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Replication channel lag retrieval failed due to query execution error. Retrying in 5 seconds.

- Error number: [MY-015548](#); Symbol: [ER_GR_RM_CHANNEL_LAG_QUERY_EXECUTION_SUCCESS](#); SQLSTATE: [HY000](#)

Message: Replication channel lag retrieved successfully resumed.

- Error number: [MY-015549](#); Symbol: [ER_GR_RM_GR_MGMT_SERVICE_ACQUIRE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to acquire Group Replication management service. Verify Group Replication status and configuration.

- Error number: [MY-015550](#); Symbol: [ER_GR_RM_GR_MEMBER_NOT_REMOVED_APPLIER_THRESHOLD_HIT_QUARANTINE](#); SQLSTATE: [HY000](#)

Message: Member threshold exceeded: applier channel lag of %d seconds exceeded tolerance threshold configured to %d seconds. However, since it joined %d seconds ago and the quarantine period is configured to %d seconds, the member will not leave the group.

- Error number: [MY-015551](#); Symbol: [ER_GR_RM_GR_MEMBER_NOT_REMOVED_RECOVERY_THRESHOLD_HIT_QUARANTINE](#); SQLSTATE: [HY000](#)

Message: Member threshold exceeded: recovery channel lag of %d seconds exceeded tolerance threshold configured to %d seconds. However, since it joined %d seconds ago and the quarantine period is configured to %d seconds, the member will not leave the group.

- Error number: [MY-015552](#); Symbol: [ER_GR_RM_GR_MEMBER_NOT_REMOVED_MEMORY_THRESHOLD_HIT_QUARANTINE](#); SQLSTATE: [HY000](#)

Message: Member threshold exceeded: memory used of %d%% exceeded tolerance threshold configured to %d%%. However, since it joined %d seconds ago and the quarantine period is configured to %d seconds, the member will not leave the group.

- Error number: [MY-015553](#); Symbol: [ER_GR_RM_GR_MEMBER_NOT_REMOVED_APPLIER_THRESHOLD_HIT_N_MEMBERS](#); SQLSTATE: [HY000](#)

Message: Member threshold exceeded: applier channel lag of %d seconds exceeded tolerance threshold configured to %d seconds. However, the group has less than 3 members, the member will not leave the group.

- Error number: [MY-015554](#); Symbol: [ER_GR_RM_GR_MEMBER_NOT_REMOVED_RECOVERY_THRESHOLD_HIT_N_MEMBERS](#); SQLSTATE: [HY000](#)

Message: Member threshold exceeded: recovery channel lag of %d seconds exceeded tolerance threshold configured to %d seconds. However, the group has less than 3 members, the member will not leave the group.

- Error number: [MY-015555](#); Symbol: [ER_GR_RM_GR_MEMBER_NOT_REMOVED_MEMORY_THRESHOLD_HIT_N_MEMBERS](#); SQLSTATE: [HY000](#)

Message: Member threshold exceeded: memory used of %d%% exceeded tolerance threshold configured to %d%%. However, the group has less than 3 members, the member will not leave the group.
- Error number: [MY-015556](#); Symbol: [ER_GR_RM_MEMBER_LEAVING_APPLIER_THRESHOLD_HIT](#); SQLSTATE: [HY000](#)

Message: Member exiting group: applier channel lag of %d seconds exceeded tolerance threshold configured to %d seconds.
- Error number: [MY-015557](#); Symbol: [ER_GR_RM_MEMBER_LEAVING_RECOVERY_THRESHOLD_HIT](#); SQLSTATE: [HY000](#)

Message: Member exiting group: recovery channel lag of %d seconds exceeded tolerance threshold configured to %d seconds.
- Error number: [MY-015558](#); Symbol: [ER_GR_RM_MEMBER_LEAVING_MEMORY_THRESHOLD_HIT](#); SQLSTATE: [HY000](#)

Message: Member exiting group: memory used of %d%% exceeded tolerance threshold configured to %d%%.
- Error number: [MY-015559](#); Symbol: [ER_NO_PATCH_DOWNGRADE_FOR_INNOVATION_RELEASES](#); SQLSTATE: [HY000](#)

Message: Patch downgrade from %d to %d is not supported because MySQL server version %d is an innovation release.
- Error number: [MY-015560](#); Symbol: [ER_WARN_OPTION_USAGE_COUNTER_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed reading the initial usedCounter value for option %s: %s
- Error number: [MY-015561](#); Symbol: [ER_GRP_PREFER_MOST_UPDATED_CONFIG_DIFFER_ON_FAILOVER](#); SQLSTATE: [HY000](#)

Message: Members have different configurations (option `group_replication_elect_prefer_most_updated.enabled`) on usage of most up-to-date method on primary failover, method will not be used.
- Error number: [MY-015562](#); Symbol: [ER_GRP_PRIMARY_ELECTION_METHOD_MOST_UPDATE](#); SQLSTATE: [HY000](#)

Message: Member with uuid %s was elected primary since it was the most up-to-date member with %lu transactions more than second most up-to-date member %s. In case of a tie member weight and then uuid lexical order was used over the most updated members.
- Error number: [MY-015563](#); Symbol: [ER_GRP_PRIMARY_ELECTION_METHOD_MEMBER_WEIGHT](#); SQLSTATE: [HY000](#)

Message: Member with uuid %s was elected primary since it was highest weight member with value %d. In case of a tie uuid lexical order was used.
- Error number: [MY-015564](#); Symbol: [ER_GRP_PRIMARY_ELECTION_FATAL_PROCESS](#); SQLSTATE: [HY000](#)

Message: Fatal error during the primary election process of Group Replication. The server will leave the group.

-
- Error number: [MY-015565](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_HASHICORP_DATA_EXTRACT_FAILED](#); SQLSTATE: [HY000](#)
Message: Hashicorp Vault DATA extract failed.
 - Error number: [MY-015566](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_HASHICORP_KEY_MALFORMED](#); SQLSTATE: [HY000](#)
Message: Hashicorp Vault KEY malformed.
 - Error number: [MY-015567](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_HASHICORP_AUTH_FAIL](#); SQLSTATE: [HY000](#)
Message: Hashicorp Vault server authentication failed.
 - Error number: [MY-015568](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_HASHICORP_CURL_SETOPT_FAILED](#); SQLSTATE: [HY000](#)
Message: Hashicorp Vault server curl_easy_setopt failed.
 - Error number: [MY-015569](#); Symbol: [ER_COMPONENT_FIREWALL_OTHER_ERROR](#); SQLSTATE: [HY000](#)
Message: Firewall component error: '%s'.
 - Error number: [MY-015570](#); Symbol: [ER_COMPONENT_FIREWALL_INVALID_RELOAD_INTERVAL_VALUE](#); SQLSTATE: [HY000](#)
Message: Invalid firewall reload interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d.
 - Error number: [MY-015571](#); Symbol: [ER_COMPONENT_FIREWALL_VAR_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)
Message: Cannot register variable '%s'. '%s'.
 - Error number: [MY-015572](#); Symbol: [ER_COMPONENT_FIREWALL_NOTIFICATION_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)
Message: Firewall component failed to register notification service. Periodical reloads will not work.
 - Error number: [MY-015573](#); Symbol: [ER_COMPONENT_FIREWALL_RECORDING_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: Statement from %s was truncated and won't be recorded, consider enlarging value of max_digest_length variable.
 - Error number: [MY-015574](#); Symbol: [ER_COMPONENT_FIREWALL_SUSPICIOUS_STMT_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: SUSPICIOUS STATEMENT from %s. Statement truncated.
 - Error number: [MY-015575](#); Symbol: [ER_COMPONENT_FIREWALL_ACCESS_DENIED_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: ACCESS DENIED for %s. Statement truncated.
 - Error number: [MY-015576](#); Symbol: [ER_COMPONENT_FIREWALL_SUSPICIOUS_STMT](#); SQLSTATE: [HY000](#)
Message: SUSPICIOUS STATEMENT from %s. Statement "%s" doesn't match any statement from any allowlist.
-

-
- Error number: [MY-015577](#); Symbol: [ER_COMPONENT_FIREWALL_ACCESS_DENIED](#); SQLSTATE: [HY000](#)

Message: ACCESS DENIED for %s. Statement: Statement "%s" doesn't match any statement from any allowlist.
 - Error number: [MY-015578](#); Symbol: [ER_COMPONENT_FIREWALL_CANNOT_ACCESS_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot access %s.%s table.
 - Error number: [MY-015579](#); Symbol: [ER_COMPONENT_FIREWALL_INVALID_TABLE_DEFINITION](#); SQLSTATE: [HY000](#)

Message: Invalid definition of %s.%s table.
 - Error number: [MY-015580](#); Symbol: [ER_COMPONENT_FIREWALL_CANNOT_READ_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot read data from %s.%s table.
 - Error number: [MY-015581](#); Symbol: [ER_COMPONENT_FIREWALL_DATABASE](#); SQLSTATE: [HY000](#)

Message: Error accessing database: %s.
 - Error number: [MY-015582](#); Symbol: [ER_COMPONENT_FIREWALL_INIT](#); SQLSTATE: [HY000](#)

Message: Error while initializing the component: %s.
 - Error number: [MY-015583](#); Symbol: [ER_COMPONENT_FIREWALL_PROCESSING_ERROR](#); SQLSTATE: [HY000](#)

Message: Error on processing statement.
 - Error number: [MY-015584](#); Symbol: [ER_COMPONENT_FIREWALL_TRACING_ERROR](#); SQLSTATE: [HY000](#)

Message: Error on tracing suspicious statement.
 - Error number: [MY-015585](#); Symbol: [ER_COMPONENT_FIREWALL_PROCESSING_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Exception on processing statement: '%s'.
 - Error number: [MY-015586](#); Symbol: [ER_NOTE_COMPONENT_FIREWALL_RELOAD](#); SQLSTATE: [HY000](#)

Message: Cache reload with interval %d seconds is on.
 - Error number: [MY-015587](#); Symbol: [ER_COMPONENT_FIREWALL_RELOAD_TOO_SHORT_PERIOD](#); SQLSTATE: [HY000](#)

Message: Attempt to reload cache before the previous reload not finished. Consider increasing value of component_firewall.reload_interval_seconds.
 - Error number: [MY-015588](#); Symbol: [ER_VAR_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s.%s'. Please check if it is not already registered.
 - Error number: [MY-015589](#); Symbol: [ER_VAR_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s.%s'. Please check if it was registered properly in the first place.

-
- Error number: [MY-015590](#); Symbol: [ER_SERVER_STARTING_WITH_RESOURCE](#); SQLSTATE: [HY000](#)
Message: MySQL Server has access to %llu %s.
 - Error number: [MY-015591](#); Symbol: [ER_INFO_AUTHENTICATION_OCI](#); SQLSTATE: [HY000](#)
Message: authentication_oci plugin reported: %s.
 - Error number: [MY-015592](#); Symbol: [ER_SERVER_MEMORY_OPTION_INVALID](#); SQLSTATE: [HY000](#)
Message: MySQL Server configured to use %llu bytes but can only access %llu bytes.
 - Error number: [MY-015593](#); Symbol: [ER_WARN_KEYRING_PLUGIN_DEPRECATED](#); SQLSTATE: [HY000](#)
Message: Plugin %s is of the deprecated keyring plugin type. Please use the corresponding keyring component instead.
 - Error number: [MY-015594](#); Symbol: [ER_AUDIT_LOG_OFFLOAD_INFO](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-015595](#); Symbol: [ER_AUDIT_LOG_OFFLOAD_WARNING](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-015596](#); Symbol: [ER_AUDIT_LOG_OFFLOAD_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-015597](#); Symbol: [ER_WARN_SERVER_MEMORY_INIT_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to read or validate server_memory, and falling back to total physical memory.
 - Error number: [MY-015598](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_PATH_EMPTY](#); SQLSTATE: [HY000](#)
Message: Keyring kmip path is empty in configuration file.
 - Error number: [MY-015599](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_INVALID_KEY_TYPE](#); SQLSTATE: [HY000](#)
Message: Invalid key type: %s used. Should be AES or SECRET.
 - Error number: [MY-015600](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_INVALID_KEY_LENGTH](#); SQLSTATE: [HY000](#)
Message: Invalid key length: %d used.
 - Error number: [MY-015601](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_GENERATE_KEY_INVALID_PARAMETER](#); SQLSTATE: [HY000](#)
Message: Invalid key generate parameter: %s = %s, must be %s.
 - Error number: [MY-015602](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_LOAD_KEY_UID](#); SQLSTATE: [HY000](#)
Message: Could not load keys uids from the KMIP server
 - Error number: [MY-015603](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ALLOCATE](#); SQLSTATE: [HY000](#)
Message: Could not allocate memory for %s object.

-
- Error number: [MY-015604](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ADD_ATTRIBUTE](#); SQLSTATE: [HY000](#)
Message: Could not add attribute, attribute_name=%s attribute value=%s
 - Error number: [MY-015605](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_FETCH_KEY](#); SQLSTATE: [HY000](#)
Message: Could not fetch generated key
 - Error number: [MY-015606](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_INIT_PRIMARY](#); SQLSTATE: [HY000](#)
Message: Could not initialize bio with primary server!
 - Error number: [MY-015607](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_INIT_STANDBY](#); SQLSTATE: [HY000](#)
Message: Could not initialize bio with standby server: %s
 - Error number: [MY-015608](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_TRYING_STANDBY](#); SQLSTATE: [HY000](#)
Message: Could not connect to the primary server %s. Trying the standby servers.
 - Error number: [MY-015609](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_KEY_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Private key does not match the certificate public key because of %s
 - Error number: [MY-015610](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_SET_KEY_FILE](#); SQLSTATE: [HY000](#)
Message: Error while setting the private key '%s' file: %s.
 - Error number: [MY-015611](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_SET_CERTIFICATE_FILE](#); SQLSTATE: [HY000](#)
Message: Error while setting the certificate '%s' file: %s.
 - Error number: [MY-015612](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_LOAD_SSL_TRUST_STORE](#); SQLSTATE: [HY000](#)
Message: Error while setting the ca certificate '%s' file: %s.
 - Error number: [MY-015613](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_REMOVE_KEY](#); SQLSTATE: [HY000](#)
Message: Could not remove the '%s' key.
 - Error number: [MY-015614](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_CONNECTION_TO_SERVER_FAILED](#); SQLSTATE: [HY000](#)
Message: Could not connect to the OKV server
 - Error number: [MY-015615](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_INIT_CLIENT](#); SQLSTATE: [HY000](#)
Message: Could not initialize OKV client, failed to allocate memory for client environment settings.
 - Error number: [MY-015616](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_INIT_SSL_LAYER](#); SQLSTATE: [HY000](#)
Message: Could not initialize SSL layer, because of the following SSL error: %s

-
- Error number: [MY-015617](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_RETRIEVE_KEY_SIGNATURE](#); SQLSTATE: [HY000](#)

Message: Could not retrieve key signature from custom attributes
 - Error number: [MY-015618](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_RETRIEVE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not retrieve key from OKV
 - Error number: [MY-015619](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_STANDBY_SERVER_COUNT_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: Number of STANDBY_SERVER values exceeded maximum limit of 64.
 - Error number: [MY-015620](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_GENERATE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not generate the key.
 - Error number: [MY-015621](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_STORE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not store the key.
 - Error number: [MY-015622](#); Symbol: [ER_WARN_COMPONENT_KEYRING_KMIP_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)

Message: Duplicate key found in kmip keyring with Name: %s and Owner: %s.
 - Error number: [MY-015623](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ACTIVATE_KEYS](#); SQLSTATE: [HY000](#)

Message: Could not activate the key.
 - Error number: [MY-015624](#); Symbol: [ER_KEYRING_COMPONENT_KMIP_FAILED_TO_STORE_OR_GENERATE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not store/generate the key - failed to set key attribute x-key-ready
 - Error number: [MY-015625](#); Symbol: [ER_WARN_DEPRECATED_SASL_MECHANISM](#); SQLSTATE: [HY000](#)

Message: Value '%s' of variable authentication_ldap_sasl_auth_method_name is deprecated and will be removed in future. Consider using more secure '%s'.
 - Error number: [MY-015626](#); Symbol: [ER_INVALID_SERVER_OPTION_CHARSET](#); SQLSTATE: [HY000](#)

Message: Character set 'utf8' rejected as command line option.
 - Error number: [MY-015627](#); Symbol: [ER_INVALID_SERVER_OPTION_COLLATION](#); SQLSTATE: [HY000](#)

Message: Collation '%s' rejected as command line option.
 - Error number: [MY-015628](#); Symbol: [ER_FAILED_TO_FIND_CHARSET_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown character set: '%s'.

-
- Error number: [MY-015629](#); Symbol: [ER_WARN_THREAD_POOL_QUERY_THREADS_INCOMPATIBLE_MTL](#); SQLSTATE: [HY000](#)

Message: The default or user configured value thread_pool_query_threads_per_group(%u) exceeds transaction threads limit per group (%u). To ensure correct operation, the server is automatically setting thread_pool_query_threads_per_group to %u. If this is not intended, consider setting thread_pool_max_transactions_limit to a higher value.%s
 - Error number: [MY-015630](#); Symbol: [ER_WARN_THREAD_POOL_QUERY_THREADS_MISMATCH_INCOMPATIBLE_ALGO](#); SQLSTATE: [HY000](#)

Message: The configured value thread_pool_query_threads_per_group(1) is not recommended when used with HIGH_CONCURRENCY_ALGORITHM. Consider setting thread_pool_query_threads_per_group to a higher value for better performance.
 - Error number: [MY-015631](#); Symbol: [ER_WARN_THREAD_POOL_DEDICATED_LISTENERS_INCOMPATIBLE_MTL](#); SQLSTATE: [HY000](#)

Message: The thread_pool_dedicated_listeners option can only be set to ON if thread_pool_max_transaction_limit > 0. Since this requirement is not met, the server is automatically disabling thread_pool_dedicated_listeners. To use dedicated listeners, please consider enabling thread_pool_max_transactions_limit.
 - Error number: [MY-015632](#); Symbol: [ER_CONN_CONTROL_STAT_CONN_EXEMPTED_USERS_UPDATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to update connection delay user exempt stats
 - Error number: [MY-015633](#); Symbol: [ER_AUTOPILOT_OLTP_ADVISOR_INFO](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-015634](#); Symbol: [ER_AUTOPILOT_OLTP_ADVISOR_WARNING](#); SQLSTATE: [HY000](#)

Message: %s
 - Error number: [MY-015635](#); Symbol: [ER_AUTOPILOT_OLTP_ADVISOR_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

Chapter 3 Client Error Message Reference

Client error messages originate from within the MySQL client library. Here is an example client error message, as displayed by the `mysql` client:

```
$> mysql -h no-such-host
ERROR 2005 (HY000): Unknown MySQL server host 'no-such-host' (0)
```

Each client error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For client errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

The client library also makes available to host client programs any errors that originate on the server side and are received by the client from the server. For a list of server-side errors, see [Chapter 2, Server Error Message Reference](#).

In addition to the errors in the following list, the client library can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: `2000`; Symbol: `CR_UNKNOWN_ERROR`;
Message: Unknown MySQL error
- Error number: `2001`; Symbol: `CR_SOCKET_CREATE_ERROR`;
Message: Can't create UNIX socket (%d)
- Error number: `2002`; Symbol: `CR_CONNECTION_ERROR`;
Message: Can't connect to local MySQL server through socket '%s' (%d)
- Error number: `2003`; Symbol: `CR_CONN_HOST_ERROR`;
Message: Can't connect to MySQL server on '%s:%u' (%d)
- Error number: `2004`; Symbol: `CR_IPSOCK_ERROR`;
Message: Can't create TCP/IP socket (%d)
- Error number: `2005`; Symbol: `CR_UNKNOWN_HOST`;
Message: Unknown MySQL server host '%s' (%d)
- Error number: `2006`; Symbol: `CR_SERVER_GONE_ERROR`;
Message: MySQL server has gone away
- Error number: `2007`; Symbol: `CR_VERSION_ERROR`;
Message: Protocol mismatch; server version = %d, client version = %d
- Error number: `2008`; Symbol: `CR_OUT_OF_MEMORY`;
Message: MySQL client ran out of memory
- Error number: `2009`; Symbol: `CR_WRONG_HOST_INFO`;
Message: Wrong host info
- Error number: `2010`; Symbol: `CR_LOCALHOST_CONNECTION`;
Message: Localhost via UNIX socket

-
- Error number: [2011](#); Symbol: [CR_TCP_CONNECTION](#);
Message: %s via TCP/IP
 - Error number: [2012](#); Symbol: [CR_SERVER_HANDSHAKE_ERR](#);
Message: Error in server handshake
 - Error number: [2013](#); Symbol: [CR_SERVER_LOST](#);
Message: Lost connection to MySQL server during query
 - Error number: [2014](#); Symbol: [CR_COMMANDS_OUT_OF_SYNC](#);
Message: Commands out of sync; you can't run this command now

Commands were executed in an improper order. This error occurs when a function is called that is not appropriate for the current state of the connection. For example, if `mysql_stmt_fetch()` is not called enough times to read an entire result set (that is, enough times to return `MYSQL_NO_DATA`), this error may occur for the following C API call.
 - Error number: [2015](#); Symbol: [CR_NAMEDPIPE_CONNECTION](#);
Message: Named pipe: %s
 - Error number: [2016](#); Symbol: [CR_NAMEDPIPEWAIT_ERROR](#);
Message: Can't wait for named pipe to host: %s pipe: %s (%lu)
 - Error number: [2017](#); Symbol: [CR_NAMEDPIPEOPEN_ERROR](#);
Message: Can't open named pipe to host: %s pipe: %s (%lu)
 - Error number: [2018](#); Symbol: [CR_NAMEDPIPESETSTATE_ERROR](#);
Message: Can't set state of named pipe to host: %s pipe: %s (%lu)
 - Error number: [2019](#); Symbol: [CR_CANT_READ_CHARSET](#);
Message: Can't initialize character set %s (path: %s)
 - Error number: [2020](#); Symbol: [CR_NET_PACKET_TOO_LARGE](#);
Message: Got packet bigger than 'max_allowed_packet' bytes
 - Error number: [2021](#); Symbol: [CR_EMBEDDED_CONNECTION](#);
Message: Embedded server
 - Error number: [2022](#); Symbol: [CR_PROBE_REPLICA_STATUS](#);
Message: Error on SHOW REPLICA STATUS:
 - Error number: [2023](#); Symbol: [CR_PROBE_REPLICA_HOSTS](#);
Message: Error on SHOW REPLICA HOSTS:
 - Error number: [2024](#); Symbol: [CR_PROBE_REPLICA_CONNECT](#);
Message: Error connecting to replica:
 - Error number: [2025](#); Symbol: [CR_PROBE_SOURCE_CONNECT](#);
Message: Error connecting to source:

-
- Error number: [2026](#); Symbol: [CR_SSL_CONNECTION_ERROR](#);
Message: SSL connection error: %s
 - Error number: [2027](#); Symbol: [CR_MALFORMED_PACKET](#);
Message: Malformed packet
 - Error number: [2028](#); Symbol: [CR_WRONG_LICENSE](#);
Message: This client library is licensed only for use with MySQL servers having '%s' license
 - Error number: [2029](#); Symbol: [CR_NULL_POINTER](#);
Message: Invalid use of null pointer
 - Error number: [2030](#); Symbol: [CR_NO_PREPARE_STMT](#);
Message: Statement not prepared
 - Error number: [2031](#); Symbol: [CR_PARAMS_NOT_BOUND](#);
Message: No data supplied for parameters in prepared statement
 - Error number: [2032](#); Symbol: [CR_DATA_TRUNCATED](#);
Message: Data truncated
 - Error number: [2033](#); Symbol: [CR_NO_PARAMETERS_EXISTS](#);
Message: No parameters exist in the statement
 - Error number: [2034](#); Symbol: [CR_INVALID_PARAMETER_NO](#);
Message: Invalid parameter number

The column number for [mysql_stmt_fetch_column\(\)](#) was invalid.

The parameter number for [mysql_stmt_send_long_data\(\)](#) was invalid.

A key name was empty or the amount of connection attribute data for [mysql_options4\(\)](#) exceeds the 64KB limit.
 - Error number: [2035](#); Symbol: [CR_INVALID_BUFFER_USE](#);
Message: Can't send long data for non-string/non-binary data types (parameter: %d)
 - Error number: [2036](#); Symbol: [CR_UNSUPPORTED_PARAM_TYPE](#);
Message: Using unsupported buffer type: %d (parameter: %d)
 - Error number: [2037](#); Symbol: [CR_SHARED_MEMORY_CONNECTION](#);
Message: Shared memory: %s
 - Error number: [2038](#); Symbol: [CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR](#);
Message: Can't open shared memory; client could not create request event (%lu)
 - Error number: [2039](#); Symbol: [CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR](#);
Message: Can't open shared memory; no answer event received from server (%lu)
 - Error number: [2040](#); Symbol: [CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR](#);

-
- Message: Can't open shared memory; server could not allocate file mapping (%lu)
- Error number: 2041; Symbol: CR_SHARED_MEMORY_CONNECT_MAP_ERROR;
- Message: Can't open shared memory; server could not get pointer to file mapping (%lu)
- Error number: 2042; Symbol: CR_SHARED_MEMORY_FILE_MAP_ERROR;
- Message: Can't open shared memory; client could not allocate file mapping (%lu)
- Error number: 2043; Symbol: CR_SHARED_MEMORY_MAP_ERROR;
- Message: Can't open shared memory; client could not get pointer to file mapping (%lu)
- Error number: 2044; Symbol: CR_SHARED_MEMORY_EVENT_ERROR;
- Message: Can't open shared memory; client could not create %s event (%lu)
- Error number: 2045; Symbol: CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR;
- Message: Can't open shared memory; no answer from server (%lu)
- Error number: 2046; Symbol: CR_SHARED_MEMORY_CONNECT_SET_ERROR;
- Message: Can't open shared memory; cannot send request event to server (%lu)
- Error number: 2047; Symbol: CR_CONN_UNKNOW_PROTOCOL;
- Message: Wrong or unknown protocol
- Error number: 2048; Symbol: CR_INVALID_CONN_HANDLE;
- Message: Invalid connection handle
- Error number: 2049; Symbol: CR_UNUSED_1;
- Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure_auth' enabled)
- Error number: 2050; Symbol: CR_FETCH_CANCELED;
- Message: Row retrieval was canceled by mysql_stmt_close() call
- Error number: 2051; Symbol: CR_NO_DATA;
- Message: Attempt to read column without prior row fetch
- Error number: 2052; Symbol: CR_NO_STMT_METADATA;
- Message: Prepared statement contains no metadata
- Error number: 2053; Symbol: CR_NO_RESULT_SET;
- Message: Attempt to read a row while there is no result set associated with the statement
- Error number: 2054; Symbol: CR_NOT_IMPLEMENTED;
- Message: This feature is not implemented yet
- Error number: 2055; Symbol: CR_SERVER_LOST_EXTENDED;
- Message: Lost connection to MySQL server at '%s', system error: %d
- Error number: 2056; Symbol: CR_STMT_CLOSED;

Message: Statement closed indirectly because of a preceding %s() call

- Error number: 2057; Symbol: CR_NEW_STMT_METADATA;

Message: The number of columns in the result set differs from the number of bound buffers. You must reset the statement, rebind the result set columns, and execute the statement again

- Error number: 2058; Symbol: CR_ALREADY_CONNECTED;

Message: This handle is already connected. Use a separate handle for each connection.

- Error number: 2059; Symbol: CR_AUTH_PLUGIN_CANNOT_LOAD;

Message: Authentication plugin '%s' cannot be loaded: %s

- Error number: 2060; Symbol: CR_DUPLICATE_CONNECTION_ATTR;

Message: There is an attribute with the same name already

A duplicate connection attribute name was specified for `mysql_options4()`.

- Error number: 2061; Symbol: CR_AUTH_PLUGIN_ERR;

Message: Authentication plugin '%s' reported error: %s

- Error number: 2062; Symbol: CR_INSECURE_API_ERR;

Message: Insecure API function call: '%s' Use instead: '%s'

An insecure function call was detected. Modify the application to use the suggested alternative function instead.

- Error number: 2063; Symbol: CR_FILE_NAME_TOO_LONG;

Message: File name is too long

- Error number: 2064; Symbol: CR_SSL_FIPS_MODE_ERR;

Message: Set FIPS mode ON/STRICT failed

- Error number: 2065; Symbol: CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED;

Message: Compression protocol not supported with asynchronous protocol

- Error number: 2066; Symbol: CR_COMPRESSION_WRONGLY_CONFIGURED;

Message: Connection failed due to wrongly configured compression algorithm

- Error number: 2067; Symbol: CR_KERBEROS_USER_NOT_FOUND;

Message: SSO user not found, Please perform SSO authentication using kerberos.

- Error number: 2068; Symbol: CR_LOAD_DATA_LOCAL_INFILE_REJECTED;

Message: LOAD DATA LOCAL INFILE file request rejected due to restrictions on access.

- Error number: 2069; Symbol: CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL;

Message: Determining the real path for '%s' failed with error (%d): %s

- Error number: 2070; Symbol: CR_DNS_SRV_LOOKUP_FAILED;

Message: DNS SRV lookup failed with error : %d

-
- Error number: [2071](#); Symbol: [CR_MANDATORY_TRACKER_NOT_FOUND](#);
Message: Client does not recognise tracker type %d marked as mandatory by server.
 - Error number: [2072](#); Symbol: [CR_INVALID_FACTOR_NO](#);
Message: Invalid first argument for MYSQL_OPT_USER_PASSWORD option. Valid value should be between 1 and 3 inclusive.
 - Error number: [2073](#); Symbol: [CR_CANT_GET_SESSION_DATA](#);
Message: Can't get session data: %s
 - Error number: [2074](#); Symbol: [CR_INVALID_CLIENT_CHARSET](#);
Message: '%s' character set is having more than 1 byte minimum character length, which cannot be used as a client character set. Please use any of the single byte minimum ones, e.g. utf8mb4, latin1 etc.
 - Error number: [2075](#); Symbol: [CR_TLS_SERVER_NOT_FOUND](#);
Message: Server rejected the ssl handshake for specified sni servername, sslerror: %s

Chapter 4 Global Error Message Reference

This document lists “global” error messages that are shared in the sense that they can be produced by the MySQL server or by MySQL client programs. These errors have error codes in the range from 1 to 999.

Each global error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For global errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

If the server writes a message to the error log that has a global error code, it pads the error code with leading zeros to six digits and adds a prefix of **MY-** (example: **MY-000022**). The following list displays error codes in that format.

If a client returns a message with a global error code, it adds no zero-padding or prefix to the error code.

- Error number: **1**; Symbol: **EE_CANTCREATEFILE**;
Message: Can't create/write to file '%s' (OS errno %d - %s)
- Error number: **2**; Symbol: **EE_READ**;
Message: Error reading file '%s' (OS errno %d - %s)
- Error number: **3**; Symbol: **EE_WRITE**;
Message: Error writing file '%s' (OS errno %d - %s)
- Error number: **4**; Symbol: **EE_BADCLOSE**;
Message: Error on close of '%s' (OS errno %d - %s)
- Error number: **5**; Symbol: **EE_OUTOFMEMORY**;
Message: Out of memory (Needed %u bytes)
- Error number: **6**; Symbol: **EE_DELETE**;
Message: Error on delete of '%s' (OS errno %d - %s)
- Error number: **7**; Symbol: **EE_LINK**;
Message: Error on rename of '%s' to '%s' (OS errno %d - %s)
- Error number: **9**; Symbol: **EE_EOFERR**;
Message: Unexpected EOF found when reading file '%s' (OS errno %d - %s)
- Error number: **10**; Symbol: **EE_CANTLOCK**;
Message: Can't lock file (OS errno %d - %s)
- Error number: **11**; Symbol: **EE_CANTUNLOCK**;
Message: Can't unlock file (OS errno %d - %s)
- Error number: **12**; Symbol: **EE_DIR**;
Message: Can't read dir of '%s' (OS errno %d - %s)
- Error number: **13**; Symbol: **EE_STAT**;

-
- Message: Can't get stat of '%s' (OS errno %d - %s)
 - Error number: 14; Symbol: [EE_CANT_CHSIZE](#);
Message: Can't change size of file (OS errno %d - %s)
 - Error number: 15; Symbol: [EE_CANT_OPEN_STREAM](#);
Message: Can't open stream from handle (OS errno %d - %s)
 - Error number: 16; Symbol: [EE_GETWD](#);
Message: Can't get working directory (OS errno %d - %s)
 - Error number: 17; Symbol: [EE_SETWD](#);
Message: Can't change dir to '%s' (OS errno %d - %s)
 - Error number: 18; Symbol: [EE_LINK_WARNING](#);
Message: Warning: '%s' had %d links
 - Error number: 19; Symbol: [EE_OPEN_WARNING](#);
Message: Warning: %d files and %d streams are left open
 - Error number: 20; Symbol: [EE_DISK_FULL](#);
Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space...
 - Error number: 21; Symbol: [EE_CANT_MKDIR](#);
Message: Can't create directory '%s' (OS errno %d - %s)
 - Error number: 22; Symbol: [EE_UNKNOWN_CHARSET](#);
Message: Character set '%s' is not a compiled character set and is not specified in the '%s' file
 - Error number: 23; Symbol: [EE_OUT_OF_FILERESOURCES](#);
Message: Out of resources when opening file '%s' (OS errno %d - %s)
 - Error number: 24; Symbol: [EE_CANT_READLINK](#);
Message: Can't read value for symlink '%s' (Error %d - %s)
 - Error number: 25; Symbol: [EE_CANT_SYMLINK](#);
Message: Can't create symlink '%s' pointing at '%s' (Error %d - %s)
 - Error number: 26; Symbol: [EE_REALPATH](#);
Message: Error on realpath() on '%s' (Error %d - %s)
 - Error number: 27; Symbol: [EE_SYNC](#);
Message: Can't sync file '%s' to disk (OS errno %d - %s)
 - Error number: 28; Symbol: [EE_UNKNOWN_COLLATION](#);
Message: Collation '%s' is not a compiled collation and is not specified in the '%s' file
 - Error number: 29; Symbol: [EE_FILENOTFOUND](#);

-
- Message: File '%s' not found (OS errno %d - %s)
- Error number: [30](#); Symbol: [EE_FILE_NOT_CLOSED](#);
Message: File '%s' (fileno: %d) was not closed
 - Error number: [31](#); Symbol: [EE_CHANGE_OWNERSHIP](#);
Message: Cannot change ownership of the file '%s' (OS errno %d - %s)
 - Error number: [32](#); Symbol: [EE_CHANGE_PERMISSIONS](#);
Message: Cannot change permissions of the file '%s' (OS errno %d - %s)
 - Error number: [33](#); Symbol: [EE_CANT_SEEK](#);
Message: Cannot seek in file '%s' (OS errno %d - %s)
 - Error number: [34](#); Symbol: [EE_CAPACITY_EXCEEDED](#);
Message: Memory capacity exceeded (capacity %llu bytes)
 - Error number: [35](#); Symbol: [EE_DISK_FULL_WITH_RETRY_MSG](#);
Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space... Retry in %d secs. Message reprinted in %d secs.
 - Error number: [36](#); Symbol: [EE_FAILED_TO_CREATE_TIMER](#);
Message: Failed to create timer (OS errno %d).
 - Error number: [37](#); Symbol: [EE_FAILED_TO_DELETE_TIMER](#);
Message: Failed to delete timer (OS errno %d).
 - Error number: [38](#); Symbol: [EE_FAILED_TO_CREATE_TIMER_QUEUE](#);
Message: Failed to create timer queue (OS errno %d).
 - Error number: [39](#); Symbol: [EE_FAILED_TO_START_TIMER_NOTIFY_THREAD](#);
Message: Failed to start timer notify thread.
 - Error number: [40](#); Symbol: [EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT](#);
Message: Failed to create event to interrupt timer notifier thread (OS errno %d).
 - Error number: [41](#); Symbol: [EE_EXITING_TIMER_NOTIFY_THREAD](#);
Message: Failed to register timer event with queue (OS errno %d), exiting timer notifier thread.
 - Error number: [42](#); Symbol: [EE_WIN_LIBRARY_LOAD_FAILED](#);
Message: LoadLibrary("kernel32.dll") failed: GetLastError returns %lu.
 - Error number: [43](#); Symbol: [EE_WIN_RUN_TIME_ERROR_CHECK](#);
Message: %s.
 - Error number: [44](#); Symbol: [EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE](#);
Message: Failed to determine large page size.

-
- Error number: 45; Symbol: `EE_FAILED_TO_KILL_ALL_THREADS`;
Message: Error in my_thread_global_end(): %d thread(s) did not exit.
 - Error number: 46; Symbol: `EE_FAILED_TO_CREATE_IO_COMPLETION_PORT`;
Message: Failed to create IO completion port (OS errno %d).
 - Error number: 47; Symbol: `EE_FAILED_TO_OPEN_DEFAULTS_FILE`;
Message: Failed to open required defaults file: %s
 - Error number: 48; Symbol: `EE_FAILED_TO_HANDLE_DEFAULTS_FILE`;
Message: Fatal error in defaults handling. Program aborted!
 - Error number: 49; Symbol: `EE_WRONG_DIRECTIVE_IN_CONFIG_FILE`;
Message: Wrong '!%s' directive in config file %s at line %d.
 - Error number: 50; Symbol: `EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION`;
Message: Skipping '%s' directive as maximum include recursion level was reached in file %s at line %d.
 - Error number: 51; Symbol: `EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE`;
Message: Wrong group definition in config file %s at line %d.
 - Error number: 52; Symbol: `EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE`;
Message: Found option without preceding group in config file %s at line %d.
 - Error number: 53; Symbol: `EE_CONFIG_FILE_PERMISSION_ERROR`;
Message: %s should be readable/writable only by current user.
 - Error number: 54; Symbol: `EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE`;
Message: World-writable config file '%s' is ignored.
 - Error number: 55; Symbol: `EE_USING_DISABLED_OPTION`;
Message: %s: Option '%s' was used, but is disabled.
 - Error number: 56; Symbol: `EE_USING_DISABLED_SHORT_OPTION`;
Message: %s: Option '-%c' was used, but is disabled.
 - Error number: 57; Symbol: `EE_USING_PASSWORD_ON_CLI_IS_INSECURE`;
Message: Using a password on the command line interface can be insecure.
 - Error number: 58; Symbol: `EE_UNKNOWN_SUFFIX_FOR_VARIABLE`;
Message: Unknown suffix '%c' used for variable '%s' (value '%s').
 - Error number: 59; Symbol: `EE_SSL_ERROR_FROM_FILE`;
Message: SSL error: %s from '%s'.
 - Error number: 60; Symbol: `EE_SSL_ERROR`;
Message: SSL error: %s.

-
- Error number: [61](#); Symbol: [EE_NET_SEND_ERROR_IN_BOOTSTRAP](#);
Message: %d %s.
 - Error number: [62](#); Symbol: [EE_PACKETS_OUT_OF_ORDER](#);
Message: Packets out of order (found %u, expected %u).
 - Error number: [63](#); Symbol: [EE_UNKNOWN_PROTOCOL_OPTION](#);
Message: Unknown option to protocol: %s.
 - Error number: [64](#); Symbol: [EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY](#);
Message: Failed to locate server public key '%s'.
 - Error number: [65](#); Symbol: [EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT](#);
Message: Public key is not in Privacy Enhanced Mail format: '%s'.
 - Error number: [66](#); Symbol: [EE_DEBUG_INFO](#);
Message: %s.
 - Error number: [67](#); Symbol: [EE_UNKNOWN_VARIABLE](#);
Message: unknown variable '%s'.
 - Error number: [68](#); Symbol: [EE_UNKNOWN_OPTION](#);
Message: unknown option '--%s'.
 - Error number: [69](#); Symbol: [EE_UNKNOWN_SHORT_OPTION](#);
Message: %s: unknown option '-%c'.
 - Error number: [70](#); Symbol: [EE_OPTION_WITHOUT_ARGUMENT](#);
Message: %s: option '--%s' cannot take an argument.
 - Error number: [71](#); Symbol: [EE_OPTION_REQUIRES_ARGUMENT](#);
Message: %s: option '--%s' requires an argument.
 - Error number: [72](#); Symbol: [EE_SHORT_OPTION_REQUIRES_ARGUMENT](#);
Message: %s: option '-%c' requires an argument.
 - Error number: [73](#); Symbol: [EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE](#);
Message: %s: ignoring option '--%s' due to invalid value '%s'.
 - Error number: [74](#); Symbol: [EE_OPTION_WITH_EMPTY_VALUE](#);
Message: %s: Empty value for '%s' specified.
 - Error number: [75](#); Symbol: [EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION](#);
Message: %s: Maximum value of '%s' cannot be set.
 - Error number: [76](#); Symbol: [EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION](#);
Message: option '%s': boolean value '%s' was not recognized. Set to OFF.
 - Error number: [77](#); Symbol: [EE_FAILED_TO_SET_OPTION_VALUE](#);

Message: %s: Error while setting value '%s' to '%s'.

- Error number: 78; Symbol: `EE_INCORRECT_INT_VALUE_FOR_OPTION`;
Message: Incorrect integer value: '%s'.
- Error number: 79; Symbol: `EE_INCORRECT_UINT_VALUE_FOR_OPTION`;
Message: Incorrect unsigned integer value: '%s'.
- Error number: 80; Symbol: `EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION`;
Message: option '%s': signed value %s adjusted to %s.
- Error number: 81; Symbol: `EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION`;
Message: option '%s': unsigned value %s adjusted to %s.
- Error number: 82; Symbol: `EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION`;
Message: option '%s': value %s adjusted to %s.
- Error number: 83; Symbol: `EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION`;
Message: option '%s': value %g adjusted to %g.
- Error number: 84; Symbol: `EE_INVALID_DECIMAL_VALUE_FOR_OPTION`;
Message: Invalid decimal value for option '%s'.
- Error number: 85; Symbol: `EE_COLLATION_PARSER_ERROR`;
Message: %s.
- Error number: 86; Symbol: `EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a primary ignorable character %s.
- Error number: 87; Symbol: `EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a tertiary ignorable character %s.
- Error number: 88; Symbol: `EE_SHIFT_CHAR_OUT_OF_RANGE`;
Message: Shift character out of range: %s.
- Error number: 89; Symbol: `EE_RESET_CHAR_OUT_OF_RANGE`;
Message: Reset character out of range: %s.
- Error number: 90; Symbol: `EE_UNKNOWN_LDML_TAG`;
Message: Unknown LDML tag: '%.*s'.
- Error number: 91; Symbol: `EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a secondary ignorable character %s.
- Error number: 92; Symbol: `EE_FAILED_PROCESSING_DIRECTIVE`;
Message: Stopped processing the '%s' directive in file %s at line %d.
- Error number: 93; Symbol: `EE_PTHREAD_KILL_FAILED`;

Message: pthread_kill(thread_id:%lu, signal:%s) returned '%S'.

- Error number: 94; Symbol: EE_COLLATION_ALIAS_ERROR;

Message: %s.

Index

C

- CR_ALREADY_CONNECTED error code, 433
- CR_AUTH_PLUGIN_CANNOT_LOAD error code, 433
- CR_AUTH_PLUGIN_ERR error code, 433
- CR_CANT_GET_SESSION_DATA error code, 434
- CR_CANT_READ_CHARSET error code, 430
- CR_COMMANDS_OUT_OF_SYNC error code, 430
- CR_COMPRESSION_WRONGLY_CONFIGURED error code, 433
- CR_CONNECTION_ERROR error code, 429
- CR_CONN_HOST_ERROR error code, 429
- CR_CONN_UNKNOW_PROTOCOL error code, 432
- CR_DATA_TRUNCATED error code, 431
- CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED error code, 433
- CR_DNS_SRV_LOOKUP_FAILED error code, 433
- CR_DUPLICATE_CONNECTION_ATTR error code, 433
- CR_EMBEDDED_CONNECTION error code, 430
- CR_FETCH_CANCELED error code, 432
- CR_FILE_NAME_TOO_LONG error code, 433
- CR_INSECURE_API_ERR error code, 433
- CR_INVALID_BUFFER_USE error code, 431
- CR_INVALID_CLIENT_CHARSET error code, 434
- CR_INVALID_CONN_HANDLE error code, 432
- CR_INVALID_FACTOR_NO error code, 434
- CR_INVALID_PARAMETER_NO error code, 431
- CR_IPSOCK_ERROR error code, 429
- CR_KERBEROS_USER_NOT_FOUND error code, 433
- CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL error code, 433
- CR_LOAD_DATA_LOCAL_INFILE_REJECTED error code, 433
- CR_LOCALHOST_CONNECTION error code, 429
- CR_MALFORMED_PACKET error code, 431
- CR_MANDATORY_TRACKER_NOT_FOUND error code, 434
- CR_NAMEDPIPEOPEN_ERROR error code, 430
- CR_NAMEDPIPESETSTATE_ERROR error code, 430
- CR_NAMEDPIPEWAIT_ERROR error code, 430
- CR_NAMEDPIPE_CONNECTION error code, 430
- CR_NET_PACKET_TOO_LARGE error code, 430
- CR_NEW_STMT_METADATA error code, 433
- CR_NOT_IMPLEMENTED error code, 432
- CR_NO_DATA error code, 432
- CR_NO_PARAMETERS_EXISTS error code, 431
- CR_NO_PREPARE_STMT error code, 431
- CR_NO_RESULT_SET error code, 432
- CR_NO_STMT_METADATA error code, 432
- CR_NULL_POINTER error code, 431
- CR_OUT_OF_MEMORY error code, 429
- CR_PARAMS_NOT_BOUND error code, 431
- CR_PROBE_REPLICA_CONNECT error code, 430
- CR_PROBE_REPLICA_HOSTS error code, 430
- CR_PROBE_REPLICA_STATUS error code, 430
- CR_PROBE_SOURCE_CONNECT error code, 430
- CR_SERVER_GONE_ERROR error code, 429
- CR_SERVER_HANDSHAKE_ERR error code, 430
- CR_SERVER_LOST error code, 430
- CR_SERVER_LOST_EXTENDED error code, 432
- CR_SHARED_MEMORY_CONNECTION error code, 431
- CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR error code, 432
- CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR error code, 431
- CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR error code, 432
- CR_SHARED_MEMORY_CONNECT_MAP_ERROR error code, 432
- CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR error code, 431
- CR_SHARED_MEMORY_CONNECT_SET_ERROR error code, 432
- CR_SHARED_MEMORY_EVENT_ERROR error code, 432
- CR_SHARED_MEMORY_FILE_MAP_ERROR error code, 432
- CR_SHARED_MEMORY_MAP_ERROR error code, 432
- CR_SOCKET_CREATE_ERROR error code, 429
- CR_SSL_CONNECTION_ERROR error code, 431
- CR_SSL_FIPS_MODE_ERR error code, 433
- CR_STMT_CLOSED error code, 433
- CR_TCP_CONNECTION error code, 430
- CR_TLS_SERVER_NOT_FOUND error code, 434
- CR_UNKNOWN_ERROR error code, 429
- CR_UNKNOWN_HOST error code, 429
- CR_UNSUPPORTED_PARAM_TYPE error code, 431
- CR_UNUSED_1 error code, 432
- CR_VERSION_ERROR error code, 429
- CR_WRONG_HOST_INFO error code, 429
- CR_WRONG_LICENSE error code, 431

E

- EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION error code, 440
- EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION error code, 440
- EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION error code, 440
- EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION error code, 440
- EE_BADCLOSE error code, 435
- EE_CANTCREATEFILE error code, 435
- EE_CANTLOCK error code, 435
- EE_CANTUNLOCK error code, 435
- EE_CANT_CHSIZE error code, 436
- EE_CANT_MKDIR error code, 436
- EE_CANT_OPEN_STREAM error code, 436
- EE_CANT_READLINK error code, 436
- EE_CANT_SEEK error code, 437

EE_CANT_SYMLINK error code, 436	EE_INCORRECT_INT_VALUE_FOR_OPTION error code, 440
EE_CAPACITY_EXCEEDED error code, 437	EE_INCORRECT_UINT_VALUE_FOR_OPTION error code, 440
EE_CHANGE_OWNERSHIP error code, 437	EE_INVALID_DECIMAL_VALUE_FOR_OPTION error code, 440
EE_CHANGE_PERMISSIONS error code, 437	EE_LINK error code, 435
EE_COLLATION_ALIAS_ERROR error code, 441	EE_LINK_WARNING error code, 436
EE_COLLATION_PARSER_ERROR error code, 440	EE_NET_SEND_ERROR_IN_BOOTSTRAP error code, 439
EE_CONFIG_FILE_PERMISSION_ERROR error code, 438	EE_OPEN_WARNING error code, 436
EE_DEBUG_INFO error code, 439	EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE error code, 439
EE_DELETE error code, 435	EE_OPTION_REQUIRES_ARGUMENT error code, 439
EE_DIR error code, 435	EE_OPTION_WITHOUT_ARGUMENT error code, 439
EE_DISK_FULL error code, 436	EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE error code, 438
EE_DISK_FULL_WITH_RETRY_MSG error code, 437	EE_OPTION_WITH_EMPTY_VALUE error code, 439
EE_EOFERR error code, 435	EE_OUTOFMEMORY error code, 435
EE_EXITING_TIMER_NOTIFY_THREAD error code, 437	EE_OUT_OF_FILE_RESOURCES error code, 436
EE_FAILED_PROCESSING_DIRECTIVE error code, 440	EE_PACKETS_OUT_OF_ORDER error code, 439
EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION error code, 439	EE_PTHREAD_KILL_FAILED error code, 441
EE_FAILED_TO_CREATE_IO_COMPLETION_PORT error code, 438	EE_READ error code, 435
EE_FAILED_TO_CREATE_TIMER error code, 437	EE_REALPATH error code, 436
EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD error code, 437	EE_RESET_CHAR_OUT_OF_RANGE error code, 440
EE_FAILED_TO_CREATE_TIMER_QUEUE error code, 437	EE_SETWD error code, 436
EE_FAILED_TO_DELETE_TIMER error code, 437	EE_SHIFT_CHAR_OUT_OF_RANGE error code, 440
EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE error code, 437	EE_SHORT_OPTION_REQUIRES_ARGUMENT error code, 439
EE_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 438	EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION error code, 438
EE_FAILED_TO_KILL_ALL_THREADS error code, 438	EE_SSL_ERROR error code, 438
EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY error code, 439	EE_SSL_ERROR_FROM_FILE error code, 438
EE_FAILED_TO_OPEN_DEFAULTS_FILE error code, 438	EE_STAT error code, 436
EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNORED error code, 440	EE_SYNC error code, 436
EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNORED error code, 440	EE_UNKNOWN_CHARSET error code, 436
EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNORED error code, 440	EE_UNKNOWN_COLLATION error code, 436
EE_FAILED_TO_SET_OPTION_VALUE error code, 440	EE_UNKNOWN_LDML_TAG error code, 440
EE_FAILED_TO_START_TIMER_NOTIFY_THREAD error code, 437	EE_UNKNOWN_OPTION error code, 439
EE_FILENOTFOUND error code, 437	EE_UNKNOWN_PROTOCOL_OPTION error code, 439
EE_FILE_NOT_CLOSED error code, 437	EE_UNKNOWN_SHORT_OPTION error code, 439
EE_GETWD error code, 436	EE_UNKNOWN_SUFFIX_FOR_VARIABLE error code, 438
EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE error code, 438	EE_UNKNOWN_VARIABLE error code, 439
EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION error code, 439	EE_USING_DISABLED_OPTION error code, 438
EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE error code, 438	EE_USING_DISABLED_SHORT_OPTION error code, 438
	EE_USING_PASSWORD_ON_CLI_IS_INSECURE error code, 438
	EE_WIN_LIBRARY_LOAD_FAILED error code, 437
	EE_WIN_RUN_TIME_ERROR_CHECK error code, 437
	EE_WRITE error code, 435

EE_WRONG_DIRECTIVE_IN_CONFIG_FILE error
code, 438
error code

CR_ALREADY_CONNECTED, 433
CR_AUTH_PLUGIN_CANNOT_LOAD, 433
CR_AUTH_PLUGIN_ERR, 433
CR_CANT_GET_SESSION_DATA, 434
CR_CANT_READ_CHARSET, 430
CR_COMMANDS_OUT_OF_SYNC, 430
CR_COMPRESSION_WRONGLY_CONFIGURED,
433
CR_CONNECTION_ERROR, 429
CR_CONN_HOST_ERROR, 429
CR_CONN_UNKNOW_PROTOCOL, 432
CR_DATA_TRUNCATED, 431
CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED,
433
CR_DNS_SRV_LOOKUP_FAILED, 433
CR_DUPLICATE_CONNECTION_ATTR, 433
CR_EMBEDDED_CONNECTION, 430
CR_FETCH_CANCELED, 432
CR_FILE_NAME_TOO_LONG, 433
CR_INSECURE_API_ERR, 433
CR_INVALID_BUFFER_USE, 431
CR_INVALID_CLIENT_CHARSET, 434
CR_INVALID_CONN_HANDLE, 432
CR_INVALID_FACTOR_NO, 434
CR_INVALID_PARAMETER_NO, 431
CR_IPSOCK_ERROR, 429
CR_KERBEROS_USER_NOT_FOUND, 433
CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL,
433
CR_LOAD_DATA_LOCAL_INFILE_REJECTED,
433
CR_LOCALHOST_CONNECTION, 429
CR_MALFORMED_PACKET, 431
CR_MANDATORY_TRACKER_NOT_FOUND, 434
CR_NAMEDPIPEOPEN_ERROR, 430
CR_NAMEDPIPESETSTATE_ERROR, 430
CR_NAMEDPIPEWAIT_ERROR, 430
CR_NAMEDPIPE_CONNECTION, 430
CR_NET_PACKET_TOO_LARGE, 430
CR_NEW_STMT_METADATA, 433
CR_NOT_IMPLEMENTED, 432
CR_NO_DATA, 432
CR_NO_PARAMETERS_EXISTS, 431
CR_NO_PREPARE_STMT, 431
CR_NO_RESULT_SET, 432
CR_NO_STMT_METADATA, 432
CR_NULL_POINTER, 431
CR_OUT_OF_MEMORY, 429
CR_PARAMS_NOT_BOUND, 431
CR_PROBE_REPLICA_CONNECT, 430
CR_PROBE_REPLICA_HOSTS, 430
CR_PROBE_REPLICA_STATUS, 430
CR_PROBE_SOURCE_CONNECT, 430
CR_SERVER_GONE_ERROR, 429
CR_SERVER_HANDSHAKE_ERR, 430

CR_SERVER_LOST, 430
CR_SERVER_LOST_EXTENDED, 432
CR_SHARED_MEMORY_CONNECTION, 431
CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR,
432
CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR,
431
CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR,
432
CR_SHARED_MEMORY_CONNECT_MAP_ERROR,
432
CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR,
431
CR_SHARED_MEMORY_CONNECT_SET_ERROR,
432
CR_SHARED_MEMORY_EVENT_ERROR, 432
CR_SHARED_MEMORY_FILE_MAP_ERROR, 432
CR_SHARED_MEMORY_MAP_ERROR, 432
CR_SOCKET_CREATE_ERROR, 429
CR_SSL_CONNECTION_ERROR, 431
CR_SSL_FIPS_MODE_ERR, 433
CR_STMT_CLOSED, 433
CR_TCP_CONNECTION, 430
CR_TLS_SERVER_NOT_FOUND, 434
CR_UNKNOWN_ERROR, 429
CR_UNKNOWN_HOST, 429
CR_UNSUPPORTED_PARAM_TYPE, 431
CR_UNUSED_1, 432
CR_VERSION_ERROR, 429
CR_WRONG_HOST_INFO, 429
CR_WRONG_LICENSE, 431
EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION,
440
EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION,
440
EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION,
440
EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION,
440
EE_BADCLOSE, 435
EE_CANTCREATEFILE, 435
EE_CANTLOCK, 435
EE_CANTUNLOCK, 435
EE_CANT_CHSIZE, 436
EE_CANT_MKDIR, 436
EE_CANT_OPEN_STREAM, 436
EE_CANT_READLINK, 436
EE_CANT_SEEK, 437
EE_CANT_SYMLINK, 436
EE_CAPACITY_EXCEEDED, 437
EE_CHANGE_OWNERSHIP, 437
EE_CHANGE_PERMISSIONS, 437
EE_COLLATION_ALIAS_ERROR, 441
EE_COLLATION_PARSER_ERROR, 440
EE_CONFIG_FILE_PERMISSION_ERROR, 438
EE_DEBUG_INFO, 439
EE_DELETE, 435
EE_DIR, 435

EE_DISK_FULL, 436	EE_PTHREAD_KILL_FAILED, 441
EE_DISK_FULL_WITH_RETRY_MSG, 437	EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT, 439
EE_EOFERR, 435	EE_READ, 435
EE_EXITING_TIMER_NOTIFY_THREAD, 437	EE_REALPATH, 436
EE_FAILED_PROCESSING_DIRECTIVE, 440	EE_RESET_CHAR_OUT_OF_RANGE, 440
EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION, 439	EE_SETWD, 436
EE_FAILED_TO_CREATE_IO_COMPLETION_PORT, 438	EE_SHIFT_CHAR_OUT_OF_RANGE, 440
EE_FAILED_TO_CREATE_TIMER, 437	EE_SHORT_OPTION_REQUIRES_ARGUMENT, 439
EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT, 437	EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION, 439
EE_FAILED_TO_CREATE_TIMER_QUEUE, 437	EE_SSL_ERROR, 438
EE_FAILED_TO_DELETE_TIMER, 437	EE_SSL_ERROR_FROM_FILE, 438
EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE, 437	EE_STAT, 436
EE_FAILED_TO_HANDLE_DEFAULTS_FILE, 438	EE_SYNC, 436
EE_FAILED_TO_KILL_ALL_THREADS, 438	EE_UNKNOWN_CHARSET, 436
EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY, 439	EE_UNKNOWN_COLLATION, 436
EE_FAILED_TO_OPEN_DEFAULTS_FILE, 438	EE_UNKNOWN_LDML_TAG, 440
EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNORED_CHAR, 440	EE_UNKNOWN_OPTION, 439
EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNORED_CHAR, 440	EE_UNKNOWN_PROTOCOL_OPTION, 439
EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNORED_CHAR, 440	EE_UNKNOWN_SHORT_OPTION, 439
EE_FAILED_TO_SET_OPTION_VALUE, 440	EE_UNKNOWN_SUFFIX_FOR_VARIABLE, 438
EE_FAILED_TO_START_TIMER_NOTIFY_THREAD, 437	EE_UNKNOWN_VARIABLE, 439
EE_FILENOTFOUND, 437	EE_USING_DISABLED_OPTION, 438
EE_FILE_NOT_CLOSED, 437	EE_USING_DISABLED_SHORT_OPTION, 438
EE_GETWD, 436	EE_USING_PASSWORD_ON_CLI_IS_INSECURE, 438
EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE, 438	EE_WIN_LIBRARY_LOAD_FAILED, 437
EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION, 439	EE_WIN_RUN_TIME_ERROR_CHECK, 437
EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE, 438	EE_WRITE, 435
EE_INCORRECT_INT_VALUE_FOR_OPTION, 440	EE_WRONG_DIRECTIVE_IN_CONFIG_FILE, 438
EE_INCORRECT_UINT_VALUE_FOR_OPTION, 440	ER_ABORTING, 148
EE_INVALID_DECIMAL_VALUE_FOR_OPTION, 440	ER_ABORTING_CONNECTION, 13
EE_LINK, 435	ER_ABORTING_USER_CONNECTION, 192
EE_LINK_WARNING, 436	ER_ACCESS_DENIED_CHANGE_USER_ERROR, 56
EE_NET_SEND_ERROR_IN_BOOTSTRAP, 439	ER_ACCESS_DENIED_ERROR, 6
EE_OPEN_WARNING, 436	ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD, 193
EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE, 439	ER_ACCESS_DENIED_ERROR_WITH_PASSWORD, 193
EE_OPTION_REQUIRES_ARGUMENT, 439	ER_ACCESS_DENIED_FIREWALL, 133
EE_OPTION_WITHOUT_ARGUMENT, 439	ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_IP, 360
EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE, 438	ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED, 193
EE_OPTION_WITH_EMPTY_VALUE, 439	ER_ACCESS_DENIED_NO_PASSWORD_ERROR, 44
EE_OUTOFMEMORY, 435	ER_ACCESS_DENIED_NO_PROXY, 129
EE_OUT_OF_FILERESOURCES, 436	ER_ACCESS_DENIED_NO_PROXY_GRANT, 129
EE_PACKETS_OUT_OF_ORDER, 439	ER_ACCESS_DENIED_NO_PROXY_GRANT_WITH_NAME, 415
	ER_ACCESS_DENIED_NO_PROXY_WITH_NAME, 415
	ER_ACCOUNT_HAS_BEEN_LOCKED, 65
	ER_ACCOUNT_WITH_EXPIRED_PASSWORD, 386
	ER_ACL_OPERATION_FAILED, 72

ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG, 354	ER_APPLIER_LOG_EVENT_VALIDATION_ERROR, 81
ER_ADDRESSES_FOR_HOSTNAME_HEADER, 144	ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS, 109
ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM, 144	ER_ATTRIBUTE_IGNORED, 82
ER_ADD_PARTITION_NO_NEW_PARTITION, 34	ER_AUDIT_API_ABORT, 69
ER_ADD_PARTITION_SUBPART_ERROR, 34	ER_AUDIT_CANT_ABORT_COMMAND, 191
ER_ADMIN_WRONG_MRG_TABLE, 31	ER_AUDIT_CANT_ABORT_EVENT, 191
ER_AES_INVALID_IV, 56	ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD, 358
ER_AES_INVALID_KDF_ITERATIONS, 71	ER_AUDIT_LOG_CANNOT_READ_PASSWORD, 354
ER_AES_INVALID_KDF_NAME, 71	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 354
ER_AES_INVALID_KDF_OPTION_SIZE, 72	ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER, 212
ER_AGGREGATE_IN_ORDER_NOT_SELECT, 61	ER_AUDIT_LOG_CANNOT_STORE_PASSWORD, 354
ER_AGGREGATE_ORDER_FOR_UNION, 59	ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER, 212
ER_AGGREGATE_ORDER_NON_AGG_QUERY, 59	ER_AUDIT_LOG_CANNOT_STORE_PASSWORD, 354
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED, 103	ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY, 335
ER_ALTER_FILEGROUP_FAILED, 35	ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING, 354
ER_ALTER_INFO, 8	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE, 213
ER_ALTER_OPERATION_NOT_SUPPORTED, 54	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION, 213
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 54	ER_CHANGE_EC_EC_WRITER_FAILED_TO_INIT_ENCRYPTION, 213
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 55	ER_COLUMN_ENCRYPTION_PASSWORD_CANNOT_BE_EMPTY, 335
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 54	ER_COLUMN_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_INSTALLED, 335
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 114	ER_COPY_AUDIT_LOG_FILE_AUTO_PRUNED, 373
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 54	ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PRUNED, 354
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 54	ER_CHECK, 358
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 54	ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED, 358
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 54	ER_RENAME, 358
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 55	ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING, 358
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 61	ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING, 358
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 55	ER_AUDIT_LOG_FILE_PRUNE_FAILED, 373
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 55	ER_IDENT_FILTER_FAILED_TO_CLOSE_TABLE_AFTER, 214
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 54	ER_IDENT_FILTER_FAILED_TO_DELETE_FROM_TABLE, 214
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 55	ER_IDENT_FILTER_FAILED_TO_INIT_TABLE_FOR_PARTITION, 214
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 54	ER_IDENT_FILTER_FAILED_TO_INSERT_INTO_TABLE, 214
ER_AMBIGUOUS_FIELD_TERM, 31	ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE, 214
ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_ROLES, 196	ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FILTER, 214
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP, 109	ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE, 214
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW, 111	ER_CHANGE_UUID, 214
	ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE, 214

ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED,	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH,
212	357
ER_AUDIT_LOG_FILTER_RESULT_MSG,	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH,
213	BE_EMPTY,
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT,	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALP
214	336
ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED,	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER,
357	335
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER,	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS,
335	213
ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR,	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE,
213	213
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE,	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED,
101	213
ER_AUDIT_LOG_INVALID_FILE_CONTENT,	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED,
354	213
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE,	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE,
401	213
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED,	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EV
335	EMPTY,
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST,	ER_AUDIT_PLUGIN_HAS_INVALID_DATA,
336	164
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE,	ER_AUDIT_WARNING,
335	191
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR,	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM,
334	162
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL,	ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TAE
213	162,
ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN,	ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WIL
214	161
ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE,	ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME,
213	161,
ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR,	ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE,
214	161,
ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE,	ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAM
336	INVALID,
ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS,	ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZ
353	366
ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED,	ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED,
335	161
ER_AUDIT_LOG_OFFLOAD_ERROR,	ER_AUTHCACHE_PLUGIN_CONFIG,
425	160
ER_AUDIT_LOG_OFFLOAD_INFO,	ER_AUTHCACHE_PLUGIN_MISSING,
425	160
ER_AUDIT_LOG_OFFLOAD_WARNING,	ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_RO
425	162
ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED,	ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLV
212	162
ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED,	ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOL
354	160
ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH,	ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME,
213	366
ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED,	ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATIO
356	366
ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST,	ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLV
212	162
ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED,	ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING,
336	161
ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE,	ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWO
335	161
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT,	ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD,
357	161
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE,	
357	

ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN,	ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED
161	381
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE,	ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFF
160	382
ER_AUTHCACHE_USER_TABLE_DODGY,	ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT,
161	382
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY,	ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FA
400	382
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY,	ER_AUTHENTICATION_POLICY_MISMATCH,
382	112
ER_AUTHENTICATION_OCI_IAM,	ER_AUTH_CANT_ACTIVATE_ROLE,
383	159
ER_AUTHENTICATION_OCI_IMDS,	ER_AUTH_CANT_CREATE_RSA_PAIR,
382	159
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_TOKEN,	ER_AUTH_CANT_WRITE_PRIVKEY,
383	160
ER_AUTHENTICATION_OCI_INVALID_TOKEN,	ER_AUTH_CANT_WRITE_PUBKEY,
400	160
ER_AUTHENTICATION_OCI_NONCE,	ER_AUTH_CERTS_SAVED_TO_DATADIR,
383	160
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND,	ER_AUTH_CERT_GENERATION_DISABLED,
383	160
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS,	ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATC
383	349
ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED,	ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG,
382	378
ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR,	ER_AUTH_KEYS_SAVED_TO_DATADIR,
382	160
ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH,	ER_AUTH_KEY_GENERATION_DISABLED,
400	160
ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED,	ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT
400	160
ER_AUTHENTICATION_OPENID_CONFIGURATION_NOT_FOUND,	ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG,
416	206
ER_AUTHENTICATION_OPENID_FAILED_TO_UPDATE_CONFIGURATION,	ER_AUTH_RSA_CANT_FIND,
417	158
ER_AUTHENTICATION_OPENID_INSECURE_CONNECTION,	ER_AUTH_RSA_CANT_PARSE,
416	159
ER_AUTHENTICATION_OPENID_INVALID_CONFIGURATION,	ER_AUTH_RSA_CANT_READ,
416	159
ER_AUTHENTICATION_OPENID_INVALID_IDENTITY_PROVIDER,	ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION,
416	160
ER_AUTHENTICATION_OPENID_INVALID_TOKEN,	ER_AUTH_RSA_CONF_FILES_NOT_FOUND,
416	159
ER_AUTHENTICATION_OPENID_INVALID_TOKEN_SIZE,	ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION,
416	160
ER_AUTHENTICATION_OPENID_ISSUER_MISMATCH,	ER_AUTH_USING_EXISTING_CERTS,
416	160
ER_AUTHENTICATION_OPENID_OPTION_DEREGISTERED,	ER_AUTH_AUTOINC_READ_FAILED,
420	31
ER_AUTHENTICATION_OPENID_OPTION_REGISTER,	ER_AUTOPILOT_OLTP_ADVISOR_ERROR,
419	428
ER_AUTHENTICATION_OPENID_READ_PACKET,	ER_AUTOPILOT_OLTP_ADVISOR_INFO,
416	428
ER_AUTHENTICATION_OPENID_TOKEN_NOT_VERIFIED,	ER_AUTOPILOT_OLTP_ADVISOR_WARNING,
416	428
ER_AUTHENTICATION_OPENID_USER_MISMATCH,	ER_AUTO_CONVERT,
416	18
ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT,	ER_AUTO_INCREMENT_CONFLICT,
382	55
ER_AUTHENTICATION_PLUGIN_LOG,	ER_AUTO_INCREMENT_NOT_SUPPORTED_FOR_FLOAT
382	413
ER_AUTHENTICATION_PLUGIN_OOM,	ER_AUTO_OPTIONS_FAILED,
382	152
	ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OF
	49
	ER_BACKGROUND_HISTOGRAM_UPDATE,
	413
	ER_BACK_IN_TIME,
	147
	ER_BAD_DB_ERROR,
	6
	ER_BAD_FIELD_ERROR,
	6
	ER_BAD_FT_COLUMN,
	20
	ER_BAD_HOST_ERROR,
	5
	ER_BAD_LOG_STATEMENT,
	37
	ER_BAD_NULL_ERROR,
	6
	ER_BAD_NULL_ERROR_NOT_IGNORED,
	83
	ER_BAD_REPLICA,
	15
	ER_BAD_REPLICA_AUTO_POSITION,
	49
	ER_BAD_REPLICA_UNTIL_COND,
	20
	ER_BAD_TABLE_ERROR,
	6

ER_BAD_TIMESTAMP_FORMAT, 117	ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA, 186
ER_BASE64_DECODE_ERROR, 37	ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO, 186
ER_BASEDIR_SET_TO, 195	ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED, 195
ER_BEFORE_DML_VALIDATION_ERROR, 64	ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING, 186
ER_BEG_INITFILE, 149	ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING, 186
ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD, 402	ER_BINLOG_FAILED_TO_DELETE_LOG_FILE, 188
ER_BEYOND_SERVER_UPGRADE_THRESHOLD, 402	ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING, 186
ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX, 47	ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE, 188
ER_BINLOG_CACHE_SIZE_TOO_LARGE, 192	ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE, 187
ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX, 187	ER_BINLOG_FAILED_TO_READ_REGISTER_FILE, 188
ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG, 189	ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE, 186
ER_BINLOG_CANT_CLOSE_TMP_INDEX, 187	ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING, 186
ER_BINLOG_CANT_COPY_INDEX_TO_TMP, 187	ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK, 189
ER_BINLOG_CANT_DELETE_FILE, 187	ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK, 189
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG, 188	ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME, 188
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES, 188	ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE, 186
ER_BINLOG_CANT_FIND_LOG_IN_INDEX, 188	ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN, 186
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME, 186	ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES, 180
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES, 187	ER_BINLOG_FATAL_ERROR, 38
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX, 187	ER_BINLOG_FILE_BEING_READ_NOT_PURGED, 185
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG, 189	ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED, 185
ER_BINLOG_CANT_OPEN_FOR_LOGGING, 185	ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW, 185
ER_BINLOG_CANT_OPEN_TMP_INDEX, 187	ER_BINLOG_FILE_NAME_TOO_LONG, 185
ER_BINLOG_CANT_RESIZE_CACHE, 185	ER_BINLOG_FILE_OPEN_FAILED, 195
ER_BINLOG_CANT_SET_TMP_INDEX_NAME, 187	ER_BINLOG_IO_ERROR_READING_HEADER, 185
ER_BINLOG_CANT_TRIM_CRASHED_BINLOG, 189	ER_BINLOG_LOGGING_IMPOSSIBLE, 38
ER_BINLOG_CANT_USE_FOR_LOGGING, 186	ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS, 188
ER_BINLOG_CRASHED_BINLOG_TRIMMED, 189	ER_BINLOG_LOGGING_NOT_POSSIBLE, 204
ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED, 391	ER_BINLOG_LOGICAL_CORRUPTION, 55
ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS, 391	ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG, 204
ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED, 391	ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION, 93
ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG, 390	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP, 94
ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED, 391	
ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED, 391	
ER_BINLOG_CREATE_ROUTINE_NEED_SUPER, 28	
ER_BINLOG_END, 148	
ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG, 186	
ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG, 186	

ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS, 94	ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT, 45
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPEN_BINLOG, 93	ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT, 45
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_READ_BINLOG, 93	ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC, 46
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_BINLOG, 93	ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBS, 353
ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE, 42	ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN, 57
ER_BINLOG_NEEDS_SERVERID, 151	ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT, 45
ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_BINLOG, 180	ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE, 45
ER_BINLOG_PURGE_EMFILE, 37	ER_BINLOG_UNSAFE_INSERT_TWO_KEYS, 46
ER_BINLOG_PURGE_FATAL_ERR, 26	ER_BINLOG_UNSAFE_LIMIT, 42
ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_FOUND, 187	ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT, 192
ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTERED_FILE, 187	ER_BINLOG_UNSAFE_MIXED_STATEMENT, 44
ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTERED_FILE, 187	ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE, 42
ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE, 187	ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS, 42
ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE, 188	ER_BINLOG_UNSAFE_NOWAIT, 76
ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG, 188	ER_BINLOG_UNSAFE_REPLACE_SELECT, 45
ER_BINLOG_PURGE_PROHIBITED, 26	ER_BINLOG_UNSAFE_ROUTINE, 28
ER_BINLOG_RECOVERING_AFTER_CRASH_USING, 188	ER_BINLOG_UNSAFE_SKIP_LOCKED, 76
ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE, 41	ER_BINLOG_UNSAFE_STATEMENT, 38
ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE, 42	ER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 42
ER_BINLOG_ROW_INJECTION_AND_STMT_MODE, 42	ER_BINLOG_UNSAFE_SYSTEM_TABLE, 42
ER_BINLOG_ROW_LOGGING_FAILED, 35	ER_BINLOG_UNSAFE_SYSTEM_VARIABLE, 42
ER_BINLOG_ROW_MODE_AND_STMT_ENGINE, 41	ER_BINLOG_UNSAFE_UDF, 42
ER_BINLOG_ROW_VALUE_OPTION_IGNORED, 331	ER_BINLOG_UNSAFE_UPDATE_IGNORE, 45
ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFFIXED_COLUMNS, 331	ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT, 46
ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX, 47	ER_BINLOG_UNSAFE_XA, 71
ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE, 192	ER_BINLOG_WARNING_SUPPRESSED, 189
ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES, 54	ER_BLOBS_AND_NO_TERMINATED, 8
ER_BINLOG_STMT_MODE_AND_ROW_ENGINE, 42	ER_BLOB_CANT_HAVE_DEFAULT, 9
ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READ_ONLY, 352	ER_BLOB_FIELD_IN_PART_FUNC_ERROR, 33
ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_EXECUTION, 108	ER_BLOB_KEY_WITHOUT_LENGTH, 14
ER_BINLOG_UNSAFE_AND_STMT_ENGINE, 41	ER_BLOB_USED_AS_KEY, 8
ER_BINLOG_UNSAFE_AUTOINC_COLUMNS, 42	ER_BLOB_USED_AS_KEY, 8
ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST, 46	ER_BOOST_GEOMETRY_CENTROID_EXCEPTION, 60
	ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION, 60
	ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION, 66
	ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION, 60
	ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION, 60
	ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION, 60
	ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION, 60
	ER_BOOTSTRAP_CANT_THREAD, 140
	ER_BUFPOOL_RESIZE_INPROGRESS, 69

ER_BUILD_ID, 392	ER_BULK_PARSER_UNEXPECTED_ENCLOSED_BY_CHARACT
ER_BULK_BLOB_TOO_BIG, 131	420
ER_BULK_EXECUTOR_ERROR, 118	ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT,
ER_BULK_EXECUTOR_INFO, 395	119
ER_BULK_JSON_INVALID, 131	ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG,
ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER_BUFFER,	495
119	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR,
ER_BULK_LOADER_COMPONENT_ERROR, 119	119
ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_ESCAPE_SEQUENCE,	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG,
119	396
ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_ESCAPE_SEQUENCE,	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG,
395	118
ER_BULK_LOADER_INFO, 395	ER_BULK_READER_COMMUNICATION_ERROR,
ER_BULK_LOAD_DATA_FAILED, 118	395
ER_BULK_LOAD_RESOURCE, 123	ER_BULK_READER_COMMUNICATION_ERROR_LOG,
ER_BULK_LOAD_SECONDARY_ENGINE, 123	123
ER_BULK_LOAD_TABLE_HAS_INSTANT_COLS,	ER_BULK_READER_COULDNT_RESOLVE_HOST,
123	123
ER_BULK_MERGE_INVALID_CHUNK, 122	ER_BULK_READER_ERROR, 123
ER_BULK_MERGE_LOADER_INFO, 406	ER_BULK_READER_FILE_DOESNT_EXIST, 123
ER_BULK_MERGE_NOT_ALL_CHUNKS_CONSUMED,	ER_BULK_READER_INFO, 395
122	ER_BULK_READER_LIBCURL_ERROR, 118
ER_BULK_MULTI_READER_INFO, 406	ER_BULK_READER_LIBCURL_ERROR_LOG, 395
ER_BULK_MULTI_READER_OPEN_FILE_FAILED,	ER_BULK_READER_LIBCURL_INIT_FAILED, 118
122	ER_BULK_READER_LIBCURL_INIT_FAILED_LOG,
ER_BULK_MULTI_READER_READ_FILE_FAILED,	395
122	ER_BULK_READER_OPEN_FILE_FAILED, 123
ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED,	ER_BULK_READER_SERVER_ERROR, 118
119	ER_BULK_READER_SERVER_ERROR_LOG, 395
ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED,	ER_BULK_READER_ZSTD_ERROR, 130
395	ER_BULK_READER_ZSTD_ERROR_LOG, 415
ER_BULK_PARSER_ERROR, 130	ER_BULK_SCANNER_INFO, 415
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE,	ER_BULK_SORTING_LOADER_INFO, 406
119	ER_BULK_SORTING_LOADER_WAIT, 123
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE,	ER_BULK_SORTING_LOADER_WRITE, 123
396	ER_BULK_WRITER_INFO, 406
ER_BULK_PARSER_MISSING_ENCLOSED_BY,	ER_BULK_WRITER_LIBCURL_ERROR, 123
119	ER_BULK_WRITER_LIBCURL_ERROR_LOG, 406
ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG,	ER_BULK_WRITER_LIBCURL_INIT_FAILED, 122
395	ER_BULK_WRITER_LIBCURL_INIT_FAILED_LOG,
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED,	406
119	ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_US
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED,	34
395	ER_CALL_ME_LOCALHOST, 148
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR,	ER_CANT_CREATE FOREIGN, 16
119	ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED,
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR,	119
396	ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL,
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_END_OF_FILE,	60
119	ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL_LOG,
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_END_OF_FILE,	195
396	ER_CANNOT_CONVERT_STRING, 97
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_END_OF_FILE,	ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT,
119	69
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE,	ER_CANNOT_DISCARD_TEMPORARY_TABLE,
396	57
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE,	ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX,
119	89
ER_BULK_PARSER_UNEXPECTED_ENCLOSED_BY_CHARACTER,	ER_CANNOT_EXECUTE_IN_PRIMARY, 123
132	ER_CANNOT_FIND_KEY_IN_KEYRING, 70

ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE, 346	ER_CANT_CREATE_SCHEDULER_THREAD, 143
ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER, 98	ER_CANT_CREATE_SHM_THREAD, 147
ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_USER, 100	ER_CANT_CREATE_SHUTDOWN_THREAD, 146
ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES, 385	ER_CANT_CREATE_TABLE, 3
ER_CANNOT_LOAD_FROM_TABLE_V2, 46	ER_CANT_CREATE_TABLE_SHARE_FROM_FRM, 182
ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES, 75	ER_CANT_CREATE_TCPIP_THREAD, 147
ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_ERROR, 63	ER_CANT_CREATE_TEST_FILE, 146
ER_CANNOT_PERSIST_SENSITIVE_VARIABLES, 116	ER_CANT_CREATE_THREAD, 12
ER_CANNOT_PERSIST_TRANSACTION_ISOLATION, 133	ER_CANT_CREATE_USER_WITH_GRANT, 27
ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK, 115	ER_CANT_CREATE_UUID, 145
ER_CANNOT_SET_DATABASE_ENCRYPTION, 95	ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN, 171
ER_CANNOT_SET_LOG_ERROR_SERVICES, 195	ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID, 49
ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE, 346	ER_CANT_DO_THIS_DURING_AN_TRANSACTION, 14
ER_CANNOT_SET_TABLESPACE_ENCRYPTION, 95	ER_CANT_DROP_FIELD_OR_KEY, 9
ER_CANNOT_SET_TABLE_ENCRYPTION, 95	ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING, 65
ER_CANNOT_USER, 27	ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID, 15
ER_CANNOT_USER_REFERENCED_AS_DEFINER, 108	ER_CANT_FIND_DL_ENTRY, 11
ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE, 110	ER_CANT_FIND_SYSTEM_REC, 4
ER_CANNOT_USE_ENCRYPTION_CLAUSE, 95	ER_CANT_FIND_UDF, 11
ER_CANT_ACCESS_CAPATH, 152	ER_CANT_GET_STAT, 4
ER_CANT_AGGREGATE_2COLLATIONS, 19	ER_CANT_HASH_DO_AND_IGNORE_RULES, 152
ER_CANT_AGGREGATE_3COLLATIONS, 20	ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT, 183
ER_CANT_AGGREGATE_NCOLLATIONS, 20	ER_CANT_INCREASE_MAX_OPEN_FILES, 149
ER_CANT_ALLOC_TABLE_OBJECT, 182	ER_CANT_INITIALIZE_BUILTIN_PLUGINS, 151
ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE, 120	ER_CANT_INITIALIZE_DYNAMIC_PLUGINS, 151
ER_CANT_CHANGE_TX_CHARACTERISTICS, 36	ER_CANT_INITIALIZE_EARLY_PLUGINS, 151
ER_CANT_CHECK_PID_PATH, 255	ER_CANT_INITIALIZE_GTID, 151
ER_CANT_CHOWN_DATADIR, 151	ER_CANT_INITIALIZE_UDF, 11
ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_A, 109	ER_CANT_INIT_DBS, 150
ER_CANT_CREATE_ADMIN_THREAD, 344	ER_CANT_INIT_SCHEDULER_THREAD, 143
ER_CANT_CREATE_CACHE_FOR_DB_OPT, 183	ER_CANT_INIT_TC_LOG, 142
ER_CANT_CREATE_DB, 3	ER_CANT_INIT_TIMER, 152
ER_CANT_CREATE_FILE, 3	ER_CANT_JOIN_SHUTDOWN_THREAD, 152
ER_CANT_CREATE_GEOMETRY_OBJECT, 28	ER_CANT_LOCK, 4
ER_CANT_CREATE_HANDLER_FILE, 33	ER_CANT_LOCK_LOG_TABLE, 36
ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE, 182	ER_CANT_LOCK_TABLE, 182
ER_CANT_CREATE_HANDLE_MGR_THREAD, 142	ER_CANT_LOCK_TABLESPACE, 183
ER_CANT_CREATE_INTERRUPT_THREAD, 147	ER_CANT_MODIFY_SRID_0, 86
ER_CANT_CREATE_NAMED_PIPES_THREAD, 147	ER_CANT_MODIFY_SRS_USED_BY_COLUMN, 86
ER_CANT_CREATE_PID_FILE, 146	ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES, 163
	ER_CANT_OPEN_CA, 152
	ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE, 184
	ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET, 183
	ER_CANT_OPEN_DIR, 184
	ER_CANT_OPEN_ERROR_LOG, 152

ER_CANT_OPEN_FILE, 4	ER_CANT_STAT_DATA DIR, 151
ER_CANT_OPEN_FRM_FILE, 163	ER_CANT_STAT_FILE, 188
ER_CANT_OPEN_LIBRARY, 11	ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT, 47
ER_CANT_OPEN_TABLE_MYSQL_PROC, 184	ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG, 29
ER_CANT_PARSE_STORED_ROUTINE_BODY, 184	ER_CANT_UPDATE_WITH_READLOCK, 17
ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED COLUMNS, 359	ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD, 183
ER_CANT_READ_DIR, 4	ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE, 109
ER_CANT_READ_ERRMSG, 150	ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF, 65
ER_CANT_READ_FRM_FILE, 163	ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON, 114
ER_CANT_READ_TABLE_MYSQL_PROC, 184	ER_CANT_USE_OPTION_HERE, 18
ER_CANT_REMOVE_ALL_FIELDS, 9	ER_CANT_USE_SAME_UUID_AS_GROUP_NAME, 109
ER_CANT_REMOVE_PID_FILE, 146	ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID, 111
ER_CANT_RENAME_LOG_TABLE, 37	ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING GTID, 69
ER_CANT_REOPEN_TABLE, 12	ER_CAPACITY_EXCEEDED, 69
ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION, 334	ER_CAPACITY_EXCEEDED_IN_PARSER, 70
ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_OFF, 334	ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER, 69
ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF, 334	ER_CA_SELF_SIGNED, 144
ER_CANT_RESET_SOURCE, 71	ER_CHANGED_ENFORCE_GTID_CONSISTENCY, 142
ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY, 121	ER_CHANGED_GTID_MODE, 142
ER_CANT_SAVE_GTIDS, 152	ER_CHANGED_MAX_CONNECTIONS, 149
ER_CANT_SET_DATA_DIR, 342	ER_CHANGED_MAX_OPEN_FILES, 149
ER_CANT_SET_ERROR_LOG_SERVICE, 85	ER_CHANGED_MAX_OPEN_CACHES, 149
ER_CANT_SET_ERROR_SUPPRESSION_LIST, 87	ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_CANT_DISABLE, 113
ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE, 338	ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION WHEN GTID_MODE_IS_ON, 113
ER_CANT_SET_GTID_MODE, 65	ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION WHEN GTID_MODE_IS_OFF, 113
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN GTID_MODE_IS_ON, 50	ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_V, 113
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN GTID_MODE_IS_ON, 50	ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMATS, 113
ER_CANT_SET_GTID_NEXT_TO_AUTOMATIC_TAGGED, 124	ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_IS_NOT_EMPTY, 113
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN GTID_MODE_IS_OFF, 50	ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE, 107
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID, 50	ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM, 111
ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS, 75	ER_CHANGE_SOURCE_PASSWORD_LENGTH, 61
ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED IS NOT EMPTY, 53	ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_TO_ANONYMOUS_TO_GTID, 102
ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS IS NOT EMPTY, 54	ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_TO_ANONYMOUS_TO_GTID, 102
ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE, 182	ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_C, 101
ER_CANT_SET_PATH_FOR, 184	ER_CHARACTER_SET_MISMATCH, 107
ER_CANT_SET_PERSISTED, 120	
ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH, 109	
ER_CANT_SET_UP_PERSISTED_VALUES, 151	
ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID, 67	
ER_CANT_START_ERROR_LOG_SERVICE, 194	

ER_CHECKING_TABLE, 182	ER_CLONE_DISK_SPACE, 98
ER_CHECKREAD, 4	ER_CLONE_DONOR, 97
ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFERENCES, 342	ER_CLONE_COLUMN, 98
95	ER_CLONE_DONOR_VERSION, 98
ER_CHECK_CONSTRAINT_DUP_NAME, 94	ER_CLONE_ENCRYPTION, 98
ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED, 201	ER_CLONE_HANDLER_EXIST_TRACE, 201
94	ER_CLONE_IN_PROGRESS, 98
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED, 98	ER_CLONE_LOOPBACK, 98
94	ER_CLONE_NETWORK_PACKET, 104
ER_CHECK_CONSTRAINT_NOT_FOUND, 94	ER_CLONE_OS, 98
ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN, 98	ER_CLONE_PLATFORM, 98
94	ER_CLONE_PLUGIN_MATCH, 98
ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN, 201	ER_CLONE_PLUGIN_NOT_LOADED_TRACE, 201
94	ER_CLONE_PROTOCOL, 98
ER_CHECK_CONSTRAINT_ROW_VALUE, 94	ER_CLONE_PROTOCOL_TRACE, 342
ER_CHECK_CONSTRAINT_VARIABLES, 94	ER_CLONE_SERVER_TRACE, 342
ER_CHECK_CONSTRAINT_VIOLATED, 94	ER_CLONE_SHUTDOWN_TRACE, 355
ER_CHECK_NOT_IMPLEMENTED, 14	ER_CLONE_SYS_CONFIG, 98
ER_CHECK_NO_SUCH_TABLE, 14	ER_CLONE_TOO_MANY_CONCURRENT_CLONES, 81
ER_CHECK_TABLE_FUNCTIONS, 403	ER_CMD_NEED_SUPER_OR_CREATE_SPATIAL_REFERENCES, 132
ER_CHECK_TABLE_FUNCTIONS_DETAIL, 403	ER_COALESCE_ONLY_ON_HASH_PARTITION, 33
ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET, 397	ER_COALESCE_PARTITION_NO_PARTITION, 34
ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET, 399	ER_COLLATION_CHARSET_MISMATCH, 19
ER_CHECK_TABLE_MIN_REC_FLAG_SET, 399	ER_COLUMNACCESS_DENIED_ERROR, 12
ER_CLAUSE_IGNORED, 132	ER_COLUMN_CHANGE_SIZE, 99
ER_CLIENT_DOES_NOT_SUPPORT, 81	ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN, 94
ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS, 117	ER_COL_COUNT_DOESNT_MATCH_BINLOG, 51
ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRANSACTION, 89	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE, 36
ER_CLIENT_INTERACTION_TIMEOUT, 110	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2, 58
ER_CLIENT_KEYRING_UDF_KEY_INVALID, 102	ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CONTEXT, 117
ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG, 102	ER_COMMAND_SERVICE_BACKEND_FAILED, 117
ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID, 102	ER_COMMENT_CONTAINS_INVALID_STRING, 15
ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG, 102	ER_CONVERSION_IMPOSSIBLE, 15
ER_CLIENT_LOCAL_FILES_DISABLED, 104	ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG, 28
ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS, 102	ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION, 74
ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT, 102	ER_COMPONENTS_CANT_LOAD, 74
ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 102	ER_COMPONENTS_CANT_RELEASE_SERVICE, 74
ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_ROLE, 102	ER_COMPONENTS_CANT_SATISFY_DEPENDENCY, 74
ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT, 103	ER_COMPONENTS_CANT_UNLOAD, 74
ER_CLONE_CHARSET, 98	ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTation, 204
ER_CLONE_CLIENT_TRACE, 342	ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP, 144
ER_CLONE_CONFIG, 98	ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINITIALIZATION, 374
ER_CLONE_CREATE_HANDLER_FAIL_TRACE, 201	
ER_CLONE_DDL_IN_PROGRESS, 81	
ER_CLONE_DISALLOWED, 98	

ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INVALID, 373	ER_COMPONENT_FIREWALL_CANNOT_ACCESS_TABLE, 424
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN, 144	ER_COMPONENT_FIREWALL_CANNOT_READ_TABLE, 424
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_INVALID, 405	ER_COMPONENT_FIREWALL_DATABASE, 424
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_INVALID, 405	ER_COMPONENT_FIREWALL_INIT, 424
ER_COMPONENTS_LOAD_CANT_INITIALIZE, 74	ER_COMPONENT_FIREWALL_INVALID_RELOAD_INTERVAL, 423
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE, 74	ER_COMPONENT_FIREWALL_INVALID_TABLE_DEFINITION_IMPLEMENTATION, 424
ER_COMPONENTS_NO_SCHEME, 73	ER_COMPONENT_FIREWALL_NOTIFICATION_REGISTRATION_FAILURE, 423
ER_COMPONENTS_NO_SCHEME_SERVICE, 74	ER_COMPONENT_FIREWALL_OTHER_ERROR, 423
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP, 144	ER_COMPONENT_FIREWALL_PROCESSING_ERROR, 424
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE, 74	ER_COMPONENT_FIREWALL_PROCESSING_EXCEPTION, 424
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE, 74	ER_COMPONENT_FIREWALL_RECORDING_TRUNCATED, 423
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP, 75	ER_COMPONENT_FIREWALL_RELOAD_TOO_SHORT_PERIOD, 424
ER_COMPONENTS_UNLOAD_NOT_LOADED, 74	ER_COMPONENT_FIREWALL_SUSPICIOUS_STMT, 423
ER_COMPONENT_EE_DATA_DECRYPTION_ERROR, 392	ER_COMPONENT_FIREWALL_SUSPICIOUS_STMT_TRUNCATED, 423
ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR, 392	ER_COMPONENT_FIREWALL_TRACING_ERROR, 424
ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE, 392	ER_COMPONENT_FIREWALL_VAR_REGISTRATION_FAILURE, 423
ER_COMPONENT_EE_DATA_SIGN_ERROR, 392	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY_FAILURE, 403
ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE, 391	ER_COMPONENT_KEYRING_OCI_INVALID_CONFIG_VAR, 405
ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM, 391	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE_FAILURE, 403
ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENT, 391	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE_FAILURE, 403
ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE, 391	ER_COMPONENT_LOCK, 400
ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE, 392	ER_COMPONENT_MANIPULATE_ROW_FAILED, 75
ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE, 392	ER_COMPONENT_MASKING_ABI, 401
ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE, 391	ER_COMPONENT_MASKING_ABI_REASON, 401
ER_COMPONENT_EE_INSUFFICIENT_LENGTH, 392	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE, 401
ER_COMPONENT_EE_OPENSSL_ERROR, 392	ER_COMPONENT_MASKING_INVALID_FLUSH_INTERVAL_VALUE, 401
ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE, 391	ER_COMPONENT_MASKING_NOTIFICATION_REGISTRATION_FAILURE, 401
ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE, 391	ER_COMPONENT_MASKING_OTHER_ERROR, 401
ER_COMPONENT_FILTER_CONFUSED, 217	ER_COMPONENT_MASKING_RANDOM_CREATE, 401
ER_COMPONENT_FILTER_DIAGNOSTICS, 85	ER_COMPONENT_MASKING_RANDOM_CREATE_REASON, 401
ER_COMPONENT_FILTER_FLABBERGASTED, 80	ER_COMPONENT_MASKING_VAR_REGISTRATION_FAILURE, 401
ER_COMPONENT_FILTER_WRONG_VALUE, 332	ER_COMPONENT_SERVICE_CALL, 400
ER_COMPONENT_FIREWALL_ACCESS_DENIED, 424	
ER_COMPONENT_FIREWALL_ACCESS_DENIED_TRUNCATED, 423	

ER_COMPONENT_SERVICE_CALL_RESULT, 400	ER_CONN_SHM_CANT_CREATE_SERVICE, 156
ER_COMPONENT_TABLE_INCORRECT, 75	ER_CONN_SHM_LISTENER, 156
ER_COMPONENT_UNLOCK, 401	ER_CONN_SOCKET_ACCEPT_FAILED, 158
ER_CONCURRENT_PROCEDURE_USAGE, 114	ER_CONN_SOCKET_SELECT_FAILED, 158
ER_CONDITIONAL_DEBUG, 393	ER_CONN_TCP_ADDRESS, 156
ER_COND_ITEM_TOO_LONG, 41	ER_CONN_TCP_BIND_FAIL, 157
ER_CONFIG_OPTION_WITHOUT_GROUP, 154	ER_CONN_TCP_BIND_RETRY, 157
ER_CONFIRMING_THE_FUTURE, 147	ER_CONN_TCP_CANT_RESET_V6ONLY, 157
ER_CONFLICTING_DECLARATIONS, 21	ER_CONN_TCP_CANT_RESOLVE_HOSTNAME, 157
ER_CONFLICT_FN_PARSE_ERROR, 39	ER_CONN_TCP_CREATED, 156
ER_CONNECTIONS_SHUTDOWN_END, 405	ER_CONN_TCP_ERROR_WITH_STRERROR, 156
ER_CONNECTIONS_SHUTDOWN_START, 405	ER_CONN_TCP_IPV6_AVAILABLE, 156
ER_CONNECTION_ABORTED, 331	ER_CONN_TCP_IPV6_UNAVAILABLE, 156
ER_CONNECTION_CONTROL_FAILED_DEINIT, 420	ER_CONN_TCP_IP_NOT_LOGGED, 157
ER_CONNECTION_CONTROL_FAILED_TO_GET_ATTRIBUTES_FROM_SUPPLIER, 420	ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT, 157
ER_CONNECTION_CONTROL_FAILED_TO_GET_SECURITY_CTX, 420	ER_CONN_TCP_LISTEN_FAIL, 157
ER_CONNECTION_CONTROL_STATUS_VAR_REG_FAILED, 420	ER_CONN_TCP_NO_SOCKET, 156
ER_CONNECTION_CONTROL_STATUS_VAR_UNREG_FAILED, 420	ER_CONN_TCP_RESOLVE_INFO, 157
ER_CONNECTION_CONTROL_VARIABLE_REGISTRATION_FAILED, 420	ER_CONN_TCP_START_FAIL, 157
ER_CONNECTION_CONTROL_VARIABLE_UNREGISTRATION_FAILED, 420	ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET, 157
ER_CONNECTION_HANDLING_OOM, 146	ER_CONN_UNIX_LISTEN_FAILED, 158
ER_CONNECTION_METADATA, 15	ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE, 158
ER_CONNECT_TO_FOREIGN_DATA_SOURCE, 29	ER_CONN_UNIX_LOCK_FILE_CANT_CREATE, 158
ER_CONNECT_TO_SOURCE, 17	ER_CONN_UNIX_LOCK_FILE_CANT_DELETE, 158
ER_CONN_ATTR_TRUNCATED, 159	ER_CONN_UNIX_LOCK_FILE_CANT_OPEN, 158
ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED, 218	ER_CONN_UNIX_LOCK_FILE_CANT_READ, 158
ER_CONN_CONTROL_ERROR_MSG, 216	ER_CONN_UNIX_LOCK_FILE_CANT_SYNC, 158
ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED, 218	ER_CONN_UNIX_LOCK_FILE_CANT_WRITE, 158
ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY, 218	ER_CONN_UNIX_LOCK_FILE_EMPTY, 158
ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY, 218	ER_CONN_UNIX_LOCK_FILE_FAIL, 157
ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE, 218	ER_CONN_UNIX_LOCK_FILE_GIVING_UP, 158
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, 218	ER_CONN_UNIX_LOCK_FILE_PIDLESS, 158
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, 218	ER_CONN_UNIX_NO_BIND_NO_START, 157
ER_CONN_CONTROL_STAT_CONN_EXEMPTED_USERS, 428	ER_CONN_UNIX_NO_FD, 157
ER_CONN_INIT_CONNECT_IGNORED, 217	ER_CONN_UNIX_PATH_TOO_LONG, 157
ER_CONN_INIT_CONNECT_IGNORED_MFA, 401	ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE, 157
ER_CONN_LIMIT, 384	ER_CONSECUTIVE_REORG_PARTITIONS, 34
ER_CONN_PER_THREAD_NO_THREAD, 156	ER_CONSTRAINT_NOT_FOUND, 103
ER_CONN_PIP_CANT_CREATE_EVENT, 156	ER_CONV_FAILED, 402
ER_CONN_PIP_CANT_CREATE_PIPE, 156	ER_CON_COUNT_ERROR, 5
ER_CONN_SHM_CANT_CREATE_CONNECTION, 156	ER_COPY_FAILED, 147
	ER_CORRUPTED_JSON_DIFF, 82
	ER_CREATE_FAILED, 18
	ER_CREATE_FAILED_DB, 18
	ER_COULD_NOT_APPLY_JSON_DIFF, 82
	ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY, 340
	ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS, 335
	ER_CRASHED_ON_REPAIR, 15
	ER_CRASHED_ON_USAGE, 15
	ER_CREATED_SYSTEM_WITH_VERSION, 200
	ER_CREATE_FILEGROUP_FAILED, 35

ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_117	ER_DA_UDF_INVALID_CHARSET_SPECIFIED, 102
ER_CREATING_NEW_UUID, 145	ER_DA_UDF_INVALID_COLLATION, 103
ER_CREATING_NEW_UUID_FIRST_START, 194	ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE, 103
ER_CREDENTIALLESS_AUTO_USER_BAD, 146	ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET, 104
ER_CREDENTIALS_CONTRADICT_TO_HISTORY, 81	ER_DA_UNKNOWN_ERROR_NUMBER, 99
ER_CTE_MAX_RECURSION_DEPTH, 81	ER_DBACCESS_DENIED_ERROR, 5
ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER, 77	ER_DEBUG_CHECK_SHARES_DROPPED, 171
ER_CTE_RECURSIVE_FORBIDS_AGGREGATION, 77	ER_DEBUG_CHECK_SHARES_INFO, 171
ER_CTE_RECURSIVE_NOT_UNION, 117	ER_DEBUG_CHECK_SHARES_OPEN, 171
ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST, 77	ER_DB_ACCESS_DENIED, 99
ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE, 77	ER_DB_CREATE_EXISTS, 4
ER_CTE_RECURSIVE_REQUIRES_UNION, 77	ER_DB_DROP_EXISTS, 4
ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED, 100	ER_DB_DROP_RMDIR, 4
ER_CURRENT_PASSWORD_NOT_REQUIRED, 99	ER_DB_DROP_RMDIR2, 79
ER_CUT_VALUE_GROUP_CONCAT, 19	ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET, 183
ER_CYCLE_TIMER_IS_NOT_AVAILABLE, 201	ER_DDL_MSG_1, 380
ER_DATABASE_NAME, 39	ER_DD_ABORTING_PARTIAL_UPGRADE, 162
ER_DATA_DIRECTORY_UNUSABLE, 340	ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN, 141
ER_DATA_DIRECTORY_UNUSABLE_DELETABLE, 355	ER_DD_CANT_CREATE_OBJECT_KEY, 142
ER_DATA_INCOMPATIBLE_WITH_VECTOR, 130	ER_DD_CANT_CREATE_SP, 183
ER_DATA_OUT_OF_RANGE, 43	ER_DD_CANT_FETCH_TABLE_DATA, 183
ER_DATA_TOO_LONG, 27	ER_DD_CANT_FIX_SE_DATA, 183
ER_DATETIME_FUNCTION_OVERFLOW, 29	ER_DD_CANT_GET_OBJECT_KEY, 142
ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROWS, 99	ER_DD_CANT_RESOLVE_VIEW, 153
ER_DA_CANT_OPEN_ERROR_LOG, 108	ER_DD_CREATED_FOR_UPGRADE, 162
ER_DA_CONN_LIMIT, 114	ER_DD_ERROR_CREATING_ENTRY, 183
ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED, 111	ER_DD_FORSALES, 140
ER_DA_ERROR_LOG_MULTIPLE_FILTERS, 108	ER_DD_FRM_EXISTS_FOR_TABLE, 162
ER_DA_ERROR_LOG_TABLE_DISABLED, 108	ER_DD_INITIALIZE, 205
ER_DA_GLOBAL_CONN_LIMIT, 114	ER_DD_INITIALIZE_SQL_ERROR, 336
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT, 106	ER_DD_INIT_FAILED, 141
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID, 106	ER_DD_METADATA_NOT_FOUND, 141
ER_DA_GRP_RPL_STARTED_AUTO_REJOIN, 101	ER_DD_MINOR_DOWNGRADE, 205
ER_DA_INVALID_CONDITION_NUMBER, 48	ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED, 205
ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED, 108	ER_DD_NO_VERSION_FOUND, 205
ER_DA_OOM, 104	ER_DD_NO_WRITES_NO_REPOPULATION, 140
ER_DA_PLUGIN_INSTALL_ERROR, 99	ER_DD_OBJECT_RELEASER_REMAINS, 142
ER_DA_RPL_GTID_TABLE_CANNOT_OPEN, 99	ER_DD_OBJECT_REMAINS, 141
ER_DA_SSL_FIPS_MODE_ERROR, 114	ER_DD_OBJECT_REMAINS_IN_RELEASER, 141
ER_DA_SSL_LIBRARY_ERROR, 99	ER_DD_RESTART, 205
ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET, 104	ER_DD_SCHEMA_NOT_FOUND, 162
ER_DA_UDF_INVALID_CHARSET, 103	ER_DD_SE_INIT_FAILED, 162
	ER_DD_TABLESPACE_NOT_FOUND, 153
	ER_DD_TABLE_NOT_FOUND, 162
	ER_DD_TRG_CANT_ADD, 153
	ER_DD_TRG_CONNECTION_COLLATION_MISSING, 153
	ER_DD_TRG_DB_COLLATION_MISSING, 153
	ER_DD_TRG_DEFINER_OOM, 153
	ER_DD_TRG_FILE_UNREADABLE, 153
	ER_DD_UPDATE_DATADIR_FLAG_FAIL, 415
	ER_DD_UPDATING_PLUGIN_MD_FAILED, 141

ER_DD_UPGRADE, 205	ER_DEBUG_SYNC_THREAD_MAX, 142
ER_DD_UPGRADE_COMPLETED, 352	ER_DEBUG_SYNC_TIMEOUT, 40
ER_DD_UPGRADE_DD_OPEN_FAILED, 198	ER_DEFAULT_AS_VAL_GENERATED, 90
ER_DD_UPGRADE_DD_POPULATED, 199	ER_DEFAULT_SE_UNAVAILABLE, 152
ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR, 199	ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED, 90
ER_DD_UPGRADE_FAILED_INIT_DD_SE, 199	ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED, 90
ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE, 198	ER_DEFAULT_VAL_GENERATED_NON_PRIOR, 90
ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS, 199	ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC, 90
ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS, 199	ER_DEFAULT_VAL_GENERATED_ROW_VALUE, 90
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES, 199	ER_DEFAULT_VAL_GENERATED_VARIABLES, 90
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES, 198	ER_DEFINITION_CONTAINS_INVALID_STRING, 135
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE, 198	ER_ENGINE, 144
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE, 205	ER_DEPENDENT_BY_CHECK_CONSTRAINT, 104
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED, 200	ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE, 90
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED, 200	ER_DEPENDENT_BY_FUNCTIONAL_INDEX, 96
ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED, 199	ER_DEPENDENT_BY_GENERATED_COLUMN, 65
ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED, 199	ER_DEPENDENT_BY_PARTITION_FUNC, 97
ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED, 199	ER_DEPRECATED_NATIONAL, 86
ER_DD_UPGRADE_OFF, 205	ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS, 379
ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED, 198	ER_DEPRECATED_SYNTAX_NO_REPLACEMENT, 204
ER_DD_UPGRADE_SCHEMA_UNAVAILABLE, 205	ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT, 204
ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED, 200	ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS, 145
ER_DD_UPGRADE_SE_LOGS_FAILED, 200	ER_DEPRECATED_UTF8_ALIAS, 86
ER_DD_UPGRADE_START, 199	ER_DEPRECATE_MSG_NO_REPLACEMENT, 204
ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED, 199	ER_DEPRECATE_MSG_WITH_REPLACEMENT, 193
ER_DD_UPGRADE_TABLE_INTACT_ERROR, 203	ER_DEPRECATE_NON_COMPOSABLE_MULTIPLE_ENGINES, 131
ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED, 199	ER_DERIVED_MUST_HAVE_ALIAS, 18
ER_DD_UPGRADE_VERSION_NOT_SUPPORTED, 205	ER_DES_FILE_WRONG_KEY, 154
ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG, 204	ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN, 171
ER_DD_VERSION_FOUND, 140	ER_DETACHING_SESSION_LEFT_BY_PLUGIN, 171
ER_DD_VERSION_INSTALLED, 140	ER_DIAG_LOG_STRING, 420
ER_DD_VERSION_UNSUPPORTED, 140	ER_DIMENSION_UNSUPPORTED, 62
ER_DD_VIEW_CANT_ALLOC_CHARSET, 141	ER_DISABLED_STORAGE_ENGINE, 68
ER_DD_VIEW_CANT_CREATE, 141	ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT, 142
ER_DD_VIEW_WITHOUT_DEFINER, 153	ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONSTRUCT, 107
ER_DEBUG_SYNC_EXECUTED, 142	ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONSTRUCT, 107
ER_DEBUG_SYNC_HIT, 142	ER_DISALLOWED_OPERATION, 82
ER_DEBUG_SYNC_HIT_LIMIT, 40	ER_DISCARD_FK_CHECKS_RUNNING, 51
ER_DEBUG_SYNC_OOM, 142	

ER_DISCONNECTING_REMAINING_CLIENTS, 148
 ER_DISK_FULL_NOWAIT, 83
 ER_DIVISION_BY_ZERO, 25
 ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY, 204
 ER_DROP_FILEGROUP_FAILED, 35
 ER_DROP_INDEX_FK, 35
 ER_DROP_LAST_PARTITION, 33
 ER_DROP_PARTITION_NON_EXISTENT, 33
 ER_DROP_PK_COLUMN_TO_DROP_GIPK, 116
 ER_DUPLICATED_VALUE_IN_TYPE, 21
 ER_DUPLICATE_OPTION_KEY, 76
 ER_DUPLICATE_SYS_VAR, 337
 ER_DUPLICATE_TABLE_LOCK, 76
 ER_DUP_ARGUMENT, 17
 ER_DUP_ENTRY, 7
 ER_DUP_ENTRY_AUTOINCREMENT_CASE, 36
 ER_DUP_ENTRY_WITH_KEY_NAME, 37
 ER_DUP_FD_OPEN_FAILED, 194
 ER_DUP_FIELDNAME, 7
 ER_DUP_INDEX, 53
 ER_DUP_KEY, 4
 ER_DUP_KEYNAME, 7
 ER_DUP_LIST_ENTRY, 59
 ER_DUP_SIGNAL_SET, 40
 ER_DUP_UNIQUE, 14
 ER_DUP_UNKNOWN_IN_INDEX, 55
 ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE, 85
 ER_EMPTY_PRIVILEGE_NAME_IGNORED, 370
 ER_EMPTY_QUERY, 7
 ER_ENDING_INIT, 336
 ER_END_INITFILE, 149
 ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONE_ERRNO, 65
 ER_ENGINE_ATTRIBUTE_CONFLICT, 139
 ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED, 106
 ER_ENGINE_CANNOT_BE_DEFAULT, 129
 ER_ENGINE_CANT_DROP_MISSING_TABLE, 79
 ER_ENGINE_CANT_DROP_TABLE, 79
 ER_ENGINE_COST_FAILED_TO_READ, 169
 ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE, 169
 ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE, 169
 ER_ENGINE_COST_UNKNOWN_COST_CONSTANT, 168
 ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE, 169
 ER_ENGINE_OUT_OF_MEMORY, 58
 ER_ERRMSG_CANT_FIND_FILE, 162
 ER_ERRMSG_CANT_READ, 163
 ER_ERRMSG_MISSING_IN_FILE, 162
 ER_ERRMSG_OOM, 163
 ER_ERRMSG_REPLACEMENTS_FAILED, 191
 ER_ERRMSG_REPLACEMENT_DODGY, 191
 ER_ERROR_DURING_COMMIT, 14
 ER_ERROR_DURING_FLUSH_LOGS, 14
 ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE, 204
 ER_ERROR_DURING_OPTIMIZE_TABLE, 182
 ER_ERROR_DURING_ROLLBACK, 14
 ER_ERROR_ENABLING_KEYS, 182
 ER_ERROR_INFO_FROM_DA, 334
 ER_ERROR_IN_TRIGGER_BODY, 45
 ER_ERROR_IN_UNKNOWN_TRIGGER_BODY, 45
 ER_ERROR_LOG_DESTINATION_NOT_A_FILE, 370
 ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE, 70
 ER_ERROR_ON_READ, 4
 ER_ERROR_ON_RENAME, 4
 ER_ERROR_ON_SOURCE, 57
 ER_ERROR_ON_WRITE, 4
 ER_ERROR_WHEN_EXECUTING_COMMAND, 17
 ER_ETAG_NOT_SUPPORTED, 139
 ER_EVENT_ALREADY_EXISTS, 35
 ER_EVENT_CANNOT ALTER IN THE PAST, 37
 ER_EVENT_CANNOT_CREATE_IN_THE_PAST, 37
 ER_EVENT_CANT_FIND_TIMEZONE, 183
 ER_EVENT_CANT_GET_CHARSET, 184
 ER_EVENT_CANT_GET_COLLATION, 184
 ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT, 185
 ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD, 183
 ER_EVENT_CANT_INIT_QUEUE, 142
 ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT, 184
 ER_EVENT_DOES_NOT_EXIST, 35
 ER_EVENT_DROPPING, 170
 ER_EVENT_ENDS_BEFORE_STARTS, 35
 ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG, 185
 ER_EVENT_ERROR_DURING_COMPILATION, 170
 ER_EVENT_EXECUTION_FAILED, 143
 ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER_AND_DEVICE, 169
 ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PRIVILEGE, 170
 ER_EVENT_EXEC_TIME_IN_THE_PAST, 35
 ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG, 35
 ER_EVENT_INVALID_CREATION_CTX, 38
 ER_EVENT_LAST_EXECUTION, 143
 ER_EVENT_MESSAGE_STACK, 143
 ER_EVENT_PURGING_QUEUE, 143
 ER_EVENT_RECURSION_FORBIDDEN, 37
 ER_EVENT_SAME_NAME, 35
 ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT, 185

ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB, 185	ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION, 166
ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE, 185	ER_FAILED_TO_CREATE_RPL_OPT_TRACKER_THREAD, 420
ER_EVENT_SET_VAR_ERROR, 36	ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE, 198
ER_EVENT_UNABLE_TO_DROP_EVENT, 185	ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS, 171
ER_EXCEEDED_MAX_REGULAR_STATEMENT_HANDLER, 131	ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE, 166
ER_EXCEEDED_MV_KEYS_NUM, 100	ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP, 196
ER_EXCEEDED_MV_KEYS_SPACE, 100	ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY, 103
ER_EXCEEDS_VECTOR_MAX_DIMENSIONS, 130	ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST, 103
ER_EXCEPTIONS_WRITE_ERROR, 39	ER_FAILED_TO_FIND_CHARSET_NAME, 427
ER_EXCESS_ARGUMENTS, 149	ER_FAILED_TO_FIND_COLLATION_NAME, 194
ER_EXPLAIN_ANALYZE_JSON_FORMAT_VERSION_NOT_SUPPORTED, 131	ER_FAILED_TO_FIND_DL_ENTRY, 191
ER_EXPLAIN_INTRO_FORMAT_NOT_SUPPORTED, 121	ER_FAILED_TO_FIND_LOCALE_NAME, 194
ER_EXPLAIN_INTRO_FOR_CONNECTION_NOT_SUPPORTED, 122	ER_FAILED_TO_FIND_MYSQLD_STATUS, 203
ER_EXPLAIN_INTRO_IMPLICIT_FORMAT_NOT_SUPPORTED, 121	ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE, 192
ER_EXPLAIN_NOT_SUPPORTED, 58	ER_FAILED_TO_GET_ABSOLUTE_PATH, 194
ER_EXTERNAL_FORMAT_NOT_SUPPORTED, 139	ER_FAILED_TO_HANDLE_DEFAULTS_FILE, 337
ER_EXTERNAL_TABLE_ENGINE_NOT_SPECIFIED, 139	ER_FAILED_TO_INIT_SYS_VAR, 337
ER_EXTERNAL_TABLE_ENGINE_NOT_SUPPORTED, 139	ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE, 166
ER_EXTERNAL_TABLE_INVALID_OPTION, 139	ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD, 166
ER_FAILED_DEFAULT_ROLES, 73	ER_FAILED_TO_LOCK_MEM, 149
ER_FAILED_GET_DD_PROPERTY, 402	ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES, 169
ER_FAILED_READ_FROM_PAR_FILE, 44	ER_FAILED_TO_OPEN_SHARED_LIBRARY, 191
ER_FAILED_REVOKE_ROLE, 74	ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA, 196
ER_FAILED_ROLE_GRANT, 73	ER_FAILED_TO_READ_FILE, 192
ER_FAILED_SET_DD_PROPERTY, 402	ER_FAILED_TO_REMOVE_TEMP_TABLE, 180
ER_FAILED_START_MYSQLD_DAEMON, 195	ER_FAILED_TO_REPAIR_TABLE, 180
ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP, 197	ER_FAILED_TO_SET_PERSISTED_OPTIONS, 204
ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP, 197	ER_FAILED_TO_START_REPLICA_THREAD, 200
ER_FAILED_TO_ADD_RPL_FILTER, 201	ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE, 199
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP, 197	ER_FAILED_TO_UPDATE_RESOURCE_GROUP, 196
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH, 197	ER_FAILED_TO_VALIDATE_CERTIFICATES_SERVER_EXTENSION, 197
ER_FAILED_TO_ALLOCATE_SSL_BIO, 336	ER_FAILED_TO_WRITE_TO_FILE, 192
ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER, 197	ER_FAIL_CHROOT, 148
ER_FAILED_TO_BINLOG_DROP_EVENT, 200	ER_FAIL_SETGID, 148
ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES, 201	ER_FAIL_SETREGID, 148
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE, 166	ER_FAIL_SETREUID, 148
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_FROM, 166	ER_FAIL_SETUID, 148
ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY, 200	ER_FEATURE_DISABLED, 21
	ER_FEATURE_DISABLED_SEE_DOC, 69
	ER_FEATURE_NOT_AVAILABLE, 65
	ER_FEATURE_UNSUPPORTED, 82
	ER_FIELD_IN_GROUPING_NOT_GROUP_BY, 79

ER_FIELD_IN_ORDER_NOT_SELECT, 61	ER_FORCE_CLOSE_THREAD, 192
ER_FIELD_NOT_FOUND_PART_ERROR, 32	ER_FORCING_CLOSE, 8
ER_FIELD_SPECIFIED_TWICE, 10	ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST,
ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD,	ER_FOREIGN_DATA_STRING_INVALID, 29
41	ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE,
ER_FILEGROUP_OPTION_ONLY_ONCE, 34	29
ER_FILE_CORRUPT, 57	ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED,
ER_FILE_EXISTS_DURING_UPGRADE, 184	36
ER_FILE_EXISTS_ERROR, 8	ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO,
ER_FILE_HAS_OLD_FORMAT, 193	48
ER_FILE_NOT_FOUND, 4	ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO,
ER_FILE_TYPE_UNKNOWN, 163	48
ER_FILE_USED, 5	ER_FOREIGN_KEY_ON_PARTITIONED, 33
ER_FIREWALL_ACCESS_DENIED, 212	ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT,
ER_FIREWALL_DEPRECATED_USER_PROFILE,	106
377	ER_FOREIGN_SERVER_DOESNT_EXIST, 32
ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES,	ER_FOREIGN_SERVER_EXISTS, 32
211	ER_FOUND_MISSING_GTIDS, 255
ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES,	ER_FOUND_ROWS_WHILE_REPAIRING, 182
211	ER_FPARSER_BAD_HEADER, 24
ER_FIREWALL_INVALID_RELOAD_INTERVAL_VALUE,	ER_FPARSER_EOF_IN_COMMENT, 24
406	ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER,
ER_FIREWALL_PFS_TABLE_REGISTER_FAILED,	24
373	ER_FPARSER_ERROR_IN_PARAMETER, 24
ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED,	ER_FPARSER_TOO_BIG_FILE, 24
212	ER_FSEEK_FAIL, 26
ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT,	ER_FT_BOOL_SYNTAX_INVALID, 145
212	ER_FT_MATCHING_KEY_NOT_FOUND, 15
ER_FIREWALL_RELOADING_CACHE, 212	ER_FULLTEXT_FUNCTIONAL_INDEX, 89
ER_FIREWALL_RESET_FOR_USER, 212	ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING,
ER_FIREWALL_SCHEDULER_REGISTER_FAILED,	48
406	ER_FULLTEXT_WITH_ROLLUP, 114
ER_FIREWALL_SERVICES_NOT_ACQUIRED, 373	ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG,
ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE,	100
212	ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED,
ER_FIREWALL_STATUS_FLUSHED, 212	89
ER_FIREWALL_SUSPICIOUS_STMT, 212	ER_FUNCTIONAL_INDEX_ON_FIELD, 90
ER_FIREWALL_UDF_REGISTER_FAILED, 373	ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNC
ER_FIXING_CLIENT_CHARSET, 149	89
ER_FK_CANNOT_CHANGE_ENGINE, 91	ER_FUNCTIONAL_INDEX_ON_LOB, 89
ER_FK_CANNOT_DROP_PARENT, 87	ER_FUNCTIONAL_INDEX_PRIMARY_KEY, 89
ER_FK_CANNOT_OPEN_PARENT, 53	ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT,
ER_FK_CANNOT_USE_VIRTUAL_COLUMN, 87	89
ER_FK_COLUMN_CANNOT_CHANGE, 53	ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED,
ER_FK_COLUMN_CANNOT_CHANGE_CHILD, 53	93
ER_FK_COLUMN_CANNOT_DROP, 53	ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET,
ER_FK_COLUMN_CANNOT_DROP_CHILD, 53	107
ER_FK_COLUMN_NOT_NULL, 53	ER_FUNCTION_NOT_DEFINED, 11
ER_FK_DEPTH_EXCEEDED, 57	ER_FUNC_INEXISTENT_NAME_COLLISION, 39
ER_FK_DUP_NAME, 53	ER_FUTURE_DATE, 147
ER_FK_FAIL_ADD_SYSTEM, 52	ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED,
ER_FK_INCOMPATIBLE_COLUMNS, 91	64
ER_FK_INCORRECT_OPTION, 53	ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_AL
ER_FK_NO_COLUMN_PARENT, 87	90
ER_FK_NO_INDEX_CHILD, 52	ER_GENERATED_COLUMN_NON_PRIOR, 65
ER_FK_NO_INDEX_PARENT, 52	ER_GENERATED_COLUMN_REF_AUTO_INC, 65
ER_FK_NO_UNIQUE_INDEX_PARENT, 129	ER_GENERATED_COLUMN_ROW_VALUE, 90
ER_FORBID_SCHEMA_CHANGE, 30	

ER_GENERATED_COLUMN_VARIABLES, 90	ER_GROUP_REPLICATION_DECOMPRESS_EXCEEDS_M
ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT,	408
99	ER_GROUP_REPLICATION_DECOMPRESS_OUT_OF_ME
ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE	408
87	ER_GROUP_REPLICATION_DECOMPRESS_PROCESS,
ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE	408
87	ER_GROUP_REPLICATION_DECOMPRESS_TRUNCATED
ER_GET_ERRMSG, 21	408
ER_GET_ERRNO, 5	ER_GROUP_REPLICATION_ERROR_COMPRESS_INITIAL
ER_GET_ERRNO_FROM_STORAGE_ENGINE,	407
193	ER_GROUP_REPLICATION_ERROR_DECOMPRESS_INIT
ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER	408
57	ER_GROUP_REPLICATION_ERROR_RECEIVED_WAITING
ER_GET_TEMPORARY_ERRMSG, 21	409
ER_GIPK_COLUMN_ALTER_NOT_ALLOWED, 116	ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND
ER_GIPK_COLUMN_EXISTS, 116	117
ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS,	ER_GROUP_REPLICATION_MAX_GROUP_SIZE,
116	71
ER_GIS_DATA_WRONG_ENDIANESS, 61	ER_GROUP_REPLICATION_METADATA_CERT_INFO_EN
ER_GIS_DIFFERENT_SRIDS, 59	410
ER_GIS_DIFFERENT_SRIDS_AGGREGATION,	ER_GROUP_REPLICATION_METADATA_CERT_INFO_ER
110	409
ER_GIS_INVALID_DATA, 60	ER_GROUP_REPLICATION_METADATA_CERT_INFO_PA
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED	410
67	ER_GROUP_REPLICATION_METADATA_CERT_INFO_PA
ER_GIS_UNKNOWN_ERROR, 59	409
ER_GIS_UNKNOWN_EXCEPTION, 59	ER_GROUP_REPLICATION_METADATA_ERROR_ON_SE
ER_GIS_UNSUPPORTED_ARGUMENT, 59	410
ER_GLOBAL_CONN_LIMIT, 384	ER_GROUP_REPLICATION_METADATA_INITIALIZATION
ER_GLOBAL_VARIABLE, 17	410
ER_GLOBSTAT_CHANGE_DURING_QUERY, 101	ER_GROUP_REPLICATION_METADATA_MEMORY_ALLO
ER_GNO_EXHAUSTED, 49	410
ER_GRANT_WRONG_HOST_OR_USER, 12	ER_GROUP_REPLICATION_METADATA_MESSAGE_PAY
ER_GROUPING_ON_TIMESTAMP_IN_DST, 101	409
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR,	ER_GROUP_REPLICATION_METADATA_NO_VALID_DON
63	411
ER_GROUP_REPLICATION_CERTIFICATION_MODULE_FAILURE	ER_GROUP_REPLICATION_METADATA_PAYLOAD_DECO
410	409
ER_GROUP_REPLICATION_CERTIFIER_MESSAGE_LARGE	ER_GROUP_REPLICATION_METADATA_PAYLOAD_EMP
407	409
ER_GROUP_REPLICATION_COMMAND_FAILURE,	ER_GROUP_REPLICATION_METADATA_PROTOBUF_PA
83	408
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ERROR	ER_GROUP_REPLICATION_METADATA_READ_GTID_EX
64	409
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ERROR	ER_GROUP_REPLICATION_METADATA_SAVE_RECOVER
64	409
ER_GROUP_REPLICATION_COMPRESS_EXCEEDS_MAX_SIZE,	ER_GROUP_REPLICATION_METADATA_SENDER,
407	407
ER_GROUP_REPLICATION_COMPRESS_OUT_OF_MEMORY,	ER_GROUP_REPLICATION_METADATA_SENDER_IS_RE
408	407
ER_GROUP_REPLICATION_COMPRESS_PROCESS,	ER_GROUP_REPLICATION_METADATA_SEND_ERROR,
407	409
ER_GROUP_REPLICATION_CONFIGURATION, 63	ER_GROUP_REPLICATION_METADATA_SET_IN_RECOV
ER_GROUP_REPLICATION_DECOMPRESS_CORRUPTED,	410
408	ER_GROUP_REPLICATION_NO_CERTIFICATION_DONOR
ER_GROUP_REPLICATION_DECOMPRESS_END,	411
408	ER_GROUP_REPLICATION_PASSWORD_LENGTH,
	105

ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED,	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING,
166	373
ER_GROUP_REPLICATION_PROTOBUF_SERIALIZING_ERROR,	ER_GRP_RPL_APPLIER_ERROR_PACKET_RECEIVED,
409	412
ER_GROUP_REPLICATION_RECOVERY_ERROR_ADDED_TO_EXECUTED,	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR,
410	228
ER_GROUP_REPLICATION_RECOVERY_FETCHING_GTID_ERROR_PIPELINE_SET,	ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE,
410	246
ER_GROUP_REPLICATION_RECOVERY_METADATA_SENDER_NOT_AVAILABLE,	ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED,
410	246
ER_GROUP_REPLICATION_RECOVERY_SKIPPED_GTID_PRESENT,	ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE,
410	246
ER_GROUP_REPLICATION_RECOVERY_STOPPED_GTID_PRESENT,	ER_GRP_RPL_APPLIER_INITIALIZED,
411	244
ER_GROUP_REPLICATION_RUNNING, 63	ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLET,
	245
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_INTERRUPT,	ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING,
64	244
ER_GROUP_REPLICATION_TIMEOUT_ERROR_FETCHING_METADATA,	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED,
409	228
ER_GROUP_REPLICATION_UNKOWN_COMPRESSION_ERROR,	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN,
407	243
ER_GROUP_REPLICATION_USER_EMPTY_MSG,	ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED,
105	228
ER_GROUP_REPLICATION_USER_MANDATORY_MSG,	ER_GRP_RPL_APPLIER_THD_KILLED,
105	227
ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP,	ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL,
104	203
ER_GRP_PREFER_MOST_UPDATED_CONFIG_DIFFERENT,	ER_GRP_RPL_APPLIER_THD_SETUP_ERROR,
422	230
ER_GRP_PRIMARY_ELECTION_FATAL_PROCESS,	ER_GRP_RPL_APPLIER_THD_START_ERROR,
422	234
ER_GRP_PRIMARY_ELECTION_METHOD_MEMBER_WRONG,	ER_GRP_RPL_APPLIER_THD_STOP_ERROR,
422	234
ER_GRP_PRIMARY_ELECTION_METHOD_MOST_UPDATED,	ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT,
422	234
ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED,	ER_GRP_RPL_AUTO_INC_OFFSET_RESET,
244	235
ER_GRP_RPL_ADD_GRP_SID_TO_GRP_GTID_SID_MAP,	ER_GRP_RPL_AUTO_INC_OFFSET_SET,
228	235
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID,	ER_GRP_RPL_AUTO_INC_RESET,
236	235
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID,	ER_GRP_RPL_AUTO_INC_SET,
236	235
ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED,	ER_GRP_RPL_BINLOG_DISABLED,
236	245
ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED,	ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP,
236	233
ER_GRP_RPL_ADD_GTID_TO_GRP_GTID_EXECUTED,	ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED,
229	240
ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED,	ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG,
229	249
ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP,	ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED,
378	228
ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY,	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE,
237	239
ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED,	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE,
244	239
	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING,
	239
	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING,
	239
	ER_GRP_RPL_CANT_GENERATE_GTID,
	229
	ER_GRP_RPL_CANT_KILL_THREAD,
	356

ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED, 230	ER_GRP_RPL_DISABLE_READ_ONLY_FAILED, 232
ER_GRP_RPL_CANT_READ_GTID, 230	ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED, 231
ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM, 230	ER_GRP_RPL_DONOR_CONN_TERMINATION, 238
ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILED, 229	ER_GRP_RPL_DONOR_SERVER_CONN, 238
ER_GRP_RPL_CERTIFICATION_REC_PROCESS, 241	ER_GRP_RPL_DONOR_TRANS_INFO_ERROR, 229
ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR, 230	ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR, 378
ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED, 403	ER_GRP_RPL_ENABLE_READ_ONLY_FAILED, 232
ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED, 403	ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET, 229
ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED, 403	ER_GRP_RPL_ERROR_FETCHING_GTID_SET, 229
ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED, 231	ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO, 228
ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING, 338	ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION, 338
ER_GRP_RPL_CHECK_STATUS_TABLE, 238	ER_GRP_RPL_ERROR_MSG, 216
ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR, 355	ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL, 346
ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR, 355	ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING, 338
ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO, 244	ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSG, 228
ER_GRP_RPL_CONFIGURATION_ACTION_END, 339	ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER, 384
ER_GRP_RPL_CONFIGURATION_ACTION_ERROR, 339	ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER, 383
ER_GRP_RPL_CONFIGURATION_ACTION_KILLED, 339	ER_GRP_RPL_ERROR_STOPPING_CHANNELS, 228
ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION, 339	ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_RESOLUTION, 240
ER_GRP_RPL_CONFIGURATION_ACTION_START, 339	ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR, 238
ER_GRP_RPL_CONFIG_RECOVERY, 237	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER, 237
ER_GRP_RPL_CONFLICT_DETECTION_DISABLED, 230	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR, 237
ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE, 245	ER_GRP_RPL_EVENT_HANDLING_ERROR, 227
ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL, 236	ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE, 232
ER_GRP_RPL_CONN_KILLED, 404	ER_GRP_RPL_EXIT_GRP_GCS_ERROR, 248
ER_GRP_RPL_COPY_FROM_EMPTY_STRING, 237	ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING, 246
ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR, 228	ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBER_STATUS, 238
ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL, 238	ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS, 239
ER_GRP_RPL_CREATE_SESSION_UNABLE, 237	ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION, 242
ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM, 233	ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT, 242
ER_GRP_RPL_DEBUG_OPTIONS, 248	ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT, 240
ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFFERENT, 350	

ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE	ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE
243	112
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE	ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE
241	380
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET	ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET
240	380
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET	ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET
240	380
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP
244	380
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW
378	380
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER,	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER,
246	381
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE,	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE,
244	381
ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE	ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE
241	381
ER_GRP_RPL_FAILED_TO_INIT_HANDLER,	ER_GRP_RPL_FAILED_TO_INIT_HANDLER,
243	240
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION	ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION
345	235
ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE,	ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE,
390	236
ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT,	ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT,
238	236
ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME,	ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME,
244	235
ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID,	ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID,
378	235
ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER,	ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER,
243	236
ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER,	ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER,
243	236
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION,	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION,
240	236
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER,	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER,
243	235
ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_GRP	ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_GRP
239	249
ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE,	ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE,
243	240
ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE,	ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE,
242	245
ER_GRP_RPL_FAILED_TO_START_ON_BOOT,	ER_GRP_RPL_FAILED_TO_START_ON_BOOT,
243	246
ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS,	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS,
242	247
ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID,	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID,
241	247
ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL,	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL,
243	248
ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER,	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER,
244	248
ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER,	ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER,
244	249
ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER,	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER,
244	248
	ER_GRP_RPL_GCS_GR_ERROR_MSG, 249
	ER_GRP_RPL_GCS_INTERFACE_ERROR, 248
	ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION, 248

ER_GRP_RPL_GROUP_NAME_PARSE_ERROR,	ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGUR
228	376
ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_GRP,	ER_GRP_RPL_MEMBER_ACTION_DISABLED,
377	376
ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILURE,	ER_GRP_RPL_MEMBER_ACTION_ENABLED, 376
248	ER_GRP_RPL_MEMBER_ACTION_FAILURE, 375
ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF,	ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE,
246	375
ER_GRP_RPL_GRP_MEMBER_OFFLINE, 248	ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE
ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID,	376
245	ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON
ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID,	376
372	ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER,
ER_GRP_RPL_GRP_NAME_IS_TOO_LONG, 245	376
ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY,	ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE,
245	376
ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPLETE,	ER_GRP_RPL_MEMBER_ACTION_TRIGGERED,
377	375
ER_GRP_RPL_GTID_ALREADY_USED, 227	ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DE
ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR,	376
233	ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS,
ER_GRP_RPL_GTID_MODE_OFF, 245	376
ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR,	ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON
355	376
ER_GRP_RPL_GTID_SET_EXTRACT_ERROR,	ER_GRP_RPL_MEMBER_ADDED, 231
233	ER_GRP_RPL_MEMBER_ALREADY_EXISTS, 233
ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY,	ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP
346	234
ER_GRP_RPL_HAS_STARTED, 399	ER_GRP_RPL_MEMBER_CHANGE, 232
ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE,	ER_GRP_RPL_MEMBER_CONF_INFO, 242
230	ER_GRP_RPL_MEMBER_CONTACT_RESTORED,
ER_GRP_RPL_INTERNAL_QUERY, 237	231
ER_GRP_RPL_INVALID_BINLOG_FORMAT, 239	ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR,
ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL,	232
350	ER_GRP_RPL_MEMBER_EXPELLED, 232
ER_GRP_RPL_INVALID_DEBUG_OPTIONS, 248	ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST,
ER_GRP_RPL_INVALID_GTID_SET, 229	403
ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING,	ER_GRP_RPL_MEMBER_LEFT_GRP, 232
246	ER_GRP_RPL_MEMBER_NOT_FOUND, 237
ER_GRP_RPL_IS_STARTING, 364	ER_GRP_RPL_MEMBER_REMOVED, 231
ER_GRP_RPL_IS_STOPPED, 243	ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIB
ER_GRP_RPL_IS_STOPPING, 243	242
ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING,	ER_GRP_RPL_MEMBER_STATS_INFO, 249
338	ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR
ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING,	234
338	ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP,
ER_GRP_RPL_KILLED_FAILED_ID, 237	233
ER_GRP_RPL_KILLED_SESSION_ID, 237	ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE,
ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR,	233
233	ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE,
ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET,	353
245	ER_GRP_RPL_MEM_ONLINE, 231
ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP,	ER_GRP_RPL_MEM_REACHABLE, 231
331	ER_GRP_RPL_MEM_UNREACHABLE, 231
ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED,	ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR,
237	357
ER_GRP_RPL_MEMBER_ACTIONS_RESET, 377	ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE,
	101

ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR,	ER_GRP_RPL_PURGE_APPLIER_LOGS, 234
338	ER_GRP_RPL_PURGE_REC, 238
ER_GRP_RPL_MISSING_GRP_RPL_APPLIER,	ER_GRP_RPL_QUERY_FAIL, 237
230	ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_F
ER_GRP_RPL_MODULE_TERMINATE_ERROR,	241
245	ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS,
ER_GRP_RPL_MSG_DECODING_FAILED, 412	230
ER_GRP_RPL_MSG_DISCARDED, 230	ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING,
ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS,	TRANS_FAILED,
240	ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT,
ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED,	365
239	ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS,
ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_365,	ERROR_COMMAND_ERR,
380	ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID,
ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_365,	ERROR_CONN_ERR,
380	ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_EN
ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_SERVER_365,	ERROR_COMMAND_ERR,
406	ER_GRP_RPL_RECOVERY_EVAL_ERROR, 355
ER_GRP_RPL_NEEDS_INNODB_TABLE, 235	ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED,
ER_GRP_RPL_NEW_PRIMARY_ELECTED, 232	243
ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED,	ER_GRP_RPL_RECOVERY_STRAT_CHOICE, 356
236	ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED,
ER_GRP_RPL_NO_POSSIBLE_RECOVERY, 356	356
ER_GRP_RPL_NO_STAGE_SERVICE, 339	ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD,
ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM,	356
232	ER_GRP_RPL_RECOVERY_STRAT_FALLBACK,
ER_GRP_RPL_NO_VALID_DONOR, 237	356
ER_GRP_RPL_NULL_PACKET, 230	ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK,
ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE, 240	356
ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_RASH,	ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_FINISH
239	415
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP,	415
384	ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_START
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP,	415
397	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCY
ER_GRP_RPL_PIPELINE_CREATE_FAILED, 249	345
ER_GRP_RPL_PIPELINE_FLUSH_FAIL, 249	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREP
ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ,	345
249	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFO
ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE,	345
249	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCY
ER_GRP_RPL_PLUGIN_ABORT, 336	345
ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE,	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_S
241	ON_SERVER_START,
ER_GRP_RPL_PREEMPTIVE_GARBAGE_COLLECTION,	ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPAR
414	411
ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR,	DIFF_FROM_GRP,
339	ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT,
ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR,	250
339	ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED,
ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED,	234
235	ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN,
ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP,	250
231	ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT,
ER_GRP_RPL_PROCESS_GTID_SET_ERROR,	249
230	ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED,
ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_245,	ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT
230	ERROR,

ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER,	ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED,
235	247
ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN,	ER_GRP_RPL_SRV_BLOCKED, 231
235	ER_GRP_RPL_SRV_BLOCKED_FOR_SECS, 231
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE,	ER_GRP_RPL_SRV_NOT_ONLINE, 231
356	ER_GRP_RPL_SRV_ONLINE, 231
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER,	ER_GRP_RPL_SRV_PRIMARY_MEM, 232
381	ER_GRP_RPL_SRV_SECONDARY_MEM, 232
ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE,	ER_GRP_RPL_SSL_DISABLED, 244
242	ER_GRP_RPL_STARTED_AUTO_REJOIN, 350
ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR,	ER_GRP_RPL_STARTING_GRP_REC, 238
234	ER_GRP_RPL_START_FAILED, 233
ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER,	ER_GRP_RPL_START_GRP_RPL_FAILED, 236
234	ER_GRP_RPL_STOPPING_GRP_REC, 238
ER_GRP_RPL_SEND_STATS_ERROR, 249	ER_GRP_RPL_SUPER_READ_OFF, 237
ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED,	ER_GRP_RPL_SUPER_READ_ON, 236
344	ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR,
ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED,	232
346	ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP,
ER_GRP_RPL_SERVER_ALREADY_LEFT, 242	242
ER_GRP_RPL_SERVER_CONN_ERROR, 229	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_RE,
ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING,	369
242	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN,
ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS,	250
357	ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_O,
ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS,	232
248	ER_GRP_RPL_TRANS_GREATER_THAN_GRP,
ER_GRP_RPL_SERVER_UDF_ERROR, 339	233
ER_GRP_RPL_SESSION_OPEN_FAILED, 232	ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP,
ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGING,	265
248	ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT,
ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER,	240
383	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FRO,
ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER,	234
383	ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AF,
ER_GRP_RPL_SET_STABLE_TRANS_ERROR,	345
230	ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HA,
ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED,	345
245	WITH UPDATE EVERYWHERE,
ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED,	346
247	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAIL,
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX,	349
247	ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUT,
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD,	346
247	ER_GRP_RPL_UDF_ERROR, 101
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY,	ER_GRP_RPL_UDF_REGISTER_ERROR, 339
247	ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR,
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER,	308
247	ER_GRP_RPL_UDF_UNREGISTER_ERROR, 339
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STABLE_TO_CERTIFY_PLUGIN_TRANS,	241
247	ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET,
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER,	249
247	ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT,
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONNECT,	249
247	ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC,
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE,	241
247	

ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS,	ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED,
240	92
ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_FAILED,	ER_GR_ELECTED_PRIMARY_GTID_INFORMATION,
245	360
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_THREAD,	ER_GR_HOLD_KILLED, 91
238	ER_GR_HOLD_MEMBER_STATUS_ERROR, 91
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_THREAD,	ER_GR_HOLD_WAIT_TIMEOUT, 91
238	ER_GR_RM_CHANNEL_LAG_QUERY_EXECUTION_FAILED,
ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE,	MODE,
241	ER_GR_RM_CHANNEL_LAG_QUERY_EXECUTION_SUCCESS,
ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS,	421
241	ER_GR_RM_GR_MEMBER_NOT_REMOVED_APPLIER_THRESHOLD,
ER_GRP_RPL_UNBLOCK_WAITING_THD, 228	421
ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED,	ER_GR_MEMBER_NOT_REMOVED_APPLIER_THRESHOLD,
246	421
ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER,	ER_GR_MEMBER_MEMBER_NOT_REMOVED_MEMORY_THRESHOLD,
248	422
ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION,	ER_GR_RM_GR_MEMBER_NOT_REMOVED_MEMORY_THRESHOLD,
239	421
ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR,	ER_GR_RM_GR_MEMBER_NOT_REMOVED_RECOVERY_THRESHOLD,
228	421
ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EXECUTED_ERROR,	ER_GR_RM_GR_MEMBER_NOT_REMOVED_RECOVERY_THRESHOLD,
378	421
ER_GRP_RPL_UPDATE_GTID_SET_ERROR, 229	ER_GR_RM_GR_MGMT_SERVICE_ACQUIRE_FAILED,
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION,	421ERROR,
229	ER_GR_RM_MEMBER_LEAVING_APPLIER_THRESHOLD_HIT,
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED,	422
236	ER_GR_RM_MEMBER_LEAVING_MEMORY_THRESHOLD_HIT,
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERSION,	422ERROR,
229	ER_GR_RM_MEMBER_LEAVING_RECOVERY_THRESHOLD_HIT,
ER_GRP_RPL_VCLE_NOT_BEING_LOGGED, 408	422
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP_RPL,	ER_GR_RM_MEMORY_STATS_FETCH_FAILED,
377	420
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE,	ER_GR_RM_MEMORY_STATS_FETCH_SUCCESS,
111	420
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID,	ER_GTID_ALREADY_ADDED_BY_USER, 166
377	ER_GTID_EXECUTED_WAS_CHANGED, 54
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER,	ER_GTID_EXECUTED_WAS_UPDATED, 193
377	ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME,
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR,	50
378	ER_GTID_MODE_OFF, 61
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME,	ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY,
377	49
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE,	ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST,
242	49
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED,	ER_GTID_NEXT_TAG_GTID_MODE_OFF, 124
345	ER_GTID_NEXT_TYPE_UNDEFINED_GTID, 53
ER_GRP_RPL_WHILE_SENDING_MSG_REC, 241	ER_GTID_PURGED_WAS_CHANGED, 54
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED,	ER_GTID_PURGED_WAS_UPDATED, 193
239	ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION,
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE,	91FAILED,
240	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND,
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN,	57
92	ER_GTID_UNSAFE_CREATE_SELECT, 50
ER_GRP_TRX_CONSISTENCY_BEFORE, 92	ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE,
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED,	50
93	ER_HANDLERTON_OOM, 156
	ER_HANDSHAKE_ERROR, 5

ER_HEALTH_ERROR, 372	ER_IB_ERR_CORRUPT_TABLESPACE_UNRECOVERABLE, 411
ER_HEALTH_INFO, 372	ER_IB_ERR_DDL_LOG_INSERT_FAILURE, 366
ER_HEALTH_WARNING, 372	ER_IB_ERR_FOUND_N_DUPLICATE_KEYS, 368
ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1, 372	ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER, 369
ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2, 373	ER_IB_ERR_INDEX_DUPLICATE_KEY, 368
ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3, 373	ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER, 368
ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1, 383	ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW, 368
ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2, 383	ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER, 368
ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3, 383	ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED, 379
ER_HOSTNAME, 31	ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUFFER, 364
ER_HOSTNAME_DOESNT_RESOLVE_TO, 144	ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT, 364
ER_HOSTNAME_RESEMBLES_IPV4, 143	ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED, 364
ER_HOSTNAME_TOO_LONG, 105	ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN, 261
ER_HOSTNAME_TRUNCATED, 366	ER_IB_ERR_PARALLEL_READ_OOM, 369
ER_HOST_IS_BLOCKED, 11	ER_IB_ERR_RECOVERY_REDO_DISABLED, 365
ER_HOST_NOT_PRIVILEGED, 11	ER_IB_ERR_SCHED_SETAFFINITY_FAILED, 367
ER_HYPERGRAPH_NOT_SUPPORTED_YET, 108	ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMIINDEX, 367
ER_IB_BUFFER_POOL_FULL, 394	ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST, 367
ER_IB_BUFFER_POOL_OVERUSE, 394	ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY, 367
ER_IB_BULK_FLUSHER_INFO, 394	ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATAFILESPACE, 367
ER_IB_BULK_FLUSHER_PUNCH_HOLE, 404	ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATAFILESPACE, 367
ER_IB_BULK_LOAD_MERGE_FAIL, 396	ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE, 367
ER_IB_BULK_LOAD_STATS_INFO, 416	ER_IB_ERR_ZLIB_BUF_ERROR, 368
ER_IB_BULK_LOAD_STATS_WARN, 411	ER_IB_ERR_ZLIB_DATA_ERROR, 368
ER_IB_BULK_LOAD_SUBTREE_INFO, 394	ER_IB_ERR_ZLIB_MEM_ERROR, 368
ER_IB_BULK_LOAD_THREAD_FAIL, 396	ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED, 368
ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACE, 366	ER_IB_ERR_ZLIB_UNKNOWN_ERROR, 368
ER_IB_CLONE_GTID_PERSIST, 265	ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE, 367
ER_IB_CLONE_INTERNAL, 264	ER_IB_FIXED_PAGE_ID, 407
ER_IB_CLONE_NON_INNODB_TABLE, 355	ER_IB_HIDDEN_NAME_CONFLICT, 397
ER_IB_CLONE_OPERATION, 355	ER_IB_IMPORT_INDEX_METADATA_READ_FAILED, 311
ER_IB_CLONE_PUNCH_HOLE, 265	ER_IB_IMPORT_START_CFG_NAME, 315
ER_IB_CLONE_RESTART, 355	ER_IB_INDEX_BUILDER_DONE, 398
ER_IB_CLONE_SQL, 265	ER_IB_INDEX_BUILDER_INIT, 398
ER_IB_CLONE_START_STOP, 355	ER_IB_INDEX_LOADER_DONE, 398
ER_IB_CLONE_STATUS_FILE, 265	ER_IB_INDEX_LOG_VERSION_MISMATCH, 398
ER_IB_CLONE_TIMEOUT, 265	ER_IB_INDEX_PART_TOO_LONG, 403
ER_IB_CLONE_USER_DATA, 355	ER_IB_INNODB_TBSP_OUT_OF_SPACE, 373
ER_IB_CLONE_VALIDATE, 265	ER_IB_INSERT_DELETE_SCHEMA_DIRECTORY_DDL_LOG_INDEX, 404
ER_IB_DBLWR_BYTES_INFO, 386	ER_IB_INSTANT_ADD_DROP_COLUMN_NOT_ALLOWED, 404
ER_IB_DBLWR_DECOMPRESS_FAILED, 370	
ER_IB_DBLWR_DECRYPT_FAILED, 370	
ER_IB_DBLWR_KEY_MISSING, 370	
ER_IB_DDL_CONVERT_HEAP_NOT_FOUND, 402	
ER_IB_DELETE_SCHEMA_DIR, 417	
ER_IB_DICT_INVALID_COLUMN_POSITION, 397	
ER_IB_DICT_LOG_TABLE_INFO, 397	
ER_IB_DUPLICATE_KEY, 394	
ER_IB_ERR_ACCESSING_OUT_OF_BOUND_FIELD_IN_INDEX, 325	

ER_IB_INSTANT_ADD_NOT_POSSIBLE, 404	ER_IB_MSG_1042, 317
ER_IB_LOAD_BULK_CONCURRENCY_REDUCED, 396	ER_IB_MSG_1043, 317
ER_IB_LOB_ROLLBACK_INDEX_LEN, 359	ER_IB_MSG_1044, 317
ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION, 366	ER_IB_MSG_1045, 317
ER_IB_LONG_AHI_DISABLE_WAIT, 266	ER_IB_MSG_1046, 317
ER_IB_LONG_ROLLBACK, 414	ER_IB_MSG_1047, 317
ER_IB_LONG_ROLLBACK_FULL, 414	ER_IB_MSG_1048, 317
ER_IB_MSG_0, 256	ER_IB_MSG_1049, 317
ER_IB_MSG_1, 256	ER_IB_MSG_105, 262
ER_IB_MSG_10, 257	ER_IB_MSG_1051, 317
ER_IB_MSG_100, 262	ER_IB_MSG_1052, 317
ER_IB_MSG_1000, 314	ER_IB_MSG_1053, 317
ER_IB_MSG_1001, 314	ER_IB_MSG_1054, 317
ER_IB_MSG_1002, 314	ER_IB_MSG_1055, 317
ER_IB_MSG_1003, 314	ER_IB_MSG_1056, 317
ER_IB_MSG_1004, 314	ER_IB_MSG_1057, 317
ER_IB_MSG_1005, 314	ER_IB_MSG_1058, 318
ER_IB_MSG_1006, 314	ER_IB_MSG_1059, 318
ER_IB_MSG_1007, 314	ER_IB_MSG_106, 262
ER_IB_MSG_1008, 314	ER_IB_MSG_1060, 318
ER_IB_MSG_1009, 315	ER_IB_MSG_1065, 318
ER_IB_MSG_101, 262	ER_IB_MSG_107, 262
ER_IB_MSG_1010, 315	ER_IB_MSG_1070, 318
ER_IB_MSG_1011, 315	ER_IB_MSG_1071, 318
ER_IB_MSG_1012, 315	ER_IB_MSG_1072, 318
ER_IB_MSG_1013, 315	ER_IB_MSG_1073, 318
ER_IB_MSG_1015, 315	ER_IB_MSG_1074, 319
ER_IB_MSG_1016, 315	ER_IB_MSG_1075, 319
ER_IB_MSG_1017, 315	ER_IB_MSG_1076, 319
ER_IB_MSG_1018, 315	ER_IB_MSG_1077, 319
ER_IB_MSG_1019, 315	ER_IB_MSG_1078, 319
ER_IB_MSG_102, 262	ER_IB_MSG_1079, 319
ER_IB_MSG_1020, 315	ER_IB_MSG_108, 262
ER_IB_MSG_1021, 315	ER_IB_MSG_1080, 319
ER_IB_MSG_1022, 315	ER_IB_MSG_1081, 319
ER_IB_MSG_1023, 315	ER_IB_MSG_1082, 319
ER_IB_MSG_1024, 315	ER_IB_MSG_1083, 319
ER_IB_MSG_1025, 316	ER_IB_MSG_1086, 319
ER_IB_MSG_1026, 316	ER_IB_MSG_1087, 319
ER_IB_MSG_1027, 316	ER_IB_MSG_1088, 319
ER_IB_MSG_1028, 316	ER_IB_MSG_1089, 319
ER_IB_MSG_1029, 316	ER_IB_MSG_109, 262
ER_IB_MSG_103, 262	ER_IB_MSG_1090, 320
ER_IB_MSG_1030, 316	ER_IB_MSG_1091, 320
ER_IB_MSG_1031, 316	ER_IB_MSG_1092, 320
ER_IB_MSG_1032, 316	ER_IB_MSG_1093, 320
ER_IB_MSG_1033, 316	ER_IB_MSG_1097, 320
ER_IB_MSG_1034, 316	ER_IB_MSG_1098, 320
ER_IB_MSG_1035, 316	ER_IB_MSG_1099, 320
ER_IB_MSG_1036, 316	ER_IB_MSG_11, 257
ER_IB_MSG_1037, 316	ER_IB_MSG_110, 262
ER_IB_MSG_1038, 316	ER_IB_MSG_1100, 320
ER_IB_MSG_1039, 316	ER_IB_MSG_1101, 320
ER_IB_MSG_104, 262	ER_IB_MSG_1102, 320
ER_IB_MSG_1040, 316	ER_IB_MSG_1103, 320
ER_IB_MSG_1041, 317	ER_IB_MSG_1104, 320
	ER_IB_MSG_1105, 320
	ER_IB_MSG_1107, 320

ER_IB_MSG_1108, 320	ER_IB_MSG_1186, 325
ER_IB_MSG_1109, 321	ER_IB_MSG_1187, 325
ER_IB_MSG_111, 262	ER_IB_MSG_1188, 325
ER_IB_MSG_1110, 321	ER_IB_MSG_1189, 325
ER_IB_MSG_1111, 321	ER_IB_MSG_119, 263
ER_IB_MSG_1112, 321	ER_IB_MSG_1191, 325
ER_IB_MSG_1113, 321	ER_IB_MSG_1192, 326
ER_IB_MSG_1114, 321	ER_IB_MSG_1193, 326
ER_IB_MSG_1115, 321	ER_IB_MSG_1194, 326
ER_IB_MSG_1116, 321	ER_IB_MSG_1195, 326
ER_IB_MSG_1117, 321	ER_IB_MSG_1196, 326
ER_IB_MSG_1119, 321	ER_IB_MSG_1197, 326
ER_IB_MSG_112, 263	ER_IB_MSG_1198, 326
ER_IB_MSG_1120, 321	ER_IB_MSG_1199, 326
ER_IB_MSG_1121, 321	ER_IB_MSG_12, 257
ER_IB_MSG_1122, 321	ER_IB_MSG_120, 263
ER_IB_MSG_1123, 321	ER_IB_MSG_1200, 326
ER_IB_MSG_1124, 321	ER_IB_MSG_1201, 326
ER_IB_MSG_1125, 321	ER_IB_MSG_1202, 326
ER_IB_MSG_1126, 322	ER_IB_MSG_1203, 326
ER_IB_MSG_1127, 322	ER_IB_MSG_1204, 326
ER_IB_MSG_1128, 322	ER_IB_MSG_1205, 326
ER_IB_MSG_1129, 322	ER_IB_MSG_1206, 326
ER_IB_MSG_1130, 322	ER_IB_MSG_1207, 326
ER_IB_MSG_1131, 322	ER_IB_MSG_1208, 327
ER_IB_MSG_1132, 322	ER_IB_MSG_1209, 327
ER_IB_MSG_1133, 322	ER_IB_MSG_121, 263
ER_IB_MSG_1134, 322	ER_IB_MSG_1210, 327
ER_IB_MSG_1139, 322	ER_IB_MSG_1211, 327
ER_IB_MSG_1142, 323	ER_IB_MSG_1212, 327
ER_IB_MSG_1145, 323	ER_IB_MSG_1213, 327
ER_IB_MSG_1146, 323	ER_IB_MSG_1214, 327
ER_IB_MSG_1147, 323	ER_IB_MSG_1217, 327
ER_IB_MSG_1148, 323	ER_IB_MSG_1218, 327
ER_IB_MSG_1149, 323	ER_IB_MSG_1219, 327
ER_IB_MSG_1150, 323	ER_IB_MSG_122, 263
ER_IB_MSG_1151, 323	ER_IB_MSG_1220, 327
ER_IB_MSG_1152, 323	ER_IB_MSG_1221, 327
ER_IB_MSG_1154, 323	ER_IB_MSG_1222, 327
ER_IB_MSG_1155, 323	ER_IB_MSG_1223, 328
ER_IB_MSG_1156, 323	ER_IB_MSG_1224, 328
ER_IB_MSG_1157, 324	ER_IB_MSG_1225, 328
ER_IB_MSG_1158, 324	ER_IB_MSG_1226, 328
ER_IB_MSG_1159, 324	ER_IB_MSG_1227, 328
ER_IB_MSG_1160, 324	ER_IB_MSG_1228, 328
ER_IB_MSG_1161, 324	ER_IB_MSG_1229, 328
ER_IB_MSG_1162, 324	ER_IB_MSG_123, 263
ER_IB_MSG_1163, 324	ER_IB_MSG_1231, 328
ER_IB_MSG_1164, 324	ER_IB_MSG_1233, 328
ER_IB_MSG_1165, 324	ER_IB_MSG_1235, 328
ER_IB_MSG_1177, 325	ER_IB_MSG_1238, 328
ER_IB_MSG_1178, 325	ER_IB_MSG_1239, 328
ER_IB_MSG_1179, 325	ER_IB_MSG_124, 263
ER_IB_MSG_1180, 325	ER_IB_MSG_1241, 329
ER_IB_MSG_1181, 325	ER_IB_MSG_1245, 329
ER_IB_MSG_1182, 325	ER_IB_MSG_1246, 329
ER_IB_MSG_1183, 325	ER_IB_MSG_1247, 329
ER_IB_MSG_1185, 325	ER_IB_MSG_1248, 329

ER_IB_MSG_1249, 329
ER_IB_MSG_125, 263
ER_IB_MSG_1250, 329
ER_IB_MSG_1251, 329
ER_IB_MSG_1253, 329
ER_IB_MSG_1255, 329
ER_IB_MSG_1256, 329
ER_IB_MSG_1257, 329
ER_IB_MSG_1258, 330
ER_IB_MSG_1259, 330
ER_IB_MSG_126, 263
ER_IB_MSG_1260, 330
ER_IB_MSG_1261, 330
ER_IB_MSG_1262, 330
ER_IB_MSG_1263, 330
ER_IB_MSG_1266, 330
ER_IB_MSG_1268, 330
ER_IB_MSG_1269, 330
ER_IB_MSG_127, 263
ER_IB_MSG_1272, 336
ER_IB_MSG_1273, 336
ER_IB_MSG_1274, 337
ER_IB_MSG_1275, 337
ER_IB_MSG_1277, 337
ER_IB_MSG_128, 263
ER_IB_MSG_1280, 337
ER_IB_MSG_1281, 337
ER_IB_MSG_1282, 337
ER_IB_MSG_1283, 338
ER_IB_MSG_1284, 338
ER_IB_MSG_1285, 353
ER_IB_MSG_129, 263
ER_IB_MSG_13, 257
ER_IB_MSG_130, 263
ER_IB_MSG_131, 263
ER_IB_MSG_132, 263
ER_IB_MSG_133, 263
ER_IB_MSG_134, 264
ER_IB_MSG_135, 264
ER_IB_MSG_1357, 367
ER_IB_MSG_1358, 367
ER_IB_MSG_1359, 367
ER_IB_MSG_136, 264
ER_IB_MSG_137, 264
ER_IB_MSG_1372, 368
ER_IB_MSG_1373, 368
ER_IB_MSG_1374, 368
ER_IB_MSG_1375, 368
ER_IB_MSG_138, 264
ER_IB_MSG_1381, 368
ER_IB_MSG_139, 264
ER_IB_MSG_14, 257
ER_IB_MSG_140, 264
ER_IB_MSG_141, 264
ER_IB_MSG_142, 264
ER_IB_MSG_143, 264
ER_IB_MSG_144, 264
ER_IB_MSG_145, 264

ER_IB_MSG_146, 264
ER_IB_MSG_147, 264
ER_IB_MSG_148, 264
ER_IB_MSG_15, 257
ER_IB_MSG_156, 265
ER_IB_MSG_157, 265
ER_IB_MSG_158, 265
ER_IB_MSG_159, 265
ER_IB_MSG_16, 257
ER_IB_MSG_160, 265
ER_IB_MSG_161, 265
ER_IB_MSG_162, 265
ER_IB_MSG_163, 265
ER_IB_MSG_164, 265
ER_IB_MSG_165, 265
ER_IB_MSG_166, 266
ER_IB_MSG_167, 266
ER_IB_MSG_168, 266
ER_IB_MSG_169, 266
ER_IB_MSG_17, 257
ER_IB_MSG_170, 266
ER_IB_MSG_171, 266
ER_IB_MSG_172, 266
ER_IB_MSG_173, 266
ER_IB_MSG_174, 266
ER_IB_MSG_175, 266
ER_IB_MSG_177, 266
ER_IB_MSG_178, 266
ER_IB_MSG_179, 266
ER_IB_MSG_18, 257
ER_IB_MSG_180, 266
ER_IB_MSG_182, 266
ER_IB_MSG_183, 267
ER_IB_MSG_184, 267
ER_IB_MSG_187, 267
ER_IB_MSG_188, 267
ER_IB_MSG_189, 267
ER_IB_MSG_19, 257
ER_IB_MSG_190, 267
ER_IB_MSG_191, 267
ER_IB_MSG_192, 267
ER_IB_MSG_193, 267
ER_IB_MSG_194, 267
ER_IB_MSG_195, 267
ER_IB_MSG_196, 267
ER_IB_MSG_197, 267
ER_IB_MSG_198, 267
ER_IB_MSG_199, 267
ER_IB_MSG_2, 256
ER_IB_MSG_20, 257
ER_IB_MSG_200, 267
ER_IB_MSG_201, 268
ER_IB_MSG_202, 268
ER_IB_MSG_203, 268
ER_IB_MSG_204, 268
ER_IB_MSG_205, 268
ER_IB_MSG_206, 268
ER_IB_MSG_207, 268

ER_IB_MSG_208, 268
ER_IB_MSG_209, 268
ER_IB_MSG_21, 257
ER_IB_MSG_210, 268
ER_IB_MSG_211, 268
ER_IB_MSG_212, 268
ER_IB_MSG_213, 268
ER_IB_MSG_214, 268
ER_IB_MSG_215, 268
ER_IB_MSG_216, 268
ER_IB_MSG_217, 269
ER_IB_MSG_218, 269
ER_IB_MSG_219, 269
ER_IB_MSG_22, 258
ER_IB_MSG_220, 269
ER_IB_MSG_221, 269
ER_IB_MSG_222, 269
ER_IB_MSG_223, 269
ER_IB_MSG_224, 269
ER_IB_MSG_225, 269
ER_IB_MSG_226, 269
ER_IB_MSG_229, 269
ER_IB_MSG_23, 258
ER_IB_MSG_230, 269
ER_IB_MSG_231, 269
ER_IB_MSG_232, 269
ER_IB_MSG_233, 269
ER_IB_MSG_234, 269
ER_IB_MSG_235, 270
ER_IB_MSG_236, 270
ER_IB_MSG_237, 270
ER_IB_MSG_238, 270
ER_IB_MSG_239, 270
ER_IB_MSG_24, 258
ER_IB_MSG_240, 270
ER_IB_MSG_241, 270
ER_IB_MSG_242, 270
ER_IB_MSG_243, 270
ER_IB_MSG_244, 270
ER_IB_MSG_245, 270
ER_IB_MSG_246, 270
ER_IB_MSG_247, 270
ER_IB_MSG_248, 270
ER_IB_MSG_249, 270
ER_IB_MSG_25, 258
ER_IB_MSG_250, 270
ER_IB_MSG_251, 271
ER_IB_MSG_252, 271
ER_IB_MSG_253, 271
ER_IB_MSG_254, 271
ER_IB_MSG_255, 271
ER_IB_MSG_256, 271
ER_IB_MSG_257, 271
ER_IB_MSG_258, 271
ER_IB_MSG_259, 271
ER_IB_MSG_26, 258
ER_IB_MSG_260, 271
ER_IB_MSG_261, 271

ER_IB_MSG_262, 271
ER_IB_MSG_263, 271
ER_IB_MSG_264, 271
ER_IB_MSG_265, 271
ER_IB_MSG_266, 271
ER_IB_MSG_267, 272
ER_IB_MSG_268, 272
ER_IB_MSG_269, 272
ER_IB_MSG_27, 258
ER_IB_MSG_270, 272
ER_IB_MSG_271, 272
ER_IB_MSG_272, 272
ER_IB_MSG_273, 272
ER_IB_MSG_278, 272
ER_IB_MSG_28, 258
ER_IB_MSG_280, 272
ER_IB_MSG_281, 272
ER_IB_MSG_282, 272
ER_IB_MSG_283, 272
ER_IB_MSG_284, 272
ER_IB_MSG_285, 272
ER_IB_MSG_287, 273
ER_IB_MSG_288, 273
ER_IB_MSG_289, 273
ER_IB_MSG_29, 258
ER_IB_MSG_291, 273
ER_IB_MSG_292, 273
ER_IB_MSG_293, 273
ER_IB_MSG_294, 273
ER_IB_MSG_295, 273
ER_IB_MSG_296, 273
ER_IB_MSG_297, 273
ER_IB_MSG_298, 273
ER_IB_MSG_299, 273
ER_IB_MSG_3, 256
ER_IB_MSG_30, 258
ER_IB_MSG_300, 273
ER_IB_MSG_301, 273
ER_IB_MSG_303, 274
ER_IB_MSG_304, 274
ER_IB_MSG_305, 274
ER_IB_MSG_306, 274
ER_IB_MSG_307, 274
ER_IB_MSG_308, 274
ER_IB_MSG_309, 274
ER_IB_MSG_310, 274
ER_IB_MSG_311, 274
ER_IB_MSG_312, 274
ER_IB_MSG_313, 274
ER_IB_MSG_314, 274
ER_IB_MSG_315, 274
ER_IB_MSG_316, 274
ER_IB_MSG_317, 275
ER_IB_MSG_318, 275
ER_IB_MSG_319, 275
ER_IB_MSG_32, 258
ER_IB_MSG_320, 275
ER_IB_MSG_321, 275

ER_IB_MSG_322, 275
ER_IB_MSG_323, 275
ER_IB_MSG_324, 275
ER_IB_MSG_325, 275
ER_IB_MSG_326, 275
ER_IB_MSG_328, 275
ER_IB_MSG_329, 275
ER_IB_MSG_33, 258
ER_IB_MSG_330, 275
ER_IB_MSG_331, 275
ER_IB_MSG_332, 275
ER_IB_MSG_333, 275
ER_IB_MSG_334, 276
ER_IB_MSG_335, 276
ER_IB_MSG_336, 276
ER_IB_MSG_337, 276
ER_IB_MSG_338, 276
ER_IB_MSG_339, 276
ER_IB_MSG_34, 258
ER_IB_MSG_340, 276
ER_IB_MSG_341, 276
ER_IB_MSG_342, 276
ER_IB_MSG_343, 276
ER_IB_MSG_344, 276
ER_IB_MSG_345, 276
ER_IB_MSG_346, 276
ER_IB_MSG_347, 276
ER_IB_MSG_348, 276
ER_IB_MSG_349, 276
ER_IB_MSG_35, 258
ER_IB_MSG_350, 277
ER_IB_MSG_354, 277
ER_IB_MSG_355, 277
ER_IB_MSG_357, 277
ER_IB_MSG_358, 277
ER_IB_MSG_359, 277
ER_IB_MSG_36, 258
ER_IB_MSG_360, 277
ER_IB_MSG_361, 277
ER_IB_MSG_362, 277
ER_IB_MSG_364, 277
ER_IB_MSG_365, 277
ER_IB_MSG_367, 277
ER_IB_MSG_368, 277
ER_IB_MSG_369, 277
ER_IB_MSG_37, 258
ER_IB_MSG_370, 278
ER_IB_MSG_371, 278
ER_IB_MSG_372, 278
ER_IB_MSG_373, 278
ER_IB_MSG_374, 278
ER_IB_MSG_375, 278
ER_IB_MSG_376, 278
ER_IB_MSG_377, 278
ER_IB_MSG_378, 278
ER_IB_MSG_379, 278
ER_IB_MSG_38, 258
ER_IB_MSG_380, 278

ER_IB_MSG_381, 278
ER_IB_MSG_382, 278
ER_IB_MSG_383, 278
ER_IB_MSG_384, 278
ER_IB_MSG_385, 278
ER_IB_MSG_386, 279
ER_IB_MSG_387, 279
ER_IB_MSG_39, 259
ER_IB_MSG_390, 279
ER_IB_MSG_391, 279
ER_IB_MSG_392, 279
ER_IB_MSG_393, 279
ER_IB_MSG_394, 279
ER_IB_MSG_395, 279
ER_IB_MSG_396, 279
ER_IB_MSG_397, 279
ER_IB_MSG_398, 279
ER_IB_MSG_399, 279
ER_IB_MSG_4, 256
ER_IB_MSG_40, 259
ER_IB_MSG_401, 279
ER_IB_MSG_402, 279
ER_IB_MSG_403, 280
ER_IB_MSG_404, 280
ER_IB_MSG_405, 280
ER_IB_MSG_406, 280
ER_IB_MSG_407, 280
ER_IB_MSG_408, 280
ER_IB_MSG_409, 280
ER_IB_MSG_41, 259
ER_IB_MSG_410, 280
ER_IB_MSG_411, 280
ER_IB_MSG_412, 280
ER_IB_MSG_413, 280
ER_IB_MSG_414, 280
ER_IB_MSG_415, 280
ER_IB_MSG_416, 280
ER_IB_MSG_417, 280
ER_IB_MSG_418, 280
ER_IB_MSG_419, 281
ER_IB_MSG_42, 259
ER_IB_MSG_420, 281
ER_IB_MSG_421, 281
ER_IB_MSG_422, 281
ER_IB_MSG_423, 281
ER_IB_MSG_424, 281
ER_IB_MSG_425, 281
ER_IB_MSG_426, 281
ER_IB_MSG_427, 281
ER_IB_MSG_428, 281
ER_IB_MSG_429, 281
ER_IB_MSG_43, 259
ER_IB_MSG_430, 281
ER_IB_MSG_431, 281
ER_IB_MSG_432, 281
ER_IB_MSG_433, 281
ER_IB_MSG_434, 281
ER_IB_MSG_435, 282

ER_IB_MSG_436, 282
ER_IB_MSG_437, 282
ER_IB_MSG_438, 282
ER_IB_MSG_439, 282
ER_IB_MSG_44, 259
ER_IB_MSG_440, 282
ER_IB_MSG_441, 282
ER_IB_MSG_442, 282
ER_IB_MSG_443, 282
ER_IB_MSG_445, 282
ER_IB_MSG_446, 282
ER_IB_MSG_447, 282
ER_IB_MSG_448, 282
ER_IB_MSG_449, 282
ER_IB_MSG_45, 259
ER_IB_MSG_450, 282
ER_IB_MSG_451, 282
ER_IB_MSG_452, 283
ER_IB_MSG_453, 283
ER_IB_MSG_454, 283
ER_IB_MSG_455, 283
ER_IB_MSG_456, 283
ER_IB_MSG_457, 283
ER_IB_MSG_458, 283
ER_IB_MSG_459, 283
ER_IB_MSG_46, 259
ER_IB_MSG_460, 283
ER_IB_MSG_461, 283
ER_IB_MSG_462, 283
ER_IB_MSG_463, 283
ER_IB_MSG_464, 283
ER_IB_MSG_465, 283
ER_IB_MSG_466, 283
ER_IB_MSG_467, 283
ER_IB_MSG_468, 284
ER_IB_MSG_469, 284
ER_IB_MSG_47, 259
ER_IB_MSG_470, 284
ER_IB_MSG_471, 284
ER_IB_MSG_472, 284
ER_IB_MSG_473, 284
ER_IB_MSG_474, 284
ER_IB_MSG_475, 284
ER_IB_MSG_476, 284
ER_IB_MSG_477, 284
ER_IB_MSG_478, 284
ER_IB_MSG_479, 284
ER_IB_MSG_48, 259
ER_IB_MSG_480, 284
ER_IB_MSG_481, 284
ER_IB_MSG_482, 284
ER_IB_MSG_483, 284
ER_IB_MSG_484, 285
ER_IB_MSG_485, 285
ER_IB_MSG_486, 285
ER_IB_MSG_487, 285
ER_IB_MSG_488, 285
ER_IB_MSG_489, 285

ER_IB_MSG_49, 259
ER_IB_MSG_490, 285
ER_IB_MSG_491, 285
ER_IB_MSG_492, 285
ER_IB_MSG_493, 285
ER_IB_MSG_494, 285
ER_IB_MSG_495, 285
ER_IB_MSG_496, 285
ER_IB_MSG_497, 285
ER_IB_MSG_498, 285
ER_IB_MSG_499, 285
ER_IB_MSG_5, 256
ER_IB_MSG_50, 259
ER_IB_MSG_500, 286
ER_IB_MSG_501, 286
ER_IB_MSG_502, 286
ER_IB_MSG_503, 286
ER_IB_MSG_504, 286
ER_IB_MSG_505, 286
ER_IB_MSG_506, 286
ER_IB_MSG_507, 286
ER_IB_MSG_508, 286
ER_IB_MSG_509, 286
ER_IB_MSG_51, 259
ER_IB_MSG_510, 286
ER_IB_MSG_511, 286
ER_IB_MSG_512, 286
ER_IB_MSG_513, 286
ER_IB_MSG_514, 286
ER_IB_MSG_515, 286
ER_IB_MSG_516, 287
ER_IB_MSG_517, 287
ER_IB_MSG_518, 287
ER_IB_MSG_519, 287
ER_IB_MSG_52, 259
ER_IB_MSG_520, 287
ER_IB_MSG_521, 287
ER_IB_MSG_522, 287
ER_IB_MSG_523, 287
ER_IB_MSG_524, 287
ER_IB_MSG_525, 287
ER_IB_MSG_526, 287
ER_IB_MSG_527, 287
ER_IB_MSG_53, 259
ER_IB_MSG_530, 287
ER_IB_MSG_531, 287
ER_IB_MSG_532, 287
ER_IB_MSG_533, 287
ER_IB_MSG_534, 288
ER_IB_MSG_537, 288
ER_IB_MSG_538, 288
ER_IB_MSG_539, 288
ER_IB_MSG_54, 259
ER_IB_MSG_540, 288
ER_IB_MSG_541, 288
ER_IB_MSG_543, 288
ER_IB_MSG_544, 288
ER_IB_MSG_545, 288

ER_IB_MSG_546, 288
ER_IB_MSG_547, 288
ER_IB_MSG_548, 288
ER_IB_MSG_549, 288
ER_IB_MSG_55, 260
ER_IB_MSG_550, 288
ER_IB_MSG_551, 288
ER_IB_MSG_552, 288
ER_IB_MSG_553, 289
ER_IB_MSG_554, 289
ER_IB_MSG_555, 289
ER_IB_MSG_556, 289
ER_IB_MSG_557, 289
ER_IB_MSG_558, 289
ER_IB_MSG_559, 289
ER_IB_MSG_56, 260
ER_IB_MSG_560, 289
ER_IB_MSG_561, 289
ER_IB_MSG_562, 289
ER_IB_MSG_563, 289
ER_IB_MSG_564, 289
ER_IB_MSG_566, 289
ER_IB_MSG_567, 289
ER_IB_MSG_568, 289
ER_IB_MSG_569, 290
ER_IB_MSG_57, 260
ER_IB_MSG_570, 290
ER_IB_MSG_571, 290
ER_IB_MSG_573, 290
ER_IB_MSG_574, 290
ER_IB_MSG_578, 290
ER_IB_MSG_579, 290
ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL,
363
ER_IB_MSG_58, 260
ER_IB_MSG_580, 290
ER_IB_MSG_581, 290
ER_IB_MSG_582, 290
ER_IB_MSG_583, 290
ER_IB_MSG_584, 290
ER_IB_MSG_585, 290
ER_IB_MSG_586, 290
ER_IB_MSG_587, 290
ER_IB_MSG_588, 290
ER_IB_MSG_589, 291
ER_IB_MSG_59, 260
ER_IB_MSG_590, 291
ER_IB_MSG_591, 291
ER_IB_MSG_592, 291
ER_IB_MSG_593, 291
ER_IB_MSG_594, 291
ER_IB_MSG_595, 291
ER_IB_MSG_596, 291
ER_IB_MSG_597, 291
ER_IB_MSG_598, 291
ER_IB_MSG_599, 291
ER_IB_MSG_6, 257
ER_IB_MSG_60, 260

ER_IB_MSG_600, 291
ER_IB_MSG_601, 291
ER_IB_MSG_602, 291
ER_IB_MSG_603, 291
ER_IB_MSG_604, 291
ER_IB_MSG_605, 292
ER_IB_MSG_606, 292
ER_IB_MSG_607, 292
ER_IB_MSG_608, 292
ER_IB_MSG_609, 292
ER_IB_MSG_61, 260
ER_IB_MSG_611, 292
ER_IB_MSG_612, 292
ER_IB_MSG_613, 292
ER_IB_MSG_614, 292
ER_IB_MSG_615, 292
ER_IB_MSG_616, 292
ER_IB_MSG_617, 292
ER_IB_MSG_619, 292
ER_IB_MSG_62, 260
ER_IB_MSG_623, 292
ER_IB_MSG_624, 293
ER_IB_MSG_626, 293
ER_IB_MSG_627, 293
ER_IB_MSG_628, 293
ER_IB_MSG_629, 293
ER_IB_MSG_63, 260
ER_IB_MSG_630, 293
ER_IB_MSG_631, 293
ER_IB_MSG_632, 293
ER_IB_MSG_633, 293
ER_IB_MSG_634, 293
ER_IB_MSG_635, 293
ER_IB_MSG_636, 293
ER_IB_MSG_637, 293
ER_IB_MSG_638, 293
ER_IB_MSG_639, 293
ER_IB_MSG_64, 260
ER_IB_MSG_642, 293
ER_IB_MSG_643, 294
ER_IB_MSG_644, 294
ER_IB_MSG_645, 294
ER_IB_MSG_646, 294
ER_IB_MSG_647, 294
ER_IB_MSG_648, 294
ER_IB_MSG_649, 294
ER_IB_MSG_65, 260
ER_IB_MSG_650, 294
ER_IB_MSG_651, 294
ER_IB_MSG_652, 294
ER_IB_MSG_654, 294
ER_IB_MSG_655, 294
ER_IB_MSG_656, 294
ER_IB_MSG_657, 294
ER_IB_MSG_658, 294
ER_IB_MSG_659, 295
ER_IB_MSG_66, 260
ER_IB_MSG_660, 295

ER_IB_MSG_661, 295
ER_IB_MSG_662, 295
ER_IB_MSG_663, 295
ER_IB_MSG_67, 260
ER_IB_MSG_68, 260
ER_IB_MSG_69, 260
ER_IB_MSG_694, 295
ER_IB_MSG_695, 295
ER_IB_MSG_696, 295
ER_IB_MSG_697, 295
ER_IB_MSG_7, 257
ER_IB_MSG_70, 260
ER_IB_MSG_707, 296
ER_IB_MSG_708, 296
ER_IB_MSG_709, 296
ER_IB_MSG_71, 260
ER_IB_MSG_710, 296
ER_IB_MSG_711, 296
ER_IB_MSG_712, 296
ER_IB_MSG_713, 296
ER_IB_MSG_714, 296
ER_IB_MSG_715, 296
ER_IB_MSG_716, 296
ER_IB_MSG_718, 296
ER_IB_MSG_719, 296
ER_IB_MSG_72, 261
ER_IB_MSG_720, 297
ER_IB_MSG_722, 297
ER_IB_MSG_723, 297
ER_IB_MSG_724, 297
ER_IB_MSG_725, 297
ER_IB_MSG_726, 297
ER_IB_MSG_727, 297
ER_IB_MSG_728, 297
ER_IB_MSG_73, 261
ER_IB_MSG_737, 298
ER_IB_MSG_738, 298
ER_IB_MSG_739, 298
ER_IB_MSG_74, 261
ER_IB_MSG_740, 298
ER_IB_MSG_741, 298
ER_IB_MSG_742, 298
ER_IB_MSG_743, 298
ER_IB_MSG_744, 298
ER_IB_MSG_745, 298
ER_IB_MSG_746, 298
ER_IB_MSG_747, 298
ER_IB_MSG_748, 298
ER_IB_MSG_749, 298
ER_IB_MSG_75, 261
ER_IB_MSG_750, 298
ER_IB_MSG_751, 299
ER_IB_MSG_752, 299
ER_IB_MSG_753, 299
ER_IB_MSG_754, 299
ER_IB_MSG_755, 299
ER_IB_MSG_756, 299
ER_IB_MSG_757, 299

ER_IB_MSG_758, 299
ER_IB_MSG_759, 299
ER_IB_MSG_76, 261
ER_IB_MSG_760, 299
ER_IB_MSG_761, 299
ER_IB_MSG_762, 299
ER_IB_MSG_763, 299
ER_IB_MSG_764, 299
ER_IB_MSG_765, 299
ER_IB_MSG_766, 299
ER_IB_MSG_767, 300
ER_IB_MSG_768, 300
ER_IB_MSG_769, 300
ER_IB_MSG_77, 261
ER_IB_MSG_770, 300
ER_IB_MSG_771, 300
ER_IB_MSG_772, 300
ER_IB_MSG_773, 300
ER_IB_MSG_774, 300
ER_IB_MSG_775, 300
ER_IB_MSG_776, 300
ER_IB_MSG_777, 300
ER_IB_MSG_778, 300
ER_IB_MSG_779, 300
ER_IB_MSG_78, 261
ER_IB_MSG_780, 300
ER_IB_MSG_781, 300
ER_IB_MSG_782, 300
ER_IB_MSG_783, 301
ER_IB_MSG_784, 301
ER_IB_MSG_785, 301
ER_IB_MSG_786, 301
ER_IB_MSG_787, 301
ER_IB_MSG_788, 301
ER_IB_MSG_789, 301
ER_IB_MSG_79, 261
ER_IB_MSG_790, 301
ER_IB_MSG_791, 301
ER_IB_MSG_792, 301
ER_IB_MSG_793, 301
ER_IB_MSG_794, 301
ER_IB_MSG_795, 301
ER_IB_MSG_796, 301
ER_IB_MSG_797, 301
ER_IB_MSG_798, 301
ER_IB_MSG_799, 302
ER_IB_MSG_8, 257
ER_IB_MSG_80, 261
ER_IB_MSG_801, 302
ER_IB_MSG_802, 302
ER_IB_MSG_803, 302
ER_IB_MSG_804, 302
ER_IB_MSG_805, 302
ER_IB_MSG_806, 302
ER_IB_MSG_807, 302
ER_IB_MSG_808, 302
ER_IB_MSG_809, 302
ER_IB_MSG_81, 261

ER_IB_MSG_810, 302
ER_IB_MSG_811, 302
ER_IB_MSG_812, 302
ER_IB_MSG_813, 302
ER_IB_MSG_814, 302
ER_IB_MSG_815, 302
ER_IB_MSG_816, 303
ER_IB_MSG_817, 303
ER_IB_MSG_818, 303
ER_IB_MSG_819, 303
ER_IB_MSG_82, 261
ER_IB_MSG_820, 303
ER_IB_MSG_821, 303
ER_IB_MSG_822, 303
ER_IB_MSG_823, 303
ER_IB_MSG_824, 303
ER_IB_MSG_825, 303
ER_IB_MSG_826, 303
ER_IB_MSG_827, 303
ER_IB_MSG_828, 303
ER_IB_MSG_829, 303
ER_IB_MSG_831, 303
ER_IB_MSG_832, 303
ER_IB_MSG_833, 304
ER_IB_MSG_834, 304
ER_IB_MSG_835, 304
ER_IB_MSG_836, 304
ER_IB_MSG_837, 304
ER_IB_MSG_838, 304
ER_IB_MSG_839, 304
ER_IB_MSG_84, 261
ER_IB_MSG_840, 304
ER_IB_MSG_841, 304
ER_IB_MSG_842, 304
ER_IB_MSG_844, 304
ER_IB_MSG_845, 304
ER_IB_MSG_847, 304
ER_IB_MSG_848, 304
ER_IB_MSG_849, 305
ER_IB_MSG_85, 261
ER_IB_MSG_850, 305
ER_IB_MSG_851, 305
ER_IB_MSG_852, 305
ER_IB_MSG_853, 305
ER_IB_MSG_854, 305
ER_IB_MSG_855, 305
ER_IB_MSG_856, 305
ER_IB_MSG_857, 305
ER_IB_MSG_858, 305
ER_IB_MSG_859, 305
ER_IB_MSG_86, 261
ER_IB_MSG_860, 305
ER_IB_MSG_861, 305
ER_IB_MSG_862, 305
ER_IB_MSG_863, 305
ER_IB_MSG_864, 305
ER_IB_MSG_865, 306
ER_IB_MSG_866, 306

ER_IB_MSG_867, 306
ER_IB_MSG_868, 306
ER_IB_MSG_869, 306
ER_IB_MSG_870, 306
ER_IB_MSG_871, 306
ER_IB_MSG_872, 306
ER_IB_MSG_873, 306
ER_IB_MSG_874, 306
ER_IB_MSG_875, 306
ER_IB_MSG_876, 306
ER_IB_MSG_877, 306
ER_IB_MSG_878, 306
ER_IB_MSG_879, 306
ER_IB_MSG_880, 306
ER_IB_MSG_881, 307
ER_IB_MSG_882, 307
ER_IB_MSG_883, 307
ER_IB_MSG_884, 307
ER_IB_MSG_885, 307
ER_IB_MSG_886, 307
ER_IB_MSG_887, 307
ER_IB_MSG_888, 307
ER_IB_MSG_889, 307
ER_IB_MSG_890, 307
ER_IB_MSG_891, 307
ER_IB_MSG_892, 307
ER_IB_MSG_893, 307
ER_IB_MSG_894, 307
ER_IB_MSG_895, 307
ER_IB_MSG_896, 307
ER_IB_MSG_897, 308
ER_IB_MSG_898, 308
ER_IB_MSG_899, 308
ER_IB_MSG_9, 257
ER_IB_MSG_900, 308
ER_IB_MSG_901, 308
ER_IB_MSG_902, 308
ER_IB_MSG_903, 308
ER_IB_MSG_904, 308
ER_IB_MSG_905, 308
ER_IB_MSG_906, 308
ER_IB_MSG_907, 308
ER_IB_MSG_908, 308
ER_IB_MSG_909, 308
ER_IB_MSG_910, 308
ER_IB_MSG_911, 308
ER_IB_MSG_912, 308
ER_IB_MSG_913, 309
ER_IB_MSG_914, 309
ER_IB_MSG_915, 309
ER_IB_MSG_916, 309
ER_IB_MSG_917, 309
ER_IB_MSG_918, 309
ER_IB_MSG_919, 309
ER_IB_MSG_920, 309
ER_IB_MSG_921, 309
ER_IB_MSG_922, 309
ER_IB_MSG_923, 309

ER_IB_MSG_924, 309
ER_IB_MSG_925, 309
ER_IB_MSG_926, 309
ER_IB_MSG_927, 309
ER_IB_MSG_928, 309
ER_IB_MSG_929, 310
ER_IB_MSG_930, 310
ER_IB_MSG_931, 310
ER_IB_MSG_932, 310
ER_IB_MSG_933, 310
ER_IB_MSG_934, 310
ER_IB_MSG_935, 310
ER_IB_MSG_936, 310
ER_IB_MSG_937, 310
ER_IB_MSG_938, 310
ER_IB_MSG_939, 310
ER_IB_MSG_940, 310
ER_IB_MSG_941, 310
ER_IB_MSG_942, 310
ER_IB_MSG_943, 310
ER_IB_MSG_944, 310
ER_IB_MSG_945, 311
ER_IB_MSG_946, 311
ER_IB_MSG_948, 311
ER_IB_MSG_949, 311
ER_IB_MSG_95, 261
ER_IB_MSG_950, 311
ER_IB_MSG_951, 311
ER_IB_MSG_952, 311
ER_IB_MSG_953, 311
ER_IB_MSG_954, 311
ER_IB_MSG_955, 311
ER_IB_MSG_956, 311
ER_IB_MSG_957, 311
ER_IB_MSG_958, 311
ER_IB_MSG_959, 311
ER_IB_MSG_96, 262
ER_IB_MSG_960, 311
ER_IB_MSG_961, 312
ER_IB_MSG_962, 312
ER_IB_MSG_963, 312
ER_IB_MSG_964, 312
ER_IB_MSG_965, 312
ER_IB_MSG_966, 312
ER_IB_MSG_967, 312
ER_IB_MSG_968, 312
ER_IB_MSG_969, 312
ER_IB_MSG_97, 262
ER_IB_MSG_970, 312
ER_IB_MSG_971, 312
ER_IB_MSG_972, 312
ER_IB_MSG_973, 312
ER_IB_MSG_974, 312
ER_IB_MSG_975, 312
ER_IB_MSG_976, 312
ER_IB_MSG_977, 313
ER_IB_MSG_978, 313
ER_IB_MSG_979, 313

ER_IB_MSG_98, 262
ER_IB_MSG_980, 313
ER_IB_MSG_981, 313
ER_IB_MSG_982, 313
ER_IB_MSG_983, 313
ER_IB_MSG_984, 313
ER_IB_MSG_985, 313
ER_IB_MSG_986, 313
ER_IB_MSG_987, 313
ER_IB_MSG_988, 313
ER_IB_MSG_989, 313
ER_IB_MSG_99, 262
ER_IB_MSG_990, 313
ER_IB_MSG_991, 313
ER_IB_MSG_992, 313
ER_IB_MSG_993, 314
ER_IB_MSG_994, 314
ER_IB_MSG_995, 314
ER_IB_MSG_996, 314
ER_IB_MSG_997, 314
ER_IB_MSG_998, 314
ER_IB_MSG_999, 314
ER_IB_MSG_ABORTING_LOG_ARCHIVER, 404
ER_IB_MSG_BAD_DBLWR_FILE_NAME, 361
ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED,
355
ER_IB_MSG_BUF_PENDING_IO, 320
ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN,
329
ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS,
394
ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_COD
394
ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE,
394
ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE,
364
ER_IB_MSG_CANT_DECRYPT_REDO_LOG, 304
ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA,
304
ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA,
393
ER_IB_MSG_CLOCK_GETTIME_FAILED, 353
ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED,
353
ER_IB_MSG_CLONE_DDL_APPLY, 381
ER_IB_MSG_CLONE_DDL_INVALIDATE, 381
ER_IB_MSG_CLONE_DDL_NTFN, 381
ER_IB_MSG_CREATED_UNDO_SPACE, 370
ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_C
322
ER_IB_MSG_DBLWR_1285, 361
ER_IB_MSG_DBLWR_1286, 361
ER_IB_MSG_DBLWR_1287, 361
ER_IB_MSG_DBLWR_1288, 361
ER_IB_MSG_DBLWR_1290, 361
ER_IB_MSG_DBLWR_1293, 361
ER_IB_MSG_DBLWR_1294, 361

ER_IB_MSG_DBLWR_1295, 361	ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY,
ER_IB_MSG_DBLWR_1296, 361	360
ER_IB_MSG_DBLWR_1297, 361	ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR,
ER_IB_MSG_DBLWR_1298, 361	279
ER_IB_MSG_DBLWR_1300, 361	ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN, 363
ER_IB_MSG_DBLWR_1301, 362	ER_IB_MSG_IBUF_CURSOR_RESTORATION_FAILED,
ER_IB_MSG_DBLWR_1304, 362	292
ER_IB_MSG_DBLWR_1305, 362	ER_IB_MSG_IBUF_FAILED_TO_RESTORE_POSITION,
ER_IB_MSG_DBLWR_1306, 362	292
ER_IB_MSG_DBLWR_1307, 362	ER_IB_MSG_IGNORE_SCAN_PATH, 277
ER_IB_MSG_DBLWR_1308, 362	ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR,
ER_IB_MSG_DBLWR_1309, 362	279
ER_IB_MSG_DBLWR_1310, 362	ER_IB_MSG_INCORRECT_SIZE, 370
ER_IB_MSG_DBLWR_1311, 362	ER_IB_MSG_INJECT_CRASH, 369
ER_IB_MSG_DBLWR_1312, 362	ER_IB_MSG_INJECT_FAILURE, 369
ER_IB_MSG_DBLWR_1313, 362	ER_IB_MSG_INNODB_END_INITIALIZE, 363
ER_IB_MSG_DBLWR_1314, 362	ER_IB_MSG_INNODB_FLUSH_METHOD, 415
ER_IB_MSG_DBLWR_1315, 362	ER_IB_MSG_INNODB_START_INITIALIZE, 363
ER_IB_MSG_DBLWR_1316, 362	ER_IB_MSG_INVALID_LOCATION_FOR_TABLE,
ER_IB_MSG_DBLWR_1317, 362	289
ER_IB_MSG_DBLWR_1318, 362	ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE,
ER_IB_MSG_DBLWR_1320, 363	364
ER_IB_MSG_DBLWR_1321, 363	ER_IB_MSG_INVALID_LOCATION_WRONG_DB,
ER_IB_MSG_DBLWR_1323, 363	364
ER_IB_MSG_DBLWR_1324, 363	ER_IB_MSG_INVALID_PAGE_TYPE, 394
ER_IB_MSG_DBLWR_1325, 363	ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS,
ER_IB_MSG_DBLWR_1326, 363	342
ER_IB_MSG_DBLWR_1327, 363	ER_IB_MSG_LOG_CHECKPOINT_FOUND, 388
ER_IB_MSG_DBLWR_LOAD_WRONG_SIZE, 362	ER_IB_MSG_LOG_CORRUPT, 295
ER_IB_MSG_DBLWR_OPEN_OR_CREATE_WRONG_SIZE, 363	ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY,
	329
ER_IB_MSG_DDL_FAIL_NO_BUILDER, 403	ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED,
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK, 294	388
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT,	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE,
351	297
ER_IB_MSG_DDL_LOG_FAIL_POST_DDL, 351	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ,
ER_IB_MSG_DICT_PARTITION_NOT_FOUND,	387
360	ER_IB_MSG_LOG_FILES_CREATED_BY_MEB,
ER_IB_MSG_DOWNGRADE_PARTITION_FILE,	297
359	ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY,
ER_IB_MSG_DROPPED_UNDO_SPACE, 370	297
ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE,	ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATE,
341	389
ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR, 341	ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE,
ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR, 342	318
ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT, 341	ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES,
ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE,	322
342	ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED,
ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE,	329
341	ER_IB_MSG_LOG_FILES_FOUND_MISSING, 389
ER_IB_MSG_FILE_RESIZE, 318	ER_IB_MSG_LOG_FILES_INITIALIZED, 318
ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME,	ER_IB_MSG_LOG_FILES_INVALID_SET, 322
360	ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED,
ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH,	388
360	ER_IB_MSG_LOG_FILES_RESIZE_FINISHED, 388
ER_IB_MSG_FIL_STATE_MOVED_CORRECTED,	ER_IB_MSG_LOG_FILES_RESIZE_ON_START,
360	327
ER_IB_MSG_FIL_STATE_MOVED_PREV, 415	

ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED, 388	ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIAL, 387
ER_IB_MSG_LOG_FILES_REWRITING, 323	ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_U, 330
ER_IB_MSG_LOG_FILES_UPGRADE, 388	ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORE, 390
ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS, 389	ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE, 390
ER_IB_MSG_LOG_FILE_FOREIGN_UUID, 388	ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED, 389
ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW, 389	ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED, 389
ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD, 389	ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0, 389
ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN, 296	ER_IB_MSG_LOG_UPGRADE_CLONED_DB, 388
ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM, 330	ER_IB_MSG_LOG_UPGRADE_CORRUPTION_UNEXPECTED, 388
ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED, 387	ER_IB_MSG_LOG_UPGRADE_FORCED_RECV, 387
ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES, 388	ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE, 387
ER_IB_MSG_LOG_FILE_INVALID_START_LSN, 388	ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES, 388
ER_IB_MSG_LOG_FILE_IS_EMPTY, 386	ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER, 328
ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED, 390	ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN, 387
ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE, 389	ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN, 387
ER_IB_MSG_LOG_FILE_MISSING_FOR_ID, 388	ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE, 328
ER_IB_MSG_LOG_FILE_OPEN_FAILED, 318	ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER, 328
ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED, 318	ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER, 393
ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED, 318	ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE, 387
ER_IB_MSG_LOG_FILE_REMOVE_FAILED, 389	ER_IB_MSG_LOG_WRITER_WRITE_FAILED, 387
ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED, 389	ER_IB_MSG_MADVISE_FAILED, 341
ER_IB_MSG_LOG_FILE_RESIZE_FAILED, 318	ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED, 341
ER_IB_MSG_LOG_FILE_SIZE_INVALID, 322	ER_IB_MSG_MASTER_KEY_ROTATED, 370
ER_IB_MSG_LOG_FILE_TOO_BIG, 386	ER_IB_MSG_MAX_UNDO_SPACES_REACHED, 341
ER_IB_MSG_LOG_FILE_TOO_SMALL, 386	ER_IB_MSG_NOT_END_WITH_IBU, 342
ER_IB_MSG_LOG_FILE_TRUNCATE, 389	ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND, 337
ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE, 390	ER_IB_MSG_OPENED_N_UNDO_TS, 319
ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED, 390	ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS, 364
ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED, 390	ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION, 393
ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED, 390	ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG, 379
ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9, 330	ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG, 379
ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30, 296	ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER, 351
ER_IB_MSG_LOG_FORMAT_OLD, 297	
ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED, 295	
ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN, 295	
ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED, 387	
ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR, 387	

ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT,	ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE,
351	324
ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE,	ER_IB_MSG_UNDO_TRUNCATE_START, 324
297	ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN,
ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND,	364
296	ER_IB_MSG_UNEXPECTED_FILE_EXISTS, 274
ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOGFILE,	ER_IB_MSG_UNPROCESSED_REDO_LOG_RECORDS,
387	295
ER_IB_MSG_RECOVERY_CORRUPT, 323	ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED,
ER_IB_MSG_RECOVERY_IN_READ_ONLY, 298	277
ER_IB_MSG_RECOVERY_IS_NEEDED, 298	ER_IB_MSG_UPGRADE_PARTITION_FILE, 359
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG,	ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT,
379	359
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG,	ER_IB_MSG_USING_UNDO_SPACE, 341
379	ER_IB_MSG_WAITING_ON_LAGGING_REDO_LOG_CONSUMPTION,
ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE,	
297	ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD,
ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY,	337
379	ER_IB_MSG_WILL_CREATE_N_UNDO_TS, 327
ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY,	ER_IB_MSG_WRONG_TABLESPACE_DIR, 342
379	ER_IB_PARALLEL_READER_WORKER_INFO, 394
ER_IB_MSG_RESUME_OP_FOR_SPACE, 337	ER_IB_PRIMARY_KEY_IS_INSTANT, 397
ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR,	ER_IB_RDBLWR_BYTES_INFO, 386
367	ER_IB_RECV_FIRST_REC_GROUP_INVALID, 352
ER_IB_MSG_SDI_Z_STREAM_ERROR, 342	ER_IB_RELOCK_LATCH_ORDER_VIOLATION,
ER_IB_MSG_SDI_Z_UNKNOWN_ERROR, 342	367
ER_IB_MSG_SKIP_HIDDEN_DIR, 358	ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK,
ER_IB_MSG_STATS_SAMPLING_TOO_LARGE,	399
373	ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK,
ER_IB_MSG_SUBMIT_DETAILED_BUG_REPORT,	399
413	ER_IB_RESURRECT_RECORD_COMPLETE, 399
ER_IB_MSG_THREAD_CONCURRENCY_CHANGED,	ER_IB_RESURRECT_RECORD_PROGRESS, 399
330	ER_IB_RESURRECT_TRX_INSERT, 399
ER_IB_MSG_TOO_LONG_PATH, 352	ER_IB_RESURRECT_TRX_INSERT_COMPLETE,
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETE,	399
325	ER_IB_RESURRECT_TRX_UPDATE, 399
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETE,	ER_IB_RESURRECT_TRX_UPDATE_COMPLETE,
366	400
ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME,	ER_IB_SELECT_COUNT_STAR, 398
384	ER_IB_SYNC_READ_FAILED, 407
ER_IB_MSG_UNDO_ALTERED_ACTIVE, 369	ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED,
ER_IB_MSG_UNDO_ALTERED_INACTIVE, 369	366
ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED,	ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY,
381	367
ER_IB_MSG_UNDO_MARKED_ACTIVE, 369	ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE,
ER_IB_MSG_UNDO_MARKED_EMPTY, 369	367
ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE,	ER_IB_WARN_ACCESSING_NONEXISTING_SPACE,
324	272
ER_IB_MSG_UNDO_TRUNCATE_COMPLETE,	ER_IB_WARN_MANY_NON_LRU_FILES_OPENED,
324	384
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE,	ER_IB_WARN_OPEN_PARTITION_FILE, 359
369	ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH,
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE,	381
324	ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE,
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE,	375
324	ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED,
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL,	365
369	

ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY, 397	ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WO 170
ER_IB_WRN_OLD_GEOMETRY_TYPE, 375	ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE, 170
ER_IB_WRN_PAGE_ARCH_FLUSH_DATA, 364	ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE, 170
ER_IB_WRN_REDO_DISABLED, 365	ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD, 358
ER_IB_WRN_REDO_ENABLED, 365	ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT, 170
ER_IB_WRONG_PAGEID_AFTER_SYNC_READ, 407	ER_INIT_ROOT_WITHOUT_PASSWORD, 170
ER_IB_WRONG_PAGE_ID, 406	ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED, 202
ER_IDENTIFIED_BY_UNSUPPORTED, 112	ER_INNODB_AUTO_INCREMENT_INCREMENT_SIZE_OUT_OF_RANGE, 110
ER_IDENT_CAUSES_TOO_LONG_PATH, 55	ER_INNODB_CANNOT_CREATE_TABLE, 202
ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE, 356	ER_INNODB_CANNOT_CREATE_INDEX, 202
ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_OR_DIFFERENT_TABLE, 116	ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR, 190
ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FUNC_INNODB, 116	ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD, 190
ER_ILLEGAL_GRANT_FOR_TABLE, 12	ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK, 190
ER_ILLEGAL_HA, 5	ER_INNODB_CLUSTERED_INDEX_PRIVATE, 191
ER_ILLEGAL_HA_CREATE_OPTION, 32	ER_INNODB_COMPRESSION_FAILURE, 110
ER_ILLEGAL_PRIVILEGE_LEVEL, 80	ER_INNODB_DIFF_IN_REF_LEN, 202
ER_ILLEGAL_REFERENCE, 18	ER_INNODB_DIRTY_WATER_MARK_NOT_LOW, 190
ER_ILLEGAL_USER_VAR, 61	ER_INNODB_ERROR_LOGGER_FATAL_MSG, 203
ER_ILLEGAL_VALUE_FOR_TYPE, 25	ER_INNODB_ERROR_LOGGER_MSG, 203
ER_IMDS_OCI_ERROR, 417	ER_INNODB_FAILED_TO_FIND_IDX, 202
ER_IMDS_OCI_INFO, 417	ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE, 202
ER_IMDS_OCI_WARNING, 417	ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO, 202
ER_IMPLICIT_COMPARISON_FOR_JSON, 107	ER_INNODB_FILES_SAME, 190
ER_IMPOSSIBLE_STRING_CONVERSION, 107	ER_INNODB_FORCED_RECOVERY, 56
ER_IMP_INCOMPATIBLE_CFG_VERSION, 104	ER_INNODB_FT_AUX_NOT_HEX_ID, 56
ER_IMP_INCOMPATIBLE_DD_VERSION, 79	ER_INNODB_FT_LIMIT, 51
ER_IMP_INCOMPATIBLE_MYSQLD_VERSION, 79	ER_INNODB_FT_WRONG_DOCID_COLUMN, 51
ER_IMP_INCOMPATIBLE_SDI_VERSION, 79	ER_INNODB_FT_WRONG_DOCID_INDEX, 51
ER_IMP_NO_FILES_MATCHED, 79	ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYS, 202
ER_IMP_SCHEMA_DOES_NOT_EXIST, 79	ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYS, 202
ER_IMP_TABLE_ALREADY_EXISTS, 79	ER_INNODB_IDX_COLUMN_CNT_DIFF, 202
ER_INCOMPATIBLE_TYPE_AGG, 130	ER_INNODB_ILLEGAL_COLON_IN_POOL, 190
ER_INCONSISTENT_ERROR, 332	ER_INNODB_IMPORT_DROP_COL_METADATA_MISMATCH, 122
ER_INCONSISTENT_PARTITION_INFO_ERROR, 32	ER_INNODB_IMPORT_ENUM_NULL_TERMINATOR_MISMATCH, 122
ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR, 32	ER_INNODB_IMPORT_ERROR, 52
ER_INCORRECT_CURRENT_PASSWORD, 99	ER_INNODB_IMPORT_WRONG_DROPPED_ENUM_LENGTH, 122
ER_INCORRECT_GLOBAL_LOCAL_VAR, 18	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES, 122
ER_INCORRECT_TYPE, 61	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES, 122
ER_INDEX_COLUMN_TOO_LONG, 45	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES, 122
ER_INDEX_CORRUPT, 45	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES, 122
ER_INDEX_OTHER_THAN_PK, 118	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES, 122
ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX, 87	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES, 122
ER_INFORMATION_SCHEMA_VERSION_CHANGE, 402	
ER_INFO_AUTHENTICATION_OCI, 425	
ER_INIT_BOOTSTRAP_COMPLETE, 170	
ER_INIT_CANT_OPEN_BOOTSTRAP_FILE, 170	
ER_INIT_CREATING_DD, 170	
ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WO 170	

ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE, 110	ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH, 96
ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQL, 190	ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT, 96
ER_INNODB_INDEX_CORRUPT, 52	ER_INNODB_TRX_XLATION_TABLE_OOM, 190
ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED, 120	ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT, 364
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FIELDS, 120	ER_INNODB_UNDO_LOG_FULL, 58
ER_INNODB_INTERNAL_INDEX, 202	ER_INNODB_UNKNOWN_COLLATION, 189
ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE, 110	ER_INNODB_UNREGISTERED_TRX_ACTIVE, 190
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY, 189	ER_INNODB_USE_MONITOR_GROUP_NAME, 203
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LABEL, 343	ER_INSECURE_CHANGE_SOURCE, 48
ER_INNODB_INVALID_LOG_GROUP_HOME_DIR, 189	ER_INSECURE_PLAIN_TEXT, 48
ER_INNODB_INVALID_MONITOR_COUNTER_NAME, 203	ER_INSERT_INFO, 9
ER_INNODB_INVALID_PAGE_SIZE, 190	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT, 43
ER_INNODB_IO_CAPACITY_EXCEEDS_MAX, 190	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT, 43
ER_INNODB_IO_WRITE_ERROR_RETRYING, 371	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOGOFF, 44
ER_INNODB_IO_WRITE_FAILED, 371	ER_INSTALL_COMPONENT_SET_NULL_VALUE, 120
ER_INNODB_MANDATORY, 145	ER_INSTALL_COMPONENT_SET_UNUSED_VALUE, 120
ER_INNODB_MAX_ROW_VERSION, 115	ER_INSTALL_PLUGIN_CONFLICT_CLIENT, 111
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED, 203	ER_INSTALL_PLUGIN_CONFLICT_LOG, 378
ER_INNODB_MONITOR_IS_ENABLED, 203	ER_INTERNAL_ERROR, 52
ER_INNODB_NO_FT_TEMP_TABLE, 51	ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED, 117
ER_INNODB_ONLINE_LOG_TOO_BIG, 51	ER_INVALID_ADMIN_ADDRESS, 344
ER_INNODB_OUT_OF_RESOURCES, 360	ER_INVALID_ARGUMENT_FOR_LOGARITHM, 58
ER_INNODB_PK_NOT_IN_MYSQL, 190	ER_INVALID_ASSIGNMENT_TARGET, 112
ER_INNODB_PK_ONLY_IN_MYSQL, 191	ER_INVALID_AUTHENTICATION_POLICY, 381
ER_INNODB_READ_ONLY, 56	ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE, 73
ER_INNODB_REDO_ARCHIVING_ENABLED, 106	ER_INVALID_BITWISE_OPERANDS_SIZE, 73
ER_INNODB_REDO_DISABLED, 106	ER_INVALID_CAST, 108
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE, 96	ER_INVALID_CAST_POLYGON_RING_DIRECTION, 110
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID, 96	ER_INVALID_CAST_TO_GEOMETRY, 110
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH, 96	ER_INVALID_CAST_TO_JSON, 67
ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY, 96	ER_INVALID_CHARACTER_STRING, 21
ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS, 96	ER_INVALID_CHARSET_AND_DEFAULT_IS_MB, 133
ER_INNODB_REDO_LOG_ARCHIVE_FAILED, 97	ER_INVALID_CLAUSE_COMBINATION, 132
ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE, 96	ER_INVALID_CLAUSE_IN_CONTEXT, 132
ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE, 97	ER_INVALID_COLLATION_FOR_CHARSET, 194
ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND, 96	ER_INVALID_DD_OBJECT, 72
ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR, 96	ER_INVALID_DD_OBJECT_ID, 72
ER_INNODB_REDO_LOG_ARCHIVE_SESSION, 97	ER_INVALID_DD_OBJECT_NAME, 72
	ER_INVALID_DEFAULT, 7
	ER_INVALID_DEFAULT_UTF8MB4_COLLATION, 86
	ER_INVALID_ENCRYPTION_OPTION, 70
	ER_INVALID_ENCRYPTION_REQUEST, 95
	ER_INVALID_ERROR_LOG_NAME, 152
	ER_INVALID_FIELD_SIZE, 58

ER_INVALID_FILE_FORMAT, 414	ER_INVALID_USER_ATTRIBUTE_JSON, 106
ER_INVALID_GEOJSON CRS_NOT_TOP_LEVEL, 83	ER_INVALID_USER_FOR_REGISTRATION, 113
ER_INVALID_GEOJSON_MISSING_MEMBER, 62	ER_INVALID_USE_OF_FORCE_OPTION, 83
ER_INVALID_GEOJSON_UNSPECIFIED, 62	ER_INVALID_USE_OF_NULL, 12
ER_INVALID_GEOJSON_WRONG_TYPE, 62	ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENT, 142
ER_INVALID_GROUP_FUNC_USE, 10	ER_INVALID_VALUE_OF_BIND_ADDRESSES, 338
ER_INVALID_INFO_IN_FRM, 163	ER_INVALID_VCPU_ID, 82
ER_INVALID_INSTRUMENT, 145	ER_INVALID_VCPU_RANGE, 82
ER_INVALID_JSON_ATTRIBUTE, 106	ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER, 364
ER_INVALID_JSON_BINARY_DATA, 67	ER_INVALID_YEAR_COLUMN_LENGTH, 52
ER_INVALID_JSON_CHARSET, 67	ER_IO_ERR_LOG_INDEX_READ, 26
ER_INVALID_JSON_CHARSET_IN_FUNCTION, 67	ER_IO_READ_ERROR, 52
ER_INVALID_JSON_DATA, 62	ER_IO_WRITE_ERROR, 52
ER_INVALID_JSON_PATH, 67	ER_IPSOCK_ERROR, 8
ER_INVALID_JSON_PATH_ARRAY_CELL, 69	ER_IS_QUERY_INVALID_CLAUSE, 75
ER_INVALID_JSON_PATH_CHARSET, 67	ER_I_S_SKIPPED_TABLESPACE, 81
ER_INVALID_JSON_PATH_WILDCARD, 68	ER_JDV_ALGO_TEMPTABLE_NOT_SUPPORTED, 133
ER_INVALID_JSON_TEXT, 67	ER_JDV ALTER_OR_REPLACE_NOT_SUPPORTED, 137
ER_INVALID_JSON_TEXT_IN_PARAM, 67	ER_JDV_CANNOT_BE_USED_WITH, 138
ER_INVALID_JSON_TYPE, 97	ER_JDV_DML_INFO, 138
ER_INVALID_JSON_VALUE_FOR_CAST, 68	ER_JDV_ETAG_MISMATCH, 138
ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX, 100	ER_JDV_EXPLICIT_AUTO_INCREMENT_NOT_ALLOWED, 139
ER_INVALID_LOGGER, 417	ER_JDV_FEATURE_EDITION_LIMIT, 138
ER_INVALID_METER, 417	ER_JDV_INSERT_VALUE_NOT_FIXED, 138
ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER, 113	ER_JDV_INVALID_BINARY_TYPE_HEADER, 139
ER_INVALID_MFA_PLUGIN_SPECIFIED, 112	ER_JDV_INVALID_DEFINITION_ALIAS_NOT_USED_FOR, 137
ER_INVALID_MULTIPLE_CLAUSES, 95	ER_JDV_INVALID_DEFINITION_COLUMN_LIST_NOT_SUPPORTED, 136
ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP, 349	ER_JDV_INVALID_DEFINITION_COLUMN_TYPE_NOT_SUPPORTED, 135
ER_INVALID_NO_OF_ARGS, 79	ER_JDV_INVALID_DEFINITION_COMPOSITE_KEY_USED, 137
ER_INVALID_ON_UPDATE, 21	ER_JDV_INVALID_DEFINITION_CONTEXT_PREPARE_FAILED, 135
ER_INVALID_OPTION_CHARACTERS, 76	ER_JDV_INVALID_DEFINITION_CTE_NOT_SUPPORTED, 134
ER_INVALID_OPTION_END_CHARACTER, 76	ER_JDV_INVALID_DEFINITION_DUPLICATE_COLUMN_NAME, 136
ER_INVALID_OPTION_KEY, 76	ER_JDV_INVALID_DEFINITION_DUPLICATE_KEYS_NOT_SUPPORTED, 136
ER_INVALID_OPTION_KEY_VALUE_PAIR, 76	ER_JDV_INVALID_DEFINITION_GROUPBY_NOT_SUPPORTED, 134
ER_INVALID_OPTION_START_CHARACTER, 76	ER_JDV_INVALID_DEFINITION_ID_KEY_NOT_USED_BY, 136
ER_INVALID_OPTION_VALUE, 76	ER_JDV_INVALID_DEFINITION_ID_KEY_USED_BY_NOT_SUPPORTED, 136
ER_INVALID_OR_OLD_TABLE_OR_DB_NAME, 172	ER_JDV_INVALID_DEFINITION_INCONSISTENT_TABLE_FORMAT, 136
ER_INVALID_OUTER_REFERENCE, 132	ER_JDV_INVALID_DEFINITION_LIMIT_NOT_SUPPORTED, 134
ER_INVALID_PARAMETER_USE, 107	
ER_INVALID_PLUGIN_FOR_REGISTRATION, 112	
ER_INVALID_PROPERTY_KEY, 346	
ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN, 62	
ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH, 402	
ER_INVALID_SERVER_OPTION_CHARSET, 427	
ER_INVALID_SERVER_OPTION_COLLATION, 427	
ER_INVALID_SERVER_UPGRADE_NOT_LTS, 402	
ER_INVALID_THREAD_ID, 82	
ER_INVALID_THREAD_PRIORITY, 82	
ER_INVALID_TIME_ZONE_INTERVAL, 107	
ER_INVALID_TLS_VERSION, 385	
ER_INVALID_TYPE_FOR_JSON, 67	

ER_JDV_INVALID_DEFINITION_MULTI_TABLES_NOT_SUPPORTED, 134	ER_JSON_INVALID_PRIMARY_KEY_MUST_BE_PROVIDED, 137
ER_JDV_INVALID_DEFINITION_MUSTBE_JSON_OBJECT_FOR_NESTED, 135	ER_JSON_INVALID_EXPECTED_JSON_TYPE, 137
ER_JDV_INVALID_DEFINITION_MUSTBE_JSON_OBJECT_FOR_SINGLETON, 135	ER_JDV_UNMAPPED_KEY, 137
ER_JDV_INVALID_DEFINITION_NON_BASE_TABLE_NOT_SUPPORTED, 135	ER_JDV_SINGLETON_VALUE_NOT_FIXED, 138
ER_JDV_INVALID_DEFINITION_NON_SIMPLE_SELECT_NOT_SUPPORTED, 134	ER_JDV_WITH_CHECK_OPTION_NOT_SUPPORTED, 135
ER_JDV_INVALID_DEFINITION_NO_JSON_OBJECT_IN_ROOT, 135	ER_JSON_BAD_ONE_OR_ALL_ARG, 68
ER_JDV_INVALID_DEFINITION_NO_JSON_OBJ_IN_ARRAY, 135	ER_JSON_DOCUMENT_NULL_KEY, 68
ER_JDV_INVALID_DEFINITION_NO_WHERE_CONDITION, 134	ER_JSON_DOCUMENT_TOO_DEEP, 68
ER_JDV_INVALID_DEFINITION_ORDERBY_NOT_SUPPORTED, 134	ER_JSON_KEY_TOO_BIG, 68
ER_JDV_INVALID_DEFINITION_RELATIONSHIP_RULES_VIOLATED, 135	ER_JSON_PARSE_ERROR, 154
ER_JDV_INVALID_DEFINITION_SAME_TABLE_INCONSISTENT, 136	ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED, 102
ER_JDV_INVALID_DEFINITION_TABLE_WITHOUT_PK, 135	ER_JSON_SINGLETON_KEY, 68
ER_JDV_INVALID_DEFINITION_TABLE_WITHOUT_PK, 136	ER_JSON_VACUOUS_PATH, 68
ER_JDV_INVALID_DEFINITION_WHERE_CONDITION, 134	ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX, 100
ER_JDV_INVALID_DEFINITION_WHERE_USES_NON_IMMEDIATE_PARENT, 137	ER_JT_MAX_NESTED_PATH, 83
ER_JDV_INVALID_DEFINITION_WINDOW_FUNCTION, 134	ER_KERBEROS_CREATE_USER, 111
ER_JDV_INVALID_DEFINITION_WRONG_ANNOTATION, 133	ER_KEYRING_CACHE_OOM, 147
ER_JDV_INVALID_DEFINITION_WRONG_FIELD_TYPE, 135	ER_KEYRING_ACCESS_DENIED_ERROR, 71
ER_JDV_INVALID_DEFINITION_WRONG_WHERE_FOR, 134	ER_KEYRING_AWS_ID_NOT_SET, 226
ER_JDV_INVALID_JSON_DUALITY_OBJECT_USAGE, 137	ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE, 226
ER_JDV_INVALID_TABLE_ANNOTATIONS_FOR_NESTED, 136	ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONTAINER, 226
ER_JDV_INVALID_TABLE_ANNOTATIONS_FOR_SINGLETON, 136	ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONTAINER, 226
ER_JDV_JOIN_CONDITION_NOT_SATISFIED, 137	ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING, 226
ER_JDV_JOIN_CONDITION_VIOLATION, 138	ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING, 226
ER_JDV_MISSING_DELETE_TAG, 138	ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS, 227
ER_JDV_MISSING_ETAG, 138	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 226
ER_JDV_MISSING_INSERT_TAG, 137	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 226
ER_JDV_MISSING_READONLY_SUBOBJECT, 138	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 226
ER_JDV_MISSING_UPDATE_TAG, 138	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 226
ER_JDV_MISSING_VALUE, 138	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 226
ER_JDV_NULL_INSERT_VALUE, 138	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 226
ER_JDV_NULL_UPDATE_VALUE, 138	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 226
ER_JDV_OPERATION_NOT_SUPPORTED, 137	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 225
ER_JDV_PK_DUPLICATES_NOT_IDENTICAL, 137	ER_KEYRING_AWS_FAILED_TO_CREATE_KEYRING, 227
ER_JDV_PK_UPDATES_NOT_ALLOWED, 138	

ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY,	ER_KEYRING_COMPONENT_KEYRING_FILE_INVALID_FO
227	413
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK,	ER_KEYRING_COMPONENT_KEYRING_FILE_JSON_EXT
227	413
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID,	ER_KEYRING_COMPONENT_KEYRING_FILE_KEY_EXTR
225	413
ER_KEYRING_AWS_FAILED_TO_SET_REGION,	ER_KEYRING_COMPONENT_KEYRING_FILE_NAME_EMP
225	412
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_	ER_KEYRING_COMPONENT_KEYRING_FILE_READ_FAIL
227	412
ER_KEYRING_AWS_INCORRECT_FILE, 226	ER_KEYRING_COMPONENT_KEYRING_HASHICORP_AU
ER_KEYRING_AWS_INCORRECT_PROXY, 357	423
ER_KEYRING_AWS_INCORRECT_REGION, 227	ER_KEYRING_COMPONENT_KEYRING_HASHICORP_CU
ER_KEYRING_AWS_INIT_FAILURE, 226	423
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH,	ER_KEYRING_COMPONENT_KEYRING_HASHICORP_DA
225	423
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH,	ER_KEYRING_COMPONENT_KEYRING_HASHICORP_KE
226	423
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIP	ER_KEYRING_COMPONENT_KMIP_CONNECTION_TO_S
226	426
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR, 71	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ACTIVAT
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_	KEY_ID,
222	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ADD_AT
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID	KEY,
222	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ALLOCA
ER_KEYRING_COMPONENT_AWS_ADD_TO_DOC_FAIL	ED,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_FETCH_I
ER_KEYRING_COMPONENT_AWS_BACKEND_OPERATIO	ON_FAILED,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_GENERA
ER_KEYRING_COMPONENT_AWS_CACHE_OPERATION	FAILED,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_INIT_CLI
ER_KEYRING_COMPONENT_AWS_CANNOT_ENCRYPT	READ_ONLY,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_INIT_SSE
ER_KEYRING_COMPONENT_AWS_CLIENT_CREATE_	FAILED,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_LOAD_K
ER_KEYRING_COMPONENT_AWS_CLIENT_OPERATION	FAILED,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_LOAD_S
ER_KEYRING_COMPONENT_AWS_FILE_OPEN_FAILED	ED,
418	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_REMOVE
ER_KEYRING_COMPONENT_AWS_FILE_PARSE_FAIL	ED,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_RETRIEV
ER_KEYRING_COMPONENT_AWS_FILE_PATH_EMPTY	ED,
418	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_RETRIEV
ER_KEYRING_COMPONENT_AWS_FILE_READ_FAILED	ED,
418	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_SET_CE
ER_KEYRING_COMPONENT_AWS_FILE_WRITE_FAIL	ED,
418	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_SET_KEY
ER_KEYRING_COMPONENT_AWS_GENERATE_KEY_IN	VALID_PARAMETER,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_STORE
ER_KEYRING_COMPONENT_AWS_KEY_EXTRACT_FAIL	ED,
419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_STORE
ER_KEYRING_COMPONENT_AWS_READ_ONLY_LIMIT	ED,
419	ER_KEYRING_COMPONENT_KMIP_GENERATE_KEY_INV
ER_KEYRING_COMPONENT_AWS_WRITE_AFTER_READ	ENCRYPTION_FAILED,
419	ER_KEYRING_COMPONENT_KMIP_INIT_PRIMARY,
ER_KEYRING_COMPONENT_EXCEPTION, 374	426
ER_KEYRING_COMPONENT_KEYRING_FILE_DECRYPT	ER_KEYRING_COMPONENT_KMIP_INIT_STANDBY,
413	426

ER_KEYRING_COMPONENT_KMIP_INVALID_KEY_LENGTH, 425	ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE, 224
ER_KEYRING_COMPONENT_KMIP_INVALID_KEY_TYPE, 425	ER_KEYRING_OKV_FAILED_TO_FETCH_KEY, 224
ER_KEYRING_COMPONENT_KMIP_KEY_MISMATCH, 426	ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY, 223
ER_KEYRING_COMPONENT_KMIP_PATH_EMPTY, 425	ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY, 224
ER_KEYRING_COMPONENT_KMIP_STANDBY_SERVER_COUNT_EXCEEDED, 427	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY, 224
ER_KEYRING_COMPONENT_KMIP_TRYING_STANDBY_SERVER, 426	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR, 223
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_FAILED, 374	ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT, 224
ER_KEYRING_COMPONENT_NOT_INITIALIZED, 374	ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER, 224
ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE, 222	ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID, 224
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING, 223	ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE, 225
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP, 223	ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE, 224
ER_KEYRING_FAILED_TO_GET_FILE_STAT, 222	ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY, 224
ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT, 223	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY, 225
ER_KEYRING_FAILED_TO_REMOVE_FILE, 222	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE, 225
ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_KEYRING, 223	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE, 225
ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE, 222	ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE, 225
ER_KEYRING_FAILED_TO_TRUNCATE_FILE, 222	ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE, 225
ER_KEYRING_FILE_IO_ERROR, 222	ER_KEYRING_OKV_FAILED_TO_STORE_KEY, 224
ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE, 222	ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY, 224
ER_KEYRING_INCORRECT_FILE, 222	ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED, 223
ER_KEYRING_INVALID_KEY_LENGTH, 222	ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER, 223
ER_KEYRING_INVALID_KEY_TYPE, 221	ER_KEYRING_OKV_INVALID_KEY_TYPE, 223
ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEYRING, 223	ER_KEYRING_OKV_KEY_MISMATCH, 225
ER_KEYRING_LOGGER_ERROR_MSG, 212	ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED, 385
ER_KEYRING_MIGRATE_FAILED, 331	ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR, 222
ER_KEYRING_MIGRATE_MEMORY_DEALLOCATION_FAILED, 414	ER_KEYRING_UDF_KEYRING_SERVICE_ERROR, 70
ER_KEYRING_MIGRATE_SKIPPED_KEY, 414	ER_KEYRING_UNKNOWN_ERROR, 222
ER_KEYRING_MIGRATION_EXTRA_OPTIONS, 256	ER_KEY_COLUMN_DOES_NOT_EXIST, 8
ER_KEYRING_MIGRATION_FAILED, 205	ER_KEY_DOES_NOT_EXIST, 14
ER_KEYRING_MIGRATION_FAILURE, 71	ER_KEY_NOT_FOUND, 5
ER_KEYRING_MIGRATION_STATUS, 71	ER_KEY_PART_0, 26
ER_KEYRING_MIGRATION_SUCCESSFUL, 205	ER_KEY_REF_DOES_NOT_MATCH_TABLE_REF, 18
ER_KEYRING_OCI_HTTP_REQUEST, 393	
ER_KEYRING_OCI_INVALID_JSON, 393	
ER_KEYRING_OCI_PARSE_JSON, 393	
ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED, 224	
ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS, 224	

ER_KILLED_THREADS_OF_PLUGIN, 171	ER_LDAP_AUTH_CREATE_CONNECTION_KEY,
ER_KILLING_THREAD, 171	253
ER_KILL_DENIED_ERROR, 9	ER_LDAP_AUTH_CREATING_LDAP_CONNECTION,
ER_LANGUAGE_COMPONENT, 121	253
ER_LANGUAGE_COMPONENT_CANNOT_UNINSTALL,	ER_LDAP_AUTH_DEINIT_FAILED, 250
121	ER_LDAP_AUTH_DELETING_CONNECTION_KEY,
ER_LANGUAGE_COMPONENT_CONCURRENCY_LIMIT,	253
128	ER_LDAP_AUTH_DISTINGUISHED_NAME, 254
ER_LANGUAGE_COMPONENT_CONVERSION,	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECT
129	254
ER_LANGUAGE_COMPONENT_ERROR, 404	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT,
ER_LANGUAGE_COMPONENT_INFO, 404	250
ER_LANGUAGE_COMPONENT_INSTALL_ERROR,	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_C
412	250
ER_LANGUAGE_COMPONENT_INTERNAL, 128	ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNE
ER_LANGUAGE_COMPONENT_INTERNAL_ERROR,	250
412	ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY
ER_LANGUAGE_COMPONENT_KEYWORD, 129	252
ER_LANGUAGE_COMPONENT_NOT_AVAILABLE,	ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_R
121	252
ER_LANGUAGE_COMPONENT_RUNTIME, 128	ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNEC
ER_LANGUAGE_COMPONENT_SERVER_ERROR,	254
412	ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PL
ER_LANGUAGE_COMPONENT_SET_SYSTEM_VARIABLE,	252
129	ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEIN
ER_LANGUAGE_COMPONENT_TIMEZONE, 128	252
ER_LANGUAGE_COMPONENT_UNSUPPORTED_LANGUAGE,	ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT
121	252
ER_LANGUAGE_COMPONENT_UNSUPPORTED_TYPE,	ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_REC
129	252
ER_LANGUAGE_COMPONENT_VM_API_FUNCTION_ERROR,	ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT, 252
412	ER_LDAP_AUTH_FAILED_TO_SEARCH_DN, 255
ER_LANGUAGE_COMPONENT_VM_INTERNAL_ERROR,	ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET,
412	251
ER_LANGUAGE_COMPONENT_WARNING, 404	ER_LDAP_AUTH_FREEING_CONNECTION, 253
ER_LATITUDE_OUT_OF_RANGE, 80	ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL,
ER_LCTN_CHANGED, 205	253
ER_LCTN_NOT_FOUND, 331	ER_LDAP_AUTH_GRP_DN_PARSING_FAILED,
ER_LDAP_AUTH_CERTIFICATE_NAME, 252	347
ER_LDAP_AUTH_COMMUNICATION_HOST_INFO,	ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE,
254	347
ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER,	ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECT
253	347
ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL,	ER_LDAP_AUTH_GRP_IS_FULL_DN, 251
253	ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE,
ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED,	347
252	ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO,
ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER,	347
255	ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL,
ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL,	347
253	ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL,
ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING,	251
251	ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INF
ER_LDAP_AUTH_CONN_POOL_INITIALIZING,	347
250	ER_LDAP_AUTH_INFO_USER_MAP, 415
ER_LDAP_AUTH_CONN_POOL_NOT_CREATED,	ER_LDAP_AUTH_INIT_FAILED, 254
250	ER_LDAP_AUTH_LDAPS, 347
	ER_LDAP_AUTH_LDAP_INFO_NULL, 253

ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT, 252	ER_LDAP_MAPPING_GET_USER_PROXY, 347
ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED, 252	ER_LDAP_MAPPING_INFO, 347
ER_LDAP_AUTH_METHOD_TO_CLIENT, 254	ER_LDAP_MAPPING_IS_QUOTE, 349
ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP, 252	ER_LDAP_MAPPING_NON_DESIRED_STATE, 349
ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED, 254	ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP, 348
ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET, 253	ER_LDAP_MAPPING_PARSING_CURRENT_STATE, 348
ER_LDAP_AUTH_POOLED_CONNECTION_KEY, 253	ER_LDAP_MAPPING_PARSING_ERROR, 348
ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO, 250	ER_LDAP_MAPPING_PARSING_MAPPING_INFO, 348
ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION, 254	ER_LDAP_MAPPING_PROCESS_DELIMITER, 348
ER_LDAP_AUTH_POOL_REINITIALIZING, 251	ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND, 348
ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL, 253	ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND, 348
ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO, 254	ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA, 348
ER_LDAP_AUTH_SASL_PROCESS_SASL, 254	ER_LDAP_MAPPING_PROCESS_MAPPING, 348
ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT, 254	ER_LDAP_MAPPING_TRIMMING_SPACES, 348
ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME, 251	ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP, 347
ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND, 253	ER_LH_AVRO_CANNOT_PARSE_HEADER, 128
ER_LDAP_AUTH_SETTING_USERNAME, 251	ER_LH_AVRO_DECODING_ERR, 127
ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH, 250	ER_LH_AVRO_ENUM_CANNOT_CONVERT_CHARSET, 126
ER_LDAP_AUTH_STARTED_FOR_USER, 254	ER_LH_AVRO_ENUM_MISMATCH, 126
ER_LDAP_AUTH_STARTING_TLS, 253	ER_LH_AVRO_FILE_DATA_CORRUPT, 126
ER_LDAP_AUTH_TLS_CONF, 250	ER_LH_AVRO_FILE_ENDS_UNEXPECTEDLY, 126
ER_LDAP_AUTH_TLS_CONNECTION, 250	ER_LH_AVRO_HEADER_METADATA_ERR, 127
ER_LDAP_AUTH_USER_AUTH_DATA, 251	ER_LH_AVRO_HEADER_MISMATCH, 126
ER_LDAP_AUTH_USER_BIND_FAILED, 254	ER_LH_AVRO_HEADER_NO_SCHEMA, 127
ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS, 251	ER_LH_AVRO_INVALID_BLOCK_RECORD_COUNT, 126
ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED, 254	ER_LH_AVRO_INVALID_BLOCK_SIZE, 126
ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO, 251	ER_LH_AVRO_INVALID_NAME_IN_SCHEMA, 127
ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND, 340	ER_LH_AVRO_INVALID_RECORD, 133
ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES, 251	ER_LH_AVRO_INVALID_UNION, 126
ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP, 251	ER_LH_AVRO_NO_CODEC_IN_HEADER, 127
ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED, 251	ER_LH_AVRO_SCHEMA_DEPTH_EXCEEDS_MAX, 126
ER_LDAP_EMPTY_USERDN_PASSWORD, 354	ER_LH_AVRO_TYPE_CANNOT_CONVERT, 126
ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE, 348	ER_LH_AWS_AUTH_ERR, 125
ER_LDAP_MAPPING_EMPTY_MAPPING, 348	ER_LH_BAD_VALUE, 124
ER_LDAP_MAPPING_GETTING_NEXT_MAPPING, 348	ER_LH_CANNOT_CONVERT_STRING, 125
	ER_LH_CHARSET_UNSUPPORTED, 125
	ER_LH_COLUMN_ENGINE_ATTR_ERR, 131
	ER_LH_COLUMN_MAX_ERR, 125
	ER_LH_COLUMN_MISMATCH_ERR, 125
	ER_LH_COL_IS_EMPTY, 124
	ER_LH_COL_IS_EMPTY_WARN, 124
	ER_LH_COL_NAME_DUPLICATE, 139
	ER_LH_COL_NAME_MISSING, 139
	ER_LH_COL_NOT_NULLABLE, 124
	ER_LH_CP_COMMIT_FAILED, 132
	ER_LH_CP_NOT_ENABLED, 132
	ER_LH_CP_NO_VALIDATION_MODE, 132

ER_LH_CP_NO_VECTOR_STORE, 132	ER_LH_TOO_LARGE_ROW_ERR, 128
ER_LH_CP_TOO_MANY_CHANGES, 131	ER_LH_TOO_LARGE_VALUE_ERR, 128
ER_LH_CSV_PARSING_ERR, 125	ER_LH_UNSTRUCTURED_ENCODING_ERR, 131
ER_LH_DATETIME_FORMAT, 125	ER_LH_UNSTRUCTURED_FILE_PARSE_ERR, 130
ER_LH_DECIMAL_OOM_ERR, 124	ER_LH_UNSTRUCTURED_FILE_TOO_LARGE, 131
ER_LH_DECIMAL_PRECISION_EXCEEDS_SCHEMA, 124	ER_LH_UNSTRUCTURED_FILE_TYPE_MISMATCH_ERR, 131
ER_LH_DECIMAL_UNKNOWN_ERR, 124	ER_LH_UNSTRUCTURED_INVALID_LANGUAGE, 132
ER_LH_DECOMPRESSION_ERR, 133	ER_LH_UNSTRUCTURED_NO_DATA_FOUND, 130
ER_LH_DELTA_METADATA_READ_ERROR, 140	ER_LH_UNSTRUCTURED_OBJ_READ_ERR, 131
ER_LH_DELTA_SCHEMA_MISMATCH, 139	ER_LH_UNSTRUCTURED_OCI_GENAI_FAILURE, 139
ER_LH_DELTA_UNSUPPORTED_ERROR, 140	ER_LH_UNSTRUCTURED_PAGE_CHUNK_WARN, 133
ER_LH_DUPLICATE_FILE, 126	ER_LH_UNSTRUCTURED_PARTIAL_FILE_PARSE_ERR, 139
ER_LH_EMPTY_FILE, 126	ER_LH_UNSTRUCTURED_SCHEMA_ERR, 131
ER_LH_EXCEEDS_MAX, 125	ER_LH_UNSTRUCTURED_TOO_MANY_CHUNKS, 133
ER_LH_EXCEEDS_MIN, 124	ER_LH_UNSTRUCTURED_TRUNCATION_ERROR, 133
ER_LH_FORMAT_HEADER_NO_MAGIC_BYTES, 126	ER_LH_USER_DATA_ACCESS_FAILED, 130
ER_LH_GENCOL_ERROR, 140	ER_LH_VECTOR_TOO_MANY_ENTRIES, 132
ER_LH_INFER_COL_NAME_MISMATCH, 139	ER_LH_WARN_COL_MISSING_NOT_NULLABLE, 124
ER_LH_INFER_FILE_HAS_NO_DATA, 127	ER_LH_WARN_DATETIME_MULTIPLE_PARAM_USE, 140
ER_LH_INFER_JSON_INVALID_SCHEMA, 130	ER_LH_WARN_DECIMAL_ROUNDING, 124
ER_LH_INFER_NO_DATA, 128	ER_LH_WARN_EXCEEDS_MAX_TRUNCATING, 125
ER_LH_INFER_NO_FILES, 128	ER_LH_WARN_EXCEEDS_MIN_TRUNCATING, 125
ER_LH_INFER_NUM_COL_MISMATCH, 127	ER_LH_WARN_INFER_SKIPPED_FILES, 127
ER_LH_INFER_WARN_GOT_EXCEPTION, 128	ER_LH_WARN_INFER_SKIPPED_LINES, 127
ER_LH_INVALID_JSON_FILE_FORMAT_SCHEMA, 130	ER_LH_WARN_INFER_USE_DEFAULT_COL_NAMES, 128
ER_LH_INVALID_VALUE_IN_VECTOR, 133	ER_LH_WARN_INFER_USE_DEFAULT_DELIMITERS, 133
ER_LH_JSON_FILE_FORMAT_WARN_INFER_SCHEMA, 130	ER_LH_WARN_SUMMARY, 132
ER_LH_JSON_PARSING, 129	ER_LH_WARN_TRUNCATED, 125
ER_LH_NO_FILES_FOUND, 126	ER_LH_WARN_VECTOR_LOSSY_CONVERSION, 133
ER_LH_NO_FILES_FOUND_NO_SECURE_FILE_PRIV, 139	ER_LIBRARIES_NOT_SUPPORTED, 132
ER_LH_NO_SEGMENTS_GENERATED, 131	ER_LIBRARY_INVALID, 133
ER_LH_OOM, 127	ER_LIMITED_PART_RANGE, 34
ER_LH_OUT_OF_RANGE, 125	ER_LOAD_BULK_DATA_FAILED, 120
ER_LH_PARQUET_CANNOT_LOCATE_OFFSET, 127	ER_LOAD_BULK_DATA_UNSORTED, 118
ER_LH_PARQUET_CANNOT_LOCATE_SCHEMA, 127	ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL, 120
ER_LH_PARQUET_CANNOT_READ_HEADER, 128	ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOAD, 396
ER_LH_PARQUET_CANT_OPEN_FILE, 128	ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD, 120
ER_LH_PARQUET_DECIMAL_CONVERSION_ERR, 125	
ER_LH_PARQUET_NON_UTF8_FILE_ENC, 127	
ER_LH_PARQUET_ROW_GROUP_SIZE_EXCEEDS_MAX, 127	
ER_LH_PARQUET_SCHEMA_MISMATCH, 127	
ER_LH_PARQUET_TYPE_CANNOT_CONVERT, 127	
ER_LH_REAL_IS_NAN, 125	
ER_LH_RESOURCE_PRINCIPAL_BUCKET_ERR, 126	
ER_LH_RESOURCE_PRINCIPAL_ERR, 125	
ER_LH_STRING_TOO_LONG, 125	

ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD, 396	ER_LOWER_CASE_TABLE_NAMES_USING_2, 150
ER_LOAD_BULK_JSON_ERROR, 416	ER_MALFORMED_GTID_SET_ENCODING, 49
ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY, 154	ER_MALFORMED_GTID_SET_SPECIFICATION, 49
ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR, 27	ER_MALFORMED_GTID_SPECIFICATION, 49
ER_LOAD_INFO, 8	ER_MALFORMED_PACKET, 53
ER_LOCAL_VARIABLE, 17	ER_MANDATORY_ROLE, 80
ER_LOCKING_SERVICE_DEADLOCK, 66	ER_MASTER_KEY_ROTATION_BINLOG_FAILED, 70
ER_LOCKING_SERVICE_TIMEOUT, 67	ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE, 70
ER_LOCKING_SERVICE_WRONG_NAME, 66	ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE, 70
ER_LOCK_ABORTED, 43	ER_MAXVALUE_IN_VALUES_IN, 41
ER_LOCK_DEADLOCK, 16	ER_MAX_PREPARED_STMT_COUNT_REACHED, 31
ER_LOCK_NOWAIT, 77	ER_MDL_OUT_OF_RESOURCES, 106
ER_LOCK_ORDER_DEPENDENCIES_SYNTAX, 354	ER_MECAB_CHARSET_LOADED, 207
ER_LOCK_ORDER_FAILED_READ_FILE, 354	ER_MECAB_CREATE_LATTICE_FAILED, 207
ER_LOCK_ORDER_FAILED_WRITE_FILE, 354	ER_MECAB_CREATING_MODEL, 206
ER_LOCK_ORDER_INIT_FAILED, 353	ER_MECAB_FAILED_TO_CREATE_MODEL, 206
ER_LOCK_ORDER_MESSAGE, 354	ER_MECAB_FAILED_TO_CREATE_TRIGGER, 207
ER_LOCK_ORDER_SCANNER_SYNTAX, 355	ER_MECAB_NOT_SUPPORTED, 206
ER_LOCK_OR_ACTIVE_TRANSACTION, 15	ER_MECAB_NOT_VERIFIED, 206
ER_LOCK_REFUSED_BY_ENGINE, 70	ER_MECAB_OOM_WHILE_PARSING_TEXT, 207
ER_LOCK_TABLE_FULL, 16	ER_MECAB_PARSE_FAILED, 207
ER_LOCK_WAIT_TIMEOUT, 16	ER_MECAB_UNSUPPORTED_CHARSET, 207
ER_LOG_BIN_BETTER_WITH_NAME, 151	ER_MESSAGE_AND_STATEMENT, 42
ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP, 402	ER_MFA_METHODS_IDENTICAL, 113
ER_LOG_CANNOT_WRITE, 141	ER_MFA_METHODS_INVALID_ORDER, 113
ER_LOG_CANNOT_WRITE_EXTENDED, 357	ER_MFA_METHOD_EXISTS, 112
ER_LOG_CLIENT_INTERACTION_TIMEOUT, 414	ER_MFA_METHOD_NOT_EXISTS, 112
ER_LOG_COMPONENT_CANNOT_INIT, 371	ER_MFA_PLUGIN_NOT_LOADED, 384
ER_LOG_COMPONENT_FLUSH_FAILED, 379	ER_MFA_PLUGIN_USER_ATTRIBUTES_CORRUPT, 384
ER_LOG_DEPRECATED_NON_COMPOSABLE_MULTIPLE_ENGINES, 415	ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE, 201
ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE, 150	ER_MIGRATE_TABLE_TO_DD_OOM, 361
ER_LOG_FILE_CANNOT_OPEN, 217	ER_MISPLACED_INTO, 104
ER_LOG_FILE_INVALID, 150	ER_MISSING_ACL_SYSTEM_TABLE, 196
ER_LOG_GENERAL_CANNOT_OPEN, 141	ER_MISSING_CURRENT_PASSWORD, 99
ER_LOG_IN_USE, 26	ER_MISSING_GRANT_SYSTEM_TABLE, 196
ER_LOG_OUTPUT_CONTRADICTION, 150	ER_MISSING_HA_CREATE_OPTION, 58
ER_LOG_PARTITION_PREFIX_KEY_NOT_SUPPORTED, 415	ER_MISSING_JSON_TABLE_VALUE, 83
ER_LOG_PRINTF_MSG, 204	ER_MISSING_JSON_VALUE, 105
ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NAME_OR_SETTINGS, 359	ER_MISSING_KEY, 57
ER_LOG_PURGE_NO_FILE, 38	ER_MISSING_SKIP_REPLICA, 20
ER_LOG_PURGE_UNKNOWN_ERR, 26	ER_MISSING_TABLESPACE_FILE, 80
ER_LOG_SANITIZATION, 414	ER_MIXING_NOT_ALLOWED, 17
ER_LOG_SLOW_CANNOT_OPEN, 141	ER_MIX_HANDLER_ERROR, 33
ER_LOG_SYSLOG_CANNOT_OPEN, 141	ER_MIX_OF_GROUP_FUNC_AND_FIELDS, 12
ER_LONGITUDE_OUT_OF_RANGE, 80	ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2, 63
ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CIFS, 150	ER_MTA_CANT_PARALLEL, 48
ER_LOWER_CASE_TABLE_NAMES_USING_0, 150	ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS, 51
	ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX, 55
	ER_MTA_FEATURE_IS_NOT_SUPPORTED, 48

ER_MTA_INCONSISTENT_DATA, 48	ER_NET_PACKET_TOO_LARGE, 13
ER_MTA_RECOVERY_FAILURE, 51	ER_NET_READ_ERROR, 13
ER_MTA_RESET_WORKERS, 51	ER_NET_READ_ERROR_FROM_PIPE, 13
ER_MTA_UPDATED_DBS_GREATER_MAX, 48	ER_NET_READ_INTERRUPTED, 13
ER_MTR_MSG_1, 380	ER_NET_UNCOMPRESS_ERROR, 13
ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME, 103	ER_NET_WAIT_ERROR, 353
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR, 33	ER_NET_WAIT_ERROR2, 375
ER_MULTIPLE_INTO_CLAUSES, 104	ER_NET_WRITE_INTERRUPTED, 13
ER_MULTIPLE_JSON_VALUES, 105	ER_NEW_ABORTING_CONNECTION, 14
ER_MULTIPLE_PRI_KEY, 7	ER_NO, 3
ER_MULTI_UPDATE_KEY_CONFLICT, 44	ER_NONEXISTING_GRANT, 12
ER_MUST_CHANGE_PASSWORD, 52	ER_NONEXISTING_PROC_GRANT, 27
ER_MUST_CHANGE_PASSWORD_LOGIN, 55	ER_NONEXISTING_TABLE_GRANT, 12
ER_MYINIT_FAILED, 149	ER_NONPOSITIVE_RADIUS, 85
ER_MYISAM_CHECK_METHOD_ERROR, 203	ER_NONUNIQ_TABLE, 7
ER_MYISAM_CRASHED_ERROR, 203	ER_NONUPDATEABLE_COLUMN, 24
ER_MYISAM_CRASHED_ERROR_IN, 155	ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT, 94
ER_MYISAM_CRASHED_ERROR_IN_THREAD, 155	ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN, 64
ER_MYSQLBACKUP_CLIENT_MSG, 115	ER_NON_DML_DYNAMIC_PARAMETERS, 131
ER_MYSQLBACKUP_MSG, 357	ER_NON_GROUPING_FIELD_USED, 31
ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD, 344	ER_NON_INSERTABLE_TABLE, 31
ER_MY_MALLOC_GETPROCADDRESS_FAILED, 386	ER_NON_ISO_SELECTION, 59
ER_MY_MALLOC_LOADLIBRARY_FAILED, 386	ER_NON_SCALAR_USED_AS_KEY, 130
ER_MY_MALLOC_USING_JEMALLOC, 386	ER_NON_UNIQ_ERROR, 6
ER_MY_MALLOC_USING_STD_MALLOC, 386	ER_NON_UPDATABLE_TABLE, 21
ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STREAM, 182	ER_NORMAL_SERVER_SHUTDOWN, 331
ER_M_BIGGER_THAN_D, 28	ER_NOTE_COMPONENT_FIREWALL_RELOAD, 424
ER_NAME_BECOMES_EMPTY, 31	ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME, 393
ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE, 201	ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS, 399
ER_NATIVE_FCT_NAME_COLLISION, 37	ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS, 399
ER_NDBINFO_NOT_UPGRADING_SCHEMA, 363	ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIED, 374
ER_NDBINFO_UPGRADING_SCHEMA, 363	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY, 374
ER_NDBINFO_UPGRADING_SCHEMA_FAIL, 363	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE, 374
ER_NDB_LOG_ENTRY, 189	ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR, 374
ER_NDB_LOG_ENTRY_WITH_PREFIX, 189	ER_NOTE_KEYRING_COMPONENT_EMPTY_DATA_ID, 413
ER_NDB_REPLICATION_SCHEMA_ERROR, 39	ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED, 375
ER_NEED_FILE_INSTEAD_OF_DIR, 151	ER_NOTE_KEYRING_COMPONENT_INITIALIZED, 374
ER_NEED_LOG_BIN, 151	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_IDENTIFIED, 375
ER_NEED_REPREPARE, 39	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_IDENTIFIED, 413
ER_NETWORK_NAMESPACES_NOT_SUPPORTED, 352	ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR, 413
ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG, 352	ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR, 413
ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WRITE, 352	
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE, 332	
ER_NET_ERROR_ON_WRITE, 13	
ER_NET_FCNTL_ERROR, 13	
ER_NET_OK_PACKET_TOO_LARGE, 62	
ER_NET_PACKETS_OUT_OF_ORDER, 13	

ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATION_FAILED, 375	ER_ORON_SUCH_INDEX_PARAM, 12
ER_NOTE_KEYRING_COMPONENT_NOT_INITIALIZED, 413	ER_NO_SUCH_TABLE, 12
ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND, 374	ER_NO_SUCH_THREAD, 9
ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED, 375	ER_NO_SUCH_USER, 30
ER_NOTE_KEYRING_COMPONENT_STORE_FAILED, 375	ER_NO_SUPER_WITHOUT_USER_PLUGIN, 161
ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_SIZE, 374	ER_NO_SYSTEM_SCHEMA_ACCESS, 75
ER_NOT_ALLOWED_COMMAND, 12	ER_NO_SYSTEM_TABLESPACE_ACCESS, 75
ER_NOT_ALLOWED_WITH_START_TRANSACTION, 106	ER_NO_SYSTEM_TABLE_ACCESS, 75
ER_NOT_FORM_FILE, 5	ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLES, 75
ER_NOT_HINT_UPDATABLE_VARIABLE, 81	ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE, 75
ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS, 85	ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE, 76
ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS, 80	ER_NO_SYSTEM_VIEW_ACCESS, 80
ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS, 85	ER_NO_TABLES_USED, 9
ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS, 217	ER_NO_THD_NO_UUID, 144
ER_NOT_KEYFILE, 5	ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA, 31
ER_NOT_RIGHT_NOW, 149	ER_NO_UNIQUE_LOGFILE, 9
ER_NOT_SUPPORTED_AUTH_MODE, 19	ER_NPIPE_CANT_CREATE, 191
ER_NOT_SUPPORTED_YET, 18	ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR, 166
ER_NOT_VALID_PASSWORD, 52	ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR, 166
ER_NO_ACCESS_TO_NATIVE_FCT, 76	ER_NPIPE_PIPE_ALREADY_IN_USE, 166
ER_NO_BINARY_LOGGING, 26	ER_NULL_CANT_BE_PERSISTED_FOR_READONLY, 121
ER_NO_BINLOG_ERROR, 34	ER_NULL_COLUMN_IN_INDEX, 11
ER_NO_CSV_NO_LOG_TABLES, 150	ER_NULL_IN_VALUES_LESS_THAN, 36
ER_NO_DB_ERROR, 6	ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE, 68
ER_NO_DEFAULT, 17	ER_NUM_THREADS_STILL_ALIVE, 406
ER_NO_DEFAULT_FOR_FIELD, 25	ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECK, 358
ER_NO_DEFAULT_FOR_VIEW_FIELD, 28	ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION, 359
ER_NO_ERROR_LOG_PARSER_CONFIGURED, 370	ER_OLD_FILE_FORMAT, 30
ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT, 38	ER_OLD_KEYFILE, 5
ER_NO_FT_MATERIALIZED_SUBQUERY, 58	ER_OLD_TEMPORALS_UPGRADED, 56
ER_NO_PARTITION_FOR_GIVEN_VALUE, 34	ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT, 46
ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT, 37	ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326, 84
ER_NO_PARTS_ERROR, 33	ER_ONLY INTEGERS ALLOWED, 37
ER_NO_PATCH_DOWNGRADE_FOR_INNOVATION_REPLACEMENT, 422	ER_ONLY_ON_RANGE_LIST_PARTITION, 34
ER_NO_PATH_FOR_SHARED_LIBRARY, 336	ER_OOM, 149
ER_NO_PERMISSION_TO_CREATE_USER, 16	ER_OOM_SAVE_GTIDS, 331
ER_NO_QUERY_PLAN_FOUND, 131	ER_OPEN_AS_READONLY, 5
ER_NO_REFERENCED_ROW, 16	ER_OPEN_ROLE_TABLES, 73
ER_NO_REFERENCED_ROW_2, 30	ER_OPERAND_COLUMNS, 18
ER_NO_SECURE_TRANSPORTS_CONFIGURED, 68	ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY, 112
ER_NO_SESSION_TEMP, 99	ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGING, 115
ER_NO_SUCH_DB, 72	ER_OPTION_PREVENTS_STATEMENT, 21
	ER_OPT_WRONG_TREE, 140
	ER_OUTOFMEMORY, 5
	ER_OUT_OF_RESOURCES, 5

ER_OUT_OF_SORTMEMORY, 5	ER_PASSWORD_NOT_ALLOWED, 11
ER_PAGE_TRACKING_CANNOT_PURGE, 93	ER_PASSWORD_NO_MATCH, 11
ER_PAGE_TRACKING_NOT_STARTED, 93	ER_PATH_IN_DATADIR, 80
ER_PAGE_TRACKING_RANGE_NOT_TRACKED, 93	ER_PATH_LENGTH, 43
ER_PARSER_TRACE, 140	ER_PERFORMANCE_SCHEMA_VERSION_CHANGE, 402
ER_PARSE_ERROR, 7	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_INIT_FAILED, 194
ER_PARSE_ERROR_IN_DIGEST_FN, 83	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_INIT_FAILED, 194
ER_PARSING_VIEW, 144	ER_PERFSCHEMA_INIT_FAILED, 151
ER_PARTIAL_REVOKES_EXIST, 100	ER_PERFSCHEMA_TABLES_INIT_FAILED, 195
ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXIST, 100	ER_PERSISTED_VARIABLES_DECRYPTION_FAILED, 385
ER_PARTITIONS_MUST_BE_DEFINED_ERROR, 32	ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED, 385
ER_PARTITION_CLAUSE_ON_NONPARTITIONED, 47	ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED, 385
ER_PARTITION_COLUMN_LIST_ERROR, 41	ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT, 386
ER_PARTITION_CONST_DOMAIN_ERROR, 36	ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_EMPTY, 385
ER_PARTITION_ENTRY_ERROR, 33	ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND, 385
ER_PARTITION_EXCHANGE_DIFFERENT_OPTION, 46	ER_PERSISTENT_PRIVILEGES_BOOTSTRAP, 195
ER_PARTITION_EXCHANGE_FOREIGN_KEY, 47	ER_PERSIST_ONLY_ACCESS_DENIED_ERROR, 80
ER_PARTITION_EXCHANGE_PART_TABLE, 46	ER_PERSIST_OPTION_HOST_TRUNCATED, 352
ER_PARTITION_EXCHANGE_TEMP_TABLE, 46	ER_PERSIST_OPTION_STATUS, 217
ER_PARTITION_FIELDS_TOO_LONG, 41	ER_PERSIST_OPTION_USER_TRUNCATED, 352
ER_PARTITION_FUNCTION_FAILURE, 34	ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL_FILTER, 201
ER_PARTITION_FUNCTION_IS_NOT_ALLOWED, 36	ER_PFS_MALLOC_ARRAY_OOM, 202
ER_PARTITION_FUNC_NOT_ALLOWED_ERROR, 32	ER_PFS_MALLOC_ARRAY_OVERFLOW, 202
ER_PARTITION_HANDLER_ADMIN_MSG, 203	ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED, 197
ER_PARTITION_INSTEAD_OF_SUBPARTITION, 47	ER_PLUGIN_CANNOT_BE_LOADED, 181
ER_PARTITION_MAXVALUE_ERROR, 32	ER_PLUGIN_CANNOT_BE_UNINSTALLED, 56
ER_PARTITION_MERGE_ERROR, 36	ER_PLUGIN_CANT_LOAD, 181
ER_PARTITION_MGMT_ON_NONPARTITIONED, 33	ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE, 181
ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW, 191	ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS, 182
ER_PARTITION_NAME, 40	ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLE, 216
ER_PARTITION_NOT_DEFINED_ERROR, 33	ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE, 216
ER_PARTITION_NO_TEMPORARY, 36	ER_PLUGIN_DELETE_BUILTIN, 39
ER_PARTITION_PREFIX_KEY_NOT_SUPPORTED, 129	
ER_PARTITION_REQUIRES_VALUES_ERROR, 32	
ER_PARTITION_WRONG_NO_PART_ERROR, 32	
ER_PARTITION_WRONG_NO_SUBPART_ERROR, 32	
ER_PARTITION_WRONG_VALUES_ERROR, 32	
ER_PART_EXPR_TOO_LONG, 80	
ER_PASSWORD_ANONYMOUS_USER, 11	
ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN, 100	
ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_PLUGIN, 83	
ER_PASSWORD_EXPIRE_ANONYMOUS_USER, 58	
ER_PASSWORD_FORMAT, 53	

ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS, 171	ER_QUERY_INTERRUPTED, 22
ER_PLUGIN_DISABLED, 181	ER_QUERY_ON_FOREIGN_DATA_SOURCE, 29
ER_PLUGIN_EXCEPTION_OPERATION_FAILED, 396	ER_QUERY_TIMEOUT, 59
ER_PLUGIN_FAILED_DEINITIALIZATION, 180	ER_RANGE_NOT_INCREASING_ERROR, 32
ER_PLUGIN_FAILED_TO_OPEN_TABLE, 335	ER_READING_TABLE_FAILED, 154
ER_PLUGIN_FAILED_TO_OPEN_TABLES, 335	ER_READY, 8
ER_PLUGIN_FORCING_SHUTDOWN, 181	ER_READ_LOG_EVENT_FAILED, 200
ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES, 181	ER_READ_ONLY_MODE, 53
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINSTALLATION, 180	ER_READ_ONLY_TRANSACTION, 16
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN, 181	ER REALLY_RUN_AS_ROOT, 148
ER_PLUGIN_INIT_FAILED, 153	ER_RECORD_FILE_FULL, 10
ER_PLUGIN_INSTALL_ERROR, 340	ER_RECOVERING_TABLE, 182
ER_PLUGIN_INVALID_TABLE_DEFINITION, 378	ER_REDUCED_DBLWR_FILE_CORRUPTED, 401
ER_PLUGIN_IS_NOT_LOADED, 34	ER_REDUCED_DBLWR_PAGE_FOUND, 401
ER_PLUGIN_IS_PERMANENT, 44	ER_REFERENCED_TRG_DOES_NOT_EXIST, 58
ER_PLUGIN_LOAD_OPTIONS_IGNORED, 358	ER_REGEXP_BAD_ESCAPE_SEQUENCE, 84
ER_PLUGIN_LOAD_PARAMETER_TOO_LONG, 181	ER_REGEXP_BAD_INTERVAL, 84
ER_PLUGIN_NOT_EARLY, 96	ER_REGEXP_BUFFER_OVERFLOW, 84
ER_PLUGIN_NOT_EARLY_DUP, 353	ER_REGEXP_ERROR, 12
ER_PLUGIN_NO_INSTALL, 46	ER_REGEXP_ILLEGAL_ARGUMENT, 84
ER_PLUGIN_NO_INSTALL_DUP, 353	ER_REGEXP_INDEX_OUTOFBOUNDS_ERROR, 84
ER_PLUGIN_NO_UNINSTALL, 45	ER_REGEXP_INTERNAL_ERROR, 84
ER_PLUGIN_OOM, 181	ER_REGEXP_INVALID_BACK_REF, 85
ER_PLUGIN_PARSING_OPTIONS_FAILED, 181	ER_REGEXP_INVALID_CAPTURE_GROUP_NAME, 99
ER_PLUGIN_REGISTRATION_DONE, 112	ER_REGEXP_INVALID_FLAG, 100
ER_PLUGIN_REGISTRATION_FAILED, 180	ER_REGEXP_INVALID_RANGE, 85
ER_PLUGIN_REQUIRES_REGISTRATION, 112	ER_REGEXP_LOOK_BEHIND_LIMIT, 85
ER_PLUGIN_SHUTTING_DOWN_PLUGIN, 180	ER_REGEXP_MAX_LT_MIN, 84
ER_PLUGIN_UNINSTALL_ERROR, 340	ER_REGEXP_MISMATCHED_PAREN, 84
ER_PLUGIN_UNKNOWN_VARIABLE_TYPE, 181	ER_REGEXP_MISSING_CLOSE_BRACKET, 85
ER_PLUGIN_VARIABLE_MISSING_NAME, 181	ER_REGEXP_MISSING_FILE, 114
ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL, 181	ER_REGEXP_MISSING_ICU_DATADIR, 384
ER_PLUGIN_VARIABLE_SET_READ_ONLY, 181	ER_REGEXP_MISSING_RESOURCE, 114
ER_POINTLESS_WITHOUT_SLOWLOG, 145	ER_REGEXP_PATTERN_TOO_BIG, 85
ER_POLYGON_TOO_LARGE, 87	ER_REGEXP_RULE_SYNTAX, 84
ER_PREPARE_FOR_PRIMARY_ENGINE, 379	ER_REGEXP_STACK_OVERFLOW, 85
ER_PREPARE_FOR_SECONDARY_ENGINE, 349	ER_REGEXP_TIME_OUT, 85
ER_PREVENTS_VARIABLE_WITHOUT_RBR, 64	ER_REGEXP_UNIMPLEMENTED, 84
ER_PRIMARY_CANT_HAVE_NULL, 14	ER_REGEX_NUMBER_TOO_BIG, 108
ER_PRIVILEGE_DEREGISTRATION, 400	ER_RELAY_LOG_FAIL, 26
ER_PRIVILEGE_REGISTRATION, 400	ER_RELAY_LOG_INIT, 26
ER_PRIVILEGE_SYSTEM_INIT_FAILED, 195	ER_RELAY_LOG_SPACE_LIMIT_DISABLED, 338
ER_PROCACCESS_DENIED_ERROR, 26	ER_RELOAD_KEYRING_FAILURE, 111
ER_PROC_AUTO_GRANT_FAIL, 27	ER_REMOVED_SPACES, 31
ER_PROC_AUTO_REVOKE_FAIL, 27	ER_RENAMED_NAME, 40
ER_PROTOCOL_COMPRESSION_RESET_LOG, 357	ER_RENAME_ROLE, 74
ER_PS_MANY_PARAM, 26	ER_REORG_HASH_ONLY_ON_SAME_NO, 33
ER_PS_NO_RECURSION, 30	ER_REORG_NO_PARAM_ERROR, 34
ER_QUALIFY_WITHOUT_WINDOW_FUNCTION, 123	ER_REORG_OUTSIDE_RANGE, 34
	ER_REORG_PARTITION_NOT_EXIST, 34
	ER_REPLACE_INACCESSIBLE_ROWS, 61
	ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK, 395
	ER_REPLICA_AM_INIT_REPOSITORY, 56
	ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP, 372

ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID, 372	AND REPLICAS DO NOT CONTAIN TRANSACTION, 51
ER_REPLICA_CANT_CREATE_CONVERSION, 43	ER_REPLICA_SOURCE_COM_FAILURE, 332
ER_REPLICA_CANT_USE_TEMPDIR, 178	ER_REPLICA_SQL_THREAD_MUST_STOP, 58
ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED, 178	ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS, 165
ER_REPLICA_CHANNEL_DOES_NOT_EXIST, 62	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS, 165
ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP, 58	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS, 165
ER_REPLICA_CHANNEL_MUST_STOP, 62	ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED, 166
ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG, 62	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION, 165
ER_REPLICA_CHANNEL_NOT_RUNNING, 62	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION, 165
ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED, 67	ER_REPLICA_THREAD, 15
ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER, 63	ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR, 59
ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP, 63	ER_REQUIRES_PRIMARY_KEY, 14
ER_REPLICA_CHANNEL_WAS_NOT_RUNNING, 63	ER_REQUIRE_ROW_FORMAT_INVALID_VALUE, 103
ER_REPLICA_CHANNEL_WAS_RUNNING, 63	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATED, 120
ER_REPLICA_CM_INIT_REPOSITORY, 56	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATED, 397
ER_REPLICA_CONFIGURATION, 51	ER_RESERVED_SYNTAX, 26
ER_REPLICA_CORRUPT_EVENT, 38	ER_RESERVED_TABLESPACE_NAME, 87
ER_REPLICA_CREATE_EVENT_FAILURE, 332	ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE, 76
ER_REPLICA_FATAL_ERROR, 332	ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER, 40
ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE, 57	ER_RESOURCE_GROUP_BIND_FAILED, 82
ER_REPLICA_HEARTBEAT_FAILURE, 332	ER_RESOURCE_GROUP_BUSY, 82
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE, 39	ER_RESOURCE_GROUP_DISABLED, 82
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 44	ER_RESOURCE_GROUP_EXISTS, 82
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 44	ER_RESOURCE_GROUP_IS_DISABLED, 197
ER_REPLICA_IGNORED_SSL_PARAMS, 20	ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED, 196
ER_REPLICA_IGNORED_TABLE, 18	ER_RESOURCE_GROUP_NOT_EXISTS, 82
ER_REPLICA_IGNORE_SERVER_IDS, 41	ER_RESOURCE_GROUP_POST_INIT_FAILED, 194
ER_REPLICA_INCIDENT, 332	ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED, 194
ER_REPLICA_KILLED_AFTER_RECONNECT, 201	ER_RESOURCE_GROUP_VALIDATION_FAILED, 196
ER_REPLICA_MAX_CHANNELS_EXCEEDED, 62	ER_RESTART_RECEIVED_INFO, 205
ER_REPLICA_MULTIPLE_CHANNELS_CMD, 62	ER_RESTART_SERVER_FAILED, 85
ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY, 62	ER_RESULT_SIZE_LIMIT_EXCEEDED, 128
ER_REPLICA_NOT_RUNNING, 15	ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT, 198
ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS, 201	ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY, 197
ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL, 87	ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE, 197
ER_REPLICA_RECONNECT_FAILED, 200	ER_RES_GRP_FEATURE_NOT_AVAILABLE, 198
ER_REPLICA_RELAY_LOG_PURGE_FAILED, 195	ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED, 198
ER_REPLICA_RELAY_LOG_READ_FAILURE, 332	ER_RES_GRP_INVALID_THREAD_PRIORITY, 198
ER_REPLICA_RELAY_LOG_TRUNCATE_INFO, 195	
ER_REPLICA_RELAY_LOG_WRITE_FAILURE, 332	

ER_RES_GRP_INVALID_VCPU_ID, 204	ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF, 107
ER_RES_GRP_INVALID_VCPU_RANGE, 204	ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE, 369
ER_RES_GRP_SET_THREAD_PRIORITY_FAILED, 197	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF, 107
ER_RES_GRP_SET_THR_AFFINITY_FAILED, 197	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL, 370
ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED, 198	ER_RPL_ASYNC_REPLICA_IO_THD_FETCH_GROUP_MAJOR, 107
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPU, 198	ER_RPL_ASYNC_SENDER_ADDED, 371
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THR, 198	ER_RPL_ASYNC_SENDER_REMOVED, 371
ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED, 197	ER_RPL_BINLOG_FILTERS_OOM, 147
ER_RETRYING_REPAIR_WITHOUT_QUICK, 182	ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED, 153
ER_RETRYING_REPAIR_WITH_KEYCACHE, 182	ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO, 171
ER_REVOKE_GRANTS, 20	ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT, 171
ER_REWRITER_LOAD_FAILED, 217	ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA, 171
ER_REWRITER_OOM, 217	ER_RPL_BINLOG_STARTING_DUMP, 171
ER_REWRITER_QUERY_ERROR_MSG, 215	ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED, 153
ER_REWRITER_QUERY_FAILED, 215	ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED, 153
ER_REWRITER_READ_FAILED, 217	ER_RPL_CANNOT_OPEN_RELAY_LOG, 382
ER_REWRITER_TABLE_MALFORMED_ERROR, 217	ER_RPL_CANT_ADD_DO_TABLE, 149
ER_ROLE_GRANTED_TO_ITSELF, 110	ER_RPL_CANT_ADD_IGNORE_TABLE, 149
ER_ROLE_NOT_GRANTED, 74	ER_RPL_CANT_CREATE_REPLICA_THREAD, 174
ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG, 200	ER_RPL_CANT_FIND_FOLLOWUP_FILE, 176
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SIZE, 47	ER_RPL_CANT_HAVE_SAME_BASENAME, 192
ER_ROW_DOES_NOT_MATCH_PARTITION, 47	ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO, 178
ER_ROW_IN_WRONG_PARTITION, 55	ER_RPL_CANT_MAKE_PATHS, 151
ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR, 155	ER_RPL_CANT_OPEN_INFO_TABLE, 166
ER_ROW_IS_REFERENCED, 17	ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO, 179
ER_ROW_IS_REFERENCED_2, 30	ER_RPL_CANT_SCAN_INFO_TABLE, 167
ER_ROW_SINGLE_PARTITION_FIELD_ERROR, 41	ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP, 97
ER_RPL_AM_INIT_INFO_MSG, 203	ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID, 167
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT, 371	ER_RPL_CORRUPTED_INFO_TABLE, 167
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM, 371	ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE, 167
ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST, 371	ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER, 93
ER_RPL_ASYNC_CHECK_CONNECTION_ERROR, 411	ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 93
ER_RPL_ASYNC_GET_GROUP_MEMBERSHIP_DETAILS, 411	ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 91
ER_RPL_ASYNC_MANAGED_NAME_ADDED, 371	ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 92
ER_RPL_ASYNC_MANAGED_NAME_REMOVED, 371	ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 92
ER_RPL_ASYNC_MONITOR_IO_THD_FETCH_GROUP_MEMBERSHIP_ERROR, 411	
ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED, 397	
ER_RPL_ASYNC_READ_FAILOVER_TABLE, 372	

ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS, 92	ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX, 167
ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 92	ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX, 167
ER_RPL_ENCRYPTION_HEADER_ERROR, 92	ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION, 381
ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 91	ER_RPL_INFINITY_DENIED, 152
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 92	ER_RPL_INFINITY_IGNORED, 152
ER_RPL_ENCRYPTION_KEY_NOT_FOUND, 91	ER_RPL_INFO_DATA_TOO_LONG, 47
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED, 92	ER_RPL_IO_THREAD_KILLED, 200
ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTIONS, 92	ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED, 417
ER_RPL_ERROR_CREATING_APPLIER_METADATA, 167	ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_SIZE, 175
ER_RPL_ERROR_CREATING_CONNECTION_METADATA, 167	ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOGS, 178
ER_RPL_ERROR_LOOKING_FOR_LOG, 176	ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER, 417
ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION, 179	ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED, 173
ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 180	ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CONFIGURED, 176
ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION, 179	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_EXISTS, 170
ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION, 180	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_EXISTS, 170
ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE, 168	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG, 173
ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE, 168	ER_RPL_MTA_RECOVERY_COMPLETE, 175
ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER_CONFIGURATION, 167	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR, 173
ER_RPL_FAILED_TO_OPEN_INFO_FILE, 168	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR, 173
ER_RPL_FAILED_TO_OPEN_RELAY_LOG, 179	ER_RPL_MTA_RECOVERY_SUCCESSFUL, 174
ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY, 167	ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED, 170
ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX, 178	ER_RPL_MTA_STATISTICS, 175
ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL, 201	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPLICATION, 168
ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED, 195	ER_RPL_OPEN_INDEX_FILE_FAILED, 178
ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED, 195	ER_RPL_PLEASE_USE_OPTION_RELAY_LOG, 178
ER_RPL_GTID_LOG_EVENT_IN_STREAM, 169	ER_RPL_PLUGIN_FUNCTION_FAILED, 153
ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE, 168	ER_RPL_RECOVERY_ERROR, 173
ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON, 192	ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG, 173
ER_RPL_GTID_TABLE_CANNOT_OPEN, 141	ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO, 173
ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION, 340	ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG, 173
ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT, 331	ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE, 173
ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE, 331	ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRED, 173
ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR, 170	ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_LOG, 173
	ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY, 178

ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY,	ER_RPL_REPLICA_GENERIC_MESSAGE, 167
178	ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED,
ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY,	196
385	ER_RPL_REPLICA_INCORRECT_CHANNEL, 191
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLOSE,	ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE,
361	191
ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_SOURCE,	ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_F
177	175
ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF,	ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOU
172	175
ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA,	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_
174	177
ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER,	ER_RPL_REPLICA_IO_THREAD_EXITING, 176
176	ER_RPL_REPLICA_IO_THREAD_KILLED, 175
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION,	ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT
175	331
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL,	ER_RPL_REPLICA_IO_THREAD_WAS_KILLED,
172	174
ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL,	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING,
173	371
ER_RPL_REPLICA_CANT_USE_CHARSET, 177	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CH
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION,	ICATION_RESUMED,
177	ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_SLAVE,	STARTED_FILE_BASED,
398	ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE, 177
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_SLAVE,	STARTED_FILE_BASED, NEXT_LOG_IS_INACTIVE,
398	177
ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL,	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFI
168	177
ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE,	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_F
175	359
ER_RPL_REPLICA_ERROR_INFO_FROM_DAEMON,	ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE,
177	177
ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_LIBRARIES,	ER_RPL_REPLICA_REPORT_HOST_TOO_LONG,
177	174
ER_RPL_REPLICA_ERROR_READING_FROM_SERVER,	ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG,
174	174
ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS,	ER_RPL_REPLICA_REPORT_USER_TOO_LONG,
178	174
ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP,	ER_RPL_REPLICA_RESET_FILTER_OPTIONS,
175	196
ER_RPL_REPLICA_ERROR_RETRYING, 174	ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS,
ER_RPL_REPLICA_ERROR_RUNNING_QUERY,	174
177	ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED,
ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM,	FROM_CONNECTION_METADATA,
168	ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST_F
ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER,	INFO_REPOSITORIES,
172	ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED,
ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION,	METADATA_STRUCTURE,
168	ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHAN
ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA,	DATA_STRUCTURE,
168	ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED
ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HA_S	359
176	ER_RPL_REPLICA_SQL_THREAD_EXITING, 177
ER_RPL_REPLICA_FILTER_CREATE_FAILED,	ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EV
196	178
ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD,	ER_RPL_REPLICA_SQL_THREAD_STARTING,
175	176

ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_P	ER_SECONDARY_ENGINE, 99
358	ER_SECONDARY_ENGINE_DDL, 99
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC	ER_SECONDARY_ENGINE_DDL_FAILED, 401
330	ER_SECONDARY_ENGINE_DDL_TRACK_PROGRESS,
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM,	415
175	ER_SECONDARY_ENGINE_PLUGIN, 98
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE	ER_SECOND_PASSWORD_CANNOT_BE_EMPTY,
174	98
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAI	ER_SECURE_AUTH_VALUE_UNSUPPORTED,
176	145
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAI	ER_SECURE_TRANSPORT_REQUIRED, 68
176	ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG,
ER_RPL_REPO_HAS_GAPS, 142	147
ER_RPL_REWRITEDB_EMPTY_FROM, 150	ER_SEC_FILE_PRIV_CANT_ACCESS_DIR, 146
ER_RPL_REWRITEDB_EMPTY_TO, 150	ER_SEC_FILE_PRIV_CANT_STAT, 146
ER_RPL_REWRITEDB_MISSING_ARROW, 150	ER_SEC_FILE_PRIV_DIRECTORY_INSECURE,
ER_RPL_SERVER_ID_MISSING, 174	146
ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_I	ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS,
180	146
ER_RPL_TRX_DELEGATES_INIT_FAILED, 153	ER_SEC_FILE_PRIV_EMPTY, 146
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM, 169	ER_SEC_FILE_PRIV_IGNORED, 146
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID	ER_SELECT_REDUCE_EVENT_IN_STREAM, 146
169	ER_SELECT_REDUCE, 18
ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM,	ER_SEMISYNC_ADD_ACK_TO_SLOT, 210
169	ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD, 209
ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN	ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER,
169	207
ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG,	ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL,
179	208
ER_RPL_WORKER_CANT_READ_RELAY_LOG,	ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION,
179	208
ER_RPL_WORKER_ID_IS, 167	ER_SEMISYNC_DISABLED_ON_SOURCE, 208
ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOB	ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE,
88	211
ER_RUN_HOOK_ERROR, 64	ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECE
ER_SAME_NAME_PARTITION, 34	210
ER_SAME_NAME_PARTITION_FIELD, 41	ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE,
ER_SCHEDULER_KILLING, 143	207
ER_SCHEDULER_STARTED, 143	ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE,
ER_SCHEDULER_STOPPED, 143	209
ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_W	ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_TH
143	210
ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT	ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD
143	211
ER_SCHEDULER_WAITING, 143	ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET,
ER_SCHEMA_DIR_CREATE_FAILED, 84	210
ER_SCHEMA_DIR_EXISTS, 84	ER_SEMISYNC_FORCED_SHUTDOWN, 208
ER_SCHEMA_DIR_MISSING, 84	ER_SEMISYNC_FUNCTION_CALLED_TWICE, 208
ER_SCHEMA_DIR_UNKNOWN, 84	ER_SEMISYNC_INIT_WAIT_POS, 209
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWE	ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY,
360	207
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWE	ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_F
360	211
ER_SCHEMA_READ_ONLY, 107	ER_SEMISYNC_MOVE_BACK_WAIT_POS, 209
ER_SDI_GET_KEYS_INVALID_TABLESPACE, 111	ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE,
ER_SDI_OPERATION_FAILED, 83	211
ER_SDI_OPERATION_FAILED_MISSING_RECORD,	ER_SEMISYNC_NO_SPACE_IN_THE_PKT, 209
104	

ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY, 207	ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK, 210
ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER, 209	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT, 209
ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED, 211	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_T, 209
ER_SEMISYNC_REPLICA_REPLY, 211	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT, 209
ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO, 211	ER_SERVERID_TOO_LARGE, 152
ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED, 211	ER_SERVER_ACL_TABLE_ERROR, 334
ER_SEMISYNC_REPLICA_SET_FAILED, 211	ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF, 349
ER_SEMISYNC_REPLICA_START, 211	ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_C, 349
ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE, 208	ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 352
ER_SEMISYNC_REPLY_MAGIC_NO_ERROR, 208	ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2, 333
ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL, 208	ER_SERVER_CANT_OPEN_FILE, 333
ER_SEMISYNC_RPL_ENABLED_ON_SOURCE, 208	ER_SERVER_CERT_VERIFY_FAILED, 405
ER_SEMISYNC_RPL_INIT_FOR_TRX, 207	ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED, 334
ER_SEMISYNC_RPL_SWITCHED_OFF, 209	ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPD, 334
ER_SEMISYNC_RPL_SWITCHED_ON, 209	ER_SERVER_COST_FAILED_TO_READ, 169
ER_SEMISYNC_SERVER_REPLY, 208	ER_SERVER_COST_INVALID_COST_CONSTANT, 168
ER_SEMISYNC_SOCKET_FD_TOO_LARGE, 211	ER_SERVER_COST_UNKNOWN_COST_CONSTANT, 168
ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH, 209	ER_SERVER_DISK_FULL_NOWAIT, 333
ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS, 208	ER_SERVER_DOWNGRADE_FROM_VERSION, 402
ER_SEMISYNC_SOURCE_OOM, 208	ER_SERVER_DOWNGRADE_HELP_TABLE_STATUS, 414
ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS, 208	ER_SERVER_DOWNGRADE_STATUS, 402
ER_SEMISYNC_SOURCE_TRX_WAIT_POS, 208	ER_SERVER_DOWNGRADE_SYS_SCHEMA, 413
ER_SEMISYNC_STARTING_ACK_RECEIVER_THD, 210	ER_SERVER_FILE_NOT_FOUND, 333
ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA, 210	ER_SERVER_FILE_USED, 333
ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD, 210	ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE, 340
ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA, 210	ER_SERVER_HANDLER_ERROR, 333
ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO, 209	ER_SERVER_INIT_COMPILED_IN_COMMANDS, 203
ER_SEMISYNC_TRACE_ENTER_FUNC, 207	ER_SERVER_ISNT_AVAILABLE, 69
ER_SEMISYNC_TRACE_EXIT, 207	ER_SERVER_MEMORY_OPTION_INVALID, 425
ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE, 207	ER_SERVER_NET_PACKET_TOO_LARGE, 333
ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE, 207	ER_SERVER_NEW_ABORTING_CONNECTION, 333
ER_SEMISYNC_TRX_SKIPPED_AT_POS, 209	ER_SERVER_NOT_FORM_FILE, 333
ER_SEMISYNC_UNREGISTERED_REPLICATOR, 210	ER_SERVER_NO_SESSION_TO_SEND_TO, 333
ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER, 210	ER_SERVER_NO_SYSTEM_TABLE_ACCESS, 333
ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER, 210	ER_SERVER_OFFLINE_MODE, 59
ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED, 210	ER_SERVER_OFFLINE_MODE_REASON, 130
	ER_SERVER_OUTOFMEMORY, 194
	ER_SERVER_OUT_OF_RESOURCES, 194
	ER_SERVER_OUT_OF_SORTMEMORY, 333
	ER_SERVER_RECORD_FILE_FULL, 333

ER_SERVER_REPLICA_AM_INIT_REPOSITORY, 332	ER_SERVER_UPGRADE_NO_SYS_VERSION, 351
ER_SERVER_REPLICA_CM_INIT_REPOSITORY, 332	ER_SERVER_UPGRADE_OFF, 350
ER_SERVER_REPLICA_CONVERSION_FAILED, 334	ER_SERVER_UPGRADE_PENDING, 350
ER_SERVER_REPLICA_IGNORED_TABLE, 334	ER_SERVER_UPGRADE_REPAIR_REQUIRED, 350
ER_SERVER_REPLICA_INIT_QUERY_FAILED, 334	ER_SERVER_UPGRADE_REPAIR_STATUS, 350
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 346	ER_SERVER_UPGRADE_SKIP, 350
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 343	ER_SERVER_UPGRADE_STATUS, 350
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 343	ER_SERVER_UPGRADE_SYSTEM_TABLES, 351
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 343	ER_SERVER_UPGRADE_SYS_SCHEMA, 350
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_KEYS, 343	ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT, 351
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 343	ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED, 351
ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR, 343	ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE, 351
ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY_FAILED, 344	ER_SERVER_UPGRADE_SYS_VERSION_EMPTY, 351
ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 343	ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED, 351
ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 343	ER_SERVER_WARN_DEPRECATED, 349
ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND, 49	ER_SERVER_WRONG_VALUE_FOR_VAR, 340
ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECORD_OVERFLOW, 343	ER_SESSION_WAS_KILLED, 69
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE_SHAPE_PREDICTION_UDF, 117	ER_SET_CONSTANTS_ONLY, 16
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY_AT_STARTUP, 344	ER_SET_EVENT_FAILED, 336
ER_SERVER_SHUTDOWN, 6	ER_SET_PASSWORD_AUTH_PLUGIN_ERROR, 344
ER_SERVER_SHUTDOWN_COMPLETE, 192	ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION, 49
ER_SERVER_SHUTDOWN_INFO, 336	ER_SE_TYPECODE_CONFLICT, 156
ER_SERVER_SOURCE_FATAL_ERROR_READING_BINARY_LOGS, 332	ER_SET_SECOND_PASSWORD_USED, 344
ER_SERVER_STARTING_WITH_RESOURCE, 425	ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE, 340
ER_SERVER_STARTUP_ADMIN_INTERFACE, 344	ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL, 216
ER_SERVER_STARTUP_MSG, 193	ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_ROUNDS, 216
ER_SERVER_TABLE_CHECK_FAILED, 334	ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING, 216
ER_SERVER_TEST_MESSAGE, 334	ER_SHA_PWD_RSA_KEY_TOO_LONG, 216
ER_SERVER_UNKNOWN_SYSTEM_VARIABLE, 333	ER_SHA_PWD_SALT_FOR_USER_CORRUPT, 216
ER_SERVER_UPGRADE_CHECKING_DB, 351	ER_SHUTDOWN_COMPLETE, 8
ER_SERVER_UPGRADE_EMPTY_SYS, 351	ER_SHUTTING_DOWN_REPLICA_THREADS, 148
ER_SERVER_UPGRADE_FAILED, 350	ER_SIGNAL_BAD_CONDITION_TYPE, 40
ER_SERVER_UPGRADE_FROM_VERSION, 346	ER_SIGNAL_EXCEPTION, 40
ER_SERVER_UPGRADE_HELP_TABLE_STATUS, 352	ER_SIGNAL_NOT_FOUND, 40
ER_SERVER_UPGRADE_INFO_FILE, 350	ER_SIGNAL_WARN, 40
ER_SERVER_UPGRADE_MYSQL_TABLES, 351	ER_SIMPLE_ERROR_LOG_COMPONENT_STATUS, 417
	ER_SIMULATED_INJECTION_ERROR, 122
	ER_SIZE_OVERFLOW_ERROR, 35
	ER_SKIP_UPDATING_METADATA_IN_SE_RDONLY_MODE, 200

ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING, 92
 ER_SOURCE, 15
 ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE, 46
 ER_SOURCE_FATAL_ERROR_READING_BINLOG, 18
 ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS, 50
 ER_SOURCE_NET_READ, 15
 ER_SOURCE_NET_WRITE, 15
 ER_SPATIAL_CANT_HAVE_NULL, 19
 ER_SPATIAL_FUNCTIONAL_INDEX, 89
 ER_SPATIAL_MUST_HAVE_GEOM_COL, 43
 ER_SPATIAL_UNIQUE_INDEX, 87
 ER_SPECIFIC_ACCESS_DENIED, 124
 ER_SPECIFIC_ACCESS_DENIED_ERROR, 17
 ER_SPVAR_NONINTEGER_TYPE, 108
 ER_SP_ALREADY_EXISTS, 22
 ER_SP_BADRETURN, 22
 ER_SP_BADSELECT, 22
 ER_SP_BADSTATEMENT, 22
 ER_SP_BAD_CURSOR_QUERY, 23
 ER_SP_BAD_CURSOR_SELECT, 23
 ER_SP_BAD_SQLSTATE, 27
 ER_SP_BAD_VAR_SHADOW, 30
 ER_SP_CANT_ALTER, 23
 ER_SP_CANT_SET_AUTOCOMMIT, 30
 ER_SP_CASE_NOT_FOUND, 24
 ER_SP_COND_MISMATCH, 22
 ER_SP_CURSOR_AFTER_HANDLER, 24
 ER_SP_CURSOR_ALREADY_OPEN, 23
 ER_SP_CURSOR_MISMATCH, 23
 ER_SP_CURSOR_NOT_OPEN, 23
 ER_SP_DOES_NOT_EXIST, 22
 ER_SP_DROP_FAILED, 22
 ER_SP_DUP_COND, 23
 ER_SP_DUP_CURS, 23
 ER_SP_DUP_HANDLER, 28
 ER_SP_DUP_PARAM, 23
 ER_SP_DUP_VAR, 23
 ER_SP_FETCH_NO_DATA, 23
 ER_SP_LABEL_MISMATCH, 22
 ER_SP_LABEL_REDEFINE, 22
 ER_SP_LILABEL_MISMATCH, 22
 ER_SP_LOAD_FAILED, 72
 ER_SP_NORETURN, 23
 ER_SP_NORETURNEND, 23
 ER_SP_NOT_VAR_ARG, 28
 ER_SP_NO_AGGREGATE, 31
 ER_SP_NO_ALTER_LANGUAGE, 121
 ER_SP_NO_DROP_SP, 25
 ER_SP_NO_RECURSION, 28
 ER_SP_NO_RECURSIVE_CREATE, 21
 ER_SP_NO_RESET, 28
 ER_SP_RECURSION_LIMIT, 30
 ER_SP_STORE_FAILED, 22
 ER_SP_SUBSELECT_NYI, 23
 ER_SPS_OUTER_VARIABLE, 23
 ER_SP_UNINIT_VAR, 22
 ER_SP_VARCOND_AFTER_CURSHNDLR, 24
 ER_SP_WRONG_NAME, 30
 ER_SP_WRONG_NO_OF_ARGS, 22
 ER_SP_WRONG_NO_OF_FETCH_ARGS, 23
 ER_SQLTHREAD_WITH_SECURE_REPLICA, 48
 ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL, 155
 ER_SQL_HA_READ_FAILED, 154
 ER_SQL_MODE_MERGED, 67
 ER_SQL_MODE_MERGED_WITH_STRICT_MODE, 193
 ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE, 109
 ER_SQL_USER_TABLE ALTER WARNING, 155
 ER_SQL_USER_TABLE_CREATE WARNING, 155
 ER_SRS_ATTRIBUTE_STRING_TOO_LONG, 86
 ER_SRS_GEOGCS_INVALID_AXES, 88
 ER_SRS_ID_ALREADY_EXISTS, 86
 ER_SRS_INVALID_ANGULAR_UNIT, 88
 ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE, 86
 ER_SRS_INVALID_HEIGHT, 117
 ER_SRS_INVALID_INVERSE_FLATTENING, 88
 ER_SRS_INVALID_LATITUDE_OF_ORIGIN, 116
 ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A, 118
 ER_SRS_INVALID_LONGITUDE_OF_ORIGIN, 116
 ER_SRS_INVALID_PRIME_MERIDIAN, 88
 ER_SRS_INVALID_SCALING, 118
 ER_SRS_INVALID_SEMI_MAJOR_AXIS, 88
 ER_SRS_INVALID_ZONE_WIDTH, 118
 ER_SRS_MISSING_MANDATORY_ATTRIBUTE, 85
 ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS, 86
 ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE, 86
 ER_SRS_NOT_CARTESIAN, 73
 ER_SRS_NOT_CARTESIAN_UNDEFINED, 73
 ER_SRS_NOT_FOUND, 75
 ER_SRS_NOT_GEOGRAPHIC, 87
 ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE, 86
 ER_SRS_PARSE_ERROR, 73
 ER_SRS_PROJ_PARAMETER_MISSING, 73
 ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT, 116
 ER_SRV_END, 405
 ER_SRV_INIT_END, 405
 ER_SRV_INIT_START, 405
 ER_SRV_START, 405
 ER_SR_BOGUS_VALUE, 154
 ER_SR_INVALID_CONTEXT, 154
 ER_SSL_FIPS_MODE_ERROR, 217
 ER_SSL_LIBRARY_ERROR, 144
 ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED, 341

ER_SSL_TRYING_DATADIR_DEFAULTS, 152	ER_SYSTEM_SCHEMA_NOT_FOUND, 141
ER_STACKSIZE_UNEXPECTED, 151	ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE
ER_STACK_BACKTRACE, 394	193
ER_STACK_OVERRUN, 11	ER_SYSTEM_TABLE_NOT_TRANSACTIONAL,
ER_STACK_OVERRUN_NEED_MORE, 29	180
ER_STARTING_AS, 147	ER_SYSTEM_VIEW_INIT_FAILED, 194
ER_STARTING_INIT, 336	ER_SYSVAR_CHANGE_DURING_QUERY, 101
ER_STARTING_REPLICA_MONITOR_IO_THREAD,	ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE
109	217
ER_STARTUP, 27	ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE
ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION,	216
123	ER_SYS_VAR_COMPONENT_OOM, 216
ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION,	ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE
407	217
ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION,	ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY
106	216
ER_STD_BAD_ALLOC_ERROR, 60	ER_SYS_VAR_NOT_FOUND, 337
ER_STD_DOMAIN_ERROR, 60	ER_TABLEACCESS_DENIED_ERROR, 12
ER_STD_INVALID_ARGUMENT, 60	ER_TABLENAME_NOT_ALLOWED_HERE, 18
ER_STD_LENGTH_ERROR, 60	ER_TABLESAMPLE_ONLY_ON_BASE_TABLES,
ER_STD_LOGIC_ERROR, 61	128
ER_STD_OUT_OF_RANGE_ERROR, 60	ER_TABLESAMPLE_PERCENTAGE, 128
ER_STD_OVERFLOW_ERROR, 60	ER_TABLESPACE_AUTO_EXTEND_ERROR, 35
ER_STD_RANGE_ERROR, 60	ER_TABLESPACE_CANNOT_BE_DECRYPTED,
ER_STD_REGEX_ERROR, 97	95
ER_STD_RUNTIME_ERROR, 61	ER_TABLESPACE_CANNOT_BE_ENCRYPTED,
ER_STD_UNDERFLOW_ERROR, 60	95
ER_STD_UNKNOWN_EXCEPTION, 61	ER_TABLESPACE_CANNOT_ENCRYPT, 70
ER_STMT_CACHE_FULL, 44	ER_TABLESPACE_DISCARDED, 52
ER_STMT_EXECUTION_NOT_ALLOWED_WITHIN_SP,	ER_TABLESPACE_DUP_FILENAME, 79
129	ER_TABLESPACE_ENGINE_MISMATCH, 81
ER_STMT_HAS_NO_OPEN_CURSOR, 28	ER_TABLESPACE_EXISTS, 52
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG, 24	ER_TABLESPACE_IS_NOT_EMPTY, 66
ER_STOP_REPLICA_IO_THREAD_DISK_SPACE,	ER_TABLESPACE_MISSING, 52
217	ER_TABLESPACE_MISSING_WITH_NAME, 72
ER_STOP_REPLICA_IO_THREAD_TIMEOUT, 56	ER_TABLESPACE_TYPE_UNKNOWN, 95
ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT,	ER_TABLES_DIFFERENT_METADATA, 47
108	ER_TABLE_CANT_HANDLE_AUTO_INCREMENT,
ER_STOP_REPLICA_SQL_THREAD_TIMEOUT, 56	13
ER_STORAGE_ENGINE_NOT_LOADED, 57	ER_TABLE_CANT_HANDLE_BLOB, 13
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT,	ER_TABLE_CANT_HANDLE_FT, 16
43	ER_TABLE_CANT_HANDLE_SPKEYS, 31
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT,	ER_TABLE_CHECK_INTEGRITY, 152
36	ER_TABLE_CORRUPT, 56
ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN,	ER_TABLE_CREATED_WITH_DIFFERENT_VERSION,
44	163
ER_SUBPARTITION_ERROR, 33	ER_TABLE_DEF_CHANGED, 28
ER_SUBPARTITION_NAME, 40	ER_TABLE_EXISTS_ERROR, 6
ER_SUBQUERY_NO_1_ROW, 18	ER_TABLE_HAS_NO_FT, 48
ER_SUBQUERY_TRANSFORM_REJECTED, 105	ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD,
ER_SUPPORTED_ONLY_WITH_HYPERGRAPH, 124	163
ER_SWITCH_TMP_ENGINE, 77	ER_TABLE_INCOMPATIBLE_YEAR_FIELD, 163
ER_SYNTAX_ERROR, 13	ER_TABLE_IN_FK_CHECK, 46
ER_SYSTEMD_NOTIFY_CONNECT_FAILED, 255	ER_TABLE_IN_SHARED_TABLESPACE, 118
ER_SYSTEMD_NOTIFY_DEBUG, 392	ER_TABLE_IN_SYSTEM_TABLESPACE, 52
ER_SYSTEMD_NOTIFY_PATH_TOO_LONG, 255	ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN,
ER_SYSTEMD_NOTIFY_WRITE_FAILED, 255	110
	ER_TABLE_MUST_HAVE_COLUMNS, 10

ER_TABLE_NAME, 40	ER_THREAD_POOL_CONNECTION_INIT_REPORT,
ER_TABLE_NAME_CAUSES_TOO_LONG_PATH,	417
101	ER_THREAD_POOL_CON_HANDLER_INIT_FAILED,
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED,	206
360	ER_THREAD_POOL_CREATE_EPOLL_FAILED,
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED,	418
360	ER_THREAD_POOL_CREATE_THREAD_FAILED,
ER_TABLE_NEEDS_DUMP_UPGRADE, 205	418
ER_TABLE_NEEDS_REBUILD, 44	ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID,
ER_TABLE_NEEDS_UPGRADE, 30	386
ER_TABLE_NOT_EMPTY, 118	ER_THREAD_POOL_EPOLL_WAIT_ERROR, 418
ER_TABLE_NOT_LOCKED, 9	ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT,
ER_TABLE_NOT_LOCKED_FOR_WRITE, 9	206
ER_TABLE_NO_PRIMARY_KEY, 118	ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HAND
ER_TABLE_REFERENCED, 71	206
ER_TABLE_SCHEMA_MISMATCH, 52	ER_THREAD_POOL_FAILED_TO_CREATE_POOL,
ER_TABLE_UPGRADE_REQUIRED, 193	206
ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT,	ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH
103	206
ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMN,	ER_THREAD_POOL_IDLE_CONNECTION_CLOSED,
103	397
ER_TABLE_WITHOUT_PK, 89	ER_THREAD_POOL_INIT_FAILED, 206
ER_TABLE_WRONG_KEY_DEFINITION, 163	ER_THREAD_POOL_LOW_LEVEL_ARM_FAILED,
ER_TARGET_TABLESPACE_UNENCRYPTED, 95	418
ER_TC_BAD_MAGIC_IN_TC_LOG, 172	ER_THREAD_POOL_LOW_LEVEL_ARM_FAILED_WITH_ERRM
ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC,	418
172	ER_THREAD_POOL_LOW_LEVEL_INIT_ALLOC_FAILED,
ER_TC_HEURISTIC_RECOVERY_FAILED, 172	418
ER_TC_HEURISTIC_RECOVERY_MODE, 172	ER_THREAD_POOL_LOW_LEVEL_INIT_FAILED,
ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY,	418
172	ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED,
ER_TC_RECOVERING_AFTER_CRASH_USING,	206
172	ER_THREAD_POOL_MTL_DISABLE, 414
ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS,	ER_THREAD_POOL_MTL_REENABLE, 414
172	ER_THREAD_POOL_PFS_TABLES_ADD_FAILED,
ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVERY,	342
172	ER_THREAD_POOL_PFS_TABLES_INIT_FAILED,
ER_TELEMETRY_ERROR, 405	342
ER_TELEMETRY_INFO, 405	ER_THREAD_POOL_PLUGIN_STARTED, 386
ER_TELEMETRY_WARNING, 405	ER_THREAD_POOL_POLL_WAIT_ERROR, 418
ER_TEMPORARY_NAME, 40	ER_THREAD_POOL_SOCKETPAIR_FAILED, 418
ER_TEMPORARY_ENGINE_ERROR, 417	ER_THREAD_POOL_SYSVAR_CHANGE, 393
ER_TEMP_FILE_WRITE_FAILURE, 56	ER_THREAD_PRIORITY_IGNORED, 192
ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT,	ER_THREAD_POOL_STILL_ALIVE, 406
88	ER_TLS_CONFIGURATION_REUSED, 366
ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT,	ER_TLS_CONFIGURED_FOR_CHANNEL, 365
88	ER_TLS_LIBRARY_ERROR_INTERNAL, 405
ER_TEXTFILE_NOT_READABLE, 8	ER_TMPDIR_PATH_TOO_LONG, 370
ER_TF_FORBIDDEN_JOIN_TYPE, 83	ER_TMP_SESSION_FOR_VAR, 392
ER_TF_MUST_HAVE_ALIAS, 83	ER_TOO_BIG_DISPLAYWIDTH, 29
ER_THE_USER_ABIDES, 149	ER_TOO_BIG_ENUM, 72
ER_THREAD_HANDLING_OOM, 146	ER_TOO_BIG_FIELDLENGTH, 8
ER_THREAD_POOL_ALLOC_FAILED, 417	ER_TOO_BIG_FOR_UNCOMPRESS, 19
ER_THREAD_POOL_BUFFER_TOO_SMALL, 206	ER_TOO_BIG_PRECISION, 28
ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_FUNCTION,	ER_TOO_BIG_ROWSIZE, 10
392	ER_TOO_BIG_SCALE, 28
ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA,	ER_TOO_BIG_SELECT, 10
206	ER_TOO_BIG_SET, 9

ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT, 31	ER_TRG_CANT_PARSE, 153
ER_TOO_LONG_BODY, 29	ER_TRG_CORRUPTED_FILE, 38
ER_TOO_LONG_FIELD_COMMENT, 39	ER_TRG_CREATION_CTX_NOT_SET, 193
ER_TOO_LONG_IDENT, 7	ER_TRG_DOES_NOT_EXIST, 25
ER_TOO_LONG_INDEX_COMMENT, 43	ER_TRG_INVALID_CREATION_CTX, 38
ER_TOO_LONG_KEY, 7	ER_TRG_IN_WRONG_SCHEMA, 29
ER_TOO_LONG_ROUTINE_COMMENT, 72	ER_TRG_NO_CLIENT_CHARSET, 144
ER_TOO_LONG_SET_ENUM_VALUE, 72	ER_TRG_NO_CREATION_CTX, 38
ER_TOO_LONG_STRING, 13	ER_TRG_NO_DEFINER, 30
ER_TOO_LONG_TABLESPACE_COMMENT, 79	ER_TRG_NO_SUCH_ROW_IN_TRG, 25
ER_TOO_LONG_TABLE_COMMENT, 39	ER_TRG_ON_VIEW_OR_TEMP_TABLE, 25
ER_TOO_LONG_TABLE_PARTITION_COMMENT, 50	ER_TRG_WITHOUT_DEFINER, 144
ER_TOO_MANY_CONCURRENT_TRXS, 40	ER_TRG_WRONG_ORDER, 347
ER_TOO_MANY_FIELDS, 10	ER_THEAD_POOL_LOW_LEVEL_INIT_FAILED, 206
ER_TOO_MANY_GROUP_BY_MODIFIER_BRANCHES, 123	ER_TRIGGER_INVALID_VALUE, 140
ER_TOO_MANY_KEYS, 7	ER_TRUNCATED_WRONG_VALUE, 21
ER_TOO_MANY_KEY_PARTS, 7	ER_TRUNCATED_WRONG_VALUE_FOR_FIELD, 25
ER_TOO_MANY_PARTITIONS_ERROR, 33	ER_TRUNCATE_ILLEGAL_FK, 44
ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR, 41	ER_TRX_GTID_COLLECT_REJECT, 155
ER_TOO_MANY_ROWS, 14	ER_TRX_WRITE_SET_OOM, 156
ER_TOO_MANY_STORAGE_ENGINES, 156	ER_TURNING_LOGGING_OFF_FOR_THE_DURATION, 189
ER_TOO_MANY_TABLES, 10	ER_TURNING_ON_PARTIAL_REVOKES, 349
ER_TOO_MANY_USER_CONNECTIONS, 15	ER_TZ_CANT_BUILD_MKTIME_MAP, 165
ER_TOO_MANY_VALUES_ERROR, 41	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE, 164
ER_TOO_MANY_WINDOWS, 115	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID, 164
ER_TO_VECTOR_CONVERSION, 130	ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE, 164
ER_TP_CANNOT_DISABLE_MTL_WITH_DL, 130	ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE, 164
ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THRESHOLD, 117	ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE, 165
ER_TRACK_VARIABLES_BOGUS, 149	ER_TZ_OOM_INITIALIZING_TIME_ZONES, 164
ER_TRANSACTION_ROLLBACK_DURING_COMMIT, 64	ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE, 164
ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84, 88	ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION, 165
ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED, 88	ER_TZ_OOM_WHILE_LOADING_TIME_ZONE, 165
ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84, 88	ER_TZ_OOM_WHILE_SETTING_TIME_ZONE, 165
ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED, 88	ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE, 164
ER_TRANSPORTS_WHAT_TRANSPORTS, 148	ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE, 165
ER_TRANS_CACHE_FULL, 15	ER_TZ_TRANSITION_TABLE_LOAD_ERROR, 165
ER_TREE_CORRUPT_2_CONSECUTIVE_REDS, 179	ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS, 165
ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT, 179	ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXIST, 164
ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT, 179	ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR, 164
ER_TREE_CORRUPT_RIGHT_IS_LEFT, 179	ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE, 164
ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK, 179	ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE, 164
ER_TRG_ALREADY_EXISTS, 25	
ER_TRG_CANT_CHANGE_ROW, 25	
ER_TRG_CANT_OPEN_TABLE, 38	

ER_UDF_ALREADY_EXISTS, 336
 ER_UDF_CANT_ALLOC_FOR_FUNCTION, 154
 ER_UDF_CANT_ALLOC_FOR_STRUCTURES, 154
 ER_UDF_CANT_OPEN_FUNCTION_TABLE, 154
 ER_UDF_DEREGISTRATION, 400
 ER_UDF_DROP_DYNAMICALLY_REGISTERED, 80
 ER_UDF_ERROR, 71
 ER_UDF_EXEC_FAILURE, 400
 ER_UDF_EXEC_FAILURE_REASON, 400
 ER_UDF_EXISTS, 11
 ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE, 154
 ER_UDF_NO_PATHS, 11
 ER_UDF_REGISTER_ERROR, 369
 ER_UDF_REGISTER_SERVICE_ERROR, 369
 ER_UDF_REGISTRATION, 400
 ER_UDF_UNREGISTER_ERROR, 370
 ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANTS, 96
 ER_UNABLE_TO_BUILD_HISTOGRAM, 80
 ER_UNABLE_TO_COLLECT_LOG_STATUS, 86
 ER_UNABLE_TO_DROP_COLUMN_STATISTICS, 80
 ER_UNABLE_TO_RESOLVE_HOSTNAME, 143
 ER_UNABLE_TO_RESOLVE_IP, 143
 ER_UNABLE_TO_SET_OPTION, 87
 ER_UNABLE_TO_STORE_COLUMN_STATISTICS, 80
 ER_UNABLE_TO_STORE_STATISTICS, 75
 ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS, 80
 ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN, 84
 ER_UNDO_RECORD_TOO_BIG, 45
 ER_UNEXPECTED_GEOMETRY_TYPE, 73
 ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF, 33
 ER_UNIT_NOT_FOUND, 100
 ER_UNKNOWN_ALTER_ALGORITHM, 51
 ER_UNKNOWN_ALTER_LOCK, 51
 ER_UNKNOWN_AUTHID, 73
 ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE, 196
 ER_UNKNOWN_CHARACTER_SET, 10
 ER_UNKNOWN_COLLATION, 20
 ER_UNKNOWN_COM_ERROR, 6
 ER_UNKNOWN_ERROR, 10
 ER_UNKNOWN_ERROR_DETECTED_IN_SE, 200
 ER_UNKNOWN_ERROR_NUMBER, 154
 ER_UNKNOWN_EXPLAIN_FORMAT, 50
 ER_UNKNOWN_KEY_CACHE, 20
 ER_UNKNOWN_LOCALE, 41
 ER_UNKNOWN_NETWORK_NAMESPACE, 352
 ER_UNKNOWN_PARTITION, 47
 ER_UNKNOWN_PROCEDURE, 10
 ER_UNKNOWN_STMT_HANDLER, 18
 ER_UNKNOWN_STORAGE_ENGINE, 21
 ER_UNKNOWN_SYSTEM_VARIABLE, 15
 ER_UNKNOWN_TABLE, 10
 ER_UNKNOWN_TABLESPACE_TYPE, 340
 ER_UNKNOWN_TABLE_IN_UPGRADE, 356
 ER_UNKNOWN_TARGET_BINLOG, 26
 ER_UNKNOWN_TIME_ZONE, 21
 ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE, 145
 ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE, 337
 ER_UNRESOLVED_HINT_NAME, 66
 ER_UNRESOLVED_TABLE_LOCK, 76
 ER_UNSUPPORTED_LOG_ENGINE, 37
 ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATION, 90
 ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN, 64
 ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE, 70
 ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN, 64
 ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN, 70
 ER_UNSUPPORTED_DATE, 147
 ER_UNSUPPORTED_ENGINE, 46
 ER_UNSUPPORTED_EXTENSION, 10
 ER_UNSUPPORTED_INDEX_ALGORITHM, 72
 ER_UNSUPPORTED_PS, 21
 ER_UNSUPPORTED_SQL_MODE, 100
 ER_UNSUPPORTED_USE_OF_GRANT_AS, 95
 ER_UNSUPPORTED_COMPRESSED_TEMPORARY_TABLE, 72
 ER_UNTIL_COND_IGNORED, 20
 ER_UPDATE_GTID_PURGED_WITH_GR, 101
 ER_UPDATE_INFO, 12
 ER_UPDATE_LOG_DEPRECATED_IGNORED, 22
 ER_UPDATE_LOG_DEPRECATED_TRANSLATED, 22
 ER_UPDATE_TABLE_USED, 9
 ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE, 14
 ER_UPDATING_DD_TABLE, 72
 ER_UPGRADE_NONEXISTENT_SCHEMA, 370
 ER_UPGRADE_PARSE_ERROR, 340
 ER_USAGE_DEPRECATION_COUNTER, 403
 ER_USERNAME, 31
 ER_USERNAME_TRUNCATED, 366
 ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCK, 104
 ER_USER_ALREADY_EXISTS, 69
 ER_USER_COLUMN_OLD_LENGTH, 70
 ER_USER_DOES_NOT_EXIST, 69
 ER_USER_LIMIT_REACHED, 17
 ER_USER_LOCK_DEADLOCK, 61
 ER_USER_LOCK_OVERLONG_NAME, 120
 ER_USER_LOCK_WRONG_NAME, 61
 ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCORRECT, 162
 ER_USER_REFERENCED_AS_DEFINER, 108

ER_USER_REGISTRATION_FAILED, 113	ER_VAR_DOES_NOT_EXIST, 79
ER_USER_REQUIRES_ROOT, 148	ER_VAR_REGISTRATION, 424
ER_USER_WHAT_USER, 148	ER_VERBOSE_HINT, 150
ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION_FAILED, 145	ER_VERBOSE_REQUIRES_HELP, 145
109	ER_VIEW_CHECKSUM, 26
ER_UUID_INVALID, 145	ER_VIEW_CHECK_FAILED, 25
ER_UUID_IS, 145	ER_VIEW_CREATION_CTX_NOT_SET, 193
ER_UUID_SALT, 144	ER_VIEW_DELETE_MERGE_VIEW, 27
ER_UUID_SCRUB, 145	ER_VIEW_FRM_NO_USER, 30
ER_VALGRIND_COUNT_LEAKS, 154	ER_VIEW_INVALID, 25
ER_VALGRIND_DO_QUICK_LEAK_CHECK, 154	ER_VIEW_INVALID_CREATION_CTX, 38
ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGES, 121	ER_VIEW_INVALID_UPDATE, 26
ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED, 256	ER_VIEW_NONUPD_CHECK, 25
ER_VALIDATE_PWD_COULD_BE_NULL, 255	ER_VIEW_NO_CREATION_CTX, 38
ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED, 214	ER_VIEW_NO_EXPLAIN, 24
ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED, 214	ER_VIEW_NO_INSERT_FIELD_LIST, 26
ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED, 255	ER_VIEW_OTHER_USER, 30
ER_VALIDATE_PWD_DICT_FILE_TOO_BIG, 215	ER_VIEW_PREVENT_UPDATE, 29
ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX, 215	ER_VIEW_RECURSIVE, 31
ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX, 215	ER_VIEW_SELECT_CLAUSE, 24
ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE, 215	ER_VIEW_SELECT_TMPTABLE, 24
ER_VALIDATE_PWD_LENGTH_CHANGED, 215	ER_VIEW_SELECT_VARIABLE, 24
ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED, 255	ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION, SECURITY_CTX,
ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED, 255	ER_VIEW_UNPARSABLE, 163
ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED, 256	ER_VIEW_WRONG_LIST, 25
ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED, 255	ER_WAITING_FOR_NO_CONNECTIONS, 403
ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED, 256	ER_WAITING_FOR_NO_THDS, 403
ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED, 256	ER_WAITPID_FAILED, 203
ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED, 256	ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES, 344
ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED, 256	ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID, 344
ER_VALUES_IS_NOT_INT_TYPE_ERROR, 44	ER_WARNING_NOT_COMPLETE_ROLLBACK, 15
ER_VALUE_OUT_OF_RANGE, 114	ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATE_DROP, 47
ER_VARIABLE_IS_NOT_STRUCT, 20	ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROP, 48
ER_VARIABLE_IS_READONLY, 39	ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID, 81
ER_VARIABLE_NOT_PERSISTED, 75	ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID, 344
ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER, 49	ER_WARN_ACCOUNT_TRIMMED, 140
ER_VARIABLE_NOT_SETTABLE_IN_SP, 53	ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS, 378
ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION, 49	ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE, 111
ER_VAR_CANT_BE_READ, 18	ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE, 378
ER_VAR_DEREGISTRATION, 424	ER_WARN_ALLOWED_PACKET_OVERFLOWED, 21
	ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME, 110
	ER_WARN_AUDIT_LOG_DISABLED, 385
	ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY, 112

ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_DEPRECATED, 105	ER_WARN_DEPRECATED_INNER_INTO, 105
379	ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH, 97
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES, 358	ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_E
ER_WARN_BAD_MAX_EXECUTION_TIME, 66	105
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED, 81	ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX, 91
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_INDEXES, 82	ER_WARN_DEPRECATED_NON_STANDARD_KEY, 129
ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATED_OR_BLOCKED_CIPHER, 399	403
ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES, 385	ER_WARN_DEPRECATED_SASL_MECHANISM, 427
ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES, 116	ER_WARN_DEPRECATED_SQLMODE, 63
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE, 29	ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS, 105
ER_WARN_CANT_OPEN_CERTIFICATE, 404	ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER, 115
ER_WARN_CA_CERT_VERIFY_FAILED, 404	ER_WARN_DEPRECATED_SYNTAX, 21
ER_WARN_CERTIFICATE_ERROR_STRING, 405	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT, 45
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MULTIPLE_KEYRING, 398	ER_WARN_DEPRECATED_SYNTAX_WITH_VER, 105
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO, 374	ER_WARN_DEPRECATED_SYSVAR_UPDATE, 63
ER_WARN_COMPONENT_KEYRING_KMIP_DUPLICATE_KEY, 427	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS, 120
ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY, 393	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_O
ER_WARN_CONFLICTING_HINT, 66	ER_WARN_DEPRECATED_USER_SET_EXPR, 91
ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_DISABLE_AUTO_POS, 114	ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION, 341
ER_WARN_DATA_OUT_OF_RANGE, 19	ER_WARN_DEPRECATED_UTF8MB3_COLLATION, 341
ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX, 89	ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION, 341
ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX, 89	ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION, 340
ER_WARN_DA_PRIVILEGE_NOT_REGISTERED, 102	ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_N
ER_WARN_DEPRECATED_CHARSET_OPTION, 384	ER_WARN_DEPRECATED_WITH_NOTE, 121
ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION, 118	ER_WARN_DEPRECATED_YEAR_UNSIGNED, 104
ER_WARN_DEPRECATED_COLLATION, 114	ER_WARN_DEPRECATED_ZEROFILL, 97
ER_WARN_DEPRECATED_COLLATION_OPTION, 384	ER_WARN_ENGINE_TRANSACTION_ROLLBACK, 39
ER_WARN_DEPRECATED_DATETIME_DELIMITER, 115	ER_WARN_FAILED_TO_SETUP_TLS, 404
ER_WARN_DEPRECATED_DYNAMIC_PRIV_IN_GRANT, 122	ER_WARN_FIELD_RESOLVED, 20
ER_WARN_DEPRECATED_ENGINE_SYNTAX_NO_REPLACEMENT, 123	ER_WARN_FUNC_INDEX_NOT_APPLICABLE, 101
ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT, 97	ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VAR
ER_WARN_DEPRECATED_FLOAT_DIGITS, 97	ER_WARN_GTID_THRESHOLD_BREACH, 372
ER_WARN_DEPRECATED_FLOAT_UNSIGNED, 97	ER_WARN_HOSTNAME_WONT_WORK, 20
ER_WARN_DEPRECATED_FOUND_ROWS, 105	ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTION, 349
ER_WARN_DEPRECATED_IDENT, 117	ER_WARN_INDEX_NOT_APPLICABLE, 47
	ER_WARN_INVALID_DB_RESTRICTIONS, 349
	ER_WARN_INVALID_HINT, 79

ER_WARN_INVALID_TIMESTAMP, 21	ER_WARN_SF_UDF_NAME_COLLISION, 115
ER_WARN_I_S_SKIPPED_TABLE, 43	ER_WARN_SP_STATEMENT_PARTIALLY_EXECUTED, 129
ER_WARN_KEYRING_PLUGIN_DEPRECATED, 425	ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED, 112
ER_WARN_LANGUAGE_COMPONENT_CANNOT_UNINSTALL, 412	ER_WARN_SRS_ID_ALREADY_EXISTS, 86
ER_WARN_LANGUAGE_COMPONENT_RESOURCE_LIMIT, 412	ER_WARN_SRS_NOT_FOUND, 73
ER_WARN_LEGACY_SYNTAX_CONVERTED, 57	ER_WARN_SRS_NOT_FOUND_AXIS_ORDER, 76
ER_WARN_LOG_DEPRECATED_NON_STANDARD_KEYS, 414	ER_WARN_THREAD_POOL_DEDICATED_LISTENERS_INCOMPATIBLE, 428
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPTED, 358	ER_WARN_THREAD_POOL_QUERY_THREADS_INCOMPLETE, 428
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 358	ER_WARN_THREAD_POOL_QUERY_THREADS_MISMATCH, 428
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_PRIVILEGES, 358	ER_WARN_THREAD_POOL_QUERY_THREADS_MISMATCH, 428
ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE, 382	ER_WARN_THREAD_POOL_QUERY_THREADS_MISMATCH, 428
ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING, 385	ER_WARN_TOO_MANY_CHANNELS, 19
ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND, 374	ER_WARN_TOO_MANY_RECORDS, 19
ER_WARN_NO_SERVERID_SPECIFIED, 192	ER_WARN_TRG_ALREADY_EXISTS, 116
ER_WARN_NO_SPACE_VERSION_COMMENT, 121	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED, 116
ER_WARN_NULL_TO_NOTNULL, 19	ER_WARN_UNKNOWN_KEYRING_AWS_REGION, 358
ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS, 59	ER_WARN_UNKNOWN_QB_NAME, 66
ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE, 66	ER_WARN_UNLOAD_THE_NOT_PERSISTED, 75
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO, 58	ER_WARN_UNSUPPORTED_HINT, 73
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR, 66	ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME, 66
ER_WARN_OPTION_RESET_AND_IGNORED_DURING_INIT, 406	ER_WARN_USING_OTHER_HANDLER, 19
ER_WARN_OPTION_USAGE_COUNTER_READ_FAILED, 422	ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED, 107
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT, 349	ER_WARN_VIEW_MERGE, 25
ER_WARN_PROPERTY_STRING_PARSE_FAILED, 346	ER_WARN_VIEW_WITHOUT_KEY, 25
ER_WARN_PURGE_LOG_IN_USE, 55	ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG, 357
ER_WARN_PURGE_LOG_IS_ACTIVE, 55	ER_WARN_WRONG_COMPRESSION_LEVEL_LOG, 357
ER_WARN_REDACTED_PRIVILEGES, 132	ER_WASTEFUL_NET_BUFFER_SIZE, 145
ER_WARN_REGEX_USING_DEFAULT, 114	ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS, 352
ER_WARN_REMOVED_SQL_MODE, 341	ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH, 77
ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_SOURCE, 377	ER_WINDOW_DUPLICATE_NAME, 78
ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_SUPPORTED, 382	ER_WINDOW_EXPLAIN_JSON, 78
ER_WARN_RESERVED_SRID_RANGE, 86	ER_WINDOW_FRAME_END_ILLEGAL, 77
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE, 359	ER_WINDOW_FRAME_ILLEGAL, 78
ER_WARN_SCHEDULED_TASK_RUN_FAILED, 401	ER_WINDOW_FRAME_START_ILLEGAL, 77
ER_WARN_SERVER_MEMORY_INIT_FAIL, 425	ER_WINDOW_INVALID_WINDOW_FUNC_IGNORES_FRAME, 78
ER_WARN_SET_OPERATIONS_BUFFER, 121	ER_WINDOW_ILLEGAL_ORDER_BY, 78
	ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE, 78
	ER_WINDOW_INVALID_WINDOW_FUNC_USE, 78
	ER_WINDOW_INVALID_WINDOW_FUNC_USE_IN_WINDOW, 78
	ER_WINDOW_NO_CHILD_PARTITIONING, 77
	ER_WINDOW_NO_GROUP_ORDER_UNUSED, 78
	ER_WINDOW_NO_INHERIT_FRAME, 77
	ER_WINDOW_NO_REDEFINE_ORDER_BY, 77

ER_WINDOW_NO_SUCH_WINDOW, 77	ER_WRONG_PARAMETERS_TO_NATIVE_FCT, 37
ER_WINDOW_RANGE_BOUND_NOT_CONSTANT, 78	ER_WRONG_PARAMETERS_TO_PROCEDURE, 10
ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE, 78	ER_WRONG_PARAMETERS_TO_STORED_FCT, 37
ER_WINDOW_RANGE_FRAME_ORDER_TYPE, 78	ER_WRONG_PARTITION_NAME, 36
ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE, 78	ER_WRONG_PERFSCHEMA_USAGE, 43
ER_WINDOW_ROWS_INTERVAL_USE, 78	ER_WRONG_SIZE_NUMBER, 35
ER_WIN_LISTEN_BUT_HOW, 148	ER_WRONG_SRID_FOR_COLUMN, 81
ER_WIN_LOAD_LIBRARY_FAILED, 203	ER_WRONG_STRING_LENGTH, 31
ER_WL9236_NOW_UNUSED, 79	ER_WRONG_SUB_KEY, 8
ER_WRITABLE_CONFIG_REMOVED, 147	ER_WRONG_SUM_SELECT, 7
ER_WRITE_ROW_TO_PARTITION_FAILED, 196	ER_WRONG_TABLESPACE_NAME, 65
ER_WRITE_SET_EXCEEDS_LIMIT, 71	ER_WRONG_TABLE_NAME, 9
ER_WRONG_ARGUMENTS, 16	ER_WRONG_TYPE_COLUMN_VALUE_ERROR, 41
ER_WRONG_AUTO_KEY, 8	ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD, 202
ER_WRONG_COLUMN_NAME, 13	ER_WRONG_TYPE_FOR_VAR, 17
ER_WRONG_COMPRESSION_ALGORITHM_CLIENT, 101	ER_WRONG_USAGE, 17
ER_WRONG_COMPRESSION_LEVEL_CLIENT, 101	ER_WRONG_VALUE, 34
ER_WRONG_COUNT_FOR_KEY, 179	ER_WRONG_VALUE_COUNT, 7
ER_WRONG_COUNT_FOR_ORIGIN, 179	ER_WRONG_VALUE_COUNT_ON_ROW, 12
ER_WRONG_COUNT_OF_ELEMENTS, 179	ER_WRONG_VALUE_FOR_TYPE, 28
ER_WRONG_DATETIME_SPEC, 147	ER_WRONG_VALUE_FOR_VAR, 17
ER_WRONG_DB_NAME, 9	ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART, 106
ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR, 32	ER_X509_CANT_CHMOD_KEY, 159
ER_WRONG_FIELD_SPEC, 7	ER_X509_CANT_CREATE_CERT, 159
ER_WRONG_FIELD_TERMINATORS, 8	ER_X509_CANT_READ_CA_CERT, 159
ER_WRONG_FIELD_WITH_GROUP, 6	ER_X509_CANT_READ_CA_KEY, 159
ER_WRONG_FIELD_WITH_GROUP_V2, 63	ER_X509_CANT_WRITE_CERT, 159
ER_WRONG_FILE_NAME, 66	ER_X509_CANT_WRITE_KEY, 159
ER_WRONG_FK_DEF, 18	ER_X509_CIPHERS_MISMATCH, 159
ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN, 64	ER_X509_ISSUER_MISMATCH, 159
ER_WRONG_GROUP_FIELD, 7	ER_X509_NEEDS_RSA_PRIVKEY, 159
ER_WRONG_JSON_TABLE_VALUE, 83	ER_X509_SUBJECT_MISMATCH, 159
ER_WRONG_KEY_COLUMN, 13	ER_XAER_DUPID, 29
ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX, 89	ER_XAER_INVALID, 27
ER_WRONG_LOCK_OF_SYSTEM_TABLE, 29	ER_XAER_NOTA, 27
ER_WRONG_MRG_TABLE, 14	ER_XAER_OUTSIDE, 27
ER_WRONG_MVI_VALUE, 101	ER_XAER_RMERR, 27
ER_WRONG_NAME_FOR_CATALOG, 20	ER_XAER_RMFAIL, 27
ER_WRONG_NAME_FOR_INDEX, 20	ER_XA_CANT_CREATE_MDL_BACKUP, 356
ER_WRONG_NATIVE_TABLE_STRUCTURE, 43	ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER, 155
ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT, 17	ER_XA_RBDEADLOCK, 38
ER_WRONG_OBJECT, 24	ER_XA_RBROLLBACK, 27
ER_WRONG_OUTER_JOIN_UNUSED, 11	ER_XA_RBTIMEOUT, 38
ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT, 37	ER_XA_RECOVERY_DONE, 155
ER_WRONG_PARAMCOUNT_TO_PROCEDURE, 10	ER_XA_RECOVER_EXPLANATION, 155
	ER_XA_RECOVER_FOUND_TRX_IN_SE, 155
	ER_XA_RECOVER_FOUND_XA_TRX, 155
	ER_XA_REPLICATION_FILTERS, 100
	ER_XA_RETRY, 71
	ER_XA_STARTING_RECOVERY, 155
	ER_XA_TEMP_TABLE, 115

ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED, 220	ER_XPLUGIN_FORCE_STOP_CLIENT, 218
ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED, 218	ER_XPLUGIN_IPv6_AVAILABLE, 220
ER_XPLUGIN_CLIENT_KILL_MSG, 220	ER_XPLUGIN_LISTENER_SETUP_FAILED, 219
ER_XPLUGIN_COMPRESSION_ERROR, 357	ER_XPLUGIN_LISTENER_STATUS_MSG, 220
ER_XPLUGIN_DETECTED_HANGING_CLIENTS, 218	ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR, 220
ER_XPLUGIN_EMPTY_ADMIN_CMD, 221	ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED, 218
ER_XPLUGIN_ERROR_MSG, 216	ER_XPLUGIN_MESSAGE_TOO_LONG, 220
ER_XPLUGIN_ERROR_READING_SOCKET, 220	ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING, 220
ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP, 219	ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION, 220
ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER, 219	ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH, 215
ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCORRECT_REFERENCE, 219	ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOCUMENT, 219
ER_XPLUGIN_FAILED_AT_SSL_CONF, 219	ER_XPLUGIN_RETRYING_BIND_ON_PORT, 220
ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT, 218	ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED, 219
ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS, 365	ER_XPLUGIN_STARTUP_FAILED, 215
ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION, 221	ER_XPLUGIN_TASK_SCHEDULING_FAILED, 219
ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONNECTION, 219	ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION, 219
ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD, 221	ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT, 219
ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT, 221	ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING, 219
ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO, 221	ER_XPLUGIN_UNINITIALIZED_MESSAGE, 220
ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX, 221	ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX, 215
ER_XPLUGIN_FAILED_TO_GET_SYS_VAR, 221	ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER, 215
ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION, 219	ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION, 215
ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION, 221	ER_XPLUING_NET_STARTUP_FAILED, 219
ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES, 219	ER_YES, 3
ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG, 221	ER_ZLIB_Z_BUF_ERROR, 19
ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT, 218	ER_ZLIB_Z_DATA_ERROR, 19
ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS, 220	ER_ZLIB_Z_MEM_ERROR, 19
ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG, 221	WARN_AES_KEY_SIZE, 72
ER_XPLUGIN_FAILED_TO_STOP_SERVICES, 332	WARN_COND_ITEM_TRUNCATED, 40
ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT, 221	WARN_DATA_TRUNCATED, 19
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX, 340	WARN_NAMED_PIPE_ACCESS_EVERYONE, 57
ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF, 221	WARN_SESSION_ASCII_SEPARATOR_NOT_IMPLEMENTED, 40
ER_XPLUGIN_FAILED_TO_USE_SSL_CONF, 215	WARN_NO_CONNECTION_METADATA, 39
ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS, 365	WARN_ON_BLOCKHOLE_IN_RBR, 56
	WARN_OPTION_BELOW_LIMIT, 44
	WARN_OPTION_IGNORED, 39
	WARN_PLUGIN_BUSY, 39
	WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB, 95
	WARN_UNSUPPORTED_ACL_TABLES_READ, 108
	WARN_USELESS_SPATIAL_INDEX, 83
	ER_ABORTING error code, 148
	ER_ABORTING_CONNECTION error code, 13

ER_ABORTING_USER_CONNECTION error code, 192
 ER_ACCESS_DENIED_CHANGE_USER_ERROR error code, 56
 ER_ACCESS_DENIED_ERROR error code, 6
 ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD error code, 193
 ER_ACCESS_DENIED_ERROR_WITH_PASSWORD error code, 193
 ER_ACCESS_DENIED_FIREWALL error code, 133
 ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK error code, 360
 ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED_BY_PASSWORD error code, 193
 ER_ACCESS_DENIED_NO_PASSWORD_ERROR error code, 44
 ER_ACCESS_DENIED_NO_PROXY error code, 129
 ER_ACCESS_DENIED_NO_PROXY_GRANT error code, 129
 ER_ACCESS_DENIED_NO_PROXY_GRANT_WITH_NAME error code, 415
 ER_ACCESS_DENIED_NO_PROXY_WITH_NAME error code, 415
 ER_ACCOUNT_HAS_BEEN_LOCKED error code, 65
 ER_ACCOUNT_WITH_EXPIRED_PASSWORD error code, 386
 ER_ACL_OPERATION_FAILED error code, 72
 ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG error code, 354
 ER_ADDRESSES_FOR_HOSTNAME_HEADER error code, 144
 ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM error code, 144
 ER_ADD_PARTITION_NO_NEW_PARTITION error code, 34
 ER_ADD_PARTITION_SUBPART_ERROR error code, 34
 ER_ADMIN_WRONG_MRG_TABLE error code, 31
 ER_AES_INVALID_IV error code, 56
 ER_AES_INVALID_KDF_ITERATIONS error code, 71
 ER_AES_INVALID_KDF_NAME error code, 71
 ER_AES_INVALID_KDF_OPTION_SIZE error code, 72
 ER_AGGREGATE_IN_ORDER_NOT_SELECT error code, 61
 ER_AGGREGATE_ORDER_FOR_UNION error code, 59
 ER_AGGREGATE_ORDER_NON_AGG_QUERY error code, 59
 ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED error code, 103
 ER_ALTER_FILEGROUP_FAILED error code, 35
 ER_ALTER_INFO error code, 8
 ER_ALTER_OPERATION_NOT_SUPPORTED error code, 54
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 54
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_ERROR error code, 54

ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE error code, 55
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN error code, 54
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_SIZE error code, 114
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY error code, 54
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK error code, 54
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_RENAME error code, 54
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS error code, 55
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS error code, 61
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN error code, 55
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK error code, 54
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_NULL error code, 55
 ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION error code, 54
 ER_AMBIGUOUS_FIELD_TERM error code, 31
 ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY error code, 196
 ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME error code, 109
 ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE error code, 111
 ER_APPLIER_LOG_EVENT_VALIDATION_ERROR error code, 81
 ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUEST error code, 109
 ER_ATTRIBUTE_IGNORED error code, 82
 ER_AUDIT_API_ABORT error code, 69
 ER_AUDIT_CANT_ABORT_COMMAND error code, 191
 ER_AUDIT_CANT_ABORT_EVENT error code, 191
 ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD error code, 358
 ER_AUDIT_LOG_CANNOT_READ_PASSWORD error code, 354
 ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD error code, 354
 ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICY error code, 212
 ER_AUDIT_LOG_CANNOT_STORE_PASSWORD error code, 354
 ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY error code, 335
 ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING error code, 354
 ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE error code, 213
 ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION error code, 213

ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION	ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR
error code, 213	error code, 334
ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_EMPTY	ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL
error code, 335	error code, 213
ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET	ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE
error code, 335	error code, 214
ER_AUDIT_LOG_FILE_AUTO_PRUNED error code,	ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE
373	error code, 213
ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PRUNED	ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR
error code, 354	error code, 214
ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT	ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY
error code, 353	error code, 336
ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_INVALID	ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID
error code, 353	error code, 353
ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_INVALID	ER_AUDIT_LOG_KEYRING_PLUGIN_NOT_INSTALLED
error code, 353	error code, 335
ER_AUDIT_LOG_FILE_PRUNE_FAILED error code,	ER_AUDIT_LOG_OFFLOAD_ERROR error code, 425
373	ER_AUDIT_LOG_OFFLOAD_INFO error code, 425
ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE	ER_AUDIT_LOG_OFFLOAD_WARNING error code,
error code, 214	425
ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE	ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED error
error code, 214	code, 212
ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ	ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED
error code, 214	error code, 354
ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT INTO TABLE	ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH
error code, 214	error code, 213
ER_AUDIT_LOG_FILTER_FAILED_TO_READ TABLE	ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED
error code, 214	error code, 356
ER_AUDIT_LOG_FILTER_FAILED_TO_STORE TABLE	ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST
error code, 214	error code, 212
ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE TABLE	ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED
error code, 214	error code, 336
ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY	ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE
error code, 214	error code, 335
ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED error	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT
code, 212	error code, 357
ER_AUDIT_LOG_FILTER_RESULT_MSG error code,	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE
213	error code, 357
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH
error code, 214	error code, 357
ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED error	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH
code, 357	error code, 71
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHA
error code, 335	error code, 336
ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIRECTORY	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER
error code, 213	error code, 335
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE error	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS
code, 101	error code, 213
ER_AUDIT_LOG_INVALID_FILE_CONTENT error	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE
code, 354	error code, 213
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED
error code, 401	error code, 213
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED
error code, 335	error code, 213
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE
error code, 336	error code, 213
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_PLUGIN
error code, 335	error code, 163

ER_AUDIT_PLUGIN_HAS_INVALID_DATA error code, 164	ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS error code, 383
ER_AUDIT_WARNING error code, 191	ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED error code, 382
ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM error code, 162	ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR error code, 382
ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLE error code, 162	ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH error code, 400
ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKED error code, 161	ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED error code, 400
ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME error code, 161	ER_AUTHENTICATION_OPENID_CONFIGURATION_NOT_SET error code, 416
ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE error code, 161	ER_AUTHENTICATION_OPENID_FAILED_TO_UPDATE_CONFIGURATION error code, 417
ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME error code, 366	ER_AUTHENTICATION_OPENID_INSECURE_CONNECTION error code, 416
ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION error code, 366	ER_AUTHENTICATION_OPENID_INVALID_CONFIGURATION error code, 416
ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED error code, 161	ER_AUTHENTICATION_OPENID_INVALID_IDENTITY_PROVIDER error code, 416
ER_AUTHCACHE_PLUGIN_CONFIG error code, 160	ER_AUTHENTICATION_OPENID_INVALID_TOKEN error code, 416
ER_AUTHCACHE_PLUGIN_MISSING error code, 160	ER_AUTHENTICATION_OPENID_INVALID_TOKEN_SIZE error code, 416
ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROLE_NAME error code, 162	ER_AUTHENTICATION_OPENID_ISSUER_MISMATCH error code, 416
ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE error code, 162	ER_AUTHENTICATION_OPENID_OPTION_DEREGISTER error code, 420
ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE error code, 160	ER_AUTHENTICATION_OPENID_OPTION_REGISTER error code, 419
ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME error code, 366	ER_AUTHENTICATION_OPENID_READ_PACKET error code, 416
ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION error code, 366	ER_AUTHENTICATION_OPENID_TOKEN_NOT_VERIFIED error code, 416
ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE error code, 162	ER_AUTHENTICATION_OPENID_USER_MISMATCH error code, 416
ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING error code, 161	ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT error code, 382
ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD error code, 161	ER_AUTHENTICATION_PLUGIN_LOG error code, 382
ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD error code, 161	ER_AUTHENTICATION_PLUGIN_OOM error code, 382
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN error code, 161	ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED error code, 381
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE error code, 160	ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT error code, 382
ER_AUTHCACHE_USER_TABLE_DODGY error code, 161	ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT error code, 382
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY error code, 400	ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED error code, 382
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY error code, 382	ER_AUTHENTICATION_POLICY_MISMATCH error code, 382
ER_AUTHENTICATION_OCI_IAM error code, 383	ER_AUTH_CANT_ACTIVATE_ROLE error code, 159
ER_AUTHENTICATION_OCI_IMDS error code, 382	ER_AUTH_CANT_CREATE_RSA_PAIR error code, 159
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_MODE error code, 383	ER_AUTH_CANT_WRITE_PRIVKEY error code, 160
ER_AUTHENTICATION_OCI_INVALID_TOKEN error code, 400	ER_AUTH_CANT_WRITE_PUBKEY error code, 160
ER_AUTHENTICATION_OCI_NONCE error code, 383	
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND error code, 383	

ER_AUTH_CERTS_SAVED_TO_DATADIR error code, 160	ER_BEFORE_DML_VALIDATION_ERROR error code, 64
ER_AUTH_CERT_GENERATION_DISABLED error code, 160	ER_BEG_INITFILE error code, 149
ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLE error code, 149	ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD error code, 402
ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG error code, 378	ER_BEYOND_SERVER_UPGRADE_THRESHOLD error code, 402
ER_AUTH_KEYS_SAVED_TO_DATADIR error code, 160	ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX error code, 47
ER_AUTH_KEY_GENERATION_DISABLED error code, 160	ER_BINLOG_CACHE_SIZE_TOO_LARGE error code, 192
ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT error code, 160	ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX error code, 187
ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG error code, 216	ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED error code, 189
ER_AUTH_RSA_CANT_FIND error code, 158	ER_BINLOG_CANT_CLOSE_TMP_INDEX error code, 187
ER_AUTH_RSA_CANT_PARSE error code, 159	ER_BINLOG_CANT_COPY_INDEX_TO_TMP error code, 187
ER_AUTH_RSA_CANT_READ error code, 159	ER_BINLOG_CANT_DELETE_FILE error code, 187
ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION error code, 160	ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_IN error code, 188
ER_AUTH_RSA_FILES_NOT_FOUND error code, 159	ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH error code, 188
ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION error code, 160	ER_BINLOG_CANT_FIND_LOG_IN_INDEX error code, 188
ER_AUTH_USING_EXISTING_CERTS error code, 160	ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME error code, 186
ER_AUTOINC_READ_FAILED error code, 31	ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG error code, 187
ER_AUTOPILOT_OLTP_ADVISOR_ERROR error code, 428	ER_BINLOG_CANT_MOVE_TMP_TO_INDEX error code, 187
ER_AUTOPILOT_OLTP_ADVISOR_INFO error code, 428	ER_BINLOG_CANT_OPEN_CRASHED_BINLOG error code, 189
ER_AUTOPILOT_OLTP_ADVISOR_WARNING error code, 428	ER_BINLOG_CANT_OPEN_FOR_LOGGING error code, 185
ER_AUTO_CONVERT error code, 18	ER_BINLOG_CANT_OPEN_TMP_INDEX error code, 187
ER_AUTO_INCREMENT_CONFLICT error code, 55	ER_BINLOG_CANT_RESIZE_CACHE error code, 185
ER_AUTO_INCREMENT_NOT_SUPPORTED_FOR_FLOAT error code, 413	ER_BINLOG_CANT_SET_TMP_INDEX_NAME error code, 187
ER_AUTO_OPTIONS_FAILED error code, 152	ER_BINLOG_CANT_TRIM_CRASHED_BINLOG error code, 189
ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_ON error code, 49	ER_BINLOG_CANT_USE_FOR_LOGGING error code, 186
ER_BACKGROUND_HISTOGRAM_UPDATE error code, 413	ER_BINLOG_CRASHED_BINLOG_TRIMMED error code, 189
ER_BACK_IN_TIME error code, 147	ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED error code, 391
ER_BAD_DB_ERROR error code, 6	ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS error code, 391
ER_BAD_FIELD_ERROR error code, 6	ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE error code, 391
ER_BAD_FT_COLUMN error code, 20	ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG error code, 390
ER_BAD_HOST_ERROR error code, 5	ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED error code, 391
ER_BAD_LOG_STATEMENT error code, 37	
ER_BAD_NULL_ERROR error code, 6	
ER_BAD_NULL_ERROR_NOT_IGNORED error code, 83	
ER_BAD_REPLICA error code, 15	
ER_BAD_REPLICA_AUTO_POSITION error code, 49	
ER_BAD_REPLICA_UNTIL_COND error code, 20	
ER_BAD_TABLE_ERROR error code, 6	
ER_BAD_TIMESTAMP_FORMAT error code, 117	
ER_BASE64_DECODE_ERROR error code, 37	
ER_BASEDIR_SET_TO error code, 195	

ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED error code, 391	ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS error code, 188
ER_BINLOG_CREATE_ROUTINE_NEED_SUPER error code, 28	ER_BINLOG_LOGGING_NOT_POSSIBLE error code, 204
ER_BINLOG_END error code, 148	ER_BINLOG_LOGICAL_CORRUPTION error code, 55
ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG error code, 186	ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG error code, 204
ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG error code, 186	ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION error code, 93
ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA error code, 186	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AFTER error code, 94
ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO error code, 186	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UP error code, 94
ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED error code, 195	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY error code, 93
ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_ERROR error code, 186	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT error code, 93
ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_ERROR error code, 186	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOG error code, 93
ER_BINLOG_FAILED_TO_DELETE_LOG_FILE error code, 188	ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE error code, 42
ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_ERROR error code, 186	ER_BINLOG_NEEDS_SERVERID error code, 151
ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE error code, 188	ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP error code, 180
ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE error code, 187	ER_BINLOG_PURGE_EMFILE error code, 37
ER_BINLOG_FAILED_TO_READ_REGISTER_FILE error code, 188	ER_BINLOG_PURGE_FATAL_ERR error code, 26
ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE error code, 188	ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX error code, 187
ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_ERROR error code, 186	ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE error code, 187
ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK error code, 189	ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE error code, 187
ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK error code, 189	ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE error code, 187
ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME error code, 188	ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE error code, 188
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE error code, 186	ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG NAME error code, 188
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN error code, 186	ER_BINLOG_PURGE_PROHIBITED error code, 26
ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES error code, 180	ER_BINLOG_RECOVERING_AFTER_CRASH_USING error code, 188
ER_BINLOG_FATAL_ERROR error code, 38	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE error code, 41
ER_BINLOG_FILE_BEING_READ_NOT_PURGED error code, 185	ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE error code, 42
ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED error code, 185	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE error code, 42
ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW error code, 185	ER_BINLOG_ROW_LOGGING_FAILED error code, 35
ER_BINLOG_FILE_NAME_TOO_LONG error code, 185	ER_BINLOG_ROW_MODE_AND_STMT_ENGINE error code, 41
ER_BINLOG_FILE_OPEN_FAILED error code, 195	ER_BINLOG_ROW_VALUE_OPTION_IGNORED error code, 331
ER_BINLOG_IO_ERROR_READING_HEADER error code, 185	ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER error code, 331
ER_BINLOG_LOGGING_IMPOSSIBLE error code, 38	ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX error code, 47
	ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE error code, 192

ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES error code, 54	ER_BINLOG_WARNING_SUPPRESSED error code, 189
ER_BINLOG_STMT_MODE_AND_ROW_ENGINE error code, 42	ER_BLOBS_AND_NO_TERMINATED error code, 8
ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READ error code, 352	ER_BLOB_CANT_HAVE_DEFAULT error code, 9
ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL error code, 108	ER_BLOB_FIELD_IN_PART_FUNC_ERROR error code, 33
ER_BINLOG_UNSAFE_AND_STMT_ENGINE error code, 41	ER_BLOB_KEY_WITHOUT_LENGTH error code, 14
ER_BINLOG_UNSAFE_AUTOINC_COLUMNS error code, 42	ER_BLOB_USED_AS_KEY error code, 8
ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST error code, 46	ER_BLOCKED_CIPHER error code, 412
ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT error code, 45	ER_BOOST_GEOMETRY_CENTROID_EXCEPTION error code, 60
ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT error code, 45	ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION error code, 60
ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC error code, 46	ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION error code, 66
ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBQUERY error code, 353	ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION error code, 60
ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN error code, 57	ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION error code, 60
ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT error code, 45	ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION error code, 60
ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE error code, 45	ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION error code, 60
ER_BINLOG_UNSAFE_INSERT_TWO_KEYS error code, 46	ER_BOOTSTRAP_CANT_THREAD error code, 140
ER_BINLOG_UNSAFE_LIMIT error code, 42	ER_BUFPOOL_RESIZE_INPROGRESS error code, 69
ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT error code, 192	ER_BUILD_ID error code, 392
ER_BINLOG_UNSAFE_MIXED_STATEMENT error code, 44	ER_BULK_BLOB_TOO_BIG error code, 131
ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELECT error code, 43	ER_BULK_EXECUTOR_ERROR error code, 118
ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS error code, 42	ER_BULK_EXECUTOR_INFO error code, 395
ER_BINLOG_UNSAFE_NOWAIT error code, 76	ER_BULK_JSON_INVALID error code, 131
ER_BINLOG_UNSAFE_REPLACE_SELECT error code, 45	ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER error code, 119
ER_BINLOG_UNSAFE_ROUTINE error code, 28	ER_BULK_LOADER_COMPONENT_ERROR error code, 119
ER_BINLOG_UNSAFE_SKIP_LOCKED error code, 76	ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_I error code, 119
ER_BINLOG_UNSAFE_STATEMENT error code, 38	ER_BULK_LOAD_ENGINE error code, 119
ER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 42	ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_I error code, 395
ER_BINLOG_UNSAFE_SYSTEM_TABLE error code, 42	ER_BULK_LOADER_INFO error code, 395
ER_BINLOG_UNSAFE_SYSTEM_VARIABLE error code, 42	ER_BULK_LOAD_DATA_FAILED error code, 118
ER_BINLOG_UNSAFE_UDF error code, 42	ER_BULK_LOAD_RESOURCE error code, 123
ER_BINLOG_UNSAFE_UPDATE_IGNORE error code, 45	ER_BULK_LOAD_SECONDARY_ENGINE error code, 123
ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT error code, 46	ER_BULK_LOAD_TABLE_HAS_INSTANT_COLS error code, 123
ER_BINLOG_UNSAFE_XA error code, 71	ER_BULK_MERGE_INVALID_CHUNK error code, 122
	ER_BULK_MERGE_LOADER_INFO error code, 406
	ER_BULK_MERGE_NOT_ALL_CHUNKS_CONSUMED error code, 122
	ER_BULK_MULTI_READER_INFO error code, 406
	ER_BULK_MULTI_READER_OPEN_FILE_FAILED error code, 122
	ER_BULK_MULTI_READER_READ_FILE_FAILED error code, 122
	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED error code, 119
	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOCAL error code, 395

ER_BULK_PARSER_ERROR error code, 130	ER_BULK_READER_SERVER_ERROR error code, 118
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE error code, 119	ER_BULK_READER_SERVER_ERROR_LOG error code, 395
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE error code, 396	ER_BULK_READER_ZSTD_ERROR error code, 130
ER_BULK_PARSER_MISSING_ENCLOSED_BY error code, 119	ER_BULK_READER_ZSTD_ERROR_LOG error code, 415
ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG error code, 395	ER_BULK_SCANNER_INFO error code, 415
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED error code, 119	ER_BULK_SORTING_LOADER_INFO error code, 406
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED_LOG error code, 395	ER_BULK_SORTING_LOADER_WAIT error code, 123
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR error code, 119	ER_BULK_SORTING_LOADER_WRITE error code, 415
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR_LOG error code, 396	ER_BULK_WRITER_INFO error code, 406
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_END_OF_INPUT error code, 119	ER_BULK_WRITER_LIBCURL_ERROR error code, 123
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_END_OF_INPUT_LOG error code, 396	ER_BULK_WRITER_LIBCURL_ERROR_LOG error code, 406
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENCLOSED_BY error code, 119	ER_BULK_WRITER_LIBMBCURL_INIT_FAILED error code, 122
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENCLOSED_BY_LOG error code, 396	ER_BULK_WRITER_LIBMBCURL_INIT_FAILED_LOG error code, 406
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE error code, 119	ER_CANNOT_ADD_SHA2_PASSWORD_SECOND_PASSWORD_USE error code, 344
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE_LOG error code, 396	ER_CANNOT_ADD_LOCALHOST error code, 148
ER_BULK_PARSER_UNEXPECTED_ENCLOSED_BY_CHARACTER error code, 132	ER_CANNOT_ADD_FOREIGN error code, 16
ER_BULK_PARSER_UNEXPECTED_ENCLOSED_BY_CHARACTER_LOG error code, 420	ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED error code, 71
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT error code, 119	ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL error code, 69
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG error code, 395	ER_CANNOT_ALTER_SRID_DUE_TO_INDEX error code, 81
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR error code, 119	ER_CANNOT_CHANGE_TO_ROOT_DIR error code, 195
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG error code, 396	ER_CANNOT_CONVERT_STRING error code, 97
ER_BULK_READER_COMMUNICATION_ERROR error code, 118	ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT error code, 69
ER_BULK_READER_COMMUNICATION_ERROR_LOG error code, 395	ER_CANNOT_DISCARD_TEMPORARY_TABLE error code, 57
ER_BULK_READER_COULDNT_RESOLVE_HOST error code, 123	ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX error code, 89
ER_BULK_READER_ERROR error code, 123	ER_CANNOT_EXECUTE_IN_PRIMARY error code, 123
ER_BULK_READER_FILE_DOESNT_EXIST error code, 123	ER_CANNOT_FIND_KEY_IN_KEYRING error code, 70
ER_BULK_READER_INFO error code, 395	ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE error code, 346
ER_BULK_READER_LIBCURL_ERROR error code, 118	ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER error code, 98
ER_BULK_READER_LIBCURL_ERROR_LOG error code, 395	ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE error code, 100
ER_BULK_READER_LIBCURL_INIT_FAILED error code, 118	ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES error code, 385
ER_BULK_READER_LIBCURL_INIT_FAILED_LOG error code, 395	ER_CANNOT_LOAD_FROM_TABLE_V2 error code, 46
ER_BULK_READER_OPEN_FILE_FAILED error code, 123	ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES error code, 75
	ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID error code, 63

ER_CANNOT_PERSIST_SENSITIVE_VARIABLES error code, 116	ER_CANT_CREATE_SCHEDULER_THREAD error code, 143
ER_CANNOT_PERSIST_TRANSACTION_ISOLATION error code, 133	ER_CANT_CREATE_SHM_THREAD error code, 147
ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK error code, 115	ER_CANT_CREATE_SHUTDOWN_THREAD error code, 146
ER_CANNOT_SET_DATABASE_ENCRYPTION error code, 95	ER_CANT_CREATE_TABLE error code, 3
ER_CANNOT_SET_LOG_ERROR_SERVICES error code, 195	ER_CANT_CREATE_TABLE_SHARE_FROM_FRM error code, 182
ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE error code, 346	ER_CANT_CREATE_TCPIP_THREAD error code, 147
ER_CANNOT_SET_TABLESPACE_ENCRYPTION error code, 95	ER_CANT_CREATE_TEST_FILE error code, 146
ER_CANNOT_SET_TABLE_ENCRYPTION error code, 95	ER_CANT_CREATE_THREAD error code, 12
ER_CANNOT_USER error code, 27	ER_CANT_CREATE_USER_WITH_GRANT error code, 27
ER_CANNOT_USER_REFERENCED_AS_DEFINER error code, 108	ER_CANT_CREATE_UUID error code, 145
ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE error code, 110	ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN error code, 171
ER_CANNOT_USE_ENCRYPTION_CLAUSE error code, 95	ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_N error code, 49
ER_CANT_ACCESS_CAPATH error code, 152	ER_CANT_DO_THIS_DURING_AN_TRANSACTION error code, 14
ER_CANT_AGGREGATE_2COLLATIONS error code, 19	ER_CANT_DROP_FIELD_OR_KEY error code, 9
ER_CANT_AGGREGATE_3COLLATIONS error code, 20	ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING error code, 65
ER_CANT_AGGREGATE_NCOLLATIONS error code, 20	ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID error code, 115
ER_CANT_ALLOC_TABLE_OBJECT error code, 182	ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION error code, 50
ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE error code, 120	ER_CANT_FIND_DL_ENTRY error code, 11
ER_CANT_CHANGE_TX_CHARACTERISTICS error code, 36	ER_CANT_FIND_SYSTEM_REC error code, 4
ER_CANT_CHECK_PID_PATH error code, 255	ER_CANT_FIND_UDF error code, 11
ER_CANT_CHOWN_DATADIR error code, 151	ER_CANT_GET_STAT error code, 4
ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_A error code, 109	ER_CANT_HASH_DO_AND_IGNORE_RULES error code, 152
ER_CANT_CREATE_ADMIN_THREAD error code, 344	ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT error code, 183
ER_CANT_CREATE_CACHE_FOR_DB_OPT error code, 183	ER_CANT_INCREASE_MAX_OPEN_FILES error code, 149
ER_CANT_CREATE_DB error code, 3	ER_CANT_INITIALIZE_BUILTIN_PLUGINS error code, 151
ER_CANT_CREATE_FILE error code, 3	ER_CANT_INITIALIZE_DYNAMIC_PLUGINS error code, 151
ER_CANT_CREATE_GEOMETRY_OBJECT error code, 28	ER_CANT_INITIALIZE_EARLY_PLUGINS error code, 151
ER_CANT_CREATE_HANDLER_FILE error code, 33	ER_CANT_INITIALIZE_GTID error code, 151
ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE error code, 182	ER_CANT_INITIALIZE_UDF error code, 11
ER_CANT_CREATE_HANDLE_MGR_THREAD error code, 142	ER_CANT_INIT_DBS error code, 150
ER_CANT_CREATE_INTERRUPT_THREAD error code, 147	ER_CANT_INIT_SCHEDULER_THREAD error code, 143
ER_CANT_CREATE_NAMED_PIPES_THREAD error code, 147	ER_CANT_INIT_TC_LOG error code, 142
ER_CANT_CREATE_PID_FILE error code, 146	ER_CANT_INIT_TIMER error code, 152
	ER_CANT_JOIN_SHUTDOWN_THREAD error code, 152
	ER_CANT_LOCK error code, 4
	ER_CANT_LOCK_LOG_TABLE error code, 36
	ER_CANT_LOCK_TABLE error code, 182
	ER_CANT_LOCK_TABLESPACE error code, 183
	ER_CANT_MODIFY_SRID_0 error code, 86

ER_CANT_MODIFY_SRS_USED_BY_COLUMN error code, 86	ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS error code, 75
ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES error code, 163	ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_N error code, 53
ER_CANT_OPEN_CA error code, 152	ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NO error code, 54
ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE error code, 184	ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE error code, 182
ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET error code, 183	ER_CANT_SET_PATH_FOR error code, 184
ER_CANT_OPEN_DIR error code, 184	ER_CANT_SET_PERSISTED error code, 120
ER_CANT_OPEN_ERROR_LOG error code, 152	ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANON error code, 109
ER_CANT_OPEN_FILE error code, 4	ER_CANT_SET_UP_PERSISTED_VALUES error code, 151
ER_CANT_OPEN_FRM_FILE error code, 163	ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID error code, 67
ER_CANT_OPEN_LIBRARY error code, 11	ER_CANT_START_ERROR_LOG_SERVICE error code, 194
ER_CANT_OPEN_TABLE_MYSQL_PROC error code, 184	ER_CANT_START_DATADIR error code, 151
ER_CANT_PARSE_STORED_ROUTINE_BODY error code, 184	ER_CANT_STAT_FILE error code, 188
ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMNS error code, 359	ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT error code, 47
ER_CANT_READ_DIR error code, 4	ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG error code, 29
ER_CANT_READ_ERRMSG error code, 150	ER_CANT_UPDATE_WITH_READLOCK error code, 17
ER_CANT_READ_FRM_FILE error code, 163	ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD error code, 183
ER_CANT_READ_TABLE_MYSQL_PROC error code, 184	ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_N error code, 109
ER_CANT_REMOVE_ALL_FIELDS error code, 9	ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF error code, 65
ER_CANT_REMOVE_PID_FILE error code, 146	ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON error code, 114
ER_CANT_RENAME_LOG_TABLE error code, 37	ER_CANT_USE_OPTION_HERE error code, 18
ER_CANT_REOPEN_TABLE error code, 12	ER_CANT_USE_SAME_UUID_AS_GROUP_NAME error code, 109
ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION error code, 334	ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID error code, 111
ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_OFF error code, 334	ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING error code, 69
ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF error code, 334	ER_CAPACITY_EXCEEDED error code, 69
ER_CANT_RESET_SOURCE error code, 71	ER_CAPACITY_EXCEEDED_IN_PARSER error code, 70
ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY error code, 121	ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER error code, 69
ER_CANT_SAVE_GTIDS error code, 152	ER_CA_SELF_SIGNED error code, 144
ER_CANT_SET_DATA_DIR error code, 342	ER_CANNOT_CHANGE_SOURCE_GTID_CONSISTENCY error code, 142
ER_CANT_SET_ERROR_LOG_SERVICE error code, 85	ER_CANNOT_CHANGE_GTID error code, 142
ER_CANT_SET_ERROR_SUPPRESSION_LIST error code, 87	ER_CANNOT_CHANGE_GTID_MODE error code, 142
ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE error code, 338	ER_CHANGED_MAX_CONNECTIONS error code, 149
ER_CANT_SET_GTID_MODE error code, 65	ER_CHANGED_MAX_OPEN_FILES error code, 149
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF error code, 50	ER_CANNOT_OPEN_TABLE_OPEN_CACHE error code, 149
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_OFF error code, 50	ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GT error code, 113
ER_CANT_SET_GTID_NEXT_TO_AUTOMATIC_TAGGED error code, 124	
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF error code, 50	
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID error code, 50	

ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITIONING error code, 113	ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS error code, 117
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITIONING error code, 113	ER_CLIENT_INVALID_POSITIONS_CREATE_DROP_TEMP_TABLE error code, 89
ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_OVERRUN_TIMEOUT error code, 113	ER_CLIENT_INVALID_POSITIONS_TIMEOUT error code, 110
ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_KEYRING_UDF_KEY_INVALID error code, 113	ER_CLIENT_INVALID_UDF_KEY_INVALID error code, 102
ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_OPTION_KEYRING_UDF_KEY_TOO_LONG error code, 113	ER_CLIENT_INVALID_UDF_KEY_TOO_LONG error code, 102
ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE error code, 47	ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID error code, 102
ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE error code, 111	ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG error code, 102
ER_CHANGE_SOURCE_PASSWORD_LENGTH error code, 61	ER_CLIENT_LOCAL_FILES_DISABLED error code, 104
ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM error code, 101	ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANY error code, 102
ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM error code, 102	ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT error code, 102
ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL error code, 101	ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 102
ER_CHARACTER_SET_MISMATCH error code, 107	ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APP error code, 102
ER_CHECKING_TABLE error code, 182	ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT error code, 108
ER_CHECKREAD error code, 4	ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT error code, 108
ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFERENCES error code, 95	ER_CLONE_CHARSET error code, 98
ER_CHECK_CONSTRAINT_DUP_NAME error code, 94	ER_CLONE_CLIENT_TRACE error code, 342
ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED error code, 94	ER_CLONE_CONFIG error code, 98
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 94	ER_CLONE_CREATE_HANDLER_FAIL_TRACE error code, 201
ER_CHECK_CONSTRAINT_NOT_FOUND error code, 94	ER_CLONE_DISALLOWED_IN_PROGRESS error code, 81
ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT error code, 94	ER_CLONE_DISALLOWED error code, 98
ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN error code, 94	ER_CLONE_DISK_SPACE error code, 98
ER_CHECK_CONSTRAINT_ROW_VALUE error code, 94	ER_CLONE_DONOR error code, 97
ER_CHECK_CONSTRAINT_VARIABLES error code, 94	ER_CLONE_DONOR_TRACE error code, 342
ER_CHECK_CONSTRAINT_VIOLATED error code, 94	ER_CLONE_DONOR_VERSION error code, 98
ER_CHECK_NOT_IMPLEMENTED error code, 14	ER_CLONE_ENCRYPTION error code, 98
ER_CHECK_NO_SUCH_TABLE error code, 14	ER_CLONE_HANDLER_EXIST_TRACE error code, 201
ER_CHECK_TABLE_FUNCTIONS error code, 403	ER_CLONE_IN_PROGRESS error code, 98
ER_CHECK_TABLE_FUNCTIONS_DETAIL error code, 403	ER_CLONE_LOOPBACK error code, 98
ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET error code, 397	ER_CLONE_NETWORK_PACKET error code, 104
ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET error code, 399	ER_CLONE_OS error code, 98
ER_CHECK_TABLE_MIN_REC_FLAG_SET error code, 399	ER_CLONE_PLATFORM error code, 98
ER_CLAUSE_IGNORED error code, 132	ER_CLONE_PLUGIN_MATCH error code, 98
ER_CLIENT_DOES_NOT_SUPPORT error code, 81	ER_CLONE_PLUGIN_NOT_LOADED_TRACE error code, 201
	ER_CLONE_PROTOCOL error code, 98
	ER_CLONE_PROTOCOL_TRACE error code, 342
	ER_CLONE_SERVER_TRACE error code, 342
	ER_CLONE_SHUTDOWN_TRACE error code, 355
	ER_CLONE_SYS_CONFIG error code, 98
	ER_CLONE_TOO_MANY_CONCURRENT_CLONES error code, 81
	ER_CMD_NEED_SUPER_OR_CREATE_SPATIAL_REFERENCES error code, 132

ER_COALESCE_ONLY_ON_HASH_PARTITION error code, 33	ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE error code, 74
ER_COALESCE_PARTITION_NO_PARTITION error code, 34	ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP error code, 75
ER_COLLATION_CHARSET_MISMATCH error code, 19	ER_COMPONENTS_UNLOAD_NOT_LOADED error code, 74
ER_COLUMNACCESS_DENIED_ERROR error code, 12	ER_COMPONENT_EE_DATA_DECRYPTION_ERROR error code, 392
ER_COLUMN_CHANGE_SIZE error code, 99	ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR error code, 392
ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_TABLE error code, 94	ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE error code, 392
ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2 error code, 51	ER_COMPONENT_EE_DATA_SIGN_ERROR error code, 392
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 36	ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE error code, 391
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2 error code, 58	ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM error code, 391
ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CODE error code, 117	ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS error code, 391
ER_COMMAND_SERVICE_BACKEND_FAILED error code, 117	ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE error code, 391
ER_COMMENT_CONTAINS_INVALID_STRING error code, 115	ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE error code, 392
ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG error code, 28	ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE error code, 392
ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION error code, 74	ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE error code, 391
ER_COMPONENTS_CANT_LOAD error code, 74	ER_COMPONENT_EE_INSUFFICIENT_LENGTH error code, 392
ER_COMPONENTS_CANT_RELEASE_SERVICE error code, 74	ER_COMPONENT_EE_OPENSSL_ERROR error code, 392
ER_COMPONENTS_CANT_SATISFY_DEPENDENCY error code, 74	ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE error code, 391
ER_COMPONENTS_CANT_UNLOAD error code, 74	ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE error code, 391
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION error code, 204	ER_COMPONENT_FILTER_CONFUSED error code, 80
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 144	ER_COMPONENT_FILTER_DIAGNOSTICS error code, 85
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DENIED error code, 374	ER_COMPONENT_FILTER_FLABBERGASTED error code, 80
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INVALID error code, 373	ER_COMPONENT_FILTER_WRONG_VALUE error code, 332
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 144	ER_COMPONENT_FIREWALL_ACCESS_DENIED error code, 424
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_FAILED error code, 405	ER_COMPONENT_FIREWALL_ACCESS_DENIED_TRUNCATED error code, 423
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_STARTED error code, 405	ER_COMPONENT_FIREWALL_CANNOT_ACCESS_TABLE error code, 424
ER_COMPONENTS_LOAD_CANT_INITIALIZE error code, 74	ER_COMPONENT_FIREWALL_CANNOT_READ_TABLE error code, 424
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION error code, 74	ER_COMPONENT_FIREWALL_DATABASE error code, 424
ER_COMPONENTS_NO_SCHEME error code, 73	ER_COMPONENT_FIREWALL_INIT error code, 424
ER_COMPONENTS_NO_SCHEME_SERVICE error code, 74	ER_COMPONENT_FIREWALL_INVALID_RELOAD_INTERVAL_VALUE error code, 423
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP error code, 144	
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE error code, 74	

ER_COMPONENT_FIREWALL_INVALID_TABLE_DEFINITION error code, 424	ER_CONDITIONAL_DEBUG error code, 393
ER_COMPONENT_FIREWALL_NOTIFICATION_REGISTRATION_FAILURE error code, 423	ER_COND_ITEM_TOO_LONG error code, 41
ER_COMPONENT_FIREWALL_OTHER_ERROR error code, 423	ER_CONNECTION_WITHOUT_GROUP error code, 154
ER_COMPONENT_FIREWALL_PROCESSING_ERROR error code, 424	ER_CONFIRMING_THE_FUTURE error code, 147
ER_COMPONENT_FIREWALL_PROCESSING_EXCEPTION error code, 424	ER_CONFLICTING_DECLARATIONS error code, 21
ER_COMPONENT_FIREWALL_RECORDING_TRUNCATED error code, 423	ER_CONFLICT_FN_PARSE_ERROR error code, 39
ER_COMPONENT_FIREWALL_RELOAD_TOO_SHORT error code, 424	ER_CONNECTIONS_SHUTDOWN_END error code, 405
ER_COMPONENT_FIREWALL_SUSPICIOUS_STMT error code, 423	ER_CONNECTIONS_SHUTDOWN_START error code, 405
ER_COMPONENT_FIREWALL_SUSPICIOUS_STMT_TRUNCATED error code, 423	ER_CONNECTION_ABORTED error code, 331
ER_COMPONENT_FIREWALL_TRACING_ERROR error code, 424	ER_CONNECTION_CONTROL_FAILED_DEINIT error code, 420
ER_COMPONENT_FIREWALL_VAR_REGISTRATION_FAILURE error code, 423	ER_CONNECTION_CONTROL_FAILED_TO_GET_ATTRIBUTE error code, 420
ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY error code, 393	ER_CONNECTION_CONTROL_FAILED_TO_GET_SECURITY_ATTRIBUTES error code, 420
ER_COMPONENT_KEYRING_OCI_INVALID_CONFIG_VARIABLE error code, 406	ER_CONNECTION_CONTROL_STATUS_VAR_REG_FAILED error code, 420
ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE error code, 393	ER_CONNECTION_CONTROL_STATUS_VAR_UNREG_FAILED error code, 420
ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE error code, 393	ER_CONNECTION_CONTROL_VARIABLE_REGISTRATION_FAILURE error code, 420
ER_COMPONENT_LOCK error code, 400	ER_CONNECTION_CONTROL_VARIABLE_UNREGISTRATION_FAILURE error code, 420
ER_COMPONENT_MANIPULATE_ROW_FAILED error code, 75	ER_CONNECTION_HANDLING_OOM error code, 146
ER_COMPONENT_MASKING_ABI error code, 401	ER_CONNECTION_METADATA error code, 15
ER_COMPONENT_MASKING_ABI_REASON error code, 401	ER_CONNECT_TO_FOREIGN_DATA_SOURCE error code, 29
ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE error code, 401	ER_CONNECT_TO_SOURCE error code, 17
ER_COMPONENT_MASKING_INVALID_FLUSH_INTERVAL error code, 411	ER_CONN_ATTR_TRUNCATED error code, 159
ER_COMPONENT_MASKING_NOTIFICATION_REGISTRATION_FAILURE error code, 412	ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED error code, 218
ER_COMPONENT_MASKING_OTHER_ERROR error code, 401	ER_CONN_CONTROL_ERROR_MSG error code, 216
ER_COMPONENT_MASKING_RANDOM_CREATE error code, 401	ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED error code, 218
ER_COMPONENT_MASKING_RANDOM_CREATE_REASON error code, 401	ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY_ACTION error code, 218
ER_COMPONENT_MASKING_VAR_REGISTRATION_FAILURE error code, 411	ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_ACTION error code, 218
ER_COMPONENT_SERVICE_CALL error code, 400	ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE error code, 218
ER_COMPONENT_SERVICE_CALL_RESULT error code, 400	ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_FAILURE error code, 218
ER_COMPONENT_TABLE_INCORRECT error code, 75	ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UNEXPECTED error code, 218
ER_COMPONENT_UNLOCK error code, 401	ER_CONN_CONTROL_STAT_CONN_EXEMPTED_USERS_UNEXPECTED error code, 428
ER_CONCURRENT_PROCEDURE_USAGE error code, 114	ER_CONN_INIT_CONNECT_IGNORED error code, 217
	ER_CONN_INIT_CONNECT_IGNORED_MFA error code, 401
	ER_CONN_LIMIT error code, 384
	ER_CONN_PER_THREAD_NO_THREAD error code, 156
	ER_CONN_PIP_CANT_CREATE_EVENT error code, 156

ER_CONN_PIP_CANT_CREATE_PIPE error code, 156	ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE error code, 157
ER_CONN_SHM_CANT_CREATE_CONNECTION error code, 156	ER_CONSECUTIVE_REORG_PARTITIONS error code, 34
ER_CONN_SHM_CANT_CREATE_SERVICE error code, 156	ER_CONSTRAINT_NOT_FOUND error code, 103
ER_CONN_SHM_LISTENER error code, 156	ER_CONVERT_MULTI_VALUE error code, 402
ER_CONN_SOCKET_ACCEPT_FAILED error code, 158	ER_CON_COUNT_ERROR error code, 5
ER_CONN_SOCKET_SELECT_FAILED error code, 158	ER_CORE_VALUES error code, 147
ER_CONN_TCP_ADDRESS error code, 156	ER_CORRUPTED_JSON_DIFF error code, 82
ER_CONN_TCP_BIND_FAIL error code, 157	ER_CORRUPT_HELP_DB error code, 18
ER_CONN_TCP_BIND_RETRY error code, 157	ER_COULD_NOT_APPLY_JSON_DIFF error code, 82
ER_CONN_TCP_CANT_RESET_V6ONLY error code, 157	ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY error code, 340
ER_CONN_TCP_CANT_RESOLVE_HOSTNAME error code, 157	ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS error code, 335
ER_CONN_TCP_CREATED error code, 156	ER_CRASHED_ON_REPAIR error code, 15
ER_CONN_TCP_ERROR_WITH_STRERROR error code, 156	ER_CRASHED_ON_USAGE error code, 15
ER_CONN_TCP_IPV6_AVAILABLE error code, 156	ER_CREATED_SYSTEM_WITH_VERSION error code, 200
ER_CONN_TCP_IPV6_UNAVAILABLE error code, 156	ER_CREATE_FILEGROUP_FAILED error code, 35
ER_CONN_TCP_IP_NOT_LOGGED error code, 157	ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR error code, 117
ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT error code, 157	ER_CREATING_NEW_UUID error code, 145
ER_CONN_TCP_LISTEN_FAIL error code, 157	ER_CREATING_NEW_UUID_FIRST_START error code, 194
ER_CONN_TCP_NO_SOCKET error code, 156	ER_CREDENTIALLESS_AUTO_USER_BAD error code, 146
ER_CONN_TCP_RESOLVE_INFO error code, 157	ER_CREDENTIALS_CONTRADICT_TO_HISTORY error code, 81
ER_CONN_TCP_START_FAIL error code, 157	ER_CTE_MAX_RECURSION_DEPTH error code, 81
ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET error code, 157	ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER error code, 77
ER_CONN_UNIX_LISTEN_FAILED error code, 158	ER_CTE_RECURSIVE_FORBIDS_AGGREGATION error code, 77
ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE error code, 158	ER_CTE_RECURSIVE_NOT_UNION error code, 117
ER_CONN_UNIX_LOCK_FILE_CANT_CREATE error code, 158	ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST error code, 77
ER_CONN_UNIX_LOCK_FILE_CANT_DELETE error code, 158	ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE error code, 77
ER_CONN_UNIX_LOCK_FILE_CANT_OPEN error code, 158	ER_CTE_RECURSIVE_REQUIRES_UNION error code, 77
ER_CONN_UNIX_LOCK_FILE_CANT_READ error code, 158	ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED error code, 100
ER_CONN_UNIX_LOCK_FILE_CANT_SYNC error code, 158	ER_CURRENT_PASSWORD_NOT_REQUIRED error code, 99
ER_CONN_UNIX_LOCK_FILE_CANT_WRITE error code, 158	ER_CUT_VALUE_GROUP_CONCAT error code, 19
ER_CONN_UNIX_LOCK_FILE_EMPTY error code, 158	ER_CYCLE_TIMER_IS_NOT_AVAILABLE error code, 201
ER_CONN_UNIX_LOCK_FILE_FAIL error code, 157	ER_DATABASE_NAME error code, 39
ER_CONN_UNIX_LOCK_FILE_GIVING_UP error code, 158	ER_DATA_DIRECTORY_UNUSABLE error code, 340
ER_CONN_UNIX_LOCK_FILE_PIDLESS error code, 158	ER_DATA_DIRECTORY_UNUSABLE_DELETABLE error code, 355
ER_CONN_UNIX_NO_BIND_NO_START error code, 157	ER_DATA_INCOMPATIBLE_WITH_VECTOR error code, 130
ER_CONN_UNIX_NO_FD error code, 157	ER_DATA_OUT_OF_RANGE error code, 43
ER_CONN_UNIX_PATH_TOO_LONG error code, 157	ER_DATA_TOO_LONG error code, 27
	ER_DATETIME_FUNCTION_OVERFLOW error code, 29

ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MA	ER_DD_CREATE_SP error code, 183
error code, 99	ER_DD_CANT_FETCH_TABLE_DATA error code, 183
ER_DA_CANT_OPEN_ERROR_LOG error code, 108	ER_DD_CANT_FIX_SE_DATA error code, 183
ER_DA_CONN_LIMIT error code, 114	ER_DD_CANT_GET_OBJECT_KEY error code, 142
ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED	ER_DD_CANT_RESOLVE_VIEW error code, 153
error code, 111	ER_DD_CREATED_FOR_UPGRADE error code, 162
ER_DA_ERROR_LOG_MULTIPLE_FILTERS error	ER_DD_ERROR_CREATING_ENTRY error code, 183
code, 108	ER_DD_FAILSAFE error code, 140
ER_DA_ERROR_LOG_TABLE_DISABLED error code,	ER_DD_FRM_EXISTS_FOR_TABLE error code, 162
108	ER_DD_INITIALIZE error code, 205
ER_DA_GLOBAL_CONN_LIMIT error code, 114	ER_DD_INITIALIZE_SQL_ERROR error code, 336
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT	ER_DD_INIT_FAILED error code, 141
error code, 106	ER_DD_METADATA_NOT_FOUND error code, 141
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID	ER_DD_MINOR_DOWNGRADE error code, 205
error code, 106	ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED
ER_DA_GRP_RPL_STARTED_AUTO_REJOIN error	error code, 205
code, 101	ER_DD_NO_VERSION_FOUND error code, 205
ER_DA_INVALID_CONDITION_NUMBER error code,	ER_DD_NO_WRITES_NO_REPOPULATION error
48	code, 140
ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED	ER_DD_OBJECT_RELEASER_REMAINS error code,
error code, 108	142
ER_DA_OOM error code, 104	ER_DD_OBJECT_REMAINS error code, 141
ER_DA_PLUGIN_INSTALL_ERROR error code, 99	ER_DD_OBJECT_REMAINS_IN_RELEASER error
ER_DA_RPL_GTID_TABLE_CANNOT_OPEN error	code, 141
code, 99	ER_DD_RESTART error code, 205
ER_DA_SSL_FIPS_MODE_ERROR error code, 114	ER_DD_SCHEMA_NOT_FOUND error code, 162
ER_DA_SSL_LIBRARY_ERROR error code, 99	ER_DD_SE_INIT_FAILED error code, 162
ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET	ER_DD_TABLESPACE_NOT_FOUND error code, 153
error code, 104	ER_DD_TABLE_NOT_FOUND error code, 162
ER_DA_UDF_INVALID_CHARSET error code, 103	ER_DD_TRG_CANT_ADD error code, 153
ER_DA_UDF_INVALID_CHARSET_SPECIFIED error	ER_DD_TRG_CONNECTION_COLLATION_MISSING
code, 102	error code, 153
ER_DA_UDF_INVALID_COLLATION error code, 103	ER_DD_TRG_DB_COLLATION_MISSING error code,
ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE	153
error code, 103	ER_DD_TRG_DEFINER_OOM error code, 153
ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET	ER_DD_TRG_FILE_UNREADABLE error code, 153
error code, 104	ER_DD_UPDATE_DATADIR_FLAG_FAIL error code,
ER_DA_UNKNOWN_ERROR_NUMBER error code,	415
99	ER_DD_UPDATING_PLUGIN_MD_FAILED error
ER_DBACCESS_DENIED_ERROR error code, 5	code, 141
ER_DEBUG_CHECK_SHARES_DROPPED error code,	ER_DD_UPGRADE error code, 205
171	ER_DD_UPGRADE_COMPLETED error code, 352
ER_DEBUG_CHECK_SHARES_INFO error code, 171	ER_DD_UPGRADE_DD_OPEN_FAILED error code,
ER_DEBUG_CHECK_SHARES_OPEN error code, 171	198
ER_DB_ACCESS_DENIED error code, 99	ER_DD_UPGRADE_DD_POPULATED error code, 199
ER_DB_CREATE_EXISTS error code, 4	ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR
ER_DB_DROP_EXISTS error code, 4	error code, 199
ER_DB_DROP_RMDIR error code, 4	ER_DD_UPGRADE_FAILED_INIT_DD_SE error code,
ER_DB_DROP_RMDIR2 error code, 79	199
ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET	ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE
error code, 183	error code, 198
ER_DDL_MSG_1 error code, 380	ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS
ER_DD_ABORTING_PARTIAL_UPGRADE error code,	error code, 199
162	ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS
ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN	error code, 199
error code, 141	ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES
ER_DD_CANT_CREATE_OBJECT_KEY error code,	error code, 199
142	

ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES error code, 198	ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC error code, 90
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE error code, 198	ER_DEFAULT_VAL_GENERATED_ROW_VALUE error code, 90
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE error code, 205	ER_DEFAULT_VAL_GENERATED_VARIABLES error code, 90
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED error code, 200	ER_DEFINITION_CONTAINS_INVALID_STRING error code, 115
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED error code, 200	ER_ENABLE_WITH_GRACE error code, 144
ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED error code, 199	ER_DEPENDENT_BY_CHECK_CONSTRAINT error code, 104
ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED error code, 199	ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE error code, 90
ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED error code, 199	ER_DEPENDENT_BY_FUNCTIONAL_INDEX error code, 96
ER_DD_UPGRADE_OFF error code, 205	ER_DEPENDENT_BY_GENERATED_COLUMN error code, 65
ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED error code, 198	ER_DEPENDENT_BY_PARTITION_FUNC error code, 97
ER_DD_UPGRADE_SCHEMA_UNAVAILABLE error code, 205	ER_DEPRECATED_NATIONAL error code, 86
ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED error code, 200	ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS error code, 379
ER_DD_UPGRADE_SE_LOGS_FAILED error code, 200	ER_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 204
ER_DD_UPGRADE_START error code, 199	ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT error code, 204
ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED error code, 199	ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS error code, 145
ER_DD_UPGRADE_TABLE_INTACT_ERROR error code, 203	ER_DEPRECATED_UTF8_ALIAS error code, 86
ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED error code, 199	ER_DEPRECATE_MSG_NO_REPLACEMENT error code, 204
ER_DD_UPGRADE_VERSION_NOT_SUPPORTED error code, 205	ER_DEPRECATE_MSG_WITH_REPLACEMENT error code, 193
ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG error code, 204	ER_DEPRECATE_NON_COMPOSABLE_MULTIPLE_ENGINE error code, 131
ER_DD_VERSION_FOUND error code, 140	ER_DERIVED_MUST_HAVE_ALIAS error code, 18
ER_DD_VERSION_INSTALLED error code, 140	ER_DES_FILE_WRONG_KEY error code, 154
ER_DD_VERSION_UNSUPPORTED error code, 140	ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN error code, 171
ER_DD_VIEW_CANT_ALLOC_CHARSET error code, 141	ER_DETACHING_SESSION_LEFT_BY_PLUGIN error code, 171
ER_DD_VIEW_CANT_CREATE error code, 141	ER_DIAG_LOG_STRING error code, 420
ER_DD_VIEW_WITHOUT_DEFINER error code, 153	ER_DIMENSION_UNSUPPORTED error code, 62
ER_DEBUG_SYNC_EXECUTED error code, 142	ER_DISABLED_STORAGE_ENGINE error code, 68
ER_DEBUG_SYNC_HIT error code, 142	ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT error code, 142
ER_DEBUG_SYNC_HIT_LIMIT error code, 40	ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT error code, 107
ER_DEBUG_SYNC_OOM error code, 142	ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT error code, 107
ER_DEBUG_SYNC_THREAD_MAX error code, 142	ER_DISALLOWED_OPERATION error code, 82
ER_DEBUG_SYNC_TIMEOUT error code, 40	ER_DISABLED_FK_CHECKS_RUNNING error code, 51
ER_DEFAULT_AS_VAL_GENERATED error code, 90	ER_DISCONNECTING_REMAINING_CLIENTS error code, 148
ER_DEFAULT_SE_UNAVAILABLE error code, 152	ER_DISK_FULL_NOWAIT error code, 83
ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED error code, 90	ER_DIVISION_BY_ZERO error code, 25
ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION error code, 90	
ER_DEFAULT_VAL_GENERATED_NON_PRIOR error code, 90	

ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY error code, 204	ER_ERRMSG_REPLACEMENTS_FAILED error code, 191
ER_DROP_FILEGROUP_FAILED error code, 35	ER_ERRMSG_REPLACEMENT_DODGY error code, 191
ER_DROP_INDEX_FK error code, 35	ER_ERROR_DURING_COMMIT error code, 14
ER_DROP_LAST_PARTITION error code, 33	ER_ERROR_DURING_FLUSH_LOGS error code, 14
ER_DROP_PARTITION_NON_EXISTENT error code, 33	ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE error code, 204
ER_DROP_PK_COLUMN_TO_DROP_GIPK error code, 116	ER_ERROR_DURING_OPTIMIZE_TABLE error code, 182
ER_DUPLICATED_VALUE_IN_TYPE error code, 21	ER_ERROR_DURING_ROLLBACK error code, 14
ER_DUPLICATE_OPTION_KEY error code, 76	ER_ERROR_ENABLING_KEYS error code, 182
ER_DUPLICATE_SYS_VAR error code, 337	ER_ERROR_INFO_FROM_DA error code, 334
ER_DUPLICATE_TABLE_LOCK error code, 76	ER_ERROR_IN_TRIGGER_BODY error code, 45
ER_DUP_ARGUMENT error code, 17	ER_ERROR_IN_UNKNOWN_TRIGGER_BODY error code, 45
ER_DUP_ENTRY error code, 7	ER_ERROR_LOG_DESTINATION_NOT_A_FILE error code, 370
ER_DUP_ENTRY_AUTOINCREMENT_CASE error code, 36	ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE error code, 70
ER_DUP_ENTRY_WITH_KEY_NAME error code, 37	ER_ERROR_ON_READ error code, 4
ER_DUP_FD_OPEN_FAILED error code, 194	ER_ERROR_ON_RENAME error code, 4
ER_DUP_FIELDNAME error code, 7	ER_ERROR_ON_SOURCE error code, 57
ER_DUP_INDEX error code, 53	ER_ERROR_ON_WRITE error code, 4
ER_DUP_KEY error code, 4	ER_ERROR_WHEN_EXECUTING_COMMAND error code, 17
ER_DUP_KEYNAME error code, 7	ER_ETAG_NOT_SUPPORTED error code, 139
ER_DUP_LIST_ENTRY error code, 59	ER_EVENT_ALREADY_EXISTS error code, 35
ER_DUP_SIGNAL_SET error code, 40	ER_EVENT_CANNOT ALTER IN THE PAST error code, 37
ER_DUP_UNIQUE error code, 14	ER_EVENT_CANNOT_CREATE IN THE PAST error code, 37
ER_DUP_UNKNOWN_IN_INDEX error code, 55	ER_EVENT_CANT_FIND_TIMEZONE error code, 183
ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE error code, 85	ER_EVENT_CANT_GET_CHARSET error code, 184
ER_EMPTY_PRIVILEGE_NAME_IGNORED error code, 370	ER_EVENT_CANT_GET_COLLATION error code, 184
ER_EMPTY_QUERY error code, 7	ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT error code, 185
ER_ENDING_INIT error code, 336	ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD error code, 183
ER_END_INITFILE error code, 149	ER_EVENT_CANT_INIT_QUEUE error code, 142
ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONE error code, 65	ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT error code, 184
ER_ENGINE_ATTRIBUTE_CONFLICT error code, 139	ER_EVENT_DOES_NOT_EXIST error code, 35
ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED error code, 106	ER_EVENT_DROPPING error code, 170
ER_ENGINE_CANNOT_BE_DEFAULT error code, 129	ER_EVENT_ENDS_BEFORE_STARTS error code, 35
ER_ENGINE_CANT_DROP_MISSING_TABLE error code, 79	ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BUFFER AND ERROR error code, 185
ER_ENGINE_CANT_DROP_TABLE error code, 79	ER_EVENT_ERROR_DURING_COMPILATION error code, 170
ER_ENGINE_COST_FAILED_TO_READ error code, 169	ER_EVENT_EXECUTION_FAILED error code, 143
ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SELECT error code, 169	ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER error code, 169
ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SELECT error code, 169	ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PRIVILEGES error code, 170
ER_ENGINE_COST_UNKNOWN_COST_CONSTANT error code, 168	ER_EVENT_EXEC_TIME_IN_THE_PAST error code, 35
ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE error code, 169	ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG error code, 35
ER_ENGINE_OUT_OF_MEMORY error code, 58	
ER_ERRMSG_CANT_FIND_FILE error code, 162	
ER_ERRMSG_CANT_READ error code, 163	
ER_ERRMSG_MISSING_IN_FILE error code, 162	
ER_ERRMSG_OOM error code, 163	

ER_EVENT_INVALID_CREATION_CTX error code, 38	ER_FAILED_TO_ALLOCATE_SSL_BIO error code, 336
ER_EVENT_LAST_EXECUTION error code, 143	ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER error code, 197
ER_EVENT_MESSAGE_STACK error code, 143	ER_FAILED_TO_BINLOG_DROP_EVENT error code, 200
ER_EVENT_PURGING_QUEUE error code, 143	ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES error code, 201
ER_EVENT_RECURSION_FORBIDDEN error code, 37	ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE error code, 166
ER_EVENT_SAME_NAME error code, 35	ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM error code, 166
ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT error code, 185	ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY error code, 200
ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB error code, 185	ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREADS error code, 166
ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE error code, 185	ER_FAILED_TO_CREATE_RPL_OPT_TRACKER_THREAD error code, 420
ER_EVENT_SET_VAR_ERROR error code, 36	ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE error code, 198
ER_EVENT_UNABLE_TO_DROP_EVENT error code, 185	ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS error code, 171
ER_EXCEEDED_MAX_REGULAR_STATEMENT_HANDLER error code, 131	ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE error code, 166
ER_EXCEEDED_MV_KEYS_NUM error code, 100	ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP error code, 196
ER_EXCEEDED_MV_KEYS_SPACE error code, 100	ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY error code, 103
ER_EXCEEDS_VECTOR_MAX_DIMENSIONS error code, 130	ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST error code, 103
ER_EXCEPTIONS_WRITE_ERROR error code, 39	ER_FAILED_TO_FIND_CHARSET_NAME error code, 427
ER_EXCESS_ARGUMENTS error code, 149	ER_FAILED_TO_FIND_COLLATION_NAME error code, 194
ER_EXPLAIN_ANALYZE_JSON_FORMAT_VERSION_NOT_SUPPORTED error code, 131	ER_FAILED_TO_FIND_DL_ENTRY error code, 191
ER_EXPLAIN_INT0_FORMAT_NOT_SUPPORTED error code, 121	ER_FAILED_TO_FIND_LOCALE_NAME error code, 194
ER_EXPLAIN_INT0_FOR_CONNECTION_NOT_SUPPORTED error code, 122	ER_FAILED_TO_FIND_MYSQLD_STATUS error code, 203
ER_EXPLAIN_INT0_IMPLICIT_FORMAT_NOT_SUPPORTED error code, 121	ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE error code, 192
ER_EXPLAIN_NOT_SUPPORTED error code, 58	ER_FAILED_TO_GET_ABSOLUTE_PATH error code, 194
ER_EXTERNAL_FORMAT_NOT_SUPPORTED error code, 139	ER_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 337
ER_EXTERNAL_TABLE_ENGINE_NOT_SPECIFIED error code, 139	ER_FAILED_TO_INIT_SYS_VAR error code, 337
ER_EXTERNAL_TABLE_ENGINE_NOT_SUPPORTED error code, 139	ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION error code, 166
ER_EXTERNAL_TABLE_INVALID_OPTION error code, 139	ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREADS error code, 166
ER_FAILED_DEFAULT_ROLES error code, 73	ER_FAILED_TO_LOCK_MEM error code, 149
ER_FAILED_GET_DD_PROPERTY error code, 402	ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES error code, 169
ER_FAILED_READ_FROM_PAR_FILE error code, 44	ER_FAILED_TO_OPEN_SHARED_LIBRARY error code, 191
ER_FAILED_REVOKE_ROLE error code, 74	ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA error code, 196
ER_FAILED_ROLE_GRANT error code, 73	ER_FAILED_TO_READ_FILE error code, 192
ER_FAILED_SET_DD_PROPERTY error code, 402	
ER_FAILED_START_MYSQLD_DAEMON error code, 195	
ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP error code, 197	
ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP error code, 197	
ER_FAILED_TO_ADD_RPL_FILTER error code, 201	
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP error code, 197	
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP error code, 197	

ER_FAILED_TO_REMOVE_TEMP_TABLE error code, 180	ER_FIREWALL_SCHEDULER_REGISTER_FAILED error code, 406
ER_FAILED_TO_REPAIR_TABLE error code, 180	ER_FIREWALL_SERVICES_NOT_ACQUIRED error code, 373
ER_FAILED_TO_SET_PERSISTED_OPTIONS error code, 204	ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE error code, 212
ER_FAILED_TO_START_REPLICA_THREAD error code, 200	ER_FIREWALL_STATUS_FLUSHED error code, 212
ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE error code, 199	ER_FIREWALL_SUSPICIOUS_STMT error code, 212
ER_FAILED_TO_UPDATE_RESOURCE_GROUP error code, 196	ER_FIREWALL_UDF_REGISTER_FAILED error code, 373
ER_FAILED_TO_VALIDATE_CERTIFICATES_SERVER error code, 404	ER_FIXING_CLIENT_CHARSET error code, 149
ER_FAILED_TO_WRITE_TO_FILE error code, 192	ER_FK_CANNOT_CHANGE_ENGINE error code, 91
ER_FAIL_CHROOT error code, 148	ER_FK_CANNOT_DROP_PARENT error code, 87
ER_FAIL_SETGID error code, 148	ER_FK_CANNOT_OPEN_PARENT error code, 53
ER_FAIL_SETREGID error code, 148	ER_FK_CANNOT_USE_VIRTUAL_COLUMN error code, 87
ER_FAIL_SETREUID error code, 148	ER_FK_COLUMN_CANNOT_CHANGE error code, 53
ER_FAIL_SETUID error code, 148	ER_FK_COLUMN_CANNOT_CHANGE_CHILD error code, 53
ER_FEATURE_DISABLED error code, 21	ER_FK_COLUMN_CANNOT_DROP error code, 53
ER_FEATURE_DISABLED_SEE_DOC error code, 69	ER_FK_COLUMN_CANNOT_DROP_CHILD error code, 53
ER_FEATURE_NOT_AVAILABLE error code, 65	ER_FK_COLUMN_NOT_NULL error code, 53
ER_FEATURE_UNSUPPORTED error code, 82	ER_FK_DEPTH_EXCEEDED error code, 57
ER_FIELD_IN_GROUPING_NOT_GROUP_BY error code, 79	ER_FK_DUP_NAME error code, 53
ER_FIELD_IN_ORDER_NOT_SELECT error code, 61	ER_FK_FAIL_ADD_SYSTEM error code, 52
ER_FIELD_NOT_FOUND_PART_ERROR error code, 32	ER_FK_INCOMPATIBLE_COLUMNS error code, 91
ER_FIELD_SPECIFIED_TWICE error code, 10	ER_FK_INCORRECT_OPTION error code, 53
ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD error code, 41	ER_FK_NO_COLUMN_PARENT error code, 87
ER_FILEGROUP_OPTION_ONLY_ONCE error code, 34	ER_FK_NO_INDEX_CHILD error code, 52
ER_FILE_CORRUPT error code, 57	ER_FK_NO_INDEX_PARENT error code, 52
ER_FILE_EXISTS_DURING_UPGRADE error code, 184	ER_FK_NO_UNIQUE_INDEX_PARENT error code, 129
ER_FILE_EXISTS_ERROR error code, 8	ER_FORBID_SCHEMA_CHANGE error code, 30
ER_FILE_HAS_OLD_FORMAT error code, 193	ER_FORCE_CLOSE_THREAD error code, 192
ER_FILE_NOT_FOUND error code, 4	ER_FORCING_CLOSE error code, 8
ER_FILE_TYPE_UNKNOWN error code, 163	ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST error code, 29
ER_FILE_USED error code, 5	ER_FOREIGN_DATA_STRING_INVALID error code, 29
ER_FIREWALL_ACCESS_DENIED error code, 212	ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE error code, 29
ER_FIREWALL_DEPRECATED_USER_PROFILE error code, 377	ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED error code, 36
ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES error code, 211	ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO error code, 48
ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES error code, 211	ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO error code, 48
ER_FIREWALL_INVALID_RELOAD_INTERVAL_VALUE error code, 406	ER_FOREIGN_KEY_ON_PARTITIONED error code, 33
ER_FIREWALL_PFS_TABLE_REGISTER_FAILED error code, 373	ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT error code, 106
ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED error code, 212	ER_FOREIGN_SERVER_DOESNT_EXIST error code, 32
ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT error code, 212	ER_FOREIGN_SERVER_EXISTS error code, 32
ER_FIREWALL_RELOADING_CACHE error code, 212	ER_FOUND_MISSING_GTIDS error code, 255
ER_FIREWALL_RESET_FOR_USER error code, 212	ER_FOUND_ROWS_WHILE_REPAIRING error code, 182

ER_FPARSER_BAD_HEADER error code, 24	ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER error code, 57
ER_FPARSER_EOF_IN_COMMENT error code, 24	ER_GET_TEMPORARY_ERRMSG error code, 21
ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER error code, 24	ER_GIPK_COLUMN_ALTER_NOT_ALLOWED error code, 116
ER_FPARSER_ERROR_IN_PARAMETER error code, 24	ER_GIPK_COLUMN_EXISTS error code, 116
ER_FPARSER_TOO_BIG_FILE error code, 24	ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS error code, 116
ER_FSEEK_FAIL error code, 26	ER_GIS_DATA_WRONG_ENDIANESS error code, 61
ER_FT_BOOL_SYNTAX_INVALID error code, 145	ER_GIS_DIFFERENT_SRIDS error code, 59
ER_FT_MATCHING_KEY_NOT_FOUND error code, 15	ER_GIS_DIFFERENT_SRIDS_AGGREGATION error code, 110
ER_FULLTEXT_FUNCTIONAL_INDEX error code, 89	ER_GIS_INVALID_DATA error code, 60
ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING error code, 48	ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED error code, 67
ER_FULLTEXT_WITH_ROLLUP error code, 114	ER_GIS_UNKNOWN_ERROR error code, 59
ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG error code, 100	ER_GIS_UNKNOWN_EXCEPTION error code, 59
ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED error code, 89	ER_GIS_UNSUPPORTED_ARGUMENT error code, 59
ER_FUNCTIONAL_INDEX_ON_FIELD error code, 90	ER_GLOBAL_CONN_LIMIT error code, 384
ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_ERROR error code, 89	ER_GLOBAL_VARIABLE error code, 17
ER_FUNCTIONAL_INDEX_ON_LOB error code, 89	ER_GLOBSTAT_CHANGE_DURING_QUERY error code, 101
ER_FUNCTIONAL_INDEX_PRIMARY_KEY error code, 89	ER_GNO_EXHAUSTED error code, 49
ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT error code, 89	ER_GRANT_WRONG_HOST_OR_USER error code, 12
ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED error code, 93	ER_GROUPING_ON_TIMESTAMP_IN_DST error code, 101
ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET error code, 107	ER_GROUP_REPLICATION_APPLIER_INIT_ERROR error code, 63
ER_FUNCTION_NOT_DEFINED error code, 11	ER_GROUP_REPLICATION_CERTIFICATION_MODULE_FAILURE error code, 410
ER_FUNC_INEXISTENT_NAME_COLLISION error code, 39	ER_GROUP_REPLICATION_CERTIFIER_MESSAGE_LARGE error code, 407
ER_FUTURE_DATE error code, 147	ER_GROUP_REPLICATION_COMMAND_FAILURE error code, 83
ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED error code, 64	ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR error code, 64
ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 90	ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR error code, 64
ER_GENERATED_COLUMN_NON_PRIOR error code, 65	ER_GROUP_REPLICATION_COMPRESS_EXCEEDS_MAX_SIZE error code, 407
ER_GENERATED_COLUMN_REF_AUTO_INC error code, 65	ER_GROUP_REPLICATION_COMPRESS_OUT_OF_MEMORY error code, 408
ER_GENERATED_COLUMN_ROW_VALUE error code, 90	ER_GROUP_REPLICATION_COMPRESS_PROCESS error code, 407
ER_GENERATED_COLUMN_VARIABLES error code, 90	ER_GROUP_REPLICATION_CONFIGURATION error code, 63
ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT error code, 99	ER_GROUP_REPLICATION_DECOMPRESS_CORRUPTED error code, 408
ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE error code, 87	ER_GROUP_REPLICATION_DECOMPRESS_END error code, 408
ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE error code, 87	ER_GROUP_REPLICATION_DECOMPRESS_EXCEEDS_MAX_SIZE error code, 408
ER_GET_ERRMSG error code, 21	ER_GROUP_REPLICATION_DECOMPRESS_OUT_OF_MEMORY error code, 408
ER_GET_ERRNO error code, 5	ER_GROUP_REPLICATION_DECOMPRESS_PROCESS error code, 408
ER_GET_ERRNO_FROM_STORAGE_ENGINE error code, 193	

ER_GROUP_REPLICATION_DECOMPRESS_TRUNCATED	ER_GROUP_REPLICATION_RECOVERY_FETCHING_GTID
error code, 408	error code, 410
ER_GROUP_REPLICATION_ERROR_COMPRESS_INITIALIZED	ER_GROUP_REPLICATION_RECOVERY_METADATA_SEND
error code, 407	error code, 410
ER_GROUP_REPLICATION_ERROR_DECOMPRESS_INITIALIZED	ER_GROUP_REPLICATION_RECOVERY_SKIPPED_GTID_PACKET
error code, 408	error code, 410
ER_GROUP_REPLICATION_ERROR_RECEIVED_WAITING_FOR_METADATA	ER_GROUP_REPLICATION_RECOVERY_STOPPED_GTID_PACKET
error code, 409	error code, 411
ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE	ER_GROUP_REPLICATION_RUNNING
error code, 117	error code, 63
ER_GROUP_REPLICATION_MAX_GROUP_SIZE	ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT
error code, 71	error code, 64
ER_GROUP_REPLICATION_METADATA_CERT_INFO_ENCODING_ERROR	ER_GROUP_REPLICATION_TIMEOUT_ERROR_FETCHING_PACKET
error code, 410	error code, 409
ER_GROUP_REPLICATION_METADATA_CERT_INFO_ERROR_PACKET	ER_GROUP_REPLICATION_UNKOWN_COMPRESSION_TYPE
error code, 409	error code, 407
ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_COUNT_ERROR	ER_GROUP_REPLICATION_USER_EMPTY_MSG
error code, 410	error code, 405
ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_EMPTY	ER_GROUP_REPLICATION_USER_MANDATORY_MSG
error code, 409	error code, 405
ER_GROUP_REPLICATION_METADATA_ERROR_ON_SEND_ERROR	ER_GRP_OPERATION_NOT_ALLOWED_GRP_MUST_STOP
error code, 410	error code, 404
ER_GROUP_REPLICATION_METADATA_INITIALIZATION_FAILURE	ER_GRP_PREFERS_MOST_UPDATED_CONFIG_DIFFER_ON_PRIMARY
error code, 410	error code, 422
ER_GROUP_REPLICATION_METADATA_MEMORY_ALLOCATION	ER_GRP_PRIMARY_ELECTION_FATAL_PROCESS
error code, 410	error code, 422
ER_GROUP_REPLICATION_METADATA_MESSAGE_PAYLOAD_EMPTY	ER_GRP_PRIMARY_ELECTION_METHOD_MEMBER_WEIGHT
error code, 409	error code, 422
ER_GROUP_REPLICATION_METADATA_NO_VALID_DONORS	ER_GRP_PRIMARY_ELECTION_METHOD_MOST_UPDATED
error code, 411	error code, 422
ER_GROUP_REPLICATION_METADATA_PAYLOAD_DECODING	ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQL
error code, 409	error code, 244
ER_GROUP_REPLICATION_METADATA_PAYLOAD_EMPTY	ER_GRP_RPL_ADD_GRP_SID_TO_GRP_GTID_SID_MAP_ERROR
error code, 409	error code, 228
ER_GROUP_REPLICATION_METADATA_PROTOBUF_PARSE	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_PACKET
error code, 408	error code, 236
ER_GROUP_REPLICATION_METADATA_READ_GTID_EXECUTE	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_PACKET
error code, 409	error code, 236
ER_GROUP_REPLICATION_METADATA_SAVE_RECOVERY	ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILURE
error code, 409	error code, 236
ER_GROUP_REPLICATION_METADATA_SENDER	ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILURE
error code, 407	error code, 236
ER_GROUP_REPLICATION_METADATA_SENDER_IS_REMOTE	ER_GRP_RPL_ADD_GTID_TO_GRP_GTID_EXECUTED_ERROR
error code, 407	error code, 229
ER_GROUP_REPLICATION_METADATA_SEND_ERROR	ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTE
error code, 409	error code, 229
ER_GROUP_REPLICATION_METADATA_SET_IN_RECOVERY	ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP
error code, 410	error code, 378
ER_GROUP_REPLICATION_NO_CERTIFICATION_DONORS_AVAILABLE	ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY
error code, 411	error code, 237
ER_GROUP_REPLICATION_PASSWORD_LENGTH	ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED
error code, 105	error code, 244
ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING
error code, 166	error code, 373
ER_GROUP_REPLICATION_PROTOBUF_SERIALIZING_ERROR	ER_GRP_RPL_APPLIER_ERROR_PACKET_RECEIVED
error code, 409	error code, 412
ER_GROUP_REPLICATION_RECOVERY_ERROR_ADD_GTID_TO_EXECUTED	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR
error code, 410	error code, 228

ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE error code, 246	ER_GRP_RPL_CANT_READ_GTID error code, 230
ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED error code, 246	ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM error code, 230
ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE error code, 246	ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE error code, 229
ER_GRP_RPL_APPLIER_INITIALIZED error code, 244	ER_GRP_RPL_CERTIFICATION_REC_PROCESS error code, 241
ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE error code, 245	ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR error code, 230
ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING error code, 244	ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED error code, 408
ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED error code, 228	ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED error code, 403
ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT error code, 243	ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED error code, 404
ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED error code, 228	ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED error code, 231
ER_GRP_RPL_APPLIER_THD_KILLED error code, 227	ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING error code, 338
ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL error code, 403	ER_GRP_RPL_CHECK_STATUS_TABLE error code, 238
ER_GRP_RPL_APPLIER_THD_SETUP_ERROR error code, 234	ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR error code, 355
ER_GRP_RPL_APPLIER_THD_START_ERROR error code, 234	ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR error code, 355
ER_GRP_RPL_APPLIER_THD_STOP_ERROR error code, 234	ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO error code, 244
ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT error code, 338	ER_GRP_RPL_CONFIGURATION_ACTION_END error code, 339
ER_GRP_RPL_AUTO_INC_OFFSET_RESET error code, 235	ER_GRP_RPL_CONFIGURATION_ACTION_ERROR error code, 339
ER_GRP_RPL_AUTO_INC_OFFSET_SET error code, 235	ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR error code, 339
ER_GRP_RPL_AUTO_INC_RESET error code, 235	ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION error code, 339
ER_GRP_RPL_AUTO_INC_SET error code, 235	ER_GRP_RPL_CONFIGURATION_ACTION_START error code, 339
ER_GRP_RPL_BINLOG_DISABLED error code, 245	ER_GRP_RPL_CONFIG_RECOVERY error code, 237
ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP error code, 233	ER_GRP_RPL_CONFLICT_DETECTION_DISABLED error code, 230
ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED error code, 240	ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE error code, 245
ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG error code, 249	ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL error code, 236
ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED error code, 228	ER_GRP_RPL_CONN_KILLED error code, 404
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR mode error code, 239	ER_GRP_RPL_COPY_FROM_EMPTY_STRING error code, 237
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE mode error code, 239	ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR error code, 228
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING error code, 239	ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL error code, 238
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING error code, 239	ER_GRP_RPL_CREATE_SESSION_UNABLE error code, 237
ER_GRP_RPL_CANT_GENERATE_GTID error code, 229	ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM error code, 233
ER_GRP_RPL_CANT_KILL_THREAD error code, 356	ER_GRP_RPL_DEBUG_OPTIONS error code, 248
ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED error code, 230	ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP error code, 350

ER_GRP_RPL_DISABLE_READ_ONLY_FAILED error code, 232	ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_G error code, 242
ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED error code, 231	ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT error code, 240
ER_GRP_RPL_DONOR_CONN_TERMINATION error code, 238	ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_C error code, 243
ER_GRP_RPL_DONOR_SERVER_CONN error code, 238	ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY error code, 241
ER_GRP_RPL_DONOR_TRANS_INFO_ERROR error code, 229	ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET error code, 240
ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR error code, 378	ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET error code, 240
ER_GRP_RPL_ENABLE_READ_ONLY_FAILED error code, 232	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP error code, 244
ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED error code, 229	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW error code, 378
ER_GRP_RPL_ERROR_FETCHING_GTID_SET error code, 229	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER error code, 246
ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO error code, 228	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE error code, 244
ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION error code, 338	ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE error code, 241
ER_GRP_RPL_ERROR_MSG error code, 216	ER_GRP_RPL_FAILED_TO_INIT_HANDLER error code, 243
ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL error code, 346	ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFT error code, 345
ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING error code, 338	ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE error code, 390
ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSG error code, 228	ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EV error code, 238
ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER error code, 384	ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME error code, 244
ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER error code, 383	ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_U error code, 378
ER_GRP_RPL_ERROR_STOPPING_CHANNELS error code, 228	ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OB error code, 248
ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT error code, 240	ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_O error code, 243
ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR error code, 238	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME error code, 240
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER error code, 237	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB error code, 243
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR error code, 237	ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR error code, 239
ER_GRP_RPL_EVENT_HANDLING_ERROR error code, 227	ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODU error code, 243
ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE error code, 232	ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_EN error code, 242
ER_GRP_RPL_EXIT_GRP_GCS_ERROR error code, 248	ER_GRP_RPL_FAILED_TO_START_ON_BOOT error code, 248
ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLER error code, 246	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH error code, 242
ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP error code, 238	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER error code, 241
ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS error code, 239	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL error code, 248
ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION error code, 242	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE error code, 244

ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE error code, 244	ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR error code, 248
ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE error code, 244	ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT error code, 249
ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION error code, 112	ER_GRP_RPL_GCS_GR_ERROR_MSG error code, 249
ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST error code, 380	ER_GRP_RPL_GCS_INTERFACE_ERROR error code, 248
ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION error code, 380	ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION error code, 248
ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA error code, 380	ER_GRP_RPL_GROUP_NAME_PARSE_ERROR error code, 228
ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_ERROR error code, 380	ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID error code, 377
ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DETAILED_CONFIGURATION error code, 380	ER_GRP_RPL_GROUP_COMMUNICATION_ENG_INIT_FAILED error code, 248
ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY error code, 381	ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF error code, 246
ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY error code, 381	ER_GRP_RPL_GRP_MEMBER_OFFLINE error code, 248
ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_ERROR error code, 381	ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID error code, 245
ER_GRP_RPL_FATAL_REC_PROCESS error code, 240	ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GROUP error code, 372
ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED error code, 235	ER_GRP_RPL_GRP_NAME_IS_TOO_LONG error code, 245
ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED error code, 236	ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY error code, 245
ER_GRP_RPL_FETCH_LOG_EVENT_FAILED error code, 236	ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE error code, 377
ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED error code, 235	ER_GRP_RPL_GTID_ALREADY_USED error code, 227
ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED error code, 235	ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR error code, 233
ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED error code, 235	ER_GRP_RPL_GTID_MODE_OFF error code, 245
ER_GRP_RPL_FETCH_TRANS_DATA_FAILED error code, 234	ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR error code, 355
ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED error code, 236	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR error code, 233
ER_GRP_RPL_FINISHED_AUTO_REJOIN error code, 350	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY error code, 346
ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED error code, 235	ER_GRP_RPL_HAS_STARTED error code, 399
ER_GRP_RPL_FLOW_CONTROL_STATS error code, 249	ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE error code, 230
ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN error code, 246	ER_GRP_RPL_INTERNAL_QUERY error code, 237
ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX error code, 245	ER_GRP_RPL_INVALID_BINLOG_FORMAT error code, 299
ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX error code, 246	ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL error code, 350
ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY error code, 241	ER_GRP_RPL_INVALID_DEBUG_OPTIONS error code, 248
ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING error code, 347	ER_GRP_RPL_INVALID_GTID_SET error code, 229
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET error code, 248	ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING error code, 246
	ER_GRP_RPL_IS_STARTING error code, 364
	ER_GRP_RPL_IS_STOPPED error code, 243
	ER_GRP_RPL_IS_STOPPING error code, 243

ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING error code, 338	ER_GRP_RPL_MEMBER_NOT_FOUND error code, 237
ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING error code, 338	ER_GRP_RPL_MEMBER_REMOVED error code, 231
ER_GRP_RPL_KILLED_FAILED_ID error code, 237	ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE error code, 242
ER_GRP_RPL_KILLED_SESSION_ID error code, 237	ER_GRP_RPL_MEMBER_STATS_INFO error code, 249
ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR error code, 233	ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR error code, 234
ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET error code, 245	ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP_MEMBER error code, 233
ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP error code, 331	ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE error code, 233
ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED error code, 237	ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE error code, 353
ER_GRP_RPL_MEMBER_ACTIONS_RESET error code, 377	ER_GRP_RPL_MEM_ONLINE error code, 231
ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION error code, 376	ER_GRP_RPL_MEM_REACHABLE error code, 231
ER_GRP_RPL_MEMBER_ACTION_DISABLED error code, 376	ER_GRP_RPL_MEM_UNREACHABLE error code, 231
ER_GRP_RPL_MEMBER_ACTION_ENABLED error code, 376	ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR error code, 357
ER_GRP_RPL_MEMBER_ACTION_FAILURE error code, 375	ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE error code, 101
ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE error code, 375	ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR error code, 338
ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE error code, 376	ER_GRP_RPL_MISSING_GRP_RPL_APPLIER error code, 230
ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER error code, 376	ER_GRP_RPL_MODULE_TERMINATE_ERROR error code, 245
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN error code, 376	ER_GRP_RPL_MSG_DECODING_FAILED error code, 412
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVER error code, 376	ER_GRP_RPL_MSG_DISCARDED error code, 230
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED error code, 375	ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS error code, 240
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT error code, 376	ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED error code, 239
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS error code, 376	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR error code, 380
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER error code, 376	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR error code, 380
ER_GRP_RPL_MEMBER_ADDED error code, 231	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_SERVER_ERROR error code, 380
ER_GRP_RPL_MEMBER_ALREADY_EXISTS error code, 233	ER_GRP_RPL_NO_JOIN error code, 246
ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP error code, 234	ER_GRP_RPL_NEEDS_INNO_DB_TABLE error code, 235
ER_GRP_RPL_MEMBER_CHANGE error code, 232	ER_GRP_RPL_NEW_PRIMARY_ELECTED error code, 232
ER_GRP_RPL_MEMBER_CONF_INFO error code, 242	ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED error code, 236
ER_GRP_RPL_MEMBER_CONTACT_RESTORED error code, 231	ER_GRP_RPL_NO_POSSIBLE_RECOVERY error code, 356
ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR error code, 232	ER_GRP_RPL_NO_STAGE_SERVICE error code, 339
ER_GRP_RPL_MEMBER_EXPELLED error code, 232	ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM error code, 232
ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST error code, 403	ER_GRP_RPL_NO_VALID_DONOR error code, 237
ER_GRP_RPL_MEMBER_LEFT_GRP error code, 232	ER_GRP_RPL_NULL_PACKET error code, 230
	ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE error code, 240
	ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION error code, 239

ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_ERROR error code, 384	ER_GRP_RPL_RECOVERY_STRAT_FALLBACK error code, 356
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_ERROR error code, 397	ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK error code, 356
ER_GRP_RPL_PIPELINE_CREATE_FAILED error code, 249	ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_FINISH error code, 415
ER_GRP_RPL_PIPELINE_FLUSH_FAIL error code, 249	ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_START error code, 415
ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ error code, 249	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES error code, 345
ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE error code, 249	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE error code, 345
ER_GRP_RPL_PLUGIN_ABORT error code, 336	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_ON_COMMIT_START error code, 345
ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE error code, 241	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES error code, 345
ER_GRP_RPL_PREEMPTIVE_GARBAGE_COLLECTION error code, 414	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC error code, 346
ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR error code, 339	ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE error code, 345
ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR error code, 339	ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT error code, 250
ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED error code, 235	ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED error code, 250
ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP error code, 231	ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN error code, 234
ER_GRP_RPL_PROCESS_GTID_SET_ERROR error code, 230	ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT error code, 250
ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR error code, 230	ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED error code, 249
ER_GRP_RPL_PURGE_APPLIER_LOGS error code, 234	ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SUPPORTED error code, 245
ER_GRP_RPL_PURGE_REC error code, 238	ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER_READ_ONLY error code, 235
ER_GRP_RPL_QUERY_FAIL error code, 237	ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN error code, 235
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SECONDARY error code, 241	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE error code, 356
ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS error code, 230	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER error code, 381
ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING error code, 110	ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE error code, 242
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 365	ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR error code, 234
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_ERROR error code, 365	ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER_READ_ONLY error code, 234
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 365	ER_GRP_RPL_SEND_STATS_ERROR error code, 249
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR error code, 365	ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED error code, 340
ER_GRP_RPL_RECOVERY_EVAL_ERROR error code, 355	ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED error code, 346
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMEOUT error code, 243	ER_GRP_RPL_SERVER_ALREADY_LEFT error code, 242
ER_GRP_RPL_RECOVERY_STRAT_CHOICE error code, 356	ER_GRP_RPL_SERVER_CONN_ERROR error code, 242
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED error code, 356	ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING error code, 242
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD error code, 356	

ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DURATION_ERROR error code, 357	ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR error code, 232
ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DURATION_ERROR error code, 248	ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP error code, 242
ER_GRP_RPL_SERVER_UDF_ERROR error code, 339	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN error code, 369
ER_GRP_RPL_SESSION_OPEN_FAILED error code, 232	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN error code, 350
ER_GRP_RPL_SET_GRP_COMMUNICATION_ENGINE_LOGGING_ERROR error code, 248	ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON error code, 242
ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER error code, 383	ER_GRP_RPL_TRANS_GREATER_THAN_GRP error code, 233
ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER error code, 383	ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP error code, 233
ER_GRP_RPL_SET_STABLE_TRANS_ERROR error code, 230	ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT error code, 240
ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_ERROR error code, 245	ER_GRP_RPL_UPDATE_TABLES_WHERE error code, 234
ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED error code, 247	ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER error code, 345
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECONDARY error code, 247	ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLER error code, 345
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION error code, 247	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED error code, 346
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY error code, 247	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED error code, 345
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER error code, 247	ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION error code, 346
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION error code, 247	ER_GRP_RPL_UDF_REGISTER_ERROR error code, 101
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED error code, 247	ER_GRP_RPL_UDF_REGISTER_ERROR error code, 101
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN error code, 247	ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR error code, 339
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE error code, 247	ER_GRP_RPL_UDF_UNREGISTER_ERROR error code, 339
ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED error code, 247	ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS error code, 241
ER_GRP_RPL_SRV_BLOCKED error code, 231	ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET error code, 249
ER_GRP_RPL_SRV_BLOCKED_FOR_SECS error code, 231	ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT error code, 249
ER_GRP_RPL_SRV_NOT_ONLINE error code, 231	ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_RECORD error code, 241
ER_GRP_RPL_SRV_ONLINE error code, 231	ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS error code, 240
ER_GRP_RPL_SRV_PRIMARY_MEM error code, 232	ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE error code, 245
ER_GRP_RPL_SRV_SECONDARY_MEM error code, 232	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER error code, 238
ER_GRP_RPL_SSL_DISABLED error code, 244	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILED error code, 238
ER_GRP_RPL_STARTED_AUTO_REJOIN error code, 350	ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE error code, 241
ER_GRP_RPL_STARTING_GRP_REC error code, 238	ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS error code, 241
ER_GRP_RPL_START_FAILED error code, 233	ER_GRP_RPL_UNBLOCK_WAITING_THD error code, 228
ER_GRP_RPL_START_GRP_RPL_FAILED error code, 236	
ER_GRP_RPL_STOPPING_GRP_REC error code, 238	
ER_GRP_RPL_SUPER_READ_OFF error code, 237	
ER_GRP_RPL_SUPER_READ_ON error code, 236	

ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED	ER_GR_RM_CHANNEL_LAG_QUERY_EXECUTION_SUCCESS error code, 421
error code, 246	ER_GR_MEMBER_NOT_REMOVED_APPLIER_THRESHOLD error code, 421
ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT error code, 248	ER_GR_MEMBER_NOT_REMOVED_APPLIER_THRESHOLD error code, 421
ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION error code, 239	ER_GR_RM_GR_MEMBER_NOT_REMOVED_APPLIER_THRESHOLD error code, 421
ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR error code, 228	ER_GR_RM_GR_MEMBER_NOT_REMOVED_MEMORY_THRESHOLD error code, 422
ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EXCEEDED error code, 378	ER_GR_RM_GR_MEMBER_NOT_REMOVED_MEMORY_THRESHOLD error code, 421
ER_GRP_RPL_UPDATE_GTID_SET_ERROR error code, 229	ER_GR_RM_GR_MEMBER_NOT_REMOVED_RECOVERY_THRESHOLD error code, 421
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION FROM error code, 229	ER_GR_RM_GR_MEMBER_NOT_REMOVED_RECOVERY_THRESHOLD error code, 421
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED error code, 236	ER_GR_RM_GR_MGMT_SERVICE_ACQUIRE_FAILED error code, 421
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERIFY ERROR error code, 229	ER_GRORM_MEMBER_LEAVING_APPLIER_THRESHOLD_HIT error code, 422
ER_GRP_RPL_VCLE_NOT_BEING_LOGGED error code, 408	ER_GR_RM_MEMBER_LEAVING_MEMORY_THRESHOLD_HIT error code, 422
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRPGR error code, 377	ER_GR_RM_MEMBER_LEAVING_RECOVERY_THRESHOLD_HIT error code, 422
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE error code, 111	ER_GR_RM_MEMORY_STATS_FETCH_FAILED error code, 420
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID error code, 377	ER_GR_RM_MEMORY_STATS_FETCH_SUCCESS error code, 420
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER UUID error code, 377	ER_GROUSLEADY_ADDED_BY_USER error code, 166
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR error code, 378	ER_GTID_EXECUTED_WAS_CHANGED error code, 54
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP NAME error code, 377	ER_NAME_EXECUTED_WAS_UPDATED error code, 193
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE error code, 242	ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME error code, 50
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED error code, 345	ER_GTID_MODE_OFF error code, 61
ER_GRP_RPL_WHILE_SENDING_MSG_REC error code, 241	ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 49
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING error code, 239	ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_EMPTY error code, 49
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED error code, 240	ER_GTID_NEXT_TAG_GTID_MODE_OFF error code, 124
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN error code, 92	ER_GTID_NEXT_TYPE_UNDEFINED_GTID error code, 53
ER_GRP_TRX_CONSISTENCY_BEFORE error code, 92	ER_GTID_PURGED_WAS_CHANGED error code, 54
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED error code, 93	ER_GTID_PURGED_WAS_UPDATED error code, 193
ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED error code, 92	ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 91
ER_GR_ELECTED_PRIMARY_GTID_INFORMATION error code, 360	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_A error code, 57
ER_GR_HOLD_KILLED error code, 91	ER_GTID_UNSAFE_CREATE_SELECT error code, 50
ER_GR_HOLD_MEMBER_STATUS_ERROR error code, 91	ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE error code, 50
ER_GR_HOLD_WAIT_TIMEOUT error code, 91	ER_HANDLERTON_OOM error code, 156
ER_GR_RM_CHANNEL_LAG_QUERY_EXECUTION_FAILED error code, 421	ER_HANDSHAKE_ERROR error code, 5
	ER_HEALTH_ERROR error code, 372
	ER_HEALTH_INFO error code, 372
	ER_HEALTH_WARNING error code, 372

ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1 error code, 372	ER_IB_DUPLICATE_KEY error code, 394
ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2 error code, 373	ER_IB_ERR_ACCESSING_OUT_OF_BOUND_FIELD_IN_INDEX error code, 325
ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3 error code, 373	ER_IB_ERR_CORRUPT_TABLESPACE_UNRECOVERABLE error code, 411
ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1 error code, 383	ER_IB_ERR_DDL_LOG_INSERT_FAILURE error code, 366
ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2 error code, 383	ER_IB_ERR_FOUND_N_DUPLICATE_KEYS error code, 368
ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3 error code, 383	ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER error code, 369
ER_HOSTNAME error code, 31	ER_IB_ERR_INDEX_DUPLICATE_KEY error code, 368
ER_HOSTNAME_DOESNT_RESOLVE_TO error code, 144	ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER error code, 368
ER_HOSTNAME_RESEMBLES_IPV4 error code, 143	ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW error code, 368
ER_HOSTNAME_TOO_LONG error code, 105	ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER error code, 368
ER_HOSTNAME_TRUNCATED error code, 366	ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED error code, 379
ER_HOST_IS_BLOCKED error code, 11	ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUFFER error code, 364
ER_HOST_NOT_PRIVILEGED error code, 11	ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT error code, 364
ER_HYPERGRAPH_NOT_SUPPORTED_YET error code, 108	ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED error code, 364
ER_IB_BUFFER_POOL_FULL error code, 394	ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN error code, 261
ER_IB_BUFFER_POOL_OVERUSE error code, 394	ER_IB_ERR_PARALLEL_READ_OOM error code, 369
ER_IB_BULK_FLUSHER_INFO error code, 394	ER_IB_ERR_RECOVERY_REDO_DISABLED error code, 365
ER_IB_BULK_FLUSHER_PUNCH_HOLE error code, 404	ER_IB_ERR_SCHED_SETAFFINITY_FAILED error code, 367
ER_IB_BULK_LOAD_MERGE_FAIL error code, 396	ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON error code, 367
ER_IB_BULK_LOAD_STATS_INFO error code, 416	ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST error code, 367
ER_IB_BULK_LOAD_STATS_WARN error code, 411	ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY error code, 367
ER_IB_BULK_LOAD_SUBTREE_INFO error code, 394	ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATA error code, 367
ER_IB_BULK_LOAD_THREAD_FAIL error code, 396	ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE error code, 367
ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES error code, 366	ER_IB_ERR_ZLIB_BUF_ERROR error code, 368
ER_IB_CLONE_GTID_PERSIST error code, 265	ER_IB_ERR_ZLIB_DATA_ERROR error code, 368
ER_IB_CLONE_INTERNAL error code, 264	ER_IB_ERR_ZLIB_MEM_ERROR error code, 368
ER_IB_CLONE_NON_INNOODB_TABLE error code, 355	ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED error code, 368
ER_IB_CLONE_OPERATION error code, 355	ER_IB_ERR_ZLIB_UNKNOWN_ERROR error code, 368
ER_IB_CLONE_PUNCH_HOLE error code, 265	ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE error code, 367
ER_IB_CLONE_RESTART error code, 355	ER_IB_FIXED_PAGE_ID error code, 407
ER_IB_CLONE_SQL error code, 265	ER_IB_HIDDEN_NAME_CONFLICT error code, 397
ER_IB_CLONE_START_STOP error code, 355	ER_IB_IMPORT_INDEX_METADATA_READ_FAILED error code, 311
ER_IB_CLONE_STATUS_FILE error code, 265	ER_IB_IMPORT_START_CFG_NAME error code, 315
ER_IB_CLONE_TIMEOUT error code, 265	
ER_IB_CLONE_USER_DATA error code, 355	
ER_IB_CLONE_VALIDATE error code, 265	
ER_IB_DBLWR_BYTES_INFO error code, 386	
ER_IB_DBLWR_DECOMPRESS_FAILED error code, 370	
ER_IB_DBLWR_DECRYPT_FAILED error code, 370	
ER_IB_DBLWR_KEY_MISSING error code, 370	
ER_IB_DDL_CONVERT_HEAP_NOT_FOUND error code, 402	
ER_IB_DELETE_SCHEMA_DIR error code, 417	
ER_IB_DICT_INVALID_COLUMN_POSITION error code, 397	
ER_IB_DICT_LOG_TABLE_INFO error code, 397	

ER_IB_INDEX_BUILDER_DONE error code, 398	ER_IB_MSG_1030 error code, 316
ER_IB_INDEX_BUILDER_INIT error code, 398	ER_IB_MSG_1031 error code, 316
ER_IB_INDEX_LOADER_DONE error code, 398	ER_IB_MSG_1032 error code, 316
ER_IB_INDEX_LOG_VERSION_MISMATCH error code, 398	ER_IB_MSG_1033 error code, 316
ER_IB_INDEX_PART_TOO_LONG error code, 403	ER_IB_MSG_1034 error code, 316
ER_IB_INNOODB_TBSP_OUT_OF_SPACE error code, 373	ER_IB_MSG_1035 error code, 316
ER_IB_INSERT_DELETE_SCHEMA_DIRECTORY_DDL error code, 417	ER_IB_MSG_1036 error code, 316
ER_IB_INSTANT_ADD_DROP_COLUMN_NOT_ALLOWED error code, 404	ER_IB_MSG_1037 error code, 316
ER_IB_INSTANT_ADD_NOT_POSSIBLE error code, 404	ER_IB_MSG_1038 error code, 316
ER_IB_LOAD_BULK_CONCURRENCY_REDUCED error code, 396	ER_IB_MSG_1039 error code, 316
ER_IB_LOB_ROLLBACK_INDEX_LEN error code, 359	ER_IB_MSG_104 error code, 262
ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION error code, 366	ER_IB_MSG_1040 error code, 316
ER_IB_LONG_AHI_DISABLE_WAIT error code, 266	ER_IB_MSG_1041 error code, 317
ER_IB_LONG_ROLLBACK error code, 414	ER_IB_MSG_1042 error code, 317
ER_IB_LONG_ROLLBACK_FULL error code, 414	ER_IB_MSG_1043 error code, 317
ER_IB_MSG_0 error code, 256	ER_IB_MSG_1044 error code, 317
ER_IB_MSG_1 error code, 256	ER_IB_MSG_1045 error code, 317
ER_IB_MSG_10 error code, 257	ER_IB_MSG_1046 error code, 317
ER_IB_MSG_100 error code, 262	ER_IB_MSG_1047 error code, 317
ER_IB_MSG_1000 error code, 314	ER_IB_MSG_1048 error code, 317
ER_IB_MSG_1001 error code, 314	ER_IB_MSG_1049 error code, 317
ER_IB_MSG_1002 error code, 314	ER_IB_MSG_105 error code, 262
ER_IB_MSG_1003 error code, 314	ER_IB_MSG_1051 error code, 317
ER_IB_MSG_1004 error code, 314	ER_IB_MSG_1052 error code, 317
ER_IB_MSG_1005 error code, 314	ER_IB_MSG_1053 error code, 317
ER_IB_MSG_1006 error code, 314	ER_IB_MSG_1054 error code, 317
ER_IB_MSG_1007 error code, 314	ER_IB_MSG_1055 error code, 317
ER_IB_MSG_1008 error code, 314	ER_IB_MSG_1056 error code, 317
ER_IB_MSG_1009 error code, 315	ER_IB_MSG_1057 error code, 317
ER_IB_MSG_101 error code, 262	ER_IB_MSG_1058 error code, 318
ER_IB_MSG_1010 error code, 315	ER_IB_MSG_1059 error code, 318
ER_IB_MSG_1011 error code, 315	ER_IB_MSG_106 error code, 262
ER_IB_MSG_1012 error code, 315	ER_IB_MSG_1060 error code, 318
ER_IB_MSG_1013 error code, 315	ER_IB_MSG_1065 error code, 318
ER_IB_MSG_1015 error code, 315	ER_IB_MSG_107 error code, 262
ER_IB_MSG_1016 error code, 315	ER_IB_MSG_1070 error code, 318
ER_IB_MSG_1017 error code, 315	ER_IB_MSG_1071 error code, 318
ER_IB_MSG_1018 error code, 315	ER_IB_MSG_1072 error code, 318
ER_IB_MSG_1019 error code, 315	ER_IB_MSG_1073 error code, 318
ER_IB_MSG_102 error code, 262	ER_IB_MSG_1074 error code, 319
ER_IB_MSG_1020 error code, 315	ER_IB_MSG_1075 error code, 319
ER_IB_MSG_1021 error code, 315	ER_IB_MSG_1076 error code, 319
ER_IB_MSG_1022 error code, 315	ER_IB_MSG_1077 error code, 319
ER_IB_MSG_1023 error code, 315	ER_IB_MSG_1078 error code, 319
ER_IB_MSG_1024 error code, 315	ER_IB_MSG_1079 error code, 319
ER_IB_MSG_1025 error code, 316	ER_IB_MSG_108 error code, 262
ER_IB_MSG_1026 error code, 316	ER_IB_MSG_1080 error code, 319
ER_IB_MSG_1027 error code, 316	ER_IB_MSG_1081 error code, 319
ER_IB_MSG_1028 error code, 316	ER_IB_MSG_1082 error code, 319
ER_IB_MSG_1029 error code, 316	ER_IB_MSG_1083 error code, 319
ER_IB_MSG_103 error code, 262	ER_IB_MSG_1086 error code, 319
	ER_IB_MSG_1087 error code, 319
	ER_IB_MSG_1088 error code, 319
	ER_IB_MSG_1089 error code, 319
	ER_IB_MSG_109 error code, 262
	ER_IB_MSG_1090 error code, 320
	ER_IB_MSG_1091 error code, 320
	ER_IB_MSG_1092 error code, 320

ER_IB_MSG_1229 error code, 328
ER_IB_MSG_123 error code, 263
ER_IB_MSG_1231 error code, 328
ER_IB_MSG_1233 error code, 328
ER_IB_MSG_1235 error code, 328
ER_IB_MSG_1238 error code, 328
ER_IB_MSG_1239 error code, 328
ER_IB_MSG_124 error code, 263
ER_IB_MSG_1241 error code, 329
ER_IB_MSG_1245 error code, 329
ER_IB_MSG_1246 error code, 329
ER_IB_MSG_1247 error code, 329
ER_IB_MSG_1248 error code, 329
ER_IB_MSG_1249 error code, 329
ER_IB_MSG_125 error code, 263
ER_IB_MSG_1250 error code, 329
ER_IB_MSG_1251 error code, 329
ER_IB_MSG_1253 error code, 329
ER_IB_MSG_1255 error code, 329
ER_IB_MSG_1256 error code, 329
ER_IB_MSG_1257 error code, 329
ER_IB_MSG_1258 error code, 330
ER_IB_MSG_1259 error code, 330
ER_IB_MSG_126 error code, 263
ER_IB_MSG_1260 error code, 330
ER_IB_MSG_1261 error code, 330
ER_IB_MSG_1262 error code, 330
ER_IB_MSG_1263 error code, 330
ER_IB_MSG_1266 error code, 330
ER_IB_MSG_1268 error code, 330
ER_IB_MSG_1269 error code, 330
ER_IB_MSG_127 error code, 263
ER_IB_MSG_1272 error code, 336
ER_IB_MSG_1273 error code, 336
ER_IB_MSG_1274 error code, 337
ER_IB_MSG_1275 error code, 337
ER_IB_MSG_1277 error code, 337
ER_IB_MSG_128 error code, 263
ER_IB_MSG_1280 error code, 337
ER_IB_MSG_1281 error code, 337
ER_IB_MSG_1282 error code, 337
ER_IB_MSG_1283 error code, 338
ER_IB_MSG_1284 error code, 338
ER_IB_MSG_1285 error code, 353
ER_IB_MSG_129 error code, 263
ER_IB_MSG_13 error code, 257
ER_IB_MSG_130 error code, 263
ER_IB_MSG_131 error code, 263
ER_IB_MSG_132 error code, 263
ER_IB_MSG_133 error code, 263
ER_IB_MSG_134 error code, 264
ER_IB_MSG_135 error code, 264
ER_IB_MSG_1357 error code, 367
ER_IB_MSG_1358 error code, 367
ER_IB_MSG_1359 error code, 367
ER_IB_MSG_136 error code, 264
ER_IB_MSG_137 error code, 264
ER_IB_MSG_1372 error code, 368

ER_IB_MSG_1373 error code, 368
ER_IB_MSG_1374 error code, 368
ER_IB_MSG_1375 error code, 368
ER_IB_MSG_138 error code, 264
ER_IB_MSG_1381 error code, 368
ER_IB_MSG_139 error code, 264
ER_IB_MSG_14 error code, 257
ER_IB_MSG_140 error code, 264
ER_IB_MSG_141 error code, 264
ER_IB_MSG_142 error code, 264
ER_IB_MSG_143 error code, 264
ER_IB_MSG_144 error code, 264
ER_IB_MSG_145 error code, 264
ER_IB_MSG_146 error code, 264
ER_IB_MSG_147 error code, 264
ER_IB_MSG_148 error code, 264
ER_IB_MSG_15 error code, 257
ER_IB_MSG_156 error code, 265
ER_IB_MSG_157 error code, 265
ER_IB_MSG_158 error code, 265
ER_IB_MSG_159 error code, 265
ER_IB_MSG_16 error code, 257
ER_IB_MSG_160 error code, 265
ER_IB_MSG_161 error code, 265
ER_IB_MSG_162 error code, 265
ER_IB_MSG_163 error code, 265
ER_IB_MSG_164 error code, 265
ER_IB_MSG_165 error code, 265
ER_IB_MSG_166 error code, 266
ER_IB_MSG_167 error code, 266
ER_IB_MSG_168 error code, 266
ER_IB_MSG_169 error code, 266
ER_IB_MSG_17 error code, 257
ER_IB_MSG_170 error code, 266
ER_IB_MSG_171 error code, 266
ER_IB_MSG_172 error code, 266
ER_IB_MSG_173 error code, 266
ER_IB_MSG_174 error code, 266
ER_IB_MSG_175 error code, 266
ER_IB_MSG_177 error code, 266
ER_IB_MSG_178 error code, 266
ER_IB_MSG_179 error code, 266
ER_IB_MSG_18 error code, 257
ER_IB_MSG_180 error code, 266
ER_IB_MSG_182 error code, 266
ER_IB_MSG_183 error code, 267
ER_IB_MSG_184 error code, 267
ER_IB_MSG_187 error code, 267
ER_IB_MSG_188 error code, 267
ER_IB_MSG_189 error code, 267
ER_IB_MSG_19 error code, 257
ER_IB_MSG_190 error code, 267
ER_IB_MSG_191 error code, 267
ER_IB_MSG_192 error code, 267
ER_IB_MSG_193 error code, 267
ER_IB_MSG_194 error code, 267
ER_IB_MSG_195 error code, 267
ER_IB_MSG_196 error code, 267

ER_IB_MSG_531 error code, 287
ER_IB_MSG_532 error code, 287
ER_IB_MSG_533 error code, 287
ER_IB_MSG_534 error code, 288
ER_IB_MSG_537 error code, 288
ER_IB_MSG_538 error code, 288
ER_IB_MSG_539 error code, 288
ER_IB_MSG_54 error code, 259
ER_IB_MSG_540 error code, 288
ER_IB_MSG_541 error code, 288
ER_IB_MSG_543 error code, 288
ER_IB_MSG_544 error code, 288
ER_IB_MSG_545 error code, 288
ER_IB_MSG_546 error code, 288
ER_IB_MSG_547 error code, 288
ER_IB_MSG_548 error code, 288
ER_IB_MSG_549 error code, 288
ER_IB_MSG_55 error code, 260
ER_IB_MSG_550 error code, 288
ER_IB_MSG_551 error code, 288
ER_IB_MSG_552 error code, 288
ER_IB_MSG_553 error code, 289
ER_IB_MSG_554 error code, 289
ER_IB_MSG_555 error code, 289
ER_IB_MSG_556 error code, 289
ER_IB_MSG_557 error code, 289
ER_IB_MSG_558 error code, 289
ER_IB_MSG_559 error code, 289
ER_IB_MSG_56 error code, 260
ER_IB_MSG_560 error code, 289
ER_IB_MSG_561 error code, 289
ER_IB_MSG_562 error code, 289
ER_IB_MSG_563 error code, 289
ER_IB_MSG_564 error code, 289
ER_IB_MSG_566 error code, 289
ER_IB_MSG_567 error code, 289
ER_IB_MSG_568 error code, 289
ER_IB_MSG_569 error code, 290
ER_IB_MSG_57 error code, 260
ER_IB_MSG_570 error code, 290
ER_IB_MSG_571 error code, 290
ER_IB_MSG_573 error code, 290
ER_IB_MSG_574 error code, 290
ER_IB_MSG_578 error code, 290
ER_IB_MSG_579 error code, 290
ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL error
code, 363
ER_IB_MSG_58 error code, 260
ER_IB_MSG_580 error code, 290
ER_IB_MSG_581 error code, 290
ER_IB_MSG_582 error code, 290
ER_IB_MSG_583 error code, 290
ER_IB_MSG_584 error code, 290
ER_IB_MSG_585 error code, 290
ER_IB_MSG_586 error code, 290
ER_IB_MSG_587 error code, 290
ER_IB_MSG_588 error code, 290
ER_IB_MSG_589 error code, 291

ER_IB_MSG_59 error code, 260
ER_IB_MSG_590 error code, 291
ER_IB_MSG_591 error code, 291
ER_IB_MSG_592 error code, 291
ER_IB_MSG_593 error code, 291
ER_IB_MSG_594 error code, 291
ER_IB_MSG_595 error code, 291
ER_IB_MSG_596 error code, 291
ER_IB_MSG_597 error code, 291
ER_IB_MSG_598 error code, 291
ER_IB_MSG_599 error code, 291
ER_IB_MSG_6 error code, 257
ER_IB_MSG_60 error code, 260
ER_IB_MSG_600 error code, 291
ER_IB_MSG_601 error code, 291
ER_IB_MSG_602 error code, 291
ER_IB_MSG_603 error code, 291
ER_IB_MSG_604 error code, 291
ER_IB_MSG_605 error code, 292
ER_IB_MSG_606 error code, 292
ER_IB_MSG_607 error code, 292
ER_IB_MSG_608 error code, 292
ER_IB_MSG_609 error code, 292
ER_IB_MSG_61 error code, 260
ER_IB_MSG_611 error code, 292
ER_IB_MSG_612 error code, 292
ER_IB_MSG_613 error code, 292
ER_IB_MSG_614 error code, 292
ER_IB_MSG_615 error code, 292
ER_IB_MSG_616 error code, 292
ER_IB_MSG_617 error code, 292
ER_IB_MSG_619 error code, 292
ER_IB_MSG_62 error code, 260
ER_IB_MSG_623 error code, 292
ER_IB_MSG_624 error code, 293
ER_IB_MSG_626 error code, 293
ER_IB_MSG_627 error code, 293
ER_IB_MSG_628 error code, 293
ER_IB_MSG_629 error code, 293
ER_IB_MSG_63 error code, 260
ER_IB_MSG_630 error code, 293
ER_IB_MSG_631 error code, 293
ER_IB_MSG_632 error code, 293
ER_IB_MSG_633 error code, 293
ER_IB_MSG_634 error code, 293
ER_IB_MSG_635 error code, 293
ER_IB_MSG_636 error code, 293
ER_IB_MSG_637 error code, 293
ER_IB_MSG_638 error code, 293
ER_IB_MSG_639 error code, 293
ER_IB_MSG_64 error code, 260
ER_IB_MSG_642 error code, 293
ER_IB_MSG_643 error code, 294
ER_IB_MSG_644 error code, 294
ER_IB_MSG_645 error code, 294
ER_IB_MSG_646 error code, 294
ER_IB_MSG_647 error code, 294
ER_IB_MSG_648 error code, 294

ER_IB_MSG_911 error code, 308
ER_IB_MSG_912 error code, 308
ER_IB_MSG_913 error code, 309
ER_IB_MSG_914 error code, 309
ER_IB_MSG_915 error code, 309
ER_IB_MSG_916 error code, 309
ER_IB_MSG_917 error code, 309
ER_IB_MSG_918 error code, 309
ER_IB_MSG_919 error code, 309
ER_IB_MSG_920 error code, 309
ER_IB_MSG_921 error code, 309
ER_IB_MSG_922 error code, 309
ER_IB_MSG_923 error code, 309
ER_IB_MSG_924 error code, 309
ER_IB_MSG_925 error code, 309
ER_IB_MSG_926 error code, 309
ER_IB_MSG_927 error code, 309
ER_IB_MSG_928 error code, 309
ER_IB_MSG_929 error code, 310
ER_IB_MSG_930 error code, 310
ER_IB_MSG_931 error code, 310
ER_IB_MSG_932 error code, 310
ER_IB_MSG_933 error code, 310
ER_IB_MSG_934 error code, 310
ER_IB_MSG_935 error code, 310
ER_IB_MSG_936 error code, 310
ER_IB_MSG_937 error code, 310
ER_IB_MSG_938 error code, 310
ER_IB_MSG_939 error code, 310
ER_IB_MSG_940 error code, 310
ER_IB_MSG_941 error code, 310
ER_IB_MSG_942 error code, 310
ER_IB_MSG_943 error code, 310
ER_IB_MSG_944 error code, 310
ER_IB_MSG_945 error code, 311
ER_IB_MSG_946 error code, 311
ER_IB_MSG_948 error code, 311
ER_IB_MSG_949 error code, 311
ER_IB_MSG_95 error code, 261
ER_IB_MSG_950 error code, 311
ER_IB_MSG_951 error code, 311
ER_IB_MSG_952 error code, 311
ER_IB_MSG_953 error code, 311
ER_IB_MSG_954 error code, 311
ER_IB_MSG_955 error code, 311
ER_IB_MSG_956 error code, 311
ER_IB_MSG_957 error code, 311
ER_IB_MSG_958 error code, 311
ER_IB_MSG_959 error code, 311
ER_IB_MSG_96 error code, 262
ER_IB_MSG_960 error code, 311
ER_IB_MSG_961 error code, 312
ER_IB_MSG_962 error code, 312
ER_IB_MSG_963 error code, 312
ER_IB_MSG_964 error code, 312
ER_IB_MSG_965 error code, 312
ER_IB_MSG_966 error code, 312
ER_IB_MSG_967 error code, 312

ER_IB_MSG_968 error code, 312
ER_IB_MSG_969 error code, 312
ER_IB_MSG_97 error code, 262
ER_IB_MSG_970 error code, 312
ER_IB_MSG_971 error code, 312
ER_IB_MSG_972 error code, 312
ER_IB_MSG_973 error code, 312
ER_IB_MSG_974 error code, 312
ER_IB_MSG_975 error code, 312
ER_IB_MSG_976 error code, 312
ER_IB_MSG_977 error code, 313
ER_IB_MSG_978 error code, 313
ER_IB_MSG_979 error code, 313
ER_IB_MSG_98 error code, 262
ER_IB_MSG_980 error code, 313
ER_IB_MSG_981 error code, 313
ER_IB_MSG_982 error code, 313
ER_IB_MSG_983 error code, 313
ER_IB_MSG_984 error code, 313
ER_IB_MSG_985 error code, 313
ER_IB_MSG_986 error code, 313
ER_IB_MSG_987 error code, 313
ER_IB_MSG_988 error code, 313
ER_IB_MSG_989 error code, 313
ER_IB_MSG_99 error code, 262
ER_IB_MSG_990 error code, 313
ER_IB_MSG_991 error code, 313
ER_IB_MSG_992 error code, 313
ER_IB_MSG_993 error code, 314
ER_IB_MSG_994 error code, 314
ER_IB_MSG_995 error code, 314
ER_IB_MSG_996 error code, 314
ER_IB_MSG_997 error code, 314
ER_IB_MSG_998 error code, 314
ER_IB_MSG_999 error code, 314
ER_IB_MSG_ABORTING_LOG_ARCHIVER error
code, 404
ER_IB_MSG_BAD_DBLWR_FILE_NAME error code,
361
ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED
error code, 355
ER_IB_MSG_BUF_PENDING_IO error code, 320
ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN
error code, 329
ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS
error code, 394
ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE
error code, 394
ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE
error code, 394
ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE
error code, 364
ER_IB_MSG_CANT_DECRYPT_REDO_LOG error
code, 304
ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA
error code, 304
ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA
error code, 393

ER_IB_MSG_CLOCK_GETTIME_FAILED error code, 353	ER_IB_MSG_DDL_LOG_FAIL_POST_DDL error code, 351
ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED error code, 353	ER_IB_MSG_DICT_PARTITION_NOT_FOUND error code, 360
ER_IB_MSG_CLONE_DDL_APPLY error code, 381	ER_IB_MSG_DOWNGRADE_PARTITION_FILE error code, 359
ER_IB_MSG_CLONE_DDL_INVALIDATE error code, 381	ER_IB_MSG_DROPPED_UNDO_SPACE error code, 370
ER_IB_MSG_CLONE_DDL_NTFN error code, 381	ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE error code, 341
ER_IB_MSG_CREATED_UNDO_SPACE error code, 370	ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR error code, 341
ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED error code, 322	ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR error code, 342
ER_IB_MSG_DBLWR_1285 error code, 361	ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT error code, 341
ER_IB_MSG_DBLWR_1286 error code, 361	ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE error code, 342
ER_IB_MSG_DBLWR_1287 error code, 361	ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE error code, 341
ER_IB_MSG_DBLWR_1288 error code, 361	ER_IB_MSG_FILE_RESIZE error code, 318
ER_IB_MSG_DBLWR_1290 error code, 361	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME error code, 360
ER_IB_MSG_DBLWR_1293 error code, 361	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH error code, 360
ER_IB_MSG_DBLWR_1294 error code, 361	ER_IB_MSG_FIL_STATE_MOVED_CORRECTED error code, 360
ER_IB_MSG_DBLWR_1295 error code, 361	ER_IB_MSG_FIL_STATE_MOVED_PREV error code, 415
ER_IB_MSG_DBLWR_1296 error code, 361	ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY error code, 360
ER_IB_MSG_DBLWR_1297 error code, 361	ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR error code, 279
ER_IB_MSG_DBLWR_1298 error code, 361	ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN error code, 363
ER_IB_MSG_DBLWR_1300 error code, 361	ER_IB_MSG_IBUF_CURSOR_RESTORATION_FAILED error code, 292
ER_IB_MSG_DBLWR_1301 error code, 362	ER_IB_MSG_IBUF_FAILED_TO_RESTORE_POSITION error code, 292
ER_IB_MSG_DBLWR_1304 error code, 362	ER_IB_MSG_IGNORE_SCAN_PATH error code, 277
ER_IB_MSG_DBLWR_1305 error code, 362	ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR error code, 279
ER_IB_MSG_DBLWR_1306 error code, 362	ER_IB_MSG_INCORRECT_SIZE error code, 370
ER_IB_MSG_DBLWR_1307 error code, 362	ER_IB_MSG_INJECT_CRASH error code, 369
ER_IB_MSG_DBLWR_1308 error code, 362	ER_IB_MSG_INJECT_FAILURE error code, 369
ER_IB_MSG_DBLWR_1309 error code, 362	ER_IB_MSG_INNODB_END_INITIALIZE error code, 363
ER_IB_MSG_DBLWR_1310 error code, 362	ER_IB_MSG_INNODB_FLUSH_METHOD error code, 415
ER_IB_MSG_DBLWR_1311 error code, 362	ER_IB_MSG_INNODB_START_INITIALIZE error code, 363
ER_IB_MSG_DBLWR_1312 error code, 362	ER_IB_MSG_INVALID_LOCATION_FOR_TABLE error code, 289
ER_IB_MSG_DBLWR_1313 error code, 362	ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE error code, 364
ER_IB_MSG_DBLWR_1314 error code, 362	ER_IB_MSG_INVALID_LOCATION_WRONG_DB error code, 364
ER_IB_MSG_DBLWR_1315 error code, 362	ER_IB_MSG_INVALID_PAGE_TYPE error code, 394
ER_IB_MSG_DBLWR_1316 error code, 362	
ER_IB_MSG_DBLWR_1317 error code, 362	
ER_IB_MSG_DBLWR_1318 error code, 362	
ER_IB_MSG_DBLWR_1320 error code, 363	
ER_IB_MSG_DBLWR_1321 error code, 363	
ER_IB_MSG_DBLWR_1323 error code, 363	
ER_IB_MSG_DBLWR_1324 error code, 363	
ER_IB_MSG_DBLWR_1325 error code, 363	
ER_IB_MSG_DBLWR_1326 error code, 363	
ER_IB_MSG_DBLWR_1327 error code, 363	
ER_IB_MSG_DBLWR_LOAD_WRONG_SIZE error code, 362	
ER_IB_MSG_DBLWR_OPEN_OR_CREATE_WRONG_SIZE error code, 363	
ER_IB_MSG_DDL_FAIL_NO_BUILDER error code, 403	
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK error code, 294	
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT error code, 351	

ER_IB_MSG_LOG_LOCK_FREE_HASH_USAGE_STATS error code, 342	ER_IB_MSG_LOG_FILE_INVALID_START_LSN error code, 388
ER_IB_MSG_LOG_CHECKPOINT_FOUND error code, 388	ER_IB_MSG_LOG_FILE_IS_EMPTY error code, 386
ER_IB_MSG_LOG_CORRUPT error code, 295	ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED error code, 390
ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY_MODE error code, 329	ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE error code, 389
ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED error code, 388	ER_IB_MSG_LOG_FILE_MISSING_FOR_ID error code, 388
ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE error code, 297	ER_IB_MSG_LOG_FILE_OPEN_FAILED error code, 318
ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY_MODE error code, 387	ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED error code, 318
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB error code, 297	ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED error code, 318
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE error code, 297	ER_IB_MSG_LOG_FILE_REMOVE_FAILED error code, 389
ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATE_OR_REPLACE error code, 389	ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED error code, 389
ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE error code, 318	ER_IB_MSG_LOG_FILE_RESIZE_FAILED error code, 318
ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES error code, 322	ER_IB_MSG_LOG_FILE_SIZE_INVALID error code, 322
ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED error code, 329	ER_IB_MSG_LOG_FILE_TOO_BIG error code, 386
ER_IB_MSG_LOG_FILES_FOUND_MISSING error code, 389	ER_IB_MSG_LOG_FILE_TOO_SMALL error code, 386
ER_IB_MSG_LOG_FILES_INITIALIZED error code, 318	ER_IB_MSG_LOG_FILE_TRUNCATE error code, 389
ER_IB_MSG_LOG_FILES_INVALID_SET error code, 322	ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED error code, 390
ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED error code, 388	ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED error code, 390
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED error code, 388	ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED error code, 390
ER_IB_MSG_LOG_FILES_RESIZE_ON_START error code, 327	ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED error code, 390
ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED error code, 388	ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9 error code, 330
ER_IB_MSG_LOG_FILES_REWRITING error code, 323	ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30 error code, 296
ER_IB_MSG_LOG_FILES_UPGRADE error code, 388	ER_IB_MSG_LOG_FORMAT_OLD error code, 297
ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS error code, 389	ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED error code, 295
ER_IB_MSG_LOG_FILE_FOREIGN_UUID error code, 388	ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN error code, 295
ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW error code, 389	ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED error code, 387
ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD error code, 389	ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR error code, 387
ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN error code, 296	ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE error code, 387
ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM error code, 330	ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNREASONABLE error code, 330
ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED error code, 387	ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED error code, 390
ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES error code, 388	ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE error code, 390
	ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED error code, 389

ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED error code, 389	ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE error code, 387
ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0 error code, 389	ER_IB_MSG_RECOVERY_CORRUPT error code, 323
ER_IB_MSG_LOG_UPGRADE_CLONED_DB error code, 388	ER_IB_MSG_RECOVERY_IN_READ_ONLY error code, 298
ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXP208 error code, 388	ER_IB_MSG_RECOVERY_IS_NEEDED error code, 387
ER_IB_MSG_LOG_UPGRADE_FORCED_RECV error code, 387	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IB error code, 379
ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE error code, 387	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXP error code, 379
ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES error code, 388	ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE error code, 297
ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER error code, 328	ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY error code, 379
ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN error code, 387	ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY error code, 379
ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN error code, 387	ER_IB_MSG_RESUME_OP_FOR_SPACE error code, 337
ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE error code, 328	ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR error code, 367
ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER error code, 328	ER_IB_MSG_SDI_Z_STREAM_ERROR error code, 342
ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER error code, 393	ER_IB_MSG_SDI_Z_UNKNOWN_ERROR error code, 342
ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE error code, 387	ER_IB_MSG_SKIP_HIDDEN_DIR error code, 358
ER_IB_MSG_LOG_WRITER_WRITE_FAILED error code, 387	ER_IB_MSG_STATS_SAMPLING_TOO_LARGE error code, 373
ER_IB_MSG_MADVISE_FAILED error code, 341	ER_IB_MSG_SUBMIT_DETAILED_BUG_REPORT error code, 413
ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED error code, 341	ER_IB_MSG_THREAD_CONCURRENCY_CHANGED error code, 330
ER_IB_MSG_MASTER_KEY_ROTATED error code, 370	ER_IB_MSG_TOO_LONG_PATH error code, 352
ER_IB_MSG_MAX_UNDO_SPACES_REACHED error code, 341	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED error code, 325
ER_IB_MSG_NOT_END_WITH_IBU error code, 342	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED error code, 366
ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND error code, 337	ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME error code, 384
ER_IB_MSG_OPENED_N_UNDO_TS error code, 319	ER_IB_MSG_UNDO_ALTERED_ACTIVE error code, 369
ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS error code, 364	ER_IB_MSG_UNDO_ALTERED_INACTIVE error code, 369
ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION error code, 393	ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED error code, 381
ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG error code, 379	ER_IB_MSG_UNDO_MARKED_ACTIVE error code, 369
ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG error code, 379	ER_IB_MSG_UNDO_MARKED_EMPTY error code, 369
ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER error code, 351	ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE error code, 324
ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT error code, 351	ER_IB_MSG_UNDO_TRUNCATE_COMPLETE error code, 324
ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE error code, 297	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE error code, 369
ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND error code, 296	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE error code, 324

ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE error code, 324	ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE error code, 367
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL error code, 369	ER_IB_WARN_ACCESSING_NONEXISTING_SPACE error code, 272
ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG error code, 324	ER_IB_WARN_MANY_NON_LRU_FILES_OPENED error code, 384
ER_IB_MSG_UNDO_TRUNCATE_START error code, 324	ER_IB_WARN_OPEN_PARTITION_FILE error code, 359
ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN error code, 364	ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH error code, 381
ER_IB_MSG_UNEXPECTED_FILE_EXISTS error code, 274	ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE error code, 375
ER_IB_MSG_UNPROCESSED_REDO_LOG_RECORDS error code, 295	ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED error code, 365
ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED error code, 277	ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY error code, 397
ER_IB_MSG_UPGRADE_PARTITION_FILE error code, 359	ER_IB_WRN_OLD_GEOMETRY_TYPE error code, 375
ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT error code, 359	ER_IB_WRN_PAGE_ARCH_FLUSH_DATA error code, 364
ER_IB_MSG_USING_UNDO_SPACE error code, 341	ER_IB_WRN_REDO_DISABLED error code, 365
ER_IB_MSG_WAITING_ON_LAGGING_REDO_LOG_CONSUMER error code, 404	ER_IB_WRN_REDO_ENABLED error code, 365
ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD error code, 337	ER_IB_WRONG_PAGEID_AFTER_SYNC_READ error code, 407
ER_IB_MSG_WILL_CREATE_N_UNDO_TS error code, 327	ER_IB_WRONG_PAGE_ID error code, 406
ER_IB_MSG_WRONG_TABLESPACE_DIR error code, 342	ER_IDENTIFIED_BY_UNSUPPORTED error code, 112
ER_IB_PARALLEL_READER_WORKER_INFO error code, 394	ER_IDENT_CAUSES_TOO_LONG_PATH error code, 55
ER_IB_PRIMARY_KEY_IS_INSTANT error code, 397	ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE error code, 356
ER_IB_RDBLWR_BYTES_INFO error code, 386	ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DI error code, 116
ER_IB_RECV_FIRST_REC_GROUP_INVALID error code, 352	ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_N error code, 116
ER_IB_RELOCK_LATCH_ORDER_VIOLATION error code, 367	ER_ILLEGAL_GRANT_FOR_TABLE error code, 12
ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK error code, 399	ER_ILLEGAL_HA error code, 5
ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK error code, 399	ER_ILLEGAL_HA_CREATE_OPTION error code, 32
ER_IB_RESURRECT_RECORD_COMPLETE error code, 399	ER_ILLEGAL_PRIVILEGE_LEVEL error code, 80
ER_IB_RESURRECT_RECORD_PROGRESS error code, 399	ER_ILLEGAL_REFERENCE error code, 18
ER_IB_RESURRECT_TRX_INSERT error code, 399	ER_ILLEGAL_USER_VAR error code, 61
ER_IB_RESURRECT_TRX_INSERT_COMPLETE error code, 399	ER_ILLEGAL_VALUE_FOR_TYPE error code, 25
ER_IB_RESURRECT_TRX_UPDATE error code, 399	ER_IMDS_OCI_ERROR error code, 417
ER_IB_RESURRECT_TRX_UPDATE_COMPLETE error code, 400	ER_IMDS_OCI_INFO error code, 417
ER_IB_SELECT_COUNT_STAR error code, 398	ER_IMDS_OCI_WARNING error code, 417
ER_IB_SYNC_READ_FAILED error code, 407	ER_IMPLICIT_COMPARISON_FOR_JSON error code, 107
ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED error code, 366	ER_IMPOSSIBLE_STRING_CONVERSION error code, 107
ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECT error code, 367	ER_IMP_INCOMPATIBLE_CFG_VERSION error code, 104
	ER_IMP_INCOMPATIBLE_DD_VERSION error code, 79
	ER_IMP_INCOMPATIBLE_MYSQLD_VERSION error code, 79
	ER_IMP_INCOMPATIBLE_SDI_VERSION error code, 79
	ER_IMP_NO_FILES_MATCHED error code, 79

ER_IMP_SCHEMA_DOES_NOT_EXIST error code, 79	ER_INNODB_ERROR_LOGGER_FATAL_MSG error code, 203
ER_IMP_TABLE_ALREADY_EXISTS error code, 79	ER_INNODB_ERROR_LOGGER_MSG error code, 203
ER_INCOMPATIBLE_TYPE_AGG error code, 130	ER_INNODB_FAILED_TO_FIND_IDX error code, 202
ER_INCONSISTENT_ERROR error code, 332	ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE error code, 202
ER_INCONSISTENT_PARTITION_INFO_ERROR error code, 32	ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO error code, 202
ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR error code, 32	ER_INNODB_FILES_SAME error code, 190
ER_INCORRECT_CURRENT_PASSWORD error code, 99	ER_INNODB_FORCED_RECOVERY error code, 56
ER_INCORRECT_GLOBAL_LOCAL_VAR error code, 18	ER_INNODB_FT_AUX_NOT_HEX_ID error code, 56
ER_INCORRECT_TYPE error code, 61	ER_INNODB_FT_LIMIT error code, 51
ER_INDEX_COLUMN_TOO_LONG error code, 45	ER_INNODB_FT_WRONG_DOCID_COLUMN error code, 51
ER_INDEX_CORRUPT error code, 45	ER_INNODB_FT_WRONG_DOCID_INDEX error code, 51
ER_INDEX_OTHER_THAN_PK error code, 118	ER_INNODB_INDEX error code, 190
ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX error code, 87	ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL error code, 202
ER_INFORMATION_SCHEMA_VERSION_CHANGE error code, 402	ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL error code, 202
ER_INFO_AUTHENTICATION_OCI error code, 425	ER_INNODB_IDX_COLUMN_CNT_DIFF error code, 202
ER_INIT_BOOTSTRAP_COMPLETE error code, 170	ER_INNODB_ILLEGAL_COLON_IN_POOL error code, 190
ER_INIT_CANT_OPEN_BOOTSTRAP_FILE error code, 170	ER_INNODB_IMPORT_DROP_COL_METADATA_MISMATCH error code, 122
ER_INIT_CREATING_DD error code, 170	ER_INNODB_IMPORT_ENUM_NULL_TERMINATOR_MISSING error code, 122
ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE error code, 170	ER_INNODB_IMPORT_ERROR error code, 52
ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE error code, 170	ER_INNODB_IMPORT_WRONG_DROPPED_ENUM_LENGTH error code, 122
ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE error code, 170	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES_TOO_FEW error code, 122
ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE error code, 170	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES_ZERO error code, 122
ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD error code, 358	ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE error code, 110
ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT error code, 170	ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS error code, 190
ER_INIT_ROOT_WITHOUT_PASSWORD error code, 170	ER_INNODB_INDEX_CORRUPT error code, 52
ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED error code, 202	ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED_MAX_SIZE error code, 120
ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE error code, 110	ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FIELDS error code, 120
ER_INNODB_CANNOT_CREATE_TABLE error code, 202	ER_INNODB_INTERNAL_INDEX error code, 202
ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR error code, 190	ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE error code, 110
ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD error code, 190	ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY error code, 189
ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK error code, 190	ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION error code, 343
ER_INNODB_CLUSTERED_INDEX_PRIVATE error code, 191	ER_INNODB_INVALID_LOG_GROUP_HOME_DIR error code, 189
ER_INNODB_COMPRESSION_FAILURE error code, 110	ER_INNODB_INVALID_MONITOR_COUNTER_NAME error code, 203
ER_INNODB_DIFF_IN_REF_LEN error code, 202	ER_INNODB_INVALID_PAGE_SIZE error code, 190
ER_INNODB_DIRTY_WATER_MARK_NOT_LOW error code, 190	

ER_INNODB_IO_CAPACITY_EXCEEDS_MAX error code, 190	ER_INSECURE_PLAIN_TEXT error code, 48
ER_INNODB_IO_WRITE_ERROR_RETRYING error code, 371	ER_INSERT_INFO error code, 9
ER_INNODB_IO_WRITE_FAILED error code, 371	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG error code, 43
ER_INNODB_MANDATORY error code, 145	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG error code, 43
ER_INNODB_MAX_ROW_VERSION error code, 115	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG error code, 44
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED error code, 203	ER_INSTALL_COMPONENT_SET_NULL_VALUE error code, 120
ER_INNODB_MONITOR_IS_ENABLED error code, 203	ER_INSTALL_COMPONENT_SET_UNUSED_VALUE error code, 120
ER_INNODB_NO_FT_TEMP_TABLE error code, 51	ER_INSTALL_PLUGIN_CONFLICT_CLIENT error code, 111
ER_INNODB_ONLINE_LOG_TOO_BIG error code, 51	ER_INSTALL_PLUGIN_CONFLICT_LOG error code, 378
ER_INNODB_OUT_OF_RESOURCES error code, 360	ER_INTERNAL_ERROR error code, 52
ER_INNODB_PK_NOT_IN_MYSQL error code, 190	ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED error code, 117
ER_INNODB_PK_ONLY_IN_MYSQL error code, 191	ER_INVALID_ADMIN_ADDRESS error code, 344
ER_INNODB_READ_ONLY error code, 56	ER_INVALID_ARGUMENT_FOR_LOGARITHM error code, 58
ER_INNODB_REDO_ARCHIVING_ENABLED error code, 106	ER_INVALID_ASSIGNMENT_TARGET error code, 112
ER_INNODB_REDO_DISABLED error code, 106	ER_INVALID_AUTHENTICATION_POLICY error code, 381
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE error code, 96	ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE error code, 73
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID error code, 96	ER_INVALID_BITWISE_OPERANDS_SIZE error code, 73
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH error code, 96	ER_INVALID_CAST error code, 108
ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY error code, 96	ER_INVALID_CAST_POLYGON_RING_DIRECTION error code, 110
ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS error code, 96	ER_INVALID_CAST_TO_GEOMETRY error code, 110
ER_INNODB_REDO_LOG_ARCHIVE_FAILED error code, 97	ER_INVALID_CAST_TO_JSON error code, 67
ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE error code, 96	ER_INVALID_CHARACTER_STRING error code, 21
ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE error code, 97	ER_INVALID_CHARSET_AND_DEFAULT_IS_MB error code, 163
ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND error code, 96	ER_INVALID_CLAUSE_COMBINATION error code, 132
ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR error code, 96	ER_INVALID_CLAUSE_IN_CONTEXT error code, 132
ER_INNODB_REDO_LOG_ARCHIVE_SESSION error code, 97	ER_INVALID_COLLATION_FOR_CHARSET error code, 194
ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR error code, 96	ER_INVALID_DD_OBJECT error code, 72
ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT error code, 96	ER_INVALID_DD_OBJECT_ID error code, 72
ER_INNODB_TRX_XLATION_TABLE_OOM error code, 190	ER_INVALID_DD_OBJECT_NAME error code, 72
ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT error code, 364	ER_INVALID_DEFAULT error code, 7
ER_INNODB_UNDO_LOG_FULL error code, 58	ER_INVALID_DEFAULT_UTF8MB4_COLLATION error code, 86
ER_INNODB_UNKNOWN_COLLATION error code, 189	ER_INVALID_ENCRYPTION_OPTION error code, 70
ER_INNODB_UNREGISTERED_TRX_ACTIVE error code, 190	ER_INVALID_ENCRYPTION_REQUEST error code, 95
ER_INNODB_USE_MONITOR_GROUP_NAME error code, 203	ER_INVALID_ERROR_LOG_NAME error code, 152
ER_INSECURE_CHANGE_SOURCE error code, 48	ER_INVALID_FIELD_SIZE error code, 58
	ER_INVALID_FILE_FORMAT error code, 414
	ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL error code, 83

ER_INVALID_GEOJSON_MISSING_MEMBER error code, 62	ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH error code, 402
ER_INVALID_GEOJSON_UNSPECIFIED error code, 62	ER_INVALID_SERVER_OPTION_CHARSET error code, 427
ER_INVALID_GEOJSON_WRONG_TYPE error code, 62	ER_INVALID_SERVER_OPTION_COLLATION error code, 427
ER_INVALID_GROUP_FUNC_USE error code, 10	ER_INVALID_SERVER_UPGRADE_NOT_LTS error code, 402
ER_INVALID_INFO_IN_FRM error code, 163	ER_INVALID_THREAD_ID error code, 82
ER_INVALID_INSTRUMENT error code, 145	ER_INVALID_THREAD_PRIORITY error code, 82
ER_INVALID_JSON_ATTRIBUTE error code, 106	ER_INVALID_TIME_ZONE_INTERVAL error code, 107
ER_INVALID_JSON_BINARY_DATA error code, 67	ER_INVALID_TLS_VERSION error code, 385
ER_INVALID_JSON_CHARSET error code, 67	ER_INVALID_TYPE_FOR_JSON error code, 67
ER_INVALID_JSON_CHARSET_IN_FUNCTION error code, 67	ER_INVALID_USER_ATTRIBUTE_JSON error code, 106
ER_INVALID_JSON_DATA error code, 62	ER_INVALID_USER_FOR_REGISTRATION error code, 113
ER_INVALID_JSON_PATH error code, 67	ER_INVALID_USE_OF_FORCE_OPTION error code, 83
ER_INVALID_JSON_PATH_ARRAY_CELL error code, 69	ER_INVALID_USE_OF_NULL error code, 12
ER_INVALID_JSON_PATH_CHARSET error code, 67	ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY error code, 142
ER_INVALID_JSON_PATH_WILDCARD error code, 68	ER_INVALID_VALUE_OF_BIND_ADDRESSES error code, 338
ER_INVALID_JSON_TEXT error code, 67	ER_INVALID_VCPU_ID error code, 82
ER_INVALID_JSON_TEXT_IN_PARAM error code, 67	ER_INVALID_VCPU_RANGE error code, 82
ER_INVALID_JSON_TYPE error code, 97	ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER error code, 364
ER_INVALID_JSON_VALUE_FOR_CAST error code, 68	ER_INVALID_YEAR_COLUMN_LENGTH error code, 52
ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX error code, 100	ER_INVALID_YEAR_LOG_INDEX_READ error code, 26
ER_INVALID_LOGGER error code, 417	ER_IO_READ_ERROR error code, 52
ER_INVALID_METER error code, 417	ER_IO_WRITE_ERROR error code, 52
ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS error code, 113	ER_IPSOCK_ERROR error code, 8
ER_INVALID_MFA_PLUGIN_SPECIFIED error code, 112	ER_IS_QUERY_INVALID_CLAUSE error code, 75
ER_INVALID_MULTIPLE_CLAUSES error code, 95	ER_I_S_SKIPPED_TABLESPACE error code, 81
ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP error code, 349	ER_JDV_ALGO_TEMPTABLE_NOT_SUPPORTED error code, 133
ER_INVALID_NO_OF_ARGS error code, 79	ER_JDV ALTER_OR_REPLACE_NOT_SUPPORTED error code, 137
ER_INVALID_ON_UPDATE error code, 21	ER_JDV_CANNOT_BE_USED_WITH error code, 138
ER_INVALID_OPTION_CHARACTERS error code, 76	ER_JDV_DML_INFO error code, 138
ER_INVALID_OPTION_END_CHARACTER error code, 76	ER_JDV_ETAG_MISMATCH error code, 138
ER_INVALID_OPTION_KEY error code, 76	ER_JDV_EXPLICIT_AUTO_INCREMENT_NOT_ALLOWED error code, 139
ER_INVALID_OPTION_KEY_VALUE_PAIR error code, 76	ER_JDV_FEATURE_EDITION_LIMIT error code, 138
ER_INVALID_OPTION_START_CHARACTER error code, 76	ER_JDV_INSERT_VALUE_NOT_FIXED error code, 138
ER_INVALID_OPTION_VALUE error code, 76	ER_JDV_INVALID_BINARY_TYPE_HEADER error code, 139
ER_INVALID_OR_OLD_TABLE_OR_DB_NAME error code, 172	ER_JDV_INVALID_DEFINITION_ALIAS_NOT_USED_FOR_SAME error code, 137
ER_INVALID_OUTER_REFERENCE error code, 132	ER_JDV_INVALID_DEFINITION_COLUMN_LIST_NOT_SUPPORT error code, 136
ER_INVALID_PARAMETER_USE error code, 107	ER_JDV_INVALID_DEFINITION_COLUMN_TYPE_NOT_SUPPORT error code, 135
ER_INVALID_PLUGIN_FOR_REGISTRATION error code, 112	ER_JDV_INVALID_DEFINITION_COMPOSITE_KEY_USED error code, 137
ER_INVALID_PROPERTY_KEY error code, 346	
ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN error code, 62	

ER_JDV_INVALID_DEFINITION_CONTEXT_PREPARE_FAILED error code, 135	ER_JDV_INVALID_TABLE_ANNOTATIONS_FOR_NESTED_OBJECT error code, 136
ER_JDV_INVALID_DEFINITION_CTE_NOT_SUPPORTED error code, 134	ER_JDV_INVALID_TABLE_ANNOTATIONS_FOR_SINGLETON error code, 136
ER_JDV_INVALID_DEFINITION_DUPLICATE_COLUMNS error code, 136	ER_JDV_INVALID_CONDITION_NOT_SATISFIED error code, 137
ER_JDV_INVALID_DEFINITION_DUPLICATE_KEYS error code, 136	ER_JDV_INVALID_CONDITION_VIOLATION error code, 138
ER_JDV_INVALID_DEFINITION_GROUPBY_NOT_SUPPORTED error code, 134	ER_JDV_MISSING_DELETE_TAG error code, 138
ER_JDV_INVALID_DEFINITION_ID_KEY_NOT_USED_BY_NOT_SUPPORTED error code, 136	ER_JDV_MISSING_ETAG error code, 138
ER_JDV_INVALID_DEFINITION_ID_KEY_USED_BY_NOT_SUPPORTED error code, 136	ER_JDV_MISSING_INSERT_TAG error code, 137
ER_JDV_INVALID_DEFINITION_INCONSISTENT_TABLE error code, 136	ER_JDV_MISSING_READONLY_SUBOBJECT error code, 138
ER_JDV_INVALID_DEFINITION_LIMIT_NOT_SUPPORTED error code, 134	ER_JDV_MISSING_UPDATE_TAG error code, 138
ER_JDV_INVALID_DEFINITION_MULTI_TABLES_NOT_SUPPORTED error code, 134	ER_JDV_MISSING_COBALT error code, 138
ER_JDV_INVALID_DEFINITION_MUSTBE_JSON_OBJECT error code, 135	ER_JDV_NULL_INSERT_VALUE error code, 138
ER_JDV_INVALID_DEFINITION_MUSTBE_JSON_OBJECT error code, 135	ER_JDV_NULL_UPDATE_VALUE error code, 138
ER_JDV_INVALID_DEFINITION_NON_BASE_TABLE error code, 135	ER_JDV_OPERATION_NOT_SUPPORTED error code, 138
ER_JDV_INVALID_DEFINITION_NON_SIMPLE_SELECT error code, 134	ER_JDV_PK_DUPLICATES_NOT_IDENTICAL error code, 137
ER_JDV_INVALID_DEFINITION_NO_JSON_OBJECT_IN_ARRAY error code, 135	ER_JDV_PK_UPDATES_NOT_ALLOWED error code, 138
ER_JDV_INVALID_DEFINITION_NO_JSON_OBJ_IN_ARRAY error code, 135	ER_JDV_PRIMARY_KEY_MUST_BE_PROVIDED error code, 137
ER_JDV_INVALID_DEFINITION_NO_WHERE_CONDITION error code, 134	ER_JDV_UNEXPECTED_JSON_TYPE error code, 138
ER_JDV_INVALID_DEFINITION_ORDERBY_NOT_SUPPORTED error code, 134	ER_JDV_UNMAPPED_KEY error code, 137
ER_JDV_INVALID_DEFINITION_RELATIONSHIP_RULES error code, 135	ER_JDV_UPDATE_VALUE_NOT_FIXED error code, 138
ER_JDV_INVALID_DEFINITION_SAME_TABLE_INCONSISTENT error code, 136	ER_JDV_UPDATE_WITH_CHECK_OPTION_NOT_SUPPORTED error code, 133
ER_JDV_INVALID_DEFINITION_TABLE_WITHOUT_PK error code, 135	ER_JSON_BAD_ARG error code, 68
ER_JDV_INVALID_DEFINITION_TABLE_WITHOUT_PK error code, 136	ER_JSON_DOCUMENT_NULL_KEY error code, 68
ER_JDV_INVALID_DEFINITION_WHERE_CONDITION error code, 134	ER_JSON_DOCUMENT_TOO_DEEP error code, 68
ER_JDV_INVALID_DEFINITION_WHERE_USES_NON_INTEGER error code, 137	ER_JSON_KEY_TOO_BIG error code, 68
ER_JDV_INVALID_DEFINITION_WINDOW_FUNCTION error code, 134	ER_JSON_PARSE_ERROR error code, 154
ER_JDV_INVALID_DEFINITION_WRONG_ANNOTATIONS error code, 133	ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILS error code, 102
ER_JDV_INVALID_DEFINITION_WRONG_FIELD_TYPE error code, 135	ER_JSON_USED_AS_KEY error code, 68
ER_JDV_INVALID_DEFINITION_WRONG_WHERE_FORMAT error code, 134	ER_JSON_VACUOUS_PATH error code, 68
ER_JDV_INVALID_JSON_DUALITY_OBJECT_USAGE error code, 137	ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX error code, 100
	ER_JSON_VALUE_TOO_BIG error code, 68
	ER_JSON_WRONG_NESTED_PATH error code, 83
	ER_JT_VALUE_OUT_OF_RANGE error code, 83
	ER_KEYRING_CREATE_USER error code, 111
	ER_KEYCACHE_OOM error code, 147
	ER_KEYRING_ACCESS_DENIED_ERROR error code, 71
	ER_KEYRING_AWS_CMK_ID_NOT_SET error code, 226
	ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE error code, 226
	ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_COM error code, 225
	ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM error code, 225

ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_COMPONENT error code, 226	ER_KEYRING_COMPONENT_AWS_BACKEND_OPERATION_FAILED error code, 419
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_COMPONENT error code, 226	ER_KEYRING_COMPONENT_AWS_CACHE_OPERATION_FAILED error code, 419
ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS error code, 227	ER_KEYRING_COMPONENT_AWS_CANNOT_ENCRYPT_READ error code, 419
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY error code, 227	ER_KEYRING_COMPONENT_AWS_CLIENT_CREATE_FAILED error code, 419
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY error code, 227	ER_KEYRING_COMPONENT_AWS_CLIENT_OPERATION_FAILED error code, 419
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 227	ER_KEYRING_COMPONENT_AWS_FILE_OPEN_FAILED error code, 418
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR error code, 226	ER_KEYRING_COMPONENT_AWS_FILE_PARSE_FAILED error code, 419
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY error code, 227	ER_KEYRING_COMPONENT_AWS_FILE_PATH_EMPTY error code, 418
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL error code, 226	ER_KEYRING_COMPONENT_AWS_FILE_READ_FAILED error code, 418
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR error code, 226	ER_KEYRING_COMPONENT_AWS_FILE_WRITE_FAILED error code, 418
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_ERROR error code, 226	ER_KEYRING_COMPONENT_AWS_GENERATE_KEY_INVALID error code, 419
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE error code, 225	ER_KEYRING_COMPONENT_AWS_KEY_EXTRACT_FAILED error code, 419
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP error code, 227	ER_KEYRING_COMPONENT_AWS_READ_ONLY_LIMIT error code, 419
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY error code, 227	ER_KEYRING_COMPONENT_AWS_WRITE_AFTER_REENCRYPT error code, 419
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK error code, 227	ER_KEYRING_COMPONENT_EXCEPTION error code, 374
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID error code, 225	ER_KEYRING_COMPONENT_KEYRING_FILE_DECRYPT_FAILED error code, 413
ER_KEYRING_AWS_FAILED_TO_SET_REGION error code, 225	ER_KEYRING_COMPONENT_KEYRING_FILE_INVALID_FORMAT error code, 413
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP error code, 227	ER_KEYRING_COMPONENT_KEYRING_FILE_JSON_EXTRACT_FAILED error code, 413
ER_KEYRING_AWS_INCORRECT_FILE error code, 226	ER_KEYRING_COMPONENT_KEYRING_FILE_KEY_EXTRACT_FAILED error code, 413
ER_KEYRING_AWS_INCORRECT_PROXY error code, 357	ER_KEYRING_COMPONENT_KEYRING_FILE_NAME_EMPTY error code, 412
ER_KEYRING_AWS_INCORRECT_REGION error code, 227	ER_KEYRING_COMPONENT_KEYRING_FILE_READ_FAILED error code, 412
ER_KEYRING_AWS_INIT_FAILURE error code, 226	ER_KEYRING_COMPONENT_KEYRING_HASHICORP_AUTH_FAILED error code, 423
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH error code, 225	ER_KEYRING_COMPONENT_KEYRING_HASHICORP_CURL_SEQUENCE error code, 423
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH error code, 226	ER_KEYRING_COMPONENT_KEYRING_HASHICORP_DATA_EXTRACT_FAILED error code, 423
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER error code, 226	ER_KEYRING_COMPONENT_KEYRING_HASHICORP_KEY_MALFORMED error code, 423
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR error code, 71	ER_KEYRING_COMPONENT_KMIP_CONNECTION_TO_SERVER_FAILED error code, 426
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY error code, 222	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ACTIVATE_KEY error code, 427
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY error code, 222	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ADD_ATTRIBUTES error code, 426
ER_KEYRING_COMPONENT_AWS_ADD_TO_DOC_FAILED error code, 419	ER_KEYRING_COMPONENT_KMIP_FAILED_TO_ALLOCATE error code, 425

ER_KEYRING_COMPONENT_KMIP_FAILED_TO_FETCH_KEY error code, 426	ER_KEYRING_FAILED_TO_REMOVE_FILE error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_GENERATE_KEY error code, 427	ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_KEY error code, 223
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_INIT_CLIENT error code, 426	ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_INIT_SSL_LAYER error code, 426	ER_KEYRING_FAILED_TO_TRUNCATE_FILE error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_LOAD_KEY error code, 425	ER_KEYRING_FILE_IO_ERROR error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_LOAD_SSL_CERT error code, 426	ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_REMOVE_KEY error code, 426	ER_KEYRING_INCORRECT_FILE error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_RETRIEVE_KEY error code, 427	ER_KEYRING_INVALID_KEY_LENGTH error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_RETRIEVE_KEY error code, 427	ER_KEYRING_INVALID_KEY_TYPE error code, 221
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_RETRIEVE_KEY error code, 427	ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_SET_CERTIFICATE error code, 426	ER_KEYRING_LOGGER_ERROR_MSG error code, 222
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_SET_KEY error code, 426	ER_KEYRING_MIGRATE_FAILED error code, 331
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_STORE_KEY error code, 427	ER_KEYRING_MIGRATE_MEMORY_DEALLOCATION_FAILED error code, 414
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_STORE_KEY error code, 427	ER_KEYRING_MIGRATE_SKIPPED_KEY error code, 414
ER_KEYRING_COMPONENT_KMIP_FAILED_TO_STORE_KEY error code, 427	ER_KEYRING_MIGRATION_EXTRA_OPTIONS error code, 256
ER_KEYRING_COMPONENT_KMIP_GENERATE_KEY_INVALID_PARAMETER error code, 425	ER_KEYRING_MIGRATION_FAILED error code, 205
ER_KEYRING_COMPONENT_KMIP_INIT_PRIMARY error code, 426	ER_KEYRING_MIGRATION_FAILURE error code, 71
ER_KEYRING_COMPONENT_KMIP_INIT_STANDBY error code, 426	ER_KEYRING_MIGRATION_STATUS error code, 71
ER_KEYRING_COMPONENT_KMIP_INVALID_KEY_LENGTH error code, 425	ER_KEYRING_MIGRATION_SUCCESSFUL error code, 205
ER_KEYRING_COMPONENT_KMIP_INVALID_KEY_TYPE error code, 425	ER_KEYRING_OCI_HTTP_REQUEST error code, 393
ER_KEYRING_COMPONENT_KMIP_KEY_MISMATCH error code, 426	ER_KEYRING_OCI_INVALID_JSON error code, 393
ER_KEYRING_COMPONENT_KMIP_PATH_EMPTY error code, 425	ER_KEYRING_OCI_PARSE_JSON error code, 393
ER_KEYRING_COMPONENT_KMIP_STANDBY_SERVER_CONFIGURATION_FAILED error code, 427	ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED error code, 224
ER_KEYRING_COMPONENT_KMIP_TRYING_STANDBY error code, 426	ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS error code, 224
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR error code, 374	ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE error code, 224
ER_KEYRING_COMPONENT_NOT_INITIALIZED error code, 374	ER_KEYRING_OKV_FAILED_TO_FETCH_KEY error code, 224
ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 222	ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY error code, 223
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 223	ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER error code, 224
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 223	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY error code, 224
ER_KEYRING_FAILED_TO_GET_FILE_STAT error code, 222	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_EMPTY_KEY error code, 223
ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT error code, 223	ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT error code, 224
	ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER error code, 224
	ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID error code, 224
	ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE error code, 225

ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE error code, 224	ER_LANGUAGE_COMPONENT_INTERNAL_ERROR error code, 412
ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY error code, 224	ER_LANGUAGE_COMPONENT_KEYWORD error code, 129
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY error code, 225	ER_LANGUAGE_COMPONENT_NOT_AVAILABLE error code, 121
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE error code, 225	ER_LANGUAGE_COMPONENT_RUNTIME error code, 128
ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE error code, 225	ER_LANGUAGE_COMPONENT_SERVER_ERROR error code, 412
ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE error code, 225	ER_LANGUAGE_COMPONENT_SET_SYSTEM_VARIABLE error code, 129
ER_KEYRING_OKV_FAILED_TO_STORE_KEY error code, 224	ER_LANGUAGE_COMPONENT_TIMEZONE error code, 128
ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY error code, 224	ER_LANGUAGE_COMPONENT_UNSUPPORTED_LANGUAGE error code, 121
ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURATION error code, 223	ER_LANGUAGE_COMPONENT_UNSUPPORTED_TYPE error code, 129
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONFIG error code, 223	ER_LANGUAGE_COMPONENT_VM_API_FUNCTION_ERROR error code, 412
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR error code, 223	ER_LANGUAGE_COMPONENT_VM_INTERNAL_ERROR error code, 412
ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER error code, 223	ER_LANGUAGE_COMPONENT_WARNING error code, 404
ER_KEYRING_OKV_INVALID_KEY_TYPE error code, 223	ER_LATITUDE_OUT_OF_RANGE error code, 80
ER_KEYRING_OKV_KEY_MISMATCH error code, 225	ER_LCTN_CHANGED error code, 205
ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED error code, 385	ER_LCTN_NOT_FOUND error code, 331
ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR error code, 222	ER_LDAP_AUTH_CERTIFICATE_NAME error code, 252
ER_KEYRING_UDF_KEYRING_SERVICE_ERROR error code, 70	ER_LDAP_AUTH_COMMUNICATION_HOST_INFO error code, 254
ER_KEYRING_UNKNOWN_ERROR error code, 222	ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER error code, 253
ER_KEY_COLUMN_DOES_NOT_EXISTS error code, 8	ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL error code, 253
ER_KEY_DOES_NOT_EXISTS error code, 14	ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED error code, 252
ER_KEY_NOT_FOUND error code, 5	ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER error code, 255
ER_KEY_PART_0 error code, 26	ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL error code, 253
ER_KEY_REF_DO_NOT_MATCH_TABLE_REF error code, 18	ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING error code, 251
ER_KILLED_THREADS_OF_PLUGIN error code, 171	ER_LDAP_AUTH_CONN_POOL_INITIALIZING error code, 250
ER_KILLING_THREAD error code, 171	ER_LDAP_AUTH_CONN_POOL_NOT_CREATED error code, 250
ER_KILL_DENIED_ERROR error code, 9	ER_LDAP_AUTH_CREATE_CONNECTION_KEY error code, 253
ER_LANGUAGE_COMPONENT error code, 121	ER_LDAP_AUTH_CREATING_LDAP_CONNECTION error code, 253
ER_LANGUAGE_COMPONENT_CANNOT_UNINSTALL error code, 121	ER_LDAP_AUTH_DEINIT_FAILED error code, 250
ER_LANGUAGE_COMPONENT_CONCURRENCY_LIMIT error code, 128	ER_LDAP_AUTH_DELETING_CONNECTION_KEY error code, 253
ER_LANGUAGE_COMPONENT_CONVERSION error code, 129	ER_LDAP_AUTH_DISTINGUISHED_NAME error code, 254
ER_LANGUAGE_COMPONENT_ERROR error code, 404	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION error code, 254
ER_LANGUAGE_COMPONENT_INFO error code, 404	
ER_LANGUAGE_COMPONENT_INSTALL_ERROR error code, 412	
ER_LANGUAGE_COMPONENT_INTERNAL error code, 128	

ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 250	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP error code, 252
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 250	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED error code, 254
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION error code, 250	ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET error code, 253
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY error code, 252	ER_LDAP_AUTH_POOLED_CONNECTION_KEY error code, 253
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT error code, 252	ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO error code, 250
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION error code, 254	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION error code, 254
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_AVAILABLE error code, 252	ER_LDAP_AUTH_READY_REINITIALIZING error code, 251
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINITIALIZE error code, 252	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL error code, 253
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INITIALIZE error code, 252	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO error code, 254
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCT error code, 252	ER_LDAP_AUTH_STARTING_SASL_PROCESS_SASL error code, 254
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT error code, 252	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT error code, 254
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN error code, 255	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME error code, 251
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET error code, 251	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND error code, 253
ER_LDAP_AUTH_FREEING_CONNECTION error code, 253	ER_LDAP_AUTH_SETTING_USERNAME error code, 251
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL error code, 253	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH error code, 250
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED error code, 347	ER_LDAP_AUTH_STARTED_FOR_USER error code, 254
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE error code, 347	ER_LDAP_AUTH_STARTING_TLS error code, 253
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS error code, 347	ER_LDAP_AUTH_TLS_CONF error code, 250
ER_LDAP_AUTH_GRP_IS_FULL_DN error code, 251	ER_LDAP_AUTH_TLS_CONNECTION error code, 250
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE error code, 347	ER_LDAP_AUTH_USER_AUTH_DATA error code, 251
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO error code, 347	ER_LDAP_AUTH_USER_BIND_FAILED error code, 254
ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL error code, 347	ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS error code, 251
ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL error code, 251	ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED error code, 254
ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO error code, 347	ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO error code, 251
ER_LDAP_AUTH_INFO_USER_MAP error code, 415	ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND error code, 340
ER_LDAP_AUTH_INIT_FAILED error code, 254	ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES error code, 251
ER_LDAP_AUTH_LDAPS error code, 347	ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP error code, 251
ER_LDAP_AUTH_LDAP_INFO_NULL error code, 253	ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED error code, 251
ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT error code, 252	ER_LDAP_EMPTY_USERDN_PASSWORD error code, 354
ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED error code, 252	ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE error code, 348
ER_LDAP_AUTH_METHOD_TO_CLIENT error code, 254	

ER_LDAP_MAPPING_EMPTY_MAPPING error code, 348	ER_LH_AVRO_SCHEMA_DEPTH_EXCEEDS_MAX error code, 126
ER_LDAP_MAPPING_GETTING_NEXT_MAPPING error code, 348	ER_LH_AVRO_TYPE_CANNOT_CONVERT error code, 126
ER_LDAP_MAPPING_GET_USER_PROXY error code, 347	ER_LH_AWS_AUTH_ERR error code, 125
ER_LDAP_MAPPING_INFO error code, 347	ER_LH_BAD_VALUE error code, 124
ER_LDAP_MAPPING_IS_QUOTE error code, 349	ER_LH_CANNOT_CONVERT_STRING error code, 125
ER_LDAP_MAPPING_NON_DESIRED_STATE error code, 349	ER_LH_CHARSET_UNSUPPORTED error code, 125
ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP error code, 348	ER_LH_COLUMN_ENGINE_ATTR_ERR error code, 125
ER_LDAP_MAPPING_PARSING_CURRENT_STATE error code, 348	ER_LH_COLUMN_MAX_ERR error code, 125
ER_LDAP_MAPPING_PARSING_ERROR error code, 348	ER_LH_COLUMN_MISMATCH_ERR error code, 125
ER_LDAP_MAPPING_PARSING_MAPPING_INFO error code, 348	ER_LH_COL_IS_EMPTY error code, 124
ER_LDAP_MAPPING_PROCESS_DELIMITER error code, 348	ER_LH_COL_IS_EMPTY_WARN error code, 124
ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA error code, 348	ER_LH_COL_NAME_DUPLICATE error code, 139
ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL error code, 348	ER_LH_COL_NAME_MISSING error code, 139
ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA error code, 348	ER_LH_COL_NOT_NULLABLE error code, 124
ER_LDAP_MAPPING_PROCESS_MAPPING error code, 348	ER_LH_CP_COMMIT_FAILED error code, 132
ER_LDAP_MAPPING_TRIMMING_SPACES error code, 348	ER_LH_CP_NOT_ENABLED error code, 132
ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP error code, 347	ER_LH_CP_NO_VALIDATION_MODE error code, 132
ER_LH_AVRO_CANNOT_PARSE_HEADER error code, 128	ER_LH_CP_NO_VECTOR_STORE error code, 132
ER_LH_AVRO_DECODING_ERR error code, 127	ER_LH_CSV_TOO_MANY_CHANGES error code, 131
ER_LH_AVRO_ENUM_CANNOT_CONVERT_CHARSET error code, 126	ER_LH_CSV_PARSING_ERR error code, 125
ER_LH_AVRO_ENUM_MISMATCH error code, 126	ER_LH_DATETIME_FORMAT error code, 125
ER_LH_AVRO_FILE_DATA_CORRUPT error code, 126	ER_LH_DECIMAL_OOM_ERR error code, 124
ER_LH_AVRO_FILE_ENDS_UNEXPECTEDLY error code, 126	ER_LH_DECIMAL_PRECISION_EXCEEDS_SCHEMA error code, 124
ER_LH_AVRO_HEADER_METADATA_ERR error code, 127	ER_LH_DECIMAL_UNKNOWN_ERR error code, 124
ER_LH_AVRO_HEADER_MISMATCH error code, 126	ER_LH_DECOMPRESSION_ERR error code, 133
ER_LH_AVRO_HEADER_NO_SCHEMA error code, 127	ER_LH_DELTA_METADATA_READ_ERROR error code, 140
ER_LH_AVRO_INVALID_BLOCK_RECORD_COUNT error code, 126	ER_LH_DELTA_SCHEMA_MISMATCH error code, 139
ER_LH_AVRO_INVALID_BLOCK_SIZE error code, 126	ER_LH_DELTA_UNSUPPORTED_ERROR error code, 140
ER_LH_AVRO_INVALID_NAME_IN_SCHEMA error code, 127	ER_LH_DUPLICATE_FILE error code, 126
ER_LH_AVRO_INVALID_RECORD error code, 133	ER_LH_EMPTY_FILE error code, 126
ER_LH_AVRO_INVALID_UNION error code, 126	ER_LH_EXCEEDS_MAX error code, 125
ER_LH_AVRO_NO_CODEC_IN_HEADER error code, 127	ER_LH_EXCEEDS_MIN error code, 124
	ER_LH_FORMAT_HEADER_NO_MAGIC_BYTES error code, 126
	ER_LH_GENCOL_ERROR error code, 140
	ER_LH_INFER_COL_NAME_MISMATCH error code, 139
	ER_LH_INFER_FILE_HAS_NO_DATA error code, 127
	ER_LH_INFER_JSON_INVALID_SCHEMA error code, 130
	ER_LH_INFER_NO_DATA error code, 128
	ER_LH_INFER_NO_FILES error code, 128
	ER_LH_INFER_NUM_COL_MISMATCH error code, 127
	ER_LH_INFER_WARN_GOT_EXCEPTION error code, 128
	ER_LH_INVALID_JSON_FILE_FORMAT_SCHEMA error code, 130
	ER_LH_INVALID_VALUE_IN_VECTOR error code, 133

ER_LH_JSON_FILE_FORMAT_WARN_INFER_SCHEMA error code, 130	ER_LH_UNSTRUCTURED_TOO_MANY_CHUNKS error code, 133
ER_LH_JSON_PARSING error code, 129	ER_LH_UNSTRUCTURED_TRUNCATION_ERROR error code, 133
ER_LH_NO_FILES_FOUND error code, 126	ER_LH_USER_DATA_ACCESS_FAILED error code, 130
ER_LH_NO_FILES_FOUND_NO_SECURE_FILE_PRIV error code, 139	ER_LH_VECTOR_TOO_MANY_ENTRIES error code, 132
ER_LH_NO_SEGMENTS_GENERATED error code, 131	ER_LH_WARN_COL_MISSING_NOT_NULLABLE error code, 124
ER_LH_OOM error code, 127	ER_LH_WARN_DATETIME_MULTIPLE_PARAM_USE error code, 140
ER_LH_OUT_OF_RANGE error code, 125	ER_LH_WARN_DECIMAL_ROUNDING error code, 124
ER_LH_PARQUET_CANNOT_LOCATE_OFFSET error code, 127	ER_LH_WARN_EXCEEDS_MAX_TRUNCATING error code, 125
ER_LH_PARQUET_CANNOT_LOCATE_SCHEMA error code, 127	ER_LH_WARN_EXCEEDS_MIN_TRUNCATING error code, 125
ER_LH_PARQUET_CANNOT_READ_HEADER error code, 128	ER_LH_WARN_INFER_SKIPPED_FILES error code, 127
ER_LH_PARQUET_CANT_OPEN_FILE error code, 128	ER_LH_WARN_INFER_SKIPPED_LINES error code, 127
ER_LH_PARQUET_DECIMAL_CONVERSION_ERR error code, 125	ER_LH_WARN_INFER_USE_DEFAULT_COL_NAMES error code, 128
ER_LH_PARQUET_NON_UTF8_FILE_ENC error code, 127	ER_LH_WARN_INFER_USE_DEFAULT_DELIMITERS error code, 133
ER_LH_PARQUET_ROW_GROUP_SIZE_EXCEEDS_MAX error code, 127	ER_LH_WARN_SUMMARY error code, 132
ER_LH_PARQUET_SCHEMA_MISMATCH error code, 127	ER_LH_WARN_TRUNCATED error code, 125
ER_LH_PARQUET_TYPE_CANNOT_CONVERT error code, 127	ER_LH_WARN_VECTOR_LOSSY_CONVERSION error code, 133
ER_LH_REAL_IS_NAN error code, 125	ER_LIBRARIES_NOT_SUPPORTED error code, 132
ER_LH_RESOURCE_PRINCIPAL_BUCKET_ERR error code, 126	ER_LIBRARY_INVALID error code, 133
ER_LH_RESOURCE_PRINCIPAL_ERR error code, 125	ER_LIMITED_PART_RANGE error code, 34
ER_LH_STRING_TOO_LONG error code, 125	ER_LOAD_BULK_DATA_FAILED error code, 120
ER_LH_TOO_LARGE_ROW_ERR error code, 128	ER_LOAD_BULK_DATA_UNSORTED error code, 118
ER_LH_TOO_LARGE_VALUE_ERR error code, 128	ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL error code, 120
ER_LH_UNSTRUCTURED_ENCODING_ERR error code, 131	ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG error code, 396
ER_LH_UNSTRUCTURED_FILE_PARSE_ERR error code, 130	ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD error code, 120
ER_LH_UNSTRUCTURED_FILE_TOO_LARGE error code, 131	ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG error code, 396
ER_LH_UNSTRUCTURED_FILE_TYPE_MISMATCH_ERR error code, 131	ER_LOAD_BULK_JSON_ERROR error code, 416
ER_LH_UNSTRUCTURED_INVALID_LANGUAGE error code, 132	ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY error code, 154
ER_LH_UNSTRUCTURED_NO_DATA_FOUND error code, 130	ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR error code, 27
ER_LH_UNSTRUCTURED_OBJ_READ_ERR error code, 131	ER_LOAD_INFO error code, 8
ER_LH_UNSTRUCTURED_OCI_GENAI_FAILURE error code, 139	ER_LOCAL_VARIABLE error code, 17
ER_LH_UNSTRUCTURED_PAGE_CHUNK_WARN error code, 133	ER_LOCKING_SERVICE_DEADLOCK error code, 66
ER_LH_UNSTRUCTURED_PARTIAL_FILE_PARSE_ERR error code, 139	ER_LOCKING_SERVICE_TIMEOUT error code, 67
ER_LH_UNSTRUCTURED_SCHEMA_ERR error code, 131	ER_LOCKING_SERVICE_WRONG_NAME error code, 66
	ER_LOCK_ABORTED error code, 43
	ER_LOCK_DEADLOCK error code, 16
	ER_LOCK_NOWAIT error code, 77

ER_LOCK_ORDER_DEPENDENCIES_SYNTAX error code, 354	ER_MALFORMED_GTID_SPECIFICATION error code, 49
ER_LOCK_ORDER_FAILED_READ_FILE error code, 354	ER_MALFORMED_PACKET error code, 53
ER_LOCK_ORDER_FAILED_WRITE_FILE error code, 354	ER_MANDATORY_ROLE error code, 80
ER_LOCK_ORDER_INIT_FAILED error code, 353	ER_MASTER_KEY_ROTATION_BINLOG_FAILED error code, 70
ER_LOCK_ORDER_MESSAGE error code, 354	ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE error code, 70
ER_LOCK_ORDER_SCANNER_SYNTAX error code, 355	ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE error code, 70
ER_LOCK_OR_ACTIVE_TRANSACTION error code, 15	ER_MAXVALUE_IN_VALUES_IN error code, 41
ER_LOCK_REFUSED_BY_ENGINE error code, 70	ER_MAX_PREPARED_STMT_COUNT_REACHED error code, 31
ER_LOCK_TABLE_FULL error code, 16	ER_MDL_OUT_OF_RESOURCES error code, 106
ER_LOCK_WAIT_TIMEOUT error code, 16	ER_MECAB_CHARSET_LOADED error code, 207
ER_LOG_BIN_BETTER_WITH_NAME error code, 151	ER_MECAB_CREATE_LATTICE_FAILED error code, 207
ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP error code, 402	ER_MECAB_CREATING_MODEL error code, 206
ER_LOG_CANNOT_WRITE error code, 141	ER_MECAB_FAILED_TO_CREATE_MODEL error code, 206
ER_LOG_CANNOT_WRITE_EXTENDED error code, 357	ER_MECAB_FAILED_TO_CREATE_TRIGGER error code, 207
ER_LOG_CLIENT_INTERACTION_TIMEOUT error code, 414	ER_MECAB_NOT_SUPPORTED error code, 206
ER_LOG_COMPONENT_CANNOT_INIT error code, 371	ER_MECAB_NOT_VERIFIED error code, 206
ER_LOG_COMPONENT_FLUSH_FAILED error code, 379	ER_MECAB_OOM_WHILE_PARSING_TEXT error code, 207
ER_LOG_DEPRECATED_NON_COMPOSABLE_MULTIPLE_ERROR error code, 415	ER_MECAB_PARSE_FAILED error code, 207
ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE error code, 150	ER_MECAB_UNSUPPORTED_CHARSET error code, 207
ER_LOG_FILE_CANNOT_OPEN error code, 217	ER_MESSAGE_AND_STATEMENT error code, 42
ER_LOG_FILE_INVALID error code, 150	ER_MFA_METHODS_IDENTICAL error code, 113
ER_LOG_GENERAL_CANNOT_OPEN error code, 141	ER_MFA_METHODS_INVALID_ORDER error code, 113
ER_LOG_IN_USE error code, 26	ER_MFA_METHOD_EXISTS error code, 112
ER_LOG_OUTPUT_CONTRADICTION error code, 150	ER_MFA_METHOD_NOT_EXISTS error code, 112
ER_LOG_PARTITION_PREFIX_KEY_NOT_SUPPORTED error code, 415	ER_MFA_PLUGIN_NOT_LOADED error code, 384
ER_LOG_PRINTF_MSG error code, 204	ER_MFA_USER_ATTRIBUTES_CORRUPT error code, 384
ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOR_SECOND error code, 359	ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE error code, 201
ER_LOG_PURGE_NO_FILE error code, 38	ER_MISPLACED_TABLE_TO_DD_OOM error code, 361
ER_LOG_PURGE_UNKNOWN_ERR error code, 26	ER_MISPLACED_INTO error code, 104
ER_LOG_SANITIZATION error code, 414	ER_MISSING_ACL_SYSTEM_TABLE error code, 196
ER_LOG_SLOW_CANNOT_OPEN error code, 141	ER_MISSING_CURRENT_PASSWORD error code, 99
ER_LOG_SYSLOG_CANNOT_OPEN error code, 141	ER_MISSING_GRANT_SYSTEM_TABLE error code, 196
ER_LONGITUDE_OUT_OF_RANGE error code, 80	ER_MISSING_HA_CREATE_OPTION error code, 58
ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI error code, 150	ER_MISSING_JSON_TABLE_VALUE error code, 83
ER_LOWER_CASE_TABLE_NAMES_USING_0 error code, 150	ER_MISSING_JSON_VALUE error code, 105
ER_LOWER_CASE_TABLE_NAMES_USING_2 error code, 150	ER_MISSING_KEY error code, 57
ER_MALFORMED_GTID_SET_ENCODING error code, 49	ER_MISSING_SKIP_REPLICA error code, 20
ER_MALFORMED_GTID_SET_SPECIFICATION error code, 49	ER_MISSING_TABLESPACE_FILE error code, 80
	ER_MIXING_NOT_ALLOWED error code, 17
	ER_MIX_HANDLER_ERROR error code, 33
	ER_MIX_OF_GROUP_FUNC_AND_FIELDS error code, 12
	ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2 error code, 63

ER_MTA_CANT_PARALLEL error code, 48	ER_NDB_LOG_ENTRY_WITH_PREFIX error code, 189
ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS error code, 51	ER_NDB_REPLICATION_SCHEMA_ERROR error code, 39
ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX error code, 55	ER_NEED_FILE_INSTEAD_OF_DIR error code, 151
ER_MTA_FEATURE_IS_NOT_SUPPORTED error code, 48	ER_NEED_LOG_BIN error code, 151
ER_MTA_INCONSISTENT_DATA error code, 48	ER_NEED_REPREPARE error code, 39
ER_MTA_RECOVERY_FAILURE error code, 51	ER_NETWORK_NAMESPACES_NOT_SUPPORTED error code, 352
ER_MTA_RESET_WORKERS error code, 51	ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG error code, 352
ER_MTA_UPDATED_DBS_GREATER_MAX error code, 48	ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD error code, 352
ER_MTR_MSG_1 error code, 380	ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE error code, 332
ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME error code, 103	ER_NET_ERROR_ON_WRITE error code, 13
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR error code, 33	ER_NET_FCNTL_ERROR error code, 13
ER_MULTIPLE_INTO_CLAUSES error code, 104	ER_NET_OK_PACKET_TOO_LARGE error code, 62
ER_MULTIPLE_JSON_VALUES error code, 105	ER_NET_PACKETS_OUT_OF_ORDER error code, 13
ER_MULTIPLE_PRI_KEY error code, 7	ER_NET_PACKET_TOO_LARGE error code, 13
ER_MULTI_UPDATE_KEY_CONFLICT error code, 44	ER_NET_READ_ERROR error code, 13
ER_MUST_CHANGE_PASSWORD error code, 52	ER_NET_READ_ERROR_FROM_PIPE error code, 13
ER_MUST_CHANGE_PASSWORD_LOGIN error code, 55	ER_NET_READ_INTERRUPTED error code, 13
ER_MYINIT_FAILED error code, 149	ER_NET_UNCOMPRESS_ERROR error code, 13
ER_MYISAM_CHECK_METHOD_ERROR error code, 203	ER_NET_WAIT_ERROR error code, 353
ER_MYISAM_CRASHED_ERROR error code, 203	ER_NET_WAIT_ERROR2 error code, 375
ER_MYISAM_CRASHED_ERROR_IN error code, 155	ER_NET_WRITE_INTERRUPTED error code, 13
ER_MYISAM_CRASHED_ERROR_IN_THREAD error code, 155	ER_NEW_ABORTING_CONNECTION error code, 14
ER_MYSQLBACKUP_CLIENT_MSG error code, 115	ER_NO error code, 3
ER_MYSQLBACKUP_MSG error code, 357	ER_NONEXISTING_GRANT error code, 12
ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD error code, 344	ER_NONEXISTING_PROC_GRANT error code, 27
ER_MY_MALLOC_GETPROCADDRESS_FAILED error code, 386	ER_NONEXISTING_TABLE_GRANT error code, 12
ER_MY_MALLOC_LOADLIBRARY_FAILED error code, 386	ER_NONPOSITIVE_RADIUS error code, 85
ER_MY_MALLOC_USING_JEMALLOC error code, 386	ER_NONPOSITIVE_TABLE_NAME error code, 7
ER_MY_MALLOC_USING_STD_MALLOC error code, 386	ER_NONUPDATEABLE_COLUMN error code, 24
ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STD error code, 182	ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT error code, 94
ER_M_BIGGER_THAN_D error code, 28	ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN error code, 64
ER_NAME_BECOMES_EMPTY error code, 31	ER_NON_DML_DYNAMIC_PARAMETERS error code, 131
ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE error code, 201	ER_NON_GROUPING_FIELD_USED error code, 31
ER_NATIVE_FCT_NAME_COLLISION error code, 37	ER_NON_INSERTABLE_TABLE error code, 31
ER_NDBINFO_NOT_UPGRADING_SCHEMA error code, 363	ER_NON_RO_SELECT_DISABLE_TIMER error code, 59
ER_NDBINFO_UPGRADING_SCHEMA error code, 363	ER_NON_SCALAR_USED_AS_KEY error code, 130
ER_NDBINFO_UPGRADING_SCHEMA_FAIL error code, 363	ER_NON_UNIQ_ERROR error code, 6
ER_NDB_LOG_ENTRY error code, 189	ER_NON_UPDATABLE_TABLE error code, 21
	ER_NORMAL_SERVER_SHUTDOWN error code, 331
	ER_NOTE_COMPONENT_FIREWALL_RELOAD error code, 424
	ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME error code, 393
	ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS error code, 399
	ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS error code, 399

ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER error code, 374	ER_NO_DEFAULT error code, 17
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY error code, 374	ER_NO_DEFAULT_FOR_FIELD error code, 25
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODEL error code, 374	ER_NO_DEFAULT_FOR_VIEW_FIELD error code, 28
ER_NOTE_KEYRING_COMPONENT_AES_OPERATION error code, 374	ER_NO_ERROR_LOG_PARSER_CONFIGURED error code, 370
ER_NOTE_KEYRING_COMPONENT_EMPTY_DATA_ID error code, 413	ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATE error code, 38
ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED error code, 375	ER_NO_FT_MATERIALIZED_SUBQUERY error code, 34
ER_NOTE_KEYRING_COMPONENT_INITIALIZED error code, 374	ER_NO_PARTITION_FOR_GIVEN_VALUE error code, 30
ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ERROR error code, 375	ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT error code, 37
ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ERROR error code, 413	ER_NO_PARTS_ERROR error code, 33
ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR error code, 413	ER_NO_PARTITION_FOR_INNOVATION_RELEASES error code, 422
ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR error code, 413	ER_NO_PARTITION_FOR_SHARED_LIBRARY error code, 336
ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR error code, 375	ER_NO_PERMISSION_TO_CREATE_USER error code, 16
ER_NOTE_KEYRING_COMPONENT_NOT_INITIALIZED error code, 413	ER_NO_QUERY_PLAN_FOUND error code, 131
ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND error code, 374	ER_NO_REFERENCED_ROW error code, 16
ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED error code, 375	ER_NO_REFERENCED_ROW_2 error code, 30
ER_NOTE_KEYRING_COMPONENT_STORE_FAILED error code, 375	ER_NO_SECURE_TRANSPORTS_CONFIGURED error code, 68
ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_LENGTH error code, 374	ER_NO_SESSION_TEMP error code, 99
ER_NOT_ALLOWED_COMMAND error code, 12	ER_NO_SUCH_DB error code, 72
ER_NOT_ALLOWED_WITH_START_TRANSACTION error code, 106	ER_NO_SUCH_INDEX error code, 8
ER_NOT_FORM_FILE error code, 5	ER_NO_SUCH_TABLE error code, 12
ER_NOT_HINT_UPDATABLE_VARIABLE error code, 81	ER_NO_SUCH_THREAD error code, 9
ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS error code, 85	ER_NO_SUCH_USER error code, 30
ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS error code, 80	ER_NO_SUPER_WITHOUT_USER_PLUGIN error code, 161
ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS error code, 85	ER_NO_SYSTEM_SCHEMA_ACCESS error code, 75
ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS error code, 217	ER_NO_SYSTEM_TABLESPACE_ACCESS error code, 75
ER_NOT_KEYFILE error code, 5	ER_NO_SYSTEM_TABLE_ACCESS error code, 75
ER_NOT_RIGHT_NOW error code, 149	ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE error code, 75
ER_NOT_SUPPORTED_AUTH_MODE error code, 19	ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE error code, 75
ER_NOT_SUPPORTED_YET error code, 18	ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE error code, 76
ER_NOT_VALID_PASSWORD error code, 52	ER_NO_SYSTEM_VIEW_ACCESS error code, 80
ER_NO_ACCESS_TO_NATIVE_FCT error code, 76	ER_NO_TABLES_USED error code, 9
ER_NO_BINARY_LOGGING error code, 26	ER_NO_THD_NO_UUID error code, 144
ER_NO_BINLOG_ERROR error code, 34	ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA error code, 31
ER_NO_CSV_NO_LOG_TABLES error code, 150	ER_NO_UNIQUE_LOGFILE error code, 9
ER_NO_DB_ERROR error code, 6	ER_NPIPE_CANT_CREATE error code, 191
	ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR error code, 166
	ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR error code, 166
	ER_NPIPE_PIPE_ALREADY_IN_USE error code, 166
	ER_NULL_CANT_BE_PERSISTED_FOR_READONLY error code, 121
	ER_NULL_COLUMN_IN_INDEX error code, 11

ER_NULL_IN_VALUES_LESS_THAN error code, 36	ER_PARTITION_EXCHANGE_FOREIGN_KEY error code, 47
ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE error code, 68	ER_PARTITION_EXCHANGE_PART_TABLE error code, 46
ER_NUM_THREADS_STILL_ALIVE error code, 406	ER_PARTITION_EXCHANGE_TEMP_TABLE error code, 46
ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION error code, 358	ER_PARTITION_FIELDS_TOO_LONG error code, 41
ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION error code, 359	ER_PARTITION_FUNCTION_FAILURE error code, 34
ER_OLD_FILE_FORMAT error code, 30	ER_PARTITION_FUNCTION_IS_NOT_ALLOWED error code, 36
ER_OLD_KEYFILE error code, 5	ER_PARTITION_FUNC_NOT_ALLOWED_ERROR error code, 32
ER_OLD_TEMPORALS_UPGRADED error code, 56	ER_PARTITION_INCONSISTENT error code, 12
ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG error code, 46	ER_PARTITION_HANDLER_ADMIN_MSG error code, 203
ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326 error code, 84	ER_PARTITION_INSTEAD_OF_SUBPARTITION error code, 47
ER_ONLY INTEGERS_ALLOWED error code, 37	ER_PARTITION_MAXVALUE_ERROR error code, 32
ER_ONLY_ON_RANGE_LIST_PARTITION error code, 34	ER_PARTITION_MERGE_ERROR error code, 36
ER_OOM error code, 149	ER_PARTITION_MGMT_ON_NONPARTITIONED error code, 33
ER_OOM_SAVE_GTIDS error code, 331	ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE error code, 191
ER_OPEN_AS_READONLY error code, 5	ER_PARTITION_NAME error code, 40
ER_OPEN_ROLE_TABLES error code, 73	ER_PARTITION_NOT_DEFINED_ERROR error code, 33
ER_OPERAND_COLUMNS error code, 18	ER_PARTITION_NOT_TEMPORARY error code, 36
ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY error code, 112	ER_PARTITION_PREFIX_KEY_NOT_SUPPORTED error code, 129
ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE error code, 115	ER_PARTITION_REQUIRES_VALUES_ERROR error code, 32
ER_OPTION_PREVENTS_STATEMENT error code, 21	ER_PARTITION_WRONG_NO_PART_ERROR error code, 32
ER_OPT_WRONG_TREE error code, 140	ER_PARTITION_WRONG_NO_SUBPART_ERROR error code, 32
ER_OUTOFMEMORY error code, 5	ER_PARTITION_WRONG_VALUES_ERROR error code, 32
ER_OUT_OF_RESOURCES error code, 5	ER_PART_EXPR_TOO_LONG error code, 80
ER_OUT_OF_SORTMEMORY error code, 5	ER_PASSWORD_ANONYMOUS_USER error code, 11
ER_PAGE_TRACKING_CANNOT_PURGE error code, 93	ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE error code, 100
ER_PAGE_TRACKING_NOT_STARTED error code, 93	ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH error code, 83
ER_PAGE_TRACKING_RANGE_NOT_TRACKED error code, 93	ER_PASSWORD_EXPIRE_ANONYMOUS_USER error code, 58
ER_PARSER_TRACE error code, 140	ER_PASSWORD_FORMAT error code, 53
ER_PARSE_ERROR error code, 7	ER_PASSWORD_NOT_ALLOWED error code, 11
ER_PARSE_ERROR_IN_DIGEST_FN error code, 83	ER_PASSWORD_NO_MATCH error code, 11
ER_PARSING_VIEW error code, 144	ER_PATH_IN_DATADIR error code, 80
ER_PARTIAL_REVOKES_EXIST error code, 100	ER_PATH_LENGTH error code, 43
ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXIST error code, 100	ER_PERFORMANCE_SCHEMA_VERSION_CHANGE error code, 402
ER_PARTITIONS_MUST_BE_DEFINED_ERROR error code, 32	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOT error code, 194
ER_PARTITION_CLAUSE_ON_NONPARTITIONED error code, 47	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 194
ER_PARTITION_COLUMN_LIST_ERROR error code, 41	ER_PERFSCHEMA_INIT_FAILED error code, 151
ER_PARTITION_CONST_DOMAIN_ERROR error code, 36	
ER_PARTITION_ENTRY_ERROR error code, 33	
ER_PARTITION_EXCHANGE_DIFFERENT_OPTION error code, 46	

ER_PERFSHEMA_TABLES_INIT_FAILED error code, 195	ER_PLUGIN_FAILED_DEINITIALIZATION error code, 180
ER_PERSISTED_VARIABLES_DECRYPTION_FAILED error code, 385	ER_PLUGIN_FAILED_TO_OPEN_TABLE error code, 335
ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED error code, 385	ER_PLUGIN_FAILED_TO_OPEN_TABLES error code, 335
ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED error code, 385	ER_PLUGIN_FORCING_SHUTDOWN error code, 181
ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT error code, 386	ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES error code, 181
ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED error code, 385	ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION error code, 181
ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND error code, 385	ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN error code, 181
ER_PERSISTENT_PRIVILEGES_BOOTSTRAP error code, 195	ER_PLUGIN_INIT_FAILED error code, 153
ER_PERSIST_ONLY_ACCESS_DENIED_ERROR error code, 80	ER_PLUGIN_INSTALL_ERROR error code, 340
ER_PERSIST_OPTION_HOST_TRUNCATED error code, 352	ER_PLUGIN_INVALID_TABLE_DEFINITION error code, 378
ER_PERSIST_OPTION_STATUS error code, 217	ER_PLUGIN_IS_NOT_LOADED error code, 34
ER_PERSIST_OPTION_USER_TRUNCATED error code, 352	ER_PLUGIN_IS_PERMANENT error code, 44
ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_REPO error code, 201	ER_PLUGIN_LOAD_OPTIONS_IGNORED error code, 358
ER_PFS_MALLOC_ARRAY_OOM error code, 202	ER_PLUGIN_LOAD_PARAMETER_TOO_LONG error code, 181
ER_PFS_MALLOC_ARRAY_OVERFLOW error code, 202	ER_PLUGIN_NOT_EARLY error code, 96
ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED error code, 197	ER_PLUGIN_NOT_EARLY_DUP error code, 353
ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE error code, 337	ER_PLUGIN_NO_INSTALL error code, 46
ER_PID_FILE_PRIV_DIRECTORY_INSECURE error code, 255	ER_PLUGIN_NO_INSTALL_DUP error code, 353
ER_PK_INDEX_CANT_BE_INVISIBLE error code, 73	ER_PLUGIN_NO_UNINSTALL error code, 45
ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED error code, 66	ER_PLUGIN_OOM error code, 181
ER_PLUGINS_SHUTDOWN_END error code, 405	ER_PLUGIN_PARSING_OPTIONS_FAILED error code, 181
ER_PLUGINS_SHUTDOWN_START error code, 405	ER_PLUGIN_REGISTRATION_DONE error code, 112
ER_PLUGIN_BAD_OPTIONS error code, 181	ER_PLUGIN_REGISTRATION_FAILED error code, 180
ER_PLUGIN_CANNOT_BE_UNINSTALLED error code, 56	ER_PLUGIN_REQUIRES_REGISTRATION error code, 112
ER_PLUGIN_CANT_LOAD error code, 181	ER_PLUGIN_SHUTTING_DOWN_PLUGIN error code, 180
ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE error code, 181	ER_PLUGIN_UNINSTALL_ERROR error code, 340
ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS error code, 182	ER_PLUGIN_UNKNOWN_VARIABLE_TYPE error code, 181
ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLE error code, 216	ER_PLUGIN_VARIABLE_MISSING_NAME error code, 181
ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE error code, 216	ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL error code, 181
ER_PLUGIN_DELETE_BUILTIN error code, 39	ER_PLUGIN_VARIABLE_SET_READ_ONLY error code, 181
ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS error code, 171	ER_PLUGIN_VARIABLES_WITHOUT_SLOWLOG error code, 145
ER_PLUGIN_DISABLED error code, 181	ER_POLYGON_TOO_LARGE error code, 87
ER_PLUGIN_EXCEPTION_OPERATION_FAILED error code, 396	ER_PREPARE_FOR_PRIMARY_ENGINE error code, 379
	ER_PREPARE_FOR_SECONDARY_ENGINE error code, 349
	ER_PREVENTS_VARIABLE_WITHOUT_RBR error code, 64
	ER_PRIMARY_CANT_HAVE_NULL error code, 14
	ER_PRIVILEGE_DEREGISTRATION error code, 400

ER_PRIVILEGE_REGISTRATION error code, 400
 ER_PRIVILEGE_SYSTEM_INIT_FAILED error code, 195
 ER_PROCAccess_DENIED_ERROR error code, 26
 ER_PROC_AUTO_GRANT_FAIL error code, 27
 ER_PROC_AUTO_REVOKE_FAIL error code, 27
 ER_PROTOCOL_COMPRESSION_RESET_LOG error code, 357
 ER_PS_MANY_PARAM error code, 26
 ER_PS_NO_RECURSION error code, 30
 ER_QUALIFY_WITHOUT_WINDOW_FUNCTION error code, 123
 ER_QUERY_INTERRUPTED error code, 22
 ER_QUERY_ON_FOREIGN_DATA_SOURCE error code, 29
 ER_QUERY_TIMEOUT error code, 59
 ER_RANGE_NOT_INCREASING_ERROR error code, 32
 ER_READING_TABLE_FAILED error code, 154
 ER_READY error code, 8
 ER_READ_LOG_EVENT_FAILED error code, 200
 ER_READ_ONLY_MODE error code, 53
 ER_READ_ONLY_TRANSACTION error code, 16
 ER REALLY_RUN_AS_ROOT error code, 148
 ER_RECORD_FILE_FULL error code, 10
 ER_RECOVERING_TABLE error code, 182
 ER_REDUCED_DBLWR_FILE_CORRUPTED error code, 401
 ER_REDUCED_DBLWR_PAGE_FOUND error code, 401
 ER_REFERENCED_TRG_DOES_NOT_EXIST error code, 58
 ER_REGEX_BAD_ESCAPE_SEQUENCE error code, 84
 ER_REGEX_BAD_INTERVAL error code, 84
 ER_REGEX_BUFFER_OVERFLOW error code, 84
 ER_REGEX_ERROR error code, 12
 ER_REGEX_ILLEGAL_ARGUMENT error code, 84
 ER_REGEX_INDEX_OUTOFBOUNDS_ERROR error code, 84
 ER_REGEX_INTERNAL_ERROR error code, 84
 ER_REGEX_INVALID_BACK_REF error code, 85
 ER_REGEX_INVALID_CAPTURE_GROUP_NAME error code, 99
 ER_REGEX_INVALID_FLAG error code, 100
 ER_REGEX_INVALID_RANGE error code, 85
 ER_REGEX_LOOK_BEHIND_LIMIT error code, 85
 ER_REGEX_MAX_LT_MIN error code, 84
 ER_REGEX_MISMATCHED_PAREN error code, 84
 ER_REGEX_MISSING_CLOSE_BRACKET error code, 85
 ER_REGEX_MISSING_FILE error code, 114
 ER_REGEX_MISSING_ICU_DATADIR error code, 384
 ER_REGEX_MISSING_RESOURCE error code, 114
 ER_REGEX_PATTERN_TOO_BIG error code, 85
 ER_REGEX_RULE_SYNTAX error code, 84
 ER_REGEX_STACK_OVERFLOW error code, 85
 ER_REGEX_TIME_OUT error code, 85
 ER_REGEX_UNIMPLEMENTED error code, 84
 ER_REGEX_NUMBER_TOO_BIG error code, 108
 ER_RELAY_LOG_FAIL error code, 26
 ER_RELAY_LOG_INIT error code, 26
 ER_RELAY_LOG_SPACE_LIMIT_DISABLED error code, 338
 ER_RELOAD_KEYRING_FAILURE error code, 111
 ER_REMOVED_SPACES error code, 31
 ER_RENAMED_NAME error code, 40
 ER_RENAME_ROLE error code, 74
 ER_REORG_HASH_ONLY_ON_SAME_NO error code, 33
 ER_REORG_NO_PARAM_ERROR error code, 34
 ER_REORG_OUTSIDE_RANGE error code, 34
 ER_REORG_PARTITION_NOT_EXIST error code, 34
 ER_REPLACE_INACCESSIBLE_ROWS error code, 61
 ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK error code, 395
 ER_REPLICA_AM_INIT_REPOSITORY error code, 56
 ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GFR error code, 372
 ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND error code, 372
 ER_REPLICA_CANT_CREATE_CONVERSION error code, 43
 ER_REPLICA_CANT_USE_TMPDIR error code, 178
 ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED error code, 178
 ER_REPLICA_CHANNEL_DOES_NOT_EXIST error code, 62
 ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP error code, 58
 ER_REPLICA_CHANNEL_MUST_STOP error code, 62
 ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG error code, 62
 ER_REPLICA_CHANNEL_NOT_RUNNING error code, 62
 ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED error code, 67
 ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER error code, 63
 ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP error code, 63
 ER_REPLICA_CHANNEL_WAS_NOT_RUNNING error code, 63
 ER_REPLICA_CHANNEL_WAS_RUNNING error code, 63
 ER_REPLICA_CM_INIT_REPOSITORY error code, 56
 ER_REPLICA_CONFIGURATION error code, 51
 ER_REPLICA_CORRUPT_EVENT error code, 38
 ER_REPLICA_CREATE_EVENT_FAILURE error code, 332
 ER_REPLICA_FATAL_ERROR error code, 332
 ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE error code, 57
 ER_REPLICA_HEARTBEAT_FAILURE error code, 332

ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE error code, 39	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITHOUT_ERROR error code, 120
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE error code, 44	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITHOUT_ERROR error code, 397
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE error code, 44	ER_RESERVED_SYNTAX error code, 26
ER_REPLICA_IGNORED_SSL_PARAMS error code, 20	ER_RESERVED_TABLESPACE_NAME error code, 87
ER_REPLICA_IGNORED_TABLE error code, 18	ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE error code, 76
ER_REPLICA_IGNORE_SERVER_IDS error code, 41	ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER error code, 40
ER_REPLICA_INCIDENT error code, 332	ER_RESOURCE_GROUP_BIND_FAILED error code, 82
ER_REPLICA_KILLED_AFTER_RECONNECT error code, 201	ER_RESOURCE_GROUP_BUSY error code, 82
ER_REPLICA_MAX_CHANNELS_EXCEEDED error code, 62	ER_RESOURCE_GROUP_DISABLED error code, 82
ER_REPLICA_MULTIPLE_CHANNELS_CMD error code, 62	ER_RESOURCE_GROUP_EXISTS error code, 82
ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY error code, 62	ER_RESOURCE_GROUP_IS_DISABLED error code, 197
ER_REPLICA_NOT_RUNNING error code, 15	ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED error code, 196
ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 201	ER_RESOURCE_GROUP_NOT_EXISTS error code, 82
ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL error code, 87	ER_RESOURCE_GROUP_POST_INIT_FAILED error code, 194
ER_REPLICA_RECONNECT_FAILED error code, 200	ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED error code, 194
ER_REPLICA_RELAY_LOG_PURGE_FAILED error code, 195	ER_RESOURCE_GROUP_VALIDATION_FAILED error code, 196
ER_REPLICA_RELAY_LOG_READ_FAILURE error code, 332	ER_RESTART_RECEIVED_INFO error code, 205
ER_REPLICA_RELAY_LOG_TRUNCATE_INFO error code, 195	ER_RESTART_SERVER_FAILED error code, 85
ER_REPLICA_RELAY_LOG_WRITE_FAILURE error code, 332	ER_RESULT_SIZE_LIMIT_EXCEEDED error code, 128
ER_REPLICA_SILENT_RETRY_TRANSACTION error code, 51	ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT error code, 198
ER_REPLICA_SOURCE_COM_FAILURE error code, 332	ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY error code, 197
ER_REPLICA_SQL_THREAD_MUST_STOP error code, 58	ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE error code, 197
ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTID error code, 165	ER_RES_GRP_FEATURE_NOT_AVAILABLE error code, 198
ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTID error code, 165	ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED error code, 198
ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTID error code, 165	ER_RES_GRP_INVALID_THREAD_PRIORITY error code, 198
ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTID error code, 165	ER_RES_GRP_INVALID_VCPU_ID error code, 204
ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED error code, 166	ER_RES_GRP_INVALID_VCPU_RANGE error code, 204
ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION error code, 165	ER_RES_GRP_SET_THREAD_PRIORITY_FAILED error code, 197
ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION error code, 165	ER_RES_GRP_SET_THR_AFFINITY_FAILED error code, 197
ER_REPLICA_THREAD error code, 15	ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED error code, 197
ER_REPLICA_WORKER_STOPPED_PREVIOUS_THREAD error code, 59	ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED error code, 198
ER_REQUIRES_PRIMARY_KEY error code, 14	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED error code, 198
ER_REQUIRE_ROW_FORMAT_INVALID_VALUE error code, 103	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED error code, 198

ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED error code, 197	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL error code, 373
ER_RETRYING_REPAIR_WITHOUT_QUICK error code, 182	ER_RPL_ASYNC_REPLICA_IO_THD_FETCH_GROUP_MAJORITY error code, 411
ER_RETRYING_REPAIR_WITH_KEYCACHE error code, 182	ER_RPL_ASYNC_SENDER_ADDED error code, 371
ER_REVOKE_GRANTS error code, 20	ER_RPL_ASYNC_SENDER_REMOVED error code, 371
ER_REWRITER_LOAD_FAILED error code, 217	ER_RPL_BINLOG_FILTERS_OOM error code, 147
ER_REWRITER_OOM error code, 217	ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED error code, 153
ER_REWRITER_QUERY_ERROR_MSG error code, 215	ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO error code, 171
ER_REWRITER_QUERY_FAILED error code, 215	ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT error code, 171
ER_REWRITER_READ_FAILED error code, 217	ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA error code, 171
ER_REWRITER_TABLE_MALFORMED_ERROR error code, 217	ER_RPL_BINLOG_STARTING_DUMP error code, 171
ER_ROLE_GRANTED_TO_ITSELF error code, 110	ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED error code, 153
ER_ROLE_NOT_GRANTED error code, 74	ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED error code, 153
ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG error code, 200	ER_RPL_CANNOT_OPEN_RELAY_LOG error code, 382
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SELECTOR error code, 47	ER_RPL_CANT_ADD_DO_TABLE error code, 149
ER_ROW_DOES_NOT_MATCH_PARTITION error code, 47	ER_RPL_CANT_ADD_IGNORE_TABLE error code, 149
ER_ROW_IN_WRONG_PARTITION error code, 55	ER_RPL_CANT_CREATE_REPLICA_THREAD error code, 174
ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR error code, 155	ER_RPL_CANT_FIND_FOLLOWUP_FILE error code, 176
ER_ROW_IS_REFERENCED error code, 17	ER_RPL_CANT_HAVE_SAME_BASENAME error code, 192
ER_ROW_IS_REFERENCED_2 error code, 30	ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO error code, 178
ER_ROW_SINGLE_PARTITION_FIELD_ERROR error code, 41	ER_RPL_CANT_MAKE_PATHS error code, 151
ER_RPL_AM_INIT_INFO_MSG error code, 203	ER_RPL_CANT_OPEN_INFO_TABLE error code, 166
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT error code, 371	ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO error code, 179
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM error code, 371	ER_RPL_CANT_SCAN_INFO_TABLE error code, 167
ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST error code, 371	ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP error code, 97
ER_RPL_ASYNC_CHECK_CONNECTION_ERROR error code, 411	ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID error code, 167
ER_RPL_ASYNC_GET_GROUP_MEMBERSHIP_DETAILS_ERROR error code, 411	ER_RPL_CORRUPTED_INFO_TABLE error code, 167
ER_RPL_ASYNC_MANAGED_NAME_ADDED error code, 371	ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE error code, 167
ER_RPL_ASYNC_MANAGED_NAME_REMOVED error code, 371	ER_RPL_CRYPT_ERROR error code, 93
ER_RPL_ASYNC_MONITOR_IO_THD_FETCH_GROUP_MAJORITY error code, 411	ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY error code, 93
ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTOR error code, 397	ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 93
ER_RPL_ASYNC_READ_FAILOVER_TABLE error code, 372	ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 91
ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFFSET error code, 107	ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 92
ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE error code, 369	ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 92
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF error code, 107	ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS error code, 92

ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 92	ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT error code, 331
ER_RPL_ENCRYPTION_HEADER_ERROR error code, 92	ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE error code, 331
ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 91	ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR error code, 170
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 92	ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX error code, 167
ER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 91	ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX error code, 167
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 92	ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION error code, 381
ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTIONS error code, 92	ER_RPL_INFINITY_DENIED error code, 152
ER_RPL_ERROR_CREATING_APPLIER_METADATA error code, 167	ER_RPL_INFINITY_IGNORED error code, 152
ER_RPL_ERROR_CREATING_CONNECTION_METADATA error code, 167	ER_RPL_INFO_DATA_TOO_LONG error code, 47
ER_RPL_ERROR_LOOKING_FOR_LOG error code, 176	ER_RPL_IO_THREAD_KILLED error code, 200
ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION error code, 179	ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED error code, 417
ER_RPL_ERROR_READING_SOURCE_CONFIGURATION error code, 180	ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PAGES error code, 175
ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION error code, 179	ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_ENTRIES error code, 178
ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION error code, 180	ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER error code, 417
ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILES error code, 168	ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED error code, 173
ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE error code, 168	ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CURRENT error code, 176
ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER_CONFIGURATION error code, 167	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA error code, 176
ER_RPL_FAILED_TO_OPEN_INFO_FILE error code, 168	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_FORMAT error code, 176
ER_RPL_FAILED_TO_OPEN_RELAY_LOG error code, 179	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG error code, 173
ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFOPRIMARY error code, 167	ER_RPL_MTA_RECOVERY_COMPLETE error code, 175
ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX error code, 178	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR error code, 173
ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL error code, 201	ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR error code, 173
ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED error code, 195	ER_RPL_MTA_RECOVERY_SUCCESSFUL error code, 174
ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED error code, 195	ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED error code, 180
ER_RPL_GTID_LOG_EVENT_IN_STREAM error code, 169	ER_RPL_MTA_STATISTICS error code, 175
ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE error code, 168	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORY error code, 168
ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 192	ER_RPL_OPEN_INDEX_FILE_FAILED error code, 178
ER_RPL_GTID_TABLE_CANNOT_OPEN error code, 141	ER_RPL_PLEASE_USE_OPTION_RELAY_LOG error code, 178
ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 340	ER_RPL_PLUGIN_FUNCTION_FAILED error code, 173
	ER_RPL_PLUGINTYPE_EXPRESSION error code, 173
	ER_RPL_RECOVERY_ERROR error code, 173
	ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG error code, 173
	ER_RPL_REPLICATION_FILE_SOURCE_POS_INFO error code, 173

ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX error code, 173	ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_IN error code, 172
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE error code, 173	ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA error code, 168
ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID error code, 173	ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_REQUIRES_POSITION error code, 168
ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION error code, 173	ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH error code, 176
ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY error code, 178	ER_RPL_REPLICA_FILTER_CREATE_FAILED error code, 196
ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY error code, 178	ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD error code, 175
ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY error code, 385	ER_RPL_REPLICA_GENERIC_MESSAGE error code, 167
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLOSE error code, 361	ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED error code, 196
ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_ERROR error code, 177	ER_RPL_REPLICA_INCORRECT_CHANNEL error code, 191
ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE error code, 172	ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE error code, 191
ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA error code, 174	ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR error code, 175
ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER error code, 176	ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE error code, 175
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION error code, 175	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED error code, 177
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL error code, 172	ER_RPL_REPLICA_IO_THREAD_EXITING error code, 176
ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL error code, 173	ER_RPL_REPLICA_IO_THREAD_KILLED error code, 175
ER_RPL_REPLICA_CANT_USE_CHARSET error code, 177	ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 331
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICA error code, 177	ER_RPL_REPLICA_IO_THREAD_WAS_KILLED error code, 174
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL error code, 398	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING error code, 371
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL error code, 398	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_C error code, 372
ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL error code, 168	ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER error code, 178
ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE error code, 175	ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE error code, 177
ER_RPL_REPLICA_ERROR_INFO_FROM_DA error code, 177	ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE error code, 177
ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED error code, 177	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONNECTION error code, 177
ER_RPL_REPLICA_ERROR_READING_FROM_SERVER error code, 174	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON error code, 359
ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS error code, 178	ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE error code, 177
ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP error code, 175	ER_RPL_REPLICA_REPORT_HOST_TOO_LONG error code, 174
ER_RPL_REPLICA_ERROR_RETRYING error code, 174	ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG error code, 174
ER_RPL_REPLICA_ERROR_RUNNING_QUERY error code, 177	ER_RPL_REPLICA_REPORT_USER_TOO_LONG error code, 174
ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL error code, 168	ER_RPL_REPLICA_RECONNECT_METADATA error code, 196

ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBBOUSAME_NAME_PARTITION_FIELD error code, 174	ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBBOUSAME_NAME_PARTITION_FIELD error code, 41
ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED error code, 176	ER_SCHEDULER_KILLING error code, 143
ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED error code, 398	ER_SCHEDULER_STARTED error code, 143
ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED error code, 397	ER_SCHEDULER_STOPPED error code, 143
ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HASECHANGED error code, 398	HOST_PORT_UNCHANGED error code, 143
ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED error code, 359	ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER error code, 143
ER_RPL_REPLICA_SQL_THREAD_EXITING error code, 177	ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT error code, 143
ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING error code, 178	ER_SCHEDULER_WAITING error code, 143
ER_RPL_REPLICA_SQL_THREAD_STARTING error code, 176	ER_SCHEMA_DIR_CREATE_FAILED error code, 84
ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS error code, 358	ER_SCHEMA_DIR_MISSING error code, 84
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXECUTED error code, 330	ER_SCHEMA_DIR_UNKNOWN error code, 84
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM error code, 175	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 360
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_IP error code, 174	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_IP error code, 360
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 176	ER_SCHEMA_READ_ONLY error code, 107
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 176	ER_SECONDARY_ENGINE_INVALID_TABLESPACE error code, 111
ER_RPL_REPO_HAS_GAPS error code, 142	ER_SECONDARY_ENGINE_OPERATION_FAILED error code, 83
ER_RPL_REWRITEDB_EMPTY_FROM error code, 150	ER_SDI_OPERATION_FAILED_MISSING_RECORD error code, 104
ER_RPL_REWRITEDB_EMPTY_TO error code, 150	ER_SECONDARY_ENGINE error code, 99
ER_RPL_REWRITEDB_MISSING_ARROW error code, 150	ER_SECONDARY_ENGINE_DDL error code, 99
ER_RPL_SERVER_ID_MISSING error code, 174	ER_SECONDARY_ENGINE_DDL_FAILED error code, 105
ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED error code, 180	ER_SECONDARY_ENGINE_DDL_TRACK_PROGRESS error code, 115
ER_RPL_TRX_DELEGATES_INIT_FAILED error code, 153	ER_SECONDARY_ENGINE_PLUGIN error code, 98
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM error code, 169	ER_SECOND_PASSWORD_CANNOT_BE_EMPTY error code, 98
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_ERROR error code, 169	ER_SECURE_AUTH_VALUE_UNSUPPORTED error code, 145
ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM error code, 169	ER_SECURE_TRANSPORT_REQUIRED error code, 68
ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM error code, 169	ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG error code, 147
ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG error code, 179	ER_SEC_FILE_PRIV_CANT_ACCESS_DIR error code, 146
ER_RPL_WORKER_CANT_READ_RELAY_LOG error code, 179	ER_SEC_FILE_PRIV_CANT_STAT error code, 146
ER_RPL_WORKER_ID_IS error code, 167	ER_SEC_FILE_PRIV_DIRECTORY_INSECURE error code, 146
ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL error code, 88	ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS error code, 146
ER_RUN_HOOK_ERROR error code, 64	ER_SEC_FILE_PRIV_EMPTY error code, 146
ER_SAME_NAME_PARTITION error code, 34	ER_SEC_FILE_PRIV_IGNORED error code, 146
	ER_SEC_FILE_PRIV_NULL error code, 146
	ER_SELECT_REDUCED error code, 18
	ER_SEMISYNC_ADD_ACK_TO_SLOT error code, 210
	ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD error code, 209
	ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER error code, 207
	ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POSITION error code, 208
	ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES error code, 208

ER_SEMISYNC_DISABLED_ON_SOURCE error code, 208	ER_SEMISYNC_SERVER_REPLY error code, 208
ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE error code, 211	ER_SEMISYNC_SOCKET_FD_TOO_LARGE error code, 211
ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_REMOTE error code, 210	ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH error code, 209
ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE error code, 207	ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS error code, 208
ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE error code, 209	ER_SEMISYNC_SOURCE_OOM error code, 208
ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD error code, 210	ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS error code, 208
ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD error code, 211	ER_SEMISYNC_SOURCE_TRX_WAIT_POS error code, 208
ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET error code, 210	ER_SEMISYNC_STARTING_ACK_RECEIVER_THD error code, 210
ER_SEMISYNC_FORCED_SHUTDOWN error code, 208	ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA error code, 210
ER_SEMISYNC_FUNCTION_CALLED_TWICE error code, 208	ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD error code, 210
ER_SEMISYNC_INIT_WAIT_POS error code, 209	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA error code, 210
ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY error code, 207	ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO error code, 209
ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT error code, 211	ER_SEMISYNC_TRACE_ENTER_FUNC error code, 207
ER_SEMISYNC_MOVE_BACK_WAIT_POS error code, 209	ER_SEMISYNC_TRACE_EXIT error code, 207
ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE error code, 211	ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE error code, 207
ER_SEMISYNC_NO_SPACE_IN_THE_PKT error code, 209	ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE error code, 207
ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY error code, 207	ER_SEMISYNC_TRX_SKIPPED_AT_POS error code, 209
ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER error code, 209	ER_SEMISYNC_UNREGISTERED_REPLICATOR error code, 210
ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED error code, 211	ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER error code, 210
ER_SEMISYNC_REPLICA_REPLY error code, 211	ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER error code, 210
ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO error code, 211	ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED error code, 210
ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED error code, 211	ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK error code, 210
ER_SEMISYNC_REPLICA_SET_FAILED error code, 211	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT error code, 209
ER_SEMISYNC_REPLICA_START error code, 211	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT error code, 209
ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE error code, 208	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT error code, 209
ER_SEMISYNC_REPLY_MAGIC_NO_ERROR error code, 208	ER_SERVERID_TOO_LARGE error code, 152
ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL error code, 208	ER_SERVER_ACL_TABLE_ERROR error code, 334
ER_SEMISYNC_RPL_ENABLED_ON_SOURCE error code, 208	ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_SYNC error code, 349
ER_SEMISYNC_RPL_INIT_FOR_TRX error code, 207	ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE error code, 349
ER_SEMISYNC_RPL_SWITCHED_OFF error code, 209	ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 352
ER_SEMISYNC_RPL_SWITCHED_ON error code, 209	ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2 error code, 333
	ER_SERVER_CANT_OPEN_FILE error code, 333

ER_SERVER_CERT_VERIFY_FAILED error code, 405	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 346
ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED error code, 334	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 343
ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 334	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 343
ER_SERVER_COST_FAILED_TO_READ error code, 169	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 343
ER_SERVER_COST_INVALID_COST_CONSTANT error code, 168	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS error code, 343
ER_SERVER_COST_UNKNOWN_COST_CONSTANT error code, 168	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 343
ER_SERVER_DISK_FULL_NOWAIT error code, 333	ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR error code, 343
ER_SERVER_DOWNGRADE_FROM_VERSION error code, 402	ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER error code, 344
ER_SERVER_DOWNGRADE_HELP_TABLE_STATUS error code, 414	ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 343
ER_SERVER_DOWNGRADE_STATUS error code, 402	ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 343
ER_SERVER_DOWNGRADE_SYS_SCHEMA error code, 413	ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 343
ER_SERVER_FILE_NOT_FOUND error code, 333	ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 343
ER_SERVER_FILE_USED error code, 333	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE error code, 343
ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE error code, 340	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER error code, 344
ER_SERVER_HANDLER_ERROR error code, 333	ER_SERVER_SHUTDOWN error code, 6
ER_SERVER_INIT_COMPILED_IN_COMMANDS error code, 203	ER_SERVER_SHUTDOWN_COMPLETE error code, 192
ER_SERVER_ISNT_AVAILABLE error code, 69	ER_SERVER_SHUTDOWN_INFO error code, 336
ER_SERVER_MEMORY_OPTION_INVALID error code, 425	ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 332
ER_SERVER_NET_PACKET_TOO_LARGE error code, 333	ER_SERVER_STARTING_WITH_RESOURCE error code, 425
ER_SERVER_NEW_ABORTING_CONNECTION error code, 333	ER_SERVER_STARTUP_ADMIN_INTERFACE error code, 344
ER_SERVER_NOT_FORM_FILE error code, 333	ER_SERVER_STARTUP_MSG error code, 193
ER_SERVER_NO_SESSION_TO_SEND_TO error code, 333	ER_SERVER_TABLE_CHECK_FAILED error code, 334
ER_SERVER_NO_SYSTEM_TABLE_ACCESS error code, 333	ER_SERVER_TEST_MESSAGE error code, 334
ER_SERVER_OFFLINE_MODE error code, 59	ER_SERVER_UNKNOWN_SYSTEM_VARIABLE error code, 333
ER_SERVER_OFFLINE_MODE_REASON error code, 130	ER_SERVER_UPGRADE_CHECKING_DB error code, 351
ER_SERVER_OUTOFMEMORY error code, 194	ER_SERVER_UPGRADE_EMPTY_SYS error code, 351
ER_SERVER_OUT_OF_RESOURCES error code, 194	ER_SERVER_UPGRADE_FAILED error code, 350
ER_SERVER_OUT_OF_SORTMEMORY error code, 333	ER_SERVER_UPGRADE_FROM_VERSION error code, 346
ER_SERVER_RECORD_FILE_FULL error code, 333	ER_SERVER_UPGRADE_HELP_TABLE_STATUS error code, 352
ER_SERVER_REPLICA_AM_INIT_REPOSITORY error code, 332	ER_SERVER_UPGRADE_INFO_FILE error code, 350
ER_SERVER_REPLICA_CM_INIT_REPOSITORY error code, 332	ER_SERVER_UPGRADE_MYSQL_TABLES error code, 351
ER_SERVER_REPLICA_CONVERSION_FAILED error code, 334	ER_SERVER_UPGRADE_NO_SYS_VERSION error code, 351
ER_SERVER_REPLICA_IGNORED_TABLE error code, 334	
ER_SERVER_REPLICA_INIT_QUERY_FAILED error code, 334	

ER_SERVER_UPGRADE_OFF error code, 350	ER_SIMULATED_INJECTION_ERROR error code, 122
ER_SERVER_UPGRADE_PENDING error code, 350	ER_SIZE_OVERFLOW_ERROR error code, 35
ER_SERVER_UPGRADE_REPAIR_REQUIRED error code, 350	ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE error code, 200
ER_SERVER_UPGRADE_REPAIR_STATUS error code, 350	ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING error code, 92
ER_SERVER_UPGRADE_SKIP error code, 350	ER_SOURCE error code, 15
ER_SERVER_UPGRADE_STATUS error code, 350	ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE error code, 46
ER_SERVER_UPGRADE_SYSTEM_TABLES error code, 351	ER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 18
ER_SERVER_UPGRADE_SYS_SCHEMA error code, 350	ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS error code, 50
ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT error code, 351	ER_SOURCE_NET_READ error code, 15
ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED error code, 351	ER_SOURCE_NET_WRITE error code, 15
ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE error code, 351	ER_SPATIAL_CANT_HAVE_NULL error code, 19
ER_SERVER_UPGRADE_SYS_VERSION_EMPTY error code, 351	ER_SPATIAL_FUNCTIONAL_INDEX error code, 89
ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED error code, 346	ER_SPATIAL_MUST_HAVE_GEOM_COL error code, 43
ER_SERVER_WARN_DEPRECATED error code, 349	ER_SPATIAL_UNIQUE_INDEX error code, 87
ER_SERVER_WRONG_VALUE_FOR_VAR error code, 340	ER_SPECIFIC_ACCESS_DENIED error code, 124
ER_SESSION_WAS_KILLED error code, 69	ER_SPECIFIC_ACCESS_DENIED_ERROR error code, 17
ER_SETNS_FAILED error code, 352	ER_SPVAR_NONINTEGER_TYPE error code, 108
ER_SET_CONSTANTS_ONLY error code, 16	ER_SP_ALREADY_EXISTS error code, 22
ER_SET_EVENT_FAILED error code, 336	ER_SP_BADRETURN error code, 22
ER_SET_PASSWORD_AUTH_PLUGIN_ERROR error code, 116	ER_SP_BADSELECT error code, 22
ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION error code, 49	ER_SP_BADSTATEMENT error code, 22
ER_SE_TYPECODE_CONFLICT error code, 156	ER_SP_BAD_CURSOR_QUERY error code, 23
ER_SHA256_PASSWORD_SECOND_PASSWORD_USED error code, 344	ER_SP_BAD_CURSOR_SELECT error code, 23
ER_SHAPE_PREDICTION_UDF error code, 117	ER_SP_BAD_SQLSTATE error code, 27
ER_SHARED_TABLESPACE_USED_BY_PARTITIONED error code, 340	ER_SP_BAD_VAR_SHADOW error code, 30
ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL error code, 216	ER_SP_CANT ALTER error code, 23
ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND error code, 216	ER_SP_CANT SET AUTOCOMMIT error code, 30
ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING error code, 216	ER_SP_CASE_NOT_FOUND error code, 24
ER_SHA_PWD_RSA_KEY_TOO_LONG error code, 216	ER_SP_COND_MISMATCH error code, 22
ER_SHA_PWD_SALT_FOR_USER_CORRUPT error code, 216	ER_SP_CURSOR_AFTER_HANDLER error code, 24
ER_SHUTDOWN_COMPLETE error code, 8	ER_SP_CURSOR_ALREADY_OPEN error code, 23
ER_SHUTTING_DOWN_REPLICA_THREADS error code, 148	ER_SP_CURSOR_MISMATCH error code, 23
ER_SIGNAL_BAD_CONDITION_TYPE error code, 40	ER_SP_CURSOR_NOT_OPEN error code, 23
ER_SIGNAL_EXCEPTION error code, 40	ER_SP_DOES_NOT_EXIST error code, 22
ER_SIGNAL_NOT_FOUND error code, 40	ER_SP_DROP_FAILED error code, 22
ER_SIGNAL_WARN error code, 40	ER_SP_DUP_COND error code, 23
ER_SIMPLE_ERROR_LOG_COMPONENT_STATUS error code, 417	ER_SP_DUP_CURS error code, 23
	ER_SP_DUP_HANDLER error code, 28
	ER_SP_DUP_PARAM error code, 23
	ER_SP_DUP_VAR error code, 23
	ER_SP_FETCH_NO_DATA error code, 23
	ER_SP_LABEL_MISMATCH error code, 22
	ER_SP_LABEL_REDEFINE error code, 22
	ER_SP_LILABEL_MISMATCH error code, 22
	ER_SP_LOAD_FAILED error code, 72
	ER_SP_NORETURN error code, 23
	ER_SP_NORETURNEND error code, 23
	ER_SP_NOT_VAR_ARG error code, 28
	ER_SP_NO_AGGREGATE error code, 31
	ER_SP_NO ALTER LANGUAGE error code, 121

ER_SP_NO_DROP_SP error code, 25	ER_SRS_NOT_CARTESIAN_UNDEFINED error code, 73
ER_SP_NO_RECURSION error code, 28	ER_SRS_NOT_FOUND error code, 75
ER_SP_NO_RECURSIVE_CREATE error code, 21	ER_SRS_NOT_GEOGRAPHIC error code, 87
ER_SP_NO_RESET error code, 28	ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE error code, 86
ER_SP_RECURSION_LIMIT error code, 30	ER_SRS_PARSE_ERROR error code, 73
ER_SP_STORE_FAILED error code, 22	ER_SRS_PROJ_PARAMETER_MISSING error code, 73
ER_SP_SUBSELECT_NYI error code, 23	ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT error code, 116
ER_SP_UNDECLARED_VAR error code, 23	ER_SRV_END error code, 405
ER_SP_UNINIT_VAR error code, 22	ER_SRV_INIT_END error code, 405
ER_SP_VARCOND_AFTER_CURSHNDLR error code, 24	ER_SRV_INIT_START error code, 405
ER_SP_WRONG_NAME error code, 30	ER_SRV_START error code, 405
ER_SP_WRONG_NO_OF_ARGS error code, 22	ER_SR_BOGUS_VALUE error code, 154
ER_SP_WRONG_NO_OF_FETCH_ARGS error code, 23	ER_SR_INVALID_CONTEXT error code, 154
ER_SQLTHREAD_WITH_SECURE_REPLICA error code, 48	ER_SSL_FIPS_MODE_ERROR error code, 217
ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL error code, 155	ER_SSL_LIBRARY_ERROR error code, 144
ER_SQL_HA_READ_FAILED error code, 154	ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED error code, 341
ER_SQL_MODE_MERGED error code, 67	ER_SSL_TRYING_DATADIR_DEFAULTS error code, 152
ER_SQL_MODE_MERGED_WITH_STRICT_MODE error code, 193	ER_STACK_OVERFLOW error code, 151
ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID error code, 109	ER_STACK_BACKTRACE error code, 394
ER_SQL_USER_TABLE_ALTER_WARNING error code, 155	ER_STACK_OVERRUN error code, 11
ER_SQL_USER_TABLE_CREATE_WARNING error code, 155	ER_STACK_OVERRUN_NEED_MORE error code, 29
ER_SRS_ATTRIBUTE_STRING_TOO_LONG error code, 86	ER_STARTING_AS error code, 147
ER_SRS_GEOGCS_INVALID_AXES error code, 88	ER_STARTING_INIT error code, 336
ER_SRS_ID_ALREADY_EXISTS error code, 86	ER_STARTING_REPLICA_MONITOR_IO_THREAD error code, 109
ER_SRS_INVALID_ANGULAR_UNIT error code, 88	ER_STARTUP error code, 27
ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE error code, 86	ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION error code, 123
ER_SRS_INVALID_HEIGHT error code, 117	ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION_L error code, 407
ER_SRS_INVALID_INVERSE_FLATTENING error code, 88	ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION error code, 106
ER_SRS_INVALID_LATITUDE_OF_ORIGIN error code, 116	ER_STD_BAD_ALLOC_ERROR error code, 60
ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A error code, 118	ER_STD_DOMAIN_ERROR error code, 60
ER_SRS_INVALID_LONGITUDE_OF_ORIGIN error code, 116	ER_STD_INVALID_ARGUMENT error code, 60
ER_SRS_INVALID_PRIME_MERIDIAN error code, 88	ER_STD_LENGTH_ERROR error code, 60
ER_SRS_INVALID_SCALING error code, 118	ER_STD_LOGIC_ERROR error code, 61
ER_SRS_INVALID_SEMI_MAJOR_AXIS error code, 88	ER_STD_OUT_OF_RANGE_ERROR error code, 60
ER_SRS_INVALID_ZONE_WIDTH error code, 118	ER_STD_OVERFLOW_ERROR error code, 60
ER_SRS_MISSING_MANDATORY_ATTRIBUTE error code, 85	ER_STD_RANGE_ERROR error code, 60
ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS error code, 86	ER_STD_REGEX_ERROR error code, 97
ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE error code, 86	ER_STD_RUNTIME_ERROR error code, 61
ER_SRS_NOT_CARTESIAN error code, 73	ER_STD_UNDERFLOW_ERROR error code, 60
	ER_STD_UNKNOWN_EXCEPTION error code, 61
	ER_STMT_CACHE_FULL error code, 44
	ER_STMT_EXECUTION_NOT_ALLOWED_WITHIN_SP_OR_TRG error code, 129
	ER_STMT_HAS_NO_OPEN_CURSOR error code, 28
	ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG error code, 24
	ER_STOP_REPLICA_IO_THREAD_DISK_SPACE error code, 217

ER_STOP_REPLICA_IO_THREAD_TIMEOUT error code, 56	ER_TABLESPACE_CANNOT_BE_DECRYPTED error code, 95
ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT error code, 108	ER_TABLESPACE_CANNOT_BE_ENCRYPTED error code, 95
ER_STOP_REPLICA_SQL_THREAD_TIMEOUT error code, 56	ER_TABLESPACE_CANNOT_ENCRYPT error code, 70
ER_STORAGE_ENGINE_NOT_LOADED error code, 57	ER_TABLESPACE_DISCARDED error code, 52
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 43	ER_TABLESPACE_DUP_FILENAME error code, 79
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 36	ER_TABLESPACE_ENGINE_MISMATCH error code, 81
ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN error code, 44	ER_TABLESPACE_EXISTS error code, 52
ER_SUBPARTITION_ERROR error code, 33	ER_TABLESPACE_IS_NOT_EMPTY error code, 66
ER_SUBPARTITION_NAME error code, 40	ER_TABLESPACE_MISSING error code, 52
ER_SUBQUERY_NO_1_ROW error code, 18	ER_TABLESPACE_MISSING_WITH_NAME error code, 72
ER_SUBQUERY_TRANSFORM_REJECTED error code, 105	ER_TABLESPACE_TYPE_UNKNOWN error code, 95
ER_SUPPORTED_ONLY_WITH_HYPERGRAPH error code, 124	ER_TABLES_DIFFERENT_METADATA error code, 47
ER_SWITCH_TMP_ENGINE error code, 77	ER_TABLE_CANT_HANDLE_AUTO_INCREMENT error code, 13
ER_SYNTAX_ERROR error code, 13	ER_TABLE_CANT_HANDLE_BLOB error code, 13
ER_SYSTEMD_NOTIFY_CONNECT_FAILED error code, 255	ER_TABLE_CANT_HANDLE_FT error code, 16
ER_SYSTEMD_NOTIFY_DEBUG error code, 392	ER_TABLE_CANT_HANDLE_SPKEYS error code, 31
ER_SYSTEMD_NOTIFY_PATH_TOO_LONG error code, 255	ER_TABLE_CHECK_INTACT error code, 152
ER_SYSTEMD_NOTIFY_WRITE_FAILED error code, 255	ER_TABLE_CORRUPT error code, 56
ER_SYSTEM_SCHEMA_NOT_FOUND error code, 141	ER_TABLE_CREATED_WITH_DIFFERENT_VERSION error code, 163
ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE error code, 193	ER_TABLE_DEF_CHANGED error code, 28
ER_SYSTEM_TABLE_NOT_TRANSACTIONAL error code, 180	ER_TABLE_EXISTS_ERROR error code, 6
ER_SYSTEM_VIEW_INIT_FAILED error code, 194	ER_TABLE_HAS_NO_FT error code, 48
ER_SYSVAR_CHANGE_DURING_QUERY error code, 101	ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD error code, 163
ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT error code, 217	ER_TABLE_INCOMPATIBLE_YEAR_FIELD error code, 163
ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTION error code, 217	ER_TABLE_IN_FK_CHECK error code, 46
ER_SYS_VAR_COMPONENT_OOM error code, 216	ER_TABLE_IN_SHARED_TABLESPACE error code, 118
ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE error code, 217	ER_TABLE_IN_SYSTEM_TABLESPACE error code, 52
ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY error code, 216	ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN error code, 118
ER_SYS_VAR_NOT_FOUND error code, 337	ER_TABLE_MUST_HAVE_COLUMNS error code, 10
ER_TABLEACCESS_DENIED_ERROR error code, 12	ER_TABLE_OPTIMIZE error code, 40
ER_TABLENAME_NOT_ALLOWED_HERE error code, 18	ER_TABLE_NAME_CAUSES_TOO_LONG_PATH error code, 101
ER_TABLESAMPLE_ONLY_ON_BASE_TABLES error code, 128	ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 360
ER_TABLESAMPLE_PERCENTAGE error code, 128	ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_PARTITION error code, 360
ER_TABLESPACE_AUTO_EXTEND_ERROR error code, 35	ER_TABLE_NEEDS_DUMP_UPGRADE error code, 205
	ER_TABLE_NEEDS_REBUILD error code, 44
	ER_TABLE_NEEDS_UPGRADE error code, 30
	ER_TABLE_NOT_EMPTY error code, 118
	ER_TABLE_NOT_LOCKED error code, 9
	ER_TABLE_NOT_LOCKED_FOR_WRITE error code, 9
	ER_TABLE_NO_PRIMARY_KEY error code, 118
	ER_TABLE_REFERENCED error code, 71

ER_TABLE_SCHEMA_MISMATCH error code, 52	ER_THREAD_POOL_EPOLL_WAIT_ERROR error code, 418
ER_TABLE_UPGRADE_REQUIRED error code, 193	ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT error code, 206
ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT error code, 103	ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLE error code, 206
ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMN error code, 103	ER_THREAD_POOL_FAILED_TO_CREATE_POOL error code, 206
ER_TABLE_WITHOUT_PK error code, 89	ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONTEXT error code, 206
ER_TABLE_WRONG_KEY_DEFINITION error code, 163	ER_THREAD_POOL_IDLE_CONNECTION_CLOSED error code, 397
ER_TARGET_TABLESPACE_UNENCRYPTED error code, 95	ER_THREAD_POOL_INIT_FAILED error code, 206
ER_TC_BAD_MAGIC_IN_TC_LOG error code, 172	ER_THREAD_POOL_LOW_LEVEL_ARM_FAILED error code, 418
ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC error code, 172	ER_THREAD_POOL_LOW_LEVEL_ARM_FAILED_WITH_ERRNO error code, 418
ER_TC_HEURISTIC_RECOVERY_FAILED error code, 172	ER_THREAD_POOL_LOW_LEVEL_INIT_ALLOC_FAILED error code, 418
ER_TC_HEURISTIC_RECOVERY_MODE error code, 172	ER_THREAD_POOL_LOW_LEVEL_INIT_FAILED error code, 418
ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY error code, 172	ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED error code, 206
ER_TC_RECOVERING_AFTER_CRASH_USING error code, 172	ER_THREAD_POOL_MTL_DISABLE error code, 414
ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS error code, 172	ER_THREAD_POOL_MTL_REENABLE error code, 414
ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVERY error code, 172	ER_THREAD_POOL_PFS_TABLES_ADD_FAILED error code, 342
ER_TELEMETRY_ERROR error code, 405	ER_THREAD_POOL_PFS_TABLES_INIT_FAILED error code, 342
ER_TELEMETRY_INFO error code, 405	ER_THREAD_POOL_PLUGIN_STARTED error code, 386
ER_TELEMETRY_WARNING error code, 405	ER_THREAD_POOL_POLL_WAIT_ERROR error code, 418
ER_TEMPORARY_NAME error code, 40	ER_THREAD_POOL_SOCKETPAIR_FAILED error code, 418
ER_TEMPTABLE_ENGINE_ERROR error code, 417	ER_THREAD_POOL_SYSVAR_CHANGE error code, 393
ER_TEMP_FILE_WRITE_FAILURE error code, 56	ER_THREAD_PRIORITY_IGNORED error code, 192
ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT error code, 88	ER_THREAD_STILL_ALIVE error code, 406
ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT error code, 88	ER_TLS_CONFIGURATION_REUSED error code, 366
ER_TEXTFILE_NOT_READABLE error code, 8	ER_TLS_CONFIGURED_FOR_CHANNEL error code, 365
ER_TF_FORBIDDEN_JOIN_TYPE error code, 83	ER_TLS_LIBRARY_ERROR_INTERNAL error code, 418
ER_TF_MUST_HAVE_ALIAS error code, 83	ER_TMPDIR_PATH_TOO_LONG error code, 370
ER_THE_USER_ABIDES error code, 149	ER_UNEXPECTED_SESSION_FOR_VAR error code, 392
ER_THREAD_HANDLING_OOM error code, 146	ER_TOO_BIG_DISPLAYWIDTH error code, 29
ER_THREAD_POOL_ALLOC_FAILED error code, 417	ER_TOO_BIG_ENUM error code, 72
ER_THREAD_POOL_BUFFER_TOO_SMALL error code, 206	ER_TOO_BIG_FIELDLENGTH error code, 8
ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PLUGIN error code, 392	ER_TOO_BIG_FOR_UNCOMPRESS error code, 19
ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA error code, 206	ER_TOO_BIG_PRECISION error code, 28
ER_THREAD_POOL_CONNECTION_INIT_REPORT error code, 417	ER_TOO_BIG_ROW_SIZE error code, 10
ER_THREAD_POOL_CON_HANDLER_INIT_FAILED error code, 206	ER_TOO_BIG_SCALE error code, 28
ER_THREAD_POOL_CREATE_EPOLL_FAILED error code, 418	ER_TOO_BIG_SELECT error code, 10
ER_THREAD_POOL_CREATE_THREAD_FAILED error code, 418	ER_TOO_BIG_SET error code, 9
ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID error code, 386	ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT error code, 31

ER_TOO_LONG_BODY error code, 29	ER_TREE_CORRUPT_RIGHT_IS_LEFT error code, 179
ER_TOO_LONG_FIELD_COMMENT error code, 39	ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK error code, 179
ER_TOO_LONG_IDENT error code, 7	ER_TRG_ALREADY_EXISTS error code, 25
ER_TOO_LONG_INDEX_COMMENT error code, 43	ER_TRG_CANT_CHANGE_ROW error code, 25
ER_TOO_LONG_KEY error code, 7	ER_TRG_CANT_OPEN_TABLE error code, 38
ER_TOO_LONG_ROUTINE_COMMENT error code, 72	ER_TRG_CANT_PARSE error code, 153
ER_TOO_LONG_SET_ENUM_VALUE error code, 72	ER_TRG_CORRUPTED_FILE error code, 38
ER_TOO_LONG_STRING error code, 13	ER_TRG_CREATION_CTX_NOT_SET error code, 193
ER_TOO_LONG_TABLESPACE_COMMENT error code, 79	ER_TRG_DOES_NOT_EXIST error code, 25
ER_TOO_LONG_TABLE_COMMENT error code, 39	ER_TRG_INVALID_CREATION_CTX error code, 38
ER_TOO_LONG_TABLE_PARTITION_COMMENT error code, 50	ER_TRG_IN_WRONG_SCHEMA error code, 29
ER_TOO_MANY_CONCURRENT_TRXS error code, 40	ER_TRG_NO_CLIENT_CHARSET error code, 144
ER_TOO_MANY_FIELDS error code, 10	ER_TRG_NO_CREATION_CTX error code, 38
ER_TOO_MANY_GROUP_BY_MODIFIER_BRANCHES error code, 123	ER_TRG_NO_DEFINER error code, 30
ER_TOO_MANY_KEYS error code, 7	ER_TRG_NO_SUCH_ROW_IN_TRG error code, 25
ER_TOO_MANY_KEY_PARTS error code, 7	ER_TRG_ON_VIEW_OR_TEMP_TABLE error code, 25
ER_TOO_MANY_PARTITIONS_ERROR error code, 33	ER_TRG_WITHOUT_DEFINER error code, 144
ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR error code, 41	ER_TRG_WRONG_ORDER error code, 347
ER_TOO_MANY_ROWS error code, 14	ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED error code, 206
ER_TOO_MANY_STORAGE_ENGINES error code, 156	ER_TRIGGER_INVALID_VALUE error code, 140
ER_TOO_MANY_TABLES error code, 10	ER_TRUNCATED_WRONG_VALUE error code, 21
ER_TOO_MANY_USER_CONNECTIONS error code, 15	ER_TRUNCATED_WRONG_VALUE_FOR_FIELD error code, 25
ER_TOO_MANY_VALUES_ERROR error code, 41	ER_TRUNCATE_ILLEGAL_FK error code, 44
ER_TOO_MANY_WINDOWS error code, 115	ER_TRX_GTID_COLLECT_REJECT error code, 155
ER_TO_VECTOR_CONVERSION error code, 130	ER_TRX_WRITE_SET_OOM error code, 156
ER_TP_CANNOT_DISABLE_MTL_WITH_DL error code, 130	ER_TURNING_LOGGING_OFF_FOR_THE_DURATION error code, 189
ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THRESHOLD error code, 117	ER_TURNING_ON_PARTIAL_REVOKES error code, 349
ER_TRACK_VARIABLES_BOGUS error code, 149	ER_TZ_CANT_BUILD_MKTIME_MAP error code, 165
ER_TRANSACTION_ROLLBACK_DURING_COMMIT error code, 64	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE error code, 164
ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84 error code, 88	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID error code, 164
ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED error code, 88	ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE error code, 164
ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84 error code, 88	ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE error code, 164
ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED error code, 88	ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE error code, 165
ER_TRANSPORTS_WHAT_TRANSPORTS error code, 148	ER_TZ_OOM_INITIALIZING_TIME_ZONES error code, 164
ER_TRANS_CACHE_FULL error code, 15	ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE error code, 164
ER_TREE_CORRUPT_2_CONSECUTIVE_REDS error code, 179	ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION error code, 165
ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT error code, 179	ER_TZ_OOM_WHILE_LOADING_TIME_ZONE error code, 165
ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT error code, 179	ER_TZ_OOM_WHILE_SETTING_TIME_ZONE error code, 165
	ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE error code, 164

ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE error code, 165	ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF error code, 33
ER_TZ_TRANSITION_TABLE_LOAD_ERROR error code, 165	ER_UNIT_NOT_FOUND error code, 100
ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS error code, 165	ER_UNKNOWN_ALTER_ALGORITHM error code, 51
ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_ERROR error code, 164	ER_UNKNOWN_ALTER_LOCK error code, 51
ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR error code, 164	ER_UNKNOWN_AUTHID error code, 73
ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE error code, 164	ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE error code, 196
ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE error code, 164	ER_UNKNOWN_CHARACTER_SET error code, 10
ER_UDF_ALREADY_EXISTS error code, 336	ER_UNKNOWN_COLLATION error code, 20
ER_UDF_CANT_ALLOC_FOR_FUNCTION error code, 154	ER_UNKNOWN_COM_ERROR error code, 6
ER_UDF_CANT_ALLOC_FOR_STRUCTURES error code, 154	ER_UNKNOWN_ERROR error code, 10
ER_UDF_CANT_OPEN_FUNCTION_TABLE error code, 154	ER_UNKNOWN_ERROR_DETECTED_IN_SE error code, 200
ER_UDF_DEREGISTRATION error code, 400	ER_UNKNOWN_ERROR_NUMBER error code, 154
ER_UDF_DROP_DYNAMICALLY_REGISTERED error code, 80	ER_UNKNOWN_EXPLAIN_FORMAT error code, 50
ER_UDF_ERROR error code, 71	ER_UNKNOWN_KEY_CACHE error code, 20
ER_UDF_EXEC_FAILURE error code, 400	ER_UNKNOWN_LOCALE error code, 41
ER_UDF_EXEC_FAILURE_REASON error code, 400	ER_UNKNOWN_NETWORK_NAMESPACE error code, 352
ER_UDF_EXISTS error code, 11	ER_UNKNOWN_PARTITION error code, 47
ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE error code, 154	ER_UNKNOWN_PROCEDURE error code, 10
ER_UDF_NO_PATHS error code, 11	ER_UNKNOWN_STMT_HANDLER error code, 18
ER_UDF_REGISTER_ERROR error code, 369	ER_UNKNOWN_STORAGE_ENGINE error code, 21
ER_UDF_REGISTER_SERVICE_ERROR error code, 369	ER_UNKNOWN_SYSTEM_VARIABLE error code, 15
ER_UDF_REGISTRATION error code, 400	ER_UNKNOWN_TABLE error code, 10
ER_UDF_UNREGISTER_ERROR error code, 370	ER_UNKNOWN_TABLESPACE_TYPE error code, 340
ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT error code, 96	ER_UNKNOWN_TABLE_IN_UPGRADE error code, 356
ER_UNABLE_TO_BUILD_HISTOGRAM error code, 80	ER_UNKNOWN_TARGET_BINLOG error code, 26
ER_UNABLE_TO_COLLECT_LOG_STATUS error code, 86	ER_UNKNOWN_TIME_ZONE error code, 21
ER_UNABLE_TO_DROP_COLUMN_STATISTICS error code, 80	ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE error code, 145
ER_UNABLE_TO_RESOLVE_HOSTNAME error code, 143	ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE error code, 337
ER_UNABLE_TO_RESOLVE_IP error code, 143	ER_UNRESOLVED_HINT_NAME error code, 66
ER_UNABLE_TO_SET_OPTION error code, 87	ER_UNRESOLVED_TABLE_LOCK error code, 76
ER_UNABLE_TO_STORE_COLUMN_STATISTICS error code, 80	ER_UNSUPPORTED_LOG_ENGINE error code, 37
ER_UNABLE_TO_STORE_STATISTICS error code, 75	ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED error code, 90
ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS error code, 80	ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN error code, 64
ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN error code, 84	ER_UNSUPPORTED ALTER_ENCRYPTION_INPLACE error code, 70
ER_UNDO_RECORD_TOO_BIG error code, 45	ER_UNSUPPORTED ALTER_INPLACE_ON_VIRTUAL_COLUMN error code, 64
ER_UNEXPECTED_GEOMETRY_TYPE error code, 73	ER_UNSUPPORTED ALTER_ONLINE_ON_VIRTUAL_COLUMN error code, 70
	ER_UNSUPPORTED_DATE error code, 147
	ER_UNSUPPORTED_ENGINE error code, 46
	ER_UNSUPPORTED_EXTENSION error code, 10
	ER_UNSUPPORTED_INDEX_ALGORITHM error code, 72
	ER_UNSUPPORTED_PS error code, 21
	ER_UNSUPPORTED_SQL_MODE error code, 100
	ER_UNSUPPORTED_USE_OF_GRANT_AS error code, 95

ER_UNSUPPORT_COMPRESSED_TEMPORARY_TABLE error code, 72	ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED error code, 255
ER_UNTIL_COND_IGNORED error code, 20	ER_VALIDATE_PWD_DICT_FILE_TOO_BIG error code, 215
ER_UPDATE_GTID_PURGED_WITH_GR error code, 101	ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY error code, 215
ER_UPDATE_INFO error code, 12	ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX error code, 215
ER_UPDATE_LOG_DEPRECATED_IGNORED error code, 22	ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE error code, 215
ER_UPDATE_LOG_DEPRECATED_TRANSLATED error code, 22	ER_VALIDATE_PWD_LENGTH_CHANGED error code, 215
ER_UPDATE_TABLE_USED error code, 9	ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED error code, 255
ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE error code, 14	ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED error code, 255
ER_UPDATING_DD_TABLE error code, 72	ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED error code, 256
ER_UPGRADE_NONEXISTENT_SCHEMA error code, 370	ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED error code, 255
ER_UPGRADE_PARSE_ERROR error code, 340	ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED error code, 256
ER_USAGE_DEPRECATION_COUNTER error code, 403	ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED error code, 256
ER_USERNAME error code, 31	ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED error code, 256
ER_USERNAME_TRUNCATED error code, 366	ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED error code, 256
ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT error code, 104	ER_VALUES_IS_NOT_INT_TYPE_ERROR error code, 44
ER_USER_ALREADY_EXISTS error code, 69	ER_VALUE_OUT_OF_RANGE error code, 114
ER_USER_COLUMN_OLD_LENGTH error code, 70	ER_VARIABLE_IS_NOT_STRUCT error code, 20
ER_USER_DOES_NOT_EXIST error code, 69	ER_VARIABLE_IS_READONLY error code, 39
ER_USER_LIMIT_REACHED error code, 17	ER_VARIABLE_NOT_PERSISTED error code, 75
ER_USER_LOCK_DEADLOCK error code, 61	ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER error code, 49
ER_USER_LOCK_OVERLONG_NAME error code, 120	ER_VARIABLE_NOT_SETTABLE_IN_SP error code, 53
ER_USER_LOCK_WRONG_NAME error code, 61	ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION error code, 49
ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_CORRUPTED error code, 162	ER_VAR_CANT_BE_READ error code, 18
ER_USER_REFERENCED_AS_DEFINER error code, 108	ER_VAR_DEREGISTRATION error code, 424
ER_USER_REGISTRATION_FAILED error code, 113	ER_VAR_DOES_NOT_EXIST error code, 79
ER_USER_REQUIRES_ROOT error code, 148	ER_VAR_REGISTRATION error code, 424
ER_USER_WHAT_USER error code, 148	ER_VERBOSE_HINT error code, 150
ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION error code, 109	ER_VERBOSE_REQUIRES_HELP error code, 145
ER_UUID_INVALID error code, 145	ER_VIEW_CHECKSUM error code, 26
ER_UUID_IS error code, 145	ER_VIEW_CHECKSUM_FAILED error code, 25
ER_UUID_SALT error code, 144	ER_VIEW_CREATION_CTX_NOT_SET error code, 193
ER_UUID_SCRUB error code, 145	ER_VIEW_DELETE_MERGE_VIEW error code, 27
ER_VALGRIND_COUNT_LEAKS error code, 154	ER_VIEW_FRM_NO_USER error code, 30
ER_VALGRIND_DO_QUICK_LEAK_CHECK error code, 154	ER_VIEW_INVALID error code, 25
ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGES error code, 121	ER_VIEW_INVALID_CREATION_CTX error code, 38
ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED error code, 256	ER_VIEW_MULTIUPDATE error code, 26
ER_VALIDATE_PWD_COULD_BE_NULL error code, 255	ER_VIEW_NONUPD_CHECK error code, 25
ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED error code, 214	ER_VIEW_NO_CREATION_CTX error code, 38
ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED error code, 214	ER_VIEW_NO_EXPLAIN error code, 24

ER_VIEW_NO_INSERT_FIELD_LIST error code, 26	ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES error code, 385
ER_VIEW_OTHER_USER error code, 30	ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES error code, 116
ER_VIEW_PREVENT_UPDATE error code, 29	ER_WARN_CANT_DROP_DEFAULT_KEYCACHE error code, 29
ER_VIEW_RECURSIVE error code, 31	ER_WARN_CANT_OPEN_CERTIFICATE error code, 404
ER_VIEW_SELECT_CLAUSE error code, 24	ER_WARN_CA_CERT_VERIFY_FAILED error code, 404
ER_VIEW_SELECT_TMPTABLE error code, 24	ER_WARN_CERTIFICATE_ERROR_STRING error code, 405
ER_VIEW_SELECT_VARIABLE error code, 24	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MISMATCH error code, 398
ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION error code, 141	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NO_PLUGIN error code, 374
ER_VIEW_UNPARSABLE error code, 163	ER_WARN_COMPONENT_KEYRING_KMIP_DUPLICATE_KEYMOD error code, 427
ER_VIEW_WRONG_LIST error code, 25	ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY error code, 393
ER_WAITING_FOR_NO_CONNECTIONS error code, 403	ER_WARN_CONFLICTING_HINT error code, 66
ER_WAITING_FOR_NO_THDS error code, 403	ER_WARN_DEPRECATED_GTID_ONLY_WITH_SOURCE_AUTO_POSITION error code, 114
ER_WAITPID_FAILED error code, 203	ER_WARN_DEPRECATED_RANGE_OF_RANGE error code, 19
ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES error code, 344	ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX error code, 89
ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE error code, 344	ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX error code, 89
ER_WARNING_NOT_COMPLETE_ROLLBACK error code, 15	ER_WARN_DA_PRIVILEGE_NOT_REGISTERED error code, 102
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CRAVEDTEMP error code, 47	ER_WARN_DEPRECATED_CHARSET_OPTION error code, 384
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPTEMP error code, 48	ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION error code, 118
ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID error code, 81	ER_WARN_DEPRECATED_COLLATION error code, 114
ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID error code, 344	ER_WARN_DEPRECATED_COLLATION_OPTION error code, 384
ER_WARN_ACCOUNT_TRIMMED error code, 140	ER_WARN_DEPRECATED_DATETIME_DELIMITER error code, 115
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDARY error code, 111	ER_WARN_DEPRECATED_DYNAMIC_PRIV_IN_GRANT error code, 122
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDARY error code, 378	ER_WARN_DEPRECATED_ENGINE_SYNTAX_NO_REPLACEMENT error code, 113
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE error code, 111	ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT error code, 117
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE error code, 378	ER_WARN_DEPRECATED_FLOAT_DIGITS error code, 97
ER_WARN_ALLOWED_PACKET_OVERFLOWED error code, 21	ER_WARN_DEPRECATED_FLOAT_UNSIGNED error code, 97
ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME_SPACE error code, 110	ER_WARN_DEPRECATED_FOUND_ROWS error code, 105
ER_WARN_AUDIT_LOG_DISABLED error code, 385	ER_WARN_DEPRECATED_IDENT error code, 117
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY error code, 112	ER_WARN_DEPRECATED_INNER_INTO error code, 105
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY error code, 379	ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH error code, 97
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES error code, 358	
ER_WARN_BAD_MAX_EXECUTION_TIME error code, 66	
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED error code, 81	
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_UPDATES error code, 82	
ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATED error code, 399	

ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR error code, 105	ER_WARN_INVALID_DB_RESTRICTIONS error code, 349
ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX error code, 91	ER_WARN_INVALID_HINT error code, 79
ER_WARN_DEPRECATED_NON_STANDARD_KEY error code, 129	ER_WARN_INVALID_TIMESTAMP error code, 21
ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER error code, 403	ER_WARN_I_S_SKIPPED_TABLE error code, 43
ER_WARN_DEPRECATED_SASL_MECHANISM error code, 427	ER_WARN_KEYRING_PLUGIN_DEPRECATED error code, 425
ER_WARN_DEPRECATED_SQLMODE error code, 63	ER_WARN_LANGUAGE_COMPONENT_CANNOT_UNINSTALL error code, 412
ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS error code, 105	ER_WARN_LANGUAGE_COMPONENT_RESOURCE_LIMIT error code, 412
ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER error code, 115	ER_WARN_LEGACY_SYNTAX_CONVERTED error code, 57
ER_WARN_DEPRECATED_SYNTAX error code, 21	ER_WARN_LOG_DEPRECATED_NON_STANDARD_KEY error code, 414
ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 43	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT error code, 358
ER_WARN_DEPRECATED_SYNTAX_WITH_VER error code, 36	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 358
ER_WARN_DEPRECATED_SYSVAR_UPDATE error code, 63	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL error code, 358
ER_WARN_DEPRECATED_USER_DEFINED_COLLATION error code, 120	ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO error code, 382
ER_WARN_DEPRECATED_USER_DEFINED_COLLATION_NAME error code, 398	ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING error code, 385
ER_WARN_DEPRECATED_USER_SET_EXPR error code, 91	ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND error code, 374
ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION error code, 341	ER_WARN_NO_SERVERID_SPECIFIED error code, 102
ER_WARN_DEPRECATED_UTF8MB3_COLLATION error code, 91	ER_WARN_NO_SPACE_VERSION_COMMENT error code, 121
ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION error code, 341	ER_WARN_NULL_TO_NOTNULL error code, 19
ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION error code, 340	ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS error code, 59
ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS error code, 105	ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE error code, 66
ER_WARN_DEPRECATED_WITH_NOTE error code, 121	ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO error code, 58
ER_WARN_DEPRECATED_YEAR_UNSIGNED error code, 104	ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR error code, 66
ER_WARN_DEPRECATED_ZEROFILL error code, 97	ER_WARN_OPTION_RESET_AND_IGNORED_DURING_INIT error code, 406
ER_WARN_ENGINE_TRANSACTION_ROLLBACK error code, 39	ER_WARN_OPTION_USAGE_COUNTER_READ_FAILED error code, 422
ER_WARN_FAILED_TO_SETUP_TLS error code, 404	ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT error code, 349
ER_WARN_FIELD_RESOLVED error code, 20	ER_WARN_PROPERTY_STRING_PARSE_FAILED error code, 346
ER_WARN_FUNC_INDEX_NOT_APPLICABLE error code, 101	ER_WARN_PURGE_LOG_IN_USE error code, 55
ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET error code, 378	ER_WARN_PURGE_LOG_IS_ACTIVE error code, 55
ER_WARN_GTID_THRESHOLD_BREACH error code, 372	ER_WARN_REDACTED_PRIVILEGES error code, 132
ER_WARN_HOSTNAME_WONT_WORK error code, 20	ER_WARN_REGEXP_USING_DEFAULT error code, 114
ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS error code, 349	ER_WARN_REMOVED_SQL_MODE error code, 341
ER_WARN_INDEX_NOT_APPLICABLE error code, 47	ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME error code, 377
	ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ALLOWED error code, 382

ER_WARN_RESERVED_SRID_RANGE error code, 86	ER_WINDOW_FRAME_ILLEGAL error code, 78
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE error code, 359	ER_WINDOW_INVALID_WINDOW_FUNC_START_ILLEGAL error code, 77
ER_WARN_SCHEDULED_TASK_RUN_FAILED error code, 401	ER_WINDOW_FUNCTION_IGNORES_FRAME error code, 78
ER_WARN_SERVER_MEMORY_INIT_FAIL error code, 425	ER_WINDOW_ILLEGAL_ORDER_BY error code, 78
ER_WARN_SET_OPERATIONS_BUFFER error code, 121	ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE error code, 78
ER_WARN_SF_UDF_NAME_COLLISION error code, 115	ER_WINDOW_INVALID_WINDOW_FUNC_USE error code, 78
ER_WARN_SP_STATEMENT_PARTIALLY_EXECUTED error code, 129	ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SP error code, 78
ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED error code, 112	ER_WINDOW_NO_CHILD_PARTITIONING error code, 77
ER_WARN_SRS_ID_ALREADY_EXISTS error code, 86	ER_WINDOW_NO_GROUP_ORDER_UNUSED error code, 78
ER_WARN_SRS_NOT_FOUND error code, 73	ER_WINDOW_NO_INHERIT_FRAME error code, 77
ER_WARN_SRS_NOT_FOUND_AXIS_ORDER error code, 76	ER_WINDOW_NO_REDEFINE_ORDER_BY error code, 77
ER_WARN_THREAD_POOL_DEDICATED_LISTENERS_ERROR error code, 428	ER_WINDOW_NO_SUCH_WINDOW error code, 77
ER_WARN_THREAD_POOL_QUERY_THREADS_INCOMPATIBLE error code, 428	ER_WINDOW_RANGE_BOUND_NOT_CONSTANT error code, 78
ER_WARN_THREAD_POOL_QUERY_THREADS_MISMATCH error code, 428	ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE error code, 78
ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR error code, 365	ER_WINDOW_RANGE_FRAME_ORDER_TYPE error code, 78
ER_WARN_TOO_FEW_RECORDS error code, 19	ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE error code, 78
ER_WARN_TOO_MANY_RECORDS error code, 19	ER_WINDOW_ROWS_INTERVAL_USE error code, 78
ER_WARN_TRG_ALREADY_EXISTS error code, 116	ER_WIN_LISTEN_BUT_HOW error code, 148
ER_WARN_TRIGGER_DOESNT_HAVE_CREATED error code, 58	ER_WIN_LOAD_LIBRARY_FAILED error code, 203
ER_WARN_UNKNOWN_KEYRING_AWS_REGION error code, 358	ER_WL9236_NOW_UNUSED error code, 79
ER_WARN_UNKNOWN_QB_NAME error code, 66	ER_WRITABLE_CONFIG_REMOVED error code, 147
ER_WARN_UNLOAD_THE_NOT_PERSISTED error code, 75	ER_WRITE_ROW_TO_PARTITION_FAILED error code, 196
ER_WARN_UNSUPPORTED_HINT error code, 73	ER_WRITE_SET_EXCEEDS_LIMIT error code, 71
ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME error code, 66	ER_WRONG_ARGUMENTS error code, 16
ER_WARN_USING_OTHER_HANDLER error code, 19	ER_WRONG_AUTO_KEY error code, 8
ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED error code, 107	ER_WRONG_COLUMN_NAME error code, 13
ER_WARN_VIEW_MERGE error code, 25	ER_WRONG_COMPRESSION_ALGORITHM_CLIENT error code, 101
ER_WARN_VIEW_WITHOUT_KEY error code, 25	ER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 101
ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG error code, 357	ER_WRONG_COUNT_FOR_KEY error code, 179
ER_WARN_WRONG_COMPRESSION_LEVEL_LOG error code, 357	ER_WRONG_COUNT_FOR_ORIGIN error code, 179
ER_WASTEFUL_NET_BUFFER_SIZE error code, 145	ER_WRONG_COUNT_OF_ELEMENTS error code, 179
ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS error code, 352	ER_WRONG_DATETIME_SPEC error code, 147
ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH error code, 77	ER_WRONG_DB_NAME error code, 9
ER_WINDOW_DUPLICATE_NAME error code, 78	ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR error code, 32
ER_WINDOW_EXPLAIN_JSON error code, 78	ER_WRONG_FIELD_SPEC error code, 7
ER_WINDOW_FRAME_END_ILLEGAL error code, 77	ER_WRONG_FIELD_TERMINATORS error code, 8
	ER_WRONG_FIELD_WITH_GROUP error code, 6
	ER_WRONG_FIELD_WITH_GROUP_V2 error code, 63
	ER_WRONG_FILE_NAME error code, 66
	ER_WRONG_FK_DEF error code, 18

ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN error code, 64
 ER_WRONG_GROUP_FIELD error code, 7
 ER_WRONG_JSON_TABLE_VALUE error code, 83
 ER_WRONG_KEY_COLUMN error code, 13
 ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX error code, 89
 ER_WRONG_LOCK_OF_SYSTEM_TABLE error code, 29
 ER_WRONG_MRG_TABLE error code, 14
 ER_WRONG_MVI_VALUE error code, 101
 ER_WRONG_NAME_FOR_CATALOG error code, 20
 ER_WRONG_NAME_FOR_INDEX error code, 20
 ER_WRONG_NATIVE_TABLE_STRUCTURE error code, 43
 ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT error code, 17
 ER_WRONG_OBJECT error code, 24
 ER_WRONG_OUTER_JOIN_UNUSED error code, 11
 ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT error code, 37
 ER_WRONG_PARAMCOUNT_TO_PROCEDURE error code, 10
 ER_WRONG_PARAMETERS_TO_NATIVE_FCT error code, 37
 ER_WRONG_PARAMETERS_TO_PROCEDURE error code, 10
 ER_WRONG_PARAMETERS_TO_STORED_FCT error code, 37
 ER_WRONG_PARTITION_NAME error code, 36
 ER_WRONG_PERFSCHEMA_USAGE error code, 43
 ER_WRONG_SIZE_NUMBER error code, 35
 ER_WRONG_SRID_FOR_COLUMN error code, 81
 ER_WRONG_STRING_LENGTH error code, 31
 ER_WRONG_SUB_KEY error code, 8
 ER_WRONG_SUM_SELECT error code, 7
 ER_WRONG_TABLESPACE_NAME error code, 65
 ER_WRONG_TABLE_NAME error code, 9
 ER_WRONG_TYPE_COLUMN_VALUE_ERROR error code, 41
 ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD error code, 202
 ER_WRONG_TYPE_FOR_VAR error code, 17
 ER_WRONG_USAGE error code, 17
 ER_WRONG_VALUE error code, 34
 ER_WRONG_VALUE_COUNT error code, 7
 ER_WRONG_VALUE_COUNT_ON_ROW error code, 12
 ER_WRONG_VALUE_FOR_TYPE error code, 28
 ER_WRONG_VALUE_FOR_VAR error code, 17
 ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE error code, 106
 ER_X509_CANT_CHMOD_KEY error code, 159
 ER_X509_CANT_CREATE_CERT error code, 159
 ER_X509_CANT_READ_CA_CERT error code, 159
 ER_X509_CANT_READ_CA_KEY error code, 159
 ER_X509_CANT_WRITE_CERT error code, 159
 ER_X509_CANT_WRITE_KEY error code, 159
 ER_X509_CIPHERS_MISMATCH error code, 159
 ER_X509_ISSUER_MISMATCH error code, 159
 ER_X509_NEEDS_RSA_PRIVKEY error code, 159
 ER_X509_SUBJECT_MISMATCH error code, 159
 ER_XAER_DUPID error code, 29
 ER_XAER_INVAL error code, 27
 ER_XAER_NOTA error code, 27
 ER_XAER_OUTSIDE error code, 27
 ER_XAER_RMERR error code, 27
 ER_XAER_RMFAIL error code, 27
 ER_XA_CANT_CREATE_MDL_BACKUP error code, 356
 ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER error code, 155
 ER_XA_RBDEADLOCK error code, 38
 ER_XA_RBROLLBACK error code, 27
 ER_XA_RBTIMEOUT error code, 38
 ER_XA_RECOVERY_DONE error code, 155
 ER_XA_RECOVER_EXPLANATION error code, 155
 ER_XA_RECOVER_FOUND_TRX_IN_SE error code, 155
 ER_XA_RECOVER_FOUND_XA_TRX error code, 155
 ER_XA_REPLICATION_FILTERS error code, 100
 ER_XA_RETRY error code, 71
 ER_XA_STARTING_RECOVERY error code, 155
 ER_XA_TEMP_TABLE error code, 115
 ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED error code, 220
 ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED error code, 218
 ER_XPLUGIN_CLIENT_KILL_MSG error code, 220
 ER_XPLUGIN_COMPRESSION_ERROR error code, 357
 ER_XPLUGIN_DETECTED_HANGING_CLIENTS error code, 218
 ER_XPLUGIN_EMPTY_ADMIN_CMD error code, 221
 ER_XPLUGIN_ERROR_MSG error code, 216
 ER_XPLUGIN_ERROR_READING_SOCKET error code, 220
 ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP error code, 219
 ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER error code, 219
 ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE error code, 220
 ER_XPLUGIN_FAILED_AT_SSL_CONF error code, 219
 ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT error code, 218
 ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS error code, 365
 ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION error code, 221
 ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONNECTION error code, 219
 ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD error code, 221

ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT error code, 221	ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED error code, 219
ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO error code, 221	ER_XPLUGIN_STARTUP_FAILED error code, 215
ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX error code, 221	ER_XPLUGIN_TASK_SCHEDULING_FAILED error code, 219
ER_XPLUGIN_FAILED_TO_GET_SYS_VAR error code, 221	ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION error code, 220
ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION error code, 219	ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT error code, 219
ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION error code, 221	ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD error code, 219
ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES error code, 219	ER_XPLUGIN_UNINITIALIZED_MESSAGE error code, 220
ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG error code, 221	ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX error code, 215
ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT error code, 218	ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER error code, 215
ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS error code, 220	ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION error code, 215
ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG error code, 221	ER_XPLUING_NET_STARTUP_FAILED error code, 219
ER_XPLUGIN_FAILED_TO_STOP_SERVICES error code, 332	ER_YES error code, 3
ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT error code, 221	ER_ZLIB_Z_BUF_ERROR error code, 19
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX error code, 340	ER_ZLIB_Z_DATA_ERROR error code, 19
ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF error code, 221	ER_ZLIB_Z_MEM_ERROR error code, 19
ER_XPLUGIN_FAILED_TO_USE_SSL_CONF error code, 215	
ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS error code, 365	W
ER_XPLUGIN_FORCE_STOP_CLIENT error code, 218	WARN_AES_KEY_SIZE error code, 72
ER_XPLUGIN_IPv6_AVAILABLE error code, 220	WARN_COND_ITEM_TRUNCATED error code, 40
ER_XPLUGIN_LISTENER_SETUP_FAILED error code, 219	WARN_DATA_TRUNCATED error code, 19
ER_XPLUGIN_LISTENER_STATUS_MSG error code, 220	WARN_NAMED_PIPE_ACCESS_EVERYONE error code, 57
ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR error code, 220	WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED error code, 40
ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED error code, 218	WARN_NO_CONNECTION_METADATA error code, 39
ER_XPLUGIN_MESSAGE_TOO_LONG error code, 220	WARN_ON_BLOCKHOLE_IN_RBR error code, 56
ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY error code, 220	WARN_OPTION_BELOW_LIMIT error code, 44
ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION error code, 220	WARN_OPTION_IGNORED error code, 39
ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN error code, 215	WARN_PLUGIN_BUSY error code, 39
ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTION error code, 219	WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB error code, 95
ER_XPLUGIN_RETRYING_BIND_ON_PORT error code, 220	WARN_UNSUPPORTED_ACL_TABLES_READ error code, 108
	WARN_USELESS_SPATIAL_INDEX error code, 83